
Amazon Simple Queue Service

API Reference

API Version 2012-11-05



Amazon Simple Queue Service: API Reference

Table of Contents

Welcome	1
Actions	2
AddPermission	3
Request Parameters	3
Errors	4
Examples	4
See Also	5
ChangeMessageVisibility	6
Request Parameters	6
Errors	7
Examples	7
See Also	8
ChangeMessageVisibilityBatch	9
Request Parameters	9
Response Elements	9
Errors	9
Examples	10
See Also	11
CreateQueue	12
Request Parameters	12
Response Elements	15
Errors	15
Examples	16
See Also	17
DeleteMessage	18
Request Parameters	18
Errors	18
Examples	19
See Also	19
DeleteMessageBatch	20
Request Parameters	20
Response Elements	20
Errors	20
Examples	21
See Also	22
DeleteQueue	23
Request Parameters	23
Errors	23
Examples	23
See Also	24
GetQueueAttributes	25
Request Parameters	25
Response Elements	27
Errors	27
Examples	28
See Also	29
GetQueueUrl	31
Request Parameters	31
Response Elements	31
Errors	31
Examples	32
See Also	32
ListDeadLetterSourceQueues	33
Request Parameters	33

Response Elements	33
Errors	34
Examples	34
See Also	34
ListQueues	36
Request Parameters	36
Response Elements	36
Errors	37
Examples	37
See Also	37
ListQueueTags	39
Request Parameters	39
Response Elements	39
Errors	39
Examples	39
See Also	40
PurgeQueue	41
Request Parameters	41
Errors	41
Examples	41
See Also	42
ReceiveMessage	43
Request Parameters	43
Response Elements	46
Errors	46
Examples	46
See Also	47
RemovePermission	49
Request Parameters	49
Errors	49
Examples	49
See Also	50
SendMessage	51
Request Parameters	51
Response Elements	53
Errors	54
Examples	54
See Also	55
SendMessageBatch	56
Request Parameters	56
Response Elements	56
Errors	57
Examples	57
See Also	59
SetQueueAttributes	60
Request Parameters	60
Errors	62
Examples	63
See Also	65
TagQueue	66
Request Parameters	66
Errors	66
Examples	66
See Also	67
UntagQueue	68
Request Parameters	68
Errors	68

Examples	68
See Also	69
Data Types	70
BatchResultErrorEntry	71
Contents	71
See Also	71
ChangeMessageVisibilityBatchRequestEntry	72
Contents	72
See Also	72
ChangeMessageVisibilityBatchResultEntry	73
Contents	73
See Also	73
DeleteMessageBatchRequestEntry	74
Contents	74
See Also	74
DeleteMessageBatchResultEntry	75
Contents	75
See Also	75
Message	76
Contents	76
See Also	77
MessageAttributeValue	78
Contents	78
See Also	78
MessageSystemAttributeValue	80
Contents	80
See Also	80
SendMessageBatchRequestEntry	82
Contents	82
See Also	84
SendMessageBatchResultEntry	85
Contents	85
See Also	86
Common Parameters	87
Common Errors	89

Welcome

Welcome to the *Amazon SQS API Reference*.

Amazon SQS is a reliable, highly-scalable hosted queue for storing messages as they travel between applications or microservices. Amazon SQS moves data between distributed application components and helps you decouple these components.

For information on the permissions you need to use this API, see [Identity and access management](#) in the *Amazon SQS Developer Guide*.

You can use [Amazon SDKs](#) to access Amazon SQS using your favorite programming language. The SDKs perform tasks such as the following automatically:

- Cryptographically sign your service requests
- Retry requests
- Handle error responses

Additional information

- [Amazon SQS Product Page](#)
- *Amazon SQS Developer Guide*
 - [Making API Requests](#)
 - [Amazon SQS Message Attributes](#)
 - [Amazon SQS Dead-Letter Queues](#)
- [Amazon SQS in the *Amazon Command Line Interface*](#)
- *Amazon Web Services General Reference*
 - [Regions and Endpoints](#)

This document was last published on October 4, 2022.

Actions

The following actions are supported:

- [AddPermission](#) (p. 3)
- [ChangeMessageVisibility](#) (p. 6)
- [ChangeMessageVisibilityBatch](#) (p. 9)
- [CreateQueue](#) (p. 12)
- [DeleteMessage](#) (p. 18)
- [DeleteMessageBatch](#) (p. 20)
- [DeleteQueue](#) (p. 23)
- [GetQueueAttributes](#) (p. 25)
- [GetQueueUrl](#) (p. 31)
- [ListDeadLetterSourceQueues](#) (p. 33)
- [ListQueues](#) (p. 36)
- [ListQueueTags](#) (p. 39)
- [PurgeQueue](#) (p. 41)
- [ReceiveMessage](#) (p. 43)
- [RemovePermission](#) (p. 49)
- [SendMessage](#) (p. 51)
- [SendMessageBatch](#) (p. 56)
- [SetQueueAttributes](#) (p. 60)
- [TagQueue](#) (p. 66)
- [UntagQueue](#) (p. 68)

AddPermission

Adds a permission to a queue for a specific [principal](#). This allows sharing access to the queue.

When you create a queue, you have full control access rights for the queue. Only you, the owner of the queue, can grant or deny permissions to the queue. For more information about these permissions, see [Allow Developers to Write Messages to a Shared Queue](#) in the *Amazon SQS Developer Guide*.

Note

- `AddPermission` generates a policy for you. You can use [SetQueueAttributes \(p. 60\)](#) to upload your policy. For more information, see [Using Custom Policies with the Amazon SQS Access Policy Language](#) in the *Amazon SQS Developer Guide*.
- An Amazon SQS policy can have a maximum of seven actions per statement.
- To remove the ability to change queue permissions, you must deny permission to the `AddPermission`, `RemovePermission`, and `SetQueueAttributes` actions in your IAM policy.

Some actions take lists of parameters. These lists are specified using the `param.n` notation. Values of `n` are integers starting from 1. For example, a parameter list with two elements looks like this:

```
&AttributeName.1=first
```

```
&AttributeName.2=second
```

Note

Cross-account permissions don't apply to this action. For more information, see [Grant cross-account permissions to a role and a user name](#) in the *Amazon SQS Developer Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 87\)](#).

ActionName.N

The action the client wants to allow for the specified principal. Valid values: the name of any action or `*`.

For more information about these actions, see [Overview of Managing Access Permissions to Your Amazon Simple Queue Service Resource](#) in the *Amazon SQS Developer Guide*.

Specifying `SendMessage`, `DeleteMessage`, or `ChangeMessageVisibility` for `ActionName.n` also grants permissions for the corresponding batch versions of those actions: `SendMessageBatch`, `DeleteMessageBatch`, and `ChangeMessageVisibilityBatch`.

Type: Array of strings

Required: Yes

AWSAccountId.N

The Amazon Web Services account numbers of the [principals](#) who are to receive permission. For information about locating the Amazon Web Services account identification, see [Your Amazon Identifiers](#) in the *Amazon SQS Developer Guide*.

Type: Array of strings

Required: Yes

Label

The unique identification of the permission you're setting (for example, `AliceSendMessage`). Maximum 80 characters. Allowed characters include alphanumeric characters, hyphens (-), and underscores (_).

Type: String

Required: Yes

QueueUrl

The URL of the Amazon SQS queue to which permissions are added.

Queue URLs and names are case-sensitive.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 89\)](#).

OverLimit

The specified action violates a limit. For example, `ReceiveMessage` returns this error if the maximum number of in flight messages is reached and `AddPermission` returns this error if the maximum number of permissions for the queue is reached.

HTTP Status Code: 403

Examples

Example

The following example query request grants a [SendMessage \(p. 51\)](#) permission to the principal whose Amazon Web Services account number is 123456789012 and a [ReceiveMessage \(p. 43\)](#) permission to the principal whose Amazon Web Services account number is 111111111111. The structure of `AUTHPARAMS` depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/  
?Action=AddPermission  
&Label=MyLabel  
&AWSAccountId.1=123456789012  
&ActionName.1=SendMessage  
&AWSAccountId.2=111111111111  
&ActionName.2=ReceiveMessage  
&Expires=2020-04-18T22%3A52%3A43PST  
&Version=2012-11-05  
&AUTHPARAMS
```

Sample Response

```
<AddPermissionResponse>
  <ResponseMetadata>
    <RequestId>9a285199-c8d6-47c2-bdb2-314cb47d599d</RequestId>
  </ResponseMetadata>
</AddPermissionResponse>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ChangeMessageVisibility

Changes the visibility timeout of a specified message in a queue to a new value. The default visibility timeout for a message is 30 seconds. The minimum is 0 seconds. The maximum is 12 hours. For more information, see [Visibility Timeout](#) in the *Amazon SQS Developer Guide*.

For example, you have a message with a visibility timeout of 5 minutes. After 3 minutes, you call `ChangeMessageVisibility` with a timeout of 10 minutes. You can continue to call `ChangeMessageVisibility` to extend the visibility timeout to the maximum allowed time. If you try to extend the visibility timeout beyond the maximum, your request is rejected.

An Amazon SQS message has three basic states:

1. Sent to a queue by a producer.
2. Received from the queue by a consumer.
3. Deleted from the queue.

A message is considered to be *stored* after it is sent to a queue by a producer, but not yet received from the queue by a consumer (that is, between states 1 and 2). There is no limit to the number of stored messages. A message is considered to be *in flight* after it is received from a queue by a consumer, but not yet deleted from the queue (that is, between states 2 and 3). There is a limit to the number of in flight messages.

Limits that apply to in flight messages are unrelated to the *unlimited* number of stored messages.

For most standard queues (depending on queue traffic and message backlog), there can be a maximum of approximately 120,000 in flight messages (received from a queue by a consumer, but not yet deleted from the queue). If you reach this limit, Amazon SQS returns the `OverLimit` error message. To avoid reaching the limit, you should delete messages from the queue after they're processed. You can also increase the number of queues you use to process your messages. To request a limit increase, [file a support request](#).

For FIFO queues, there can be a maximum of 20,000 in flight messages (received from a queue by a consumer, but not yet deleted from the queue). If you reach this limit, Amazon SQS returns no error messages.

Important

If you attempt to set the `VisibilityTimeout` to a value greater than the maximum time left, Amazon SQS returns an error. Amazon SQS doesn't automatically recalculate and increase the timeout to the maximum remaining time.

Unlike with a queue, when you change the visibility timeout for a specific message the timeout value is applied immediately but isn't saved in memory for that message. If you don't delete a message after it is received, the visibility timeout for the message reverts to the original timeout value (not to the value you set using the `ChangeMessageVisibility` action) the next time the message is received.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 87).

QueueUrl

The URL of the Amazon SQS queue whose message's visibility is changed.

Queue URLs and names are case-sensitive.

Type: String

Required: Yes

ReceiptHandle

The receipt handle associated with the message whose visibility timeout is changed. This parameter is returned by the [ReceiveMessage](#) (p. 43) action.

Type: String

Required: Yes

VisibilityTimeout

The new value for the message's visibility timeout (in seconds). Values range: 0 to 43200. Maximum: 12 hours.

Type: Integer

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 89).

AWS.SimpleQueueService.MessageNotInflight

The specified message isn't in flight.

HTTP Status Code: 400

ReceiptHandleInvalid

The specified receipt handle isn't valid.

HTTP Status Code: 400

Examples

Example

The following example query request changes the visibility timeout for a message to 60 seconds. The structure of `AUTHPARAMS` depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/  
?Action=ChangeMessageVisibility  
&VisibilityTimeout=60  
&ReceiptHandle=MbZj6wDWli%2BJvwwJaBV%2B3dcjk2YW2vA3%2BSTFFljT  
M8tJJg6HRG6PYSasuWXPJB%2BCwLj1FjgXUv1uSj1gUPAWV66FU/WeR4mq2OKpEGY  
WbnLmpRCJVAYeMjeU5ZBdtcQ%2BQEauMZc8ZRv37sIW2iJKq3M9MFx1YvV11A2x/K  
SbkJ0=  
&Expires=2020-04-18T22%3A52%3A43PST  
&Version=2012-11-05  
&AUTHPARAMS
```

Sample Response

```
<ChangeMessageVisibilityResponse>
  <ResponseMetadata>
    <RequestId>6a7a282a-d013-4a59-aba9-335b0fa48bed</RequestId>
  </ResponseMetadata>
</ChangeMessageVisibilityResponse>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ChangeMessageVisibilityBatch

Changes the visibility timeout of multiple messages. This is a batch version of [ChangeMessageVisibility \(p. 6\)](#). The result of the action on each message is reported individually in the response. You can send up to 10 [ChangeMessageVisibility \(p. 6\)](#) requests with each `ChangeMessageVisibilityBatch` action.

Important

Because the batch request can result in a combination of successful and unsuccessful actions, you should check for batch errors even when the call returns an HTTP status code of 200.

Some actions take lists of parameters. These lists are specified using the `param.n` notation. Values of `n` are integers starting from 1. For example, a parameter list with two elements looks like this:

```
&AttributeName.1=first
```

```
&AttributeName.2=second
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 87\)](#).

ChangeMessageVisibilityBatchRequestEntry.N

A list of receipt handles of the messages for which the visibility timeout must be changed.

Type: Array of [ChangeMessageVisibilityBatchRequestEntry \(p. 72\)](#) objects

Required: Yes

QueueUrl

The URL of the Amazon SQS queue whose messages' visibility is changed.

Queue URLs and names are case-sensitive.

Type: String

Required: Yes

Response Elements

The following elements are returned by the service.

BatchResultErrorEntry.N

A list of [BatchResultErrorEntry \(p. 71\)](#) items.

Type: Array of [BatchResultErrorEntry \(p. 71\)](#) objects

ChangeMessageVisibilityBatchResultEntry.N

A list of [ChangeMessageVisibilityBatchResultEntry \(p. 73\)](#) items.

Type: Array of [ChangeMessageVisibilityBatchResultEntry \(p. 73\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 89\)](#).

AWS.SimpleQueueService.BatchEntryIdsNotDistinct

Two or more batch entries in the request have the same Id.

HTTP Status Code: 400

AWS.SimpleQueueService.EmptyBatchRequest

The batch request doesn't contain any entries.

HTTP Status Code: 400

AWS.SimpleQueueService.InvalidBatchEntryId

The Id of a batch entry in a batch request doesn't abide by the specification.

HTTP Status Code: 400

AWS.SimpleQueueService.TooManyEntriesInBatchRequest

The batch request contains more entries than permissible.

HTTP Status Code: 400

Examples

Example

`ChangeMessageVisibilityBatch` request changes the visibility timeout settings for two messages. You must URL-encode the entire URL. However, in this example only the message body is URL-encoded to make the example easier to read.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/
&Action=ChangeMessageVisibilityBatch
&ChangeMessageVisibilityBatchRequestEntry.1.Id=change_visibility_msg_2
&ChangeMessageVisibilityBatchRequestEntry.1.ReceiptHandle=gfk0T0R0waama4f
VFffkjKz mhMCymjQvfTFk2LxT33G4ms5subrE0deLKWSScPU1oD3J9zgeS4PQQ3U30qOumIE6
AdAv3w%2F%2Fa1IXW6AqaWhGsEPaLm3Vf6IiWqdm8u5imB%2BNTwj3tQRzOWdTOePjOjPcTpR
xBtXix%2BEvwJOZUma9wabv%2BSw6ZHjwmNcVDx8dZXJhVp16Bksiox%2FGrUvrVTCJRTWTLc
59oHLLF8sEkKzRmGNzTDGTiV%2BYjhFQj60FD3rVaXmzTsonXrRkKJ72uIHVMGVQIAGgBX6HGv
9LDmYhPXw4hy%2FNgiG%3D%3D
&ChangeMessageVisibilityBatchRequestEntry.1.VisibilityTimeout=45
&ChangeMessageVisibilityBatchRequestEntry.2.Id=change_visibility_msg_3
&ChangeMessageVisibilityBatchRequestEntry.2.ReceiptHandle=gfk0T0R0waama4f
VFffkjKz mhMCymjQvfTFk2LxT33FUGBz3%2BnougdeLKWSScPU1%2FXgx%2BxcNnjqQ3U30q
OumIE6AdAv3w%2F%2Fa1IXW6AqaWhGsEPaLm3Vf6IiWqdm8u5imB%2BNTwj3tQRzOWdTOePjO
sogjZM%2F7kzn4Ew27XLU9I%2FYaWYmKvDbq%2Fk3HKVB9HfB43kE49atP2aWrzNL4yunG4lQ
4cfRRtfJdcGGQNHQ2%2Byd0U5f5qR1dZr1iDo5xk946eQat83AxTRP%2BY4QioV7FAeSLH9su
9xpX6HGv9LDmYhPXw4hy%2FNgiG%3D%3D
&ChangeMessageVisibilityBatchRequestEntry.2.VisibilityTimeout=45
&Expires=2020-10-18T22%3A52%3A43PST
&Version=2012-11-05
```

Sample Response

```
<ChangeMessageVisibilityBatchResponse>
  <ChangeMessageVisibilityBatchResult>
    <ChangeMessageVisibilityBatchResultEntry>
      <Id>change_visibility_msg_2</Id>
```

```
</ChangeMessageVisibilityBatchResultEntry>
<ChangeMessageVisibilityBatchResultEntry>
  <Id>change_visibility_msg_3</Id>
</ChangeMessageVisibilityBatchResultEntry>
</ChangeMessageVisibilityBatchResult>
<ResponseMetadata>
  <RequestId>ca9668f7-ab1b-4f7a-8859-f15747ab17a7</RequestId>
</ResponseMetadata>
</ChangeMessageVisibilityBatchResponse>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateQueue

Creates a new standard or FIFO queue. You can pass one or more attributes in the request. Keep the following in mind:

- If you don't specify the `FifoQueue` attribute, Amazon SQS creates a standard queue.

Note

You can't change the queue type after you create it and you can't convert an existing standard queue into a FIFO queue. You must either create a new FIFO queue for your application or delete your existing standard queue and recreate it as a FIFO queue. For more information, see [Moving From a Standard Queue to a FIFO Queue](#) in the *Amazon SQS Developer Guide*.

- If you don't provide a value for an attribute, the queue is created with the default value for the attribute.
- If you delete a queue, you must wait at least 60 seconds before creating a queue with the same name.

To successfully create a new queue, you must provide a queue name that adheres to the [limits related to queues](#) and is unique within the scope of your queues.

Note

After you create a queue, you must wait at least one second after the queue is created to be able to use the queue.

To get the queue URL, use the [GetQueueUrl \(p. 31\)](#) action. [GetQueueUrl \(p. 31\)](#) requires only the `QueueName` parameter. be aware of existing queue names:

- If you provide the name of an existing queue along with the exact names and values of all the queue's attributes, `CreateQueue` returns the queue URL for the existing queue.
- If the queue name, attribute names, or attribute values don't match an existing queue, `CreateQueue` returns an error.

Some actions take lists of parameters. These lists are specified using the `param.n` notation. Values of `n` are integers starting from 1. For example, a parameter list with two elements looks like this:

```
&AttributeName.1=first
```

```
&AttributeName.2=second
```

Note

Cross-account permissions don't apply to this action. For more information, see [Grant cross-account permissions to a role and a user name](#) in the *Amazon SQS Developer Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 87\)](#).

Attribute , Attribute.N.Name (key), Attribute.N.Value (value)

A map of attributes with their corresponding values.

The following lists the names, descriptions, and values of the special request parameters that the `CreateQueue` action uses:

- `DelaySeconds` – The length of time, in seconds, for which the delivery of all messages in the queue is delayed. Valid values: An integer from 0 to 900 seconds (15 minutes). Default: 0.

- `MaximumMessageSize` – The limit of how many bytes a message can contain before Amazon SQS rejects it. Valid values: An integer from 1,024 bytes (1 KiB) to 262,144 bytes (256 KiB). Default: 262,144 (256 KiB).
- `MessageRetentionPeriod` – The length of time, in seconds, for which Amazon SQS retains a message. Valid values: An integer from 60 seconds (1 minute) to 1,209,600 seconds (14 days). Default: 345,600 (4 days).
- `Policy` – The queue's policy. A valid Amazon policy. For more information about policy structure, see [Overview of Amazon IAM Policies](#) in the *Amazon IAM User Guide*.
- `ReceiveMessageWaitTimeSeconds` – The length of time, in seconds, for which a [ReceiveMessage](#) (p. 43) action waits for a message to arrive. Valid values: An integer from 0 to 20 (seconds). Default: 0.
- `VisibilityTimeout` – The visibility timeout for the queue, in seconds. Valid values: An integer from 0 to 43,200 (12 hours). Default: 30. For more information about the visibility timeout, see [Visibility Timeout](#) in the *Amazon SQS Developer Guide*.

The following attributes apply only to [dead-letter queues](#):

- `RedrivePolicy` – The string that includes the parameters for the dead-letter queue functionality of the source queue as a JSON object. The parameters are as follows:
 - `deadLetterTargetArn` – The Amazon Resource Name (ARN) of the dead-letter queue to which Amazon SQS moves messages after the value of `maxReceiveCount` is exceeded.
 - `maxReceiveCount` – The number of times a message is delivered to the source queue before being moved to the dead-letter queue. Default: 10. When the `ReceiveCount` for a message exceeds the `maxReceiveCount` for a queue, Amazon SQS moves the message to the dead-letter-queue.
- `RedriveAllowPolicy` – The string that includes the parameters for the permissions for the dead-letter queue redrive permission and which source queues can specify dead-letter queues as a JSON object. The parameters are as follows:
 - `redrivePermission` – The permission type that defines which source queues can specify the current queue as the dead-letter queue. Valid values are:
 - `allowAll` – (Default) Any source queues in this Amazon account in the same Region can specify this queue as the dead-letter queue.
 - `denyAll` – No source queues can specify this queue as the dead-letter queue.
 - `byQueue` – Only queues specified by the `sourceQueueArns` parameter can specify this queue as the dead-letter queue.
 - `sourceQueueArns` – The Amazon Resource Names (ARN)s of the source queues that can specify this queue as the dead-letter queue and redrive messages. You can specify this parameter only when the `redrivePermission` parameter is set to `byQueue`. You can specify up to 10 source queue ARNs. To allow more than 10 source queues to specify dead-letter queues, set the `redrivePermission` parameter to `allowAll`.

Note

The dead-letter queue of a FIFO queue must also be a FIFO queue. Similarly, the dead-letter queue of a standard queue must also be a standard queue.

The following attributes apply only to [server-side-encryption](#):

- `KmsMasterKeyId` – The ID of an Amazon managed customer master key (CMK) for Amazon SQS or a custom CMK. For more information, see [Key Terms](#). While the alias of the Amazon managed CMK for Amazon SQS is always `alias/aws/sqs`, the alias of a custom CMK can, for example, be `alias/MyAlias`. For more examples, see [KeyId](#) in the *Amazon Key Management Service API Reference*.
- `KmsDataKeyReusePeriodSeconds` – The length of time, in seconds, for which Amazon SQS can reuse a [data key](#) to encrypt or decrypt messages before calling Amazon KMS again. An integer representing seconds, between 60 seconds (1 minute) and 86,400 seconds (24 hours). Default: 300 (5 minutes). A shorter time period provides better security but results in more calls to KMS

which might incur charges after Free Tier. For more information, see [How Does the Data Key Reuse Period Work?](#)

- `SqsManagedSseEnabled` – Enables server-side queue encryption using SQS owned encryption keys. Only one server-side encryption option is supported per queue (e.g. [SSE-KMS](#) or [SSE-SQS](#)).

The following attributes apply only to [FIFO \(first-in-first-out\) queues](#):

- `FifoQueue` – Designates a queue as FIFO. Valid values are `true` and `false`. If you don't specify the `FifoQueue` attribute, Amazon SQS creates a standard queue. You can provide this attribute only during queue creation. You can't change it for an existing queue. When you set this attribute, you must also provide the `MessageGroupId` for your messages explicitly.

For more information, see [FIFO queue logic](#) in the *Amazon SQS Developer Guide*.

- `ContentBasedDeduplication` – Enables content-based deduplication. Valid values are `true` and `false`. For more information, see [Exactly-once processing](#) in the *Amazon SQS Developer Guide*. Note the following:
 - Every message must have a unique `MessageDeduplicationId`.
 - You may provide a `MessageDeduplicationId` explicitly.
 - If you aren't able to provide a `MessageDeduplicationId` and you enable `ContentBasedDeduplication` for your queue, Amazon SQS uses a SHA-256 hash to generate the `MessageDeduplicationId` using the body of the message (but not the attributes of the message).
 - If you don't provide a `MessageDeduplicationId` and the queue doesn't have `ContentBasedDeduplication` set, the action fails with an error.
 - If the queue has `ContentBasedDeduplication` set, your `MessageDeduplicationId` overrides the generated one.
 - When `ContentBasedDeduplication` is in effect, messages with identical content sent within the deduplication interval are treated as duplicates and only one copy of the message is delivered.
 - If you send one message with `ContentBasedDeduplication` enabled and then another message with a `MessageDeduplicationId` that is the same as the one generated for the first `MessageDeduplicationId`, the two messages are treated as duplicates and only one copy of the message is delivered.

The following attributes apply only to [high throughput for FIFO queues](#):

- `DeduplicationScope` – Specifies whether message deduplication occurs at the message group or queue level. Valid values are `messageGroup` and `queue`.
- `FifoThroughputLimit` – Specifies whether the FIFO queue throughput quota applies to the entire queue or per message group. Valid values are `perQueue` and `perMessageGroupId`. The `perMessageGroupId` value is allowed only when the value for `DeduplicationScope` is `messageGroup`.

To enable high throughput for FIFO queues, do the following:

- Set `DeduplicationScope` to `messageGroup`.
- Set `FifoThroughputLimit` to `perMessageGroupId`.

If you set these attributes to anything other than the values shown for enabling high throughput, normal throughput is in effect and deduplication occurs as specified.

For information on throughput quotas, see [Quotas related to messages](#) in the *Amazon SQS Developer Guide*.

Type: String to string map

Valid Keys: All | Policy | VisibilityTimeout | MaximumMessageSize
| MessageRetentionPeriod | ApproximateNumberOfMessages |

ApproximateNumberOfMessagesNotVisible | CreatedTimestamp |
LastModifiedTimestamp | QueueArn | ApproximateNumberOfMessagesDelayed |
DelaySeconds | ReceiveMessageWaitTimeSeconds | RedrivePolicy | FifoQueue |
ContentBasedDeduplication | KmsMasterKeyId | KmsDataKeyReusePeriodSeconds
| DeduplicationScope | FifoThroughputLimit | RedriveAllowPolicy |
SqsManagedSseEnabled

Required: No

QueueName

The name of the new queue. The following limits apply to this name:

- A queue name can have up to 80 characters.
- Valid values: alphanumeric characters, hyphens (-), and underscores (_).
- A FIFO queue name must end with the `.fifo` suffix.

Queue URLs and names are case-sensitive.

Type: String

Required: Yes

Tag, Tag.N.Key (key), Tag.N.Value (value)

Add cost allocation tags to the specified Amazon SQS queue. For an overview, see [Tagging Your Amazon SQS Queues](#) in the *Amazon SQS Developer Guide*.

When you use queue tags, keep the following guidelines in mind:

- Adding more than 50 tags to a queue isn't recommended.
- Tags don't have any semantic meaning. Amazon SQS interprets tags as character strings.
- Tags are case-sensitive.
- A new tag with a key identical to that of an existing tag overwrites the existing tag.

For a full list of tag restrictions, see [Quotas related to queues](#) in the *Amazon SQS Developer Guide*.

Note

To be able to tag a queue on creation, you must have the `sqs:CreateQueue` and `sqs:TagQueue` permissions.

Cross-account permissions don't apply to this action. For more information, see [Grant cross-account permissions to a role and a user name](#) in the *Amazon SQS Developer Guide*.

Type: String to string map

Required: No

Response Elements

The following element is returned by the service.

QueueUrl

The URL of the created Amazon SQS queue.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 89\)](#).

AWS.SimpleQueueService.QueueDeletedRecently

You must wait 60 seconds after deleting a queue before you can create another queue with the same name.

HTTP Status Code: 400

QueueAlreadyExists

A queue with this name already exists. Amazon SQS returns this error only if the request includes attributes whose values differ from those of the existing queue.

HTTP Status Code: 400

Examples

Example

The following example query request creates a new queue named `MyQueue`. The structure of `AUTHPARAMS` depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/  
?Action=CreateQueue  
&QueueName=MyQueue  
&Tag.Key=QueueType  
&Tag.Value=Production  
&Attribute.1.Name=VisibilityTimeout  
&Attribute.1.Value=40  
&Expires=2020-10-18T22%3A52%3A43PST  
&Version=2012-11-05  
&AUTHPARAMS
```

Sample Response

```
<CreateQueueResponse>  
  <CreateQueueResult>  
    <QueueUrl>https://queue.amazonaws.com/123456789012/MyQueue</QueueUrl>  
  </CreateQueueResult>  
  <ResponseMetadata>  
    <RequestId>7a62c49f-347e-4fc4-9331-6e8e7a96aa73</RequestId>  
  </ResponseMetadata>  
</CreateQueueResponse>
```

Example

The following example creates a delay queue which hides each message from consumers for the first 45 seconds that the message is in the queue by calling the `CreateQueue` action with the `DelaySeconds` attribute set to 45 seconds.

Note

Queue URLs and names are case-sensitive.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/
```

```
?Action=CreateQueue
&QueueName=MyQueue
&Attribute.1.Name=DelaySeconds
&Attribute.1.Value=45
&Expires=2020-12-20T22%3A52%3A43PST
&Version=2012-11-05
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteMessage

Deletes the specified message from the specified queue. To select the message to delete, use the `ReceiptHandle` of the message (*not* the `MessageId` which you receive when you send the message). Amazon SQS can delete a message from a queue even if a visibility timeout setting causes the message to be locked by another consumer. Amazon SQS automatically deletes messages left in a queue longer than the retention period configured for the queue.

Note

The `ReceiptHandle` is associated with a *specific instance* of receiving a message. If you receive a message more than once, the `ReceiptHandle` is different each time you receive a message. When you use the `DeleteMessage` action, you must provide the most recently received `ReceiptHandle` for the message (otherwise, the request succeeds, but the message might not be deleted).

For standard queues, it is possible to receive a message even after you delete it. This might happen on rare occasions if one of the servers which stores a copy of the message is unavailable when you send the request to delete the message. The copy remains on the server and might be returned to you during a subsequent receive request. You should ensure that your application is idempotent, so that receiving a message more than once does not cause issues.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 87\)](#).

QueueUrl

The URL of the Amazon SQS queue from which messages are deleted.

Queue URLs and names are case-sensitive.

Type: String

Required: Yes

ReceiptHandle

The receipt handle associated with the message to delete.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 89\)](#).

InvalidIdFormat

The specified receipt handle isn't valid for the current version.

HTTP Status Code: 400

ReceiptHandleInvalid

The specified receipt handle isn't valid.

HTTP Status Code: 400

Examples

Example

The following example query request deletes a message from the queue named `MyQueue`. The structure of `AUTHPARAMS` depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/  
?Action=DeleteMessage  
&ReceiptHandle=MbZj6wDwli%2BJvwwJaBV%2B3dcjk2YW2vA3%2BSTFFljT  
M8tJJg6HRG6PYSasuWXPJB%2BCwLj1FjgXUv1uSj1gUPAWV66FU/WeR4mq2OKpEGY  
WbnLmpRCJVAYeMjeU5ZBdtcQ%2BQEauMZc8ZRv37sIW2iJKq3M9MFx1YvV11A2x/K  
SbkJ0=  
&Expires=2020-04-18T22%3A52%3A43PST  
&Version=2012-11-05  
&AUTHPARAMS
```

Sample Response

```
<DeleteMessageResponse>  
  <ResponseMetadata>  
    <RequestId>b5293cb5-d306-4a17-9048-b263635abe42</RequestId>  
  </ResponseMetadata>  
</DeleteMessageResponse>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteMessageBatch

Deletes up to ten messages from the specified queue. This is a batch version of [DeleteMessage \(p. 18\)](#). The result of the action on each message is reported individually in the response.

Important

Because the batch request can result in a combination of successful and unsuccessful actions, you should check for batch errors even when the call returns an HTTP status code of 200.

Some actions take lists of parameters. These lists are specified using the `param.n` notation. Values of `n` are integers starting from 1. For example, a parameter list with two elements looks like this:

```
&AttributeName.1=first
```

```
&AttributeName.2=second
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 87\)](#).

DeleteMessageBatchRequestEntry.N

A list of receipt handles for the messages to be deleted.

Type: Array of [DeleteMessageBatchRequestEntry \(p. 74\)](#) objects

Required: Yes

QueueUrl

The URL of the Amazon SQS queue from which messages are deleted.

Queue URLs and names are case-sensitive.

Type: String

Required: Yes

Response Elements

The following elements are returned by the service.

BatchResultErrorEntry.N

A list of [BatchResultErrorEntry \(p. 71\)](#) items.

Type: Array of [BatchResultErrorEntry \(p. 71\)](#) objects

DeleteMessageBatchResultEntry.N

A list of [DeleteMessageBatchResultEntry \(p. 75\)](#) items.

Type: Array of [DeleteMessageBatchResultEntry \(p. 75\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 89\)](#).

AWS.SimpleQueueService.BatchEntryIdsNotDistinct

Two or more batch entries in the request have the same Id.

HTTP Status Code: 400

AWS.SimpleQueueService.EmptyBatchRequest

The batch request doesn't contain any entries.

HTTP Status Code: 400

AWS.SimpleQueueService.InvalidBatchEntryId

The Id of a batch entry in a batch request doesn't abide by the specification.

HTTP Status Code: 400

AWS.SimpleQueueService.TooManyEntriesInBatchRequest

The batch request contains more entries than permissible.

HTTP Status Code: 400

Examples

Example

In the following example, a `DeleteMessageBatch` request deletes two messages. You must URL-encode the entire URL. However, in this example only the message body is URL-encoded to make the example easier to read. The structure of `AUTHPARAMS` depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/  
&Action=DeleteMessageBatch  
&DeleteMessageBatchRequestEntry.1.Id=msg1  
&DeleteMessageBatchRequestEntry.1.ReceiptHandle=gfk0T0R0waama4fVffkjPQrr  
vzMrOg0fTFk2LxT33EuB8wR0ZCFgKWYXGWFoqqCIiprQUEhir%2F5LeGPpYTLzjqLQxyQYaQ  
ALeSNHb0us3uE84uujxpBhsDkZUQkjFFkNqBXn48x1McVhTcI3YlH%2Bd%2BIqetIOHgBCZAP  
x6r%2B09dWabXeI6nbK5Ygih21DCdAwFV68Jo8DXhb3ErEfoDqx7vyvC5nCpdwqv%2BJhU%2  
FTNGjNN8t51v5c%2FAXvQsAzyZVNapxUrHit4NxRhKJ72uICcxruyE8eRXLxIVNgeNP8ZEDcw  
7zZU1Zw%3D%3D  
&DeleteMessageBatchRequestEntry.2.Id=msg2  
&DeleteMessageBatchRequestEntry.2.ReceiptHandle=gfk0T0R0waama4fVffkjKzMH  
MCymjQvfTFk2LxT33G4ms5subrE0deLKWSScPU1oD3J9zgeS4PQQ3U30qOumIE6AdAv3w%2F%  
2Fa1IXW6AqaWhGsEPaLm3Vf6IiWqdM8u5imB%2BNTw3tQRzOWdTOepjOjPcTpRxBtXix%2BE  
vwJOZUma9wabv%2BSw6ZHjwmNcVDx8dZXJhVp16Bksiox%2FGrUvrVTCJRTWTLc59oHLLF8sE  
kKzRmGNzTDGTiV%2BYjHfQj60FD3rVaXmzTsonXrhKJ72uIHVMGVQIAGgB%2BqAbSsqfKHDQtV  
OmJJgkHug%3D%3D  
&Expires=2020-10-18T22:30:52Z  
&Version=2012-11-05  
&AUTHPARAMS
```

Sample Response

```
<DeleteMessageBatchResponse>  
  <DeleteMessageBatchResult>
```

```
<DeleteMessageBatchResultEntry>
  <Id>msg1</Id>
</DeleteMessageBatchResultEntry>
<DeleteMessageBatchResultEntry>
  <Id>msg2</Id>
</DeleteMessageBatchResultEntry>
</DeleteMessageBatchResult>
<ResponseMetadata>
  <RequestId>d6f86b7a-74d1-4439-b43f-196a1e29cd85</RequestId>
</ResponseMetadata>
</DeleteMessageBatchResponse>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteQueue

Deletes the queue specified by the `QueueUrl`, regardless of the queue's contents.

Important

Be careful with the `DeleteQueue` action: When you delete a queue, any messages in the queue are no longer available.

When you delete a queue, the deletion process takes up to 60 seconds. Requests you send involving that queue during the 60 seconds might succeed. For example, a [SendMessage \(p. 51\)](#) request might succeed, but after 60 seconds the queue and the message you sent no longer exist.

When you delete a queue, you must wait at least 60 seconds before creating a queue with the same name.

Note

Cross-account permissions don't apply to this action. For more information, see [Grant cross-account permissions to a role and a user name](#) in the *Amazon SQS Developer Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 87\)](#).

QueueUrl

The URL of the Amazon SQS queue to delete.

Queue URLs and names are case-sensitive.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 89\)](#).

Examples

Example

The following example query request deletes the specified queue. The structure of `AUTHPARAMS` depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/  
?Action=DeleteQueue  
&Expires=2020-04-18T22%3A52%3A43PST  
&Version=2012-11-05  
&AUTHPARAMS
```

Sample Response

```
<DeleteQueueResponse>
  <ResponseMetadata>
    <RequestId>6fde8d1e-52cd-4581-8cd9-c512f4c64223</RequestId>
  </ResponseMetadata>
</DeleteQueueResponse>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetQueueAttributes

Gets attributes for the specified queue.

Note

To determine whether a queue is [FIFO](#), you can check whether `QueueName` ends with the `.fifo` suffix.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 87).

AttributeName.N

A list of attributes for which to retrieve information.

The `AttributeName.N` parameter is optional, but if you don't specify values for this parameter, the request returns empty results.

Note

In the future, new attributes might be added. If you write code that calls this action, we recommend that you structure your code so that it can handle new attributes gracefully.

The following attributes are supported:

Important

The `ApproximateNumberOfMessagesDelayed`, `ApproximateNumberOfMessagesNotVisible`, and `ApproximateNumberOfMessagesVisible` metrics may not achieve consistency until at least 1 minute after the producers stop sending messages. This period is required for the queue metadata to reach eventual consistency.

- `All` – Returns all values.
- `ApproximateNumberOfMessages` – Returns the approximate number of messages available for retrieval from the queue.
- `ApproximateNumberOfMessagesDelayed` – Returns the approximate number of messages in the queue that are delayed and not available for reading immediately. This can happen when the queue is configured as a delay queue or when a message has been sent with a delay parameter.
- `ApproximateNumberOfMessagesNotVisible` – Returns the approximate number of messages that are in flight. Messages are considered to be *in flight* if they have been sent to a client but have not yet been deleted or have not yet reached the end of their visibility window.
- `CreatedTimestamp` – Returns the time when the queue was created in seconds ([epoch time](#)).
- `DelaySeconds` – Returns the default delay on the queue in seconds.
- `LastModifiedTimestamp` – Returns the time when the queue was last changed in seconds ([epoch time](#)).
- `MaximumMessageSize` – Returns the limit of how many bytes a message can contain before Amazon SQS rejects it.
- `MessageRetentionPeriod` – Returns the length of time, in seconds, for which Amazon SQS retains a message.
- `Policy` – Returns the policy of the queue.
- `QueueArn` – Returns the Amazon resource name (ARN) of the queue.
- `ReceiveMessageWaitTimeSeconds` – Returns the length of time, in seconds, for which the `ReceiveMessage` action waits for a message to arrive.
- `VisibilityTimeout` – Returns the visibility timeout for the queue. For more information about the visibility timeout, see [Visibility Timeout](#) in the *Amazon SQS Developer Guide*.

The following attributes apply only to [dead-letter queues](#):

- **RedrivePolicy** – The string that includes the parameters for the dead-letter queue functionality of the source queue as a JSON object. The parameters are as follows:
 - **deadLetterTargetArn** – The Amazon Resource Name (ARN) of the dead-letter queue to which Amazon SQS moves messages after the value of **maxReceiveCount** is exceeded.
 - **maxReceiveCount** – The number of times a message is delivered to the source queue before being moved to the dead-letter queue. Default: 10. When the **ReceiveCount** for a message exceeds the **maxReceiveCount** for a queue, Amazon SQS moves the message to the dead-letter-queue.
- **RedriveAllowPolicy** – The string that includes the parameters for the permissions for the dead-letter queue redrive permission and which source queues can specify dead-letter queues as a JSON object. The parameters are as follows:
 - **redrivePermission** – The permission type that defines which source queues can specify the current queue as the dead-letter queue. Valid values are:
 - **allowAll** – (Default) Any source queues in this Amazon account in the same Region can specify this queue as the dead-letter queue.
 - **denyAll** – No source queues can specify this queue as the dead-letter queue.
 - **byQueue** – Only queues specified by the **sourceQueueArns** parameter can specify this queue as the dead-letter queue.
 - **sourceQueueArns** – The Amazon Resource Names (ARN)s of the source queues that can specify this queue as the dead-letter queue and redrive messages. You can specify this parameter only when the **redrivePermission** parameter is set to **byQueue**. You can specify up to 10 source queue ARNs. To allow more than 10 source queues to specify dead-letter queues, set the **redrivePermission** parameter to **allowAll**.

Note

The dead-letter queue of a FIFO queue must also be a FIFO queue. Similarly, the dead-letter queue of a standard queue must also be a standard queue.

The following attributes apply only to [server-side-encryption](#):

- **KmsMasterKeyId** – Returns the ID of an Amazon managed customer master key (CMK) for Amazon SQS or a custom CMK. For more information, see [Key Terms](#).
- **KmsDataKeyReusePeriodSeconds** – Returns the length of time, in seconds, for which Amazon SQS can reuse a data key to encrypt or decrypt messages before calling Amazon KMS again. For more information, see [How Does the Data Key Reuse Period Work?](#)
- **SqsManagedSseEnabled** – Returns information about whether the queue is using SSE-SQS encryption using SQS owned encryption keys. Only one server-side encryption option is supported per queue (e.g. [SSE-KMS](#) or [SSE-SQS](#)).

The following attributes apply only to [FIFO \(first-in-first-out\) queues](#):

- **FifoQueue** – Returns information about whether the queue is FIFO. For more information, see [FIFO queue logic](#) in the *Amazon SQS Developer Guide*.

Note

To determine whether a queue is [FIFO](#), you can check whether **QueueName** ends with the **.fifo** suffix.

- **ContentBasedDeduplication** – Returns whether content-based deduplication is enabled for the queue. For more information, see [Exactly-once processing](#) in the *Amazon SQS Developer Guide*.

The following attributes apply only to [high throughput for FIFO queues](#):

- **DeduplicationScope** – Specifies whether message deduplication occurs at the message group or queue level. Valid values are **messageGroup** and **queue**.
- **FifoThroughputLimit** – Specifies whether the FIFO queue throughput quota applies to the entire queue or per message group. Valid values are **perQueue** and **perMessageGroupId**.

The `perMessageGroupId` value is allowed only when the value for `DeduplicationScope` is `messageGroup`.

To enable high throughput for FIFO queues, do the following:

- Set `DeduplicationScope` to `messageGroup`.
- Set `FifoThroughputLimit` to `perMessageGroupId`.

If you set these attributes to anything other than the values shown for enabling high throughput, normal throughput is in effect and deduplication occurs as specified.

For information on throughput quotas, see [Quotas related to messages](#) in the *Amazon SQS Developer Guide*.

Type: Array of strings

Valid Values: `All` | `Policy` | `VisibilityTimeout` | `MaximumMessageSize` | `MessageRetentionPeriod` | `ApproximateNumberOfMessages` | `ApproximateNumberOfMessagesNotVisible` | `CreatedTimestamp` | `LastModifiedTimestamp` | `QueueArn` | `ApproximateNumberOfMessagesDelayed` | `DelaySeconds` | `ReceiveMessageWaitTimeSeconds` | `RedrivePolicy` | `FifoQueue` | `ContentBasedDeduplication` | `KmsMasterKeyId` | `KmsDataKeyReusePeriodSeconds` | `DeduplicationScope` | `FifoThroughputLimit` | `RedriveAllowPolicy` | `SqsManagedSseEnabled`

Required: No

QueueUrl

The URL of the Amazon SQS queue whose attribute information is retrieved.

Queue URLs and names are case-sensitive.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

Attribute , Attribute.N.Name (key), Attribute.N.Value (value)

A map of attributes to their respective values.

Type: String to string map

Valid Keys: `All` | `Policy` | `VisibilityTimeout` | `MaximumMessageSize` | `MessageRetentionPeriod` | `ApproximateNumberOfMessages` | `ApproximateNumberOfMessagesNotVisible` | `CreatedTimestamp` | `LastModifiedTimestamp` | `QueueArn` | `ApproximateNumberOfMessagesDelayed` | `DelaySeconds` | `ReceiveMessageWaitTimeSeconds` | `RedrivePolicy` | `FifoQueue` | `ContentBasedDeduplication` | `KmsMasterKeyId` | `KmsDataKeyReusePeriodSeconds` | `DeduplicationScope` | `FifoThroughputLimit` | `RedriveAllowPolicy` | `SqsManagedSseEnabled`

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 89\)](#).

InvalidAttributeName

The specified attribute doesn't exist.

HTTP Status Code: 400

Examples

Example

The following example query requests gets all the attribute values for the specified queue. The structure of AUTHPARAMS depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/  
?Action=GetQueueAttributes  
&AttributeName.1=All  
&Expires=2020-10-18T22%3A52%3A43PST  
&Version=2012-11-05  
&AUTHPARAMS
```

Sample Response

```
<GetQueueAttributesResponse>  
  <GetQueueAttributesResult>  
    <Attribute>  
      <Name>ReceiveMessageWaitTimeSeconds</Name>  
      <Value>2</Value>  
    </Attribute>  
    <Attribute>  
      <Name>VisibilityTimeout</Name>  
      <Value>30</Value>  
    </Attribute>  
    <Attribute>  
      <Name>ApproximateNumberOfMessages</Name>  
      <Value>0</Value>  
    </Attribute>  
    <Attribute>  
      <Name>ApproximateNumberOfMessagesNotVisible</Name>  
      <Value>0</Value>  
    </Attribute>  
    <Attribute>  
      <Name>CreatedTimestamp</Name>  
      <Value>1286771522</Value>  
    </Attribute>  
    <Attribute>  
      <Name>LastModifiedTimestamp</Name>  
      <Value>1286771522</Value>  
    </Attribute>  
    <Attribute>  
      <Name>QueueArn</Name>  
      <Value>arn:aws:sqs:us-east-2:123456789012:MyQueue</Value>  
    </Attribute>  
    <Attribute>  
      <Name>MaximumMessageSize</Name>  
      <Value>8192</Value>  
    </Attribute>  
    <Attribute>
```

```
<Name>MessageRetentionPeriod</Name>
  <Value>345600</Value>
</Attribute>
</GetQueueAttributesResult>
<ResponseMetadata>
  <RequestId>1ea71be5-b5a2-4f9d-b85a-945d8d08cd0b</RequestId>
</ResponseMetadata>
</GetQueueAttributesResponse>
```

Example

The following example query request gets three attribute values for the specified queue. The structure of AUTHPARAMS depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/
?Action=GetQueueAttributes
&Action=GetQueueAttributes
&AttributeName.1=VisibilityTimeout
&AttributeName.2=DelaySeconds
&AttributeName.3=ReceiveMessageWaitTimeSeconds
&Expires=2020-10-18T22%3A52%3A43PST
&Version=2012-11-05
&AUTHPARAMS
```

Sample Response

```
<GetQueueAttributesResponse>
  <GetQueueAttributesResult>
    <Attribute>
      <Name>VisibilityTimeout</Name>
      <Value>30</Value>
    </Attribute>
    <Attribute>
      <Name>DelaySeconds</Name>
      <Value>0</Value>
    </Attribute>
    <Attribute>
      <Name>ReceiveMessageWaitTimeSeconds</Name>
      <Value>2</Value>
    </Attribute>
  </GetQueueAttributesResult>
</GetQueueAttributesResponse>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)

- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetQueueUrl

Returns the URL of an existing Amazon SQS queue.

To access a queue that belongs to another AWS account, use the `QueueOwnerAWSAccountId` parameter to specify the account ID of the queue's owner. The queue's owner must grant you permission to access the queue. For more information about shared queue access, see [AddPermission \(p. 3\)](#) or see [Allow Developers to Write Messages to a Shared Queue](#) in the *Amazon SQS Developer Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 87\)](#).

QueueName

The name of the queue whose URL must be fetched. Maximum 80 characters. Valid values: alphanumeric characters, hyphens (-), and underscores (_).

Queue URLs and names are case-sensitive.

Type: String

Required: Yes

QueueOwnerAWSAccountId

The Amazon Web Services account ID of the account that created the queue.

Type: String

Required: No

Response Elements

The following element is returned by the service.

QueueUrl

The URL of the queue.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 89\)](#).

AWS.SimpleQueueService.NonExistentQueue

The specified queue doesn't exist.

HTTP Status Code: 400

Examples

Example

The following example query request gets the URL for the specified queue. The structure of AUTHPARAMS depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/  
?Action=GetQueueUrl  
&QueueName=MyQueue  
&Expires=2020-10-24T22%3A52%3A43PST  
&Version=2012-11-05  
&AUTHPARAMS
```

Sample Response

```
<GetQueueUrlResponse>  
  <GetQueueUrlResult>  
    <QueueUrl>https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue</QueueUrl>  
  </GetQueueUrlResult>  
  <ResponseMetadata>  
    <RequestId>470a6f13-2ed9-4181-ad8a-2fdea142988e</RequestId>  
  </ResponseMetadata>  
</GetQueueUrlResponse>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListDeadLetterSourceQueues

Returns a list of your queues that have the `RedrivePolicy` queue attribute configured with a dead-letter queue.

The `ListDeadLetterSourceQueues` methods supports pagination. Set parameter `MaxResults` in the request to specify the maximum number of results to be returned in the response. If you do not set `MaxResults`, the response includes a maximum of 1,000 results. If you set `MaxResults` and there are additional results to display, the response includes a value for `NextToken`. Use `NextToken` as a parameter in your next request to `ListDeadLetterSourceQueues` to receive the next page of results.

For more information about using dead-letter queues, see [Using Amazon SQS Dead-Letter Queues](#) in the *Amazon SQS Developer Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 87\)](#).

MaxResults

Maximum number of results to include in the response. Value range is 1 to 1000. You must set `MaxResults` to receive a value for `NextToken` in the response.

Type: Integer

Required: No

NextToken

Pagination token to request the next set of results.

Type: String

Required: No

QueueUrl

The URL of a dead-letter queue.

Queue URLs and names are case-sensitive.

Type: String

Required: Yes

Response Elements

The following elements are returned by the service.

NextToken

Pagination token to include in the next request. Token value is `null` if there are no additional results to request, or if you did not set `MaxResults` in the request.

Type: String

QueueUrl.N

A list of source queue URLs that have the `RedrivePolicy` queue attribute configured with a dead-letter queue.

Type: Array of strings

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 89\)](#).

AWS.SimpleQueueService.NonExistentQueue

The specified queue doesn't exist.

HTTP Status Code: 400

Examples

Example

The following example query request returns a list of dead letter source queues. In this example, only one source queue, `MySourceQueue`, is configured with a dead-letter queue. The structure of `AUTHPARAMS` depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Sample Request

```
?Action=ListDeadLetterSourceQueues
&Expires=2020-12-12T22%3A52%3A43PST
&Version=2012-11-05
&AUTHPARAMS
```

Sample Response

```
<ListDeadLetterSourceQueuesResponse xmlns="https://queue.amazonaws.com/doc/2012-11-05/">
  <ListDeadLetterSourceQueuesResult>
    <QueueUrl>https://sqs.us-east-2.amazonaws.com/123456789012/MySourceQueue</QueueUrl>
  </ListDeadLetterSourceQueuesResult>
  <ResponseMetadata>
    <RequestId>8ffb921f-b85e-53d9-abcf-d8d0057f38fc</RequestId>
  </ResponseMetadata>
</ListDeadLetterSourceQueuesResponse>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

ListQueues

Returns a list of your queues in the current region. The response includes a maximum of 1,000 results. If you specify a value for the optional `QueueNamePrefix` parameter, only queues with a name that begins with the specified value are returned.

The `listQueues` methods supports pagination. Set parameter `MaxResults` in the request to specify the maximum number of results to be returned in the response. If you do not set `MaxResults`, the response includes a maximum of 1,000 results. If you set `MaxResults` and there are additional results to display, the response includes a value for `NextToken`. Use `NextToken` as a parameter in your next request to `listQueues` to receive the next page of results.

Note

Cross-account permissions don't apply to this action. For more information, see [Grant cross-account permissions to a role and a user name](#) in the *Amazon SQS Developer Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 87).

MaxResults

Maximum number of results to include in the response. Value range is 1 to 1000. You must set `MaxResults` to receive a value for `NextToken` in the response.

Type: Integer

Required: No

NextToken

Pagination token to request the next set of results.

Type: String

Required: No

QueueNamePrefix

A string to use for filtering the list results. Only those queues whose name begins with the specified string are returned.

Queue URLs and names are case-sensitive.

Type: String

Required: No

Response Elements

The following elements are returned by the service.

NextToken

Pagination token to include in the next request. Token value is `null` if there are no additional results to request, or if you did not set `MaxResults` in the request.

Type: String

QueueUrl.N

A list of queue URLs, up to 1,000 entries, or the value of MaxResults that you sent in the request.

Type: Array of strings

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 89\)](#).

Examples

Example

The following example query request returns the queues whose names begin with the letter t. The structure of AUTHPARAMS depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/  
?Action=ListQueues  
&QueueNamePrefix=M  
&Expires=2020-04-18T22%3A52%3A43PST  
&Version=2012-11-05  
&AUTHPARAMS
```

Sample Response

```
<ListQueuesResponse>  
  <ListQueuesResult>  
    <QueueUrl>https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue</QueueUrl>  
  </ListQueuesResult>  
  <ResponseMetadata>  
    <RequestId>725275ae-0b9b-4762-b238-436d7c65a1ac</RequestId>  
  </ResponseMetadata>  
</ListQueuesResponse>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListQueueTags

List all cost allocation tags added to the specified Amazon SQS queue. For an overview, see [Tagging Your Amazon SQS Queues](#) in the *Amazon SQS Developer Guide*.

Note

Cross-account permissions don't apply to this action. For more information, see [Grant cross-account permissions to a role and a user name](#) in the *Amazon SQS Developer Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 87\)](#).

QueueUrl

The URL of the queue.

Type: String

Required: Yes

Response Elements

The following element is returned by the service.

Tag , Tag.N.Key (key), Tag.N.Value (value)

The list of all tags added to the specified queue.

Type: String to string map

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 89\)](#).

Examples

Example

This example illustrates one usage of ListQueueTags.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/  
?Action=ListQueueTags  
&Expires=2020-10-18T22%3A52%3A43PST  
&Version=2012-11-05  
&AUTHPARAMS
```

Sample Response

```
<ListQueueTagsResponse>
```

```
<ListQueueTagsResult>
  <Tag>
    <Key>QueueType</Key>
    <Value>Production</Value>
  </Tag>
  <Tag>
    <Key>Owner</Key>
    <Value>Developer123</Value>
  </Tag>
</ListQueueTagsResult>
<ResponseMetadata>
  <RequestId>a1b2c3d4-e567-8901-23f4-g5678901hi23</RequestId>
</ResponseMetadata>
</ListQueueTagsResponse>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

PurgeQueue

Deletes the messages in a queue specified by the `QueueURL` parameter.

Important

When you use the `PurgeQueue` action, you can't retrieve any messages deleted from a queue. The message deletion process takes up to 60 seconds. We recommend waiting for 60 seconds regardless of your queue's size.

Messages sent to the queue *before* you call `PurgeQueue` might be received but are deleted within the next minute.

Messages sent to the queue *after* you call `PurgeQueue` might be deleted while the queue is being purged.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 87\)](#).

QueueUrl

The URL of the queue from which the `PurgeQueue` action deletes messages.

Queue URLs and names are case-sensitive.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 89\)](#).

AWS.SimpleQueueService.NonExistentQueue

The specified queue doesn't exist.

HTTP Status Code: 400

AWS.SimpleQueueService.PurgeQueueInProgress

Indicates that the specified queue previously received a `PurgeQueue` request within the last 60 seconds (the time it can take to delete the messages in the queue).

HTTP Status Code: 403

Examples

Example

The following example query request purges a queue named `MyQueue`. The structure of `AUTHPARAMS` depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/  
?Action=PurgeQueue  
&Expires=2020-12-12T22%3A52%3A43PST  
&Version=2012-11-05  
&AUTHPARAMS
```

Sample Response

```
<PurgeQueueResponse>  
  <ResponseMetadata>  
    <RequestId>6fde8d1e-52cd-4581-8cd9-c512f4c64223</RequestId>  
  </ResponseMetadata>  
</PurgeQueueResponse>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ReceiveMessage

Retrieves one or more messages (up to 10), from the specified queue. Using the `waitTimeSeconds` parameter enables long-poll support. For more information, see [Amazon SQS Long Polling](#) in the *Amazon SQS Developer Guide*.

Short poll is the default behavior where a weighted random set of machines is sampled on a `ReceiveMessage` call. Thus, only the messages on the sampled machines are returned. If the number of messages in the queue is small (fewer than 1,000), you most likely get fewer messages than you requested per `ReceiveMessage` call. If the number of messages in the queue is extremely small, you might not receive any messages in a particular `ReceiveMessage` response. If this happens, repeat the request.

For each message returned, the response includes the following:

- The message body.
- An MD5 digest of the message body. For information about MD5, see [RFC1321](#).
- The `MessageId` you received when you sent the message to the queue.
- The receipt handle.
- The message attributes.
- An MD5 digest of the message attributes.

The receipt handle is the identifier you must provide when deleting the message. For more information, see [Queue and Message Identifiers](#) in the *Amazon SQS Developer Guide*.

You can provide the `visibilityTimeout` parameter in your request. The parameter is applied to the messages that Amazon SQS returns in the response. If you don't include the parameter, the overall visibility timeout for the queue is used for the returned messages. For more information, see [Visibility Timeout](#) in the *Amazon SQS Developer Guide*.

A message that isn't deleted or a message whose visibility isn't extended before the visibility timeout expires counts as a failed receive. Depending on the configuration of the queue, the message might be sent to the dead-letter queue.

Note

In the future, new attributes might be added. If you write code that calls this action, we recommend that you structure your code so that it can handle new attributes gracefully.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 87\)](#).

AttributeName.N

A list of attributes that need to be returned along with each message. These attributes include:

- `All` – Returns all values.
- `ApproximateFirstReceiveTimestamp` – Returns the time the message was first received from the queue ([epoch time](#) in milliseconds).
- `ApproximateReceiveCount` – Returns the number of times a message has been received across all queues but not deleted.
- `AWSTraceHeader` – Returns the Amazon X-Ray trace header string.
- `SenderId`
 - For an IAM user, returns the IAM user ID, for example `ABCDEFGHI1JKLMNOPQ23R`.

- For an IAM role, returns the IAM role ID, for example `ABCDE1F2GH3I4JK5LMNOP:i-a123b456`.
- `SentTimestamp` – Returns the time the message was sent to the queue ([epoch time](#) in milliseconds).
- `SqsManagedSseEnabled` – Enables server-side queue encryption using SQS owned encryption keys. Only one server-side encryption option is supported per queue (e.g. [SSE-KMS](#) or [SSE-SQS](#)).
- `MessageDeduplicationId` – Returns the value provided by the producer that calls the [SendMessage](#) (p. 51) action.
- `MessageGroupId` – Returns the value provided by the producer that calls the [SendMessage](#) (p. 51) action. Messages with the same `MessageGroupId` are returned in sequence.
- `SequenceNumber` – Returns the value provided by Amazon SQS.

Type: Array of strings

Valid Values: `All` | `Policy` | `VisibilityTimeout` | `MaximumMessageSize` | `MessageRetentionPeriod` | `ApproximateNumberOfMessages` | `ApproximateNumberOfMessagesNotVisible` | `CreatedTimestamp` | `LastModifiedTimestamp` | `QueueArn` | `ApproximateNumberOfMessagesDelayed` | `DelaySeconds` | `ReceiveMessageWaitTimeSeconds` | `RedrivePolicy` | `FifoQueue` | `ContentBasedDeduplication` | `KmsMasterKeyId` | `KmsDataKeyReusePeriodSeconds` | `DeduplicationScope` | `FifoThroughputLimit` | `RedriveAllowPolicy` | `SqsManagedSseEnabled`

Required: No

MaxNumberOfMessages

The maximum number of messages to return. Amazon SQS never returns more messages than this value (however, fewer messages might be returned). Valid values: 1 to 10. Default: 1.

Type: Integer

Required: No

MessageAttributeName.N

The name of the message attribute, where *N* is the index.

- The name can contain alphanumeric characters and the underscore (`_`), hyphen (`-`), and period (`.`).
- The name is case-sensitive and must be unique among all attribute names for the message.
- The name must not start with AWS-reserved prefixes such as `AWS.` or `Amazon.` (or any casing variants).
- The name must not start or end with a period (`.`), and it should not have periods in succession (`..`).
- The name can be up to 256 characters long.

When using `ReceiveMessage`, you can send a list of attribute names to receive, or you can return all of the attributes by specifying `All` or `.*` in your request. You can also use all message attributes starting with a prefix, for example `bar.*`.

Type: Array of strings

Required: No

QueueUrl

The URL of the Amazon SQS queue from which messages are received.

Queue URLs and names are case-sensitive.

Type: String

Required: Yes

ReceiveRequestAttemptId

This parameter applies only to FIFO (first-in-first-out) queues.

The token used for deduplication of `ReceiveMessage` calls. If a networking issue occurs after a `ReceiveMessage` action, and instead of a response you receive a generic error, it is possible to retry the same action with an identical `ReceiveRequestAttemptId` to retrieve the same set of messages, even if their visibility timeout has not yet expired.

- You can use `ReceiveRequestAttemptId` only for 5 minutes after a `ReceiveMessage` action.
- When you set `FifoQueue`, a caller of the `ReceiveMessage` action can provide a `ReceiveRequestAttemptId` explicitly.
- If a caller of the `ReceiveMessage` action doesn't provide a `ReceiveRequestAttemptId`, Amazon SQS generates a `ReceiveRequestAttemptId`.
- It is possible to retry the `ReceiveMessage` action with the same `ReceiveRequestAttemptId` if none of the messages have been modified (deleted or had their visibility changes).
- During a visibility timeout, subsequent calls with the same `ReceiveRequestAttemptId` return the same messages and receipt handles. If a retry occurs within the deduplication interval, it resets the visibility timeout. For more information, see [Visibility Timeout](#) in the *Amazon SQS Developer Guide*.

Important

If a caller of the `ReceiveMessage` action still processes messages when the visibility timeout expires and messages become visible, another worker consuming from the same queue can receive the same messages and therefore process duplicates. Also, if a consumer whose message processing time is longer than the visibility timeout tries to delete the processed messages, the action fails with an error.

To mitigate this effect, ensure that your application observes a safe threshold before the visibility timeout expires and extend the visibility timeout as necessary.

- While messages with a particular `MessageGroupId` are invisible, no more messages belonging to the same `MessageGroupId` are returned until the visibility timeout expires. You can still receive messages with another `MessageGroupId` as long as it is also visible.
- If a caller of `ReceiveMessage` can't track the `ReceiveRequestAttemptId`, no retries work until the original visibility timeout expires. As a result, delays might occur but the messages in the queue remain in a strict order.

The maximum length of `ReceiveRequestAttemptId` is 128 characters.

`ReceiveRequestAttemptId` can contain alphanumeric characters (a-z, A-Z, 0-9) and punctuation (!"#\$%&'()*+,-./:;<=>?@[\\]^_`{|}~).

For best practices of using `ReceiveRequestAttemptId`, see [Using the ReceiveRequestAttemptId Request Parameter](#) in the *Amazon SQS Developer Guide*.

Type: String

Required: No

VisibilityTimeout

The duration (in seconds) that the received messages are hidden from subsequent retrieve requests after being retrieved by a `ReceiveMessage` request.

Type: Integer

Required: No

WaitTimeSeconds

The duration (in seconds) for which the call waits for a message to arrive in the queue before returning. If a message is available, the call returns sooner than `waitTimeSeconds`. If no messages are available and the wait time expires, the call returns successfully with an empty list of messages.

Important

To avoid HTTP errors, ensure that the HTTP response timeout for `ReceiveMessage` requests is longer than the `waitTimeSeconds` parameter. For example, with the Java SDK, you can set HTTP transport settings using the [NettyNioAsyncHttpClient](#) for asynchronous clients, or the [ApacheHttpClient](#) for synchronous clients.

Type: Integer

Required: No

Response Elements

The following element is returned by the service.

Message.N

A list of messages.

Type: Array of [Message \(p. 76\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 89\)](#).

OverLimit

The specified action violates a limit. For example, `ReceiveMessage` returns this error if the maximum number of in flight messages is reached and `AddPermission` returns this error if the maximum number of permissions for the queue is reached.

HTTP Status Code: 403

Examples

Example

The following example query request receives messages from the specified queue. The structure of `AUTHPARAMS` depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/  
?Action=ReceiveMessage  
&MaxNumberOfMessages=5  
&VisibilityTimeout=15  
&AttributeName=All  
&Expires=2020-04-18T22%3A52%3A43PST  
&Version=2012-11-05
```

&AUTHPARAMS

Sample Response

```
<ReceiveMessageResponse>
  <ReceiveMessageResult>
    <Message>
      <MessageId>5fea7756-0ea4-451a-a703-a558b933e274</MessageId>
      <ReceiptHandle>
        MbZj6wDWli+JvwwJaBV+3dcjk2YW2vA3+STFFljTM8tJJg6HRG6PYSasuWXPJB+Cw
        Lj1FjgXUv1uSj1gUPAWV66FU/WeR4mq2OKpEGYWbnLmpRCJVAyeMjeU5ZBdteQ+QE
        auMzc8ZRv37sIW2iJKq3M9MFx1YvV11A2x/KSbkJO=
      </ReceiptHandle>
      <MD5OfBody>fafb00f5732ab283681e124bf8747ed1</MD5OfBody>
      <Body>This is a test message</Body>
      <Attribute>
        <Name>SenderId</Name>
        <Value>195004372649</Value>
      </Attribute>
      <Attribute>
        <Name>SentTimestamp</Name>
        <Value>1238099229000</Value>
      </Attribute>
      <Attribute>
        <Name>ApproximateReceiveCount</Name>
        <Value>5</Value>
      </Attribute>
      <Attribute>
        <Name>ApproximateFirstReceiveTimestamp</Name>
        <Value>1250700979248</Value>
      </Attribute>
    </Message>
  </ReceiveMessageResult>
  <ResponseMetadata>
    <RequestId>b6633655-283d-45b4-ae4-4e84e0ae6afa</RequestId>
  </ResponseMetadata>
</ReceiveMessageResponse>
```

Example

The following example enables long polling by calling the `ReceiveMessage` action with the `WaitTimeSeconds` parameter set to 10 seconds.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/
?Action=ReceiveMessage
&WaitTimeSeconds=10
&MaxNumberOfMessages=5
&VisibilityTimeout=15
&AttributeName=All
&Expires=2020-04-18T22%3A52%3A43PST
&Version=2012-11-05
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

RemovePermission

Revokes any permissions in the queue policy that matches the specified `Label` parameter.

Note

- Only the owner of a queue can remove permissions from it.
- Cross-account permissions don't apply to this action. For more information, see [Grant cross-account permissions to a role and a user name](#) in the *Amazon SQS Developer Guide*.
- To remove the ability to change queue permissions, you must deny permission to the `AddPermission`, `RemovePermission`, and `SetQueueAttributes` actions in your IAM policy.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 87\)](#).

Label

The identification of the permission to remove. This is the label added using the [AddPermission \(p. 3\)](#) action.

Type: String

Required: Yes

QueueUrl

The URL of the Amazon SQS queue from which permissions are removed.

Queue URLs and names are case-sensitive.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 89\)](#).

Examples

Example

The following example query request removes the `testLabel` permission from the queue named `MyQueue`. The structure of `AUTHPARAMS` depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/  
?Action=RemovePermission  
&Label=MyLabel
```

```
&Expires=2020-04-18T22%3A52%3A43PST  
&Version=2012-11-05  
&AUTHPARAMS
```

Sample Response

```
<RemovePermissionResponse>  
  <ResponseMetadata>  
    <RequestId>f8bdb362-6616-42c0-977a-ce9a8bcce3bb</RequestId>  
  </ResponseMetadata>  
</RemovePermissionResponse>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

SendMessage

Delivers a message to the specified queue.

Important

A message can include only XML, JSON, and unformatted text. The following Unicode characters are allowed:

`#x9 | #xA | #xD | #x20 to #xD7FF | #xE000 to #xFFFF | #x10000 to #x10FFFF`

Any characters not included in this list will be rejected. For more information, see the [W3C specification for characters](#).

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 87\)](#).

DelaySeconds

The length of time, in seconds, for which to delay a specific message. Valid values: 0 to 900. Maximum: 15 minutes. Messages with a positive `DelaySeconds` value become available for processing after the delay period is finished. If you don't specify a value, the default value for the queue applies.

Note

When you set `FifoQueue`, you can't set `DelaySeconds` per message. You can set this parameter only on a queue level.

Type: Integer

Required: No

MessageAttribute , `MessageAttribute.N.Name` (key), `MessageAttribute.N.Value` (value)

Each message attribute consists of a `Name`, `Type`, and `Value`. For more information, see [Amazon SQS message attributes](#) in the *Amazon SQS Developer Guide*.

Type: String to [MessageAttributeValue \(p. 78\)](#) object map

Required: No

MessageBody

The message to send. The minimum size is one character. The maximum size is 256 KB.

Important

A message can include only XML, JSON, and unformatted text. The following Unicode characters are allowed:

`#x9 | #xA | #xD | #x20 to #xD7FF | #xE000 to #xFFFF | #x10000 to #x10FFFF`

Any characters not included in this list will be rejected. For more information, see the [W3C specification for characters](#).

Type: String

Required: Yes

MessageDeduplicationId

This parameter applies only to FIFO (first-in-first-out) queues.

The token used for deduplication of sent messages. If a message with a particular `MessageDeduplicationId` is sent successfully, any messages sent with the same `MessageDeduplicationId` are accepted successfully but aren't delivered during the 5-minute

deduplication interval. For more information, see [Exactly-once processing](#) in the *Amazon SQS Developer Guide*.

- Every message must have a unique `MessageDeduplicationId`,
 - You may provide a `MessageDeduplicationId` explicitly.
 - If you aren't able to provide a `MessageDeduplicationId` and you enable `ContentBasedDeduplication` for your queue, Amazon SQS uses a SHA-256 hash to generate the `MessageDeduplicationId` using the body of the message (but not the attributes of the message).
 - If you don't provide a `MessageDeduplicationId` and the queue doesn't have `ContentBasedDeduplication` set, the action fails with an error.
 - If the queue has `ContentBasedDeduplication` set, your `MessageDeduplicationId` overrides the generated one.
- When `ContentBasedDeduplication` is in effect, messages with identical content sent within the deduplication interval are treated as duplicates and only one copy of the message is delivered.
- If you send one message with `ContentBasedDeduplication` enabled and then another message with a `MessageDeduplicationId` that is the same as the one generated for the first `MessageDeduplicationId`, the two messages are treated as duplicates and only one copy of the message is delivered.

Note

The `MessageDeduplicationId` is available to the consumer of the message (this can be useful for troubleshooting delivery issues).

If a message is sent successfully but the acknowledgement is lost and the message is resent with the same `MessageDeduplicationId` after the deduplication interval, Amazon SQS can't detect duplicate messages.

Amazon SQS continues to keep track of the message deduplication ID even after the message is received and deleted.

The maximum length of `MessageDeduplicationId` is 128 characters.

`MessageDeduplicationId` can contain alphanumeric characters (a–z, A–Z, 0–9) and punctuation (!"#\$%&'()*+,-./:;<=>?@[\\]^_`{|}~).

For best practices of using `MessageDeduplicationId`, see [Using the MessageDeduplicationId Property](#) in the *Amazon SQS Developer Guide*.

Type: String

Required: No

MessageGroupId

This parameter applies only to FIFO (first-in-first-out) queues.

The tag that specifies that a message belongs to a specific message group. Messages that belong to the same message group are processed in a FIFO manner (however, messages in different message groups might be processed out of order). To interleave multiple ordered streams within a single queue, use `MessageGroupId` values (for example, session data for multiple users). In this scenario, multiple consumers can process the queue, but the session data of each user is processed in a FIFO fashion.

- You must associate a non-empty `MessageGroupId` with a message. If you don't provide a `MessageGroupId`, the action fails.
- `ReceiveMessage` might return messages with multiple `MessageGroupId` values. For each `MessageGroupId`, the messages are sorted by time sent. The caller can't specify a `MessageGroupId`.

The length of `MessageGroupId` is 128 characters. Valid values: alphanumeric characters and punctuation (!"#\$%&'()*+,-./:;<=>?@[\\]^_`{|}~).

For best practices of using `MessageGroupId`, see [Using the MessageGroupId Property](#) in the *Amazon SQS Developer Guide*.

Important

`MessageGroupId` is required for FIFO queues. You can't use it for Standard queues.

Type: String

Required: No

MessageSystemAttribute , `MessageSystemAttribute.N.Name` (key), `MessageSystemAttribute.N.Value` (value)

The message system attribute to send. Each message system attribute consists of a `Name`, `Type`, and `Value`.

Important

- Currently, the only supported message system attribute is `AWSTraceHeader`. Its type must be `String` and its value must be a correctly formatted Amazon X-Ray trace header string.
- The size of a message system attribute doesn't count towards the total size of a message.

Type: String to [MessageSystemAttributeValue](#) (p. 80) object map

Valid Keys: `AWSTraceHeader`

Required: No

QueueUrl

The URL of the Amazon SQS queue to which a message is sent.

Queue URLs and names are case-sensitive.

Type: String

Required: Yes

Response Elements

The following elements are returned by the service.

MD5OfMessageAttributes

An MD5 digest of the non-URL-encoded message attribute string. You can use this attribute to verify that Amazon SQS received the message correctly. Amazon SQS URL-decodes the message before creating the MD5 digest. For information about MD5, see [RFC1321](#).

Type: String

MD5OfMessageBody

An MD5 digest of the non-URL-encoded message body string. You can use this attribute to verify that Amazon SQS received the message correctly. Amazon SQS URL-decodes the message before creating the MD5 digest. For information about MD5, see [RFC1321](#).

Type: String

MD5OfMessageSystemAttributes

An MD5 digest of the non-URL-encoded message system attribute string. You can use this attribute to verify that Amazon SQS received the message correctly. Amazon SQS URL-decodes the message before creating the MD5 digest.

Type: String

MessageId

An attribute containing the `MessageId` of the message sent to the queue. For more information, see [Queue and Message Identifiers](#) in the *Amazon SQS Developer Guide*.

Type: String

SequenceNumber

This parameter applies only to FIFO (first-in-first-out) queues.

The large, non-consecutive number that Amazon SQS assigns to each message.

The length of `SequenceNumber` is 128 bits. `SequenceNumber` continues to increase for a particular `MessageGroupId`.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 89).

AWS.SimpleQueueService.UnsupportedOperation

Error code 400. Unsupported operation.

HTTP Status Code: 400

InvalidMessageContents

The message contains characters outside the allowed set.

HTTP Status Code: 400

Examples

Example

The following example `SendMessage` request sends a message containing `This is a test message` to the queue. You must URL-encode the entire URL. However, in this example only the message body is URL-encoded to make the example easier to read. The structure of `AUTHPARAMS` depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/  
?Action=SendMessage  
&MessageBody=This+is+a+test+message  
&MessageAttribute.1.Name=my_attribute_name_1  
&MessageAttribute.1.Value.StringValue=my_attribute_value_1  
&MessageAttribute.1.Value.DataType=String  
&MessageAttribute.2.Name=my_attribute_name_2  
&MessageAttribute.2.Value.StringValue=my_attribute_value_2  
&MessageAttribute.2.Value.DataType=String  
&Expires=2020-05-05T22%3A52%3A43PST  
&Version=2012-11-05
```

&AUTHPARAMS

Sample Response

```
<SendMessageResponse>
  <SendMessageResult>
    <MD5OfMessageBody>fafb00f5732ab283681e124bf8747ed1</MD5OfMessageBody>
    <MD5OfMessageAttributes>3ae8f24a165a8cedc005670c81a27295</MD5OfMessageAttributes>
    <MessageId>5fea7756-0ea4-451a-a703-a558b933e274</MessageId>
  </SendMessageResult>
  <ResponseMetadata>
    <RequestId>27daac76-34dd-47df-bd01-1f6e873584a0</RequestId>
  </ResponseMetadata>
</SendMessageResponse>
```

Example

The following example creates a *message timer*—applying a 45-second initial visibility delay to a single message— by calling the `SendMessage` action with the `DelaySeconds` parameter set to 45 seconds.

Note

Queue URLs and names are case-sensitive.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/
?Action=SendMessage
&MessageBody=This+is+a+test+message
&DelaySeconds=45
&Expires=2020-12-18T22%3A52%3A43PST
&Version=2012-11-05
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

SendMessageBatch

Delivers up to ten messages to the specified queue. This is a batch version of [SendMessage \(p. 51\)](#). For a FIFO queue, multiple messages within a single batch are enqueued in the order they are sent.

The result of sending each message is reported individually in the response. Because the batch request can result in a combination of successful and unsuccessful actions, you should check for batch errors even when the call returns an HTTP status code of 200.

The maximum allowed individual message size and the maximum total payload size (the sum of the individual lengths of all of the batched messages) are both 256 KB (262,144 bytes).

Important

A message can include only XML, JSON, and unformatted text. The following Unicode characters are allowed:

`#x9 | #xA | #xD | #x20 to #xD7FF | #xE000 to #xFFFF | #x10000 to #x10FFFF`

Any characters not included in this list will be rejected. For more information, see the [W3C specification for characters](#).

If you don't specify the `DelaySeconds` parameter for an entry, Amazon SQS uses the default value for the queue.

Some actions take lists of parameters. These lists are specified using the `param.n` notation. Values of `n` are integers starting from 1. For example, a parameter list with two elements looks like this:

```
&AttributeName.1=first
```

```
&AttributeName.2=second
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 87\)](#).

QueueUrl

The URL of the Amazon SQS queue to which batched messages are sent.

Queue URLs and names are case-sensitive.

Type: String

Required: Yes

SendMessageBatchRequestEntry.N

A list of [SendMessageBatchRequestEntry \(p. 82\)](#) items.

Type: Array of [SendMessageBatchRequestEntry \(p. 82\)](#) objects

Required: Yes

Response Elements

The following elements are returned by the service.

BatchResultErrorEntry.N

A list of [BatchResultErrorEntry \(p. 71\)](#) items with error details about each message that can't be enqueued.

Type: Array of [BatchResultErrorEntry](#) (p. 71) objects

SendMessageBatchResultEntry.N

A list of [SendMessageBatchResultEntry](#) (p. 85) items.

Type: Array of [SendMessageBatchResultEntry](#) (p. 85) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 89).

AWS.SimpleQueueService.BatchEntryIdsNotDistinct

Two or more batch entries in the request have the same Id.

HTTP Status Code: 400

AWS.SimpleQueueService.BatchRequestTooLong

The length of all the messages put together is more than the limit.

HTTP Status Code: 400

AWS.SimpleQueueService.EmptyBatchRequest

The batch request doesn't contain any entries.

HTTP Status Code: 400

AWS.SimpleQueueService.InvalidBatchEntryId

The Id of a batch entry in a batch request doesn't abide by the specification.

HTTP Status Code: 400

AWS.SimpleQueueService.TooManyEntriesInBatchRequest

The batch request contains more entries than permissible.

HTTP Status Code: 400

AWS.SimpleQueueService.UnsupportedOperation

Error code 400. Unsupported operation.

HTTP Status Code: 400

Examples

Example

The following example `SendMessageBatch` request sends two messages to the queue. You must URL-encode the entire URL. However, in this example only the message body is URL-encoded to make the example easier to read. The structure of `AUTHPARAMS` depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/
```

```
?Action=SendMessageBatch
&SendMessageBatchRequestEntry.1.Id=test_msg_001
&SendMessageBatchRequestEntry.1.MessageBody=test%20message%20body%201
&SendMessageBatchRequestEntry.2.Id=test_msg_002
&SendMessageBatchRequestEntry.2.MessageBody=test%20message%20body%202
&SendMessageBatchRequestEntry.2.DelaySeconds=60
&SendMessageBatchRequestEntry.2.MessageAttribute.1.Name=test_attribute_name_1
&SendMessageBatchRequestEntry.2.MessageAttribute.1.Value.StringValue=test_attribute_value_1
&SendMessageBatchRequestEntry.2.MessageAttribute.1.Value.DataType=String
&Expires=2020-05-05T22%3A52%3A43PST
&Version=2012-11-05
&AUTHPARAMS
```

Sample Response

```
<SendMessageBatchResponse>
<SendMessageBatchResult>
  <SendMessageBatchResultEntry>
    <Id>test_msg_001</Id>
    <MessageId>0a5231c7-8bff-4955-be2e-8dc7c50a25fa</MessageId>
    <MD5OfMessageBody>0e024d309850c78cba5eabbef7cae71</MD5OfMessageBody>
  </SendMessageBatchResultEntry>
  <SendMessageBatchResultEntry>
    <Id>test_msg_002</Id>
    <MessageId>15ee1ed3-87e7-40c1-bdaa-2e49968ea7e9</MessageId>
    <MD5OfMessageBody>7fb8146a82f95e0af155278f406862c2</MD5OfMessageBody>
    <MD5OfMessageAttributes>295c5fa15a51aae6884d1d7c1d99ca50</MD5OfMessageAttributes>
  </SendMessageBatchResultEntry>
</SendMessageBatchResult>
<ResponseMetadata>
  <RequestId>ca1ad5d0-8271-408b-8d0f-1351bf547e74</RequestId>
</ResponseMetadata>
</SendMessageBatchResponse>
```

Example

The following example sends multiple messages with *message timers*—applying a visibility delay of variable length to the messages in the batch—by calling the `SendMessageBatch` action *without* a value for `DelaySeconds` for the first message and with the values of 45 seconds and 2 minutes for the second and third messages. (You can use `SendMessageBatch` to send up to 10 messages by assigning either identical or different values to each message (or by not assigning values at all).

Note

If you don't set a value for the `DelaySeconds` parameter, the message might still be subject to a delay if you add the message to a *delay queue*. For more information about using delay queues, see [Amazon SQS Delay Queues](#) in the *Amazon SQS Developer Guide*.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/
?Action=SendMessageBatch
&SendMessageBatchRequestEntry.1.Id=test_msg_no_message_timer
&SendMessageBatchRequestEntry.1.MessageBody=test%20message%20body%201
&SendMessageBatchRequestEntry.2.Id=test_msg_delay_45_seconds
&SendMessageBatchRequestEntry.2.MessageBody=test%20message%20body%202
&SendMessageBatchRequestEntry.2.DelaySeconds=45
&SendMessageBatchRequestEntry.3.Id=test_msg_delay_2_minutes
&SendMessageBatchRequestEntry.3.MessageBody=test%20message%20body%203
&SendMessageBatchRequestEntry.3.DelaySeconds=120
&Expires=2020-12-18T22%3A52%3A43PST
&Version=2012-11-05
```

&AUTHPARAMS

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

SetQueueAttributes

Sets the value of one or more queue attributes. When you change a queue's attributes, the change can take up to 60 seconds for most of the attributes to propagate throughout the Amazon SQS system. Changes made to the `MessageRetentionPeriod` attribute can take up to 15 minutes.

Note

- In the future, new attributes might be added. If you write code that calls this action, we recommend that you structure your code so that it can handle new attributes gracefully.
- Cross-account permissions don't apply to this action. For more information, see [Grant cross-account permissions to a role and a user name](#) in the *Amazon SQS Developer Guide*.
- To remove the ability to change queue permissions, you must deny permission to the `AddPermission`, `RemovePermission`, and `SetQueueAttributes` actions in your IAM policy.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 87).

Attribute , Attribute.N.Name (key), Attribute.N.Value (value)

A map of attributes to set.

The following lists the names, descriptions, and values of the special request parameters that the `SetQueueAttributes` action uses:

- `DelaySeconds` – The length of time, in seconds, for which the delivery of all messages in the queue is delayed. Valid values: An integer from 0 to 900 (15 minutes). Default: 0.
- `MaximumMessageSize` – The limit of how many bytes a message can contain before Amazon SQS rejects it. Valid values: An integer from 1,024 bytes (1 KiB) up to 262,144 bytes (256 KiB). Default: 262,144 (256 KiB).
- `MessageRetentionPeriod` – The length of time, in seconds, for which Amazon SQS retains a message. Valid values: An integer representing seconds, from 60 (1 minute) to 1,209,600 (14 days). Default: 345,600 (4 days).
- `Policy` – The queue's policy. A valid Amazon policy. For more information about policy structure, see [Overview of Amazon IAM Policies](#) in the *Amazon Identity and Access Management User Guide*.
- `ReceiveMessageWaitTimeSeconds` – The length of time, in seconds, for which a [ReceiveMessage](#) (p. 43) action waits for a message to arrive. Valid values: An integer from 0 to 20 (seconds). Default: 0.
- `VisibilityTimeout` – The visibility timeout for the queue, in seconds. Valid values: An integer from 0 to 43,200 (12 hours). Default: 30. For more information about the visibility timeout, see [Visibility Timeout](#) in the *Amazon SQS Developer Guide*.

The following attributes apply only to [dead-letter queues](#):

- `RedrivePolicy` – The string that includes the parameters for the dead-letter queue functionality of the source queue as a JSON object. The parameters are as follows:
 - `deadLetterTargetArn` – The Amazon Resource Name (ARN) of the dead-letter queue to which Amazon SQS moves messages after the value of `maxReceiveCount` is exceeded.
 - `maxReceiveCount` – The number of times a message is delivered to the source queue before being moved to the dead-letter queue. Default: 10. When the `ReceiveCount` for a message

exceeds the `maxReceiveCount` for a queue, Amazon SQS moves the message to the dead-letter-queue.

- `RedriveAllowPolicy` – The string that includes the parameters for the permissions for the dead-letter queue redrive permission and which source queues can specify dead-letter queues as a JSON object. The parameters are as follows:
 - `redrivePermission` – The permission type that defines which source queues can specify the current queue as the dead-letter queue. Valid values are:
 - `allowAll` – (Default) Any source queues in this Amazon account in the same Region can specify this queue as the dead-letter queue.
 - `denyAll` – No source queues can specify this queue as the dead-letter queue.
 - `byQueue` – Only queues specified by the `sourceQueueArns` parameter can specify this queue as the dead-letter queue.
 - `sourceQueueArns` – The Amazon Resource Names (ARN)s of the source queues that can specify this queue as the dead-letter queue and redrive messages. You can specify this parameter only when the `redrivePermission` parameter is set to `byQueue`. You can specify up to 10 source queue ARNs. To allow more than 10 source queues to specify dead-letter queues, set the `redrivePermission` parameter to `allowAll`.

Note

The dead-letter queue of a FIFO queue must also be a FIFO queue. Similarly, the dead-letter queue of a standard queue must also be a standard queue.

The following attributes apply only to [server-side-encryption](#):

- `KmsMasterKeyId` – The ID of an Amazon managed customer master key (CMK) for Amazon SQS or a custom CMK. For more information, see [Key Terms](#). While the alias of the AWS-managed CMK for Amazon SQS is always `alias/aws/sqs`, the alias of a custom CMK can, for example, be `alias/MyAlias`. For more examples, see [KeyId](#) in the *Amazon Key Management Service API Reference*.
- `KmsDataKeyReusePeriodSeconds` – The length of time, in seconds, for which Amazon SQS can reuse a [data key](#) to encrypt or decrypt messages before calling Amazon KMS again. An integer representing seconds, between 60 seconds (1 minute) and 86,400 seconds (24 hours). Default: 300 (5 minutes). A shorter time period provides better security but results in more calls to KMS which might incur charges after Free Tier. For more information, see [How Does the Data Key Reuse Period Work?](#).
- `SqsManagedSseEnabled` – Enables server-side queue encryption using SQS owned encryption keys. Only one server-side encryption option is supported per queue (e.g. [SSE-KMS](#) or [SSE-SQS](#)).

The following attribute applies only to [FIFO \(first-in-first-out\) queues](#):

- `ContentBasedDeduplication` – Enables content-based deduplication. For more information, see [Exactly-once processing](#) in the *Amazon SQS Developer Guide*. Note the following:
 - Every message must have a unique `MessageDeduplicationId`.
 - You may provide a `MessageDeduplicationId` explicitly.
 - If you aren't able to provide a `MessageDeduplicationId` and you enable `ContentBasedDeduplication` for your queue, Amazon SQS uses a SHA-256 hash to generate the `MessageDeduplicationId` using the body of the message (but not the attributes of the message).
 - If you don't provide a `MessageDeduplicationId` and the queue doesn't have `ContentBasedDeduplication` set, the action fails with an error.
 - If the queue has `ContentBasedDeduplication` set, your `MessageDeduplicationId` overrides the generated one.
 - When `ContentBasedDeduplication` is in effect, messages with identical content sent within the deduplication interval are treated as duplicates and only one copy of the message is delivered.

- If you send one message with `ContentBasedDeduplication` enabled and then another message with a `MessageDeduplicationId` that is the same as the one generated for the first `MessageDeduplicationId`, the two messages are treated as duplicates and only one copy of the message is delivered.

The following attributes apply only to [high throughput for FIFO queues](#):

- `DeduplicationScope` – Specifies whether message deduplication occurs at the message group or queue level. Valid values are `messageGroup` and `queue`.
- `FifoThroughputLimit` – Specifies whether the FIFO queue throughput quota applies to the entire queue or per message group. Valid values are `perQueue` and `perMessageGroupId`. The `perMessageGroupId` value is allowed only when the value for `DeduplicationScope` is `messageGroup`.

To enable high throughput for FIFO queues, do the following:

- Set `DeduplicationScope` to `messageGroup`.
- Set `FifoThroughputLimit` to `perMessageGroupId`.

If you set these attributes to anything other than the values shown for enabling high throughput, normal throughput is in effect and deduplication occurs as specified.

For information on throughput quotas, see [Quotas related to messages](#) in the *Amazon SQS Developer Guide*.

Type: String to string map

Valid Keys: `All` | `Policy` | `VisibilityTimeout` | `MaximumMessageSize` | `MessageRetentionPeriod` | `ApproximateNumberOfMessages` | `ApproximateNumberOfMessagesNotVisible` | `CreatedTimestamp` | `LastModifiedTimestamp` | `QueueArn` | `ApproximateNumberOfMessagesDelayed` | `DelaySeconds` | `ReceiveMessageWaitTimeSeconds` | `RedrivePolicy` | `FifoQueue` | `ContentBasedDeduplication` | `KmsMasterKeyId` | `KmsDataKeyReusePeriodSeconds` | `DeduplicationScope` | `FifoThroughputLimit` | `RedriveAllowPolicy` | `SqsManagedSseEnabled`

Required: Yes

QueueUrl

The URL of the Amazon SQS queue whose attributes are set.

Queue URLs and names are case-sensitive.

Type: String

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 89\)](#).

InvalidAttributeName

The specified attribute doesn't exist.

HTTP Status Code: 400

Examples

Example

The following example query request sets a policy that gives all users [ReceiveMessage \(p. 43\)](#) permission for a queue named `MyQueue`. For more examples of policies, see [Custom Amazon SQS Access Policy Language Examples](#) in the *Amazon SQS Developer Guide*. The structure of `AUTHPARAMS` depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/  
?Action=SetQueueAttributes  
&Attribute.Name=Policy  
&Attribute.Value=%7B%22Version%22%3A%222012-11-05%22%2C%22Id%22  
%3A%222F123456789012%2FMyQueue%2FSQSDefaultPolicy%22%2C%22Stat  
ement%22%3A%5B%7B%22Sid%22%3A%22Queue1ReceiveMessage%22%2C%22Effe  
ct%22%3A%22Allow%22%2C%22Principal%22%3A%7B%22AWS%22%3A%22*%22%7D  
%2C%22Action%22%3A%22SQS%3AReceiveMessage%22%2C%22Resource%22%3A%  
22arn%3Aaws%3Aaws%3Asqs%3Aus%2Deast%2D1%3A123456789012%3Atest  
Queue%22%7D%5D%7D  
&Timestamp=2015-12-06T16%3A57%3A31.000Z  
&Version=2012-11-05  
&AUTHPARAMS
```

Example

The following example query request sets the visibility timeout to 35 seconds for a queue named `MyQueue`. The structure of `AUTHPARAMS` depends on the signature of the API request. For more information, see [Examples of Signed Signature Version 4 Requests](#) in the *Amazon General Reference*.

Note

An Amazon SQS message has three basic states:

1. Sent to a queue by a producer.
2. Received from the queue by a consumer.
3. Deleted from the queue.

A message is considered to be *stored* after it is sent to a queue by a producer, but not yet received from the queue by a consumer (that is, between states 1 and 2). There is no limit to the number of stored messages. A message is considered to be *in flight* after it is received from a queue by a consumer, but not yet deleted from the queue (that is, between states 2 and 3). There is a limit to the number of in flight messages.

Limits that apply to in flight messages are unrelated to the *unlimited* number of stored messages.

For most standard queues (depending on queue traffic and message backlog), there can be a maximum of approximately 120,000 in flight messages (received from a queue by a consumer, but not yet deleted from the queue). If you reach this limit, Amazon SQS returns the `OverLimit` error message. To avoid reaching the limit, you should delete messages from the queue after they're processed. You can also increase the number of queues you use to process your messages. To request a limit increase, [file a support request](#).

For FIFO queues, there can be a maximum of 20,000 in flight messages (received from a queue by a consumer, but not yet deleted from the queue). If you reach this limit, Amazon SQS returns no error messages.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/  
?Action=SetQueueAttributes  
&Attribute.Name=VisibilityTimeout  
&Attribute.Value=35  
&Expires=2020-04-18T22%3A52%3A43PST  
&Version=2012-11-05  
&AUTHPARAMS
```

Sample Response

```
<SetQueueAttributesResponse>  
  <ResponseMetadata>  
    <RequestId>e5cca473-4fc0-4198-a451-8abb94d02c75</RequestId>  
  </ResponseMetadata>  
</SetQueueAttributesResponse>
```

Example

The following example sets a queue named `MyDeadLetterQueue` as the dead-letter queue for a queue name `MySourceQueue` by calling the `SetQueueAttributes` action with the configuration details for the dead-letter queue.

Note

Queue URLs and names are case-sensitive.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MySourceQueue/  
?Action=SetQueueAttributes  
&Attribute.1.Value=%7B%22maxReceiveCount%22%3A%225%22%2C+%22deadLetterTargetArn%22%3A%22arn%3Aaws%3Asqs%3Aus-east-2%3A123456789012%3AMyDeadLetterQueue%22%7D  
&Attribute.1.Name=RedrivePolicy  
&Version=2012-11-05
```

Sample Response

```
<SetQueueAttributesResponse xmlns="https://queue.amazonaws.com/doc/2012-11-05/">  
  <ResponseMetadata>  
    <RequestId>40945605-b328-53b5-aed4-1cc24a7240e8</RequestId>  
  </ResponseMetadata>  
</SetQueueAttributesResponse>
```

Example

The following example enables long polling by calling the `SetQueueAttributes` action with the `ReceiveMessageWaitTimeSeconds` parameter set to 20 seconds.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/  
?Action=SetQueueAttributes  
&Attribute.Name=ReceiveMessageWaitTimeSeconds  
&Attribute.Value=20  
&Expires=2020-04-18T22%3A52%3A43PST
```

```
&Version=2012-11-05  
&AUTHPARAMS
```

Example

The following example changes an existing queue into a delay queue by calling the `SetQueueAttributes` action with the `DelaySeconds` attribute set to 45 seconds. Changing the `DelaySeconds` attribute from its default value of 0 to a positive integer less than or equal to 900 changes the queue into a delay queue.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/  
?Action=SetQueueAttributes  
&DelaySeconds=45  
&Expires=2020-12-20T22%3A52%3A43PST  
&Version=2012-11-05  
&AUTHPARAMS
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

TagQueue

Add cost allocation tags to the specified Amazon SQS queue. For an overview, see [Tagging Your Amazon SQS Queues](#) in the *Amazon SQS Developer Guide*.

When you use queue tags, keep the following guidelines in mind:

- Adding more than 50 tags to a queue isn't recommended.
- Tags don't have any semantic meaning. Amazon SQS interprets tags as character strings.
- Tags are case-sensitive.
- A new tag with a key identical to that of an existing tag overwrites the existing tag.

For a full list of tag restrictions, see [Quotas related to queues](#) in the *Amazon SQS Developer Guide*.

Note

Cross-account permissions don't apply to this action. For more information, see [Grant cross-account permissions to a role and a user name](#) in the *Amazon SQS Developer Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 87\)](#).

QueueUrl

The URL of the queue.

Type: String

Required: Yes

Tag , Tag.N.Key (key), Tag.N.Value (value)

The list of tags to be added to the specified queue.

Type: String to string map

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 89\)](#).

Examples

Example

This example illustrates one usage of TagQueue.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/  
?Action=TagQueue  
&Tag.Key=QueueType
```

```
&Tag.Value=Production
&Expires=2020-10-18T22%3A52%3A43PST
&Version=2012-11-05
&AUTHPARAMS
```

Sample Response

```
<TagQueueResponse>
  <ResponseMetadata>
    <RequestId>a1b2c3d4-e567-8901-23f4-g5678901hi23</RequestId>
  </ResponseMetadata>
</TagQueueResponse>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UntagQueue

Remove cost allocation tags from the specified Amazon SQS queue. For an overview, see [Tagging Your Amazon SQS Queues](#) in the *Amazon SQS Developer Guide*.

Note

Cross-account permissions don't apply to this action. For more information, see [Grant cross-account permissions to a role and a user name](#) in the *Amazon SQS Developer Guide*.

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 87).

QueueUrl

The URL of the queue.

Type: String

Required: Yes

TagKey.N

The list of tags to be removed from the specified queue.

Type: Array of strings

Required: Yes

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 89).

Examples

Example

This example illustrates one usage of UntagQueue.

Sample Request

```
https://sqs.us-east-2.amazonaws.com/123456789012/MyQueue/  
?Action=UntagQueue  
&TagKey=QueueType  
&Expires=2020-10-18T22%3A52%3A43PST  
&Version=2012-11-05  
&AUTHPARAMS
```

Sample Response

```
<UntagQueueResponse>  
  <ResponseMetadata>  
    <RequestId>a1b2c3d4-e567-8901-23f4-g5678901hi23</RequestId>  
  </ResponseMetadata>
```

`</UntagQueueResponse>`

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

Data Types

The Amazon Simple Queue Service API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [BatchResultErrorEntry](#) (p. 71)
- [ChangeMessageVisibilityBatchRequestEntry](#) (p. 72)
- [ChangeMessageVisibilityBatchResultEntry](#) (p. 73)
- [DeleteMessageBatchRequestEntry](#) (p. 74)
- [DeleteMessageBatchResultEntry](#) (p. 75)
- [Message](#) (p. 76)
- [MessageAttributeValue](#) (p. 78)
- [MessageSystemAttributeValue](#) (p. 80)
- [SendMessageBatchRequestEntry](#) (p. 82)
- [SendMessageBatchResultEntry](#) (p. 85)

BatchResultErrorEntry

Gives a detailed description of the result of an action on each entry in the request.

Contents

Code

An error code representing why the action failed on this entry.

Type: String

Required: Yes

Id

The Id of an entry in a batch request.

Type: String

Required: Yes

Message

A message explaining why the action failed on this entry.

Type: String

Required: No

SenderFault

Specifies whether the error happened due to the caller of the batch API action.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ChangeMessageVisibilityBatchRequestEntry

Encloses a receipt handle and an entry id for each message in [ChangeMessageVisibilityBatch](#) (p. 9).

Important

All of the following list parameters must be prefixed with `ChangeMessageVisibilityBatchRequestEntry.n`, where `n` is an integer value starting with 1. For example, a parameter list for this action might look like this:

```
&ChangeMessageVisibilityBatchRequestEntry.1.Id=change_visibility_msg_2
```

```
&ChangeMessageVisibilityBatchRequestEntry.1.ReceiptHandle=your_receipt_handle
```

```
&ChangeMessageVisibilityBatchRequestEntry.1.VisibilityTimeout=45
```

Contents

Id

An identifier for this particular receipt handle used to communicate the result.

Note

The Ids of a batch request need to be unique within a request. This identifier can have up to 80 characters. The following characters are accepted: alphanumeric characters, hyphens(-), and underscores (_).

Type: String

Required: Yes

ReceiptHandle

A receipt handle.

Type: String

Required: Yes

VisibilityTimeout

The new value (in seconds) for the message's visibility timeout.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ChangeMessageVisibilityBatchResultEntry

Encloses the Id of an entry in [ChangeMessageVisibilityBatch](#) (p. 9).

Contents

Id

Represents a message whose visibility timeout has been changed successfully.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DeleteMessageBatchRequestEntry

Encloses a receipt handle and an identifier for it.

Contents

Id

An identifier for this particular receipt handle. This is used to communicate the result.

Note

The Ids of a batch request need to be unique within a request.

This identifier can have up to 80 characters. The following characters are accepted: alphanumeric characters, hyphens(-), and underscores (_).

Type: String

Required: Yes

ReceiptHandle

A receipt handle.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DeleteMessageBatchResultEntry

Encloses the Id of an entry in [DeleteMessageBatch](#) (p. 20).

Contents

Id

Represents a successfully deleted message.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Message

An Amazon SQS message.

Contents

Attribute , Attribute.N.Name (key) , Attribute.N.Value (value)

A map of the attributes requested in [ReceiveMessage \(p. 43\)](#) to their respective values.

Supported attributes:

- `ApproximateReceiveCount`
- `ApproximateFirstReceiveTimestamp`
- `MessageDeduplicationId`
- `MessageGroupId`
- `SenderId`
- `SentTimestamp`
- `SequenceNumber`

`ApproximateFirstReceiveTimestamp` and `SentTimestamp` are each returned as an integer representing the [epoch time](#) in milliseconds.

Type: String to string map

Valid Keys: `SenderId` | `SentTimestamp` | `ApproximateReceiveCount` | `ApproximateFirstReceiveTimestamp` | `SequenceNumber` | `MessageDeduplicationId` | `MessageGroupId` | `AWSTraceHeader`

Required: No

Body

The message's contents (not URL-encoded).

Type: String

Required: No

MD5OfBody

An MD5 digest of the non-URL-encoded message body string.

Type: String

Required: No

MD5OfMessageAttributes

An MD5 digest of the non-URL-encoded message attribute string. You can use this attribute to verify that Amazon SQS received the message correctly. Amazon SQS URL-decodes the message before creating the MD5 digest. For information about MD5, see [RFC1321](#).

Type: String

Required: No

MessageAttribute , MessageAttribute.N.Name (key) , MessageAttribute.N.Value (value)

Each message attribute consists of a `Name`, `Type`, and `Value`. For more information, see [Amazon SQS message attributes](#) in the *Amazon SQS Developer Guide*.

Type: String to [MessageAttributeValue \(p. 78\)](#) object map

Required: No

MessageId

A unique identifier for the message. A `MessageId` is considered unique across all Amazon Web Services accounts for an extended period of time.

Type: String

Required: No

ReceiptHandle

An identifier associated with the act of receiving the message. A new receipt handle is returned every time you receive a message. When deleting a message, you provide the last received receipt handle to delete the message.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

MessageAttributeValue

The user-specified message attribute value. For string data types, the `Value` attribute has the same restrictions on the content as the message body. For more information, see [SendMessage \(p. 51\)](#).

`Name`, `type`, `value` and the message body must not be empty or null. All parts of the message attribute, including `Name`, `Type`, and `Value`, are part of the message size restriction (256 KB or 262,144 bytes).

Contents

BinaryListValue.N

Not implemented. Reserved for future use.

Type: Array of Base64-encoded binary data objects

Required: No

BinaryValue

Binary type attributes can store any binary data, such as compressed data, encrypted data, or images.

Type: Base64-encoded binary data object

Required: No

DataType

Amazon SQS supports the following logical data types: `String`, `Number`, and `Binary`. For the `Number` data type, you must use `StringValue`.

You can also append custom labels. For more information, see [Amazon SQS Message Attributes](#) in the *Amazon SQS Developer Guide*.

Type: String

Required: Yes

StringListValue.N

Not implemented. Reserved for future use.

Type: Array of strings

Required: No

StringValue

Strings are Unicode with UTF-8 binary encoding. For a list of code values, see [ASCII Printable Characters](#).

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

MessageSystemAttributeValue

The user-specified message system attribute value. For string data types, the `value` attribute has the same restrictions on the content as the message body. For more information, see [SendMessage \(p. 51\)](#).

`Name`, `type`, `value` and the message body must not be empty or null.

Contents

BinaryListValue.N

Not implemented. Reserved for future use.

Type: Array of Base64-encoded binary data objects

Required: No

BinaryValue

Binary type attributes can store any binary data, such as compressed data, encrypted data, or images.

Type: Base64-encoded binary data object

Required: No

DataType

Amazon SQS supports the following logical data types: `String`, `Number`, and `Binary`. For the `Number` data type, you must use `StringValue`.

You can also append custom labels. For more information, see [Amazon SQS Message Attributes](#) in the *Amazon SQS Developer Guide*.

Type: String

Required: Yes

StringListValue.N

Not implemented. Reserved for future use.

Type: Array of strings

Required: No

StringValue

Strings are Unicode with UTF-8 binary encoding. For a list of code values, see [ASCII Printable Characters](#).

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SendMessageBatchRequestEntry

Contains the details of a single Amazon SQS message along with an `Id`.

Contents

DelaySeconds

The length of time, in seconds, for which a specific message is delayed. Valid values: 0 to 900. Maximum: 15 minutes. Messages with a positive `DelaySeconds` value become available for processing after the delay period is finished. If you don't specify a value, the default value for the queue is applied.

Note

When you set `FifoQueue`, you can't set `DelaySeconds` per message. You can set this parameter only on a queue level.

Type: Integer

Required: No

Id

An identifier for a message in this batch used to communicate the result.

Note

The `Ids` of a batch request need to be unique within a request. This identifier can have up to 80 characters. The following characters are accepted: alphanumeric characters, hyphens(-), and underscores (_).

Type: String

Required: Yes

MessageAttribute , `MessageAttribute.N.Name` (key) , `MessageAttribute.N.Value` (value)

Each message attribute consists of a `Name`, `Type`, and `Value`. For more information, see [Amazon SQS message attributes](#) in the *Amazon SQS Developer Guide*.

Type: String to [MessageAttributeValue](#) (p. 78) object map

Required: No

MessageBody

The body of the message.

Type: String

Required: Yes

MessageDeduplicationId

This parameter applies only to FIFO (first-in-first-out) queues.

The token used for deduplication of messages within a 5-minute minimum deduplication interval. If a message with a particular `MessageDeduplicationId` is sent successfully, subsequent messages with the same `MessageDeduplicationId` are accepted successfully but aren't delivered. For more information, see [Exactly-once processing](#) in the *Amazon SQS Developer Guide*.

- Every message must have a unique `MessageDeduplicationId`,
 - You may provide a `MessageDeduplicationId` explicitly.

- If you aren't able to provide a `MessageDeduplicationId` and you enable `ContentBasedDeduplication` for your queue, Amazon SQS uses a SHA-256 hash to generate the `MessageDeduplicationId` using the body of the message (but not the attributes of the message).
- If you don't provide a `MessageDeduplicationId` and the queue doesn't have `ContentBasedDeduplication` set, the action fails with an error.
- If the queue has `ContentBasedDeduplication` set, your `MessageDeduplicationId` overrides the generated one.
- When `ContentBasedDeduplication` is in effect, messages with identical content sent within the deduplication interval are treated as duplicates and only one copy of the message is delivered.
- If you send one message with `ContentBasedDeduplication` enabled and then another message with a `MessageDeduplicationId` that is the same as the one generated for the first `MessageDeduplicationId`, the two messages are treated as duplicates and only one copy of the message is delivered.

Note

The `MessageDeduplicationId` is available to the consumer of the message (this can be useful for troubleshooting delivery issues).
If a message is sent successfully but the acknowledgement is lost and the message is resent with the same `MessageDeduplicationId` after the deduplication interval, Amazon SQS can't detect duplicate messages.
Amazon SQS continues to keep track of the message deduplication ID even after the message is received and deleted.

The length of `MessageDeduplicationId` is 128 characters. `MessageDeduplicationId` can contain alphanumeric characters (a-z, A-Z, 0-9) and punctuation (!"#\$%&'()*+,-./:;<=>?@[\\]^_`{|}~).

For best practices of using `MessageDeduplicationId`, see [Using the MessageDeduplicationId Property](#) in the *Amazon SQS Developer Guide*.

Type: String

Required: No

MessageGroupId

This parameter applies only to FIFO (first-in-first-out) queues.

The tag that specifies that a message belongs to a specific message group. Messages that belong to the same message group are processed in a FIFO manner (however, messages in different message groups might be processed out of order). To interleave multiple ordered streams within a single queue, use `MessageGroupId` values (for example, session data for multiple users). In this scenario, multiple consumers can process the queue, but the session data of each user is processed in a FIFO fashion.

- You must associate a non-empty `MessageGroupId` with a message. If you don't provide a `MessageGroupId`, the action fails.
- `ReceiveMessage` might return messages with multiple `MessageGroupId` values. For each `MessageGroupId`, the messages are sorted by time sent. The caller can't specify a `MessageGroupId`.

The length of `MessageGroupId` is 128 characters. Valid values: alphanumeric characters and punctuation (!"#\$%&'()*+,-./:;<=>?@[\\]^_`{|}~).

For best practices of using `MessageGroupId`, see [Using the MessageGroupId Property](#) in the *Amazon SQS Developer Guide*.

Important

`MessageGroupId` is required for FIFO queues. You can't use it for Standard queues.

Type: String

Required: No

MessageSystemAttribute , MessageSystemAttribute.N.Name (key) , MessageSystemAttribute.N.Value (value)

The message system attribute to send Each message system attribute consists of a Name, Type, and Value.

Important

- Currently, the only supported message system attribute is `AWSTraceHeader`. Its type must be `String` and its value must be a correctly formatted Amazon X-Ray trace header string.
- The size of a message system attribute doesn't count towards the total size of a message.

Type: String to [MessageSystemAttributeValue](#) (p. 80) object map

Valid Keys: `AWSTraceHeader`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SendMessageBatchResultEntry

Encloses a `MessageId` for a successfully-enqueued message in a [SendMessageBatch](#) (p. 56).

Contents

Id

An identifier for the message in this batch.

Type: String

Required: Yes

MD5OfMessageAttributes

An MD5 digest of the non-URL-encoded message attribute string. You can use this attribute to verify that Amazon SQS received the message correctly. Amazon SQS URL-decodes the message before creating the MD5 digest. For information about MD5, see [RFC1321](#).

Type: String

Required: No

MD5OfMessageBody

An MD5 digest of the non-URL-encoded message body string. You can use this attribute to verify that Amazon SQS received the message correctly. Amazon SQS URL-decodes the message before creating the MD5 digest. For information about MD5, see [RFC1321](#).

Type: String

Required: Yes

MD5OfMessageSystemAttributes

An MD5 digest of the non-URL-encoded message system attribute string. You can use this attribute to verify that Amazon SQS received the message correctly. Amazon SQS URL-decodes the message before creating the MD5 digest. For information about MD5, see [RFC1321](#).

Type: String

Required: No

MessageId

An identifier for the message.

Type: String

Required: Yes

SequenceNumber

This parameter applies only to FIFO (first-in-first-out) queues.

The large, non-consecutive number that Amazon SQS assigns to each message.

The length of `SequenceNumber` is 128 bits. As `SequenceNumber` continues to increase for a particular `MessageGroupId`.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signature Version 4 Signing Process](#) in the *Amazon Web Services General Reference*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: `AWS4-HMAC-SHA256`

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: `access_key/YYYYMMDD/region/service/aws4_request`.

For more information, see [Task 2: Create a String to Sign for Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'THHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: `20120325T120000Z`.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is

not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Handling Dates in Signature Version 4](#) in the *Amazon Web Services General Reference*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to Amazon Security Token Service (Amazon STS). For a list of services that support temporary security credentials from Amazon Security Token Service, go to [Amazon Services That Work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from the Amazon Security Token Service, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Task 1: Create a Canonical Request For Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all Amazon services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to Amazon standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or Amazon access key ID provided does not exist in our records.

HTTP Status Code: 403

InvalidParameterCombination

Parameters that must not be used together were used together.

HTTP Status Code: 400

InvalidParameterValue

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

InvalidQueryParameter

The Amazon query string is malformed or does not adhere to Amazon standards.

HTTP Status Code: 400

MalformedQueryString

The query string contains a syntax error.

HTTP Status Code: 404

MissingAction

The request is missing an action or a required parameter.

HTTP Status Code: 400

MissingAuthenticationToken

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 403

MissingParameter

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The Amazon access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 403

ValidationError

The input fails to satisfy the constraints specified by an Amazon service.

HTTP Status Code: 400