亚马逊云科技

API Reference

Amazon MSK Connect



API Version 2021-09-14

Amazon MSK Connect: API Reference

Table of Contents

Welcome **1**
Actions **2**
CreateConnector 3
Request Syntax 3
URI Request Parameters 5
Request Body 5
Response Syntax 8
Response Elements 8
Errors 9
See Also 10
CreateCustomPlugin 11
Request Syntax 11
URI Request Parameters 11
Request Body 11
Response Syntax 12
Response Elements 13
Errors 13
See Also 15
CreateWorkerConfiguration 16
Request Syntax 16
URI Request Parameters 16
Request Body 16
Response Syntax 17
Response Elements 17
Errors 18
See Also 20
DeleteConnector 21
Request Syntax 21
URI Request Parameters 21
Request Body 21
Response Syntax 21
Response Elements 21
Errors 22
See Also 23

DeleteCustomPlugin ... 24
Request Syntax ... 24
URI Request Parameters ... 24
Request Body ... 24
Response Syntax ... 24
Response Elements ... 24
Errors ... 25
See Also ... 26
DeleteWorkerConfiguration ... 27
Request Syntax ... 27
URI Request Parameters ... 27
Request Body ... 27
Response Syntax ... 27
Response Elements ... 27
Errors ... 28
See Also ... 29
DescribeConnector ... 30
Request Syntax ... 30
URI Request Parameters ... 30
Request Body ... 30
Response Syntax ... 30
Response Elements ... 32
Errors ... 35
See Also ... 36
DescribeConnectorOperation ... 37
Request Syntax ... 37
URI Request Parameters ... 37
Request Body ... 37
Response Syntax ... 37
Response Elements ... 39
Errors ... 41
See Also ... 42
DescribeCustomPlugin ... 43
Request Syntax ... 43
URI Request Parameters ... 43
Request Body ... 43

Response Syntax ... 43
Response Elements ... 44
Errors ... 45
See Also ... 46
DescribeWorkerConfiguration ... 48
Request Syntax ... 48
URI Request Parameters ... 48
Request Body ... 48
Response Syntax ... 48
Response Elements ... 49
Errors ... 50
See Also ... 51
ListConnectorOperations ... 52
Request Syntax ... 52
URI Request Parameters ... 52
Request Body ... 52
Response Syntax ... 52
Response Elements ... 53
Errors ... 53
See Also ... 54
ListConnectors ... 56
Request Syntax ... 56
URI Request Parameters ... 56
Request Body ... 56
Response Syntax ... 56
Response Elements ... 58
Errors ... 59
See Also ... 60
ListCustomPlugins ... 61
Request Syntax ... 61
URI Request Parameters ... 61
Request Body ... 61
Response Syntax ... 61
Response Elements ... 62
Errors ... 63
See Also ... 64

ListTagsForResource ... 65
Request Syntax ... 65
URI Request Parameters ... 65
Request Body ... 65
Response Syntax ... 65
Response Elements ... 65
Errors ... 66
See Also ... 67
ListWorkerConfigurations ... 68
Request Syntax ... 68
URI Request Parameters ... 68
Request Body ... 68
Response Syntax ... 68
Response Elements ... 69
Errors ... 69
See Also ... 70
PauseConnector ... 72
Request Syntax ... 72
URI Request Parameters ... 72
Request Body ... 72
Response Syntax ... 72
Response Elements ... 72
Errors ... 73
See Also ... 74
RestartConnector ... 75
Request Syntax ... 75
URI Request Parameters ... 75
Request Body ... 75
Response Syntax ... 75
Response Elements ... 76
Errors ... 76
See Also ... 77
ResumeConnector ... 78
Request Syntax ... 78
URI Request Parameters ... 78
Request Body ... 78

Response Syntax ... 78
Response Elements ... 78
Errors ... 79
See Also ... 80
TagResource ... 81
Request Syntax ... 81
URI Request Parameters ... 81
Request Body ... 81
Response Syntax ... 82
Response Elements ... 82
Errors ... 82
See Also ... 83
UntagResource ... 84
Request Syntax ... 84
URI Request Parameters ... 84
Request Body ... 84
Response Syntax ... 84
Response Elements ... 84
Errors ... 85
See Also ... 86
UpdateConnector ... 87
Request Syntax ... 87
URI Request Parameters ... 87
Request Body ... 88
Response Syntax ... 88
Response Elements ... 89
Errors ... 89
See Also ... 90
Data Types ... 92
ApacheKafkaCluster ... 95
Contents ... 95
See Also ... 95
ApacheKafkaClusterDescription ... 96
Contents ... 96
See Also ... 96
AutoScaling ... 97

Contents 97
See Also 98
AutoScalingDescription 99
Contents 99
See Also 100
AutoScalingUpdate 101
Contents 101
See Also 102
Capacity 103
Contents 103
See Also 103
CapacityDescription 104
Contents 104
See Also 104
CapacityUpdate 105
Contents 105
See Also 105
CloudWatchLogsLogDelivery 106
Contents 106
See Also 106
CloudWatchLogsLogDeliveryDescription 107
Contents 107
See Also 107
ConnectorOperationStep 108
Contents 108
See Also 108
ConnectorOperationSummary 109
Contents 109
See Also 110
ConnectorSummary 111
Contents 111
See Also 114
CustomPlugin 115
Contents 115
See Also 115
CustomPluginDescription 116

Contents ... 116
See Also ... 116
CustomPluginFileDescription ... 117
Contents ... 117
See Also ... 117
CustomPluginLocation ... 118
Contents ... 118
See Also ... 118
CustomPluginLocationDescription ... 119
Contents ... 119
See Also ... 119
CustomPluginRevisionSummary ... 120
Contents ... 120
See Also ... 121
CustomPluginSummary ... 122
Contents ... 122
See Also ... 123
FirehoseLogDelivery ... 124
Contents ... 124
See Also ... 124
FirehoseLogDeliveryDescription ... 125
Contents ... 125
See Also ... 125
KafkaCluster ... 126
Contents ... 126
See Also ... 126
KafkaClusterClientAuthentication ... 127
Contents ... 127
See Also ... 127
KafkaClusterClientAuthenticationDescription ... 128
Contents ... 128
See Also ... 128
KafkaClusterDescription ... 129
Contents ... 129
See Also ... 129
KafkaClusterEncryptionInTransit ... 130

Contents 130
See Also 130
KafkaClusterEncryptionInTransitDescription 131
Contents 131
See Also 131
LogDelivery 132
Contents 132
See Also 132
LogDeliveryDescription 133
Contents 133
See Also 133
Plugin 134
Contents 134
See Also 134
PluginDescription 135
Contents 135
See Also 135
ProvisionedCapacity 136
Contents 136
See Also 136
ProvisionedCapacityDescription 137
Contents 137
See Also 137
ProvisionedCapacityUpdate 138
Contents 138
See Also 138
S3Location 139
Contents 139
See Also 139
S3LocationDescription 140
Contents 140
See Also 140
S3LogDelivery 141
Contents 141
See Also 141
S3LogDeliveryDescription 142

Contents 142
See Also 142
ScaleInPolicy 143
Contents 143
See Also 143
ScaleInPolicyDescription 144
Contents 144
See Also 144
ScaleInPolicyUpdate 145
Contents 145
See Also 145
ScaleOutPolicy 146
Contents 146
See Also 146
ScaleOutPolicyDescription 147
Contents 147
See Also 147
ScaleOutPolicyUpdate 148
Contents 148
See Also 148
StateDescription 149
Contents 149
See Also 149
Vpc 150
Contents 150
See Also 150
VpcDescription 151
Contents 151
See Also 151
WorkerConfiguration 152
Contents 152
See Also 152
WorkerConfigurationDescription 153
Contents 153
See Also 153
WorkerConfigurationRevisionDescription 154

Contents 154
See Also 154
WorkerConfigurationRevisionSummary 156
Contents 156
See Also 156
WorkerConfigurationSummary 157
Contents 157
See Also 158
WorkerLogDelivery 159
Contents 159
See Also 159
WorkerLogDeliveryDescription 160
Contents 160
See Also 160
WorkerSetting 161
Contents 161
See Also 161
Common Parameters 162
Common Error Types 165

Welcome

This document was last published on November 19, 2026.

Actions

The following actions are supported:

- CreateConnector
- CreateCustomPlugin
- CreateWorkerConfiguration
- DeleteConnector
- DeleteCustomPlugin
- DeleteWorkerConfiguration
- DescribeConnector
- DescribeConnectorOperation
- DescribeCustomPlugin
- DescribeWorkerConfiguration
- ListConnectorOperations
- ListConnectors
- ListCustomPlugins
- ListTagsForResource
- ListWorkerConfigurations
- PauseConnector
- RestartConnector
- ResumeConnector
- TagResource
- UntagResource
- UpdateConnector

CreateConnector

Creates a connector using the specified properties.

Request Syntax

```
POST /v1/connectors HTTP/1.1
Content-type: application/json

{
   "capacity": {
      "autoScaling": {
         "maxAutoscalingTaskCount": number,
         "maxWorkerCount": number,
         "mcuCount": number,
         "minWorkerCount": number,
         "scaleInPolicy": {
            "cpuUtilizationPercentage": number
         },
         "scaleOutPolicy": {
            "cpuUtilizationPercentage": number
         }
      },
      "provisionedCapacity": {
         "mcuCount": number,
         "workerCount": number
      }
   },
   "connectorConfiguration": {
      "string" : "string"
   },
   "connectorDescription": "string",
   "connectorName": "string",
   "kafkaCluster": {
      "apacheKafkaCluster": {
         "bootstrapServers": "string",
         "vpc": {
            "securityGroups": [ "string" ],
            "subnets": [ "string" ]
         }
      }
   },
   "kafkaClusterClientAuthentication": {
```

```
      "authenticationType": "string"
   },
   "kafkaClusterEncryptionInTransit": {
      "encryptionType": "string"
   },
   "kafkaConnectVersion": "string",
   "logDelivery": {
      "workerLogDelivery": {
         "cloudWatchLogs": {
            "enabled": boolean,
            "logGroup": "string"
         },
         "firehose": {
            "deliveryStream": "string",
            "enabled": boolean
         },
         "s3": {
            "bucket": "string",
            "enabled": boolean,
            "prefix": "string"
         }
      }
   },
   "networkType": "string",
   "plugins": [
      {
         "customPlugin": {
            "customPluginArn": "string",
            "revision": number
         }
      }
   ],
   "serviceExecutionRoleArn": "string",
   "tags": {
      "string" : "string"
   },
   "workerConfiguration": {
      "revision": number,
      "workerConfigurationArn": "string"
   }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

capacity

Information about the capacity allocated to the connector. Exactly one of the two properties must be specified.

Type: Capacity object

Required: Yes

connectorConfiguration

A map of keys to values that represent the configuration for the connector.

Type: String to string map

Required: Yes

connectorDescription

A summary description of the connector.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

connectorName

The name of the connector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

kafkaCluster

Specifies which Apache Kafka cluster to connect to.

Type: KafkaCluster object

Required: Yes

kafkaClusterClientAuthentication

Details of the client authentication used by the Apache Kafka cluster.

Type: KafkaClusterClientAuthentication object

Required: Yes

kafkaClusterEncryptionInTransit

Details of encryption in transit to the Apache Kafka cluster.

Type: KafkaClusterEncryptionInTransit object

Required: Yes

kafkaConnectVersion

The version of Kafka Connect. It has to be compatible with both the Apache Kafka cluster's version and the plugins.

Type: String

Required: Yes

logDelivery

Details about log delivery.

Type: LogDelivery object

Required: No

networkType

The network type of the connector. It gives connectors connectivity to either IPv4 (IPV4) or IPv4 and IPv6 (DUAL) destinations. Defaults to IPV4.

Type: String

Valid Values: `IPV4 | DUAL`

Required: No

plugins

> **Important**
>
> Amazon MSK Connect does not currently support specifying multiple plugins as a list. To use more than one plugin for your connector, you can create a single custom plugin using a ZIP file that bundles multiple plugins together.

Specifies which plugin to use for the connector. You must specify a single-element list containing one `customPlugin` object.

Type: Array of Plugin objects

Required: Yes

serviceExecutionRoleArn

The Amazon Resource Name (ARN) of the IAM role used by the connector to access the Amazon Web Services resources that it needs. The types of resources depends on the logic of the connector. For example, a connector that has Amazon S3 as a destination must have permissions that allow it to write to the S3 destination bucket.

Type: String

Required: Yes

tags

The tags you want to attach to the connector.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

workerConfiguration

Specifies which worker configuration to use with the connector.

Type: WorkerConfiguration object

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "connectorArn": "string",
   "connectorName": "string",
   "connectorState": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

connectorArn

The Amazon Resource Name (ARN) that Amazon assigned to the connector.

Type: String

connectorName

The name of the connector.

Type: String

connectorState

The state of the connector.

Type: String

Valid Values: `RUNNING | CREATING | UPDATING | DELETING | FAILED | PAUSED | RESTARTING | PAUSING | RESUMING`

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ConflictException

HTTP Status Code 409: Conflict. A resource with this name already exists. Retry your request with another name.

HTTP Status Code: 409

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

CreateCustomPlugin

Creates a custom plugin using the specified properties.

Request Syntax

```
POST /v1/custom-plugins HTTP/1.1
Content-type: application/json

{
   "contentType": "string",
   "description": "string",
   "location": {
      "s3Location": {
         "bucketArn": "string",
         "fileKey": "string",
         "objectVersion": "string"
      }
   },
   "name": "string",
   "tags": {
      "string" : "string"
   }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

contentType

The type of the plugin file.

Type: String

Valid Values: `JAR | ZIP`

Required: Yes

description

A summary description of the custom plugin.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

location

Information about the location of a custom plugin.

Type: CustomPluginLocation object

Required: Yes

name

The name of the custom plugin.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

tags

The tags you want to attach to the custom plugin.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
   "customPluginArn": "string",
   "customPluginState": "string",
   "name": "string",
   "revision": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

customPluginArn

The Amazon Resource Name (ARN) that Amazon assigned to the custom plugin.

Type: String

customPluginState

The state of the custom plugin.

Type: String

Valid Values: `CREATING | CREATE_FAILED | ACTIVE | UPDATING | UPDATE_FAILED | DELETING`

name

The name of the custom plugin.

Type: String

revision

The revision of the custom plugin.

Type: Long

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ConflictException

HTTP Status Code 409: Conflict. A resource with this name already exists. Retry your request with another name.

HTTP Status Code: 409

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

CreateWorkerConfiguration

Creates a worker configuration using the specified properties.

Request Syntax

```
POST /v1/worker-configurations HTTP/1.1
Content-type: application/json

{
   "description": "string",
   "name": "string",
   "propertiesFileContent": "string",
   "tags": {
      "string" : "string"
   }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

description

A summary description of the worker configuration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

name

The name of the worker configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

propertiesFileContent

Base64 encoded contents of connect-distributed.properties file.

Type: String

Required: Yes

tags

The tags you want to attach to the worker configuration.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "creationTime": "string",
   "latestRevision": {
      "creationTime": "string",
      "description": "string",
      "revision": number
   },
   "name": "string",
   "workerConfigurationArn": "string",
   "workerConfigurationState": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

creationTime

The time that the worker configuration was created.

Type: Timestamp

latestRevision

The latest revision of the worker configuration.

Type: WorkerConfigurationRevisionSummary object

name

The name of the worker configuration.

Type: String

workerConfigurationArn

The Amazon Resource Name (ARN) that Amazon assigned to the worker configuration.

Type: String

workerConfigurationState

The state of the worker configuration.

Type: String

Valid Values: `ACTIVE | DELETING`

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ConflictException

HTTP Status Code 409: Conflict. A resource with this name already exists. Retry your request with another name.

HTTP Status Code: 409

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

DeleteConnector

Deletes the specified connector.

Request Syntax

```
DELETE /v1/connectors/connectorArn?currentVersion=currentVersion HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

connectorArn

The Amazon Resource Name (ARN) of the connector that you want to delete.

Required: Yes

currentVersion

The current version of the connector that you want to delete.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "connectorArn": "string",
   "connectorState": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

connectorArn

The Amazon Resource Name (ARN) of the connector that you requested to delete.

Type: String

connectorState

The state of the connector that you requested to delete.

Type: String

Valid Values: `RUNNING | CREATING | UPDATING | DELETING | FAILED | PAUSED | RESTARTING | PAUSING | RESUMING`

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

DeleteCustomPlugin

Deletes a custom plugin.

Request Syntax

```
DELETE /v1/custom-plugins/customPluginArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

customPluginArn

The Amazon Resource Name (ARN) of the custom plugin that you want to delete.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "customPluginArn": "string",
   "customPluginState": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

customPluginArn

The Amazon Resource Name (ARN) of the custom plugin that you requested to delete.

Type: String

customPluginState

The state of the custom plugin.

Type: String

Valid Values: `CREATING | CREATE_FAILED | ACTIVE | UPDATING | UPDATE_FAILED | DELETING`

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

DeleteWorkerConfiguration

Deletes the specified worker configuration.

Request Syntax

```
DELETE /v1/worker-configurations/workerConfigurationArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

workerConfigurationArn

The Amazon Resource Name (ARN) of the worker configuration that you want to delete.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "workerConfigurationArn": "string",
   "workerConfigurationState": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

workerConfigurationArn

The Amazon Resource Name (ARN) of the worker configuration that you requested to delete.

Type: String

workerConfigurationState

The state of the worker configuration.

Type: String

Valid Values: `ACTIVE | DELETING`

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

DescribeConnector

Returns summary information about the connector.

Request Syntax

```
GET /v1/connectors/connectorArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

connectorArn

The Amazon Resource Name (ARN) of the connector that you want to describe.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "capacity": {
      "autoScaling": {
         "maxAutoscalingTaskCount": number,
         "maxWorkerCount": number,
         "mcuCount": number,
         "minWorkerCount": number,
         "scaleInPolicy": {
            "cpuUtilizationPercentage": number
         },
         "scaleOutPolicy": {
            "cpuUtilizationPercentage": number
         }
      },
```

```
      "provisionedCapacity": {
         "mcuCount": number,
         "workerCount": number
      }
   },
   "connectorArn": "string",
   "connectorConfiguration": {
      "string" : "string"
   },
   "connectorDescription": "string",
   "connectorName": "string",
   "connectorState": "string",
   "creationTime": "string",
   "currentVersion": "string",
   "kafkaCluster": {
      "apacheKafkaCluster": {
         "bootstrapServers": "string",
         "vpc": {
            "securityGroups": [ "string" ],
            "subnets": [ "string" ]
         }
      }
   },
   "kafkaClusterClientAuthentication": {
      "authenticationType": "string"
   },
   "kafkaClusterEncryptionInTransit": {
      "encryptionType": "string"
   },
   "kafkaConnectVersion": "string",
   "logDelivery": {
      "workerLogDelivery": {
         "cloudWatchLogs": {
            "enabled": boolean,
            "logGroup": "string"
         },
         "firehose": {
            "deliveryStream": "string",
            "enabled": boolean
         },
         "s3": {
            "bucket": "string",
            "enabled": boolean,
            "prefix": "string"
```

```
            }
         }
      },
      "networkType": "string",
      "plugins": [
         {
            "customPlugin": {
               "customPluginArn": "string",
               "revision": number
            }
         }
      ],
      "serviceExecutionRoleArn": "string",
      "stateDescription": {
         "code": "string",
         "message": "string"
      },
      "workerConfiguration": {
         "revision": number,
         "workerConfigurationArn": "string"
      }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

capacity

Information about the capacity of the connector, whether it is auto scaled or provisioned.

Type: CapacityDescription object

connectorArn

The Amazon Resource Name (ARN) of the connector.

Type: String

connectorConfiguration

A map of keys to values that represent the configuration for the connector.

Type: String to string map

connectorDescription

A summary description of the connector.

Type: String

connectorName

The name of the connector.

Type: String

connectorState

The state of the connector.

Type: String

Valid Values: `RUNNING | CREATING | UPDATING | DELETING | FAILED | PAUSED | RESTARTING | PAUSING | RESUMING`

creationTime

The time the connector was created.

Type: Timestamp

currentVersion

The current version of the connector.

Type: String

kafkaCluster

The Apache Kafka cluster that the connector is connected to.

Type: KafkaClusterDescription object

kafkaClusterClientAuthentication

The type of client authentication used to connect to the Apache Kafka cluster. The value is NONE when no client authentication is used.

Type: KafkaClusterClientAuthenticationDescription object

kafkaClusterEncryptionInTransit

Details of encryption in transit to the Apache Kafka cluster.

Type: KafkaClusterEncryptionInTransitDescription object

kafkaConnectVersion

The version of Kafka Connect. It has to be compatible with both the Apache Kafka cluster's version and the plugins.

Type: String

logDelivery

Details about delivering logs to Amazon CloudWatch Logs.

Type: LogDeliveryDescription object

networkType

The network type of the connector. It gives connectors connectivity to either IPv4 (IPV4) or IPv4 and IPv6 (DUAL) destinations. Defaults to IPV4.

Type: String

Valid Values: `IPV4 | DUAL`

plugins

Specifies which plugins were used for this connector.

Type: Array of PluginDescription objects

serviceExecutionRoleArn

The Amazon Resource Name (ARN) of the IAM role used by the connector to access Amazon Web Services resources.

Type: String

stateDescription

Details about the state of a connector.

Type: StateDescription object

workerConfiguration

Specifies which worker configuration was used for the connector.

Type: WorkerConfigurationDescription object

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

DescribeConnectorOperation

Returns information about the specified connector's operations.

Request Syntax

```
GET /v1/connectorOperations/connectorOperationArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

connectorOperationArn

ARN of the connector operation to be described.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "connectorArn": "string",
   "connectorOperationArn": "string",
   "connectorOperationState": "string",
   "connectorOperationType": "string",
   "creationTime": "string",
   "endTime": "string",
   "errorInfo": {
      "code": "string",
      "message": "string"
   },
   "operationSteps": [
      {
         "stepState": "string",
```

```
            "stepType": "string"
         }
      ],
      "originConnectorConfiguration": {
         "string" : "string"
      },
      "originWorkerSetting": {
         "capacity": {
            "autoScaling": {
               "maxAutoscalingTaskCount": number,
               "maxWorkerCount": number,
               "mcuCount": number,
               "minWorkerCount": number,
               "scaleInPolicy": {
                  "cpuUtilizationPercentage": number
               },
               "scaleOutPolicy": {
                  "cpuUtilizationPercentage": number
               }
            },
            "provisionedCapacity": {
               "mcuCount": number,
               "workerCount": number
            }
         }
      },
      "targetConnectorConfiguration": {
         "string" : "string"
      },
      "targetWorkerSetting": {
         "capacity": {
            "autoScaling": {
               "maxAutoscalingTaskCount": number,
               "maxWorkerCount": number,
               "mcuCount": number,
               "minWorkerCount": number,
               "scaleInPolicy": {
                  "cpuUtilizationPercentage": number
               },
               "scaleOutPolicy": {
                  "cpuUtilizationPercentage": number
               }
            },
            "provisionedCapacity": {
```

```
            "mcuCount": number,
            "workerCount": number
         }
      }
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

connectorArn

The Amazon Resource Name (ARN) of the connector.

Type: String

connectorOperationArn

The Amazon Resource Name (ARN) of the connector operation.

Type: String

connectorOperationState

The state of the connector operation.

Type: String

Valid Values: `PENDING | UPDATE_IN_PROGRESS | UPDATE_COMPLETE | UPDATE_FAILED | ROLLBACK_IN_PROGRESS | ROLLBACK_FAILED | ROLLBACK_COMPLETE | PAUSE_COMPLETE | PAUSE_FAILED | RESUME_COMPLETE | RESUME_FAILED | PAUSE_IN_PROGRESS | RESUME_IN_PROGRESS | RESTART_IN_PROGRESS | RESTART_COMPLETE | RESTART_FAILED`

connectorOperationType

The type of connector operation performed.

Type: String

Valid Values: `UPDATE_WORKER_SETTING | UPDATE_CONNECTOR_CONFIGURATION | ISOLATE_CONNECTOR | RESTORE_CONNECTOR | RESTART_CONNECTOR | PAUSE_CONNECTOR | RESUME_CONNECTOR`

creationTime

The time when the operation was created.

Type: Timestamp

endTime

The time when the operation ended.

Type: Timestamp

errorInfo

Details about the state of a resource.

Type: StateDescription object

operationSteps

The array of operation steps taken.

Type: Array of ConnectorOperationStep objects

originConnectorConfiguration

The origin connector configuration.

Type: String to string map

originWorkerSetting

The origin worker setting.

Type: WorkerSetting object

targetConnectorConfiguration

The target connector configuration.

Type: String to string map

targetWorkerSetting

The target worker setting.

Type: WorkerSetting object

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

DescribeCustomPlugin

A summary description of the custom plugin.

Request Syntax

```
GET /v1/custom-plugins/customPluginArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

customPluginArn

Returns information about a custom plugin.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "creationTime": "string",
   "customPluginArn": "string",
   "customPluginState": "string",
   "description": "string",
   "latestRevision": {
      "contentType": "string",
      "creationTime": "string",
      "description": "string",
      "fileDescription": {
         "fileMd5": "string",
         "fileSize": number
      },
      "location": {
```

```
            "s3Location": {
               "bucketArn": "string",
               "fileKey": "string",
               "objectVersion": "string"
            }
         },
         "revision": number
      },
      "name": "string",
      "stateDescription": {
         "code": "string",
         "message": "string"
      }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

creationTime

The time that the custom plugin was created.

Type: Timestamp

customPluginArn

The Amazon Resource Name (ARN) of the custom plugin.

Type: String

customPluginState

The state of the custom plugin.

Type: String

Valid Values: `CREATING | CREATE_FAILED | ACTIVE | UPDATING | UPDATE_FAILED | DELETING`

description

The description of the custom plugin.

Type: String

latestRevision

The latest successfully created revision of the custom plugin. If there are no successfully created revisions, this field will be absent.

Type: CustomPluginRevisionSummary object

name

The name of the custom plugin.

Type: String

stateDescription

Details about the state of a custom plugin.

Type: StateDescription object

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)

- Amazon SDK for Ruby V3

DescribeWorkerConfiguration

Returns information about a worker configuration.

Request Syntax

```
GET /v1/worker-configurations/workerConfigurationArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

workerConfigurationArn

The Amazon Resource Name (ARN) of the worker configuration that you want to get information about.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "creationTime": "string",
   "description": "string",
   "latestRevision": {
      "creationTime": "string",
      "description": "string",
      "propertiesFileContent": "string",
      "revision": number
   },
   "name": "string",
   "workerConfigurationArn": "string",
   "workerConfigurationState": "string"
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

creationTime

The time that the worker configuration was created.

Type: Timestamp

description

The description of the worker configuration.

Type: String

latestRevision

The latest revision of the custom configuration.

Type: WorkerConfigurationRevisionDescription object

name

The name of the worker configuration.

Type: String

workerConfigurationArn

The Amazon Resource Name (ARN) of the custom configuration.

Type: String

workerConfigurationState

The state of the worker configuration.

Type: String

Valid Values: `ACTIVE | DELETING`

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

ListConnectorOperations

Lists information about a connector's operation(s).

Request Syntax

```
GET /v1/connectors/connectorArn/operations?maxResults=maxResults&nextToken=nextToken
 HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

connectorArn

The Amazon Resource Name (ARN) of the connector for which to list operations.

Required: Yes

maxResults

Maximum number of connector operations to fetch in one get request.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

If the response is truncated, it includes a NextToken. Send this NextToken in a subsequent request to continue listing from where it left off.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "connectorOperations": [
      {
```

```
            "connectorOperationArn": "string",
            "connectorOperationState": "string",
            "connectorOperationType": "string",
            "creationTime": "string",
            "endTime": "string"
        }
    ],
    "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

connectorOperations

An array of connector operation descriptions.

Type: Array of ConnectorOperationSummary objects

nextToken

If the response is truncated, it includes a NextToken. Send this NextToken in a subsequent request to continue listing from where it left off.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2

- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

ListConnectors

Returns a list of all the connectors in this account and Region. The list is limited to connectors whose name starts with the specified prefix. The response also includes a description of each of the listed connectors.

Request Syntax

```
GET /v1/connectors?
connectorNamePrefix=connectorNamePrefix&maxResults=maxResults&nextToken=nextToken
 HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

connectorNamePrefix

The name prefix that you want to use to search for and list connectors.

maxResults

The maximum number of connectors to list in one response.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

If the response of a ListConnectors operation is truncated, it will include a NextToken. Send this NextToken in a subsequent request to continue listing from where the previous operation left off.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
   "connectors": [
      {
         "capacity": {
            "autoScaling": {
               "maxAutoscalingTaskCount": number,
               "maxWorkerCount": number,
               "mcuCount": number,
               "minWorkerCount": number,
               "scaleInPolicy": {
                  "cpuUtilizationPercentage": number
               },
               "scaleOutPolicy": {
                  "cpuUtilizationPercentage": number
               }
            },
            "provisionedCapacity": {
               "mcuCount": number,
               "workerCount": number
            }
         },
         "connectorArn": "string",
         "connectorDescription": "string",
         "connectorName": "string",
         "connectorState": "string",
         "creationTime": "string",
         "currentVersion": "string",
         "kafkaCluster": {
            "apacheKafkaCluster": {
               "bootstrapServers": "string",
               "vpc": {
                  "securityGroups": [ "string" ],
                  "subnets": [ "string" ]
               }
            }
         },
         "kafkaClusterClientAuthentication": {
            "authenticationType": "string"
         },
         "kafkaClusterEncryptionInTransit": {
            "encryptionType": "string"
         },
         "kafkaConnectVersion": "string",
         "logDelivery": {
            "workerLogDelivery": {
```

```
                "cloudWatchLogs": {
                   "enabled": boolean,
                   "logGroup": "string"
                },
                "firehose": {
                   "deliveryStream": "string",
                   "enabled": boolean
                },
                "s3": {
                   "bucket": "string",
                   "enabled": boolean,
                   "prefix": "string"
                }
             }
          },
          "networkType": "string",
          "plugins": [
             {
                "customPlugin": {
                   "customPluginArn": "string",
                   "revision": number
                }
             }
          ],
          "serviceExecutionRoleArn": "string",
          "workerConfiguration": {
             "revision": number,
             "workerConfigurationArn": "string"
          }
       }
    ],
    "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

connectors

An array of connector descriptions.

Type: Array of ConnectorSummary objects

nextToken

If the response of a ListConnectors operation is truncated, it will include a NextToken. Send this NextToken in a subsequent request to continue listing from where it left off.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

ListCustomPlugins

Returns a list of all of the custom plugins in this account and Region.

Request Syntax

```
GET /v1/custom-plugins?maxResults=maxResults&namePrefix=namePrefix&nextToken=nextToken
 HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of custom plugins to list in one response.

Valid Range: Minimum value of 1. Maximum value of 100.

namePrefix

Lists custom plugin names that start with the specified text string.

nextToken

If the response of a ListCustomPlugins operation is truncated, it will include a NextToken. Send this NextToken in a subsequent request to continue listing from where the previous operation left off.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "customPlugins": [
      {
```

```
         "creationTime": "string",
         "customPluginArn": "string",
         "customPluginState": "string",
         "description": "string",
         "latestRevision": {
            "contentType": "string",
            "creationTime": "string",
            "description": "string",
            "fileDescription": {
               "fileMd5": "string",
               "fileSize": number
            },
            "location": {
               "s3Location": {
                  "bucketArn": "string",
                  "fileKey": "string",
                  "objectVersion": "string"
               }
            },
            "revision": number
         },
         "name": "string"
      }
   ],
   "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

customPlugins

An array of custom plugin descriptions.

Type: Array of CustomPluginSummary objects

nextToken

If the response of a ListCustomPlugins operation is truncated, it will include a NextToken. Send this NextToken in a subsequent request to continue listing from where the previous operation left off.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

ListTagsForResource

Lists all the tags attached to the specified resource.

Request Syntax

```
GET /v1/tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource for which you want to list all attached tags.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "tags": {
      "string" : "string"
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

Lists the tags attached to the specified resource in the corresponding request.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

ListWorkerConfigurations

Returns a list of all of the worker configurations in this account and Region.

Request Syntax

```
GET /v1/worker-configurations?
maxResults=maxResults&namePrefix=namePrefix&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of worker configurations to list in one response.

Valid Range: Minimum value of 1. Maximum value of 100.

namePrefix

Lists worker configuration names that start with the specified text string.

nextToken

If the response of a ListWorkerConfigurations operation is truncated, it will include a NextToken. Send this NextToken in a subsequent request to continue listing from where the previous operation left off.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "nextToken": "string",
   "workerConfigurations": [
```

```
      {
         "creationTime": "string",
         "description": "string",
         "latestRevision": {
            "creationTime": "string",
            "description": "string",
            "revision": number
         },
         "name": "string",
         "workerConfigurationArn": "string",
         "workerConfigurationState": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If the response of a ListWorkerConfigurations operation is truncated, it will include a NextToken. Send this NextToken in a subsequent request to continue listing from where the previous operation left off.

Type: String

workerConfigurations

An array of worker configuration descriptions.

Type: Array of WorkerConfigurationSummary objects

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

PauseConnector

Pauses the specified connector. The operation runs asynchronously. To track the pause, pass the connector operation ARN from the response to `DescribeConnectorOperation`.

Request Syntax

```
PUT /v1/connectors/connectorArn/pause HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

connectorArn

The Amazon Resource Name (ARN) of the connector that you want to pause.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "connectorArn": "string",
   "connectorOperationArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

connectorArn

The Amazon Resource Name (ARN) of the connector.

Type: String

connectorOperationArn

The Amazon Resource Name (ARN) of the connector operation created to perform the pause.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ConflictException

HTTP Status Code 409: Conflict. A resource with this name already exists. Retry your request with another name.

HTTP Status Code: 409

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

RestartConnector

Restarts the specified connector. By default, this operation restarts the connector and all of its tasks. This operation is asynchronous and returns a connector operation ARN that you can pass to `DescribeConnectorOperation` to track the state of the restart.

Request Syntax

```
POST /v1/connectors/connectorArn/restart?onlyFailedTasks=onlyFailedTasks HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

connectorArn

The Amazon Resource Name (ARN) of the connector that you want to restart.

Required: Yes

onlyFailedTasks

Specifies whether to restart only the connector's failed tasks. If `true`, the operation restarts only the tasks that are currently in a failed state, and healthy tasks continue running. If `false` or not specified, the operation restarts the connector and all of its tasks.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "connectorArn": "string",
   "connectorOperationArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

connectorArn

The Amazon Resource Name (ARN) of the connector.

Type: String

connectorOperationArn

The Amazon Resource Name (ARN) of the connector operation created to perform the restart.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

ResumeConnector

Resumes the specified paused connector. The operation runs asynchronously. To track the resume, pass the connector operation ARN from the response to `DescribeConnectorOperation`.

Request Syntax

```
PUT /v1/connectors/connectorArn/resume HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

connectorArn

The Amazon Resource Name (ARN) of the connector that you want to resume.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "connectorArn": "string",
   "connectorOperationArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

connectorArn

The Amazon Resource Name (ARN) of the connector.

Type: String

connectorOperationArn

The Amazon Resource Name (ARN) of the connector operation created to perform the resume.

Type: String

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ConflictException

HTTP Status Code 409: Conflict. A resource with this name already exists. Retry your request with another name.

HTTP Status Code: 409

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

TagResource

Attaches tags to the specified resource.

Request Syntax

```
POST /v1/tags/resourceArn HTTP/1.1
Content-type: application/json

{
   "tags": {
      "string" : "string"
   }
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource to which you want to attach tags.

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

The tags that you want to attach to the resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ConflictException

HTTP Status Code 409: Conflict. A resource with this name already exists. Retry your request with another name.

HTTP Status Code: 409

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

UntagResource

Removes tags from the specified resource.

Request Syntax

```
DELETE /v1/tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource from which you want to remove tags.

Required: Yes

tagKeys

The keys of the tags that you want to remove from the resource.

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

UpdateConnector

Updates the specified connector. For request body, specify only one parameter: either `capacity` or `connectorConfiguration`.

Request Syntax

```
PUT /v1/connectors/connectorArn?currentVersion=currentVersion HTTP/1.1
Content-type: application/json

{
   "capacity": {
      "autoScaling": {
         "maxAutoscalingTaskCount": number,
         "maxWorkerCount": number,
         "mcuCount": number,
         "minWorkerCount": number,
         "scaleInPolicy": {
            "cpuUtilizationPercentage": number
         },
         "scaleOutPolicy": {
            "cpuUtilizationPercentage": number
         }
      },
      "provisionedCapacity": {
         "mcuCount": number,
         "workerCount": number
      }
   },
   "connectorConfiguration": {
      "string" : "string"
   },
   "skipHealthValidation": boolean
}
```

URI Request Parameters

The request uses the following URI parameters.

connectorArn

The Amazon Resource Name (ARN) of the connector that you want to update.

Required: Yes

currentVersion

The current version of the connector that you want to update.

Required: Yes

Request Body

The request accepts the following data in JSON format.

capacity

The target capacity.

Type: CapacityUpdate object

Required: No

connectorConfiguration

A map of keys to values that represent the configuration for the connector.

Type: String to string map

Required: No

skipHealthValidation

Specifies whether the update bypasses connector-level and task-level health checks. If `true`, the update skips the health checks. The update stays in effect even if the connector or its tasks are unhealthy, and Amazon MSK Connect doesn't roll it back. If `false` or not specified, the health checks run. If they fail, MSK Connect automatically rolls the connector back to its previous configuration, and the update doesn't take effect. To update a connector that is in the PAUSED state, you must set this parameter to `true`.

Type: Boolean

Required: No

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
   "connectorArn": "string",
   "connectorOperationArn": "string",
   "connectorState": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

connectorArn

The Amazon Resource Name (ARN) of the connector.

Type: String

connectorOperationArn

The Amazon Resource Name (ARN) of the connector operation.

Type: String

connectorState

The state of the connector.

Type: String

Valid Values: `RUNNING | CREATING | UPDATING | DELETING | FAILED | PAUSED | RESTARTING | PAUSING | RESUMING`

Errors

For information about the errors that are common to all actions, see Common Error Types.

BadRequestException

HTTP Status Code 400: Bad request due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 400

ForbiddenException

HTTP Status Code 403: Access forbidden. Correct your credentials and then retry your request.

HTTP Status Code: 403

InternalServerErrorException

HTTP Status Code 500: Unexpected internal server error. Retrying your request might resolve the issue.

HTTP Status Code: 500

NotFoundException

HTTP Status Code 404: Resource not found due to incorrect input. Correct your request and then retry it.

HTTP Status Code: 404

ServiceUnavailableException

HTTP Status Code 503: Service Unavailable. Retrying your request in some time might resolve the issue.

HTTP Status Code: 503

TooManyRequestsException

HTTP Status Code 429: Limit exceeded. Resource limit reached.

HTTP Status Code: 429

UnauthorizedException

HTTP Status Code 401: Unauthorized request. The provided credentials couldn't be validated.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon Command Line Interface V2
- Amazon SDK for .NET V4
- Amazon SDK for C++
- Amazon SDK for Go v2
- Amazon SDK for Java V2
- Amazon SDK for JavaScript V3
- Amazon SDK for Kotlin
- Amazon SDK for PHP V3
- Amazon SDK for Python (Boto3)
- Amazon SDK for Ruby V3

Data Types

The Managed Streaming for Kafka Connect API contains several data types that various actions use. This section describes each data type in detail.

> **Note**
>
> The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- ApacheKafkaCluster
- ApacheKafkaClusterDescription
- AutoScaling
- AutoScalingDescription
- AutoScalingUpdate
- Capacity
- CapacityDescription
- CapacityUpdate
- CloudWatchLogsLogDelivery
- CloudWatchLogsLogDeliveryDescription
- ConnectorOperationStep
- ConnectorOperationSummary
- ConnectorSummary
- CustomPlugin
- CustomPluginDescription
- CustomPluginFileDescription
- CustomPluginLocation
- CustomPluginLocationDescription
- CustomPluginRevisionSummary
- CustomPluginSummary

- FirehoseLogDelivery
- FirehoseLogDeliveryDescription
- KafkaCluster
- KafkaClusterClientAuthentication
- KafkaClusterClientAuthenticationDescription
- KafkaClusterDescription
- KafkaClusterEncryptionInTransit
- KafkaClusterEncryptionInTransitDescription
- LogDelivery
- LogDeliveryDescription
- Plugin
- PluginDescription
- ProvisionedCapacity
- ProvisionedCapacityDescription
- ProvisionedCapacityUpdate
- S3Location
- S3LocationDescription
- S3LogDelivery
- S3LogDeliveryDescription
- ScaleInPolicy
- ScaleInPolicyDescription
- ScaleInPolicyUpdate
- ScaleOutPolicy
- ScaleOutPolicyDescription
- ScaleOutPolicyUpdate
- StateDescription
- Vpc
- VpcDescription
- WorkerConfiguration
- WorkerConfigurationDescription

- WorkerConfigurationRevisionDescription
- WorkerConfigurationRevisionSummary
- WorkerConfigurationSummary
- WorkerLogDelivery
- WorkerLogDeliveryDescription
- WorkerSetting

ApacheKafkaCluster

The details of the Apache Kafka cluster to which the connector is connected.

Contents

bootstrapServers

The bootstrap servers of the cluster.

Type: String

Required: Yes

vpc

Details of an Amazon VPC which has network connectivity to the Apache Kafka cluster.

Type: Vpc object

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

ApacheKafkaClusterDescription

The description of the Apache Kafka cluster to which the connector is connected.

Contents

bootstrapServers

The bootstrap servers of the cluster.

Type: String

Required: No

vpc

Details of an Amazon VPC which has network connectivity to the Apache Kafka cluster.

Type: VpcDescription object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

AutoScaling

Specifies how the connector scales.

Contents

maxWorkerCount

The maximum number of workers allocated to the connector.

Type: Integer

Required: Yes

mcuCount

The number of microcontroller units (MCUs) allocated to each connector worker. The valid values are 1,2,4,8.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 8.

Required: Yes

minWorkerCount

The minimum number of workers allocated to the connector.

Type: Integer

Required: Yes

maxAutoscalingTaskCount

The maximum number of tasks allocated to the connector during autoscaling operations. Must be at least equal to maxWorkerCount.

Type: Integer

Required: No

scaleInPolicy

The scale-in policy for the connector.

Type: ScaleInPolicy object

Required: No

scaleOutPolicy

The scale-out policy for the connector.

Type: ScaleOutPolicy object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

AutoScalingDescription

Information about the auto scaling parameters for the connector.

Contents

maxAutoscalingTaskCount

The maximum number of tasks allocated to the connector during autoscaling operations. Must be at least equal to maxWorkerCount.

Type: Integer

Required: No

maxWorkerCount

The maximum number of workers allocated to the connector.

Type: Integer

Required: No

mcuCount

The number of microcontroller units (MCUs) allocated to each connector worker. The valid values are 1,2,4,8.

Type: Integer

Required: No

minWorkerCount

The minimum number of workers allocated to the connector.

Type: Integer

Required: No

scaleInPolicy

The scale-in policy for the connector.

Type: ScaleInPolicyDescription object

Required: No

scaleOutPolicy

The scale-out policy for the connector.

Type: ScaleOutPolicyDescription object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

AutoScalingUpdate

The updates to the auto scaling parameters for the connector.

Contents

maxWorkerCount

The target maximum number of workers allocated to the connector.

Type: Integer

Required: Yes

mcuCount

The target number of microcontroller units (MCUs) allocated to each connector worker. The valid values are 1,2,4,8.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 8.

Required: Yes

minWorkerCount

The target minimum number of workers allocated to the connector.

Type: Integer

Required: Yes

scaleInPolicy

The target scale-in policy for the connector.

Type: ScaleInPolicyUpdate object

Required: Yes

scaleOutPolicy

The target scale-out policy for the connector.

Type: ScaleOutPolicyUpdate object

Required: Yes

maxAutoscalingTaskCount

The maximum number of tasks allocated to the connector during autoscaling operations. Must be at least equal to maxWorkerCount.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

Capacity

Information about the capacity of the connector, whether it is auto scaled or provisioned.

Contents

autoScaling

Information about the auto scaling parameters for the connector.

Type: AutoScaling object

Required: No

provisionedCapacity

Details about a fixed capacity allocated to a connector.

Type: ProvisionedCapacity object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

CapacityDescription

A description of the connector's capacity.

Contents

autoScaling

Describes the connector's auto scaling capacity.

Type: AutoScalingDescription object

Required: No

provisionedCapacity

Describes a connector's provisioned capacity.

Type: ProvisionedCapacityDescription object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

CapacityUpdate

The target capacity for the connector. The capacity can be auto scaled or provisioned.

Contents

autoScaling

The target auto scaling setting.

Type: AutoScalingUpdate object

Required: No

provisionedCapacity

The target settings for provisioned capacity.

Type: ProvisionedCapacityUpdate object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

CloudWatchLogsLogDelivery

The settings for delivering connector logs to Amazon CloudWatch Logs.

Contents

enabled

Whether log delivery to Amazon CloudWatch Logs is enabled.

Type: Boolean

Required: Yes

logGroup

The name of the CloudWatch log group that is the destination for log delivery.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

CloudWatchLogsLogDeliveryDescription

A description of the log delivery settings.

Contents

enabled

Whether log delivery to Amazon CloudWatch Logs is enabled.

Type: Boolean

Required: No

logGroup

The name of the CloudWatch log group that is the destination for log delivery.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

ConnectorOperationStep

Details of a step that is involved in a connector's operation.

Contents

stepState

The step state of the operation.

Type: String

Valid Values: `PENDING | IN_PROGRESS | COMPLETED | FAILED | CANCELLED`

Required: No

stepType

The step type of the operation.

Type: String

Valid Values: `INITIALIZE_UPDATE | FINALIZE_UPDATE | UPDATE_WORKER_SETTING | UPDATE_CONNECTOR_CONFIGURATION | VALIDATE_UPDATE`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

ConnectorOperationSummary

Summary of a connector operation.

Contents

connectorOperationArn

The Amazon Resource Name (ARN) of the connector operation.

Type: String

Required: No

connectorOperationState

The state of the connector operation.

Type: String

Valid Values: `PENDING | UPDATE_IN_PROGRESS | UPDATE_COMPLETE | UPDATE_FAILED | ROLLBACK_IN_PROGRESS | ROLLBACK_FAILED | ROLLBACK_COMPLETE | PAUSE_COMPLETE | PAUSE_FAILED | RESUME_COMPLETE | RESUME_FAILED | PAUSE_IN_PROGRESS | RESUME_IN_PROGRESS | RESTART_IN_PROGRESS | RESTART_COMPLETE | RESTART_FAILED`

Required: No

connectorOperationType

The type of connector operation performed.

Type: String

Valid Values: `UPDATE_WORKER_SETTING | UPDATE_CONNECTOR_CONFIGURATION | ISOLATE_CONNECTOR | RESTORE_CONNECTOR | RESTART_CONNECTOR | PAUSE_CONNECTOR | RESUME_CONNECTOR`

Required: No

creationTime

The time when operation was created.

Type: Timestamp

Required: No

endTime

The time when operation ended.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

ConnectorSummary

Summary of a connector.

Contents

capacity

The connector's compute capacity settings.

Type: CapacityDescription object

Required: No

connectorArn

The Amazon Resource Name (ARN) of the connector.

Type: String

Required: No

connectorDescription

The description of the connector.

Type: String

Required: No

connectorName

The name of the connector.

Type: String

Required: No

connectorState

The state of the connector.

Type: String

Valid Values: `RUNNING | CREATING | UPDATING | DELETING | FAILED | PAUSED | RESTARTING | PAUSING | RESUMING`

Required: No

creationTime

The time that the connector was created.

Type: Timestamp

Required: No

currentVersion

The current version of the connector.

Type: String

Required: No

kafkaCluster

The details of the Apache Kafka cluster to which the connector is connected.

Type: KafkaClusterDescription object

Required: No

kafkaClusterClientAuthentication

The type of client authentication used to connect to the Apache Kafka cluster. The value is NONE when no client authentication is used.

Type: KafkaClusterClientAuthenticationDescription object

Required: No

kafkaClusterEncryptionInTransit

Details of encryption in transit to the Apache Kafka cluster.

Type: KafkaClusterEncryptionInTransitDescription object

Required: No

kafkaConnectVersion

The version of Kafka Connect. It has to be compatible with both the Apache Kafka cluster's version and the plugins.

Type: String

Required: No

logDelivery

The settings for delivering connector logs to Amazon CloudWatch Logs.

Type: LogDeliveryDescription object

Required: No

networkType

The network type of the connector. It gives connectors connectivity to either IPv4 (IPV4) or IPv4 and IPv6 (DUAL) destinations. Defaults to IPV4.

Type: String

Valid Values: `IPV4 | DUAL`

Required: No

plugins

Specifies which plugins were used for this connector.

Type: Array of PluginDescription objects

Required: No

serviceExecutionRoleArn

The Amazon Resource Name (ARN) of the IAM role used by the connector to access Amazon Web Services resources.

Type: String

Required: No

workerConfiguration

The worker configurations that are in use with the connector.

Type: WorkerConfigurationDescription object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

CustomPlugin

A plugin is an Amazon resource that contains the code that defines a connector's logic.

Contents

customPluginArn

The Amazon Resource Name (ARN) of the custom plugin.

Type: String

Required: Yes

revision

The revision of the custom plugin.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 9223372036854775807.

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

CustomPluginDescription

Details about a custom plugin.

Contents

customPluginArn

The Amazon Resource Name (ARN) of the custom plugin.

Type: String

Required: No

revision

The revision of the custom plugin.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

CustomPluginFileDescription

Details about a custom plugin file.

Contents

fileMd5

The hex-encoded MD5 checksum of the custom plugin file. You can use it to validate the file.

Type: String

Required: No

fileSize

The size in bytes of the custom plugin file. You can use it to validate the file.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

CustomPluginLocation

Information about the location of a custom plugin.

Contents

s3Location

The S3 bucket Amazon Resource Name (ARN), file key, and object version of the plugin file stored in Amazon S3.

Type: S3Location object

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

CustomPluginLocationDescription

Information about the location of a custom plugin.

Contents

s3Location

The S3 bucket Amazon Resource Name (ARN), file key, and object version of the plugin file stored in Amazon S3.

Type: S3LocationDescription object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

CustomPluginRevisionSummary

Details about the revision of a custom plugin.

Contents

contentType

The format of the plugin file.

Type: String

Valid Values: `JAR | ZIP`

Required: No

creationTime

The time that the custom plugin was created.

Type: Timestamp

Required: No

description

The description of the custom plugin.

Type: String

Required: No

fileDescription

Details about the custom plugin file.

Type: CustomPluginFileDescription object

Required: No

location

Information about the location of the custom plugin.

Type: CustomPluginLocationDescription object

Required: No

revision

The revision of the custom plugin.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

CustomPluginSummary

A summary of the custom plugin.

Contents

creationTime

The time that the custom plugin was created.

Type: Timestamp

Required: No

customPluginArn

The Amazon Resource Name (ARN) of the custom plugin.

Type: String

Required: No

customPluginState

The state of the custom plugin.

Type: String

Valid Values: `CREATING | CREATE_FAILED | ACTIVE | UPDATING | UPDATE_FAILED | DELETING`

Required: No

description

A description of the custom plugin.

Type: String

Required: No

latestRevision

The latest revision of the custom plugin.

Type: CustomPluginRevisionSummary object

Required: No

name

The name of the custom plugin.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

FirehoseLogDelivery

The settings for delivering logs to Amazon Kinesis Data Firehose.

Contents

enabled

Specifies whether connector logs get delivered to Amazon Kinesis Data Firehose.

Type: Boolean

Required: Yes

deliveryStream

The name of the Kinesis Data Firehose delivery stream that is the destination for log delivery.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

FirehoseLogDeliveryDescription

A description of the settings for delivering logs to Amazon Kinesis Data Firehose.

Contents

deliveryStream

The name of the Kinesis Data Firehose delivery stream that is the destination for log delivery.

Type: String

Required: No

enabled

Specifies whether connector logs get delivered to Amazon Kinesis Data Firehose.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

KafkaCluster

The details of the Apache Kafka cluster to which the connector is connected.

Contents

apacheKafkaCluster

The Apache Kafka cluster to which the connector is connected.

Type: ApacheKafkaCluster object

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

KafkaClusterClientAuthentication

The client authentication information used in order to authenticate with the Apache Kafka cluster.

Contents

authenticationType

The type of client authentication used to connect to the Apache Kafka cluster. Value NONE means that no client authentication is used.

Type: String

Valid Values: `NONE | IAM`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

KafkaClusterClientAuthenticationDescription

The client authentication information used in order to authenticate with the Apache Kafka cluster.

Contents

authenticationType

The type of client authentication used to connect to the Apache Kafka cluster. Value NONE means that no client authentication is used.

Type: String

Valid Values: `NONE | IAM`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

KafkaClusterDescription

Details of how to connect to the Apache Kafka cluster.

Contents

apacheKafkaCluster

The Apache Kafka cluster to which the connector is connected.

Type: ApacheKafkaClusterDescription object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

KafkaClusterEncryptionInTransit

Details of encryption in transit to the Apache Kafka cluster.

Contents

encryptionType

The type of encryption in transit to the Apache Kafka cluster.

Type: String

Valid Values: `PLAINTEXT | TLS`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

KafkaClusterEncryptionInTransitDescription

The description of the encryption in transit to the Apache Kafka cluster.

Contents

encryptionType

The type of encryption in transit to the Apache Kafka cluster.

Type: String

Valid Values: `PLAINTEXT | TLS`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

LogDelivery

Details about log delivery.

Contents

workerLogDelivery

The workers can send worker logs to different destination types. This configuration specifies the details of these destinations.

Type: WorkerLogDelivery object

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

LogDeliveryDescription

The description of the log delivery settings.

Contents

workerLogDelivery

The workers can send worker logs to different destination types. This configuration specifies the details of these destinations.

Type: WorkerLogDeliveryDescription object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

Plugin

A plugin is an Amazon resource that contains the code that defines your connector logic.

Contents

customPlugin

Details about a custom plugin.

Type: CustomPlugin object

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

PluginDescription

The description of the plugin.

Contents

customPlugin

Details about a custom plugin.

Type: CustomPluginDescription object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

ProvisionedCapacity

Details about a connector's provisioned capacity.

Contents

mcuCount

The number of microcontroller units (MCUs) allocated to each connector worker. The valid values are 1,2,4,8.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 8.

Required: Yes

workerCount

The number of workers that are allocated to the connector.

Type: Integer

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

ProvisionedCapacityDescription

The description of a connector's provisioned capacity.

Contents

mcuCount

The number of microcontroller units (MCUs) allocated to each connector worker. The valid values are 1,2,4,8.

Type: Integer

Required: No

workerCount

The number of workers that are allocated to the connector.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

ProvisionedCapacityUpdate

An update to a connector's fixed capacity.

Contents

mcuCount

The number of microcontroller units (MCUs) allocated to each connector worker. The valid values are 1,2,4,8.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 8.

Required: Yes

workerCount

The number of workers that are allocated to the connector.

Type: Integer

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

S3Location

The location of an object in Amazon S3.

Contents

bucketArn

The Amazon Resource Name (ARN) of an S3 bucket.

Type: String

Required: Yes

fileKey

The file key for an object in an S3 bucket.

Type: String

Required: Yes

objectVersion

The version of an object in an S3 bucket.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

S3LocationDescription

The description of the location of an object in Amazon S3.

Contents

bucketArn

The Amazon Resource Name (ARN) of an S3 bucket.

Type: String

Required: No

fileKey

The file key for an object in an S3 bucket.

Type: String

Required: No

objectVersion

The version of an object in an S3 bucket.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

S3LogDelivery

Details about delivering logs to Amazon S3.

Contents

enabled

Specifies whether connector logs get sent to the specified Amazon S3 destination.

Type: Boolean

Required: Yes

bucket

The name of the S3 bucket that is the destination for log delivery.

Type: String

Required: No

prefix

The S3 prefix that is the destination for log delivery.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

S3LogDeliveryDescription

The description of the details about delivering logs to Amazon S3.

Contents

bucket

The name of the S3 bucket that is the destination for log delivery.

Type: String

Required: No

enabled

Specifies whether connector logs get sent to the specified Amazon S3 destination.

Type: Boolean

Required: No

prefix

The S3 prefix that is the destination for log delivery.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

ScaleInPolicy

The scale-in policy for the connector.

Contents

cpuUtilizationPercentage

Specifies the CPU utilization percentage threshold at which you want connector scale in to be triggered.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

ScaleInPolicyDescription

The description of the scale-in policy for the connector.

Contents

cpuUtilizationPercentage

Specifies the CPU utilization percentage threshold at which you want connector scale in to be triggered.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

ScaleInPolicyUpdate

An update to the connector's scale-in policy.

Contents

cpuUtilizationPercentage

The target CPU utilization percentage threshold at which you want connector scale in to be triggered.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

ScaleOutPolicy

The scale-out policy for the connector.

Contents

cpuUtilizationPercentage

The CPU utilization percentage threshold at which you want connector scale out to be triggered.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

ScaleOutPolicyDescription

The description of the scale-out policy for the connector.

Contents

cpuUtilizationPercentage

The CPU utilization percentage threshold at which you want connector scale out to be triggered.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

ScaleOutPolicyUpdate

An update to the connector's scale-out policy.

Contents

cpuUtilizationPercentage

The target CPU utilization percentage threshold at which you want connector scale out to be triggered.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

StateDescription

Details about the state of a resource.

Contents

code

A code that describes the state of a resource.

Type: String

Required: No

message

A message that describes the state of a resource.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

Vpc

Information about the VPC in which the connector resides.

Contents

subnets

The subnets for the connector.

Type: Array of strings

Required: Yes

securityGroups

The security groups for the connector.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

VpcDescription

The description of the VPC in which the connector resides.

Contents

securityGroups

The security groups for the connector.

Type: Array of strings

Required: No

subnets

The subnets for the connector.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

WorkerConfiguration

The configuration of the workers, which are the processes that run the connector logic.

Contents

revision

The revision of the worker configuration.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 9223372036854775807.

Required: Yes

workerConfigurationArn

The Amazon Resource Name (ARN) of the worker configuration.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

WorkerConfigurationDescription

The description of the worker configuration.

Contents

revision

The revision of the worker configuration.

Type: Long

Required: No

workerConfigurationArn

The Amazon Resource Name (ARN) of the worker configuration.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

WorkerConfigurationRevisionDescription

The description of the worker configuration revision.

Contents

creationTime

The time that the worker configuration was created.

Type: Timestamp

Required: No

description

The description of the worker configuration revision.

Type: String

Required: No

propertiesFileContent

Base64 encoded contents of the connect-distributed.properties file.

Type: String

Required: No

revision

The description of a revision of the worker configuration.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++

- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

WorkerConfigurationRevisionSummary

The summary of a worker configuration revision.

Contents

creationTime

The time that a worker configuration revision was created.

Type: Timestamp

Required: No

description

The description of a worker configuration revision.

Type: String

Required: No

revision

The revision of a worker configuration.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

WorkerConfigurationSummary

The summary of a worker configuration.

Contents

creationTime

The time that a worker configuration was created.

Type: Timestamp

Required: No

description

The description of a worker configuration.

Type: String

Required: No

latestRevision

The latest revision of a worker configuration.

Type: WorkerConfigurationRevisionSummary object

Required: No

name

The name of the worker configuration.

Type: String

Required: No

workerConfigurationArn

The Amazon Resource Name (ARN) of the worker configuration.

Type: String

Required: No

workerConfigurationState

The state of the worker configuration.

Type: String

Valid Values: `ACTIVE | DELETING`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

WorkerLogDelivery

Workers can send worker logs to different destination types. This configuration specifies the details of these destinations.

Contents

cloudWatchLogs

Details about delivering logs to Amazon CloudWatch Logs.

Type: CloudWatchLogsLogDelivery object

Required: No

firehose

Details about delivering logs to Amazon Kinesis Data Firehose.

Type: FirehoseLogDelivery object

Required: No

s3

Details about delivering logs to Amazon S3.

Type: S3LogDelivery object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

WorkerLogDeliveryDescription

Workers can send worker logs to different destination types. This configuration specifies the details of these destinations.

Contents

cloudWatchLogs

Details about delivering logs to Amazon CloudWatch Logs.

Type: CloudWatchLogsLogDeliveryDescription object

Required: No

firehose

Details about delivering logs to Amazon Kinesis Data Firehose.

Type: FirehoseLogDeliveryDescription object

Required: No

s3

Details about delivering logs to Amazon S3.

Type: S3LogDeliveryDescription object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

WorkerSetting

Details about worker setting of a connector

Contents

capacity

A description of the connector's capacity.

Type: CapacityDescription object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- Amazon SDK for C++
- Amazon SDK for Java V2
- Amazon SDK for Ruby V3

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see Signing Amazon API requests in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: `AWS4-HMAC-SHA256`

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key*/*YYYYMMDD*/*region*/*service*/aws4_request.

For more information, see Create a signed Amazon API request in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: `20120325T120000Z`.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see Elements of an Amazon API request signature in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to Amazon Security Token Service (Amazon STS). For a list of services that support temporary security credentials from Amazon STS, see Amazon Web Services services that work with IAM in the *IAM User Guide*.

Condition: If you're using temporary security credentials from Amazon STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see Create a signed Amazon API request in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this Amazon service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to Amazon standards. Verify that you're using valid Amazon credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact Amazon Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your Amazon account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The Amazon SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or Amazon access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400