



API Reference

# Amazon Compute Optimizer



API Version 2019-11-01

# Amazon Compute Optimizer: API Reference

# Table of Contents

Welcome .....	1
Actions .....	2
DeleteRecommendationPreferences .....	4
Request Syntax .....	4
Request Parameters .....	4
Response Elements .....	5
Errors .....	5
See Also .....	6
DescribeRecommendationExportJobs .....	8
Request Syntax .....	8
Request Parameters .....	8
Response Syntax .....	9
Response Elements .....	10
Errors .....	10
See Also .....	11
ExportAutoScalingGroupRecommendations .....	13
Request Syntax .....	13
Request Parameters .....	13
Response Syntax .....	17
Response Elements .....	17
Errors .....	18
See Also .....	19
ExportEBSVolumeRecommendations .....	20
Request Syntax .....	20
Request Parameters .....	20
Response Syntax .....	23
Response Elements .....	23
Errors .....	24
See Also .....	25
ExportEC2InstanceRecommendations .....	26
Request Syntax .....	26
Request Parameters .....	26
Response Syntax .....	30
Response Elements .....	30

Errors .....	31
See Also .....	32
ExportECSServiceRecommendations .....	33
Request Syntax .....	33
Request Parameters .....	33
Response Syntax .....	36
Response Elements .....	36
Errors .....	37
See Also .....	38
ExportIdleRecommendations .....	39
Request Syntax .....	39
Request Parameters .....	39
Response Syntax .....	42
Response Elements .....	42
Errors .....	42
See Also .....	44
ExportLambdaFunctionRecommendations .....	45
Request Syntax .....	45
Request Parameters .....	45
Response Syntax .....	48
Response Elements .....	48
Errors .....	49
See Also .....	50
ExportLicenseRecommendations .....	51
Request Syntax .....	51
Request Parameters .....	51
Response Syntax .....	54
Response Elements .....	54
Errors .....	55
See Also .....	56
ExportRDSDatabaseRecommendations .....	57
Request Syntax .....	57
Request Parameters .....	57
Response Syntax .....	62
Response Elements .....	62
Errors .....	63

See Also .....	64
GetAutoScalingGroupRecommendations .....	65
Request Syntax .....	65
Request Parameters .....	65
Response Syntax .....	67
Response Elements .....	69
Errors .....	70
See Also .....	71
GetEBSVolumeRecommendations .....	73
Request Syntax .....	73
Request Parameters .....	73
Response Syntax .....	74
Response Elements .....	76
Errors .....	77
See Also .....	78
GetEC2InstanceRecommendations .....	79
Request Syntax .....	79
Request Parameters .....	79
Response Syntax .....	81
Response Elements .....	83
Errors .....	84
See Also .....	85
GetEC2RecommendationProjectedMetrics .....	87
Request Syntax .....	87
Request Parameters .....	87
Response Syntax .....	88
Response Elements .....	89
Errors .....	89
See Also .....	90
GetECSServiceRecommendationProjectedMetrics .....	92
Request Syntax .....	92
Request Parameters .....	92
Response Syntax .....	93
Response Elements .....	93
Errors .....	94
See Also .....	95

GetECSServiceRecommendations .....	96
Request Syntax .....	96
Request Parameters .....	96
Response Syntax .....	97
Response Elements .....	100
Errors .....	100
See Also .....	101
GetEffectiveRecommendationPreferences .....	103
Request Syntax .....	103
Request Parameters .....	103
Response Syntax .....	103
Response Elements .....	104
Errors .....	106
See Also .....	107
GetEnrollmentStatus .....	108
Response Syntax .....	108
Response Elements .....	108
Errors .....	109
See Also .....	110
GetEnrollmentStatusesForOrganization .....	111
Request Syntax .....	111
Request Parameters .....	111
Response Syntax .....	112
Response Elements .....	112
Errors .....	113
See Also .....	113
GetIdleRecommendations .....	115
Request Syntax .....	115
Request Parameters .....	115
Response Syntax .....	117
Response Elements .....	118
Errors .....	118
See Also .....	119
GetLambdaFunctionRecommendations .....	121
Request Syntax .....	121
Request Parameters .....	121

Response Syntax .....	123
Response Elements .....	124
Errors .....	125
See Also .....	126
GetLicenseRecommendations .....	127
Request Syntax .....	127
Request Parameters .....	127
Response Syntax .....	128
Response Elements .....	130
Errors .....	130
See Also .....	131
GetRDSDatabaseRecommendationProjectedMetrics .....	133
Request Syntax .....	133
Request Parameters .....	133
Response Syntax .....	134
Response Elements .....	135
Errors .....	135
See Also .....	136
GetRDSDatabaseRecommendations .....	138
Request Syntax .....	138
Request Parameters .....	138
Response Syntax .....	140
Response Elements .....	143
Errors .....	143
See Also .....	144
GetRecommendationPreferences .....	146
Request Syntax .....	146
Request Parameters .....	146
Response Syntax .....	147
Response Elements .....	148
Errors .....	149
See Also .....	150
GetRecommendationSummaries .....	151
Request Syntax .....	151
Request Parameters .....	151
Response Syntax .....	152

Response Elements .....	154
Errors .....	154
See Also .....	155
PutRecommendationPreferences .....	156
Request Syntax .....	156
Request Parameters .....	157
Response Elements .....	161
Errors .....	161
See Also .....	162
UpdateEnrollmentStatus .....	163
Request Syntax .....	163
Request Parameters .....	163
Response Syntax .....	164
Response Elements .....	164
Errors .....	165
See Also .....	166
<b>Data Types .....</b>	<b>167</b>
AccountEnrollmentStatus .....	171
Contents .....	171
See Also .....	172
AutoScalingGroupConfiguration .....	173
Contents .....	173
See Also .....	174
AutoScalingGroupEstimatedMonthlySavings .....	175
Contents .....	175
See Also .....	175
AutoScalingGroupRecommendation .....	176
Contents .....	176
See Also .....	179
AutoScalingGroupRecommendationOption .....	180
Contents .....	180
See Also .....	182
AutoScalingGroupSavingsOpportunityAfterDiscounts .....	183
Contents .....	183
See Also .....	183
ContainerConfiguration .....	184

Contents .....	184
See Also .....	184
ContainerRecommendation .....	185
Contents .....	185
See Also .....	185
CurrentPerformanceRiskRatings .....	186
Contents .....	186
See Also .....	186
CustomizableMetricParameters .....	188
Contents .....	188
See Also .....	188
DBStorageConfiguration .....	190
Contents .....	190
See Also .....	191
EBSEffectiveRecommendationPreferences .....	192
Contents .....	192
See Also .....	192
EBSEstimatedMonthlySavings .....	193
Contents .....	193
See Also .....	193
EBSFilter .....	194
Contents .....	194
See Also .....	195
EBSSavingsEstimationMode .....	196
Contents .....	196
See Also .....	196
EBSSavingsOpportunityAfterDiscounts .....	197
Contents .....	197
See Also .....	197
EBSUtilizationMetric .....	198
Contents .....	198
See Also .....	199
ECSEffectiveRecommendationPreferences .....	200
Contents .....	200
See Also .....	200
ECSEstimatedMonthlySavings .....	201

Contents .....	201
See Also .....	201
<b>ECSSavingsEstimationMode</b> .....	202
Contents .....	202
See Also .....	202
<b>ECSSavingsOpportunityAfterDiscounts</b> .....	203
Contents .....	203
See Also .....	203
<b>ECSServiceProjectedMetric</b> .....	204
Contents .....	204
See Also .....	205
<b>ECSServiceProjectedUtilizationMetric</b> .....	206
Contents .....	206
See Also .....	207
<b>ECSServiceRecommendation</b> .....	208
Contents .....	208
See Also .....	211
<b>ECSServiceRecommendationFilter</b> .....	212
Contents .....	212
See Also .....	213
<b>ECSServiceRecommendationOption</b> .....	214
Contents .....	214
See Also .....	215
<b>ECSServiceRecommendedOptionProjectedMetric</b> .....	217
Contents .....	217
See Also .....	217
<b>ECSServiceUtilizationMetric</b> .....	219
Contents .....	219
See Also .....	220
<b>EffectivePreferredResource</b> .....	221
Contents .....	221
See Also .....	222
<b>EffectiveRecommendationPreferences</b> .....	223
Contents .....	223
See Also .....	225
<b>EnrollmentFilter</b> .....	226

Contents .....	226
See Also .....	226
EstimatedMonthlySavings .....	227
Contents .....	227
See Also .....	227
ExportDestination .....	228
Contents .....	228
See Also .....	228
ExternalMetricsPreference .....	229
Contents .....	229
See Also .....	229
ExternalMetricStatus .....	230
Contents .....	230
See Also .....	230
Filter .....	231
Contents .....	231
See Also .....	234
GetRecommendationError .....	235
Contents .....	235
See Also .....	235
Gpu .....	237
Contents .....	237
See Also .....	237
GpuInfo .....	238
Contents .....	238
See Also .....	238
IdleEstimatedMonthlySavings .....	239
Contents .....	239
See Also .....	239
IdleRecommendation .....	240
Contents .....	240
See Also .....	242
IdleRecommendationError .....	243
Contents .....	243
See Also .....	243
IdleRecommendationFilter .....	245

Contents .....	245
See Also .....	245
IdleSavingsOpportunity .....	247
Contents .....	247
See Also .....	247
IdleSavingsOpportunityAfterDiscounts .....	248
Contents .....	248
See Also .....	248
IdleSummary .....	249
Contents .....	249
See Also .....	249
IdleUtilizationMetric .....	250
Contents .....	250
See Also .....	251
InferredWorkloadSaving .....	252
Contents .....	252
See Also .....	253
InstanceEstimatedMonthlySavings .....	254
Contents .....	254
See Also .....	254
InstanceRecommendation .....	255
Contents .....	255
See Also .....	262
InstanceRecommendationOption .....	263
Contents .....	263
See Also .....	267
InstanceSavingsEstimationMode .....	268
Contents .....	268
See Also .....	268
InstanceSavingsOpportunityAfterDiscounts .....	269
Contents .....	269
See Also .....	269
JobFilter .....	270
Contents .....	270
See Also .....	271
LambdaEffectiveRecommendationPreferences .....	272

Contents .....	272
See Also .....	272
LambdaEstimatedMonthlySavings .....	273
Contents .....	273
See Also .....	273
LambdaFunctionMemoryProjectedMetric .....	274
Contents .....	274
See Also .....	274
LambdaFunctionMemoryRecommendationOption .....	276
Contents .....	276
See Also .....	277
LambdaFunctionRecommendation .....	278
Contents .....	278
See Also .....	282
LambdaFunctionRecommendationFilter .....	283
Contents .....	283
See Also .....	284
LambdaFunctionUtilizationMetric .....	285
Contents .....	285
See Also .....	286
LambdaSavingsEstimationMode .....	287
Contents .....	287
See Also .....	287
LambdaSavingsOpportunityAfterDiscounts .....	288
Contents .....	288
See Also .....	288
LicenseConfiguration .....	289
Contents .....	289
See Also .....	290
LicenseRecommendation .....	291
Contents .....	291
See Also .....	293
LicenseRecommendationFilter .....	294
Contents .....	294
See Also .....	295
LicenseRecommendationOption .....	296

Contents .....	296
See Also .....	297
MemorySizeConfiguration .....	298
Contents .....	298
See Also .....	298
MetricSource .....	299
Contents .....	299
See Also .....	299
OrderBy .....	300
Contents .....	300
See Also .....	300
PreferredResource .....	301
Contents .....	301
See Also .....	302
ProjectedMetric .....	303
Contents .....	303
See Also .....	305
RDSDatabaseProjectedMetric .....	306
Contents .....	306
See Also .....	307
RDSDatabaseRecommendedOptionProjectedMetric .....	308
Contents .....	308
See Also .....	308
RDSDBInstanceRecommendationOption .....	310
Contents .....	310
See Also .....	311
RDSDBRecommendation .....	313
Contents .....	313
See Also .....	317
RDSDBRecommendationFilter .....	318
Contents .....	318
See Also .....	319
RDSDBStorageRecommendationOption .....	320
Contents .....	320
See Also .....	321
RDSDBUtilizationMetric .....	322

Contents .....	322
See Also .....	323
<b>RDSEffectiveRecommendationPreferences</b> .....	324
Contents .....	324
See Also .....	325
<b>RDSInstanceEstimatedMonthlySavings</b> .....	326
Contents .....	326
See Also .....	326
<b>RDSInstanceSavingsOpportunityAfterDiscounts</b> .....	327
Contents .....	327
See Also .....	327
<b>RDSSavingsEstimationMode</b> .....	328
Contents .....	328
See Also .....	328
<b>RDSStorageEstimatedMonthlySavings</b> .....	329
Contents .....	329
See Also .....	329
<b>RDSStorageSavingsOpportunityAfterDiscounts</b> .....	330
Contents .....	330
See Also .....	330
<b>ReasonCodeSummary</b> .....	331
Contents .....	331
See Also .....	331
<b>RecommendationExportJob</b> .....	332
Contents .....	332
See Also .....	333
<b>RecommendationPreferences</b> .....	334
Contents .....	334
See Also .....	334
<b>RecommendationPreferencesDetail</b> .....	336
Contents .....	336
See Also .....	338
<b>RecommendationSource</b> .....	340
Contents .....	340
See Also .....	340
<b>RecommendationSummary</b> .....	341

Contents .....	341
See Also .....	343
RecommendedOptionProjectedMetric .....	344
Contents .....	344
See Also .....	345
S3Destination .....	346
Contents .....	346
See Also .....	346
S3DestinationConfig .....	348
Contents .....	348
See Also .....	348
SavingsOpportunity .....	349
Contents .....	349
See Also .....	350
Scope .....	351
Contents .....	351
See Also .....	352
ServiceConfiguration .....	353
Contents .....	353
See Also .....	354
Summary .....	355
Contents .....	355
See Also .....	355
Tag .....	356
Contents .....	356
See Also .....	356
UtilizationMetric .....	357
Contents .....	357
See Also .....	360
UtilizationPreference .....	361
Contents .....	361
See Also .....	361
VolumeConfiguration .....	362
Contents .....	362
See Also .....	363
VolumeRecommendation .....	364

Contents .....	364
See Also .....	366
VolumeRecommendationOption .....	367
Contents .....	367
See Also .....	368
<b>Common Parameters .....</b>	<b>369</b>
<b>Common Errors .....</b>	<b>372</b>

# Welcome

Amazon Compute Optimizer is a service that analyzes the configuration and utilization metrics of your Amazon compute resources, such as Amazon EC2 instances, Amazon EC2 Auto Scaling groups, Amazon Lambda functions, Amazon EBS volumes, and Amazon ECS services on Fargate. It reports whether your resources are optimal, and generates optimization recommendations to reduce the cost and improve the performance of your workloads. Compute Optimizer also provides recent utilization metric data, in addition to projected utilization metric data for the recommendations, which you can use to evaluate which recommendation provides the best price-performance trade-off. The analysis of your usage patterns can help you decide when to move or resize your running resources, and still meet your performance and capacity requirements. For more information about Compute Optimizer, including the required permissions to use the service, see the [Amazon Compute Optimizer User Guide](#).

This document was last published on July 3, 2025.

# Actions

The following actions are supported:

- [DeleteRecommendationPreferences](#)
- [DescribeRecommendationExportJobs](#)
- [ExportAutoScalingGroupRecommendations](#)
- [ExportEBSVolumeRecommendations](#)
- [ExportEC2InstanceRecommendations](#)
- [ExportECSServiceRecommendations](#)
- [ExportIdleRecommendations](#)
- [ExportLambdaFunctionRecommendations](#)
- [ExportLicenseRecommendations](#)
- [ExportRDSDatabaseRecommendations](#)
- [GetAutoScalingGroupRecommendations](#)
- [GetEBSVolumeRecommendations](#)
- [GetEC2InstanceRecommendations](#)
- [GetEC2RecommendationProjectedMetrics](#)
- [GetECSServiceRecommendationProjectedMetrics](#)
- [GetECSServiceRecommendations](#)
- [GetEffectiveRecommendationPreferences](#)
- [GetEnrollmentStatus](#)
- [GetEnrollmentStatusesForOrganization](#)
- [GetIdleRecommendations](#)
- [GetLambdaFunctionRecommendations](#)
- [GetLicenseRecommendations](#)
- [GetRDSDatabaseRecommendationProjectedMetrics](#)
- [GetRDSDatabaseRecommendations](#)
- [GetRecommendationPreferences](#)
- [GetRecommendationSummaries](#)
- [PutRecommendationPreferences](#)

- [UpdateEnrollmentStatus](#)

# DeleteRecommendationPreferences

Deletes a recommendation preference, such as enhanced infrastructure metrics.

For more information, see [Activating enhanced infrastructure metrics](#) in the *Amazon Compute Optimizer User Guide*.

## Request Syntax

```
{  
    "recommendationPreferenceNames": [ "string" ],  
    "resourceType": "string",  
    "scope": {  
        "name": "string",  
        "value": "string"  
    }  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### recommendationPreferenceNames

The name of the recommendation preference to delete.

Type: Array of strings

Valid Values: EnhancedInfrastructureMetrics | InferredWorkloadTypes  
| ExternalMetricsPreference | LookBackPeriodPreference |  
PreferredResources | UtilizationPreferences

Required: Yes

### resourceType

The target resource type of the recommendation preference to delete.

The Ec2Instance option encompasses standalone instances and instances that are part of Auto Scaling groups. The AutoScalingGroup option encompasses only instances that are part of an Auto Scaling group.

Type: String

Valid Values: Ec2Instance | AutoScalingGroup | RdsDBInstance | AuroraDBClusterStorage

Required: Yes

### scope

An object that describes the scope of the recommendation preference to delete.

You can delete recommendation preferences that are created at the organization level (for management accounts of an organization only), account level, and resource level. For more information, see [Activating enhanced infrastructure metrics](#) in the *Amazon Compute Optimizer User Guide*.

Type: [Scope](#) object

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerError**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

### **OptInRequiredException**

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

### **ResourceNotFoundException**

A resource that is required for the action doesn't exist.

HTTP Status Code: 400

### **ServiceUnavailableException**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

### **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DescribeRecommendationExportJobs

Describes recommendation export jobs created in the last seven days.

Use the [ExportAutoScalingGroupRecommendations](#) or [ExportEC2InstanceRecommendations](#) actions to request an export of your recommendations. Then use the [DescribeRecommendationExportJobs](#) action to view your export jobs.

## Request Syntax

```
{  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "jobIds": [ "string" ],  
    "maxResults": number,  
    "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [filters](#)

An array of objects to specify a filter that returns a more specific list of export jobs.

Type: Array of [JobFilter](#) objects

Required: No

### [jobIds](#)

The identification numbers of the export jobs to return.

An export job ID is returned when you create an export using the [ExportAutoScalingGroupRecommendations](#) or [ExportEC2InstanceRecommendations](#) actions.

All export jobs created in the last seven days are returned if this parameter is omitted.

Type: Array of strings

Required: No

### maxResults

The maximum number of export jobs to return with a single request.

To retrieve the remaining results, make another request with the returned nextToken value.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000.

Required: No

### nextToken

The token to advance to the next page of export jobs.

Type: String

Required: No

## Response Syntax

```
{  
    "nextToken": "string",  
    "recommendationExportJobs": [  
        {  
            "creationTimestamp": number,  
            "destination": {  
                "s3": {  
                    "bucket": "string",  
                    "key": "string",  
                    "metadataKey": "string"  
                }  
            },  
            "failureReason": "string",  
            "jobId": "string",  
            "lastUpdatedTimestamp": number,  
            "resourceType": "string",  
        }  
    ]  
}
```

```
        "status": "string"
    }
]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [nextToken](#)

The token to use to advance to the next page of export jobs.

This value is null when there are no more pages of export jobs to return.

Type: String

### [recommendationExportJobs](#)

An array of objects that describe recommendation export jobs.

Type: Array of [RecommendationExportJob](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerError**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

### **OptInRequiredException**

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

### **ResourceNotFoundException**

A resource that is required for the action doesn't exist.

HTTP Status Code: 400

### **ServiceUnavailableException**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

### **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# ExportAutoScalingGroupRecommendations

Exports optimization recommendations for Auto Scaling groups.

Recommendations are exported in a comma-separated values (.csv) file, and its metadata in a JavaScript Object Notation (JSON) (.json) file, to an existing Amazon Simple Storage Service (Amazon S3) bucket that you specify. For more information, see [Exporting Recommendations](#) in the *Compute Optimizer User Guide*.

You can have only one Auto Scaling group export job in progress per Amazon Region.

## Request Syntax

```
{  
    "accountIds": [ "string" ],  
    "fieldsToExport": [ "string" ],  
    "fileFormat": "string",  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "includeMemberAccounts": boolean,  
    "recommendationPreferences": {  
        "cpuVendorArchitectures": [ "string" ]  
    },  
    "s3DestinationConfig": {  
        "bucket": "string",  
        "keyPrefix": "string"  
    }  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### accountIds

The IDs of the Amazon accounts for which to export Auto Scaling group recommendations.

If your account is the management account of an organization, use this parameter to specify the member account for which you want to export recommendations.

This parameter cannot be specified together with the include member accounts parameter. The parameters are mutually exclusive.

Recommendations for member accounts are not included in the export if this parameter, or the include member accounts parameter, is omitted.

You can specify multiple account IDs per request.

Type: Array of strings

Required: No

### fieldsToExport

The recommendations data to include in the export file. For more information about the fields that can be exported, see [Exported files](#) in the *Compute Optimizer User Guide*.

Type: Array of strings

Valid Values: AccountId | AutoScalingGroupArn | AutoScalingGroupName | Finding | UtilizationMetricsCpuMaximum | UtilizationMetricsMemoryMaximum | UtilizationMetricsEbsReadOpsPerSecondMaximum | UtilizationMetricsEbsWriteOpsPerSecondMaximum | UtilizationMetricsEbsReadBytesPerSecondMaximum | UtilizationMetricsEbsWriteBytesPerSecondMaximum | UtilizationMetricsDiskReadOpsPerSecondMaximum | UtilizationMetricsDiskWriteOpsPerSecondMaximum | UtilizationMetricsDiskReadBytesPerSecondMaximum | UtilizationMetricsDiskWriteBytesPerSecondMaximum | UtilizationMetricsNetworkInBytesPerSecondMaximum | UtilizationMetricsNetworkOutBytesPerSecondMaximum | UtilizationMetricsNetworkPacketsInPerSecondMaximum | UtilizationMetricsNetworkPacketsOutPerSecondMaximum | LookbackPeriodInDays | CurrentConfigurationInstanceType | CurrentConfigurationDesiredCapacity | CurrentConfigurationMinSize | CurrentConfigurationMaxSize | CurrentConfigurationAllocationStrategy | CurrentConfigurationMixedInstanceTypes | CurrentConfigurationType | CurrentOnDemandPrice | CurrentStandardOneYearNoUpfrontReservedPrice

```
| CurrentStandardThreeYearNoUpfrontReservedPrice |
CurrentVCPUs | CurrentMemory | CurrentStorage | CurrentNetwork
| RecommendationOptionsConfigurationInstanceType |
RecommendationOptionsConfigurationDesiredCapacity
| RecommendationOptionsConfigurationMinSize |
RecommendationOptionsConfigurationMaxSize |
RecommendationOptionsConfigurationEstimatedInstanceHourReductionPercentage
| RecommendationOptionsConfigurationAllocationStrategy
| RecommendationOptionsConfigurationMixedInstanceTypes |
RecommendationOptionsConfigurationType |
RecommendationOptionsProjectedUtilizationMetricsCpuMaximum |
RecommendationOptionsProjectedUtilizationMetricsMemoryMaximum |
RecommendationOptionsPerformanceRisk |
RecommendationOptionsOnDemandPrice |
RecommendationOptionsStandardOneYearNoUpfrontReservedPrice |
RecommendationOptionsStandardThreeYearNoUpfrontReservedPrice
| RecommendationOptionsVCPUs | RecommendationOptionsMemory |
RecommendationOptionsStorage | RecommendationOptionsNetwork
| LastRefreshTimestamp | CurrentPerformanceRisk |
RecommendationOptionsSavingsOpportunityPercentage |
RecommendationOptionsEstimatedMonthlySavingsCurrency
| RecommendationOptionsEstimatedMonthlySavingsValue |
EffectiveRecommendationPreferencesCpuVendorArchitectures |
EffectiveRecommendationPreferencesEnhancedInfrastructureMetrics
| EffectiveRecommendationPreferencesInferredWorkloadTypes
| EffectiveRecommendationPreferencesPreferredResources
| EffectiveRecommendationPreferencesLookBackPeriod |
InferredWorkloadTypes | RecommendationOptionsMigrationEffort |
CurrentInstanceGpuInfo | RecommendationOptionsInstanceGpuInfo |
UtilizationMetricsGpuPercentageMaximum |
UtilizationMetricsGpuMemoryPercentageMaximum |
RecommendationOptionsProjectedUtilizationMetricsGpuPercentageMaximum |
RecommendationOptionsProjectedUtilizationMetricsGpuMemoryPercentageMaximum
| EffectiveRecommendationPreferencesSavingsEstimationMode |
RecommendationOptionsSavingsOpportunityAfterDiscountsPercentage |
```

RecommendationOptionsEstimatedMonthlySavingsCurrencyAfterDiscounts |  
RecommendationOptionsEstimatedMonthlySavingsValueAfterDiscounts

Required: No

### fileFormat

The format of the export file.

The only export file format currently supported is Csv.

Type: String

Valid Values: Csv

Required: No

### filters

An array of objects to specify a filter that exports a more specific set of Auto Scaling group recommendations.

Type: Array of [Filter](#) objects

Required: No

### includeMemberAccounts

Indicates whether to include recommendations for resources in all member accounts of the organization if your account is the management account of an organization.

The member accounts must also be opted in to Compute Optimizer, and trusted access for Compute Optimizer must be enabled in the organization account. For more information, see [Compute Optimizer and Amazon Organizations trusted access](#) in the *Amazon Compute Optimizer User Guide*.

Recommendations for member accounts of the organization are not included in the export file if this parameter is omitted.

This parameter cannot be specified together with the account IDs parameter. The parameters are mutually exclusive.

Recommendations for member accounts are not included in the export if this parameter, or the account IDs parameter, is omitted.

Type: Boolean

Required: No

### [recommendationPreferences](#)

An object to specify the preferences for the Auto Scaling group recommendations to export.

Type: [RecommendationPreferences](#) object

Required: No

### [s3DestinationConfig](#)

An object to specify the destination Amazon Simple Storage Service (Amazon S3) bucket name and key prefix for the export job.

You must create the destination Amazon S3 bucket for your recommendations export before you create the export job. Compute Optimizer does not create the S3 bucket for you. After you create the S3 bucket, ensure that it has the required permissions policy to allow Compute Optimizer to write the export file to it. If you plan to specify an object prefix when you create the export job, you must include the object prefix in the policy that you add to the S3 bucket. For more information, see [Amazon S3 Bucket Policy for Compute Optimizer](#) in the *Compute Optimizer User Guide*.

Type: [S3DestinationConfig](#) object

Required: Yes

## Response Syntax

```
{  
    "jobId": "string",  
    "s3Destination": {  
        "bucket": "string",  
        "key": "string",  
        "metadataKey": "string"  
    }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## **jobId**

The identification number of the export job.

Use the [DescribeRecommendationExportJobs](#) action, and specify the job ID to view the status of an export job.

Type: String

## **s3Destination**

An object that describes the destination Amazon S3 bucket of a recommendations export file.

Type: [S3Destination](#) object

# Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

## **InternalServerError**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

## **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

## **LimitExceededException**

The request exceeds a limit of the service.

HTTP Status Code: 400

## MissingAuthenticationToken

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

## OptInRequiredException

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

## ServiceUnavailableException

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# ExportEBSVolumeRecommendations

Exports optimization recommendations for Amazon EBS volumes.

Recommendations are exported in a comma-separated values (.csv) file, and its metadata in a JavaScript Object Notation (JSON) (.json) file, to an existing Amazon Simple Storage Service (Amazon S3) bucket that you specify. For more information, see [Exporting Recommendations](#) in the *Compute Optimizer User Guide*.

You can have only one Amazon EBS volume export job in progress per Amazon Region.

## Request Syntax

```
{  
    "accountIds": [ "string" ],  
    "fieldsToExport": [ "string" ],  
    "fileFormat": "string",  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "includeMemberAccounts": boolean,  
    "s3DestinationConfig": {  
        "bucket": "string",  
        "keyPrefix": "string"  
    }  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### accountIds

The IDs of the Amazon accounts for which to export Amazon EBS volume recommendations.

If your account is the management account of an organization, use this parameter to specify the member account for which you want to export recommendations.

This parameter cannot be specified together with the include member accounts parameter. The parameters are mutually exclusive.

Recommendations for member accounts are not included in the export if this parameter, or the include member accounts parameter, is omitted.

You can specify multiple account IDs per request.

Type: Array of strings

Required: No

### **fieldsToExport**

The recommendations data to include in the export file. For more information about the fields that can be exported, see [Exported files](#) in the *Compute Optimizer User Guide*.

Type: Array of strings

Valid Values: AccountId | VolumeArn | Finding | UtilizationMetricsVolumeReadOpsPerSecondMaximum | UtilizationMetricsVolumeWriteOpsPerSecondMaximum | UtilizationMetricsVolumeReadBytesPerSecondMaximum | UtilizationMetricsVolumeWriteBytesPerSecondMaximum | LookbackPeriodInDays | CurrentConfigurationVolumeType | CurrentConfigurationVolumeBaselineIOPS | CurrentConfigurationVolumeBaselineThroughput | CurrentConfigurationVolumeBurstIOPS | CurrentConfigurationVolumeBurstThroughput | CurrentConfigurationVolumeSize | CurrentMonthlyPrice | RecommendationOptionsConfigurationVolumeType | RecommendationOptionsConfigurationVolumeBaselineIOPS | RecommendationOptionsConfigurationVolumeBaselineThroughput | RecommendationOptionsConfigurationVolumeBurstIOPS | RecommendationOptionsConfigurationVolumeBurstThroughput | RecommendationOptionsConfigurationVolumeSize | RecommendationOptionsMonthlyPrice | RecommendationOptionsPerformanceRisk | LastRefreshTimestamp | CurrentPerformanceRisk | RecommendationOptionsSavingsOpportunityPercentage | RecommendationOptionsEstimatedMonthlySavingsCurrency

```
| RecommendationOptionsEstimatedMonthlySavingsValue |  
Tags | RootVolume | CurrentConfigurationRootVolume |  
EffectiveRecommendationPreferencesSavingsEstimationMode |  
RecommendationOptionsSavingsOpportunityAfterDiscountsPercentage |  
RecommendationOptionsEstimatedMonthlySavingsCurrencyAfterDiscounts |  
RecommendationOptionsEstimatedMonthlySavingsValueAfterDiscounts
```

Required: No

### fileFormat

The format of the export file.

The only export file format currently supported is Csv.

Type: String

Valid Values: Csv

Required: No

### filters

An array of objects to specify a filter that exports a more specific set of Amazon EBS volume recommendations.

Type: Array of [EBSFilter](#) objects

Required: No

### includeMemberAccounts

Indicates whether to include recommendations for resources in all member accounts of the organization if your account is the management account of an organization.

The member accounts must also be opted in to Compute Optimizer, and trusted access for Compute Optimizer must be enabled in the organization account. For more information, see [Compute Optimizer and Amazon Organizations trusted access](#) in the *Amazon Compute Optimizer User Guide*.

Recommendations for member accounts of the organization are not included in the export file if this parameter is omitted.

This parameter cannot be specified together with the account IDs parameter. The parameters are mutually exclusive.

Recommendations for member accounts are not included in the export if this parameter, or the account IDs parameter, is omitted.

Type: Boolean

Required: No

### **s3DestinationConfig**

Describes the destination Amazon Simple Storage Service (Amazon S3) bucket name and key prefix for a recommendations export job.

You must create the destination Amazon S3 bucket for your recommendations export before you create the export job. Compute Optimizer does not create the S3 bucket for you. After you create the S3 bucket, ensure that it has the required permission policy to allow Compute Optimizer to write the export file to it. If you plan to specify an object prefix when you create the export job, you must include the object prefix in the policy that you add to the S3 bucket. For more information, see [Amazon S3 Bucket Policy for Compute Optimizer](#) in the *Compute Optimizer User Guide*.

Type: [S3DestinationConfig](#) object

Required: Yes

## **Response Syntax**

```
{  
    "jobId": "string",  
    "s3Destination": {  
        "bucket": "string",  
        "key": "string",  
        "metadataKey": "string"  
    }  
}
```

## **Response Elements**

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **jobId**

The identification number of the export job.

Use the [DescribeRecommendationExportJobs](#) action, and specify the job ID to view the status of an export job.

Type: String

### **s3Destination**

Describes the destination Amazon Simple Storage Service (Amazon S3) bucket name and object keys of a recommendations export file, and its associated metadata file.

Type: [S3Destination](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerError**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### **LimitExceededException**

The request exceeds a limit of the service.

HTTP Status Code: 400

## MissingAuthenticationToken

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

## OptInRequiredException

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

## ServiceUnavailableException

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# ExportEC2InstanceRecommendations

Exports optimization recommendations for Amazon EC2 instances.

Recommendations are exported in a comma-separated values (.csv) file, and its metadata in a JavaScript Object Notation (JSON) (.json) file, to an existing Amazon Simple Storage Service (Amazon S3) bucket that you specify. For more information, see [Exporting Recommendations](#) in the *Compute Optimizer User Guide*.

You can have only one Amazon EC2 instance export job in progress per Amazon Region.

## Request Syntax

```
{  
    "accountIds": [ "string" ],  
    "fieldsToExport": [ "string" ],  
    "fileFormat": "string",  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "includeMemberAccounts": boolean,  
    "recommendationPreferences": {  
        "cpuVendorArchitectures": [ "string" ]  
    },  
    "s3DestinationConfig": {  
        "bucket": "string",  
        "keyPrefix": "string"  
    }  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### accountIds

The IDs of the Amazon accounts for which to export instance recommendations.

If your account is the management account of an organization, use this parameter to specify the member account for which you want to export recommendations.

This parameter cannot be specified together with the include member accounts parameter. The parameters are mutually exclusive.

Recommendations for member accounts are not included in the export if this parameter, or the include member accounts parameter, is omitted.

You can specify multiple account IDs per request.

Type: Array of strings

Required: No

### fieldsToExport

The recommendations data to include in the export file. For more information about the fields that can be exported, see [Exported files](#) in the *Compute Optimizer User Guide*.

Type: Array of strings

Valid Values: AccountId | InstanceArn | InstanceName | Finding | FindingReasonCodes | LookbackPeriodInDays | CurrentInstanceType | UtilizationMetricsCpuMaximum | UtilizationMetricsMemoryMaximum | UtilizationMetricsEbsReadOpsPerSecondMaximum | UtilizationMetricsEbsWriteOpsPerSecondMaximum | UtilizationMetricsEbsReadBytesPerSecondMaximum | UtilizationMetricsEbsWriteBytesPerSecondMaximum | UtilizationMetricsDiskReadOpsPerSecondMaximum | UtilizationMetricsDiskWriteOpsPerSecondMaximum | UtilizationMetricsDiskReadBytesPerSecondMaximum | UtilizationMetricsDiskWriteBytesPerSecondMaximum | UtilizationMetricsNetworkInBytesPerSecondMaximum | UtilizationMetricsNetworkOutBytesPerSecondMaximum | UtilizationMetricsNetworkPacketsInPerSecondMaximum | UtilizationMetricsNetworkPacketsOutPerSecondMaximum | CurrentOnDemandPrice | CurrentStandardOneYearNoUpfrontReservedPrice | CurrentStandardThreeYearNoUpfrontReservedPrice | CurrentVCpus | CurrentMemory | CurrentStorage | CurrentNetwork | RecommendationOptionsInstanceType |

```
RecommendationOptionsProjectedUtilizationMetricsCpuMaximum |  
RecommendationOptionsProjectedUtilizationMetricsMemoryMaximum |  
RecommendationOptionsPlatformDifferences |  
RecommendationOptionsPerformanceRisk | RecommendationOptionsVcpus  
| RecommendationOptionsMemory | RecommendationOptionsStorage |  
RecommendationOptionsNetwork | RecommendationOptionsOnDemandPrice  
| RecommendationOptionsStandardOneYearNoUpfrontReservedPrice  
| RecommendationOptionsStandardThreeYearNoUpfrontReservedPrice  
| RecommendationsSourcesRecommendationSourceArn  
| RecommendationsSourcesRecommendationSourceType  
| LastRefreshTimestamp | CurrentPerformanceRisk |  
RecommendationOptionsSavingsOpportunityPercentage |  
RecommendationOptionsEstimatedMonthlySavingsCurrency  
| RecommendationOptionsEstimatedMonthlySavingsValue |  
EffectiveRecommendationPreferencesCpuVendorArchitectures |  
EffectiveRecommendationPreferencesEnhancedInfrastructureMetrics  
| EffectiveRecommendationPreferencesInferredWorkloadTypes |  
InferredWorkloadTypes | RecommendationOptionsMigrationEffort |  
EffectiveRecommendationPreferencesExternalMetricsSource | Tags |  
InstanceState | ExternalMetricStatusCode | ExternalMetricStatusReason  
| CurrentInstanceGpuInfo | RecommendationOptionsInstanceGpuInfo |  
UtilizationMetricsGpuPercentageMaximum |  
UtilizationMetricsGpuMemoryPercentageMaximum |  
RecommendationOptionsProjectedUtilizationMetricsGpuPercentageMaximum |  
RecommendationOptionsProjectedUtilizationMetricsGpuMemoryPercentageMaximum  
| Idle | EffectiveRecommendationPreferencesPreferredResources  
| EffectiveRecommendationPreferencesLookBackPeriod |  
EffectiveRecommendationPreferencesUtilizationPreferences |  
EffectiveRecommendationPreferencesSavingsEstimationMode |  
RecommendationOptionsSavingsOpportunityAfterDiscountsPercentage |  
RecommendationOptionsEstimatedMonthlySavingsCurrencyAfterDiscounts |  
RecommendationOptionsEstimatedMonthlySavingsValueAfterDiscounts
```

Required: No

### fileFormat

The format of the export file.

The only export file format currently supported is Csv.

Type: String

Valid Values: Csv

Required: No

### filters

An array of objects to specify a filter that exports a more specific set of instance recommendations.

Type: Array of [Filter](#) objects

Required: No

### includeMemberAccounts

Indicates whether to include recommendations for resources in all member accounts of the organization if your account is the management account of an organization.

The member accounts must also be opted in to Compute Optimizer, and trusted access for Compute Optimizer must be enabled in the organization account. For more information, see [Compute Optimizer and Amazon Organizations trusted access](#) in the *Amazon Compute Optimizer User Guide*.

Recommendations for member accounts of the organization are not included in the export file if this parameter is omitted.

Recommendations for member accounts are not included in the export if this parameter, or the account IDs parameter, is omitted.

Type: Boolean

Required: No

### recommendationPreferences

An object to specify the preferences for the Amazon EC2 instance recommendations to export.

Type: [RecommendationPreferences](#) object

Required: No

## s3DestinationConfig

An object to specify the destination Amazon Simple Storage Service (Amazon S3) bucket name and key prefix for the export job.

You must create the destination Amazon S3 bucket for your recommendations export before you create the export job. Compute Optimizer does not create the S3 bucket for you. After you create the S3 bucket, ensure that it has the required permissions policy to allow Compute Optimizer to write the export file to it. If you plan to specify an object prefix when you create the export job, you must include the object prefix in the policy that you add to the S3 bucket. For more information, see [Amazon S3 Bucket Policy for Compute Optimizer](#) in the *Compute Optimizer User Guide*.

Type: [S3DestinationConfig](#) object

Required: Yes

## Response Syntax

```
{  
    "jobId": "string",  
    "s3Destination": {  
        "bucket": "string",  
        "key": "string",  
        "metadataKey": "string"  
    }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### jobId

The identification number of the export job.

Use the [DescribeRecommendationExportJobs](#) action, and specify the job ID to view the status of an export job.

Type: String

## s3Destination

An object that describes the destination Amazon S3 bucket of a recommendations export file.

Type: [S3Destination](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerException**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### **LimitExceededException**

The request exceeds a limit of the service.

HTTP Status Code: 400

### **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

### **OptInRequiredException**

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

## ServiceUnavailableException

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# ExportECSServiceRecommendations

Exports optimization recommendations for Amazon ECS services on Fargate.

Recommendations are exported in a CSV file, and its metadata in a JSON file, to an existing Amazon Simple Storage Service (Amazon S3) bucket that you specify. For more information, see [Exporting Recommendations](#) in the *Compute Optimizer User Guide*.

You can only have one Amazon ECS service export job in progress per Amazon Web Services Region.

## Request Syntax

```
{  
    "accountIds": [ "string" ],  
    "fieldsToExport": [ "string" ],  
    "fileFormat": "string",  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "includeMemberAccounts": boolean,  
    "s3DestinationConfig": {  
        "bucket": "string",  
        "keyPrefix": "string"  
    }  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### accountIds

The Amazon Web Services account IDs for the export Amazon ECS service recommendations.

If your account is the management account or the delegated administrator of an organization, use this parameter to specify the member account you want to export recommendations to.

This parameter can't be specified together with the include member accounts parameter. The parameters are mutually exclusive.

If this parameter or the include member accounts parameter is omitted, the recommendations for member accounts aren't included in the export.

You can specify multiple account IDs per request.

Type: Array of strings

Required: No

### fieldsToExport

The recommendations data to include in the export file. For more information about the fields that can be exported, see [Exported files](#) in the *Compute Optimizer User Guide*.

Type: Array of strings

Valid Values: AccountId | ServiceArn | LookbackPeriodInDays | LastRefreshTimestamp | LaunchType | CurrentPerformanceRisk | CurrentServiceConfigurationMemory | CurrentServiceConfigurationCpu | CurrentServiceConfigurationTaskDefinitionArn | CurrentServiceConfigurationAutoScalingConfiguration | CurrentServiceContainerConfigurations | UtilizationMetricsCpuMaximum | UtilizationMetricsMemoryMaximum | Finding | FindingReasonCodes | RecommendationOptionsMemory | RecommendationOptionsCpu | RecommendationOptionsSavingsOpportunityPercentage | RecommendationOptionsEstimatedMonthlySavingsCurrency | RecommendationOptionsEstimatedMonthlySavingsValue | RecommendationOptionsContainerRecommendations | RecommendationOptionsProjectedUtilizationMetricsCpuMaximum | RecommendationOptionsProjectedUtilizationMetricsMemoryMaximum | Tags | EffectiveRecommendationPreferencesSavingsEstimationMode | RecommendationOptionsSavingsOpportunityAfterDiscountsPercentage | RecommendationOptionsEstimatedMonthlySavingsCurrencyAfterDiscounts | RecommendationOptionsEstimatedMonthlySavingsValueAfterDiscounts

Required: No

## fileFormat

The format of the export file.

The CSV file is the only export file format currently supported.

Type: String

Valid Values: Csv

Required: No

## filters

An array of objects to specify a filter that exports a more specific set of Amazon ECS service recommendations.

Type: Array of [ECSServiceRecommendationFilter](#) objects

Required: No

## includeMemberAccounts

If your account is the management account or the delegated administrator of an organization, this parameter indicates whether to include recommendations for resources in all member accounts of the organization.

The member accounts must also be opted in to Compute Optimizer, and trusted access for Compute Optimizer must be enabled in the organization account. For more information, see [Compute Optimizer and Amazon Organizations trusted access](#) in the *Amazon Compute Optimizer User Guide*.

If this parameter is omitted, recommendations for member accounts of the organization aren't included in the export file.

If this parameter or the account ID parameter is omitted, recommendations for member accounts aren't included in the export.

Type: Boolean

Required: No

## s3DestinationConfig

Describes the destination Amazon Simple Storage Service (Amazon S3) bucket name and key prefix for a recommendations export job.

You must create the destination Amazon S3 bucket for your recommendations export before you create the export job. Compute Optimizer does not create the S3 bucket for you. After you create the S3 bucket, ensure that it has the required permission policy to allow Compute Optimizer to write the export file to it. If you plan to specify an object prefix when you create the export job, you must include the object prefix in the policy that you add to the S3 bucket. For more information, see [Amazon S3 Bucket Policy for Compute Optimizer](#) in the *Compute Optimizer User Guide*.

Type: [S3DestinationConfig](#) object

Required: Yes

## Response Syntax

```
{  
    "jobId": "string",  
    "s3Destination": {  
        "bucket": "string",  
        "key": "string",  
        "metadataKey": "string"  
    }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### jobId

The identification number of the export job.

To view the status of an export job, use the [DescribeRecommendationExportJobs](#) action and specify the job ID.

Type: String

### s3Destination

Describes the destination Amazon Simple Storage Service (Amazon S3) bucket name and object keys of a recommendations export file, and its associated metadata file.

Type: [S3Destination](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerException**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### **LimitExceededException**

The request exceeds a limit of the service.

HTTP Status Code: 400

### **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

### **OptInRequiredException**

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

### **ServiceUnavailableException**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# ExportIdleRecommendations

Export optimization recommendations for your idle resources.

Recommendations are exported in a comma-separated values (CSV) file, and its metadata in a JavaScript Object Notation (JSON) file, to an existing Amazon Simple Storage Service (Amazon S3) bucket that you specify. For more information, see [Exporting Recommendations](#) in the *Compute Optimizer User Guide*.

You can have only one idle resource export job in progress per Amazon Region.

## Request Syntax

```
{  
    "accountIds": [ "string" ],  
    "fieldsToExport": [ "string" ],  
    "fileFormat": "string",  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "includeMemberAccounts": boolean,  
    "s3DestinationConfig": {  
        "bucket": "string",  
        "keyPrefix": "string"  
    }  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### accountIds

The Amazon Web Services account IDs for the export idle resource recommendations.

If your account is the management account or the delegated administrator of an organization, use this parameter to specify the member account you want to export recommendations to.

This parameter can't be specified together with the include member accounts parameter. The parameters are mutually exclusive.

If this parameter or the include member accounts parameter is omitted, the recommendations for member accounts aren't included in the export.

You can specify multiple account IDs per request.

Type: Array of strings

Required: No

### [fieldsToExport](#)

The recommendations data to include in the export file. For more information about the fields that can be exported, see [Exported files](#) in the *Compute Optimizer User Guide*.

Type: Array of strings

Valid Values: AccountId | ResourceArn | ResourceId |  
ResourceType | LastRefreshTimestamp | LookbackPeriodInDays  
| SavingsOpportunity | SavingsOpportunityAfterDiscount |  
UtilizationMetricsCpuMaximum | UtilizationMetricsMemoryMaximum  
| UtilizationMetricsNetworkOutBytesPerSecondMaximum  
| UtilizationMetricsNetworkInBytesPerSecondMaximum  
| UtilizationMetricsDatabaseConnectionsMaximum  
| UtilizationMetricsEBSVolumeReadIOPSMaximum |  
UtilizationMetricsEBSVolumeWriteIOPSMaximum |  
UtilizationMetricsVolumeReadOpsPerSecondMaximum |  
UtilizationMetricsVolumeWriteOpsPerSecondMaximum | Finding |  
FindingDescription | Tags

Required: No

### [fileFormat](#)

The format of the export file. The CSV file is the only export file format currently supported.

Type: String

Valid Values: Csv

Required: No

## filters

An array of objects to specify a filter that exports a more specific set of idle resource recommendations.

Type: Array of [IdleRecommendationFilter](#) objects

Required: No

## includeMemberAccounts

If your account is the management account or the delegated administrator of an organization, this parameter indicates whether to include recommendations for resources in all member accounts of the organization.

The member accounts must also be opted in to Compute Optimizer, and trusted access for Compute Optimizer must be enabled in the organization account. For more information, see [Compute Optimizer and Amazon Organizations trusted access](#) in the *Amazon Compute Optimizer User Guide*.

If this parameter is omitted, recommendations for member accounts of the organization aren't included in the export file.

If this parameter or the account ID parameter is omitted, recommendations for member accounts aren't included in the export.

Type: Boolean

Required: No

## s3DestinationConfig

Describes the destination Amazon Simple Storage Service (Amazon S3) bucket name and key prefix for a recommendations export job.

You must create the destination Amazon S3 bucket for your recommendations export before you create the export job. Compute Optimizer does not create the S3 bucket for you. After you create the S3 bucket, ensure that it has the required permission policy to allow Compute Optimizer to write the export file to it. If you plan to specify an object prefix when you create the export job, you must include the object prefix in the policy that you add to the S3 bucket. For more information, see [Amazon S3 Bucket Policy for Compute Optimizer](#) in the *Compute Optimizer User Guide*.

Type: [S3DestinationConfig object](#)

Required: Yes

## Response Syntax

```
{  
    "jobId": "string",  
    "s3Destination": {  
        "bucket": "string",  
        "key": "string",  
        "metadataKey": "string"  
    }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [jobId](#)

The identification number of the export job.

To view the status of an export job, use the [DescribeRecommendationExportJobs](#) action and specify the job ID.

Type: String

### [s3Destination](#)

Describes the destination Amazon Simple Storage Service (Amazon S3) bucket name and object keys of a recommendations export file, and its associated metadata file.

Type: [S3Destination object](#)

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

## **InternalServerException**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

## **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

## **LimitExceededException**

The request exceeds a limit of the service.

HTTP Status Code: 400

## **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

## **OptInRequiredException**

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

## **ServiceUnavailableException**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# ExportLambdaFunctionRecommendations

Exports optimization recommendations for Amazon Lambda functions.

Recommendations are exported in a comma-separated values (.csv) file, and its metadata in a JavaScript Object Notation (JSON) (.json) file, to an existing Amazon Simple Storage Service (Amazon S3) bucket that you specify. For more information, see [Exporting Recommendations](#) in the *Compute Optimizer User Guide*.

You can have only one Lambda function export job in progress per Amazon Region.

## Request Syntax

```
{  
    "accountIds": [ "string" ],  
    "fieldsToExport": [ "string" ],  
    "fileFormat": "string",  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "includeMemberAccounts": boolean,  
    "s3DestinationConfig": {  
        "bucket": "string",  
        "keyPrefix": "string"  
    }  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### accountIds

The IDs of the Amazon accounts for which to export Lambda function recommendations.

If your account is the management account of an organization, use this parameter to specify the member account for which you want to export recommendations.

This parameter cannot be specified together with the include member accounts parameter. The parameters are mutually exclusive.

Recommendations for member accounts are not included in the export if this parameter, or the include member accounts parameter, is omitted.

You can specify multiple account IDs per request.

Type: Array of strings

Required: No

### [fieldsToExport](#)

The recommendations data to include in the export file. For more information about the fields that can be exported, see [Exported files](#) in the *Compute Optimizer User Guide*.

Type: Array of strings

Valid Values: AccountId | FunctionArn | FunctionVersion | Finding | FindingReasonCodes | NumberOfInvocations | UtilizationMetricsDurationMaximum | UtilizationMetricsDurationAverage | UtilizationMetricsMemoryMaximum | UtilizationMetricsMemoryAverage | LookbackPeriodInDays | CurrentConfigurationMemorySize | CurrentConfigurationTimeout | CurrentCostTotal | CurrentCostAverage | RecommendationOptionsConfigurationMemorySize | RecommendationOptionsCostLow | RecommendationOptionsCostHigh | RecommendationOptionsProjectedUtilizationMetricsDurationLowerBound | RecommendationOptionsProjectedUtilizationMetricsDurationUpperBound | RecommendationOptionsProjectedUtilizationMetricsDurationExpected | LastRefreshTimestamp | CurrentPerformanceRisk | RecommendationOptionsSavingsOpportunityPercentage | RecommendationOptionsEstimatedMonthlySavingsCurrency | RecommendationOptionsEstimatedMonthlySavingsValue | Tags | EffectiveRecommendationPreferencesSavingsEstimationMode | RecommendationOptionsSavingsOpportunityAfterDiscountsPercentage | RecommendationOptionsEstimatedMonthlySavingsCurrencyAfterDiscounts | RecommendationOptionsEstimatedMonthlySavingsValueAfterDiscounts

Required: No

## fileFormat

The format of the export file.

The only export file format currently supported is Csv.

Type: String

Valid Values: Csv

Required: No

## filters

An array of objects to specify a filter that exports a more specific set of Lambda function recommendations.

Type: Array of [LambdaFunctionRecommendationFilter](#) objects

Required: No

## includeMemberAccounts

Indicates whether to include recommendations for resources in all member accounts of the organization if your account is the management account of an organization.

The member accounts must also be opted in to Compute Optimizer, and trusted access for Compute Optimizer must be enabled in the organization account. For more information, see [Compute Optimizer and Amazon Organizations trusted access](#) in the *Amazon Compute Optimizer User Guide*.

Recommendations for member accounts of the organization are not included in the export file if this parameter is omitted.

This parameter cannot be specified together with the account IDs parameter. The parameters are mutually exclusive.

Recommendations for member accounts are not included in the export if this parameter, or the account IDs parameter, is omitted.

Type: Boolean

Required: No

## s3DestinationConfig

Describes the destination Amazon Simple Storage Service (Amazon S3) bucket name and key prefix for a recommendations export job.

You must create the destination Amazon S3 bucket for your recommendations export before you create the export job. Compute Optimizer does not create the S3 bucket for you. After you create the S3 bucket, ensure that it has the required permission policy to allow Compute Optimizer to write the export file to it. If you plan to specify an object prefix when you create the export job, you must include the object prefix in the policy that you add to the S3 bucket. For more information, see [Amazon S3 Bucket Policy for Compute Optimizer](#) in the *Compute Optimizer User Guide*.

Type: [S3DestinationConfig](#) object

Required: Yes

## Response Syntax

```
{  
    "jobId": "string",  
    "s3Destination": {  
        "bucket": "string",  
        "key": "string",  
        "metadataKey": "string"  
    }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### jobId

The identification number of the export job.

Use the [DescribeRecommendationExportJobs](#) action, and specify the job ID to view the status of an export job.

Type: String

### **s3Destination**

Describes the destination Amazon Simple Storage Service (Amazon S3) bucket name and object keys of a recommendations export file, and its associated metadata file.

Type: [S3Destination](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerError**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### **LimitExceededException**

The request exceeds a limit of the service.

HTTP Status Code: 400

### **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

### **OptInRequiredException**

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

### **ServiceUnavailableException**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

### **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# ExportLicenseRecommendations

Export optimization recommendations for your licenses.

Recommendations are exported in a comma-separated values (CSV) file, and its metadata in a JavaScript Object Notation (JSON) file, to an existing Amazon Simple Storage Service (Amazon S3) bucket that you specify. For more information, see [Exporting Recommendations](#) in the *Compute Optimizer User Guide*.

You can have only one license export job in progress per Amazon Region.

## Request Syntax

```
{  
    "accountIds": [ "string" ],  
    "fieldsToExport": [ "string" ],  
    "fileFormat": "string",  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "includeMemberAccounts": boolean,  
    "s3DestinationConfig": {  
        "bucket": "string",  
        "keyPrefix": "string"  
    }  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### accountIds

The IDs of the Amazon accounts for which to export license recommendations.

If your account is the management account of an organization, use this parameter to specify the member account for which you want to export recommendations.

This parameter can't be specified together with the include member accounts parameter. The parameters are mutually exclusive.

If this parameter is omitted, recommendations for member accounts aren't included in the export.

You can specify multiple account IDs per request.

Type: Array of strings

Required: No

### [fieldsToExport](#)

The recommendations data to include in the export file. For more information about the fields that can be exported, see [Exported files](#) in the *Compute Optimizer User Guide*.

Type: Array of strings

Valid Values: AccountId | ResourceArn | LookbackPeriodInDays  
| LastRefreshTimestamp | Finding | FindingReasonCodes |  
CurrentLicenseConfigurationNumberOfCores |  
CurrentLicenseConfigurationInstanceType |  
CurrentLicenseConfigurationOperatingSystem |  
CurrentLicenseConfigurationLicenseName |  
CurrentLicenseConfigurationLicenseEdition |  
CurrentLicenseConfigurationLicenseModel |  
CurrentLicenseConfigurationLicenseVersion |  
CurrentLicenseConfigurationMetricsSource |  
RecommendationOptionsOperatingSystem |  
RecommendationOptionsLicenseEdition | RecommendationOptionsLicenseModel  
| RecommendationOptionsSavingsOpportunityPercentage |  
RecommendationOptionsEstimatedMonthlySavingsCurrency |  
RecommendationOptionsEstimatedMonthlySavingsValue | Tags

Required: No

### [fileFormat](#)

The format of the export file.

A CSV file is the only export format currently supported.

Type: String

Valid Values: Csv

Required: No

### [filters](#)

An array of objects to specify a filter that exports a more specific set of license recommendations.

Type: Array of [LicenseRecommendationFilter](#) objects

Required: No

### [includeMemberAccounts](#)

Indicates whether to include recommendations for resources in all member accounts of the organization if your account is the management account of an organization.

The member accounts must also be opted in to Compute Optimizer, and trusted access for Compute Optimizer must be enabled in the organization account. For more information, see [Compute Optimizer and Amazon Organizations trusted access](#) in the *Amazon Compute Optimizer User Guide*.

If this parameter is omitted, recommendations for member accounts of the organization aren't included in the export file .

This parameter cannot be specified together with the account IDs parameter. The parameters are mutually exclusive.

Type: Boolean

Required: No

### [s3DestinationConfig](#)

Describes the destination Amazon Simple Storage Service (Amazon S3) bucket name and key prefix for a recommendations export job.

You must create the destination Amazon S3 bucket for your recommendations export before you create the export job. Compute Optimizer does not create the S3 bucket for you. After you create the S3 bucket, ensure that it has the required permission policy to allow Compute

Optimizer to write the export file to it. If you plan to specify an object prefix when you create the export job, you must include the object prefix in the policy that you add to the S3 bucket. For more information, see [Amazon S3 Bucket Policy for Compute Optimizer](#) in the *Compute Optimizer User Guide*.

Type: [S3DestinationConfig](#) object

Required: Yes

## Response Syntax

```
{  
    "jobId": "string",  
    "s3Destination": {  
        "bucket": "string",  
        "key": "string",  
        "metadataKey": "string"  
    }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [jobId](#)

The identification number of the export job.

To view the status of an export job, use the [DescribeRecommendationExportJobs](#) action and specify the job ID.

Type: String

### [s3Destination](#)

Describes the destination Amazon Simple Storage Service (Amazon S3) bucket name and object keys of a recommendations export file, and its associated metadata file.

Type: [S3Destination](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### InternalServerException

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### InvalidParameterValueException

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### LimitExceededException

The request exceeds a limit of the service.

HTTP Status Code: 400

### MissingAuthenticationToken

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

### OptInRequiredException

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

### ServiceUnavailableException

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

### ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# ExportRDSDatabaseRecommendations

Export optimization recommendations for your Amazon Aurora and Amazon Relational Database Service (Amazon RDS) databases.

Recommendations are exported in a comma-separated values (CSV) file, and its metadata in a JavaScript Object Notation (JSON) file, to an existing Amazon Simple Storage Service (Amazon S3) bucket that you specify. For more information, see [Exporting Recommendations](#) in the *Compute Optimizer User Guide*.

You can have only one Amazon Aurora or RDS export job in progress per Amazon Region.

## Request Syntax

```
{  
    "accountIds": [ "string" ],  
    "fieldsToExport": [ "string" ],  
    "fileFormat": "string",  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "includeMemberAccounts": boolean,  
    "recommendationPreferences": {  
        "cpuVendorArchitectures": [ "string" ]  
    },  
    "s3DestinationConfig": {  
        "bucket": "string",  
        "keyPrefix": "string"  
    }  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

## accountIds

The Amazon Web Services account IDs for the export Amazon Aurora and RDS database recommendations.

If your account is the management account or the delegated administrator of an organization, use this parameter to specify the member account you want to export recommendations to.

This parameter can't be specified together with the include member accounts parameter. The parameters are mutually exclusive.

If this parameter or the include member accounts parameter is omitted, the recommendations for member accounts aren't included in the export.

You can specify multiple account IDs per request.

Type: Array of strings

Required: No

## fieldsToExport

The recommendations data to include in the export file. For more information about the fields that can be exported, see [Exported files](#) in the *Compute Optimizer User Guide*.

Type: Array of strings

Valid Values: ResourceArn | AccountId | Engine | EngineVersion | Idle | MultiAZDBInstance | ClusterWriter | CurrentDBInstanceState | CurrentStorageConfigurationStorageType | CurrentStorageConfigurationAllocatedStorage | CurrentStorageConfigurationMaxAllocatedStorage | CurrentStorageConfigurationIOPS | CurrentStorageConfigurationStorageThroughput | CurrentStorageEstimatedMonthlyVolumeIOPsCostVariation | CurrentInstanceOnDemandHourlyPrice | CurrentStorageOnDemandMonthlyPrice | LookbackPeriodInDays | CurrentStorageEstimatedClusterInstanceOnDemandMonthlyCost | CurrentStorageEstimatedClusterStorageOnDemandMonthlyCost | CurrentStorageEstimatedClusterStorageIOOnDemandMonthlyCost | CurrentInstancePerformanceRisk | UtilizationMetricsCpuMaximum | UtilizationMetricsMemoryMaximum |

```
UtilizationMetricsEBSSVolumeStorageSpaceUtilizationMaximum  
| UtilizationMetricsNetworkReceiveThroughputMaximum  
| UtilizationMetricsNetworkTransmitThroughputMaximum  
| UtilizationMetricsEBSSVolumeReadIOPSMaximum |  
UtilizationMetricsEBSSVolumeWriteIOPSMaximum |  
UtilizationMetricsEBSSVolumeReadThroughputMaximum |  
UtilizationMetricsEBSSVolumeWriteThroughputMaximum  
| UtilizationMetricsDatabaseConnectionsMaximum |  
UtilizationMetricsStorageNetworkReceiveThroughputMaximum |  
UtilizationMetricsStorageNetworkTransmitThroughputMaximum  
| UtilizationMetricsAuroraMemoryHealthStateMaximum |  
UtilizationMetricsAuroraMemoryNumDeclinedSqlTotalMaximum  
| UtilizationMetricsAuroraMemoryNumKillConnTotalMaximum  
| UtilizationMetricsAuroraMemoryNumKillQueryTotalMaximum  
| UtilizationMetricsReadIOPSEphemeralStorageMaximum |  
UtilizationMetricsWriteIOPSEphemeralStorageMaximum |  
UtilizationMetricsVolumeBytesUsedAverage |  
UtilizationMetricsVolumeReadIOPsAverage |  
UtilizationMetricsVolumeWriteIOPsAverage | InstanceFinding |  
InstanceFindingReasonCodes | StorageFinding | StorageFindingReasonCodes  
| InstanceRecommendationOptionsDBInstanceClass |  
InstanceRecommendationOptionsRank |  
InstanceRecommendationOptionsPerformanceRisk |  
InstanceRecommendationOptionsProjectedUtilizationMetricsCpuMaximum |  
StorageRecommendationOptionsStorageType |  
StorageRecommendationOptionsAllocatedStorage |  
StorageRecommendationOptionsMaxAllocatedStorage |  
StorageRecommendationOptionsIOPS |  
StorageRecommendationOptionsStorageThroughput |  
StorageRecommendationOptionsRank |  
StorageRecommendationOptionsEstimatedMonthlyVolumeIOPsCostVariation  
| InstanceRecommendationOptionsInstanceOnDemandHourlyPrice |  
InstanceRecommendationOptionsSavingsOpportunityPercentage |  
InstanceRecommendationOptionsEstimatedMonthlySavingsCurrency  
| InstanceRecommendationOptionsEstimatedMonthlySavingsValue |  
InstanceRecommendationOptionsSavingsOpportunityAfterDiscountsPercentage
```

```
|  
InstanceRecommendationOptionsEstimatedMonthlySavingsCurrencyAfterDiscounts  
|  
InstanceRecommendationOptionsEstimatedMonthlySavingsValueAfterDiscounts  
| StorageRecommendationOptionsOnDemandMonthlyPrice |  
StorageRecommendationOptionsEstimatedClusterInstanceOnDemandMonthlyCost  
| StorageRecommendationOptionsEstimatedClusterStorageOnDemandMonthlyCost  
|  
StorageRecommendationOptionsEstimatedClusterStorageIOOnDemandMonthlyCost  
| StorageRecommendationOptionsSavingsOpportunityPercentage |  
StorageRecommendationOptionsEstimatedMonthlySavingsCurrency  
| StorageRecommendationOptionsEstimatedMonthlySavingsValue |  
StorageRecommendationOptionsSavingsOpportunityAfterDiscountsPercentage |  
StorageRecommendationOptionsEstimatedMonthlySavingsCurrencyAfterDiscounts  
| StorageRecommendationOptionsEstimatedMonthlySavingsValueAfterDiscounts  
| EffectiveRecommendationPreferencesCpuVendorArchitectures |  
EffectiveRecommendationPreferencesEnhancedInfrastructureMetrics  
| EffectiveRecommendationPreferencesLookBackPeriod |  
EffectiveRecommendationPreferencesSavingsEstimationMode |  
LastRefreshTimestamp | Tags | DBClusterIdentifier | PromotionTier
```

Required: No

### fileFormat

The format of the export file.

The CSV file is the only export file format currently supported.

Type: String

Valid Values: Csv

Required: No

### filters

An array of objects to specify a filter that exports a more specific set of Amazon Aurora and RDS recommendations.

Type: Array of [RDSDBRecommendationFilter](#) objects

Required: No

### **includeMemberAccounts**

If your account is the management account or the delegated administrator of an organization, this parameter indicates whether to include recommendations for resources in all member accounts of the organization.

The member accounts must also be opted in to Compute Optimizer, and trusted access for Compute Optimizer must be enabled in the organization account. For more information, see [Compute Optimizer and Amazon Organizations trusted access](#) in the *Amazon Compute Optimizer User Guide*.

If this parameter is omitted, recommendations for member accounts of the organization aren't included in the export file.

If this parameter or the account ID parameter is omitted, recommendations for member accounts aren't included in the export.

Type: Boolean

Required: No

### **recommendationPreferences**

Describes the recommendation preferences to return in the response of a [GetAutoScalingGroupRecommendations](#), [GetEC2InstanceRecommendations](#), [GetEC2RecommendationProjectedMetrics](#), [GetRDSDatabaseRecommendations](#), and [GetRDSDatabaseRecommendationProjectedMetrics](#) request.

Type: [RecommendationPreferences](#) object

Required: No

### **s3DestinationConfig**

Describes the destination Amazon Simple Storage Service (Amazon S3) bucket name and key prefix for a recommendations export job.

You must create the destination Amazon S3 bucket for your recommendations export before you create the export job. Compute Optimizer does not create the S3 bucket for you. After you create the S3 bucket, ensure that it has the required permission policy to allow Compute

Optimizer to write the export file to it. If you plan to specify an object prefix when you create the export job, you must include the object prefix in the policy that you add to the S3 bucket. For more information, see [Amazon S3 Bucket Policy for Compute Optimizer](#) in the *Compute Optimizer User Guide*.

Type: [S3DestinationConfig](#) object

Required: Yes

## Response Syntax

```
{  
    "jobId": "string",  
    "s3Destination": {  
        "bucket": "string",  
        "key": "string",  
        "metadataKey": "string"  
    }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [jobId](#)

The identification number of the export job.

To view the status of an export job, use the [DescribeRecommendationExportJobs](#) action and specify the job ID.

Type: String

### [s3Destination](#)

Describes the destination Amazon Simple Storage Service (Amazon S3) bucket name and object keys of a recommendations export file, and its associated metadata file.

Type: [S3Destination](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### InternalServerException

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### InvalidParameterValueException

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### LimitExceededException

The request exceeds a limit of the service.

HTTP Status Code: 400

### MissingAuthenticationToken

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

### OptInRequiredException

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

### ServiceUnavailableException

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

### ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetAutoScalingGroupRecommendations

Returns Auto Scaling group recommendations.

Amazon Compute Optimizer generates recommendations for Amazon EC2 Auto Scaling groups that meet a specific set of requirements. For more information, see the [Supported resources and requirements](#) in the *Amazon Compute Optimizer User Guide*.

## Request Syntax

```
{  
    "accountIds": [ "string" ],  
    "autoScalingGroupArns": [ "string" ],  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "maxResults": number,  
    "nextToken": "string",  
    "recommendationPreferences": {  
        "cpuVendorArchitectures": [ "string" ]  
    }  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### accountIds

The ID of the Amazon account for which to return Auto Scaling group recommendations.

If your account is the management account of an organization, use this parameter to specify the member account for which you want to return Auto Scaling group recommendations.

Only one account ID can be specified per request.

Type: Array of strings

Required: No

### [autoScalingGroupArns](#)

The Amazon Resource Name (ARN) of the Auto Scaling groups for which to return recommendations.

Type: Array of strings

Required: No

### [filters](#)

An array of objects to specify a filter that returns a more specific list of Auto Scaling group recommendations.

Type: Array of [Filter](#) objects

Required: No

### [maxResults](#)

The maximum number of Auto Scaling group recommendations to return with a single request.

To retrieve the remaining results, make another request with the returned nextToken value.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000.

Required: No

### [nextToken](#)

The token to advance to the next page of Auto Scaling group recommendations.

Type: String

Required: No

### [recommendationPreferences](#)

An object to specify the preferences for the Auto Scaling group recommendations to return in the response.

Type: [RecommendationPreferences](#) object

Required: No

## Response Syntax

```
{  
    "autoScalingGroupRecommendations": [  
        {  
            "accountId": "string",  
            "autoScalingGroupArn": "string",  
            "autoScalingGroupName": "string",  
            "currentConfiguration": {  
                "allocationStrategy": "string",  
                "desiredCapacity": number,  
                "estimatedInstanceHourReductionPercentage": number,  
                "instanceType": "string",  
                "maxSize": number,  
                "minSize": number,  
                "mixedInstanceTypes": [ "string" ],  
                "type": "string"  
            },  
            "currentInstanceGpuInfo": {  
                "gpus": [  
                    {  
                        "gpuCount": number,  
                        "gpuMemorySizeInMiB": number  
                    }  
                ]  
            },  
            "currentPerformanceRisk": "string",  
            "effectiveRecommendationPreferences": {  
                "cpuVendorArchitectures": [ "string" ],  
                "enhancedInfrastructureMetrics": "string",  
                "externalMetricsPreference": {  
                    "source": "string"  
                },  
                "inferredWorkloadTypes": "string",  
                "lookBackPeriod": "string",  
                "preferredResources": [  
                    {  
                        "effectiveIncludeList": [ "string" ],  
                        "excludeList": [ "string" ],  
                        "includeList": [ "string" ],  
                        "name": "string"  
                    }  
                ],  
            },  
        }  
    ]  
}
```

```
"savingsEstimationMode    "source},  
"utilizationPreferences    {  
        "metricName        "metricParameters            "headroom            "threshold        }  
    }  
]  
,  
"finding"inferredWorkloadTypes"lastRefreshTimestamp"lookBackPeriodInDays"recommendationOptions    {  
        "configuration            "allocationStrategy            "desiredCapacity            "estimatedInstanceHourReductionPercentage            "instanceType            "maxSize            "minSize            "mixedInstanceTypes            "type        },  
        "instanceGpuInfo            "gpus                {  
                    "gpuCount                    "gpuMemorySizeInMiB                }  
            ]  
        },  
        "migrationEffort        "performanceRisk        "projectedUtilizationMetrics            {  
                "name                "statistic                "value            }  
        ]  
    }  
]
```

```
        },
      ],
      "rank": number,
      "savingsOpportunity": {
        "estimatedMonthlySavings": {
          "currency": "string",
          "value": number
        },
        "savingsOpportunityPercentage": number
      },
      "savingsOpportunityAfterDiscounts": {
        "estimatedMonthlySavings": {
          "currency": "string",
          "value": number
        },
        "savingsOpportunityPercentage": number
      }
    }
  ],
  "utilizationMetrics": [
    {
      "name": "string",
      "statistic": "string",
      "value": number
    }
  ]
}
],
"errors": [
  {
    "code": "string",
    "identifier": "string",
    "message": "string"
  }
],
"nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## [autoScalingGroupRecommendations](#)

An array of objects that describe Auto Scaling group recommendations.

Type: Array of [AutoScalingGroupRecommendation](#) objects

## [errors](#)

An array of objects that describe errors of the request.

For example, an error is returned if you request recommendations for an unsupported Auto Scaling group.

Type: Array of [GetRecommendationError](#) objects

## [nextToken](#)

The token to use to advance to the next page of Auto Scaling group recommendations.

This value is null when there are no more pages of Auto Scaling group recommendations to return.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerError**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

## MissingAuthenticationToken

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

## OptInRequiredException

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

## ResourceNotFoundException

A resource that is required for the action doesn't exist.

HTTP Status Code: 400

## ServiceUnavailableException

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)

- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetEBSVolumeRecommendations

Returns Amazon Elastic Block Store (Amazon EBS) volume recommendations.

Amazon Compute Optimizer generates recommendations for Amazon EBS volumes that meet a specific set of requirements. For more information, see the [Supported resources and requirements](#) in the *Amazon Compute Optimizer User Guide*.

## Request Syntax

```
{  
    "accountIds": [ "string" ],  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "maxResults": number,  
    "nextToken": "string",  
    "volumeArns": [ "string" ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### accountIds

The ID of the Amazon account for which to return volume recommendations.

If your account is the management account of an organization, use this parameter to specify the member account for which you want to return volume recommendations.

Only one account ID can be specified per request.

Type: Array of strings

Required: No

## filters

An array of objects to specify a filter that returns a more specific list of volume recommendations.

Type: Array of [EBSFilter](#) objects

Required: No

## maxResults

The maximum number of volume recommendations to return with a single request.

To retrieve the remaining results, make another request with the returned nextToken value.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000.

Required: No

## nextToken

The token to advance to the next page of volume recommendations.

Type: String

Required: No

## volumeArns

The Amazon Resource Name (ARN) of the volumes for which to return recommendations.

Type: Array of strings

Required: No

## Response Syntax

```
{  
  "errors": [  
    {  
      "code": "string",  
      "identifier": "string",  
      "message": "string"  
    }  
  ]  
}
```

```
],
"nextToken": "string",
"volumeRecommendations": [
{
    "accountId": "string",
    "currentConfiguration": {
        "rootVolume": boolean,
        "volumeBaselineIOPS": number,
        "volumeBaselineThroughput": number,
        "volumeBurstIOPS": number,
        "volumeBurstThroughput": number,
        "volumeSize": number,
        "volumeType": "string"
    },
    "currentPerformanceRisk": "string",
    "effectiveRecommendationPreferences": {
        "savingsEstimationMode": {
            "source": "string"
        }
    },
    "finding": "string",
    "lastRefreshTimestamp": number,
    "lookBackPeriodInDays": number,
    "tags": [
        {
            "key": "string",
            "value": "string"
        }
    ],
    "utilizationMetrics": [
        {
            "name": "string",
            "statistic": "string",
            "value": number
        }
    ],
    "volumeArn": "string",
    "volumeRecommendationOptions": [
        {
            "configuration": {
                "rootVolume": boolean,
                "volumeBaselineIOPS": number,
                "volumeBaselineThroughput": number,
                "volumeBurstIOPS": number,
                "volumeSize": number
            }
        }
    ]
},
```

```
        "volumeBurstThroughput": number,
        "volumeSize": number,
        "volumeType": "string"
    },
    "performanceRisk": number,
    "rank": number,
    "savingsOpportunity": {
        "estimatedMonthlySavings": {
            "currency": "string",
            "value": number
        },
        "savingsOpportunityPercentage": number
    },
    "savingsOpportunityAfterDiscounts": {
        "estimatedMonthlySavings": {
            "currency": "string",
            "value": number
        },
        "savingsOpportunityPercentage": number
    }
}
]
}
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [errors](#)

An array of objects that describe errors of the request.

For example, an error is returned if you request recommendations for an unsupported volume.

Type: Array of [GetRecommendationError](#) objects

### [nextToken](#)

The token to use to advance to the next page of volume recommendations.

This value is null when there are no more pages of volume recommendations to return.

Type: String

### [volumeRecommendations](#)

An array of objects that describe volume recommendations.

Type: Array of [VolumeRecommendation](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerError**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

### **OptInRequiredException**

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

### **ResourceNotFoundException**

A resource that is required for the action doesn't exist.

HTTP Status Code: 400

### **ServiceUnavailableException**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

### **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetEC2InstanceRecommendations

Returns Amazon EC2 instance recommendations.

Amazon Compute Optimizer generates recommendations for Amazon Elastic Compute Cloud (Amazon EC2) instances that meet a specific set of requirements. For more information, see the [Supported resources and requirements](#) in the *Amazon Compute Optimizer User Guide*.

## Request Syntax

```
{  
    "accountIds": [ "string" ],  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "instanceArns": [ "string" ],  
    "maxResults": number,  
    "nextToken": "string",  
    "recommendationPreferences": {  
        "cpuVendorArchitectures": [ "string" ]  
    }  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### accountIds

The ID of the Amazon account for which to return instance recommendations.

If your account is the management account of an organization, use this parameter to specify the member account for which you want to return instance recommendations.

Only one account ID can be specified per request.

Type: Array of strings

Required: No

### filters

An array of objects to specify a filter that returns a more specific list of instance recommendations.

Type: Array of [Filter](#) objects

Required: No

### instanceArns

The Amazon Resource Name (ARN) of the instances for which to return recommendations.

Type: Array of strings

Required: No

### maxResults

The maximum number of instance recommendations to return with a single request.

To retrieve the remaining results, make another request with the returned nextToken value.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000.

Required: No

### nextToken

The token to advance to the next page of instance recommendations.

Type: String

Required: No

### recommendationPreferences

An object to specify the preferences for the Amazon EC2 instance recommendations to return in the response.

Type: [RecommendationPreferences](#) object

Required: No

## Response Syntax

```
{  
    "errors": [  
        {  
            "code": "string",  
            "identifier": "string",  
            "message": "string"  
        }  
    ],  
    "instanceRecommendations": [  
        {  
            "accountId": "string",  
            "currentInstanceGpuInfo": {  
                "gpus": [  
                    {  
                        "gpuCount": number,  
                        "gpuMemorySizeInMiB": number  
                    }  
                ]  
            },  
            "currentInstanceType": "string",  
            "currentPerformanceRisk": "string",  
            "effectiveRecommendationPreferences": {  
                "cpuVendorArchitectures": [ "string" ],  
                "enhancedInfrastructureMetrics": "string",  
                "externalMetricsPreference": {  
                    "source": "string"  
                },  
                "inferredWorkloadTypes": "string",  
                "lookBackPeriod": "string",  
                "preferredResources": [  
                    {  
                        "effectiveIncludeList": [ "string" ],  
                        "excludeList": [ "string" ],  
                        "includeList": [ "string" ],  
                        "name": "string"  
                    }  
                ],  
                "savingsEstimationMode": {  
                    "source": "string"  
                },  
                "utilizationPreferences": [  
                    {  
                        "cpuUtilization": "string",  
                        "idleTime": "string",  
                        "idleTimeWindow": "string",  
                        "idleTimeWindowUnit": "string",  
                        "idleTimeWindowValue": number,  
                        "idleTimeWindowUnit": "string",  
                        "idleTimeWindowValue": number  
                    }  
                ]  
            }  
        }  
    ]  
}
```

```
{  
    "metricName": "string",  
    "metricParameters": {  
        "headroom": "string",  
        "threshold": "string"  
    }  
},  
]  
],  
},  
"externalMetricStatus": {  
    "statusCode": "string",  
    "statusReason": "string"  
},  
"finding": "string",  
"findingReasonCodes": [ "string" ],  
"idle": "string",  
"inferredWorkloadTypes": [ "string" ],  
"instanceArn": "string",  
"instanceName": "string",  
"instanceState": "string",  
"lastRefreshTimestamp": number,  
"lookBackPeriodInDays": number,  
"recommendationOptions": [  
    {  
        "instanceGpuInfo": {  
            "gpus": [  
                {  
                    "gpuCount": number,  
                    "gpuMemorySizeInMiB": number  
                }  
            ]  
        },  
        "instanceType": "string",  
        "migrationEffort": "string",  
        "performanceRisk": number,  
        "platformDifferences": [ "string" ],  
        "projectedUtilizationMetrics": [  
            {  
                "name": "string",  
                "statistic": "string",  
                "value": number  
            }  
        ],  
        "rank": number,  
    }  
]
```

```
        "savingsOpportunity": {
            "estimatedMonthlySavings": {
                "currency": "string",
                "value": number
            },
            "savingsOpportunityPercentage": number
        },
        "savingsOpportunityAfterDiscounts": {
            "estimatedMonthlySavings": {
                "currency": "string",
                "value": number
            },
            "savingsOpportunityPercentage": number
        }
    }
],
"recommendationSources": [
    {
        "recommendationSourceArn": "string",
        "recommendationSourceType": "string"
    }
],
"tags": [
    {
        "key": "string",
        "value": "string"
    }
],
"utilizationMetrics": [
    {
        "name": "string",
        "statistic": "string",
        "value": number
    }
]
},
"nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### errors

An array of objects that describe errors of the request.

For example, an error is returned if you request recommendations for an instance of an unsupported instance family.

Type: Array of [GetRecommendationError](#) objects

### instanceRecommendations

An array of objects that describe instance recommendations.

Type: Array of [InstanceRecommendation](#) objects

### nextToken

The token to use to advance to the next page of instance recommendations.

This value is null when there are no more pages of instance recommendations to return.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerError**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

### **OptInRequiredException**

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

### **ResourceNotFoundException**

A resource that is required for the action doesn't exist.

HTTP Status Code: 400

### **ServiceUnavailableException**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

### **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetEC2RecommendationProjectedMetrics

Returns the projected utilization metrics of Amazon EC2 instance recommendations.

## Note

The Cpu and Memory metrics are the only projected utilization metrics returned when you run this action. Additionally, the Memory metric is returned only for resources that have the unified CloudWatch agent installed on them. For more information, see [Enabling Memory Utilization with the CloudWatch Agent](#).

## Request Syntax

```
{  
    "endTime": number,  
    "instanceArn": "string",  
    "period": number,  
    "recommendationPreferences": {  
        "cpuVendorArchitectures": [ "string" ]  
    },  
    "startTime": number,  
    "stat": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### endTime

The timestamp of the last projected metrics data point to return.

Type: Timestamp

Required: Yes

## instanceArn

The Amazon Resource Name (ARN) of the instances for which to return recommendation projected metrics.

Type: String

Required: Yes

## period

The granularity, in seconds, of the projected metrics data points.

Type: Integer

Required: Yes

## recommendationPreferences

An object to specify the preferences for the Amazon EC2 recommendation projected metrics to return in the response.

Type: [RecommendationPreferences](#) object

Required: No

## startTime

The timestamp of the first projected metrics data point to return.

Type: Timestamp

Required: Yes

## stat

The statistic of the projected metrics.

Type: String

Valid Values: Maximum | Average

Required: Yes

## Response Syntax

```
{
```

```
"recommendedOptionProjectedMetrics": [  
    {  
        "projectedMetrics            {  
                "namestring",  
                "timestampsnumber ],  
                "valuesnumber ]  
            }  
        ],  
        "ranknumber,  
        "recommendedInstanceTypestring"  
    }  
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [recommendedOptionProjectedMetrics](#)

An array of objects that describes projected metrics.

Type: Array of [RecommendedOptionProjectedMetric](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerError**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

## **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

## **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

## **OptInRequiredException**

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

## **ResourceNotFoundException**

A resource that is required for the action doesn't exist.

HTTP Status Code: 400

## **ServiceUnavailableException**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)

- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetECSServiceRecommendationProjectedMetrics

Returns the projected metrics of Amazon ECS service recommendations.

## Request Syntax

```
{  
    "endTime": number,  
    "period": number,  
    "serviceArn": "string",  
    "startTime": number,  
    "stat": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### endTime

The timestamp of the last projected metrics data point to return.

Type: Timestamp

Required: Yes

### period

The granularity, in seconds, of the projected metrics data points.

Type: Integer

Required: Yes

### serviceArn

The ARN that identifies the Amazon ECS service.

The following is the format of the ARN:

`arn:aws:ecs:region:aws_account_id:service/cluster-name/service-name`

Type: String

Required: Yes

### startTime

The timestamp of the first projected metrics data point to return.

Type: Timestamp

Required: Yes

### stat

The statistic of the projected metrics.

Type: String

Valid Values: Maximum | Average

Required: Yes

## Response Syntax

```
{  
    "recommendedOptionProjectedMetrics": [  
        {  
            "projectedMetrics": [  
                {  
                    "lowerBoundValues": [ number ],  
                    "name": "string",  
                    "timestamps": [ number ],  
                    "upperBoundValues": [ number ]  
                }  
            ],  
            "recommendedCpuUnits": number,  
            "recommendedMemorySize": number  
        }  
    ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## [recommendedOptionProjectedMetrics](#)

An array of objects that describes the projected metrics.

Type: Array of [ECSServiceRecommendedOptionProjectedMetric](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerException**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

### **OptInRequiredException**

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

### **ResourceNotFoundException**

A resource that is required for the action doesn't exist.

HTTP Status Code: 400

### **ServiceUnavailableException**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

### **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetECSServiceRecommendations

Returns Amazon ECS service recommendations.

Amazon Compute Optimizer generates recommendations for Amazon ECS services on Fargate that meet a specific set of requirements. For more information, see the [Supported resources and requirements](#) in the *Amazon Compute Optimizer User Guide*.

## Request Syntax

```
{  
    "accountIds": [ "string" ],  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "maxResults": number,  
    "nextToken": "string",  
    "serviceArns": [ "string" ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### accountIds

Return the Amazon ECS service recommendations to the specified Amazon Web Services account IDs.

If your account is the management account or the delegated administrator of an organization, use this parameter to return the Amazon ECS service recommendations to specific member accounts.

You can only specify one account ID per request.

Type: Array of strings

Required: No

### filters

An array of objects to specify a filter that returns a more specific list of Amazon ECS service recommendations.

Type: Array of [ECSServiceRecommendationFilter](#) objects

Required: No

### maxResults

The maximum number of Amazon ECS service recommendations to return with a single request.

To retrieve the remaining results, make another request with the returned nextToken value.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000.

Required: No

### nextToken

The token to advance to the next page of Amazon ECS service recommendations.

Type: String

Required: No

### serviceArns

The ARN that identifies the Amazon ECS service.

The following is the format of the ARN:

`arn:aws:ecs:region:aws_account_id:service/cluster-name/service-name`

Type: Array of strings

Required: No

## Response Syntax

```
{  
  "ecsServiceRecommendations": [
```

```
{  
    "accountId": "string",  
    "currentPerformanceRisk": "string",  
    "currentServiceConfiguration": {  
        "autoScalingConfiguration": "string",  
        "containerConfigurations": [  
            {  
                "containerName": "string",  
                "cpu": number,  
                "memorySizeConfiguration": {  
                    "memory": number,  
                    "memoryReservation": number  
                }  
            }  
        ],  
        "cpu": number,  
        "memory": number,  
        "taskDefinitionArn": "string"  
    },  
    "effectiveRecommendationPreferences": {  
        "savingsEstimationMode": {  
            "source": "string"  
        }  
    },  
    "finding": "string",  
    "findingReasonCodes": [ "string" ],  
    "lastRefreshTimestamp": number,  
    "launchType": "string",  
    "lookbackPeriodInDays": number,  
    "serviceArn": "string",  
    "serviceRecommendationOptions": [  
        {  
            "containerRecommendations": [  
                {  
                    "containerName": "string",  
                    "cpu": number,  
                    "memorySizeConfiguration": {  
                        "memory": number,  
                        "memoryReservation": number  
                    }  
                }  
            ],  
            "cpu": number,  
            "memory": number,  
        }  
    ]  
}
```

```
"projectedUtilizationMetrics": [
    {
        "lowerBoundValue": number,
        "name": "string",
        "statistic": "string",
        "upperBoundValue": number
    }
],
"savingsOpportunity": {
    "estimatedMonthlySavings": {
        "currency": "string",
        "value": number
    },
    "savingsOpportunityPercentage": number
},
"savingsOpportunityAfterDiscounts": {
    "estimatedMonthlySavings": {
        "currency": "string",
        "value": number
    },
    "savingsOpportunityPercentage": number
}
},
"tags": [
    {
        "key": "string",
        "value": "string"
    }
],
"utilizationMetrics": [
    {
        "name": "string",
        "statistic": "string",
        "value": number
    }
]
},
"errors": [
    {
        "code": "string",
        "identifier": "string",
        "message": "string"
    }
]
```

```
    }
],
"nextToken
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [ecsServiceRecommendations](#)

An array of objects that describe the Amazon ECS service recommendations.

Type: Array of [ECSServiceRecommendation](#) objects

### [errors](#)

An array of objects that describe errors of the request.

Type: Array of [GetRecommendationError](#) objects

### [nextToken](#)

The token to advance to the next page of Amazon ECS service recommendations.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerError**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

## **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

## **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

## **OptInRequiredException**

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

## **ResourceNotFoundException**

A resource that is required for the action doesn't exist.

HTTP Status Code: 400

## **ServiceUnavailableException**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)

- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetEffectiveRecommendationPreferences

Returns the recommendation preferences that are in effect for a given resource, such as enhanced infrastructure metrics. Considers all applicable preferences that you might have set at the resource, account, and organization level.

When you create a recommendation preference, you can set its status to Active or Inactive. Use this action to view the recommendation preferences that are in effect, or Active.

## Request Syntax

```
{  
    "resourceArn": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### resourceArn

The Amazon Resource Name (ARN) of the resource for which to confirm effective recommendation preferences. Only EC2 instance and Auto Scaling group ARNs are currently supported.

Type: String

Required: Yes

## Response Syntax

```
{  
    "enhancedInfrastructureMetrics": "string",  
    "externalMetricsPreference": {  
        "source": "string"  
    },  
    "lookBackPeriod": "string",  
    "preferredResources": [  
        "string"  
    ]  
}
```

```
{  
    "effectiveIncludeList": [ "string" ],  
    "excludeList": [ "string" ],  
    "includeList": [ "string" ],  
    "name": "string"  
}  
,  
"utilizationPreferences": [  
    {  
        "metricName": "string",  
        "metricParameters": {  
            "headroom": "string",  
            "threshold": "string"  
        }  
    }  
]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [enhancedInfrastructureMetrics](#)

The status of the enhanced infrastructure metrics recommendation preference. Considers all applicable preferences that you might have set at the resource, account, and organization level.

A status of Active confirms that the preference is applied in the latest recommendation refresh, and a status of Inactive confirms that it's not yet applied to recommendations.

To validate whether the preference is applied to your last generated set of recommendations, review the effectiveRecommendationPreferences value in the response of the [GetAutoScalingGroupRecommendations](#) and [GetEC2InstanceStateRecommendations](#) actions.

For more information, see [Enhanced infrastructure metrics](#) in the *Amazon Compute Optimizer User Guide*.

Type: String

Valid Values: Active | Inactive

## [\*\*externalMetricsPreference\*\*](#)

The provider of the external metrics recommendation preference. Considers all applicable preferences that you might have set at the account and organization level.

If the preference is applied in the latest recommendation refresh, an object with a valid source value appears in the response. If the preference isn't applied to the recommendations already, then this object doesn't appear in the response.

To validate whether the preference is applied to your last generated set of recommendations, review the effectiveRecommendationPreferences value in the response of the [GetEC2InstanceRecommendations](#) actions.

For more information, see [Enhanced infrastructure metrics](#) in the *Amazon Compute Optimizer User Guide*.

Type: [ExternalMetricsPreference](#) object

## [\*\*lookBackPeriod\*\*](#)

The number of days the utilization metrics of the Amazon resource are analyzed.

To validate that the preference is applied to your last generated set of recommendations, review the effectiveRecommendationPreferences value in the response of the GetAutoScalingGroupRecommendations or GetEC2InstanceRecommendations actions.

Type: String

Valid Values: DAYS\_14 | DAYS\_32 | DAYS\_93

## [\*\*preferredResources\*\*](#)

The resource type values that are considered as candidates when generating rightsizing recommendations. This object resolves any wildcard expressions and returns the effective list of candidate resource type values. It also considers all applicable preferences that you set at the resource, account, and organization level.

To validate that the preference is applied to your last generated set of recommendations, review the effectiveRecommendationPreferences value in the response of the GetAutoScalingGroupRecommendations or GetEC2InstanceRecommendations actions.

Type: Array of [EffectivePreferredResource](#) objects

## utilizationPreferences

The resource's CPU and memory utilization preferences, such as threshold and headroom, that were used to generate rightsizing recommendations. It considers all applicable preferences that you set at the resource, account, and organization level.

To validate that the preference is applied to your last generated set of recommendations, review the `effectiveRecommendationPreferences` value in the response of the `GetAutoScalingGroupRecommendations` or `GetEC2InstanceStateRecommendations` actions.

Type: Array of [UtilizationPreference](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerException**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

### **OptInRequiredException**

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

## ResourceNotFoundException

A resource that is required for the action doesn't exist.

HTTP Status Code: 400

## ServiceUnavailableException

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetEnrollmentStatus

Returns the enrollment (opt in) status of an account to the Amazon Compute Optimizer service.

If the account is the management account of an organization, this action also confirms the enrollment status of member accounts of the organization. Use the [GetEnrollmentStatusesForOrganization](#) action to get detailed information about the enrollment status of member accounts of an organization.

## Response Syntax

```
{  
    "lastUpdatedTimestamp": number,  
    "memberAccountsEnrolled": boolean,  
    "numberOfMemberAccountsOptedIn": number,  
    "status": "string",  
    "statusReason": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [lastUpdatedTimestamp](#)

The Unix epoch timestamp, in seconds, of when the account enrollment status was last updated.

Type: Timestamp

### [memberAccountsEnrolled](#)

Confirms the enrollment status of member accounts of the organization, if the account is a management account of an organization.

Type: Boolean

### [numberOfMemberAccountsOptedIn](#)

The count of organization member accounts that are opted in to the service, if your account is an organization management account.

Type: Integer

### [status](#)

The enrollment status of the account.

Type: String

Valid Values: Active | Inactive | Pending | Failed

### [statusReason](#)

The reason for the enrollment status of the account.

For example, an account might show a status of Pending because member accounts of an organization require more time to be enrolled in the service.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerError**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

## ServiceUnavailableException

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetEnrollmentStatusesForOrganization

Returns the Amazon Compute Optimizer enrollment (opt-in) status of organization member accounts, if your account is an organization management account.

To get the enrollment status of standalone accounts, use the [GetEnrollmentStatus](#) action.

## Request Syntax

```
{  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "maxResults": number,  
    "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [filters](#)

An array of objects to specify a filter that returns a more specific list of account enrollment statuses.

Type: Array of [EnrollmentFilter](#) objects

Required: No

### [maxResults](#)

The maximum number of account enrollment statuses to return with a single request. You can specify up to 100 statuses to return with each request.

To retrieve the remaining results, make another request with the returned nextToken value.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000.

Required: No

### nextToken

The token to advance to the next page of account enrollment statuses.

Type: String

Required: No

## Response Syntax

```
{  
    "accountEnrollmentStatuses": [  
        {  
            "accountId": "string",  
            "lastUpdatedTimestamp": number,  
            "status": "string",  
            "statusReason": "string"  
        }  
    ],  
    "nextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### accountEnrollmentStatuses

An array of objects that describe the enrollment statuses of organization member accounts.

Type: Array of [AccountEnrollmentStatus](#) objects

### nextToken

The token to use to advance to the next page of account enrollment statuses.

This value is null when there are no more pages of account enrollment statuses to return.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### InternalServerError

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### InvalidParameterValueException

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### MissingAuthenticationToken

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

### ServiceUnavailableException

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

### ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetIdleRecommendations

Returns idle resource recommendations. Amazon Compute Optimizer generates recommendations for idle resources that meet a specific set of requirements. For more information, see [Resource requirements](#) in the *Amazon Compute Optimizer User Guide*

## Request Syntax

```
{  
    "accountIds": [ "string" ],  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "maxResults": number,  
    "nextToken": "string",  
    "orderBy": {  
        "dimension": "string",  
        "order": "string"  
    },  
    "resourceArns": [ "string" ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### accountIds

Return the idle resource recommendations to the specified Amazon Web Services account IDs.

If your account is the management account or the delegated administrator of an organization, use this parameter to return the idle resource recommendations to specific member accounts.

You can only specify one account ID per request.

Type: Array of strings

Required: No

### [filters](#)

An array of objects to specify a filter that returns a more specific list of idle resource recommendations.

Type: Array of [IdleRecommendationFilter](#) objects

Required: No

### [maxResults](#)

The maximum number of idle resource recommendations to return with a single request.

To retrieve the remaining results, make another request with the returned nextToken value.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

### [nextToken](#)

The token to advance to the next page of idle resource recommendations.

Type: String

Required: No

### [orderBy](#)

The order to sort the idle resource recommendations.

Type: [OrderBy](#) object

Required: No

### [resourceArns](#)

The ARN that identifies the idle resource.

Type: Array of strings

Required: No

## Response Syntax

```
{  
    "errors": [  
        {  
            "code": "string",  
            "identifier": "string",  
            "message": "string",  
            "resourceType": "string"  
        }  
    ],  
    "idleRecommendations": [  
        {  
            "accountId": "string",  
            "finding": "string",  
            "findingDescription": "string",  
            "lastRefreshTimestamp": number,  
            "lookBackPeriodInDays": number,  
            "resourceArn": "string",  
            "resourceId": "string",  
            "resourceType": "string",  
            "savingsOpportunity": {  
                "estimatedMonthlySavings": {  
                    "currency": "string",  
                    "value": number  
                },  
                "savingsOpportunityPercentage": number  
            },  
            "savingsOpportunityAfterDiscounts": {  
                "estimatedMonthlySavings": {  
                    "currency": "string",  
                    "value": number  
                },  
                "savingsOpportunityPercentage": number  
            },  
            "tags": [  
                {  
                    "key": "string",  
                    "value": "string"  
                }  
            ],  
            "utilizationMetrics": [  
                {  
                    "key": "string",  
                    "value": "string"  
                }  
            ]  
        }  
    ]  
}
```

```
        "name": "string",
        "statistic": "string",
        "value": number
    }
]
}
],
"nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [errors](#)

An array of objects that describe errors of the request.

Type: Array of [IdleRecommendationError](#) objects

### [idleRecommendations](#)

An array of objects that describe the idle resource recommendations.

Type: Array of [IdleRecommendation](#) objects

### [nextToken](#)

The token to advance to the next page of idle resource recommendations.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

## **InternalServerError**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

## **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

## **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

## **OptInRequiredException**

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

## **ResourceNotFoundException**

A resource that is required for the action doesn't exist.

HTTP Status Code: 400

## **ServiceUnavailableException**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetLambdaFunctionRecommendations

Returns Amazon Lambda function recommendations.

Amazon Compute Optimizer generates recommendations for functions that meet a specific set of requirements. For more information, see the [Supported resources and requirements](#) in the *Amazon Compute Optimizer User Guide*.

## Request Syntax

```
{  
    "accountIds": [ "string" ],  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "functionArns": [ "string" ],  
    "maxResults": number,  
    "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### accountIds

The ID of the Amazon account for which to return function recommendations.

If your account is the management account of an organization, use this parameter to specify the member account for which you want to return function recommendations.

Only one account ID can be specified per request.

Type: Array of strings

Required: No

## filters

An array of objects to specify a filter that returns a more specific list of function recommendations.

Type: Array of [LambdaFunctionRecommendationFilter](#) objects

Required: No

## functionArns

The Amazon Resource Name (ARN) of the functions for which to return recommendations.

You can specify a qualified or unqualified ARN. If you specify an unqualified ARN without a function version suffix, Compute Optimizer will return recommendations for the latest (\$LATEST) version of the function. If you specify a qualified ARN with a version suffix, Compute Optimizer will return recommendations for the specified function version. For more information about using function versions, see [Using versions](#) in the *Amazon Lambda Developer Guide*.

Type: Array of strings

Required: No

## maxResults

The maximum number of function recommendations to return with a single request.

To retrieve the remaining results, make another request with the returned nextToken value.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000.

Required: No

## nextToken

The token to advance to the next page of function recommendations.

Type: String

Required: No

## Response Syntax

```
{  
  "lambdaFunctionRecommendations": [  
    {  
      "accountId": "string",  
      "currentMemorySize": number,  
      "currentPerformanceRisk": "string",  
      "effectiveRecommendationPreferences": {  
        "savingsEstimationMode": {  
          "source": "string"  
        }  
      },  
      "finding": "string",  
      "findingReasonCodes": [ "string" ],  
      "functionArn": "string",  
      "functionVersion": "string",  
      "lastRefreshTimestamp": number,  
      "lookbackPeriodInDays": number,  
      "memorySizeRecommendationOptions": [  
        {  
          "memorySize": number,  
          "projectedUtilizationMetrics": [  
            {  
              "name": "string",  
              "statistic": "string",  
              "value": number  
            }  
          ],  
          "rank": number,  
          "savingsOpportunity": {  
            "estimatedMonthlySavings": {  
              "currency": "string",  
              "value": number  
            },  
            "savingsOpportunityPercentage": number  
          },  
          "savingsOpportunityAfterDiscounts": {  
            "estimatedMonthlySavings": {  
              "currency": "string",  
              "value": number  
            },  
            "savingsOpportunityPercentage": number  
          }  
        }  
      ]  
    }  
  ]  
}
```

```
        }
    ],
    "numberOfInvocations": number,
    "tags": [
        {
            "key": "string",
            "value": "string"
        }
    ],
    "utilizationMetrics": [
        {
            "name": "string",
            "statistic": "string",
            "value": number
        }
    ]
},
"nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [lambdaFunctionRecommendations](#)

An array of objects that describe function recommendations.

Type: Array of [LambdaFunctionRecommendation](#) objects

### [nextToken](#)

The token to use to advance to the next page of function recommendations.

This value is null when there are no more pages of function recommendations to return.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### InternalServerException

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### InvalidParameterValueException

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### LimitExceededException

The request exceeds a limit of the service.

HTTP Status Code: 400

### MissingAuthenticationToken

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

### OptInRequiredException

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

### ServiceUnavailableException

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

### ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetLicenseRecommendations

Returns license recommendations for Amazon EC2 instances that run on a specific license.

Amazon Compute Optimizer generates recommendations for licenses that meet a specific set of requirements. For more information, see the [Supported resources and requirements](#) in the *Amazon Compute Optimizer User Guide*.

## Request Syntax

```
{  
    "accountIds": [ "string" ],  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "maxResults": number,  
    "nextToken": "string",  
    "resourceArns": [ "string" ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### accountIds

The ID of the Amazon account for which to return license recommendations.

If your account is the management account of an organization, use this parameter to specify the member account for which you want to return license recommendations.

Only one account ID can be specified per request.

Type: Array of strings

Required: No

## filters

An array of objects to specify a filter that returns a more specific list of license recommendations.

Type: Array of [LicenseRecommendationFilter](#) objects

Required: No

## maxResults

The maximum number of license recommendations to return with a single request.

To retrieve the remaining results, make another request with the returned nextToken value.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000.

Required: No

## nextToken

The token to advance to the next page of license recommendations.

Type: String

Required: No

## resourceArns

The ARN that identifies the Amazon EC2 instance.

The following is the format of the ARN:

arn:aws:ec2:region:aws\_account\_id:instance/instance-id

Type: Array of strings

Required: No

## Response Syntax

```
{  
  "errors": [  
    {
```

```
        "code": "string",
        "identifier": "string",
        "message": "string"
    },
],
"licenseRecommendations": [
{
    "accountId": "string",
    "currentLicenseConfiguration": {
        "instanceType": "string",
        "licenseEdition": "string",
        "licenseModel": "string",
        "licenseName": "string",
        "licenseVersion": "string",
        "metricsSource": [
            {
                "provider": "string",
                "providerArn": "string"
            }
        ],
        "numberOfCores": number,
        "operatingSystem": "string"
    },
    "finding": "string",
    "findingReasonCodes": [ "string" ],
    "lastRefreshTimestamp": number,
    "licenseRecommendationOptions": [
        {
            "licenseEdition": "string",
            "licenseModel": "string",
            "operatingSystem": "string",
            "rank": number,
            "savingsOpportunity": {
                "estimatedMonthlySavings": {
                    "currency": "string",
                    "value": number
                },
                "savingsOpportunityPercentage": number
            }
        }
    ],
    "lookbackPeriodInDays": number,
    "resourceArn": "string",
    "tags": [

```

```
        {
            "key": "string",
            "value": "string"
        }
    ]
}
],
"nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [errors](#)

An array of objects that describe errors of the request.

Type: Array of [GetRecommendationError](#) objects

### [licenseRecommendations](#)

An array of objects that describe license recommendations.

Type: Array of [LicenseRecommendation](#) objects

### [nextToken](#)

The token to use to advance to the next page of license recommendations.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

## **InternalServerError**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

## **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

## **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

## **OptInRequiredException**

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

## **ResourceNotFoundException**

A resource that is required for the action doesn't exist.

HTTP Status Code: 400

## **ServiceUnavailableException**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetRDSDatabaseRecommendationProjectedMetrics

Returns the projected metrics of Aurora and RDS database recommendations.

## Request Syntax

```
{  
    "endTime": number,  
    "period": number,  
    "recommendationPreferences": {  
        "cpuVendorArchitectures": [ "string" ]  
    },  
    "resourceArn": "string",  
    "startTime": number,  
    "stat": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### endTime

The timestamp of the last projected metrics data point to return.

Type: Timestamp

Required: Yes

### period

The granularity, in seconds, of the projected metrics data points.

Type: Integer

Required: Yes

### recommendationPreferences

Describes the recommendation preferences to return in the response of a [GetAutoScalingGroupRecommendations](#), [GetEC2InstanceRecommendations](#),

[GetEC2RecommendationProjectedMetrics](#), [GetRDSDatabaseRecommendations](#), and [GetRDSDatabaseRecommendationProjectedMetrics](#) request.

Type: [RecommendationPreferences](#) object

Required: No

### resourceArn

The ARN that identifies the Amazon Aurora or RDS database.

The following is the format of the ARN:

arn:aws:rds:{region}:{accountId}:db:{resourceName}

Type: String

Required: Yes

### startTime

The timestamp of the first projected metrics data point to return.

Type: Timestamp

Required: Yes

### stat

The statistic of the projected metrics.

Type: String

Valid Values: Maximum | Average

Required: Yes

## Response Syntax

```
{  
  "recommendedOptionProjectedMetrics": [  
    {  
      "projectedMetrics": [  
        {  
          "name": "string",  
          "value": "string"  
        }  
      ]  
    }  
  ]  
}
```

```
        "timestamps": [ number ],
        "values": [ number ]
    },
    "rank": number,
    "recommendedDBInstanceClass": "string"
}
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [recommendedOptionProjectedMetrics](#)

An array of objects that describes the projected metrics.

Type: Array of [RDSDatabaseRecommendedOptionProjectedMetric](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerError**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

## MissingAuthenticationToken

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

## OptInRequiredException

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

## ResourceNotFoundException

A resource that is required for the action doesn't exist.

HTTP Status Code: 400

## ServiceUnavailableException

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)

- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetRDSDatabaseRecommendations

Returns Amazon Aurora and RDS database recommendations.

Amazon Compute Optimizer generates recommendations for Amazon Aurora and RDS databases that meet a specific set of requirements. For more information, see the [Supported resources and requirements](#) in the *Amazon Compute Optimizer User Guide*.

## Request Syntax

```
{  
    "accountIds": [ "string" ],  
    "filters": [  
        {  
            "name": "string",  
            "values": [ "string" ]  
        }  
    ],  
    "maxResults": number,  
    "nextToken": "string",  
    "recommendationPreferences": {  
        "cpuVendorArchitectures": [ "string" ]  
    },  
    "resourceArns": [ "string" ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### accountIds

Return the Amazon Aurora and RDS database recommendations to the specified Amazon Web Services account IDs.

If your account is the management account or the delegated administrator of an organization, use this parameter to return the Amazon Aurora and RDS database recommendations to specific member accounts.

You can only specify one account ID per request.

Type: Array of strings

Required: No

### filters

An array of objects to specify a filter that returns a more specific list of Amazon Aurora and RDS database recommendations.

Type: Array of [RDSDBRecommendationFilter](#) objects

Required: No

### maxResults

The maximum number of Amazon Aurora and RDS database recommendations to return with a single request.

To retrieve the remaining results, make another request with the returned nextToken value.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000.

Required: No

### nextToken

The token to advance to the next page of Amazon Aurora and RDS database recommendations.

Type: String

Required: No

### recommendationPreferences

Describes the recommendation preferences to return in the response of a [GetAutoScalingGroupRecommendations](#), [GetEC2InstanceStateRecommendations](#), [GetEC2RecommendationProjectedMetrics](#), [GetRDSDatabaseRecommendations](#), and [GetRDSDatabaseRecommendationProjectedMetrics](#) request.

Type: [RecommendationPreferences](#) object

Required: No

### resourceArns

The ARN that identifies the Amazon Aurora or RDS database.

The following is the format of the ARN:

arn:aws:rds:{region}:{accountId}:db:{resourceName}

The following is the format of a DB Cluster ARN:

arn:aws:rds:{region}:{accountId}:cluster:{resourceName}

Type: Array of strings

Required: No

## Response Syntax

```
{  
    "errors": [  
        {  
            "code": "string",  
            "identifier": "string",  
            "message": "string"  
        }  
    ],  
    "nextToken": "string",  
    "rdsDBRecommendations": [  
        {  
            "accountId": "string",  
            "currentDBInstanceClass": "string",  
            "currentInstancePerformanceRisk": "string",  
            "currentStorageConfiguration": {  
                "allocatedStorage": number,  
                "iops": number,  
                "maxAllocatedStorage": number,  
                "storageThroughput": number,  
                "storageType": "string"  
            },  
            "currentStorageEstimatedMonthlyVolumeIOPsCostVariation": "string",  
            "dbClusterIdentifier": "string",  
            "effectiveRecommendationPreferences": {  
                "cpuVendorArchitectures": [ "string" ],  
                "enhancedInfrastructureMetrics": "string",  
                "lookBackPeriod": "string",  
                "savingsEstimationMode": {  
                    "source": "string"  
                }  
            }  
        }  
    ]  
}
```

```
        },
      ],
      "engine": "string",
      "engineVersion": "string",
      "idle": "string",
      "instanceFinding": "string",
      "instanceFindingReasonCodes": [ "string" ],
      "instanceRecommendationOptions": [
        {
          "dbInstanceClass": "string",
          "performanceRisk": number,
          "projectedUtilizationMetrics": [
            {
              "name": "string",
              "statistic": "string",
              "value": number
            }
          ],
          "rank": number,
          "savingsOpportunity": {
            "estimatedMonthlySavings": {
              "currency": "string",
              "value": number
            },
            "savingsOpportunityPercentage": number
          },
          "savingsOpportunityAfterDiscounts": {
            "estimatedMonthlySavings": {
              "currency": "string",
              "value": number
            },
            "savingsOpportunityPercentage": number
          }
        }
      ],
      "lastRefreshTimestamp": number,
      "lookbackPeriodInDays": number,
      "promotionTier": number,
      "resourceArn": "string",
      "storageFinding": "string",
      "storageFindingReasonCodes": [ "string" ],
      "storageRecommendationOptions": [
        {
          "estimatedMonthlyVolumeIOPsCostVariation": "string",

```

```
"rank": number,
"savingsOpportunity": {
    "estimatedMonthlySavings": {
        "currency": "string",
        "value": number
    },
    "savingsOpportunityPercentage": number
},
"savingsOpportunityAfterDiscounts": {
    "estimatedMonthlySavings": {
        "currency": "string",
        "value": number
    },
    "savingsOpportunityPercentage": number
},
"storageConfiguration": {
    "allocatedStorage": number,
    "iops": number,
    "maxAllocatedStorage": number,
    "storageThroughput": number,
    "storageType": "string"
}
},
],
"tags": [
    {
        "key": "string",
        "value": "string"
    }
],
"utilizationMetrics": [
    {
        "name": "string",
        "statistic": "string",
        "value": number
    }
]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### errors

An array of objects that describe errors of the request.

Type: Array of [GetRecommendationError](#) objects

### nextToken

The token to advance to the next page of Amazon Aurora and RDS database recommendations.

Type: String

### rdsDBRecommendations

An array of objects that describe the Amazon Aurora and RDS database recommendations.

Type: Array of [RDSDBRecommendation](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerError**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

## MissingAuthenticationToken

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

## OptInRequiredException

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

## ResourceNotFoundException

A resource that is required for the action doesn't exist.

HTTP Status Code: 400

## ServiceUnavailableException

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)

- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetRecommendationPreferences

Returns existing recommendation preferences, such as enhanced infrastructure metrics.

Use the scope parameter to specify which preferences to return. You can specify to return preferences for an organization, a specific account ID, or a specific EC2 instance or Auto Scaling group Amazon Resource Name (ARN).

For more information, see [Activating enhanced infrastructure metrics](#) in the *Amazon Compute Optimizer User Guide*.

## Request Syntax

```
{  
    "maxResults": number,  
    "nextToken": "string",  
    "resourceType": "string",  
    "scope": {  
        "name": "string",  
        "value": "string"  
    }  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### maxResults

The maximum number of recommendation preferences to return with a single request.

To retrieve the remaining results, make another request with the returned nextToken value.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000.

Required: No

## nextToken

The token to advance to the next page of recommendation preferences.

Type: String

Required: No

## resourceType

The target resource type of the recommendation preference for which to return preferences.

The Ec2Instance option encompasses standalone instances and instances that are part of Auto Scaling groups. The AutoScalingGroup option encompasses only instances that are part of an Auto Scaling group.

Type: String

Valid Values: Ec2Instance | AutoScalingGroup | RdsDBInstance | AuroraDBClusterStorage

Required: Yes

## scope

An object that describes the scope of the recommendation preference to return.

You can return recommendation preferences that are created at the organization level (for management accounts of an organization only), account level, and resource level. For more information, see [Activating enhanced infrastructure metrics](#) in the *Amazon Compute Optimizer User Guide*.

Type: [Scope](#) object

Required: No

## Response Syntax

```
{  
  "nextToken": "string",  
  "recommendationPreferencesDetails": [  
    {  
      "enhancedInfrastructureMetrics": "string",  
      "resourceType": "string",  
      "scope": {  
        "account": "string",  
        "organization": "string",  
        "resource": "string"  
      }  
    }  
  ]  
}
```

```
"externalMetricsPreference    "source},  
"inferredWorkloadTypes"lookBackPeriod"preferredResources    {  
        "effectiveIncludeList        "excludeList        "includeList        "name    },  
],  
"resourceType"savingsEstimationMode"scope    "name    "value},  
"utilizationPreferences    {  
        "metricName        "metricParameters            "headroom            "threshold        }  
    }  
]  
}  
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### nextToken

The token to use to advance to the next page of recommendation preferences.

This value is null when there are no more pages of recommendation preferences to return.

Type: String

### [recommendationPreferencesDetails](#)

An array of objects that describe recommendation preferences.

Type: Array of [RecommendationPreferencesDetail](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerException**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

### **OptInRequiredException**

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

### **ResourceNotFoundException**

A resource that is required for the action doesn't exist.

HTTP Status Code: 400

## ServiceUnavailableException

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetRecommendationSummaries

Returns the optimization findings for an account.

It returns the number of:

- Amazon EC2 instances in an account that are Underprovisioned, Overprovisioned, or Optimized.
- EC2Auto Scaling groups in an account that are NotOptimized, or Optimized.
- Amazon EBS volumes in an account that are NotOptimized, or Optimized.
- Lambda functions in an account that are NotOptimized, or Optimized.
- Amazon ECS services in an account that are Underprovisioned, Overprovisioned, or Optimized.
- Commercial software licenses in an account that are InsufficientMetrics, NotOptimized or Optimized.
- Amazon Aurora and Amazon RDS databases in an account that are Underprovisioned, Overprovisioned, Optimized, or NotOptimized.

## Request Syntax

```
{  
    "accountIds": [ "string" ],  
    "maxResults": number,  
    "nextToken": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### accountIds

The ID of the Amazon account for which to return recommendation summaries.

If your account is the management account of an organization, use this parameter to specify the member account for which you want to return recommendation summaries.

Only one account ID can be specified per request.

Type: Array of strings

Required: No

### [maxResults](#)

The maximum number of recommendation summaries to return with a single request.

To retrieve the remaining results, make another request with the returned nextToken value.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000.

Required: No

### [nextToken](#)

The token to advance to the next page of recommendation summaries.

Type: String

Required: No

## Response Syntax

```
{  
    "nextToken": "string",  
    "recommendationSummaries": [  
        {  
            "accountId": "string",  
            "aggregatedSavingsOpportunity": {  
                "estimatedMonthlySavings": {  
                    "currency": "string",  
                    "value": number  
                },  
                "savingsOpportunityPercentage": number  
            },  
            "currentPerformanceRiskRatings": {  
                "high": number,  
                "low": number,  
                "medium": number,  
                "veryLow": number  
            }  
        }  
    ]  
}
```

```
},
  "idleSavingsOpportunity": {
    "estimatedMonthlySavings": {
      "currency": "string",
      "value": number
    },
    "savingsOpportunityPercentage": number
  },
  "idleSummaries": [
    {
      "name": "string",
      "value": number
    }
  ],
  "inferredWorkloadSavings": [
    {
      "estimatedMonthlySavings": {
        "currency": "string",
        "value": number
      },
      "inferredWorkloadTypes": [ "string" ]
    }
  ],
  "recommendationResourceType": "string",
  "savingsOpportunity": {
    "estimatedMonthlySavings": {
      "currency": "string",
      "value": number
    },
    "savingsOpportunityPercentage": number
  },
  "summaries": [
    {
      "name": "string",
      "reasonCodeSummaries": [
        {
          "name": "string",
          "value": number
        }
      ],
      "value": number
    }
  ]
}
```

```
]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [nextToken](#)

The token to use to advance to the next page of recommendation summaries.

This value is null when there are no more pages of recommendation summaries to return.

Type: String

### [recommendationSummaries](#)

An array of objects that summarize a recommendation.

Type: Array of [RecommendationSummary](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerError**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

## MissingAuthenticationToken

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

## OptInRequiredException

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

## ServiceUnavailableException

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# PutRecommendationPreferences

Creates a new recommendation preference or updates an existing recommendation preference, such as enhanced infrastructure metrics.

For more information, see [Activating enhanced infrastructure metrics](#) in the *Amazon Compute Optimizer User Guide*.

## Request Syntax

```
{  
    "enhancedInfrastructureMetrics": "string",  
    "externalMetricsPreference": {  
        "source": "string"  
    },  
    "inferredWorkloadTypes": "string",  
    "lookBackPeriod": "string",  
    "preferredResources": [  
        {  
            "excludeList": [ "string" ],  
            "includeList": [ "string" ],  
            "name": "string"  
        }  
    ],  
    "resourceType": "string",  
    "savingsEstimationMode": "string",  
    "scope": {  
        "name": "string",  
        "value": "string"  
    },  
    "utilizationPreferences": [  
        {  
            "metricName": "string",  
            "metricParameters": {  
                "headroom": "string",  
                "threshold": "string"  
            }  
        }  
    ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [enhancedInfrastructureMetrics](#)

The status of the enhanced infrastructure metrics recommendation preference to create or update.

Specify the Active status to activate the preference, or specify Inactive to deactivate the preference.

For more information, see [Enhanced infrastructure metrics](#) in the *Amazon Compute Optimizer User Guide*.

Type: String

Valid Values: Active | Inactive

Required: No

### [externalMetricsPreference](#)

The provider of the external metrics recommendation preference to create or update.

Specify a valid provider in the source field to activate the preference. To delete this preference, see the [DeleteRecommendationPreferences](#) action.

This preference can only be set for the Ec2Instance resource type.

For more information, see [External metrics ingestion](#) in the *Amazon Compute Optimizer User Guide*.

Type: [ExternalMetricsPreference](#) object

Required: No

### [inferredWorkloadTypes](#)

The status of the inferred workload types recommendation preference to create or update.

**Note**

The inferred workload type feature is active by default. To deactivate it, create a recommendation preference.

Specify the Inactive status to deactivate the feature, or specify Active to activate it.

For more information, see [Inferred workload types](#) in the *Amazon Compute Optimizer User Guide*.

Type: String

Valid Values: Active | Inactive

Required: No

**lookBackPeriod**

The preference to control the number of days the utilization metrics of the Amazon resource are analyzed. When this preference isn't specified, we use the default value DAYS\_14.

You can only set this preference for the Amazon EC2 instance and Auto Scaling group resource types.

**Note**

- Amazon EC2 instance lookback preferences can be set at the organization, account, and resource levels.
- Auto Scaling group lookback preferences can only be set at the resource level.

Type: String

Valid Values: DAYS\_14 | DAYS\_32 | DAYS\_93

Required: No

**preferredResources**

The preference to control which resource type values are considered when generating rightsizing recommendations. You can specify this preference as a combination of include and

exclude lists. You must specify either an `includeList` or `excludeList`. If the preference is an empty set of resource type values, an error occurs.

 **Note**

You can only set this preference for the Amazon EC2 instance and Auto Scaling group resource types.

Type: Array of [PreferredResource](#) objects

Required: No

**resourceType**

The target resource type of the recommendation preference to create.

The `Ec2Instance` option encompasses standalone instances and instances that are part of Auto Scaling groups. The `AutoScalingGroup` option encompasses only instances that are part of an Auto Scaling group.

Type: String

Valid Values: `Ec2Instance` | `AutoScalingGroup` | `RdsDBInstance` | `AuroraDBClusterStorage`

Required: Yes

**savingsEstimationMode**

The status of the savings estimation mode preference to create or update.

Specify the `AfterDiscounts` status to activate the preference, or specify `BeforeDiscounts` to deactivate the preference.

Only the account manager or delegated administrator of your organization can activate this preference.

For more information, see [Savings estimation mode](#) in the *Amazon Compute Optimizer User Guide*.

Type: String

Valid Values: AfterDiscounts | BeforeDiscounts

Required: No

### scope

An object that describes the scope of the recommendation preference to create.

You can create recommendation preferences at the organization level (for management accounts of an organization only), account level, and resource level. For more information, see [Activating enhanced infrastructure metrics](#) in the *Amazon Compute Optimizer User Guide*.

#### Note

You cannot create recommendation preferences for Auto Scaling groups at the organization and account levels. You can create recommendation preferences for Auto Scaling groups only at the resource level by specifying a scope name of ResourceArn and a scope value of the Auto Scaling group Amazon Resource Name (ARN). This will configure the preference for all instances that are part of the specified Auto Scaling group. You also cannot create recommendation preferences at the resource level for instances that are part of an Auto Scaling group. You can create recommendation preferences at the resource level only for standalone instances.

Type: [Scope](#) object

Required: No

### utilizationPreferences

The preference to control the resource's CPU utilization threshold, CPU utilization headroom, and memory utilization headroom. When this preference isn't specified, we use the following default values.

CPU utilization:

- P99\_5 for threshold
- PERCENT\_20 for headroom

Memory utilization:

- PERCENT\_20 for headroom

**Note**

- You can only set CPU and memory utilization preferences for the Amazon EC2 instance resource type.
- The threshold setting isn't available for memory utilization.

Type: Array of [UtilizationPreference](#) objects

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### InternalServerException

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### InvalidParameterValueException

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### MissingAuthenticationToken

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

## OptInRequiredException

The account is not opted in to Amazon Compute Optimizer.

HTTP Status Code: 400

## ResourceNotFoundException

A resource that is required for the action doesn't exist.

HTTP Status Code: 400

## ServiceUnavailableException

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# UpdateEnrollmentStatus

Updates the enrollment (opt in and opt out) status of an account to the Amazon Compute Optimizer service.

If the account is a management account of an organization, this action can also be used to enroll member accounts of the organization.

You must have the appropriate permissions to opt in to Compute Optimizer, to view its recommendations, and to opt out. For more information, see [Controlling access with Amazon Identity and Access Management](#) in the *Amazon Compute Optimizer User Guide*.

When you opt in, Compute Optimizer automatically creates a service-linked role in your account to access its data. For more information, see [Using Service-Linked Roles for Amazon Compute Optimizer](#) in the *Amazon Compute Optimizer User Guide*.

## Request Syntax

```
{  
    "includeMemberAccounts": boolean,  
    "status": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [includeMemberAccounts](#)

Indicates whether to enroll member accounts of the organization if the account is the management account of an organization.

Type: Boolean

Required: No

### [status](#)

The new enrollment status of the account.

The following status options are available:

- Active - Opts in your account to the Compute Optimizer service. Compute Optimizer begins analyzing the configuration and utilization metrics of your Amazon resources after you opt in. For more information, see [Metrics analyzed by Amazon Compute Optimizer](#) in the *Amazon Compute Optimizer User Guide*.
- Inactive - Opts out your account from the Compute Optimizer service. Your account's recommendations and related metrics data will be deleted from Compute Optimizer after you opt out.

 **Note**

The Pending and Failed options cannot be used to update the enrollment status of an account. They are returned in the response of a request to update the enrollment status of an account.

Type: String

Valid Values: Active | Inactive | Pending | Failed

Required: Yes

## Response Syntax

```
{  
    "status": "string",  
    "statusReason": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [status](#)

The enrollment status of the account.

Type: String

Valid Values: Active | Inactive | Pending | Failed

### statusReason

The reason for the enrollment status of the account. For example, an account might show a status of Pending because member accounts of an organization require more time to be enrolled in the service.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### **InternalServerError**

An internal error has occurred. Try your call again.

HTTP Status Code: 500

### **InvalidParameterValueException**

The value supplied for the input parameter is out of range or not valid.

HTTP Status Code: 400

### **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 400

### **ServiceUnavailableException**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# Data Types

The Amazon Compute Optimizer API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccountEnrollmentStatus](#)
- [AutoScalingGroupConfiguration](#)
- [AutoScalingGroupEstimatedMonthlySavings](#)
- [AutoScalingGroupRecommendation](#)
- [AutoScalingGroupRecommendationOption](#)
- [AutoScalingGroupSavingsOpportunityAfterDiscounts](#)
- [ContainerConfiguration](#)
- [ContainerRecommendation](#)
- [CurrentPerformanceRiskRatings](#)
- [CustomizableMetricParameters](#)
- [DBStorageConfiguration](#)
- [EBSEffectiveRecommendationPreferences](#)
- [EBSEstimatedMonthlySavings](#)
- [EBSFilter](#)
- [EBSSavingsEstimationMode](#)
- [EBSSavingsOpportunityAfterDiscounts](#)
- [EBSUtilizationMetric](#)
- [ECSEffectiveRecommendationPreferences](#)
- [ECSEstimatedMonthlySavings](#)
- [ECSSavingsEstimationMode](#)

- [ECSSavingsOpportunityAfterDiscounts](#)
- [ECSServiceProjectedMetric](#)
- [ECSServiceProjectedUtilizationMetric](#)
- [ECSServiceRecommendation](#)
- [ECSServiceRecommendationFilter](#)
- [ECSServiceRecommendationOption](#)
- [ECSServiceRecommendedOptionProjectedMetric](#)
- [ECSServiceUtilizationMetric](#)
- [EffectivePreferredResource](#)
- [EffectiveRecommendationPreferences](#)
- [EnrollmentFilter](#)
- [EstimatedMonthlySavings](#)
- [ExportDestination](#)
- [ExternalMetricsPreference](#)
- [ExternalMetricStatus](#)
- [Filter](#)
- [GetRecommendationError](#)
- [Gpu](#)
- [GpuInfo](#)
- [IdleEstimatedMonthlySavings](#)
- [IdleRecommendation](#)
- [IdleRecommendationError](#)
- [IdleRecommendationFilter](#)
- [IdleSavingsOpportunity](#)
- [IdleSavingsOpportunityAfterDiscounts](#)
- [IdleSummary](#)
- [IdleUtilizationMetric](#)
- [InferredWorkloadSaving](#)
- [InstanceEstimatedMonthlySavings](#)
- [InstanceRecommendation](#)

- [InstanceRecommendationOption](#)
- [InstanceSavingsEstimationMode](#)
- [InstanceSavingsOpportunityAfterDiscounts](#)
- [JobFilter](#)
- [LambdaEffectiveRecommendationPreferences](#)
- [LambdaEstimatedMonthlySavings](#)
- [LambdaFunctionMemoryProjectedMetric](#)
- [LambdaFunctionMemoryRecommendationOption](#)
- [LambdaFunctionRecommendation](#)
- [LambdaFunctionRecommendationFilter](#)
- [LambdaFunctionUtilizationMetric](#)
- [LambdaSavingsEstimationMode](#)
- [LambdaSavingsOpportunityAfterDiscounts](#)
- [LicenseConfiguration](#)
- [LicenseRecommendation](#)
- [LicenseRecommendationFilter](#)
- [LicenseRecommendationOption](#)
- [MemorySizeConfiguration](#)
- [MetricSource](#)
- [OrderBy](#)
- [PreferredResource](#)
- [ProjectedMetric](#)
- [RDSDatabaseProjectedMetric](#)
- [RDSDatabaseRecommendedOptionProjectedMetric](#)
- [RDSDBInstanceRecommendationOption](#)
- [RDSDBRecommendation](#)
- [RDSDBRecommendationFilter](#)
- [RDSDBStorageRecommendationOption](#)
- [RDSDBUtilizationMetric](#)
- [RDSEffectiveRecommendationPreferences](#)

- [RDSInstanceEstimatedMonthlySavings](#)
- [RDSInstanceSavingsOpportunityAfterDiscounts](#)
- [RDSSavingsEstimationMode](#)
- [RDSStorageEstimatedMonthlySavings](#)
- [RDSStorageSavingsOpportunityAfterDiscounts](#)
- [ReasonCodeSummary](#)
- [RecommendationExportJob](#)
- [RecommendationPreferences](#)
- [RecommendationPreferencesDetail](#)
- [RecommendationSource](#)
- [RecommendationSummary](#)
- [RecommendedOptionProjectedMetric](#)
- [S3Destination](#)
- [S3DestinationConfig](#)
- [SavingsOpportunity](#)
- [Scope](#)
- [ServiceConfiguration](#)
- [Summary](#)
- [Tag](#)
- [UtilizationMetric](#)
- [UtilizationPreference](#)
- [VolumeConfiguration](#)
- [VolumeRecommendation](#)
- [VolumeRecommendationOption](#)

# AccountEnrollmentStatus

Describes the enrollment status of an organization's member accounts in Amazon Compute Optimizer.

## Contents

### accountId

The Amazon account ID.

Type: String

Required: No

### lastUpdatedTimestamp

The Unix epoch timestamp, in seconds, of when the account enrollment status was last updated.

Type: Timestamp

Required: No

### status

The account enrollment status.

Type: String

Valid Values: Active | Inactive | Pending | Failed

Required: No

### statusReason

The reason for the account enrollment status.

For example, an account might show a status of Pending because member accounts of an organization require more time to be enrolled in the service.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# AutoScalingGroupConfiguration

Describes the configuration of an EC2 Auto Scaling group.

## Contents

### allocationStrategy

Describes the allocation strategy that the EC2 Auto Scaling group uses. This field is only available for EC2 Auto Scaling groups with mixed instance types.

Type: String

Valid Values: Prioritized | LowestPrice

Required: No

### desiredCapacity

The desired capacity, or number of instances, for the EC2 Auto Scaling group.

Type: Integer

Required: No

### estimatedInstanceHourReductionPercentage

Describes the projected percentage reduction in instance hours after adopting the recommended configuration. This field is only available for EC2 Auto Scaling groups with scaling policies.

Type: Double

Required: No

### instanceType

The instance type for the EC2 Auto Scaling group.

Type: String

Required: No

### maxSize

The maximum size, or maximum number of instances, for the EC2 Auto Scaling group.

Type: Integer

Required: No

### minSize

The minimum size, or minimum number of instances, for the EC2 Auto Scaling group.

Type: Integer

Required: No

### mixedInstanceTypes

List the instance types within an EC2 Auto Scaling group that has mixed instance types.

Type: Array of strings

Required: No

### type

Describes whether the EC2 Auto Scaling group has a single instance type or a mixed instance type configuration.

Type: String

Valid Values: SingleInstanceType | MixedInstanceTypes

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# AutoScalingGroupEstimatedMonthlySavings

An object that describes the estimated monthly savings possible by adopting Compute Optimizer's Auto Scaling group recommendations. This is based on the Savings Plans and Reserved Instances discounts.

## Contents

### **currency**

The currency of the estimated monthly savings.

Type: String

Valid Values: USD | CNY

Required: No

### **value**

The value of the estimated monthly savings.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# AutoScalingGroupRecommendation

Describes an Auto Scaling group recommendation.

## Contents

### accountId

The Amazon account ID of the Auto Scaling group.

Type: String

Required: No

### autoScalingGroupArn

The Amazon Resource Name (ARN) of the Auto Scaling group.

Type: String

Required: No

### autoScalingGroupName

The name of the Auto Scaling group.

Type: String

Required: No

### currentConfiguration

An array of objects that describe the current configuration of the Auto Scaling group.

Type: [AutoScalingGroupConfiguration](#) object

Required: No

### currentInstanceGpuInfo

Describes the GPU accelerator settings for the current instance type of the Auto Scaling group.

Type: [GpuInfo](#) object

Required: No

## currentPerformanceRisk

The risk of the current Auto Scaling group not meeting the performance needs of its workloads. The higher the risk, the more likely the current Auto Scaling group configuration has insufficient capacity and cannot meet workload requirements.

Type: String

Valid Values: VeryLow | Low | Medium | High

Required: No

## effectiveRecommendationPreferences

An object that describes the effective recommendation preferences for the Auto Scaling group.

Type: [EffectiveRecommendationPreferences](#) object

Required: No

## finding

The finding classification of the Auto Scaling group.

Findings for Auto Scaling groups include:

- **NotOptimized**—An Auto Scaling group is considered not optimized when Amazon Compute Optimizer identifies a recommendation that can provide better performance for your workload.
- **Optimized**—An Auto Scaling group is considered optimized when Compute Optimizer determines that the group is correctly provisioned to run your workload based on the chosen instance type. For optimized resources, Compute Optimizer might recommend a new generation instance type.

Type: String

Valid Values: Underprovisioned | Overprovisioned | Optimized | NotOptimized

Required: No

## inferredWorkloadTypes

The applications that might be running on the instances in the Auto Scaling group as inferred by Compute Optimizer.

Compute Optimizer can infer if one of the following applications might be running on the instances:

- AmazonEmr - Infers that Amazon EMR might be running on the instances.
- ApacheCassandra - Infers that Apache Cassandra might be running on the instances.
- ApacheHadoop - Infers that Apache Hadoop might be running on the instances.
- Memcached - Infers that Memcached might be running on the instances.
- NGINX - Infers that NGINX might be running on the instances.
- PostgreSql - Infers that PostgreSQL might be running on the instances.
- Redis - Infers that Redis might be running on the instances.
- Kafka - Infers that Kafka might be running on the instance.
- SQLServer - Infers that SQLServer might be running on the instance.

Type: Array of strings

Valid Values: AmazonEmr | ApacheCassandra | ApacheHadoop | Memcached | Nginx | PostgreSql | Redis | Kafka | SQLServer

Required: No

### **lastRefreshTimestamp**

The timestamp of when the Auto Scaling group recommendation was last generated.

Type: Timestamp

Required: No

### **lookBackPeriodInDays**

The number of days for which utilization metrics were analyzed for the Auto Scaling group.

Type: Double

Required: No

### **recommendationOptions**

An array of objects that describe the recommendation options for the Auto Scaling group.

Type: Array of [AutoScalingGroupRecommendationOption](#) objects

Required: No

## utilizationMetrics

An array of objects that describe the utilization metrics of the Auto Scaling group.

Type: Array of [UtilizationMetric](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# AutoScalingGroupRecommendationOption

Describes a recommendation option for an Auto Scaling group.

## Contents

### configuration

An array of objects that describe an Auto Scaling group configuration.

Type: [AutoScalingGroupConfiguration](#) object

Required: No

### instanceGpuInfo

Describes the GPU accelerator settings for the recommended instance type of the Auto Scaling group.

Type: [GpuInfo](#) object

Required: No

### migrationEffort

The level of effort required to migrate from the current instance type to the recommended instance type.

For example, the migration effort is Low if Amazon EMR is the inferred workload type and an Amazon Graviton instance type is recommended. The migration effort is Medium if a workload type couldn't be inferred but an Amazon Graviton instance type is recommended. The migration effort is VeryLow if both the current and recommended instance types are of the same CPU architecture.

Type: String

Valid Values: VeryLow | Low | Medium | High

Required: No

### performanceRisk

The performance risk of the Auto Scaling group configuration recommendation.

Performance risk indicates the likelihood of the recommended instance type not meeting the resource needs of your workload. Compute Optimizer calculates an individual performance risk score for each specification of the recommended instance, including CPU, memory, EBS throughput, EBS IOPS, disk throughput, disk IOPS, network throughput, and network PPS. The performance risk of the recommended instance is calculated as the maximum performance risk score across the analyzed resource specifications.

The value ranges from 0 - 4, with 0 meaning that the recommended resource is predicted to always provide enough hardware capability. The higher the performance risk is, the more likely you should validate whether the recommendation will meet the performance requirements of your workload before migrating your resource.

Type: Double

Valid Range: Minimum value of 0. Maximum value of 4.

Required: No

### **projectedUtilizationMetrics**

An array of objects that describe the projected utilization metrics of the Auto Scaling group recommendation option.

#### **Note**

The Cpu and Memory metrics are the only projected utilization metrics returned. Additionally, the Memory metric is returned only for resources that have the unified CloudWatch agent installed on them. For more information, see [Enabling Memory Utilization with the CloudWatch Agent](#).

Type: Array of [UtilizationMetric](#) objects

Required: No

### **rank**

The rank of the Auto Scaling group recommendation option.

The top recommendation option is ranked as 1.

Type: Integer

Required: No

### savingsOpportunity

An object that describes the savings opportunity for the Auto Scaling group recommendation option. Savings opportunity includes the estimated monthly savings amount and percentage.

Type: [SavingsOpportunity](#) object

Required: No

### savingsOpportunityAfterDiscounts

An object that describes the savings opportunity for the Auto Scaling group recommendation option that includes Savings Plans and Reserved Instances discounts. Savings opportunity includes the estimated monthly savings and percentage.

Type: [AutoScalingGroupSavingsOpportunityAfterDiscounts](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# AutoScalingGroupSavingsOpportunityAfterDiscounts

Describes the savings opportunity for Auto Scaling group recommendations after applying the Savings Plans and Reserved Instances discounts.

Savings opportunity represents the estimated monthly savings you can achieve by implementing Compute Optimizer recommendations.

## Contents

### **estimatedMonthlySavings**

An object that describes the estimated monthly savings possible by adopting Compute Optimizer's Auto Scaling group recommendations. This is based on the Savings Plans and Reserved Instances pricing discounts.

Type: [AutoScalingGroupEstimatedMonthlySavings](#) object

Required: No

### **savingsOpportunityPercentage**

The estimated monthly savings possible as a percentage of monthly cost after applying the Savings Plans and Reserved Instances discounts. This saving can be achieved by adopting Compute Optimizer's Auto Scaling group recommendations.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ContainerConfiguration

Describes the container configurations within the tasks of your Amazon ECS service.

## Contents

### **containerName**

The name of the container.

Type: String

Required: No

### **cpu**

The number of CPU units reserved for the container.

Type: Integer

Required: No

### **memorySizeConfiguration**

The memory size configurations for the container.

Type: [MemorySizeConfiguration](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ContainerRecommendation

The CPU and memory recommendations for a container within the tasks of your Amazon ECS service.

## Contents

### **containerName**

The name of the container.

Type: String

Required: No

### **cpu**

The recommended number of CPU units reserved for the container.

Type: Integer

Required: No

### **memorySizeConfiguration**

The recommended memory size configurations for the container.

Type: [MemorySizeConfiguration](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# CurrentPerformanceRiskRatings

Describes the performance risk ratings for a given resource type.

Resources with a high or medium rating are at risk of not meeting the performance needs of their workloads, while resources with a low rating are performing well in their workloads.

## Contents

### high

A count of the applicable resource types with a high performance risk rating.

Type: Long

Required: No

### low

A count of the applicable resource types with a low performance risk rating.

Type: Long

Required: No

### medium

A count of the applicable resource types with a medium performance risk rating.

Type: Long

Required: No

### veryLow

A count of the applicable resource types with a very low performance risk rating.

Type: Long

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# CustomizableMetricParameters

Defines the various metric parameters that can be customized, such as threshold and headroom.

## Contents

### headroom

The headroom value in percentage used for the specified metric parameter.

The following lists the valid values for CPU and memory utilization.

- CPU utilization: PERCENT\_30 | PERCENT\_20 | PERCENT\_0
- Memory utilization: PERCENT\_30 | PERCENT\_20 | PERCENT\_10

Type: String

Valid Values: PERCENT\_30 | PERCENT\_20 | PERCENT\_10 | PERCENT\_0

Required: No

### threshold

The threshold value used for the specified metric parameter.

 **Note**

You can only specify the threshold value for CPU utilization.

Type: String

Valid Values: P90 | P95 | P99\_5

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# DBStorageConfiguration

The configuration of the recommended RDS storage.

## Contents

### allocatedStorage

The size of the DB storage in gigabytes (GB).

Type: Integer

Required: No

### iops

The provisioned IOPs of the DB storage.

Type: Integer

Required: No

### maxAllocatedStorage

The maximum limit in gibibytes (GiB) to which Amazon RDS can automatically scale the storage of the DB instance.

Type: Integer

Required: No

### storageThroughput

The storage throughput of the DB storage.

Type: Integer

Required: No

### storageType

The type of DB storage.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# EBSEffectiveRecommendationPreferences

Describes the effective recommendation preferences for Amazon EBS volumes.

## Contents

### savingsEstimationMode

Describes the savings estimation mode preference applied for calculating savings opportunity for Amazon EBS volumes.

Type: [EBSSavingsEstimationMode](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# EBSEstimatedMonthlySavings

An object that describes the estimated monthly savings possible by adopting Compute Optimizer's Amazon EBS volume recommendations. This includes any applicable discounts.

## Contents

### **currency**

The currency of the estimated monthly savings.

Type: String

Valid Values: USD | CNY

Required: No

### **value**

The value of the estimated monthly savings.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# EBSFilter

Describes a filter that returns a more specific list of Amazon Elastic Block Store (Amazon EBS) volume recommendations. Use this filter with the [GetEBSVolumeRecommendations](#) action.

You can use LambdaFunctionRecommendationFilter with the [GetLambdaFunctionRecommendations](#) action, JobFilter with the [DescribeRecommendationExportJobs](#) action, and Filter with the [GetAutoScalingGroupRecommendations](#) and [GetEC2InstanceRecommendations](#) actions.

## Contents

### **name**

The name of the filter.

Specify **Finding** to return recommendations with a specific finding classification (for example, **NotOptimized**).

You can filter your Amazon EBS volume recommendations by tag :key and tag -key tags.

A tag :key is a key and value combination of a tag assigned to your Amazon EBS volume recommendations. Use the tag key in the filter name and the tag value as the filter value. For example, to find all Amazon EBS volume recommendations that have a tag with the key of **Owner** and the value of **TeamA**, specify **tag:Owner** for the filter name and **TeamA** for the filter value.

A tag -key is the key of a tag assigned to your Amazon EBS volume recommendations. Use this filter to find all of your Amazon EBS volume recommendations that have a tag with a specific key. This doesn't consider the tag value. For example, you can find your Amazon EBS volume recommendations with a tag key value of **Owner** or without any tag keys assigned.

Type: String

Valid Values: **Finding**

Required: No

### **values**

The value of the filter.

The valid values are Optimized, or NotOptimized.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# EBSSavingsEstimationMode

Describes the savings estimation mode used for calculating savings opportunity for Amazon EBS volumes.

## Contents

### source

Describes the source for calculating the savings opportunity for Amazon EBS volumes.

Type: String

Valid Values: PublicPricing | CostExplorerRightsizing | CostOptimizationHub

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# EBSSavingsOpportunityAfterDiscounts

Describes the savings opportunity for Amazon EBS volume recommendations after applying specific discounts.

## Contents

### **estimatedMonthlySavings**

The estimated monthly savings possible as a percentage of monthly cost by adopting Compute Optimizer's Amazon EBS volume recommendations. This saving includes any applicable discounts.

Type: [EBSEstimatedMonthlySavings](#) object

Required: No

### **savingsOpportunityPercentage**

The estimated monthly savings possible as a percentage of monthly cost after applying the specific discounts. This saving can be achieved by adopting Compute Optimizer's Amazon EBS volume recommendations.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# EBSUtilizationMetric

Describes a utilization metric of an Amazon Elastic Block Store (Amazon EBS) volume.

Compare the utilization metric data of your resource against its projected utilization metric data to determine the performance difference between your current resource and the recommended option.

## Contents

### **name**

The name of the utilization metric.

The following utilization metrics are available:

- `VolumeReadOpsPerSecond` - The completed read operations per second from the volume in a specified period of time.

Unit: Count

- `VolumeWriteOpsPerSecond` - The completed write operations per second to the volume in a specified period of time.

Unit: Count

- `VolumeReadBytesPerSecond` - The bytes read per second from the volume in a specified period of time.

Unit: Bytes

- `VolumeWriteBytesPerSecond` - The bytes written to the volume in a specified period of time.

Unit: Bytes

Type: String

Valid Values: `VolumeReadOpsPerSecond` | `VolumeWriteOpsPerSecond` |  
`VolumeReadBytesPerSecond` | `VolumeWriteBytesPerSecond`

Required: No

## statistic

The statistic of the utilization metric.

The Compute Optimizer API, Amazon Command Line Interface (Amazon CLI), and SDKs return utilization metrics using only the Maximum statistic, which is the highest value observed during the specified period.

The Compute Optimizer console displays graphs for some utilization metrics using the Average statistic, which is the value of Sum / SampleCount during the specified period. For more information, see [Viewing resource recommendations](#) in the *Amazon Compute Optimizer User Guide*. You can also get averaged utilization metric data for your resources using Amazon CloudWatch. For more information, see the [Amazon CloudWatch User Guide](#).

Type: String

Valid Values: Maximum | Average

Required: No

## value

The value of the utilization metric.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ECSEffectiveRecommendationPreferences

Describes the effective recommendation preferences for Amazon ECS services.

## Contents

### savingsEstimationMode

Describes the savings estimation mode preference applied for calculating savings opportunity for Amazon ECS services.

Type: [ECSSavingsEstimationMode](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ECSEstimatedMonthlySavings

Describes the estimated monthly savings possible for Amazon ECS services by adopting Compute Optimizer recommendations. This is based on Amazon ECS service pricing after applying Savings Plans discounts.

## Contents

### **currency**

The currency of the estimated monthly savings.

Type: String

Valid Values: USD | CNY

Required: No

### **value**

The value of the estimated monthly savings for Amazon ECS services.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ECSSavingsEstimationMode

Describes the savings estimation mode used for calculating savings opportunity for Amazon ECS services.

## Contents

### source

Describes the source for calculating the savings opportunity for Amazon ECS services.

Type: String

Valid Values: PublicPricing | CostExplorerRightsizing | CostOptimizationHub

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ECSSavingsOpportunityAfterDiscounts

Describes the savings opportunity for Amazon ECS service recommendations after applying Savings Plans discounts.

Savings opportunity represents the estimated monthly savings after applying Savings Plans discounts. You can achieve this by implementing a given Compute Optimizer recommendation.

## Contents

### **estimatedMonthlySavings**

The estimated monthly savings possible by adopting Compute Optimizer's Amazon ECS service recommendations. This includes any applicable Savings Plans discounts.

Type: [ECSEstimatedMonthlySavings](#) object

Required: No

### **savingsOpportunityPercentage**

The estimated monthly savings possible as a percentage of monthly cost by adopting Compute Optimizer's Amazon ECS service recommendations. This includes any applicable Savings Plans discounts.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ECSServiceProjectedMetric

Describes the projected metrics of an Amazon ECS service recommendation option.

To determine the performance difference between your current Amazon ECS service and the recommended option, compare the metric data of your service against its projected metric data.

## Contents

### **lowerBoundValues**

The lower bound values for the projected metric.

Type: Array of doubles

Required: No

### **name**

The name of the projected metric.

The following metrics are available:

- Cpu — The percentage of allocated compute units that are currently in use on the service tasks.
- Memory — The percentage of memory that's currently in use on the service tasks.

Type: String

Valid Values: Cpu | Memory

Required: No

### **timestamps**

The timestamps of the projected metric.

Type: Array of timestamps

Required: No

### **upperBoundValues**

The upper bound values for the projected metric.

Type: Array of doubles

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ECSServiceProjectedUtilizationMetric

Describes the projected utilization metrics of an Amazon ECS service recommendation option.

To determine the performance difference between your current Amazon ECS service and the recommended option, compare the utilization metric data of your service against its projected utilization metric data.

## Contents

### **lowerBoundValue**

The lower bound values for the projected utilization metrics.

Type: Double

Required: No

### **name**

The name of the projected utilization metric.

The following utilization metrics are available:

- Cpu — The percentage of allocated compute units that are currently in use on the service tasks.
- Memory — The percentage of memory that's currently in use on the service tasks.

Type: String

Valid Values: Cpu | Memory

Required: No

### **statistic**

The statistic of the projected utilization metric.

The Compute Optimizer API, Amazon Command Line Interface (Amazon CLI), and SDKs return utilization metrics using only the Maximum statistic, which is the highest value observed during the specified period.

The Compute Optimizer console displays graphs for some utilization metrics using the Average statistic, which is the value of Sum / SampleCount during the specified period. For more

information, see [Viewing resource recommendations](#) in the *Amazon Compute Optimizer User Guide*. You can also get averaged utilization metric data for your resources using Amazon CloudWatch. For more information, see the [Amazon CloudWatch User Guide](#).

Type: String

Valid Values: Maximum | Average

Required: No

### **upperBoundValue**

The upper bound values for the projected utilization metrics.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ECSServiceRecommendation

Describes an Amazon ECS service recommendation.

## Contents

### accountId

The Amazon Web Services account ID of the Amazon ECS service.

Type: String

Required: No

### currentPerformanceRisk

The risk of the current Amazon ECS service not meeting the performance needs of its workloads. The higher the risk, the more likely the current service can't meet the performance requirements of its workload.

Type: String

Valid Values: VeryLow | Low | Medium | High

Required: No

### currentServiceConfiguration

The configuration of the current Amazon ECS service.

Type: [ServiceConfiguration](#) object

Required: No

### effectiveRecommendationPreferences

Describes the effective recommendation preferences for Amazon ECS services.

Type: [ECSEffectiveRecommendationPreferences](#) object

Required: No

### finding

The finding classification of an Amazon ECS service.

Findings for Amazon ECS services include:

- **Underprovisioned** — When Compute Optimizer detects that there's not enough memory or CPU, an Amazon ECS service is considered under-provisioned. An under-provisioned service might result in poor application performance.
- **Overprovisioned** — When Compute Optimizer detects that there's excessive memory or CPU, an Amazon ECS service is considered over-provisioned. An over-provisioned service might result in additional infrastructure costs.
- **Optimized** — When both the CPU and memory of your Amazon ECS service meet the performance requirements of your workload, the service is considered optimized.

Type: String

Valid Values: Optimized | Underprovisioned | Overprovisioned

Required: No

#### **findingReasonCodes**

The reason for the finding classification of an Amazon ECS service.

Finding reason codes for Amazon ECS services include:

- **CPUUnderprovisioned** — The service CPU configuration can be sized up to enhance the performance of your workload. This is identified by analyzing the CPUUtilization metric of the current service during the look-back period.
- **CPUOverprovisioned** — The service CPU configuration can be sized down while still meeting the performance requirements of your workload. This is identified by analyzing the CPUUtilization metric of the current service during the look-back period.
- **MemoryUnderprovisioned** — The service memory configuration can be sized up to enhance the performance of your workload. This is identified by analyzing the MemoryUtilization metric of the current service during the look-back period.
- **MemoryOverprovisioned** — The service memory configuration can be sized down while still meeting the performance requirements of your workload. This is identified by analyzing the MemoryUtilization metric of the current service during the look-back period.

Type: Array of strings

Valid Values: MemoryOverprovisioned | MemoryUnderprovisioned | CPUOverprovisioned | CPUUnderprovisioned

Required: No

### lastRefreshTimestamp

The timestamp of when the Amazon ECS service recommendation was last generated.

Type: Timestamp

Required: No

### launchType

The launch type the Amazon ECS service is using.

 **Note**

Compute Optimizer only supports the Fargate launch type.

Type: String

Valid Values: EC2 | Fargate

Required: No

### lookbackPeriodInDays

The number of days the Amazon ECS service utilization metrics were analyzed.

Type: Double

Required: No

### serviceArn

The Amazon Resource Name (ARN) of the current Amazon ECS service.

The following is the format of the ARN:

`arn:aws:ecs:region:aws_account_id:service/cluster-name/service-name`

Type: String

Required: No

## serviceRecommendationOptions

An array of objects that describe the recommendation options for the Amazon ECS service.

Type: Array of [ECSServiceRecommendationOption](#) objects

Required: No

## tags

A list of tags assigned to your Amazon ECS service recommendations.

Type: Array of [Tag](#) objects

Required: No

## utilizationMetrics

An array of objects that describe the utilization metrics of the Amazon ECS service.

Type: Array of [ECSServiceUtilizationMetric](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ECSServiceRecommendationFilter

Describes a filter that returns a more specific list of Amazon ECS service recommendations. Use this filter with the [GetECSServiceRecommendations](#) action.

## Contents

### **name**

The name of the filter.

Specify `Finding` to return recommendations with a specific finding classification.

Specify `FindingReasonCode` to return recommendations with a specific finding reason code.

You can filter your Amazon ECS service recommendations by `tag:key` and `tag-key` tags.

A `tag:key` is a key and value combination of a tag assigned to your Amazon ECS service recommendations. Use the tag key in the filter name and the tag value as the filter value. For example, to find all Amazon ECS service recommendations that have a tag with the key of `Owner` and the value of `TeamA`, specify `tag:Owner` for the filter name and `TeamA` for the filter value.

A `tag-key` is the key of a tag assigned to your Amazon ECS service recommendations. Use this filter to find all of your Amazon ECS service recommendations that have a tag with a specific key. This doesn't consider the tag value. For example, you can find your Amazon ECS service recommendations with a tag key value of `Owner` or without any tag keys assigned.

Type: String

Valid Values: `Finding` | `FindingReasonCode`

Required: No

### **values**

The value of the filter.

The valid values for this parameter are as follows:

- If you specify the `name` parameter as `Finding`, specify `Optimized`, `Underprovisioned`, or `Overprovisioned`.

- If you specify the name parameter as `FindingReasonCode`, specify `CPUUnderprovisioned`, `CPUOverprovisioned`, `MemoryUnderprovisioned`, or `MemoryOverprovisioned`.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ECSServiceRecommendationOption

Describes the recommendation options for an Amazon ECS service.

## Contents

### **containerRecommendations**

The CPU and memory size recommendations for the containers within the task of your Amazon ECS service.

Type: Array of [ContainerRecommendation](#) objects

Required: No

### **cpu**

The CPU size of the Amazon ECS service recommendation option.

Type: Integer

Required: No

### **memory**

The memory size of the Amazon ECS service recommendation option.

Type: Integer

Required: No

### **projectedUtilizationMetrics**

An array of objects that describe the projected utilization metrics of the Amazon ECS service recommendation option.

Type: Array of [ECSServiceProjectedUtilizationMetric](#) objects

Required: No

### **savingsOpportunity**

Describes the savings opportunity for recommendations of a given resource type or for the recommendation option of an individual resource.

Savings opportunity represents the estimated monthly savings you can achieve by implementing a given Compute Optimizer recommendation.

**⚠ Important**

Savings opportunity data requires that you opt in to Cost Explorer, as well as activate **Receive Amazon EC2 resource recommendations** in the Cost Explorer preferences page. That creates a connection between Cost Explorer and Compute Optimizer. With this connection, Cost Explorer generates savings estimates considering the price of existing resources, the price of recommended resources, and historical usage data. Estimated monthly savings reflects the projected dollar savings associated with each of the recommendations generated. For more information, see [Enabling Cost Explorer](#) and [Optimizing your cost with Rightsizing Recommendations](#) in the *Cost Management User Guide*.

Type: [SavingsOpportunity](#) object

Required: No

**savingsOpportunityAfterDiscounts**

Describes the savings opportunity for Amazon ECS service recommendations or for the recommendation option.

Savings opportunity represents the estimated monthly savings after applying Savings Plans discounts. You can achieve this by implementing a given Compute Optimizer recommendation.

Type: [ECSSavingsOpportunityAfterDiscounts](#) object

Required: No

**See Also**

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

# ECSServiceRecommendedOptionProjectedMetric

Describes the projected metrics of an Amazon ECS service recommendation option.

To determine the performance difference between your current Amazon ECS service and the recommended option, compare the metric data of your service against its projected metric data.

## Contents

### **projectedMetrics**

An array of objects that describe the projected metric.

Type: Array of [ECSServiceProjectedMetric](#) objects

Required: No

### **recommendedCpuUnits**

The recommended CPU size for the Amazon ECS service.

Type: Integer

Required: No

### **recommendedMemorySize**

The recommended memory size for the Amazon ECS service.

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)



# ECSServiceUtilizationMetric

Describes the utilization metric of an Amazon ECS service.

To determine the performance difference between your current Amazon ECS service and the recommended option, compare the utilization metric data of your service against its projected utilization metric data.

## Contents

### **name**

The name of the utilization metric.

The following utilization metrics are available:

- Cpu — The amount of CPU capacity that's used in the service.
- Memory — The amount of memory that's used in the service.

Type: String

Valid Values: Cpu | Memory

Required: No

### **statistic**

The statistic of the utilization metric.

The Compute Optimizer API, Amazon Command Line Interface (Amazon CLI), and SDKs return utilization metrics using only the Maximum statistic, which is the highest value observed during the specified period.

The Compute Optimizer console displays graphs for some utilization metrics using the Average statistic, which is the value of Sum / SampleCount during the specified period. For more information, see [Viewing resource recommendations](#) in the *Amazon Compute Optimizer User Guide*. You can also get averaged utilization metric data for your resources using Amazon CloudWatch. For more information, see the [Amazon CloudWatch User Guide](#).

Type: String

Valid Values: Maximum | Average

Required: No

### value

The value of the utilization metric.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# EffectivePreferredResource

Describes the effective preferred resources that Compute Optimizer considers as rightsizing recommendation candidates.

 **Note**

Compute Optimizer only supports Amazon EC2 instance types.

## Contents

### **effectiveIncludeList**

The expanded version of your preferred resource's include list.

Type: Array of strings

Required: No

### **excludeList**

The list of preferred resources values that you want excluded from rightsizing recommendation candidates.

Type: Array of strings

Required: No

### **includeList**

The list of preferred resource values that you want considered as rightsizing recommendation candidates.

Type: Array of strings

Required: No

### **name**

The name of the preferred resource list.

Type: String

**Valid Values: Ec2InstanceTypes**

**Required:** No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# EffectiveRecommendationPreferences

Describes the effective recommendation preferences for a resource.

## Contents

### cpuVendorArchitectures

Describes the CPU vendor and architecture for an instance or Auto Scaling group recommendations.

For example, when you specify AWS\_ARM64 with:

- A [GetEC2InstanceRecommendations](#) or [GetAutoScalingGroupRecommendations](#) request, Compute Optimizer returns recommendations that consist of Graviton instance types only.
- A [GetEC2RecommendationProjectedMetrics](#) request, Compute Optimizer returns projected utilization metrics for Graviton instance type recommendations only.
- A [ExportEC2InstanceRecommendations](#) or [ExportAutoScalingGroupRecommendations](#) request, Compute Optimizer exports recommendations that consist of Graviton instance types only.

Type: Array of strings

Valid Values: AWS\_ARM64 | CURRENT

Required: No

### enhancedInfrastructureMetrics

Describes the activation status of the enhanced infrastructure metrics preference.

A status of Active confirms that the preference is applied in the latest recommendation refresh, and a status of Inactive confirms that it's not yet applied to recommendations.

For more information, see [Enhanced infrastructure metrics](#) in the *Amazon Compute Optimizer User Guide*.

Type: String

Valid Values: Active | Inactive

Required: No

## externalMetricsPreference

An object that describes the external metrics recommendation preference.

If the preference is applied in the latest recommendation refresh, an object with a valid source value appears in the response. If the preference isn't applied to the recommendations already, then this object doesn't appear in the response.

Type: [ExternalMetricsPreference](#) object

Required: No

## inferredWorkloadTypes

Describes the activation status of the inferred workload types preference.

A status of Active confirms that the preference is applied in the latest recommendation refresh. A status of Inactive confirms that it's not yet applied to recommendations.

Type: String

Valid Values: Active | Inactive

Required: No

## lookBackPeriod

The number of days the utilization metrics of the Amazon resource are analyzed.

Type: String

Valid Values: DAYS\_14 | DAYS\_32 | DAYS\_93

Required: No

## preferredResources

The resource type values that are considered as candidates when generating rightsizing recommendations.

Type: Array of [EffectivePreferredResource](#) objects

Required: No

## savingsEstimationMode

Describes the savings estimation mode applied for calculating savings opportunity for a resource.

Type: [InstanceSavingsEstimationMode](#) object

Required: No

## utilizationPreferences

The resource's CPU and memory utilization preferences, such as threshold and headroom, that are used to generate rightsizing recommendations.

 **Note**

This preference is only available for the Amazon EC2 instance resource type.

Type: Array of [UtilizationPreference](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# EnrollmentFilter

Describes a filter that returns a more specific list of account enrollment statuses. Use this filter with the [GetEnrollmentStatusesForOrganization](#) action.

## Contents

### **name**

The name of the filter.

Specify Status to return accounts with a specific enrollment status (for example, Active).

Type: String

Valid Values: Status

Required: No

### **values**

The value of the filter.

The valid values are Active, Inactive, Pending, and Failed.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# EstimatedMonthlySavings

Describes the estimated monthly savings amount possible, based on On-Demand instance pricing, by adopting Compute Optimizer recommendations for a given resource.

For more information, see [Estimated monthly savings and savings opportunities](#) in the *Amazon Compute Optimizer User Guide*.

## Contents

### **currency**

The currency of the estimated monthly savings.

Type: String

Valid Values: USD

Required: No

### **value**

The value of the estimated monthly savings.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ExportDestination

Describes the destination of the recommendations export and metadata files.

## Contents

### s3

An object that describes the destination Amazon Simple Storage Service (Amazon S3) bucket name and object keys of a recommendations export file, and its associated metadata file.

Type: [S3Destination](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ExternalMetricsPreference

Describes the external metrics preferences for EC2 rightsizing recommendations.

## Contents

### source

Contains the source options for external metrics preferences.

Type: String

Valid Values: Datadog | Dynatrace | NewRelic | Instana

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ExternalMetricStatus

Describes Compute Optimizer's integration status with your chosen external metric provider. For example, Datadog.

## Contents

### **statusCode**

The status code for Compute Optimizer's integration with an external metrics provider.

Type: String

Valid Values: NO\_EXTERNAL\_METRIC\_SET | INTEGRATION\_SUCCESS |  
DATADOG\_INTEGRATION\_ERROR | DYNATRACE\_INTEGRATION\_ERROR |  
NEWRELIC\_INTEGRATION\_ERROR | INSTANA\_INTEGRATION\_ERROR |  
INSUFFICIENT\_DATADOG\_METRICS | INSUFFICIENT\_DYNATRACE\_METRICS |  
INSUFFICIENT\_NEWRELIC\_METRICS | INSUFFICIENT\_INSTANA\_METRICS

Required: No

### **statusReason**

The reason for Compute Optimizer's integration status with your external metric provider.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# Filter

Describes a filter that returns a more specific list of recommendations. Use this filter with the [GetAutoScalingGroupRecommendations](#) and [GetEC2InstanceRecommendations](#) actions.

You can use EBSFilter with the [GetEBSVolumeRecommendations](#) action, LambdaFunctionRecommendationFilter with the [GetLambdaFunctionRecommendations](#) action, and JobFilter with the [DescribeRecommendationExportJobs](#) action.

## Contents

### **name**

The name of the filter.

Specify **Finding** to return recommendations with a specific finding classification. For example, Underprovisioned.

Specify **RecommendationSourceType** to return recommendations of a specific resource type. For example, Ec2Instance.

Specify **FindingReasonCodes** to return recommendations with a specific finding reason code. For example, CPUUnderprovisioned.

Specify **InferredWorkloadTypes** to return recommendations of a specific inferred workload. For example, Redis.

You can filter your EC2 instance recommendations by tag :key and tag-key tags.

A tag :key is a key and value combination of a tag assigned to your recommendations. Use the tag key in the filter name and the tag value as the filter value. For example, to find all recommendations that have a tag with the key of Owner and the value of TeamA, specify tag:Owner for the filter name and TeamA for the filter value.

A tag-key is the key of a tag assigned to your recommendations. Use this filter to find all of your recommendations that have a tag with a specific key. This doesn't consider the tag value. For example, you can find your recommendations with a tag key value of Owner or without any tag keys assigned.

Type: String

Valid Values: Finding | FindingReasonCodes | RecommendationSourceType | InferredWorkloadTypes

Required: No

## values

The value of the filter.

The valid values for this parameter are as follows, depending on what you specify for the name parameter and the resource type that you wish to filter results for:

- Specify Optimized or NotOptimized if you specify the name parameter as Finding and you want to filter results for Auto Scaling groups.
- Specify Underprovisioned, Overprovisioned, or Optimized if you specify the name parameter as Finding and you want to filter results for EC2 instances.
- Specify Ec2Instance or AutoScalingGroup if you specify the name parameter as RecommendationSourceType.
- Specify one of the following options if you specify the name parameter as FindingReasonCodes:
  - **CPUOverprovisioned** — The instance's CPU configuration can be sized down while still meeting the performance requirements of your workload.
  - **CPUUnderprovisioned** — The instance's CPU configuration doesn't meet the performance requirements of your workload and there is an alternative instance type that provides better CPU performance.
  - **MemoryOverprovisioned** — The instance's memory configuration can be sized down while still meeting the performance requirements of your workload.
  - **MemoryUnderprovisioned** — The instance's memory configuration doesn't meet the performance requirements of your workload and there is an alternative instance type that provides better memory performance.
  - **EBSThroughputOverprovisioned** — The instance's EBS throughput configuration can be sized down while still meeting the performance requirements of your workload.
  - **EBSThroughputUnderprovisioned** — The instance's EBS throughput configuration doesn't meet the performance requirements of your workload and there is an alternative instance type that provides better EBS throughput performance.
  - **EBSIOPSOverprovisioned** — The instance's EBS IOPS configuration can be sized down while still meeting the performance requirements of your workload.

- **EBSIOPSUnderprovisioned** — The instance's EBS IOPS configuration doesn't meet the performance requirements of your workload and there is an alternative instance type that provides better EBS IOPS performance.
- **NetworkBandwidthOverprovisioned** — The instance's network bandwidth configuration can be sized down while still meeting the performance requirements of your workload.
- **NetworkBandwidthUnderprovisioned** — The instance's network bandwidth configuration doesn't meet the performance requirements of your workload and there is an alternative instance type that provides better network bandwidth performance. This finding reason happens when the NetworkIn or NetworkOut performance of an instance is impacted.
- **NetworkPPSOverprovisioned** — The instance's network PPS (packets per second) configuration can be sized down while still meeting the performance requirements of your workload.
- **NetworkPPSUnderprovisioned** — The instance's network PPS (packets per second) configuration doesn't meet the performance requirements of your workload and there is an alternative instance type that provides better network PPS performance.
- **DiskIOPSOverprovisioned** — The instance's disk IOPS configuration can be sized down while still meeting the performance requirements of your workload.
- **DiskIOPSSUnderprovisioned** — The instance's disk IOPS configuration doesn't meet the performance requirements of your workload and there is an alternative instance type that provides better disk IOPS performance.
- **DiskThroughputOverprovisioned** — The instance's disk throughput configuration can be sized down while still meeting the performance requirements of your workload.
- **DiskThroughputUnderprovisioned** — The instance's disk throughput configuration doesn't meet the performance requirements of your workload and there is an alternative instance type that provides better disk throughput performance.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# GetRecommendationError

Describes an error experienced when getting recommendations.

For example, an error is returned if you request recommendations for an unsupported Auto Scaling group, or if you request recommendations for an instance of an unsupported instance family.

## Contents

### code

The error code.

Type: String

Required: No

### identifier

The ID of the error.

Type: String

Required: No

### message

The message, or reason, for the error.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)



# Gpu

Describes the GPU accelerators for the instance type.

## Contents

### gpuCount

The number of GPUs for the instance type.

Type: Integer

Required: No

### gpuMemorySizeInMiB

The total size of the memory for the GPU accelerators for the instance type, in MiB.

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# GpuInfo

Describes the GPU accelerator settings for the instance type.

## Contents

### gpus

Describes the GPU accelerators for the instance type.

Type: Array of [Gpu](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# IdleEstimatedMonthlySavings

Describes the estimated monthly savings possible for idle resources by adopting Compute Optimizer recommendations.

## Contents

### **currency**

The currency of the estimated monthly savings.

Type: String

Valid Values: USD | CNY

Required: No

### **value**

The value of the estimated monthly savings for Idle resources.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# IdleRecommendation

Describes an Idle resource recommendation.

## Contents

### accountId

The Amazon Web Services account ID of the idle resource.

Type: String

Required: No

### finding

The finding classification of an idle resource.

Type: String

Valid Values: Idle | Unattached

Required: No

### findingDescription

A summary of the findings for the resource.

Type: String

Required: No

### lastRefreshTimestamp

The timestamp of when the idle resource recommendation was last generated.

Type: Timestamp

Required: No

### lookBackPeriodInDays

The number of days the idle resource utilization metrics were analyzed.

Type: Double

Required: No

### **resourceArn**

The ARN of the current idle resource.

Type: String

Required: No

### **resourceId**

The unique identifier for the resource.

Type: String

Required: No

### **resourceType**

The type of resource that is idle.

Type: String

Valid Values: EC2Instance | AutoScalingGroup | EBSVolume | ECSService | RDSDBInstance

Required: No

### **savingsOpportunity**

The savings opportunity for the idle resource.

Type: [IdleSavingsOpportunity](#) object

Required: No

### **savingsOpportunityAfterDiscounts**

The savings opportunity for the idle resource after any applying discounts.

Type: [IdleSavingsOpportunityAfterDiscounts](#) object

Required: No

### **tags**

A list of tags assigned to your idle resource recommendations.

Type: Array of [Tag](#) objects

Required: No

## utilizationMetrics

An array of objects that describe the utilization metrics of the idle resource.

Type: Array of [IdleUtilizationMetric](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# IdleRecommendationError

Returns of list of resources that doesn't have idle recommendations.

## Contents

### code

The error code.

Type: String

Required: No

### identifier

The ID of the error.

Type: String

Required: No

### message

The error message.

Type: String

Required: No

### resourceType

The type of resource associated with the error.

Type: String

Valid Values: EC2Instance | AutoScalingGroup | EBSVolume | ECSService | RDSDBInstance

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# IdleRecommendationFilter

Describes a filter that returns a more specific list of idle resource recommendations.

## Contents

### **name**

The name of the filter.

Specify `Finding` to return recommendations with a specific finding classification.

You can filter your idle resource recommendations by `tag:key` and `tag-key` tags.

A `tag:key` is a key and value combination of a tag assigned to your idle resource recommendations. Use the tag key in the filter name and the tag value as the filter value. For example, to find all idle resource service recommendations that have a tag with the key of `Owner` and the value of `TeamA`, specify `tag:Owner` for the filter name and `TeamA` for the filter value.

A `tag-key` is the key of a tag assigned to your idle resource recommendations. Use this filter to find all of your idle resource recommendations that have a tag with a specific key. This doesn't consider the tag value. For example, you can find your idle resource service recommendations with a tag key value of `Owner` or without any tag keys assigned.

Type: String

Valid Values: `Finding` | `ResourceType`

Required: No

### **values**

The value of the filter.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# IdleSavingsOpportunity

Describes the savings opportunity for idle resource recommendations.

## Contents

### **estimatedMonthlySavings**

The estimated monthly savings possible by adopting Compute Optimizer's idle resource recommendations.

Type: [IdleEstimatedMonthlySavings](#) object

Required: No

### **savingsOpportunityPercentage**

The estimated monthly savings possible as a percentage of monthly cost by adopting Compute Optimizer's idle resource recommendations.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# IdleSavingsOpportunityAfterDiscounts

Describes the savings opportunity for idle resource recommendations after applying discounts.

Savings opportunity represents the estimated monthly savings after applying discounts. You can achieve this by implementing a given Compute Optimizer recommendation.

## Contents

### **estimatedMonthlySavings**

The estimated monthly savings possible by adopting Compute Optimizer's idle resource recommendations. This includes any applicable discounts.

Type: [IdleEstimatedMonthlySavings](#) object

Required: No

### **savingsOpportunityPercentage**

The estimated monthly savings possible as a percentage of monthly cost by adopting Compute Optimizer's idle resource recommendations. This includes any applicable discounts.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# IdleSummary

Describes the findings summary of the idle resources.

## Contents

### **name**

The name of the finding group for the idle resources.

Type: String

Valid Values: Idle | Unattached

Required: No

### **value**

The count of idle resources in the finding group.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# IdleUtilizationMetric

Describes the utilization metric of an idle resource.

## Contents

### **name**

The name of the utilization metric.

Type: String

Valid Values: CPU | Memory | NetworkOutBytesPerSecond | NetworkInBytesPerSecond | DatabaseConnections | EBSVolumeReadIOPS | EBSVolumeWriteIOPS | VolumeReadOpsPerSecond | VolumeWriteOpsPerSecond

Required: No

### **statistic**

The statistic of the utilization metric.

The Compute Optimizer API, Amazon Command Line Interface (Amazon CLI), and SDKs return utilization metrics using only the Maximum statistic, which is the highest value observed during the specified period.

The Compute Optimizer console displays graphs for some utilization metrics using the Average statistic, which is the value of Sum / SampleCount during the specified period. For more information, see [Viewing resource recommendations](#) in the *Amazon Compute Optimizer User Guide*. You can also get averaged utilization metric data for your resources using Amazon CloudWatch. For more information, see the [Amazon CloudWatch User Guide](#).

Type: String

Valid Values: Maximum | Average

Required: No

### **value**

The value of the utilization metric.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# InferredWorkloadSaving

The estimated monthly savings after you adjust the configurations of your instances running on the inferred workload types to the recommended configurations. If the `inferredWorkloadTypes` list contains multiple entries, then the savings are the sum of the monthly savings from instances that run the exact combination of the inferred workload types.

## Contents

### **estimatedMonthlySavings**

An object that describes the estimated monthly savings amount possible by adopting Compute Optimizer recommendations for a given resource. This is based on the On-Demand instance pricing.

Type: [EstimatedMonthlySavings](#) object

Required: No

### **inferredWorkloadTypes**

The applications that might be running on the instance as inferred by Compute Optimizer.

Compute Optimizer can infer if one of the following applications might be running on the instance:

- `AmazonEmr` - Infers that Amazon EMR might be running on the instance.
- `ApacheCassandra` - Infers that Apache Cassandra might be running on the instance.
- `ApacheHadoop` - Infers that Apache Hadoop might be running on the instance.
- `Memcached` - Infers that Memcached might be running on the instance.
- `NGINX` - Infers that NGINX might be running on the instance.
- `PostgreSql` - Infers that PostgreSQL might be running on the instance.
- `Redis` - Infers that Redis might be running on the instance.
- `Kafka` - Infers that Kafka might be running on the instance.
- `SQLServer` - Infers that SQLServer might be running on the instance.

Type: Array of strings

Valid Values: `AmazonEmr` | `ApacheCassandra` | `ApacheHadoop` | `Memcached` | `Nginx` | `PostgreSql` | `Redis` | `Kafka` | `SQLServer`

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# InstanceEstimatedMonthlySavings

An object that describes the estimated monthly savings possible by adopting Compute Optimizer's Amazon EC2 instance recommendations. This is based on the Savings Plans and Reserved Instances pricing discounts.

## Contents

### **currency**

The currency of the estimated monthly savings.

Type: String

Valid Values: USD | CNY

Required: No

### **value**

The value of the estimated monthly savings.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# InstanceRecommendation

Describes an Amazon EC2 instance recommendation.

## Contents

### accountId

The Amazon account ID of the instance.

Type: String

Required: No

### currentInstanceGpuInfo

Describes the GPU accelerator settings for the current instance type.

Type: [GpuInfo](#) object

Required: No

### currentInstanceType

The instance type of the current instance.

Type: String

Required: No

### currentPerformanceRisk

The risk of the current instance not meeting the performance needs of its workloads. The higher the risk, the more likely the current instance cannot meet the performance requirements of its workload.

Type: String

Valid Values: VeryLow | Low | Medium | High

Required: No

### effectiveRecommendationPreferences

An object that describes the effective recommendation preferences for the instance.

Type: [EffectiveRecommendationPreferences](#) object

Required: No

### externalMetricStatus

An object that describes Compute Optimizer's integration status with your external metrics provider.

Type: [ExternalMetricStatus](#) object

Required: No

### finding

The finding classification of the instance.

Findings for instances include:

- **Underprovisioned** —An instance is considered under-provisioned when at least one specification of your instance, such as CPU, memory, or network, does not meet the performance requirements of your workload. Under-provisioned instances may lead to poor application performance.
- **Overprovisioned** —An instance is considered over-provisioned when at least one specification of your instance, such as CPU, memory, or network, can be sized down while still meeting the performance requirements of your workload, and no specification is under-provisioned. Over-provisioned instances may lead to unnecessary infrastructure cost.
- **Optimized** —An instance is considered optimized when all specifications of your instance, such as CPU, memory, and network, meet the performance requirements of your workload and is not over provisioned. For optimized resources, Amazon Compute Optimizer might recommend a new generation instance type.

#### Note

The valid values in your API responses appear as OVER\_PROVISIONED, UNDER\_PROVISIONED, or OPTIMIZED.

Type: String

Valid Values: Underprovisioned | Overprovisioned | Optimized | NotOptimized

Required: No

## findingReasonCodes

The reason for the finding classification of the instance.

Finding reason codes for instances include:

- **CPUOverprovisioned** — The instance's CPU configuration can be sized down while still meeting the performance requirements of your workload. This is identified by analyzing the CPUUtilization metric of the current instance during the look-back period.
- **CPUUnderprovisioned** — The instance's CPU configuration doesn't meet the performance requirements of your workload and there is an alternative instance type that provides better CPU performance. This is identified by analyzing the CPUUtilization metric of the current instance during the look-back period.
- **MemoryOverprovisioned** — The instance's memory configuration can be sized down while still meeting the performance requirements of your workload. This is identified by analyzing the memory utilization metric of the current instance during the look-back period.
- **MemoryUnderprovisioned** — The instance's memory configuration doesn't meet the performance requirements of your workload and there is an alternative instance type that provides better memory performance. This is identified by analyzing the memory utilization metric of the current instance during the look-back period.

 **Note**

Memory utilization is analyzed only for resources that have the unified CloudWatch agent installed on them. For more information, see [Enabling memory utilization with the Amazon CloudWatch Agent](#) in the *Amazon Compute Optimizer User Guide*. On Linux instances, Compute Optimizer analyses the mem\_used\_percent metric in the CWAgent namespace, or the legacy MemoryUtilization metric in the System/Linux namespace. On Windows instances, Compute Optimizer analyses the Memory % Committed Bytes In Use metric in the CWAgent namespace.

- **EBSThroughputOverprovisioned** — The instance's EBS throughput configuration can be sized down while still meeting the performance requirements of your workload. This is identified by analyzing the VolumeReadBytes and VolumeWriteBytes metrics of EBS volumes attached to the current instance during the look-back period.
- **EBSThroughputUnderprovisioned** — The instance's EBS throughput configuration doesn't meet the performance requirements of your workload and there is an alternative

instance type that provides better EBS throughput performance. This is identified by analyzing the `VolumeReadBytes` and `VolumeWriteBytes` metrics of EBS volumes attached to the current instance during the look-back period.

- **EBSIOPSOverprovisioned** — The instance's EBS IOPS configuration can be sized down while still meeting the performance requirements of your workload. This is identified by analyzing the `VolumeReadOps` and `VolumeWriteOps` metric of EBS volumes attached to the current instance during the look-back period.
- **EBSIOPSUnderprovisioned** — The instance's EBS IOPS configuration doesn't meet the performance requirements of your workload and there is an alternative instance type that provides better EBS IOPS performance. This is identified by analyzing the `VolumeReadOps` and `VolumeWriteOps` metric of EBS volumes attached to the current instance during the look-back period.
- **NetworkBandwidthOverprovisioned** — The instance's network bandwidth configuration can be sized down while still meeting the performance requirements of your workload. This is identified by analyzing the `NetworkIn` and `NetworkOut` metrics of the current instance during the look-back period.
- **NetworkBandwidthUnderprovisioned** — The instance's network bandwidth configuration doesn't meet the performance requirements of your workload and there is an alternative instance type that provides better network bandwidth performance. This is identified by analyzing the `NetworkIn` and `NetworkOut` metrics of the current instance during the look-back period. This finding reason happens when the `NetworkIn` or `NetworkOut` performance of an instance is impacted.
- **NetworkPPSOverprovisioned** — The instance's network PPS (packets per second) configuration can be sized down while still meeting the performance requirements of your workload. This is identified by analyzing the `NetworkPacketsIn` and `NetworkPacketsIn` metrics of the current instance during the look-back period.
- **NetworkPPSUnderprovisioned** — The instance's network PPS (packets per second) configuration doesn't meet the performance requirements of your workload and there is an alternative instance type that provides better network PPS performance. This is identified by analyzing the `NetworkPacketsIn` and `NetworkPacketsIn` metrics of the current instance during the look-back period.
- **DiskIOPSOverprovisioned** — The instance's disk IOPS configuration can be sized down while still meeting the performance requirements of your workload. This is identified by analyzing the `DiskReadOps` and `DiskWriteOps` metrics of the current instance during the look-back period.

- **DiskIOPSUnderprovisioned** — The instance's disk IOPS configuration doesn't meet the performance requirements of your workload and there is an alternative instance type that provides better disk IOPS performance. This is identified by analyzing the DiskRead0ps and DiskWrite0ps metrics of the current instance during the look-back period.
- **DiskThroughputOverprovisioned** — The instance's disk throughput configuration can be sized down while still meeting the performance requirements of your workload. This is identified by analyzing the DiskReadBytes and DiskWriteBytes metrics of the current instance during the look-back period.
- **DiskThroughputUnderprovisioned** — The instance's disk throughput configuration doesn't meet the performance requirements of your workload and there is an alternative instance type that provides better disk throughput performance. This is identified by analyzing the DiskReadBytes and DiskWriteBytes metrics of the current instance during the look-back period.

 **Note**

For more information about instance metrics, see [List the available CloudWatch metrics for your instances](#) in the *Amazon Elastic Compute Cloud User Guide*. For more information about EBS volume metrics, see [Amazon CloudWatch metrics for Amazon EBS](#) in the *Amazon Elastic Compute Cloud User Guide*.

Type: Array of strings

Valid Values: CPUOverprovisioned | CPUUnderprovisioned  
| MemoryOverprovisioned | MemoryUnderprovisioned |  
EBSThroughputOverprovisioned | EBSThroughputUnderprovisioned  
| EBSIOPSOverprovisioned | EBSIOPSSUnderprovisioned |  
NetworkBandwidthOverprovisioned | NetworkBandwidthUnderprovisioned  
| NetworkPPSOverprovisioned | NetworkPPSSUnderprovisioned  
| DiskIOPSOverprovisioned | DiskIOPSSUnderprovisioned |  
DiskThroughputOverprovisioned | DiskThroughputUnderprovisioned |  
GPUUnderprovisioned | GPUOverprovisioned | GPUMemoryUnderprovisioned |  
GPUMemoryOverprovisioned

Required: No

**idle**

Describes if an Amazon EC2 instance is idle.

Type: String

Valid Values: True | False

Required: No

**inferredWorkloadTypes**

The applications that might be running on the instance as inferred by Compute Optimizer.

Compute Optimizer can infer if one of the following applications might be running on the instance:

- AmazonEmr - Infers that Amazon EMR might be running on the instance.
- ApacheCassandra - Infers that Apache Cassandra might be running on the instance.
- ApacheHadoop - Infers that Apache Hadoop might be running on the instance.
- Memcached - Infers that Memcached might be running on the instance.
- NGINX - Infers that NGINX might be running on the instance.
- PostgreSql - Infers that PostgreSQL might be running on the instance.
- Redis - Infers that Redis might be running on the instance.
- Kafka - Infers that Kafka might be running on the instance.
- SQLServer - Infers that SQLServer might be running on the instance.

Type: Array of strings

Valid Values: AmazonEmr | ApacheCassandra | ApacheHadoop | Memcached | Nginx | PostgreSql | Redis | Kafka | SQLServer

Required: No

**instanceArn**

The Amazon Resource Name (ARN) of the current instance.

Type: String

Required: No

**instanceName**

The name of the current instance.

Type: String

Required: No

**instanceState**

The state of the instance when the recommendation was generated.

Type: String

Valid Values: pending | running | shutting-down | terminated | stopping | stopped

Required: No

**lastRefreshTimestamp**

The timestamp of when the instance recommendation was last generated.

Type: Timestamp

Required: No

**lookBackPeriodInDays**

The number of days for which utilization metrics were analyzed for the instance.

Type: Double

Required: No

**recommendationOptions**

An array of objects that describe the recommendation options for the instance.

Type: Array of [InstanceRecommendationOption](#) objects

Required: No

**recommendationSources**

An array of objects that describe the source resource of the recommendation.

Type: Array of [RecommendationSource](#) objects

Required: No

## tags

A list of tags assigned to your Amazon EC2 instance recommendations.

Type: Array of [Tag](#) objects

Required: No

## utilizationMetrics

An array of objects that describe the utilization metrics of the instance.

Type: Array of [UtilizationMetric](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# InstanceRecommendationOption

Describes a recommendation option for an Amazon EC2 instance.

## Contents

### instanceGpuInfo

Describes the GPU accelerator settings for the recommended instance type.

Type: [GpuInfo](#) object

Required: No

### instanceType

The instance type of the instance recommendation.

Type: String

Required: No

### migrationEffort

The level of effort required to migrate from the current instance type to the recommended instance type.

For example, the migration effort is Low if Amazon EMR is the inferred workload type and an Amazon Graviton instance type is recommended. The migration effort is Medium if a workload type couldn't be inferred but an Amazon Graviton instance type is recommended. The migration effort is VeryLow if both the current and recommended instance types are of the same CPU architecture.

Type: String

Valid Values: VeryLow | Low | Medium | High

Required: No

### performanceRisk

The performance risk of the instance recommendation option.

Performance risk indicates the likelihood of the recommended instance type not meeting the resource needs of your workload. Compute Optimizer calculates an individual performance risk score for each specification of the recommended instance, including CPU, memory, EBS throughput, EBS IOPS, disk throughput, disk IOPS, network throughput, and network PPS. The performance risk of the recommended instance is calculated as the maximum performance risk score across the analyzed resource specifications.

The value ranges from 0 - 4, with 0 meaning that the recommended resource is predicted to always provide enough hardware capability. The higher the performance risk is, the more likely you should validate whether the recommendation will meet the performance requirements of your workload before migrating your resource.

Type: Double

Valid Range: Minimum value of 0. Maximum value of 4.

Required: No

## platformDifferences

Describes the configuration differences between the current instance and the recommended instance type. You should consider the configuration differences before migrating your workloads from the current instance to the recommended instance type. The [Change the instance type guide for Linux](#) and [Change the instance type guide for Windows](#) provide general guidance for getting started with an instance migration.

Platform differences include:

- **Hypervisor** — The hypervisor of the recommended instance type is different than that of the current instance. For example, the recommended instance type uses a Nitro hypervisor and the current instance uses a Xen hypervisor. The differences that you should consider between these hypervisors are covered in the [Nitro Hypervisor](#) section of the Amazon EC2 frequently asked questions. For more information, see [Instances built on the Nitro System](#) in the *Amazon EC2 User Guide for Linux*, or [Instances built on the Nitro System](#) in the *Amazon EC2 User Guide for Windows*.
- **NetworkInterface** — The network interface of the recommended instance type is different than that of the current instance. For example, the recommended instance type supports enhanced networking and the current instance might not. To enable enhanced networking for the recommended instance type, you must install the Elastic Network Adapter (ENA) driver or the Intel 82599 Virtual Function driver. For more information, see [Networking](#)

[and storage features](#) and [Enhanced networking on Linux](#) in the *Amazon EC2 User Guide for Linux*, or [Networking and storage features](#) and [Enhanced networking on Windows](#) in the *Amazon EC2 User Guide for Windows*.

- **StorageInterface** — The storage interface of the recommended instance type is different than that of the current instance. For example, the recommended instance type uses an NVMe storage interface and the current instance does not. To access NVMe volumes for the recommended instance type, you will need to install or upgrade the NVMe driver. For more information, see [Networking and storage features](#) and [Amazon EBS and NVMe on Linux instances](#) in the *Amazon EC2 User Guide for Linux*, or [Networking and storage features](#) and [Amazon EBS and NVMe on Windows instances](#) in the *Amazon EC2 User Guide for Windows*.
- **InstanceStoreAvailability** — The recommended instance type does not support instance store volumes and the current instance does. Before migrating, you might need to back up the data on your instance store volumes if you want to preserve them. For more information, see [How do I back up an instance store volume on my Amazon EC2 instance to Amazon EBS?](#) in the *Amazon Premium Support Knowledge Base*. For more information, see [Networking and storage features](#) and [Amazon EC2 instance store](#) in the *Amazon EC2 User Guide for Linux*, or see [Networking and storage features](#) and [Amazon EC2 instance store](#) in the *Amazon EC2 User Guide for Windows*.
- **VirtualizationType** — The recommended instance type uses the hardware virtual machine (HVM) virtualization type and the current instance uses the paravirtual (PV) virtualization type. For more information about the differences between these virtualization types, see [Linux AMI virtualization types](#) in the *Amazon EC2 User Guide for Linux*, or [Windows AMI virtualization types](#) in the *Amazon EC2 User Guide for Windows*.
- **Architecture** — The CPU architecture between the recommended instance type and the current instance is different. For example, the recommended instance type might use an Arm CPU architecture and the current instance type might use a different one, such as x86. Before migrating, you should consider recompiling the software on your instance for the new architecture. Alternatively, you might switch to an Amazon Machine Image (AMI) that supports the new architecture. For more information about the CPU architecture for each instance type, see [Amazon EC2 Instance Types](#).

Type: Array of strings

Valid Values: Hypervisor | NetworkInterface | StorageInterface | InstanceStoreAvailability | VirtualizationType | Architecture

Required: No

## projectedUtilizationMetrics

An array of objects that describe the projected utilization metrics of the instance recommendation option.

### Note

The Cpu and Memory metrics are the only projected utilization metrics returned. Additionally, the Memory metric is returned only for resources that have the unified CloudWatch agent installed on them. For more information, see [Enabling Memory Utilization with the CloudWatch Agent](#).

Type: Array of [UtilizationMetric](#) objects

Required: No

## rank

The rank of the instance recommendation option.

The top recommendation option is ranked as 1.

Type: Integer

Required: No

## savingsOpportunity

An object that describes the savings opportunity for the instance recommendation option. Savings opportunity includes the estimated monthly savings amount and percentage.

Type: [SavingsOpportunity](#) object

Required: No

## savingsOpportunityAfterDiscounts

An object that describes the savings opportunity for the instance recommendation option that includes Savings Plans and Reserved Instances discounts. Savings opportunity includes the estimated monthly savings and percentage.

Type: [InstanceSavingsOpportunityAfterDiscounts](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# InstanceSavingsEstimationMode

Describes the savings estimation mode used for calculating savings opportunity for Amazon EC2 instances.

## Contents

### source

Describes the source for calculating the savings opportunity for Amazon EC2 instances.

Type: String

Valid Values: PublicPricing | CostExplorerRightsizing | CostOptimizationHub

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# InstanceSavingsOpportunityAfterDiscounts

Describes the savings opportunity for instance recommendations after applying the Savings Plans and Reserved Instances discounts.

Savings opportunity after discounts represents the estimated monthly savings you can achieve by implementing Compute Optimizer recommendations.

## Contents

### **estimatedMonthlySavings**

An object that describes the estimated monthly savings possible by adopting Compute Optimizer's Amazon EC2 instance recommendations. This is based on pricing after applying the Savings Plans and Reserved Instances discounts.

Type: [InstanceEstimatedMonthlySavings](#) object

Required: No

### **savingsOpportunityPercentage**

The estimated monthly savings possible as a percentage of monthly cost after applying the Savings Plans and Reserved Instances discounts. This saving can be achieved by adopting Compute Optimizer's EC2 instance recommendations.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# JobFilter

Describes a filter that returns a more specific list of recommendation export jobs. Use this filter with the [DescribeRecommendationExportJobs](#) action.

You can use EBSFilter with the [GetEBSVolumeRecommendations](#) action, LambdaFunctionRecommendationFilter with the [GetLambdaFunctionRecommendations](#) action, and Filter with the [GetAutoScalingGroupRecommendations](#) and [GetEC2InstanceStateRecommendations](#) actions.

## Contents

### **name**

The name of the filter.

Specify ResourceType to return export jobs of a specific resource type (for example, Ec2Instance).

Specify JobStatus to return export jobs with a specific status (e.g, Complete).

Type: String

Valid Values: ResourceType | JobStatus

Required: No

### **values**

The value of the filter.

The valid values for this parameter are as follows, depending on what you specify for the name parameter:

- Specify Ec2Instance or AutoScalingGroup if you specify the name parameter as ResourceType. There is no filter for EBS volumes because volume recommendations cannot be exported at this time.
- Specify Queued, InProgress, Complete, or Failed if you specify the name parameter as JobStatus.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# LambdaEffectiveRecommendationPreferences

Describes the effective recommendation preferences for Lambda functions.

## Contents

### savingsEstimationMode

Describes the savings estimation mode applied for calculating savings opportunity for Lambda functions.

Type: [LambdaSavingsEstimationMode](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# LambdaEstimatedMonthlySavings

Describes the estimated monthly savings possible for Lambda functions by adopting Compute Optimizer recommendations. This is based on Lambda functions pricing after applying Savings Plans discounts.

## Contents

### **currency**

The currency of the estimated monthly savings.

Type: String

Valid Values: USD | CNY

Required: No

### **value**

The value of the estimated monthly savings.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# LambdaFunctionMemoryProjectedMetric

Describes a projected utilization metric of an Amazon Lambda function recommendation option.

## Contents

### **name**

The name of the projected utilization metric.

Type: String

Valid Values: Duration

Required: No

### **statistic**

The statistic of the projected utilization metric.

Type: String

Valid Values: LowerBound | UpperBound | Expected

Required: No

### **value**

The values of the projected utilization metrics.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)



# LambdaFunctionMemoryRecommendationOption

Describes a recommendation option for an Amazon Lambda function.

## Contents

### **memorySize**

The memory size, in MB, of the function recommendation option.

Type: Integer

Required: No

### **projectedUtilizationMetrics**

An array of objects that describe the projected utilization metrics of the function recommendation option.

Type: Array of [LambdaFunctionMemoryProjectedMetric](#) objects

Required: No

### **rank**

The rank of the function recommendation option.

The top recommendation option is ranked as 1.

Type: Integer

Required: No

### **savingsOpportunity**

An object that describes the savings opportunity for the Lambda function recommendation option. Savings opportunity includes the estimated monthly savings amount and percentage.

Type: [SavingsOpportunity](#) object

Required: No

### **savingsOpportunityAfterDiscounts**

An object that describes the savings opportunity for the Lambda recommendation option which includes Saving Plans discounts. Savings opportunity includes the estimated monthly savings and percentage.

Type: [LambdaSavingsOpportunityAfterDiscounts](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# LambdaFunctionRecommendation

Describes an Amazon Lambda function recommendation.

## Contents

### accountId

The Amazon account ID of the function.

Type: String

Required: No

### currentMemorySize

The amount of memory, in MB, that's allocated to the current function.

Type: Integer

Required: No

### currentPerformanceRisk

The risk of the current Lambda function not meeting the performance needs of its workloads.

The higher the risk, the more likely the current Lambda function requires more memory.

Type: String

Valid Values: VeryLow | Low | Medium | High

Required: No

### effectiveRecommendationPreferences

Describes the effective recommendation preferences for Lambda functions.

Type: [LambdaEffectiveRecommendationPreferences](#) object

Required: No

### finding

The finding classification of the function.

Findings for functions include:

- **Optimized** — The function is correctly provisioned to run your workload based on its current configuration and its utilization history. This finding classification does not include finding reason codes.
- **NotOptimized** — The function is performing at a higher level (over-provisioned) or at a lower level (under-provisioned) than required for your workload because its current configuration is not optimal. Over-provisioned resources might lead to unnecessary infrastructure cost, and under-provisioned resources might lead to poor application performance. This finding classification can include the MemoryUnderprovisioned and MemoryOverprovisioned finding reason codes.
- **Unavailable** — Compute Optimizer was unable to generate a recommendation for the function. This could be because the function has not accumulated sufficient metric data, or the function does not qualify for a recommendation. This finding classification can include the InsufficientData and Inconclusive finding reason codes.

 **Note**

Functions with a finding of unavailable are not returned unless you specify the filter parameter with a value of Unavailable in your GetLambdaFunctionRecommendations request.

Type: String

Valid Values: Optimized | NotOptimized | Unavailable

Required: No

### **findingReasonCodes**

The reason for the finding classification of the function.

 **Note**

Functions that have a finding classification of Optimized don't have a finding reason code.

Finding reason codes for functions include:

- **MemoryOverprovisioned** — The function is over-provisioned when its memory configuration can be sized down while still meeting the performance requirements of your workload. An over-provisioned function might lead to unnecessary infrastructure cost. This finding reason code is part of the NotOptimized finding classification.
- **MemoryUnderprovisioned** — The function is under-provisioned when its memory configuration doesn't meet the performance requirements of the workload. An under-provisioned function might lead to poor application performance. This finding reason code is part of the NotOptimized finding classification.
- **InsufficientData** — The function does not have sufficient metric data for Compute Optimizer to generate a recommendation. For more information, see the [Supported resources and requirements](#) in the *Amazon Compute Optimizer User Guide*. This finding reason code is part of the Unavailable finding classification.
- **Inconclusive** — The function does not qualify for a recommendation because Compute Optimizer cannot generate a recommendation with a high degree of confidence. This finding reason code is part of the Unavailable finding classification.

Type: Array of strings

Valid Values: MemoryOverprovisioned | MemoryUnderprovisioned | InsufficientData | Inconclusive

Required: No

#### functionArn

The Amazon Resource Name (ARN) of the current function.

Type: String

Required: No

#### functionVersion

The version number of the current function.

Type: String

Required: No

#### lastRefreshTimestamp

The timestamp of when the function recommendation was last generated.

Type: Timestamp

Required: No

### **lookbackPeriodInDays**

The number of days for which utilization metrics were analyzed for the function.

Type: Double

Required: No

### **memorySizeRecommendationOptions**

An array of objects that describe the memory configuration recommendation options for the function.

Type: Array of [LambdaFunctionMemoryRecommendationOption](#) objects

Required: No

### **numberOfInvocations**

The number of times your function code was applied during the look-back period.

Type: Long

Required: No

### **tags**

A list of tags assigned to your Lambda function recommendations.

Type: Array of [Tag](#) objects

Required: No

### **utilizationMetrics**

An array of objects that describe the utilization metrics of the function.

Type: Array of [LambdaFunctionUtilizationMetric](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# LambdaFunctionRecommendationFilter

Describes a filter that returns a more specific list of Amazon Lambda function recommendations. Use this filter with the [GetLambdaFunctionRecommendations](#) action.

You can use EBSFilter with the [GetEBSVolumeRecommendations](#) action, JobFilter with the [DescribeRecommendationExportJobs](#) action, and Filter with the [GetAutoScalingGroupRecommendations](#) and [GetEC2InstanceStateRecommendations](#) actions.

## Contents

### **name**

The name of the filter.

Specify Finding to return recommendations with a specific finding classification (for example, NotOptimized).

Specify FindingReasonCode to return recommendations with a specific finding reason code (for example, MemoryUnderprovisioned).

You can filter your Lambda function recommendations by tag :key and tag -key tags.

A tag :key is a key and value combination of a tag assigned to your Lambda function recommendations. Use the tag key in the filter name and the tag value as the filter value. For example, to find all Lambda function recommendations that have a tag with the key of Owner and the value of TeamA, specify tag :Owner for the filter name and TeamA for the filter value.

A tag -key is the key of a tag assigned to your Lambda function recommendations. Use this filter to find all of your Lambda function recommendations that have a tag with a specific key. This doesn't consider the tag value. For example, you can find your Lambda function recommendations with a tag key value of Owner or without any tag keys assigned.

Type: String

Valid Values: Finding | FindingReasonCode

Required: No

### **values**

The value of the filter.

The valid values for this parameter are as follows, depending on what you specify for the name parameter:

- Specify Optimized, NotOptimized, or Unavailable if you specify the name parameter as Finding.
- Specify MemoryOverprovisioned, MemoryUnderprovisioned, InsufficientData, or Inconclusive if you specify the name parameter as FindingReasonCode.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# LambdaFunctionUtilizationMetric

Describes a utilization metric of an Amazon Lambda function.

## Contents

### **name**

The name of the utilization metric.

The following utilization metrics are available:

- Duration - The amount of time that your function code spends processing an event.
- Memory - The amount of memory used per invocation.

Type: String

Valid Values: Duration | Memory

Required: No

### **statistic**

The statistic of the utilization metric.

The Compute Optimizer API, Amazon Command Line Interface (Amazon CLI), and SDKs return utilization metrics using only the Maximum statistic, which is the highest value observed during the specified period.

The Compute Optimizer console displays graphs for some utilization metrics using the Average statistic, which is the value of Sum / SampleCount during the specified period. For more information, see [Viewing resource recommendations](#) in the *Amazon Compute Optimizer User Guide*. You can also get averaged utilization metric data for your resources using Amazon CloudWatch. For more information, see the [Amazon CloudWatch User Guide](#).

Type: String

Valid Values: Maximum | Average

Required: No

### **value**

The value of the utilization metric.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# LambdaSavingsEstimationMode

Describes the savings estimation used for calculating savings opportunity for Lambda functions.

## Contents

### source

Describes the source for calculation of savings opportunity for Lambda functions.

Type: String

Valid Values: PublicPricing | CostExplorerRightsizing | CostOptimizationHub

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# LambdaSavingsOpportunityAfterDiscounts

Describes the savings opportunity for Lambda functions recommendations after applying Savings Plans discounts.

Savings opportunity represents the estimated monthly savings after applying Savings Plans discounts. You can achieve this by implementing a given Compute Optimizer recommendation.

## Contents

### **estimatedMonthlySavings**

The estimated monthly savings possible by adopting Compute Optimizer's Lambda function recommendations. This includes any applicable Savings Plans discounts.

Type: [LambdaEstimatedMonthlySavings](#) object

Required: No

### **savingsOpportunityPercentage**

The estimated monthly savings possible as a percentage of monthly cost by adopting Compute Optimizer's Lambda function recommendations. This includes any applicable Savings Plans discounts.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# LicenseConfiguration

Describes the configuration of a license for an Amazon EC2 instance.

## Contents

### instanceType

The instance type used in the license.

Type: String

Required: No

### licenseEdition

The edition of the license for the application that runs on the instance.

Type: String

Valid Values: Enterprise | Standard | Free | NoLicenseEditionFound

Required: No

### licenseModel

The license type associated with the instance.

Type: String

Valid Values: LicenseIncluded | BringYourOwnLicense

Required: No

### licenseName

The name of the license for the application that runs on the instance.

Type: String

Valid Values: SQLServer

Required: No

## licenseVersion

The version of the license for the application that runs on the instance.

Type: String

Required: No

## metricsSource

The list of metric sources required to generate recommendations for commercial software licenses.

Type: Array of [MetricSource](#) objects

Required: No

## numberOfCores

The current number of cores associated with the instance.

Type: Integer

Required: No

## operatingSystem

The operating system of the instance.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# LicenseRecommendation

Describes a license recommendation for an EC2 instance.

## Contents

### accountId

The Amazon account ID of the license.

Type: String

Required: No

### currentLicenseConfiguration

An object that describes the current configuration of an instance that runs on a license.

Type: [LicenseConfiguration](#) object

Required: No

### finding

The finding classification for an instance that runs on a license.

Findings include:

- **InsufficientMetrics** — When Compute Optimizer detects that your CloudWatch Application Insights isn't enabled or is enabled with insufficient permissions.
- **NotOptimized** — When Compute Optimizer detects that your EC2 infrastructure isn't using any of the SQL server license features you're paying for, a license is considered not optimized.
- **Optimized** — When Compute Optimizer detects that all specifications of your license meet the performance requirements of your workload.

Type: String

Valid Values: InsufficientMetrics | Optimized | NotOptimized

Required: No

### findingReasonCodes

The reason for the finding classification for an instance that runs on a license.

Finding reason codes include:

- Optimized — All specifications of your license meet the performance requirements of your workload.
- LicenseOverprovisioned — A license is considered over-provisioned when your license can be downgraded while still meeting the performance requirements of your workload.
- InvalidCloudwatchApplicationInsights — CloudWatch Application Insights isn't configured properly.
- CloudwatchApplicationInsightsError — There is a CloudWatch Application Insights error.

Type: Array of strings

Valid Values: InvalidCloudWatchApplicationInsightsSetup | CloudWatchApplicationInsightsError | LicenseOverprovisioned | Optimized

Required: No

#### **lastRefreshTimestamp**

The timestamp of when the license recommendation was last generated.

Type: Timestamp

Required: No

#### **licenseRecommendationOptions**

An array of objects that describe the license recommendation options.

Type: Array of [LicenseRecommendationOption](#) objects

Required: No

#### **lookbackPeriodInDays**

The number of days for which utilization metrics were analyzed for an instance that runs on a license.

Type: Double

Required: No

## resourceArn

The ARN that identifies the Amazon EC2 instance.

Type: String

Required: No

## tags

A list of tags assigned to an EC2 instance.

Type: Array of [Tag](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# LicenseRecommendationFilter

Describes a filter that returns a more specific list of license recommendations. Use this filter with the GetLicenseRecommendation action.

## Contents

### **name**

The name of the filter.

Specify `Finding` to return recommendations with a specific finding classification.

Specify `FindingReasonCode` to return recommendations with a specific finding reason code.

You can filter your license recommendations by tag : key and tag - key tags.

A tag : key is a key and value combination of a tag assigned to your license recommendations. Use the tag key in the filter name and the tag value as the filter value. For example, to find all license recommendations that have a tag with the key of `Owner` and the value of `TeamA`, specify `tag:Owner` for the filter name and `TeamA` for the filter value.

A tag - key is the key of a tag assigned to your license recommendations. Use this filter to find all of your license recommendations that have a tag with a specific key. This doesn't consider the tag value. For example, you can find your license recommendations with a tag key value of `Owner` or without any tag keys assigned.

Type: String

Valid Values: `Finding` | `FindingReasonCode` | `LicenseName`

Required: No

### **values**

The value of the filter.

The valid values for this parameter are as follows, depending on what you specify for the name parameter:

- If you specify the name parameter as `Finding`, then specify `Optimized`, `NotOptimized`, or `InsufficientMetrics`.

- If you specify the name parameter as `FindingReasonCode`, then specify `Optimized`, `LicenseOverprovisioned`, `InvalidCloudwatchApplicationInsights`, or `CloudwatchApplicationInsightsError`.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# LicenseRecommendationOption

Describes the recommendation options for licenses.

## Contents

### licenseEdition

The recommended edition of the license for the application that runs on the instance.

Type: String

Valid Values: Enterprise | Standard | Free | NoLicenseEditionFound

Required: No

### licenseModel

The recommended license type associated with the instance.

Type: String

Valid Values: LicenseIncluded | BringYourOwnLicense

Required: No

### operatingSystem

The operating system of a license recommendation option.

Type: String

Required: No

### rank

The rank of the license recommendation option.

The top recommendation option is ranked as 1.

Type: Integer

Required: No

## savingsOpportunity

Describes the savings opportunity for recommendations of a given resource type or for the recommendation option of an individual resource.

Savings opportunity represents the estimated monthly savings you can achieve by implementing a given Compute Optimizer recommendation.

### Important

Savings opportunity data requires that you opt in to Cost Explorer, as well as activate **Receive Amazon EC2 resource recommendations** in the Cost Explorer preferences page. That creates a connection between Cost Explorer and Compute Optimizer. With this connection, Cost Explorer generates savings estimates considering the price of existing resources, the price of recommended resources, and historical usage data. Estimated monthly savings reflects the projected dollar savings associated with each of the recommendations generated. For more information, see [Enabling Cost Explorer](#) and [Optimizing your cost with Rightsizing Recommendations](#) in the *Cost Management User Guide*.

Type: [SavingsOpportunity](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# MemorySizeConfiguration

The memory size configurations of a container.

## Contents

### **memory**

The amount of memory in the container.

Type: Integer

Required: No

### **memoryReservation**

The limit of memory reserve for the container.

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# MetricSource

The list of metric sources required to generate recommendations for commercial software licenses.

## Contents

### **provider**

The name of the metric source provider.

Type: String

Valid Values: CloudWatchApplicationInsights

Required: No

### **providerArn**

The ARN of the metric source provider.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# OrderBy

Describes how the recommendations are ordered.

## Contents

### dimension

The dimension values to sort the recommendations.

Type: String

Valid Values: SavingsValue | SavingsValueAfterDiscount

Required: No

### order

The order to sort the recommendations.

Type: String

Valid Values: Asc | Desc

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# PreferredResource

The preference to control which resource type values are considered when generating rightsizing recommendations. You can specify this preference as a combination of include and exclude lists. You must specify either an `includeList` or `excludeList`. If the preference is an empty set of resource type values, an error occurs. For more information, see [Rightsizing recommendation preferences](#) in the *Amazon Compute Optimizer User Guide*.

## Note

- This preference is only available for the Amazon EC2 instance and Auto Scaling group resource types.
- Compute Optimizer only supports the customization of `Ec2InstanceTypes`.

## Contents

### **excludeList**

The preferred resource type values to exclude from the recommendation candidates. If this isn't specified, all supported resources are included by default. You can specify up to 1000 values in this list.

Type: Array of strings

Required: No

### **includeList**

The preferred resource type values to include in the recommendation candidates. You can specify the exact resource type value, such as `m5.large`, or use wild card expressions, such as `m5`. If this isn't specified, all supported resources are included by default. You can specify up to 1000 values in this list.

Type: Array of strings

Required: No

### **name**

The type of preferred resource to customize.

**Note**

Compute Optimizer only supports the customization of Ec2InstanceTypes.

Type: String

Valid Values: Ec2InstanceTypes

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ProjectedMetric

Describes a projected utilization metric of a recommendation option, such as an Amazon EC2 instance. This represents the projected utilization of a recommendation option had you used that resource during the analyzed period.

Compare the utilization metric data of your resource against its projected utilization metric data to determine the performance difference between your current resource and the recommended option.

## Note

The Cpu, Memory, GPU, and GPU\_MEMORY metrics are the only projected utilization metrics returned when you run the [GetEC2RecommendationProjectedMetrics](#) action. Additionally, these metrics are only returned for resources with the unified CloudWatch agent installed on them. For more information, see [Enabling Memory Utilization with the CloudWatch Agent](#) and [Enabling NVIDIA GPU utilization with the CloudWatch Agent](#).

## Contents

### **name**

The name of the projected utilization metric.

The following projected utilization metrics are returned:

- Cpu - The projected percentage of allocated EC2 compute units that would be in use on the recommendation option had you used that resource during the analyzed period. This metric identifies the processing power required to run an application on the recommendation option.

Depending on the instance type, tools in your operating system can show a lower percentage than CloudWatch when the instance is not allocated a full processor core.

- Memory - The percentage of memory that would be in use on the recommendation option had you used that resource during the analyzed period. This metric identifies the amount of memory required to run an application on the recommendation option.

Units: Percent

**Note**

The Memory metric is only returned for resources with the unified CloudWatch agent installed on them. For more information, see [Enabling Memory Utilization with the CloudWatch Agent](#).

- GPU - The projected percentage of allocated GPUs if you adjust your configurations to Compute Optimizer's recommendation option.
- GPU\_MEMORY - The projected percentage of total GPU memory if you adjust your configurations to Compute Optimizer's recommendation option.

**Note**

The GPU and GPU\_MEMORY metrics are only returned for resources with the unified CloudWatch Agent installed on them. For more information, see [Enabling NVIDIA GPU utilization with the CloudWatch Agent](#).

Type: String

Valid Values: Cpu | Memory | EBS\_READ\_OPS\_PER\_SECOND | EBS\_WRITE\_OPS\_PER\_SECOND | EBS\_READ\_BYTES\_PER\_SECOND | EBS\_WRITE\_BYTES\_PER\_SECOND | DISK\_READ\_OPS\_PER\_SECOND | DISK\_WRITE\_OPS\_PER\_SECOND | DISK\_READ\_BYTES\_PER\_SECOND | DISK\_WRITE\_BYTES\_PER\_SECOND | NETWORK\_IN\_BYTES\_PER\_SECOND | NETWORK\_OUT\_BYTES\_PER\_SECOND | NETWORK\_PACKETS\_IN\_PER\_SECOND | NETWORK\_PACKETS\_OUT\_PER\_SECOND | GPU\_PERCENTAGE | GPU\_MEMORY\_PERCENTAGE

Required: No

**timestamps**

The timestamps of the projected utilization metric.

Type: Array of timestamps

Required: No

**values**

The values of the projected utilization metrics.

Type: Array of doubles

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RDSDatabaseProjectedMetric

Describes the projected metrics of an Amazon Aurora and RDS database recommendation option.

To determine the performance difference between your current Amazon Aurora and RDS database and the recommended option, compare the metric data of your service against its projected metric data.

## Contents

### **name**

The name of the projected metric.

Type: String

Valid Values: CPU | Memory | EBSVolumeStorageSpaceUtilization | NetworkReceiveThroughput | NetworkTransmitThroughput | EBSVolumeReadIOPS | EBSVolumeWriteIOPS | EBSVolumeReadThroughput | EBSVolumeWriteThroughput | DatabaseConnections | StorageNetworkReceiveThroughput | StorageNetworkTransmitThroughput | AuroraMemoryHealthState | AuroraMemoryNumDeclinedSql | AuroraMemoryNumKillConnTotal | AuroraMemoryNumKillQueryTotal | ReadIOPSEphemeralStorage | WriteIOPSEphemeralStorage | VolumeReadIOPs | VolumeBytesUsed | VolumeWriteIOPs

Required: No

### **timestamps**

The timestamps of the projected metric.

Type: Array of timestamps

Required: No

### **values**

The values for the projected metric.

Type: Array of doubles

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RDSDatabaseRecommendedOptionProjectedMetric

Describes the projected metrics of an Amazon Aurora and RDS database recommendation option.

To determine the performance difference between your current Amazon Aurora and RDS database and the recommended option, compare the metric data of your service against its projected metric data.

## Contents

### projectedMetrics

An array of objects that describe the projected metric.

Type: Array of [RDSDatabaseProjectedMetric](#) objects

Required: No

### rank

The rank identifier of the Amazon Aurora or RDS DB instance recommendation option.

Type: Integer

Required: No

### recommendedDBInstanceState

The recommended DB instance class for the Amazon Aurora or RDS database.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)



# RDSDBInstanceRecommendationOption

Describes the recommendation options for a DB instance.

## Contents

### dbInstanceClass

Describes the DB instance class recommendation option for your Amazon Aurora or RDS database.

Type: String

Required: No

### performanceRisk

The performance risk of the DB instance recommendation option.

Type: Double

Valid Range: Minimum value of 0. Maximum value of 4.

Required: No

### projectedUtilizationMetrics

An array of objects that describe the projected utilization metrics of the DB instance recommendation option.

Type: Array of [RDSDBUtilizationMetric](#) objects

Required: No

### rank

The rank identifier of the DB instance recommendation option.

Type: Integer

Required: No

### savingsOpportunity

Describes the savings opportunity for recommendations of a given resource type or for the recommendation option of an individual resource.

Savings opportunity represents the estimated monthly savings you can achieve by implementing a given Compute Optimizer recommendation.

**⚠ Important**

Savings opportunity data requires that you opt in to Cost Explorer, as well as activate **Receive Amazon EC2 resource recommendations** in the Cost Explorer preferences page. That creates a connection between Cost Explorer and Compute Optimizer. With this connection, Cost Explorer generates savings estimates considering the price of existing resources, the price of recommended resources, and historical usage data. Estimated monthly savings reflects the projected dollar savings associated with each of the recommendations generated. For more information, see [Enabling Cost Explorer](#) and [Optimizing your cost with Rightsizing Recommendations](#) in the *Cost Management User Guide*.

Type: [SavingsOpportunity](#) object

Required: No

#### **savingsOpportunityAfterDiscounts**

Describes the savings opportunity for Amazon Aurora and RDS database recommendations or for the recommendation option.

Savings opportunity represents the estimated monthly savings after applying Savings Plans discounts. You can achieve this by implementing a given Compute Optimizer recommendation.

Type: [RDSInstanceSavingsOpportunityAfterDiscounts](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

# RDSDBRecommendation

Describes an Amazon Aurora and RDS database recommendation.

## Contents

### accountId

The Amazon account ID of the Amazon Aurora or RDS database.

Type: String

Required: No

### currentDBInstanceClass

The DB instance class of the current Aurora or RDS DB instance.

Type: String

Required: No

### currentInstancePerformanceRisk

The performance risk for the current DB instance.

Type: String

Valid Values: VeryLow | Low | Medium | High

Required: No

### currentStorageConfiguration

The configuration of the current DB storage.

Type: [DBStorageConfiguration](#) object

Required: No

### currentStorageEstimatedMonthlyVolumeIOPsCostVariation

The level of variation in monthly I/O costs for the current DB storage configuration.

Type: String

Valid Values: None | Low | Medium | High

Required: No

### **dbClusterIdentifier**

The identifier for DB cluster.

Type: String

Required: No

### **effectiveRecommendationPreferences**

Describes the effective recommendation preferences for DB instances.

Type: [RDSEffectiveRecommendationPreferences](#) object

Required: No

### **engine**

The engine of the DB instance.

Type: String

Required: No

### **engineVersion**

The database engine version.

Type: String

Required: No

### **idle**

This indicates if the DB instance is idle or not.

Type: String

Valid Values: True | False

Required: No

### **instanceFinding**

The finding classification of an Amazon Aurora and RDS DB instance.

For more information about finding classifications, see [Finding classifications for Aurora and RDS databases](#) in the *Amazon Compute Optimizer User Guide*.

Type: String

Valid Values: Optimized | Underprovisioned | Overprovisioned

Required: No

### **instanceFindingReasonCodes**

The reason for the finding classification of a DB instance.

Type: Array of strings

Valid Values: CPUOverprovisioned | NetworkBandwidthOverprovisioned | EBSIOPSOverprovisioned | EBSIOPSUnderprovisioned | EBSThroughputOverprovisioned | CPUUnderprovisioned | NetworkBandwidthUnderprovisioned | EBSThroughputUnderprovisioned | NewGenerationDBInstanceClassAvailable | NewEngineVersionAvailable | DBClusterWriterUnderprovisioned | MemoryUnderprovisioned | InstanceStorageReadIOPSUnderprovisioned | InstanceStorageWriteIOPSUnderprovisioned

Required: No

### **instanceRecommendationOptions**

An array of objects that describe the recommendation options for the RDS DB instance.

Type: Array of [RDSDBInstanceRecommendationOption](#) objects

Required: No

### **lastRefreshTimestamp**

The timestamp of when the DB instance recommendation was last generated.

Type: Timestamp

Required: No

### **lookbackPeriodInDays**

The number of days the DB instance utilization metrics were analyzed.

Type: Double

Required: No

### **promotionTier**

The promotion tier for the Aurora instance.

Type: Integer

Required: No

### **resourceArn**

The ARN of the current Amazon Aurora or RDS database.

The following is the format of the ARN:

`arn:aws:rds:{region}:{accountId}:db:{resourceName}`

Type: String

Required: No

### **storageFinding**

The finding classification of Amazon RDS DB instance storage.

For more information about finding classifications, see [Finding classifications for Aurora and RDS databases](#) in the *Amazon Compute Optimizer User Guide*.

Type: String

Valid Values: Optimized | Underprovisioned | Overprovisioned | NotOptimized

Required: No

### **storageFindingReasonCodes**

The reason for the finding classification of RDS DB instance storage.

Type: Array of strings

Valid Values: EBSVolumeAllocatedStorageUnderprovisioned |  
EBSVolumeThroughputUnderprovisioned | EBSVolumeIOPSOverprovisioned |

EBSVolumeThroughputOverprovisioned | NewGenerationStorageTypeAvailable | DBClusterStorageOptionAvailable | DBClusterStorageSavingsAvailable

Required: No

### **storageRecommendationOptions**

An array of objects that describe the recommendation options for DB instance storage.

Type: Array of [RDSDBStorageRecommendationOption](#) objects

Required: No

### **tags**

A list of tags assigned to your DB instance recommendations.

Type: Array of [Tag](#) objects

Required: No

### **utilizationMetrics**

An array of objects that describe the utilization metrics of the DB instance.

Type: Array of [RDSDBUtilizationMetric](#) objects

Required: No

## **See Also**

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RDSDBRecommendationFilter

Describes a filter that returns a more specific list of DB instance recommendations. Use this filter with the [GetECSServiceRecommendations](#) action.

## Contents

### **name**

The name of the filter.

Specify `Finding` to return recommendations with a specific finding classification.

You can filter your DB instance recommendations by `tag:key` and `tag-key` tags.

A `tag:key` is a key and value combination of a tag assigned to your DB instance recommendations. Use the tag key in the filter name and the tag value as the filter value. For example, to find all DB instance recommendations that have a tag with the key of `Owner` and the value of `TeamA`, specify `tag:Owner` for the filter name and `TeamA` for the filter value.

A `tag-key` is the key of a tag assigned to your DB instance recommendations. Use this filter to find all of your DB instance recommendations that have a tag with a specific key. This doesn't consider the tag value. For example, you can find your DB instance recommendations with a tag key value of `Owner` or without any tag keys assigned.

Type: String

Valid Values: `InstanceFinding` | `InstanceFindingReasonCode` | `StorageFinding` | `StorageFindingReasonCode` | `Idle`

Required: No

### **values**

The value of the filter.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RDSDBStorageRecommendationOption

Describes the recommendation options for DB storage.

## Contents

### estimatedMonthlyVolumeIOPsCostVariation

The projected level of variation in monthly I/O costs for the DB storage recommendation option.

Type: String

Valid Values: None | Low | Medium | High

Required: No

### rank

The rank identifier of the DB storage recommendation option.

Type: Integer

Required: No

### savingsOpportunity

Describes the savings opportunity for recommendations of a given resource type or for the recommendation option of an individual resource.

Savings opportunity represents the estimated monthly savings you can achieve by implementing a given Compute Optimizer recommendation.

#### Important

Savings opportunity data requires that you opt in to Cost Explorer, as well as activate **Receive Amazon EC2 resource recommendations** in the Cost Explorer preferences page. That creates a connection between Cost Explorer and Compute Optimizer. With this connection, Cost Explorer generates savings estimates considering the price of existing resources, the price of recommended resources, and historical usage data. Estimated monthly savings reflects the projected dollar savings associated with each of the recommendations generated. For more information, see [Enabling Cost Explorer](#) and

[Optimizing your cost with Rightsizing Recommendations](#) in the *Cost Management User Guide*.

Type: [SavingsOpportunity](#) object

Required: No

### savingsOpportunityAfterDiscounts

Describes the savings opportunity for DB storage recommendations or for the recommendation option.

Savings opportunity represents the estimated monthly savings after applying Savings Plans discounts. You can achieve this by implementing a given Compute Optimizer recommendation.

Type: [RDSStorageSavingsOpportunityAfterDiscounts](#) object

Required: No

### storageConfiguration

The recommended storage configuration.

Type: [DBStorageConfiguration](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RDSDBUtilizationMetric

Describes the utilization metric of an Amazon Aurora and RDS database.

To determine the performance difference between your current DB instance and the recommended option, compare the utilization metric data of your service against its projected utilization metric data.

## Contents

### **name**

The name of the utilization metric.

Type: String

Valid Values: CPU | Memory | EBSVolumeStorageSpaceUtilization | NetworkReceiveThroughput | NetworkTransmitThroughput | EBSVolumeReadIOPS | EBSVolumeWriteIOPS | EBSVolumeReadThroughput | EBSVolumeWriteThroughput | DatabaseConnections | StorageNetworkReceiveThroughput | StorageNetworkTransmitThroughput | AuroraMemoryHealthState | AuroraMemoryNumDeclinedSql | AuroraMemoryNumKillConnTotal | AuroraMemoryNumKillQueryTotal | ReadIOPSEphemeralStorage | WriteIOPSEphemeralStorage | VolumeReadIOPs | VolumeBytesUsed | VolumeWriteIOPs

Required: No

### **statistic**

The statistic of the utilization metric.

The Compute Optimizer API, Amazon Command Line Interface (Amazon CLI), and SDKs return utilization metrics using only the Maximum statistic, which is the highest value observed during the specified period.

The Compute Optimizer console displays graphs for some utilization metrics using the Average statistic, which is the value of Sum / SampleCount during the specified period. For more information, see [Viewing resource recommendations](#) in the *Amazon Compute Optimizer User Guide*. You can also get averaged utilization metric data for your resources using Amazon CloudWatch. For more information, see the [Amazon CloudWatch User Guide](#).

Type: String

Valid Values: Maximum | Minimum | Average

Required: No

### value

The value of the utilization metric.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RDSEffectiveRecommendationPreferences

Describes the effective recommendation preferences for Amazon Aurora and RDS databases.

## Contents

### cpuVendorArchitectures

Describes the CPU vendor and architecture for DB instance recommendations.

Type: Array of strings

Valid Values: AWS\_ARM64 | CURRENT

Required: No

### enhancedInfrastructureMetrics

Describes the activation status of the enhanced infrastructure metrics preference.

A status of Active confirms that the preference is applied in the latest recommendation refresh, and a status of Inactive confirms that it's not yet applied to recommendations.

For more information, see [Enhanced infrastructure metrics](#) in the *Amazon Compute Optimizer User Guide*.

Type: String

Valid Values: Active | Inactive

Required: No

### lookBackPeriod

The number of days the utilization metrics of the DB instance are analyzed.

Type: String

Valid Values: DAYS\_14 | DAYS\_32 | DAYS\_93

Required: No

### savingsEstimationMode

Describes the savings estimation mode preference applied for calculating savings opportunity for DB instances.

Type: [RDSSavingsEstimationMode](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RDSInstanceEstimatedMonthlySavings

Describes the estimated monthly savings possible for DB instances by adopting Compute Optimizer recommendations. This is based on DB instance pricing after applying Savings Plans discounts.

## Contents

### **currency**

The currency of the estimated monthly savings.

Type: String

Valid Values: USD | CNY

Required: No

### **value**

The value of the estimated monthly savings for DB instances.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RDSInstanceSavingsOpportunityAfterDiscounts

Describes the savings opportunity for DB instance recommendations after applying Savings Plans discounts.

Savings opportunity represents the estimated monthly savings after applying Savings Plans discounts. You can achieve this by implementing a given Compute Optimizer recommendation.

## Contents

### **estimatedMonthlySavings**

The estimated monthly savings possible by adopting Compute Optimizer's DB instance recommendations. This includes any applicable Savings Plans discounts.

Type: [RDSInstanceEstimatedMonthlySavings](#) object

Required: No

### **savingsOpportunityPercentage**

The estimated monthly savings possible as a percentage of monthly cost by adopting Compute Optimizer's DB instance recommendations. This includes any applicable Savings Plans discounts.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RDSSavingsEstimationMode

Describes the savings estimation mode used for calculating savings opportunity for DB instances.

## Contents

### source

Describes the source for calculating the savings opportunity for DB instances.

Type: String

Valid Values: PublicPricing | CostExplorerRightsizing | CostOptimizationHub

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RDSStorageEstimatedMonthlySavings

Describes the estimated monthly savings possible for DB instance storage by adopting Compute Optimizer recommendations. This is based on DB instance pricing after applying Savings Plans discounts.

## Contents

### **currency**

The currency of the estimated monthly savings.

Type: String

Valid Values: USD | CNY

Required: No

### **value**

The value of the estimated monthly savings for DB instance storage.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RDSStorageSavingsOpportunityAfterDiscounts

Describes the savings opportunity for Amazon RDS storage recommendations after applying Savings Plans discounts.

Savings opportunity represents the estimated monthly savings after applying Savings Plans discounts. You can achieve this by implementing a given Compute Optimizer recommendation.

## Contents

### **estimatedMonthlySavings**

The estimated monthly savings possible by adopting Compute Optimizer's DB instance storage recommendations. This includes any applicable Savings Plans discounts.

Type: [RDSStorageEstimatedMonthlySavings](#) object

Required: No

### **savingsOpportunityPercentage**

The estimated monthly savings possible as a percentage of monthly cost by adopting Compute Optimizer's DB instance storage recommendations. This includes any applicable Savings Plans discounts.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ReasonCodeSummary

A summary of a finding reason code.

## Contents

### **name**

The name of the finding reason code.

Type: String

Valid Values: MemoryOverprovisioned | MemoryUnderprovisioned

Required: No

### **value**

The value of the finding reason code summary.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RecommendationExportJob

Describes a recommendation export job.

Use the [DescribeRecommendationExportJobs](#) action to view your recommendation export jobs.

Use the [ExportAutoScalingGroupRecommendations](#) or [ExportEC2InstanceRecommendations](#) actions to request an export of your recommendations.

## Contents

### **creationTimestamp**

The timestamp of when the export job was created.

Type: Timestamp

Required: No

### **destination**

An object that describes the destination of the export file.

Type: [ExportDestination](#) object

Required: No

### **failureReason**

The reason for an export job failure.

Type: String

Required: No

### **jobId**

The identification number of the export job.

Type: String

Required: No

### **lastUpdatedTimestamp**

The timestamp of when the export job was last updated.

Type: Timestamp

Required: No

### **resourceType**

The resource type of the exported recommendations.

Type: String

Valid Values: Ec2Instance | AutoScalingGroup | EbsVolume | LambdaFunction | NotApplicable | EcsService | License | RdsDBInstance | AuroraDBClusterStorage | Idle

Required: No

### **status**

The status of the export job.

Type: String

Valid Values: Queued | InProgress | Complete | Failed

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RecommendationPreferences

Describes the recommendation preferences to return in the response of a [GetAutoScalingGroupRecommendations](#), [GetEC2InstanceRecommendations](#), [GetEC2RecommendationProjectedMetrics](#), [GetRDSDatabaseRecommendations](#), and [GetRDSDatabaseRecommendationProjectedMetrics](#) request.

## Contents

### cpuVendorArchitectures

Specifies the CPU vendor and architecture for Amazon EC2 instance and Auto Scaling group recommendations.

For example, when you specify AWS\_ARM64 with:

- A [GetEC2InstanceRecommendations](#) or [GetAutoScalingGroupRecommendations](#) request, Compute Optimizer returns recommendations that consist of Graviton instance types only.
- A [GetEC2RecommendationProjectedMetrics](#) request, Compute Optimizer returns projected utilization metrics for Graviton instance type recommendations only.
- A [ExportEC2InstanceRecommendations](#) or [ExportAutoScalingGroupRecommendations](#) request, Compute Optimizer exports recommendations that consist of Graviton instance types only.

Type: Array of strings

Valid Values: AWS\_ARM64 | CURRENT

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)



# RecommendationPreferencesDetail

Describes a recommendation preference.

## Contents

### enhancedInfrastructureMetrics

The status of the enhanced infrastructure metrics recommendation preference.

When the recommendations page is refreshed, a status of Active confirms that the preference is applied to the recommendations, and a status of Inactive confirms that the preference isn't yet applied to recommendations.

For more information, see [Enhanced infrastructure metrics](#) in the *Amazon Compute Optimizer User Guide*.

Type: String

Valid Values: Active | Inactive

Required: No

### externalMetricsPreference

An object that describes the external metrics recommendation preference.

If the preference is applied in the latest recommendation refresh, an object with a valid source value appears in the response. If the preference isn't applied to the recommendations already, then this object doesn't appear in the response.

Type: [ExternalMetricsPreference](#) object

Required: No

### inferredWorkloadTypes

The status of the inferred workload types recommendation preference.

When the recommendations page is refreshed, a status of Active confirms that the preference is applied to the recommendations, and a status of Inactive confirms that the preference isn't yet applied to recommendations.

Type: String

Valid Values: Active | Inactive

Required: No

### **lookBackPeriod**

The preference to control the number of days the utilization metrics of the Amazon resource are analyzed. If the preference isn't set, this object is null.

Type: String

Valid Values: DAYS\_14 | DAYS\_32 | DAYS\_93

Required: No

### **preferredResources**

The preference to control which resource type values are considered when generating rightsizing recommendations. This object resolves any wildcard expressions and returns the effective list of candidate resource type values. If the preference isn't set, this object is null.

Type: Array of [EffectivePreferredResource](#) objects

Required: No

### **resourceType**

The target resource type of the recommendation preference to create.

The Ec2Instance option encompasses standalone instances and instances that are part of Auto Scaling groups. The AutoScalingGroup option encompasses only instances that are part of an Auto Scaling group.

Type: String

Valid Values: Ec2Instance | AutoScalingGroup | RdsDBInstance | AuroraDBCclusterStorage

Required: No

### **savingsEstimationMode**

Describes the savings estimation mode used for calculating savings opportunity.

Only the account manager or delegated administrator of your organization can activate this preference.

Type: String

Valid Values: AfterDiscounts | BeforeDiscounts

Required: No

### scope

An object that describes the scope of the recommendation preference.

Recommendation preferences can be created at the organization level (for management accounts of an organization only), account level, and resource level. For more information, see [Activating enhanced infrastructure metrics](#) in the *Amazon Compute Optimizer User Guide*.

Type: [Scope](#) object

Required: No

### utilizationPreferences

The preference to control the resource's CPU utilization threshold, CPU utilization headroom, and memory utilization headroom. If the preference isn't set, this object is null.

 **Note**

This preference is only available for the Amazon EC2 instance resource type.

Type: Array of [UtilizationPreference](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

# RecommendationSource

Describes the source of a recommendation, such as an Amazon EC2 instance or Auto Scaling group.

## Contents

### **recommendationSourceArn**

The Amazon Resource Name (ARN) of the recommendation source.

Type: String

Required: No

### **recommendationSourceType**

The resource type of the recommendation source.

Type: String

Valid Values: Ec2Instance | AutoScalingGroup | EbsVolume | LambdaFunction | EcsService | License | RdsDBInstance | RdsDBInstanceStorage | AuroraDBClusterStorage

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RecommendationSummary

A summary of a recommendation.

## Contents

### accountId

The Amazon account ID of the recommendation summary.

Type: String

Required: No

### aggregatedSavingsOpportunity

Describes the savings opportunity for recommendations of a given resource type or for the recommendation option of an individual resource.

Savings opportunity represents the estimated monthly savings you can achieve by implementing a given Compute Optimizer recommendation.

#### Important

Savings opportunity data requires that you opt in to Cost Explorer, as well as activate **Receive Amazon EC2 resource recommendations** in the Cost Explorer preferences page. That creates a connection between Cost Explorer and Compute Optimizer. With this connection, Cost Explorer generates savings estimates considering the price of existing resources, the price of recommended resources, and historical usage data. Estimated monthly savings reflects the projected dollar savings associated with each of the recommendations generated. For more information, see [Enabling Cost Explorer](#) and [Optimizing your cost with Rightsizing Recommendations](#) in the *Cost Management User Guide*.

Type: [SavingsOpportunity](#) object

Required: No

### currentPerformanceRiskRatings

An object that describes the performance risk ratings for a given resource type.

Type: [CurrentPerformanceRiskRatings](#) object

Required: No

### idleSavingsOpportunity

Describes the savings opportunity for recommendations of a given resource type or for the recommendation option of an individual resource.

Savings opportunity represents the estimated monthly savings you can achieve by implementing a given Compute Optimizer recommendation.

#### Important

Savings opportunity data requires that you opt in to Cost Explorer, as well as activate **Receive Amazon EC2 resource recommendations** in the Cost Explorer preferences page. That creates a connection between Cost Explorer and Compute Optimizer. With this connection, Cost Explorer generates savings estimates considering the price of existing resources, the price of recommended resources, and historical usage data. Estimated monthly savings reflects the projected dollar savings associated with each of the recommendations generated. For more information, see [Enabling Cost Explorer](#) and [Optimizing your cost with Rightsizing Recommendations](#) in the *Cost Management User Guide*.

Type: [SavingsOpportunity](#) object

Required: No

### idleSummaries

Describes the findings summary of the idle resources.

Type: Array of [IdleSummary](#) objects

Required: No

### inferredWorkloadSavings

An array of objects that describes the estimated monthly saving amounts for the instances running on the specified inferredWorkloadTypes. The array contains the top five savings opportunities for the instances that run inferred workload types.

Type: Array of [InferredWorkloadSaving](#) objects

Required: No

### **recommendationResourceType**

The resource type that the recommendation summary applies to.

Type: String

Valid Values: Ec2Instance | AutoScalingGroup | EbsVolume | LambdaFunction | EcsService | License | RdsDBInstance | RdsDBInstanceStorage | AuroraDBClusterStorage

Required: No

### **savingsOpportunity**

An object that describes the savings opportunity for a given resource type. Savings opportunity includes the estimated monthly savings amount and percentage.

Type: [SavingsOpportunity](#) object

Required: No

### **summaries**

An array of objects that describe a recommendation summary.

Type: Array of [Summary](#) objects

Required: No

## **See Also**

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RecommendedOptionProjectedMetric

Describes a projected utilization metric of a recommendation option.

## Note

The Cpu and Memory metrics are the only projected utilization metrics returned when you run the [GetEC2RecommendationProjectedMetrics](#) action. Additionally, the Memory metric is returned only for resources that have the unified CloudWatch agent installed on them. For more information, see [Enabling Memory Utilization with the CloudWatch Agent](#).

## Contents

### **projectedMetrics**

An array of objects that describe a projected utilization metric.

Type: Array of [ProjectedMetric](#) objects

Required: No

### **rank**

The rank of the recommendation option projected metric.

The top recommendation option is ranked as 1.

The projected metric rank correlates to the recommendation option rank. For example, the projected metric ranked as 1 is related to the recommendation option that is also ranked as 1 in the same response.

Type: Integer

Required: No

### **recommendedInstanceType**

The recommended instance type.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# S3Destination

Describes the destination Amazon Simple Storage Service (Amazon S3) bucket name and object keys of a recommendations export file, and its associated metadata file.

## Contents

### bucket

The name of the Amazon S3 bucket used as the destination of an export file.

Type: String

Required: No

### key

The Amazon S3 bucket key of an export file.

The key uniquely identifies the object, or export file, in the S3 bucket.

Type: String

Required: No

### metadataKey

The Amazon S3 bucket key of a metadata file.

The key uniquely identifies the object, or metadata file, in the S3 bucket.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

# S3DestinationConfig

Describes the destination Amazon Simple Storage Service (Amazon S3) bucket name and key prefix for a recommendations export job.

You must create the destination Amazon S3 bucket for your recommendations export before you create the export job. Compute Optimizer does not create the S3 bucket for you. After you create the S3 bucket, ensure that it has the required permission policy to allow Compute Optimizer to write the export file to it. If you plan to specify an object prefix when you create the export job, you must include the object prefix in the policy that you add to the S3 bucket. For more information, see [Amazon S3 Bucket Policy for Compute Optimizer](#) in the *Compute Optimizer User Guide*.

## Contents

### bucket

The name of the Amazon S3 bucket to use as the destination for an export job.

Type: String

Required: No

### keyPrefix

The Amazon S3 bucket prefix for an export job.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# SavingsOpportunity

Describes the savings opportunity for recommendations of a given resource type or for the recommendation option of an individual resource.

Savings opportunity represents the estimated monthly savings you can achieve by implementing a given Compute Optimizer recommendation.

## Important

Savings opportunity data requires that you opt in to Cost Explorer, as well as activate **Receive Amazon EC2 resource recommendations** in the Cost Explorer preferences page. That creates a connection between Cost Explorer and Compute Optimizer. With this connection, Cost Explorer generates savings estimates considering the price of existing resources, the price of recommended resources, and historical usage data. Estimated monthly savings reflects the projected dollar savings associated with each of the recommendations generated. For more information, see [Enabling Cost Explorer](#) and [Optimizing your cost with Rightsizing Recommendations](#) in the *Cost Management User Guide*.

## Contents

### **estimatedMonthlySavings**

An object that describes the estimated monthly savings amount possible by adopting Compute Optimizer recommendations for a given resource. This is based on the On-Demand instance pricing..

Type: [EstimatedMonthlySavings](#) object

Required: No

### **savingsOpportunityPercentage**

The estimated monthly savings possible as a percentage of monthly cost by adopting Compute Optimizer recommendations for a given resource.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# Scope

Describes the scope of a recommendation preference.

Recommendation preferences can be created at the organization level (for management accounts of an organization only), account level, and resource level. For more information, see [Activating enhanced infrastructure metrics](#) in the *Amazon Compute Optimizer User Guide*.

## Note

You cannot create recommendation preferences for Auto Scaling groups at the organization and account levels. You can create recommendation preferences for Auto Scaling groups only at the resource level by specifying a scope name of ResourceArn and a scope value of the Auto Scaling group Amazon Resource Name (ARN). This will configure the preference for all instances that are part of the specified Auto Scaling group. You also cannot create recommendation preferences at the resource level for instances that are part of an Auto Scaling group. You can create recommendation preferences at the resource level only for standalone instances.

## Contents

### **name**

The name of the scope.

The following scopes are possible:

- Organization - Specifies that the recommendation preference applies at the organization level, for all member accounts of an organization.
- AccountId - Specifies that the recommendation preference applies at the account level, for all resources of a given resource type in an account.
- ResourceArn - Specifies that the recommendation preference applies at the individual resource level.

Type: String

Valid Values: Organization | AccountId | ResourceArn

Required: No

## value

The value of the scope.

If you specified the name of the scope as:

- Organization - The value must be ALL\_ACCOUNTS.
- AccountId - The value must be a 12-digit Amazon account ID.
- ResourceArn - The value must be the Amazon Resource Name (ARN) of an EC2 instance or an Auto Scaling group.

Only EC2 instance and Auto Scaling group ARNs are currently supported.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ServiceConfiguration

The Amazon ECS service configurations used for recommendations.

## Contents

### autoScalingConfiguration

Describes the Auto Scaling configuration methods for an Amazon ECS service. This affects the generated recommendations. For example, if Auto Scaling is configured on a service's CPU, then Compute Optimizer doesn't generate CPU size recommendations.

The Auto Scaling configuration methods include:

- TARGET\_TRACKING\_SCALING\_CPU — If the Amazon ECS service is configured to use target scaling on CPU, Compute Optimizer doesn't generate CPU recommendations.
- TARGET\_TRACKING\_SCALING\_MEMORY — If the Amazon ECS service is configured to use target scaling on memory, Compute Optimizer doesn't generate memory recommendations.

For more information about step scaling and target scaling, see [Step scaling policies for Application Auto Scaling](#) and [Target tracking scaling policies for Application Auto Scaling](#) in the *Application Auto Scaling User Guide*.

Type: String

Valid Values: TargetTrackingScalingCpu | TargetTrackingScalingMemory

Required: No

### containerConfigurations

The container configurations within a task of an Amazon ECS service.

Type: Array of [ContainerConfiguration](#) objects

Required: No

### cpu

The number of CPU units used by the tasks in the Amazon ECS service.

Type: Integer

Required: No

## **memory**

The amount of memory used by the tasks in the Amazon ECS service.

Type: Integer

Required: No

## **taskDefinitionArn**

The task definition ARN used by the tasks in the Amazon ECS service.

Type: String

Required: No

## **See Also**

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# Summary

The summary of a recommendation.

## Contents

### **name**

The finding classification of the recommendation.

Type: String

Valid Values: Underprovisioned | Overprovisioned | Optimized | NotOptimized

Required: No

### **reasonCodeSummaries**

An array of objects that summarize a finding reason code.

Type: Array of [ReasonCodeSummary](#) objects

Required: No

### **value**

The value of the recommendation summary.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# Tag

A list of tag key and value pairs that you define.

## Contents

### key

One part of a key-value pair that makes up a tag. A key is a general label that acts like a category for more specific tag values.

Type: String

Required: No

### value

One part of a key-value pair that make up a tag. A value acts as a descriptor within a tag category (key). The value can be empty or null.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# UtilizationMetric

Describes a utilization metric of a resource, such as an Amazon EC2 instance.

Compare the utilization metric data of your resource against its projected utilization metric data to determine the performance difference between your current resource and the recommended option.

## Contents

### **name**

The name of the utilization metric.

The following utilization metrics are available:

- Cpu - The percentage of allocated EC2 compute units that are currently in use on the instance. This metric identifies the processing power required to run an application on the instance.

Depending on the instance type, tools in your operating system can show a lower percentage than CloudWatch when the instance is not allocated a full processor core.

Units: Percent

- Memory - The percentage of memory that is currently in use on the instance. This metric identifies the amount of memory required to run an application on the instance.

Units: Percent

 **Note**

The Memory metric is returned only for resources that have the unified CloudWatch agent installed on them. For more information, see [Enabling Memory Utilization with the CloudWatch Agent](#).

- GPU - The percentage of allocated GPUs that currently run on the instance.
- GPU\_MEMORY - The percentage of total GPU memory that currently runs on the instance.

**Note**

The GPU and GPU\_MEMORY metrics are only returned for resources with the unified CloudWatch Agent installed on them. For more information, see [Enabling NVIDIA GPU utilization with the CloudWatch Agent](#).

- EBS\_READ\_OPS\_PER\_SECOND - The completed read operations from all EBS volumes attached to the instance in a specified period of time.

Unit: Count

- EBS\_WRITE\_OPS\_PER\_SECOND - The completed write operations to all EBS volumes attached to the instance in a specified period of time.

Unit: Count

- EBS\_READ\_BYTES\_PER\_SECOND - The bytes read from all EBS volumes attached to the instance in a specified period of time.

Unit: Bytes

- EBS\_WRITE\_BYTES\_PER\_SECOND - The bytes written to all EBS volumes attached to the instance in a specified period of time.

Unit: Bytes

- DISK\_READ\_OPS\_PER\_SECOND - The completed read operations from all instance store volumes available to the instance in a specified period of time.

If there are no instance store volumes, either the value is 0 or the metric is not reported.

- DISK\_WRITE\_OPS\_PER\_SECOND - The completed write operations from all instance store volumes available to the instance in a specified period of time.

If there are no instance store volumes, either the value is 0 or the metric is not reported.

- DISK\_READ\_BYTES\_PER\_SECOND - The bytes read from all instance store volumes available to the instance. This metric is used to determine the volume of the data the application reads from the disk of the instance. This can be used to determine the speed of the application.

If there are no instance store volumes, either the value is 0 or the metric is not reported.

- DISK\_WRITE\_BYTES\_PER\_SECOND - The bytes written to all instance store volumes available to the instance. This metric is used to determine the volume of the data the

application writes onto the disk of the instance. This can be used to determine the speed of the application.

If there are no instance store volumes, either the value is 0 or the metric is not reported.

- NETWORK\_IN\_BYTES\_PER\_SECOND - The number of bytes received by the instance on all network interfaces. This metric identifies the volume of incoming network traffic to a single instance.
- NETWORK\_OUT\_BYTES\_PER\_SECOND - The number of bytes sent out by the instance on all network interfaces. This metric identifies the volume of outgoing network traffic from a single instance.
- NETWORK\_PACKETS\_IN\_PER\_SECOND - The number of packets received by the instance on all network interfaces. This metric identifies the volume of incoming traffic in terms of the number of packets on a single instance.
- NETWORK\_PACKETS\_OUT\_PER\_SECOND - The number of packets sent out by the instance on all network interfaces. This metric identifies the volume of outgoing traffic in terms of the number of packets on a single instance.

Type: String

Valid Values: Cpu | Memory | EBS\_READ\_OPS\_PER\_SECOND |  
EBS\_WRITE\_OPS\_PER\_SECOND | EBS\_READ\_BYTES\_PER\_SECOND |  
EBS\_WRITE\_BYTES\_PER\_SECOND | DISK\_READ\_OPS\_PER\_SECOND |  
DISK\_WRITE\_OPS\_PER\_SECOND | DISK\_READ\_BYTES\_PER\_SECOND |  
DISK\_WRITE\_BYTES\_PER\_SECOND | NETWORK\_IN\_BYTES\_PER\_SECOND |  
NETWORK\_OUT\_BYTES\_PER\_SECOND | NETWORK\_PACKETS\_IN\_PER\_SECOND |  
NETWORK\_PACKETS\_OUT\_PER\_SECOND | GPU\_PERCENTAGE | GPU\_MEMORY\_PERCENTAGE

Required: No

### **statistic**

The statistic of the utilization metric.

The Compute Optimizer API, Amazon Command Line Interface (Amazon CLI), and SDKs return utilization metrics using only the Maximum statistic, which is the highest value observed during the specified period.

The Compute Optimizer console displays graphs for some utilization metrics using the Average statistic, which is the value of Sum / SampleCount during the specified period. For more

information, see [Viewing resource recommendations](#) in the *Amazon Compute Optimizer User Guide*. You can also get averaged utilization metric data for your resources using Amazon CloudWatch. For more information, see the [Amazon CloudWatch User Guide](#).

Type: String

Valid Values: Maximum | Average

Required: No

### **value**

The value of the utilization metric.

Type: Double

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# UtilizationPreference

The preference to control the resource's CPU utilization threshold, CPU utilization headroom, and memory utilization headroom.

 **Note**

This preference is only available for the Amazon EC2 instance resource type.

## Contents

### **metricName**

The name of the resource utilization metric name to customize.

Type: String

Valid Values: CpuUtilization | MemoryUtilization

Required: No

### **metricParameters**

The parameters to set when customizing the resource utilization thresholds.

Type: [CustomizableMetricParameters](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# VolumeConfiguration

Describes the configuration of an Amazon Elastic Block Store (Amazon EBS) volume.

## Contents

### **rootVolume**

Contains the image used to boot the instance during launch.

Type: Boolean

Required: No

### **volumeBaselineIOPS**

The baseline IOPS of the volume.

Type: Integer

Required: No

### **volumeBaselineThroughput**

The baseline throughput of the volume.

Type: Integer

Required: No

### **volumeBurstIOPS**

The burst IOPS of the volume.

Type: Integer

Required: No

### **volumeBurstThroughput**

The burst throughput of the volume.

Type: Integer

Required: No

## volumeSize

The size of the volume, in GiB.

Type: Integer

Required: No

## volumeType

The volume type.

The volume types can be the following:

- General Purpose SSD gp2 and gp3
- Provisioned IOPS SSD io1, io2, and io2 Block Express
- Throughput Optimized HDD st1
- Cold HDD sc1
- Magnetic volumes standard

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# VolumeRecommendation

Describes an Amazon Elastic Block Store (Amazon EBS) volume recommendation.

## Contents

### accountId

The Amazon account ID of the volume.

Type: String

Required: No

### currentConfiguration

An array of objects that describe the current configuration of the volume.

Type: [VolumeConfiguration](#) object

Required: No

### currentPerformanceRisk

The risk of the current EBS volume not meeting the performance needs of its workloads. The higher the risk, the more likely the current EBS volume doesn't have sufficient capacity.

Type: String

Valid Values: VeryLow | Low | Medium | High

Required: No

### effectiveRecommendationPreferences

Describes the effective recommendation preferences for Amazon EBS volume.

Type: [EBSEffectiveRecommendationPreferences](#) object

Required: No

### finding

The finding classification of the volume.

Findings for volumes include:

- **NotOptimized**—A volume is considered not optimized when Amazon Compute Optimizer identifies a recommendation that can provide better performance for your workload.
- **Optimized**—A volume is considered optimized when Compute Optimizer determines that the volume is correctly provisioned to run your workload based on the chosen volume type. For optimized resources, Compute Optimizer might recommend a new generation volume type.

Type: String

Valid Values: Optimized | NotOptimized

Required: No

### **lastRefreshTimestamp**

The timestamp of when the volume recommendation was last generated.

Type: Timestamp

Required: No

### **lookBackPeriodInDays**

The number of days for which utilization metrics were analyzed for the volume.

Type: Double

Required: No

### **tags**

A list of tags assigned to your Amazon EBS volume recommendations.

Type: Array of [Tag](#) objects

Required: No

### **utilizationMetrics**

An array of objects that describe the utilization metrics of the volume.

Type: Array of [EBSUtilizationMetric](#) objects

Required: No

**volumeArn**

The Amazon Resource Name (ARN) of the current volume.

Type: String

Required: No

**volumeRecommendationOptions**

An array of objects that describe the recommendation options for the volume.

Type: Array of [VolumeRecommendationOption](#) objects

Required: No

**See Also**

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# VolumeRecommendationOption

Describes a recommendation option for an Amazon Elastic Block Store (Amazon EBS) instance.

## Contents

### configuration

An array of objects that describe a volume configuration.

Type: [VolumeConfiguration](#) object

Required: No

### performanceRisk

The performance risk of the volume recommendation option.

Performance risk is the likelihood of the recommended volume type meeting the performance requirement of your workload.

The value ranges from 0 - 4, with 0 meaning that the recommended resource is predicted to always provide enough hardware capability. The higher the performance risk is, the more likely you should validate whether the recommendation will meet the performance requirements of your workload before migrating your resource.

Type: Double

Valid Range: Minimum value of 0. Maximum value of 4.

Required: No

### rank

The rank of the volume recommendation option.

The top recommendation option is ranked as 1.

Type: Integer

Required: No

### savingsOpportunity

An object that describes the savings opportunity for the EBS volume recommendation option.

Savings opportunity includes the estimated monthly savings amount and percentage.

Type: [SavingsOpportunity](#) object

Required: No

### **savingsOpportunityAfterDiscounts**

An object that describes the savings opportunity for the Amazon EBS volume recommendation option with specific discounts. Savings opportunity includes the estimated monthly savings and percentage.

Type: [EBSSavingsOpportunityAfterDiscounts](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing Amazon API requests](#) in the *IAM User Guide*.

## Action

The action to be performed.

Type: string

Required: Yes

## Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

## X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

## X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request").

The value is expressed in the following format: *access\_key/YYYYMMDD/region/service/aws4\_request*.

For more information, see [Create a signed Amazon API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

#### X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an Amazon API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

#### X-Amz-Security-Token

The temporary security token that was obtained through a call to Amazon Security Token Service (Amazon STS). For a list of services that support temporary security credentials from Amazon STS, see [Amazon Web Services services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from Amazon STS, you must include the security token.

Type: string

Required: Conditional

#### X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed Amazon API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

# Common Errors

This section lists the errors common to the API actions of all Amazon services. For errors specific to an API action for this service, see the topic for that API action.

## **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

## **IncompleteSignature**

The request signature does not conform to Amazon standards.

HTTP Status Code: 400

## **InternalFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## **InvalidAction**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

## **InvalidClientTokenId**

The X.509 certificate or Amazon access key ID provided does not exist in our records.

HTTP Status Code: 403

## **NotAuthorized**

You do not have permission to perform this action.

HTTP Status Code: 400

## **OptInRequired**

The Amazon access key ID needs a subscription for the service.

HTTP Status Code: 403

## **RequestExpired**

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

## **ServiceUnavailable**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

## **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

## **ValidationException**

The input fails to satisfy the constraints specified by an Amazon service.

HTTP Status Code: 400