

# Elastic Load Balancing



# Elastic Load Balancing: API Reference

# Table of Contents

Welcome .....	1
Actions .....	3
AddListenerCertificates .....	5
Request Parameters .....	5
Response Elements .....	5
Errors .....	6
See Also .....	6
AddTags .....	8
Request Parameters .....	8
Errors .....	8
Examples .....	9
See Also .....	10
AddTrustStoreRevocations .....	11
Request Parameters .....	11
Response Elements .....	11
Errors .....	11
Examples .....	12
See Also .....	12
CreateListener .....	14
Request Parameters .....	14
Response Elements .....	16
Errors .....	17
Examples .....	19
See Also .....	24
CreateLoadBalancer .....	25
Request Parameters .....	25
Response Elements .....	29
Errors .....	29
Examples .....	31
See Also .....	34
CreateRule .....	35
Request Parameters .....	35
Response Elements .....	36
Errors .....	36

Examples .....	38
See Also .....	40
CreateTargetGroup .....	42
Request Parameters .....	42
Response Elements .....	47
Errors .....	47
Examples .....	48
See Also .....	50
CreateTrustStore .....	52
Request Parameters .....	52
Response Elements .....	53
Errors .....	53
Examples .....	54
See Also .....	54
DeleteListener .....	56
Request Parameters .....	56
Errors .....	56
Examples .....	56
See Also .....	57
DeleteLoadBalancer .....	58
Request Parameters .....	58
Errors .....	58
Examples .....	59
See Also .....	59
DeleteRule .....	60
Request Parameters .....	60
Errors .....	60
Examples .....	60
See Also .....	61
DeleteSharedTrustStoreAssociation .....	62
Request Parameters .....	62
Errors .....	62
See Also .....	63
DeleteTargetGroup .....	64
Request Parameters .....	64
Errors .....	64

Examples .....	64
See Also .....	65
DeleteTrustStore .....	66
Request Parameters .....	66
Errors .....	66
Examples .....	66
See Also .....	67
DeregisterTargets .....	68
Request Parameters .....	68
Errors .....	68
Examples .....	69
See Also .....	70
DescribeAccountLimits .....	71
Request Parameters .....	71
Response Elements .....	71
Errors .....	72
See Also .....	72
DescribeCapacityReservation .....	73
Request Parameters .....	73
Response Elements .....	73
Errors .....	74
See Also .....	74
DescribeListenerAttributes .....	75
Request Parameters .....	75
Response Elements .....	75
Errors .....	75
Examples .....	75
See Also .....	76
DescribeListenerCertificates .....	77
Request Parameters .....	77
Response Elements .....	77
Errors .....	78
Examples .....	78
See Also .....	79
DescribeListeners .....	81
Request Parameters .....	81

Response Elements .....	82
Errors .....	82
Examples .....	83
See Also .....	86
DescribeLoadBalancerAttributes .....	88
Request Parameters .....	88
Response Elements .....	88
Errors .....	88
Examples .....	89
See Also .....	90
DescribeLoadBalancers .....	91
Request Parameters .....	91
Response Elements .....	92
Errors .....	92
Examples .....	92
See Also .....	94
DescribeRules .....	95
Request Parameters .....	95
Response Elements .....	95
Errors .....	96
Examples .....	96
See Also .....	99
DescribeSSLPolicies .....	100
Request Parameters .....	100
Response Elements .....	101
Errors .....	101
Examples .....	101
See Also .....	103
DescribeTags .....	104
Request Parameters .....	104
Response Elements .....	104
Errors .....	104
Examples .....	105
See Also .....	106
DescribeTargetGroupAttributes .....	107
Request Parameters .....	107

Response Elements .....	107
Errors .....	107
Examples .....	108
See Also .....	108
DescribeTargetGroups .....	110
Request Parameters .....	110
Response Elements .....	111
Errors .....	111
Examples .....	112
See Also .....	113
DescribeTargetHealth .....	115
Request Parameters .....	115
Response Elements .....	115
Errors .....	116
Examples .....	116
See Also .....	118
DescribeTrustStoreAssociations .....	120
Request Parameters .....	120
Response Elements .....	120
Errors .....	121
Examples .....	121
See Also .....	121
DescribeTrustStoreRevocations .....	123
Request Parameters .....	123
Response Elements .....	123
Errors .....	124
Examples .....	124
See Also .....	125
DescribeTrustStores .....	126
Request Parameters .....	126
Response Elements .....	127
Errors .....	127
Examples .....	127
See Also .....	128
GetResourcePolicy .....	129
Request Parameters .....	129

Response Elements .....	129
Errors .....	129
Examples .....	130
See Also .....	130
GetTrustStoreCaCertificatesBundle .....	131
Request Parameters .....	131
Response Elements .....	131
Errors .....	131
See Also .....	132
GetTrustStoreRevocationContent .....	133
Request Parameters .....	133
Response Elements .....	133
Errors .....	133
Examples .....	134
See Also .....	134
ModifyCapacityReservation .....	136
Request Parameters .....	136
Response Elements .....	136
Errors .....	137
See Also .....	138
ModifyIpPools .....	139
Request Parameters .....	139
Response Elements .....	139
Errors .....	140
See Also .....	140
ModifyListener .....	141
Request Parameters .....	141
Response Elements .....	143
Errors .....	143
Examples .....	146
See Also .....	149
ModifyListenerAttributes .....	151
Request Parameters .....	151
Response Elements .....	151
Errors .....	151
See Also .....	152

ModifyLoadBalancerAttributes .....	153
Request Parameters .....	153
Response Elements .....	153
Errors .....	154
Examples .....	154
See Also .....	158
ModifyRule .....	159
Request Parameters .....	159
Response Elements .....	159
Errors .....	160
See Also .....	161
ModifyTargetGroup .....	163
Request Parameters .....	163
Response Elements .....	165
Errors .....	165
Examples .....	166
See Also .....	167
ModifyTargetGroupAttributes .....	168
Request Parameters .....	168
Response Elements .....	168
Errors .....	168
Examples .....	169
See Also .....	170
ModifyTrustStore .....	171
Request Parameters .....	171
Response Elements .....	171
Errors .....	172
Examples .....	172
See Also .....	173
RegisterTargets .....	174
Request Parameters .....	174
Errors .....	174
Examples .....	175
See Also .....	177
RemoveListenerCertificates .....	178
Request Parameters .....	178

Errors .....	178
See Also .....	179
RemoveTags .....	180
Request Parameters .....	180
Errors .....	180
Examples .....	181
See Also .....	182
RemoveTrustStoreRevocations .....	183
Request Parameters .....	183
Errors .....	183
Examples .....	184
See Also .....	184
SetIpAddressType .....	185
Request Parameters .....	185
Response Elements .....	185
Errors .....	186
Examples .....	186
See Also .....	187
SetRulePriorities .....	188
Request Parameters .....	188
Response Elements .....	188
Errors .....	188
Examples .....	189
See Also .....	190
SetSecurityGroups .....	191
Request Parameters .....	191
Response Elements .....	191
Errors .....	192
Examples .....	192
See Also .....	193
SetSubnets .....	195
Request Parameters .....	195
Response Elements .....	197
Errors .....	197
Examples .....	198
See Also .....	199

<b>Data Types</b> .....	<b>201</b>
Action .....	204
Contents .....	204
See Also .....	206
AdministrativeOverride .....	207
Contents .....	207
See Also .....	207
AnomalyDetection .....	209
Contents .....	209
See Also .....	209
AuthenticateCognitoActionConfig .....	210
Contents .....	210
See Also .....	211
AuthenticateOidcActionConfig .....	213
Contents .....	213
See Also .....	215
AvailabilityZone .....	216
Contents .....	216
See Also .....	217
CapacityReservationStatus .....	218
Contents .....	218
See Also .....	218
Certificate .....	219
Contents .....	219
See Also .....	219
Cipher .....	220
Contents .....	220
See Also .....	220
DescribeTrustStoreRevocation .....	221
Contents .....	221
See Also .....	221
FixedResponseActionConfig .....	223
Contents .....	223
See Also .....	223
ForwardActionConfig .....	225
Contents .....	225

See Also .....	225
HostHeaderConditionConfig .....	226
Contents .....	226
See Also .....	226
HttpHeaderConditionConfig .....	227
Contents .....	227
See Also .....	227
HttpRequestMethodConditionConfig .....	229
Contents .....	229
See Also .....	229
IpamPools .....	230
Contents .....	230
See Also .....	230
Limit .....	231
Contents .....	231
See Also .....	232
Listener .....	233
Contents .....	233
See Also .....	234
ListenerAttribute .....	236
Contents .....	236
See Also .....	238
LoadBalancer .....	239
Contents .....	239
See Also .....	242
LoadBalancerAddress .....	243
Contents .....	243
See Also .....	243
LoadBalancerAttribute .....	245
Contents .....	245
See Also .....	248
LoadBalancerState .....	249
Contents .....	249
See Also .....	249
Matcher .....	250
Contents .....	250

See Also .....	250
MinimumLoadBalancerCapacity .....	252
Contents .....	252
See Also .....	252
MutualAuthenticationAttributes .....	253
Contents .....	253
See Also .....	254
PathPatternConditionConfig .....	255
Contents .....	255
See Also .....	255
QueryStringConditionConfig .....	256
Contents .....	256
See Also .....	256
QueryStringKeyValuePair .....	257
Contents .....	257
See Also .....	257
RedirectActionConfig .....	258
Contents .....	258
See Also .....	259
RevocationContent .....	261
Contents .....	261
See Also .....	261
Rule .....	263
Contents .....	263
See Also .....	264
RuleCondition .....	265
Contents .....	265
See Also .....	267
RulePriorityPair .....	268
Contents .....	268
See Also .....	268
SOURCEPConditionConfig .....	269
Contents .....	269
See Also .....	269
SslPolicy .....	270
Contents .....	270

See Also .....	270
SubnetMapping .....	272
Contents .....	272
See Also .....	273
Tag .....	274
Contents .....	274
See Also .....	274
TagDescription .....	275
Contents .....	275
See Also .....	275
TargetDescription .....	276
Contents .....	276
See Also .....	277
TargetGroup .....	278
Contents .....	278
See Also .....	281
TargetGroupAttribute .....	283
Contents .....	283
See Also .....	286
TargetGroupStickinessConfig .....	287
Contents .....	287
See Also .....	287
TargetGroupTuple .....	288
Contents .....	288
See Also .....	288
TargetHealth .....	289
Contents .....	289
See Also .....	290
TargetHealthDescription .....	292
Contents .....	292
See Also .....	293
TrustStore .....	294
Contents .....	294
See Also .....	295
TrustStoreAssociation .....	296
Contents .....	296

See Also .....	296
TrustStoreRevocation .....	297
Contents .....	297
See Also .....	297
ZonalCapacityReservationState .....	299
Contents .....	299
See Also .....	299
<b>Common Parameters .....</b>	<b>300</b>
<b>Common Errors .....</b>	<b>303</b>

# Welcome

A load balancer distributes incoming traffic across targets, such as your EC2 instances. This enables you to increase the availability of your application. The load balancer also monitors the health of its registered targets and ensures that it routes traffic only to healthy targets. You configure your load balancer to accept incoming traffic by specifying one or more listeners, which are configured with a protocol and port number for connections from clients to the load balancer. You configure a target group with a protocol and port number for connections from the load balancer to the targets, and with health check settings to be used when checking the health status of the targets.

Elastic Load Balancing supports the following types of load balancers: Application Load Balancers, Network Load Balancers, Gateway Load Balancers, and Classic Load Balancers. This reference covers the following load balancer types:

- Application Load Balancer - Operates at the application layer (layer 7) and supports HTTP and HTTPS.
- Network Load Balancer - Operates at the transport layer (layer 4) and supports TCP, TLS, and UDP.
- Gateway Load Balancer - Operates at the network layer (layer 3).

For more information, see the [Elastic Load Balancing User Guide](#).

To get started, complete the following tasks:

1. Create a load balancer using [CreateLoadBalancer](#).
2. Create a target group using [CreateTargetGroup](#).
3. Register targets for the target group using [RegisterTargets](#).
4. Create one or more listeners for your load balancer using [CreateListener](#).

To delete a load balancer and its related resources, complete the following tasks:

1. Delete the load balancer using [DeleteLoadBalancer](#).
2. Delete the target group using [DeleteTargetGroup](#).

All Elastic Load Balancing operations are idempotent, which means that they complete at most one time. If you repeat an operation, it succeeds.

This document was last published on July 3, 2025.

# Actions

The following actions are supported:

- [AddListenerCertificates](#)
- [AddTags](#)
- [AddTrustStoreRevocations](#)
- [CreateListener](#)
- [CreateLoadBalancer](#)
- [CreateRule](#)
- [CreateTargetGroup](#)
- [CreateTrustStore](#)
- [DeleteListener](#)
- [DeleteLoadBalancer](#)
- [DeleteRule](#)
- [DeleteSharedTrustStoreAssociation](#)
- [DeleteTargetGroup](#)
- [DeleteTrustStore](#)
- [DeregisterTargets](#)
- [DescribeAccountLimits](#)
- [DescribeCapacityReservation](#)
- [DescribeListenerAttributes](#)
- [DescribeListenerCertificates](#)
- [DescribeListeners](#)
- [DescribeLoadBalancerAttributes](#)
- [DescribeLoadBalancers](#)
- [DescribeRules](#)
- [DescribeSSLPolicies](#)
- [DescribeTags](#)
- [DescribeTargetGroupAttributes](#)
- [DescribeTargetGroups](#)

- [DescribeTargetHealth](#)
- [DescribeTrustStoreAssociations](#)
- [DescribeTrustStoreRevocations](#)
- [DescribeTrustStores](#)
- [GetResourcePolicy](#)
- [GetTrustStoreCaCertificatesBundle](#)
- [GetTrustStoreRevocationContent](#)
- [ModifyCapacityReservation](#)
- [ModifyIpPools](#)
- [ModifyListener](#)
- [ModifyListenerAttributes](#)
- [ModifyLoadBalancerAttributes](#)
- [ModifyRule](#)
- [ModifyTargetGroup](#)
- [ModifyTargetGroupAttributes](#)
- [ModifyTrustStore](#)
- [RegisterTargets](#)
- [RemoveListenerCertificates](#)
- [RemoveTags](#)
- [RemoveTrustStoreRevocations](#)
- [SetIpAddressType](#)
- [SetRulePriorities](#)
- [SetSecurityGroups](#)
- [SetSubnets](#)

# AddListenerCertificates

Adds the specified SSL server certificate to the certificate list for the specified HTTPS or TLS listener.

If the certificate is already in the certificate list, the call is successful but the certificate is not added again.

To get the certificate list for a listener, use [DescribeListenerCertificates](#). To remove certificates from the certificate list for a listener, use [RemoveListenerCertificates](#). To replace the default certificate for a listener, use [ModifyListener](#).

For more information, see [SSL certificates](#) in the *Application Load Balancers Guide* or [Server certificates](#) in the *Network Load Balancers Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### Certificates.member.N

The certificate to add. You can specify one certificate per call. Set CertificateArn to the certificate ARN but do not set IsDefault.

Type: Array of [Certificate](#) objects

Required: Yes

### ListenerArn

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: Yes

## Response Elements

The following element is returned by the service.

### Certificates.member.N

Information about the certificates in the certificate list.

Type: Array of [Certificate](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### CertificateNotFound

The specified certificate does not exist.

HTTP Status Code: 400

### ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

### TooManyCertificates

You've reached the limit on the number of certificates per load balancer.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)



## AddTags

Adds the specified tags to the specified Elastic Load Balancing resource. You can tag your Application Load Balancers, Network Load Balancers, Gateway Load Balancers, target groups, trust stores, listeners, and rules.

Each tag consists of a key and an optional value. If a resource already has a tag with the same key, AddTags updates its value.

To list the current tags for your resources, use [DescribeTags](#). To remove tags from your resources, use [RemoveTags](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### **ResourceArns.member.N**

The Amazon Resource Name (ARN) of the resource.

Type: Array of strings

Required: Yes

### **Tags.member.N**

The tags.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **DuplicateTagKeys**

A tag key was specified more than once.

HTTP Status Code: 400

### ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

### LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

### RuleNotFound

The specified rule does not exist.

HTTP Status Code: 400

### TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

### TooManyTags

You've reached the limit on the number of tags for this resource.

HTTP Status Code: 400

### TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

## Examples

### Add tags to a load balancer

This example adds the specified tags to the specified load balancer.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=AddTags
```

```
&ResourceArns.member.1=arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188
&Tags.member.1.Key=project
&Tags.member.1.Value=lima
&Tags.member.2.Key=department
&Tags.member.2.Value=digital-media
&Version=2015-12-01
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# AddTrustStoreRevocations

Adds the specified revocation file to the specified trust store.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### RevocationContents.member.N

The revocation file to add.

Type: Array of [RevocationContent](#) objects

Required: No

### TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

## Response Elements

The following element is returned by the service.

### TrustStoreRevocations.member.N

Information about the revocation file added to the trust store.

Type: Array of [TrustStoreRevocation](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### InvalidRevocationContent

The provided revocation file is an invalid format, or uses an incorrect algorithm.

HTTP Status Code: 400

### RevocationContentNotFound

The specified revocation file does not exist.

HTTP Status Code: 400

### TooManyTrustStoreRevocationEntries

The specified trust store has too many revocation entries.

HTTP Status Code: 400

### TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

## Examples

### Add a revocation file to a trust store.

This example adds the specified certificate revocation list to the specified trust store.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=AddTrustStoreRevocations
&TrustStoreArn=arn:aws:elasticloadbalancing:us-east-1:111122223333:truststore/my-trust-
store/3ym756xh7yj
&RevocationContents.member.1.RevocationType=CRL
&RevocationContents.member.1.S3Bucket=amzn-s3-demo-bucket
&RevocationContents.member.1.S3Key=my-crl.pem
&Version=2015-12-01
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# CreateListener

Creates a listener for the specified Application Load Balancer, Network Load Balancer, or Gateway Load Balancer.

To update a listener, use [ModifyListener](#). When you are finished with a listener, you can delete it using [DeleteListener](#). If you are finished with both the listener and the load balancer, you can delete them both using [DeleteLoadBalancer](#).

For more information, see the following:

- [Listeners for your Application Load Balancers](#)
- [Listeners for your Network Load Balancers](#)
- [Listeners for your Gateway Load Balancers](#)

This operation is idempotent, which means that it completes at most one time. If you attempt to create multiple listeners with the same settings, each call succeeds.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### AlpnPolicy.member.N

[TLS listeners] The name of the Application-Layer Protocol Negotiation (ALPN) policy. You can specify one policy name. The following are the possible values:

- HTTP1Only
- HTTP2Only
- HTTP2Optional
- HTTP2Preferred
- None

For more information, see [ALPN policies](#) in the *Network Load Balancers Guide*.

Type: Array of strings

Required: No

## Certificates.member.N

[HTTPS and TLS listeners] The default certificate for the listener. You must provide exactly one certificate. Set `CertificateArn` to the certificate ARN but do not set `IsDefault`.

To create a certificate list for the listener, use [AddListenerCertificates](#).

Type: Array of [Certificate](#) objects

Required: No

## DefaultActions.member.N

The actions for the default rule.

Type: Array of [Action](#) objects

Required: Yes

## LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

## MutualAuthentication

The mutual authentication configuration information.

Type: [MutualAuthenticationAttributes](#) object

Required: No

## Port

The port on which the load balancer is listening. You can't specify a port for a Gateway Load Balancer.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

## Protocol

The protocol for connections from clients to the load balancer. For Application Load Balancers, the supported protocols are HTTP and HTTPS. For Network Load Balancers, the supported protocols are TCP, TLS, UDP, and TCP\_UDP. You can't specify the UDP or TCP\_UDP protocol if dual-stack mode is enabled. You can't specify a protocol for a Gateway Load Balancer.

Type: String

Valid Values: HTTP | HTTPS | TCP | TLS | UDP | TCP\_UDP | GENEVE

Required: No

## SslPolicy

[HTTPS and TLS listeners] The security policy that defines which protocols and ciphers are supported.

For more information, see [Security policies](#) in the *Application Load Balancers Guide* and [Security policies](#) in the *Network Load Balancers Guide*.

Type: String

Required: No

## Tags.member.N

The tags to assign to the listener.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item.

Required: No

## Response Elements

The following element is returned by the service.

### Listeners.member.N

Information about the listener.

Type: Array of [Listener](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ALPNPolicyNotFound**

The specified ALPN policy is not supported.

HTTP Status Code: 400

### **CertificateNotFound**

The specified certificate does not exist.

HTTP Status Code: 400

### **DuplicateListener**

A listener with the specified port already exists.

HTTP Status Code: 400

### **IncompatibleProtocols**

The specified configuration is not valid with this protocol.

HTTP Status Code: 400

### **InvalidConfigurationRequest**

The requested configuration is not valid.

HTTP Status Code: 400

### **InvalidLoadBalancerAction**

The requested action is not valid.

HTTP Status Code: 400

### **LoadBalancerNotFound**

The specified load balancer does not exist.

HTTP Status Code: 400

**SSLPolicyNotFound**

The specified SSL policy does not exist.

HTTP Status Code: 400

**TargetGroupAssociationLimit**

You've reached the limit on the number of load balancers per target group.

HTTP Status Code: 400

**TargetGroupNotFound**

The specified target group does not exist.

HTTP Status Code: 400

**TooManyActions**

You've reached the limit on the number of actions per rule.

HTTP Status Code: 400

**TooManyCertificates**

You've reached the limit on the number of certificates per load balancer.

HTTP Status Code: 400

**TooManyListeners**

You've reached the limit on the number of listeners per load balancer.

HTTP Status Code: 400

**TooManyRegistrationsForTargetId**

You've reached the limit on the number of times a target can be registered with a load balancer.

HTTP Status Code: 400

**TooManyTags**

You've reached the limit on the number of tags for this resource.

HTTP Status Code: 400

## TooManyTargets

You've reached the limit on the number of targets.

HTTP Status Code: 400

## TooManyUniqueTargetGroupsPerLoadBalancer

You've reached the limit on the number of unique target groups per load balancer across all listeners. If a target group is used by multiple actions for a load balancer, it is counted as only one use.

HTTP Status Code: 400

## TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

## TrustStoreNotReady

The specified trust store is not active.

HTTP Status Code: 400

## UnsupportedProtocol

The specified protocol is not supported.

HTTP Status Code: 400

## Examples

### Create an HTTP listener

This example creates an HTTP listener for the specified Application Load Balancer that forwards requests to the specified target group.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action/CreateListener
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
&Protocol=HTTP
```

```
&Port=80
&DefaultActions.member.1.Type=forward
&DefaultActions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
&Version=2015-12-01
&AUTHPARAMS
```

## Sample Response

```
<CreateListenerResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <CreateListenerResult>
    <Listeners>
      <member>
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</
LoadBalancerArn>
        <Protocol>HTTP</Protocol>
        <Port>80</Port>
        <ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2</ListenerArn>
        <DefaultActions>
          <member>
            <Type>forward</Type>
            <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
          </member>
        </DefaultActions>
      </member>
    </Listeners>
  </CreateListenerResult>
  <ResponseMetadata>
    <RequestId>883c84bb-f387-11e5-ae48-cff02092876b</RequestId>
  </ResponseMetadata>
</CreateListenerResponse>
```

## Create an HTTPS listener

This example creates an HTTPS listener for the specified Application Load Balancer that forwards requests to the specified target group. Note that you must specify a default certificate for an HTTPS listener. You can create and manage your certificates using Amazon Certificate Manager (ACM). Alternatively, you can create a certificate using SSL/TLS tools, get the certificate signed by

a certificate authority (CA), and upload the certificate to Amazon Identity and Access Management (IAM).

## Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateListener
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
&Protocol=HTTPS
&Port=443
&Certificates.member.1.CertificateArn=arn:aws:iam::123456789012:server-certificate/my-
server-cert
&SslPolicy=ELBSecurityPolicy-2016-08
&DefaultActions.member.1.Type=forward
&DefaultActions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
&Version=2015-12-01
&AUTHPARAMS
```

## Sample Response

```
<CreateListenerResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <CreateListenerResult>
    <Listeners>
      <member>
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</
LoadBalancerArn>
        <Protocol>HTTPS</Protocol>
        <Certificates>
          <member>
            <CertificateArn>arn:aws:iam::123456789012:server-certificate/my-server-
cert</CertificateArn>
          </member>
        </Certificates>
        <Port>443</Port>
        <SslPolicy>ELBSecurityPolicy-2016-08</SslPolicy>
        <ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2</ListenerArn>
        <DefaultActions>
          <member>
            <Type>forward</Type>
```

```
<TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
  </member>
</DefaultActions>
</member>
</Listeners>
</CreateListenerResult>
<ResponseMetadata>
  <RequestId>97f1bb38-f390-11e5-b95d-3b2c1831fc26</RequestId>
</ResponseMetadata>
</CreateListenerResponse>
```

## Create a TCP listener

This example creates a TCP listener for the specified Network Load Balancer that forwards requests to the specified target group.

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateListener
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/net/
my-network-load-balancer/2d7b630a7815dda2
&Protocol=TCP
&Port=80
&DefaultActions.member.1.Type=forward
&DefaultActions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-tcp-targets/b7fce90c666d892a
&Version=2015-12-01
&AUTHPARAMS
```

## Create a TLS listener

This example creates a TLS listener for the specified Network Load Balancer that forwards requests to the specified target group.

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateListener
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/net/
my-network-load-balancer/2d7b630a7815dda2
&Protocol=TLS
&Port=443
&Certificates.member.1.CertificateArn=arn:aws:acm::123456789012:server-certificate/my-
server-cert
&SslPolicy=ELBSecurityPolicy-2016-08
&DefaultActions.member.1.Type=forward
```

```
&DefaultActions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-tls-targets/b7fce90c666d892a
&Version=2015-12-01
&AUTHPARAMS
```

## Create a UDP listener

This example creates a UDP listener for the specified Network Load Balancer that forwards requests to the specified target group.

```
https://elasticloadbalancing.amazonaws.com/?Action/CreateListener
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/net/my-network-load-balancer/2d7b630a7815dda2
&Protocol=UDP
&Port=53
&DefaultActions.member.1.Type=forward
&DefaultActions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-udp-targets/b7fce90c666d892a
&Version=2015-12-01
&AUTHPARAMS
```

## Create a TCP\_UDP listener

This example creates a TCP\_UDP listener for the specified Network Load Balancer that forwards requests to the specified target group. The target group must use the TCP\_UDP protocol.

```
https://elasticloadbalancing.amazonaws.com/?Action/CreateListener
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/net/my-network-load-balancer/2d7b630a7815dda2
&Protocol=TCP_UDP
&Port=80
&DefaultActions.member.1.Type=forward
&DefaultActions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-tcp-udp-targets/b7fce90c666d892a
&Version=2015-12-01
&AUTHPARAMS
```

## Create a listener for your Gateway Load Balancer

This example creates a listener for the specified Gateway Load Balancer that forwards requests to the specified target group. You can't specify a port or protocol.

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateListener
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/gwy/
my-gateway-load-balancer/2d7b630a7815dda2
&DefaultActions.member.1.Type=forward
&DefaultActions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-appliance-targets/b7fce90c666d892a
&Version=2015-12-01
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# CreateLoadBalancer

Creates an Application Load Balancer, Network Load Balancer, or Gateway Load Balancer.

To create listeners for your load balancer, use [CreateListener](#). To describe your current load balancers, see [DescribeLoadBalancers](#). When you are finished with a load balancer, you can delete it using [DeleteLoadBalancer](#).

For more information, see the following:

- [Application Load Balancers](#)
- [Network Load Balancers](#)
- [Gateway Load Balancers](#)

This operation is idempotent, which means that it completes at most one time. If you attempt to create multiple load balancers with the same settings, each call succeeds.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### CustomerOwnedIpv4Pool

[Application Load Balancers on Outposts] The ID of the customer-owned address pool (CoIP pool).

Type: String

Length Constraints: Maximum length of 256.

Pattern: ^(ipv4pool-coip-)[a-zA-Z0-9]+\$

Required: No

### EnablePrefixForIpv6SourceNat

[Network Load Balancers with UDP listeners] Indicates whether to use an IPv6 prefix from each subnet for source NAT. The IP address type must be dualstack. The default value is off.

Type: String

Valid Values: on | off

Required: No

### **IpAddressType**

The IP address type. Internal load balancers must use `ipv4`.

[Application Load Balancers] The possible values are `ipv4` (IPv4 addresses), `dualstack` (IPv4 and IPv6 addresses), and `dualstack-without-public-ipv4` (public IPv6 addresses and private IPv4 and IPv6 addresses).

[Network Load Balancers and Gateway Load Balancers] The possible values are `ipv4` (IPv4 addresses) and `dualstack` (IPv4 and IPv6 addresses).

Type: String

Valid Values: `ipv4` | `dualstack` | `dualstack-without-public-ipv4`

Required: No

### **IpamPools**

[Application Load Balancers] The IPAM pools to use with the load balancer.

Type: [IpamPools](#) object

Required: No

### **Name**

The name of the load balancer.

This name must be unique per region per account, can have a maximum of 32 characters, must contain only alphanumeric characters or hyphens, must not begin or end with a hyphen, and must not begin with "internal-".

Type: String

Required: Yes

### **Scheme**

The nodes of an Internet-facing load balancer have public IP addresses. The DNS name of an Internet-facing load balancer is publicly resolvable to the public IP addresses of the nodes. Therefore, Internet-facing load balancers can route requests from clients over the internet.

The nodes of an internal load balancer have only private IP addresses. The DNS name of an internal load balancer is publicly resolvable to the private IP addresses of the nodes. Therefore, internal load balancers can route requests only from clients with access to the VPC for the load balancer.

The default is an Internet-facing load balancer.

You can't specify a scheme for a Gateway Load Balancer.

Type: String

Valid Values: internet-facing | internal

Required: No

### **SecurityGroups.member.N**

[Application Load Balancers and Network Load Balancers] The IDs of the security groups for the load balancer.

Type: Array of strings

Required: No

### **SubnetMappings.member.N**

The IDs of the subnets. You can specify only one subnet per Availability Zone. You must specify either subnets or subnet mappings, but not both.

[Application Load Balancers] You must specify subnets from at least two Availability Zones. You can't specify Elastic IP addresses for your subnets.

[Application Load Balancers on Outposts] You must specify one Outpost subnet.

[Application Load Balancers on Local Zones] You can specify subnets from one or more Local Zones.

[Network Load Balancers] You can specify subnets from one or more Availability Zones. You can specify one Elastic IP address per subnet if you need static IP addresses for your internet-facing load balancer. For internal load balancers, you can specify one private IP address per subnet from the IPv4 range of the subnet. For internet-facing load balancer, you can specify one IPv6 address per subnet.

[Gateway Load Balancers] You can specify subnets from one or more Availability Zones. You can't specify Elastic IP addresses for your subnets.

Type: Array of [SubnetMapping](#) objects

Required: No

### **Subnets.member.N**

The IDs of the subnets. You can specify only one subnet per Availability Zone. You must specify either subnets or subnet mappings, but not both. To specify an Elastic IP address, specify subnet mappings instead of subnets.

[Application Load Balancers] You must specify subnets from at least two Availability Zones.

[Application Load Balancers on Outposts] You must specify one Outpost subnet.

[Application Load Balancers on Local Zones] You can specify subnets from one or more Local Zones.

[Network Load Balancers and Gateway Load Balancers] You can specify subnets from one or more Availability Zones.

Type: Array of strings

Required: No

### **Tags.member.N**

The tags to assign to the load balancer.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item.

Required: No

### **Type**

The type of load balancer. The default is application.

Type: String

Valid Values: application | network | gateway

Required: No

## Response Elements

The following element is returned by the service.

### **LoadBalancers.member.N**

Information about the load balancer.

Type: Array of [LoadBalancer](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AllocationIdNotFound**

The specified allocation ID does not exist.

HTTP Status Code: 400

### **AvailabilityZoneNotSupported**

The specified Availability Zone is not supported.

HTTP Status Code: 400

### **DuplicateLoadBalancerName**

A load balancer with the specified name already exists.

HTTP Status Code: 400

### **DuplicateTagKeys**

A tag key was specified more than once.

HTTP Status Code: 400

### **InvalidConfigurationRequest**

The requested configuration is not valid.

HTTP Status Code: 400

### **InvalidScheme**

The requested scheme is not valid.

HTTP Status Code: 400

### **InvalidSecurityGroup**

The specified security group does not exist.

HTTP Status Code: 400

### **InvalidSubnet**

The specified subnet is out of available addresses.

HTTP Status Code: 400

### **OperationNotPermitted**

This operation is not allowed.

HTTP Status Code: 400

### **ResourceInUse**

A specified resource is in use.

HTTP Status Code: 400

### **SubnetNotFound**

The specified subnet does not exist.

HTTP Status Code: 400

### **TooManyLoadBalancers**

You've reached the limit on the number of load balancers for your Amazon account.

HTTP Status Code: 400

### **TooManyTags**

You've reached the limit on the number of tags for this resource.

HTTP Status Code: 400

## Examples

### Create an Internet-facing load balancer

This example creates an Internet-facing load balancer and enables the Availability Zones for the specified subnets.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateLoadBalancer  
&Name=my-load-balancer  
&Subnets.member.1=subnet-8360a9e7  
&Subnets.member.2=subnet-b7d581c0  
&Version=2015-12-01  
&AUTHPARAMS
```

#### Sample Response

```
<CreateLoadBalancerResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">  
  <CreateLoadBalancerResult>  
    <LoadBalancers>  
      <member>  
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/my-internal-load-balancer/50dc6c495c0c9188</LoadBalancerArn>  
        <Scheme>internet-facing</Scheme>  
        <LoadBalancerName>my-load-balancer</LoadBalancerName>  
        <VpcId>vpc-3ac0fb5f</VpcId>  
        <CanonicalHostedZoneId>Z2P70J7EXAMPLE</CanonicalHostedZoneId>  
        <CreatedTime>2016-03-25T21:29:48.850Z</CreatedTime>  
        <AvailabilityZones>  
          <member>  
            <SubnetId>subnet-8360a9e7</SubnetId>  
            <ZoneName>us-west-2a</ZoneName>  
          </member>  
          <member>  
            <SubnetId>subnet-b7d581c0</SubnetId>  
            <ZoneName>us-west-2b</ZoneName>  
          </member>  
        </AvailabilityZones>  
        <SecurityGroups>
```

```
<member>sg-5943793c</member>
</SecurityGroups>
<DNSName>my-load-balancer-424835706.us-west-2.elb.amazonaws.com</DNSName>
<State>
  <Code>provisioning</Code>
</State>
<Type>application</Type>
</member>
</LoadBalancers>
</CreateLoadBalancerResult>
<ResponseMetadata>
  <RequestId>32d531b2-f2d0-11e5-9192-3fff33344cfa</RequestId>
</ResponseMetadata>
</CreateLoadBalancerResponse>
```

## Create an internal load balancer

This example creates an internal load balancer and enables the Availability Zones for the specified subnets.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateLoadBalancer
&Name=my-internal-load-balancer
&Scheme=internal
&Subnets.member.1=subnet-8360a9e7
&Subnets.member.2=subnet-b7d581c0
&Version=2015-12-01
&AUTHPARAMS
```

### Sample Response

```
<CreateLoadBalancerResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
<CreateLoadBalancerResult>
  <LoadBalancers>
    <member>
      <LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-internal-load-balancer/5b49b8d4303115c2</
LoadBalancerArn>
      <Scheme>internal</Scheme>
      <LoadBalancerName>my-internal-load-balancer</LoadBalancerName>
```

```
<VpcId>vpc-3ac0fb5f</VpcId>
<CanonicalHostedZoneId>Z2P70J7EXAMPLE</CanonicalHostedZoneId>
<CreatedTime>2016-03-25T21:29:48.850Z</CreatedTime>
<AvailabilityZones>
  <member>
    <SubnetId>subnet-8360a9e7</SubnetId>
    <ZoneName>us-west-2a</ZoneName>
  </member>
  <member>
    <SubnetId>subnet-b7d581c0</SubnetId>
    <ZoneName>us-west-2b</ZoneName>
  </member>
</AvailabilityZones>
<SecurityGroups>
  <member>sg-5943793c</member>
</SecurityGroups>
<DNSName>internal-my-internal-load-balancer-1529930873.us-
west-2.elb.amazonaws.com</DNSName>
<State>
  <Code>provisioning</Code>
</State>
<Type>application</Type>
</member>
</LoadBalancers>
</CreateLoadBalancerResult>
<ResponseMetadata>
  <RequestId>b37b9c3e-f2d0-11e5-a53c-67205c0d10fd</RequestId>
</ResponseMetadata>
</CreateLoadBalancerResponse>
```

## Create a Network Load Balancer

This example creates a Network Load Balancer and associates an Elastic IP address with each of the specified subnets.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateLoadBalancer
&Name=my-network-load-balancer
&Type=network
&SubnetMappings.member.1.SubnetId=subnet-8360a9e7
&SubnetMappings.member.1.AllocationId=eipalloc-5723d13e
&SubnetMappings.member.2.SubnetId=subnet-b7d581c0
```

```
&SubnetMappings.member.2.AllocationId=eipalloc-fc5ca095  
&Version=2015-12-01  
&AUTHPARAMS
```

## Create a Gateway Load Balancer

This example creates a Gateway Load Balancer.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action/CreateLoadBalancer  
&Name=my-gateway-load-balancer  
&Type=gateway  
&Subnets.member.1.SubnetId=subnet-066877671789bd71b  
&Subnets.member.2.SubnetId=subnet-09ed24a70bc19bbe4  
&Version=2015-12-01  
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

## CreateRule

Creates a rule for the specified listener. The listener must be associated with an Application Load Balancer.

Each rule consists of a priority, one or more actions, and one or more conditions. Rules are evaluated in priority order, from the lowest value to the highest value. When the conditions for a rule are met, its actions are performed. If the conditions for no rules are met, the actions for the default rule are performed. For more information, see [Listener rules](#) in the *Application Load Balancers Guide*.

To view your current rules, use [DescribeRules](#). To update a rule, use [ModifyRule](#). To set the priorities of your rules, use [SetRulePriorities](#). To delete a rule, use [DeleteRule](#).

### Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

#### **Actions.member.N**

The actions.

Type: Array of [Action](#) objects

Required: Yes

#### **Conditions.member.N**

The conditions.

Type: Array of [RuleCondition](#) objects

Required: Yes

#### **ListenerArn**

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: Yes

#### **Priority**

The rule priority. A listener can't have multiple rules with the same priority.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50000.

Required: Yes

### Tags.member.N

The tags to assign to the rule.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item.

Required: No

## Response Elements

The following element is returned by the service.

### Rules.member.N

Information about the rule.

Type: Array of [Rule](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### IncompatibleProtocols

The specified configuration is not valid with this protocol.

HTTP Status Code: 400

### InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

### InvalidLoadBalancerAction

The requested action is not valid.

HTTP Status Code: 400

### **ListenerNotFound**

The specified listener does not exist.

HTTP Status Code: 400

### **PriorityInUse**

The specified priority is in use.

HTTP Status Code: 400

### **TargetGroupAssociationLimit**

You've reached the limit on the number of load balancers per target group.

HTTP Status Code: 400

### **TargetGroupNotFound**

The specified target group does not exist.

HTTP Status Code: 400

### **TooManyActions**

You've reached the limit on the number of actions per rule.

HTTP Status Code: 400

### **TooManyRegistrationsForTargetId**

You've reached the limit on the number of times a target can be registered with a load balancer.

HTTP Status Code: 400

### **TooManyRules**

You've reached the limit on the number of rules per load balancer.

HTTP Status Code: 400

### **TooManyTags**

You've reached the limit on the number of tags for this resource.

HTTP Status Code: 400

### TooManyTargetGroups

You've reached the limit on the number of target groups for your Amazon account.

HTTP Status Code: 400

### TooManyTargets

You've reached the limit on the number of targets.

HTTP Status Code: 400

### TooManyUniqueTargetGroupsPerLoadBalancer

You've reached the limit on the number of unique target groups per load balancer across all listeners. If a target group is used by multiple actions for a load balancer, it is counted as only one use.

HTTP Status Code: 400

### UnsupportedProtocol

The specified protocol is not supported.

HTTP Status Code: 400

## Examples

### Create a rule that forwards to a target group if a condition is met

This example creates a rule that forwards requests to the specified target group if the URL contains the specified pattern (for example, /img/\*).

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action/CreateRule
&ListenerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-load-
balancer/50dc6c495c0c9188/f2f7dc8efc522ab2
&Priority=10
&Conditions.member.1.Field=path-pattern
&Conditions.member.1.Values.member.1=/img/*
```

```
&Actions.member.1.Type=forward
&Actions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
&Version=2015-12-01
&AUTHPARAMS
```

## Sample Response

```
<CreateRuleResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <CreateRuleResult>
    <Rules>
      <member>
        <IsDefault>false</IsDefault>
        <Conditions>
          <member>
            <Field>path-pattern</Field>
            <Values>
              <member>/img/*</member>
            </Values>
          </member>
        </Conditions>
        <Priority>10</Priority>
        <Actions>
          <member>
            <Type>forward</Type>
            <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
          </member>
        </Actions>
        <RuleArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener-rule/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2/9683b2d02a6cabee</RuleArn>
      </member>
    </Rules>
  </CreateRuleResult>
  <ResponseMetadata>
    <RequestId>c5478c83-f397-11e5-bb98-57195a6eb84a</RequestId>
  </ResponseMetadata>
</CreateRuleResponse>
```

## Create a rule with a forward rule and an authenticate-oidc rule

This example creates a rule that first authenticates the user and then forwards the request if the user is authenticated.

## Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateRule
&ListenerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-load-
balancer/50dc6c495c0c9188/f2f7dc8efc522ab2
&Priority=10
&Actions.member.1.Type=authenticate-oidc
&Actions.member.1.AuthenticateOidcConfig.Issuer="https://idp-issuer.com"
&Actions.member.1.AuthenticateOidcConfig.AuthorizationEndpoint="https://authorization-
endpoint.com"
&Actions.member.1.AuthenticateOidcConfig.TokenEndpoint="https://token-endpoint.com"
&Actions.member.1.AuthenticateOidcConfig.UserInfoEndpoint="https://user-info-
endpoint.com"
&Actions.member.1.AuthenticateOidcConfig.ClientId="abcdefghijklmnopqrstuvwxyz123456789"
&Actions.member.1.AuthenticateOidcConfig.ClientSecret="123456789012345678901234567890"
&Actions.member.1.AuthenticateOidcConfig.SessionTimeout=3600
&Actions.member.1.AuthenticateOidcConfig.Scope="email"
&Actions.member.1.AuthenticateOidcConfig.OnUnauthenticatedRequest="authenticate"
&Actions.member.1.Order=1
&Actions.member.2.Type=forward
&Actions.member.2.TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
&Actions.member.2.Order=2
&Version=2015-12-01
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)

- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# CreateTargetGroup

Creates a target group.

To register targets with the target group, use [RegisterTargets](#). To update the health check settings for the target group, use [ModifyTargetGroup](#). To monitor the health of targets in the target group, use [DescribeTargetHealth](#).

To route traffic to the targets in a target group, specify the target group in an action using [CreateListener](#) or [CreateRule](#).

To delete a target group, use [DeleteTargetGroup](#).

For more information, see the following:

- [Target groups for your Application Load Balancers](#)
- [Target groups for your Network Load Balancers](#)
- [Target groups for your Gateway Load Balancers](#)

This operation is idempotent, which means that it completes at most one time. If you attempt to create multiple target groups with the same settings, each call succeeds.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### HealthCheckEnabled

Indicates whether health checks are enabled. If the target type is lambda, health checks are disabled by default but can be enabled. If the target type is instance, ip, or alb, health checks are always enabled and can't be disabled.

Type: Boolean

Required: No

### HealthCheckIntervalSeconds

The approximate amount of time, in seconds, between health checks of an individual target.

The range is 5-300. If the target group protocol is TCP, TLS, UDP, TCP\_UDP, HTTP or HTTPS, the

default is 30 seconds. If the target group protocol is GENEVE, the default is 10 seconds. If the target type is lambda, the default is 35 seconds.

Type: Integer

Valid Range: Minimum value of 5. Maximum value of 300.

Required: No

### **HealthCheckPath**

[HTTP/HTTPS health checks] The destination for health checks on the targets.

[HTTP1 or HTTP2 protocol version] The ping path. The default is /.

[GRPC protocol version] The path of a custom health check method with the format / package.service/method. The default is /Amazon.ALB/healthcheck.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

### **HealthCheckPort**

The port the load balancer uses when performing health checks on targets. If the protocol is HTTP, HTTPS, TCP, TLS, UDP, or TCP\_UDP, the default is traffic-port, which is the port on which each target receives traffic from the load balancer. If the protocol is GENEVE, the default is port 80.

Type: String

Required: No

### **HealthCheckProtocol**

The protocol the load balancer uses when performing health checks on targets. For Application Load Balancers, the default is HTTP. For Network Load Balancers and Gateway Load Balancers, the default is TCP. The TCP protocol is not supported for health checks if the protocol of the target group is HTTP or HTTPS. The GENEVE, TLS, UDP, and TCP\_UDP protocols are not supported for health checks.

Type: String

Valid Values: HTTP | HTTPS | TCP | TLS | UDP | TCP\_UDP | GENEVE

Required: No

### **HealthCheckTimeoutSeconds**

The amount of time, in seconds, during which no response from a target means a failed health check. The range is 2–120 seconds. For target groups with a protocol of HTTP, the default is 6 seconds. For target groups with a protocol of TCP, TLS or HTTPS, the default is 10 seconds. For target groups with a protocol of GENEVE, the default is 5 seconds. If the target type is lambda, the default is 30 seconds.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 120.

Required: No

### **HealthyThresholdCount**

The number of consecutive health check successes required before considering a target healthy. The range is 2–10. If the target group protocol is TCP, TCP\_UDP, UDP, TLS, HTTP or HTTPS, the default is 5. For target groups with a protocol of GENEVE, the default is 5. If the target type is lambda, the default is 5.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 10.

Required: No

### **IpAddressType**

The IP address type. The default value is `ipv4`.

Type: String

Valid Values: `ipv4` | `ipv6`

Required: No

### **Matcher**

[HTTP/HTTPS health checks] The HTTP or gRPC codes to use when checking for a successful response from a target. For target groups with a protocol of TCP, TCP\_UDP, UDP or TLS the

range is 200-599. For target groups with a protocol of HTTP or HTTPS, the range is 200-499.

For target groups with a protocol of GENEVE, the range is 200-399.

Type: [Matcher](#) object

Required: No

## Name

The name of the target group.

This name must be unique per region per account, can have a maximum of 32 characters, must contain only alphanumeric characters or hyphens, and must not begin or end with a hyphen.

Type: String

Required: Yes

## Port

The port on which the targets receive traffic. This port is used unless you specify a port override when registering the target. If the target is a Lambda function, this parameter does not apply. If the protocol is GENEVE, the supported port is 6081.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

## Protocol

The protocol to use for routing traffic to the targets. For Application Load Balancers, the supported protocols are HTTP and HTTPS. For Network Load Balancers, the supported protocols are TCP, TLS, UDP, or TCP\_UDP. For Gateway Load Balancers, the supported protocol is GENEVE. A TCP\_UDP listener must be associated with a TCP\_UDP target group. If the target is a Lambda function, this parameter does not apply.

Type: String

Valid Values: HTTP | HTTPS | TCP | TLS | UDP | TCP\_UDP | GENEVE

Required: No

## ProtocolVersion

[HTTP/HTTPS protocol] The protocol version. Specify GRPC to send requests to targets using gRPC. Specify HTTP2 to send requests to targets using HTTP/2. The default is HTTP1, which sends requests to targets using HTTP/1.1.

Type: String

Required: No

## Tags.member.N

The tags to assign to the target group.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item.

Required: No

## TargetType

The type of target that you must specify when registering targets with this target group. You can't specify targets for a target group using more than one target type.

- instance - Register targets by instance ID. This is the default value.
- ip - Register targets by IP address. You can specify IP addresses from the subnets of the virtual private cloud (VPC) for the target group, the RFC 1918 range (10.0.0.0/8, 172.16.0.0/12, and 192.168.0.0/16), and the RFC 6598 range (100.64.0.0/10). You can't specify publicly routable IP addresses.
- lambda - Register a single Lambda function as a target.
- alb - Register a single Application Load Balancer as a target.

Type: String

Valid Values: instance | ip | lambda | alb

Required: No

## UnhealthyThresholdCount

The number of consecutive health check failures required before considering a target unhealthy. The range is 2-10. If the target group protocol is TCP, TCP\_UDP, UDP, TLS, HTTP or HTTPS, the

default is 2. For target groups with a protocol of GENEVE, the default is 2. If the target type is lambda, the default is 5.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 10.

Required: No

### VpcId

The identifier of the virtual private cloud (VPC). If the target is a Lambda function, this parameter does not apply. Otherwise, this parameter is required.

Type: String

Required: No

## Response Elements

The following element is returned by the service.

### TargetGroups.member.N

Information about the target group.

Type: Array of [TargetGroup](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### DuplicateTargetGroupName

A target group with the specified name already exists.

HTTP Status Code: 400

### InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

## TooManyTags

You've reached the limit on the number of tags for this resource.

HTTP Status Code: 400

## TooManyTargetGroups

You've reached the limit on the number of target groups for your Amazon account.

HTTP Status Code: 400

## Examples

### Create a target group to route traffic to instances registered by instance ID

This example creates a target group for an Application Load Balancer that you can use to route traffic to instances using HTTP on port 80. You register the instances by instance ID. This target group uses the default health check settings.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateTargetGroup  
&Name=my-targets  
&Protocol=HTTP  
&Port=80  
&VpcId=vpc-3ac0fb5f  
&TargetType=instance  
&Version=2015-12-01  
&AUTHPARAMS
```

#### Sample Response

```
<CreateTargetGroupResponse xmlns="http://elasticloadbalancing.amazonaws.com/  
doc/2015-12-01/">  
  <CreateTargetGroupResult>  
    <TargetGroups>  
      <member>  
        <TargetGroupArn>arn:aws:elasticloadbalancing:us-  
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>  
        <HealthCheckTimeoutSeconds>5</HealthCheckTimeoutSeconds>
```

```
<HealthCheckPort>traffic-port</HealthCheckPort>
<Matcher>
  <HttpCode>200</HttpCode>
</Matcher>
<TargetGroupName>my-targets</TargetGroupName>
<HealthCheckProtocol>HTTP</HealthCheckProtocol>
<HealthCheckPath>/</HealthCheckPath>
<Protocol>HTTP</Protocol>
<Port>80</Port>
<VpcId>vpc-3ac0fb5f</VpcId>
<HealthyThresholdCount>5</HealthyThresholdCount>
<HealthCheckIntervalSeconds>30</HealthCheckIntervalSeconds>
<UnhealthyThresholdCount>2</UnhealthyThresholdCount>
</member>
</TargetGroups>
</CreateTargetGroupResult>
<ResponseMetadata>
  <RequestId>b83fe90e-f2d5-11e5-b95d-3b2c1831fc26</RequestId>
</ResponseMetadata>
</CreateTargetGroupResponse>
```

## Create a target group to route traffic to IP addresses

This example creates a target group for a Network Load Balancer that you can use to route traffic to IP addresses using TCP on port 80. This target group uses the default health check settings.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateTargetGroup
&Name=my-ip-targets
&Protocol=TCP
&Port=80
&VpcId=vpc-09e5e2c5ef7e38ae7
&TargetType=ip
&Version=2015-12-01
&AUTHPARAMS
```

## Create a target group to route traffic to a Lambda function

This example creates a target group for an Application Load Balancer that you can use to route traffic to a Lambda function. This target group uses the default health check settings. For more information, see [Lambda functions as targets](#) in the *Application Load Balancers Guide*.

## Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateTargetGroup  
&Name=my-lambda-target  
&TargetType=lambda  
&Version=2015-12-01  
&AUTHPARAMS
```

## Create a target group for your Gateway Load Balancer

This example creates a target group for a Gateway Load Balancer. The protocol must be GENEVE and the port must be 6081.

## Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=CreateTargetGroup  
&Name=my-appliance-targets  
&Protocol=GENEVE  
&Port=6081  
&VpcId=vpc-09e5e2c5ef7e38ae7  
&TargetType=ip  
&Version=2015-12-01  
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

# CreateTrustStore

Creates a trust store.

For more information, see [Mutual TLS for Application Load Balancers](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### CaCertificatesBundleS3Bucket

The Amazon S3 bucket for the ca certificates bundle.

Type: String

Required: Yes

### CaCertificatesBundleS3Key

The Amazon S3 path for the ca certificates bundle.

Type: String

Required: Yes

### CaCertificatesBundleS3ObjectVersion

The Amazon S3 object version for the ca certificates bundle. If undefined the current version is used.

Type: String

Required: No

### Name

The name of the trust store.

This name must be unique per region and can't be changed after creation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: ^([a-zA-Z0-9]+-)\*[a-zA-Z0-9]+\\$

Required: Yes

### Tags.member.N

The tags to assign to the trust store.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item.

Required: No

## Response Elements

The following element is returned by the service.

### TrustStores.member.N

Information about the trust store created.

Type: Array of [TrustStore](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### CaCertificatesBundleNotFound

The specified ca certificate bundle does not exist.

HTTP Status Code: 400

### DuplicateTagKeys

A tag key was specified more than once.

HTTP Status Code: 400

### DuplicateTrustStoreName

A trust store with the specified name already exists.

HTTP Status Code: 400

### InvalidCaCertificatesBundle

The specified ca certificate bundle is in an invalid format, or corrupt.

HTTP Status Code: 400

### TooManyTags

You've reached the limit on the number of tags for this resource.

HTTP Status Code: 400

### TooManyTrustStores

You've reached the limit on the number of trust stores for your Amazon account.

HTTP Status Code: 400

## Examples

### Create a trust store.

This example creates a trust store using the current version of the specified ca certificate bundle.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action/CreateTrustStore  
&Name=my-trust-store  
&CaCertificatesBundleS3Bucket=amzn-s3-demo-bucket  
&CaCertificatesBundleS3Key=CAcertBundle.pem  
&Version=2015-12-01  
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)

- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DeleteListener

Deletes the specified listener.

Alternatively, your listener is deleted when you delete the load balancer to which it is attached, using [DeleteLoadBalancer](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### ListenerArn

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

### ResourceInUse

A specified resource is in use.

HTTP Status Code: 400

## Examples

### Delete a listener

This example deletes the specified listener.

## Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DeleteListener  
&ListenerArn=arn:aws:elasticloadbalancing:ua-west-2:123456789012:listener/app/my-load-  
balancer/50dc6c495c0c9188/f2f7dc8efc522ab2  
&Version=2015-12-01  
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DeleteLoadBalancer

Deletes the specified Application Load Balancer, Network Load Balancer, or Gateway Load Balancer. Deleting a load balancer also deletes its listeners.

You can't delete a load balancer if deletion protection is enabled. If the load balancer does not exist or has already been deleted, the call succeeds.

Deleting a load balancer does not affect its registered targets. For example, your EC2 instances continue to run and are still registered to their target groups. If you no longer need these EC2 instances, you can stop or terminate them.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

### OperationNotPermitted

This operation is not allowed.

HTTP Status Code: 400

### ResourceInUse

A specified resource is in use.

HTTP Status Code: 400

## Examples

### Delete a load balancer

This example deletes the specified load balancer.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DeleteLoadBalancer  
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/  
my-load-balancer/50dc6c495c0c9188  
&Version=2015-12-01  
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

## DeleteRule

Deletes the specified rule.

You can't delete the default rule.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### RuleArn

The Amazon Resource Name (ARN) of the rule.

Type: String

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### OperationNotPermitted

This operation is not allowed.

HTTP Status Code: 400

### RuleNotFound

The specified rule does not exist.

HTTP Status Code: 400

## Examples

### Delete a rule

This example deletes the specified rule.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DeleteRule
```

```
&RuleArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener-rule/app/my-load-
balancer/50dc6c495c0c9188/f2f7dc8efc522ab2/1291d13826f405c3
&Version=2015-12-01
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DeleteSharedTrustStoreAssociation

Deletes a shared trust store association.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### ResourceArn

The Amazon Resource Name (ARN) of the resource.

Type: String

Required: Yes

### TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AssociationNotFound

The specified association does not exist.

HTTP Status Code: 400

### DeleteAssociationSameAccount

The specified association can't be within the same account.

HTTP Status Code: 400

### TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DeleteTargetGroup

Deletes the specified target group.

You can delete a target group if it is not referenced by any actions. Deleting a target group also deletes any associated health checks. Deleting a target group does not affect its registered targets. For example, any EC2 instances continue to run until you stop or terminate them.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ResourceInUse

A specified resource is in use.

HTTP Status Code: 400

## Examples

### Delete a target group

This example deletes the specified target group.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DeleteTargetGroup
```

```
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-
targets/73e2d6bc24d8a067
&Version=2015-12-01
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DeleteTrustStore

Deletes a trust store.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### TrustStoreInUse

The specified trust store is currently in use.

HTTP Status Code: 400

### TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

## Examples

### Delete a trust store.

This example deletes the specified trust store.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DeleteTrustStore
```

```
&TrustStoreArn=arn:aws:elasticloadbalancing:us-east-1:111122223333:truststore/my-trust-
store/3ym756xh7yj
&Version=2015-12-01
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DeregisterTargets

Deregisters the specified targets from the specified target group. After the targets are deregistered, they no longer receive traffic from the load balancer.

The load balancer stops sending requests to targets that are deregistering, but uses connection draining to ensure that in-flight traffic completes on the existing connections. This deregistration delay is configured by default but can be updated for each target group.

For more information, see the following:

- [Deregistration delay](#) in the *Application Load Balancers User Guide*
- [Deregistration delay](#) in the *Network Load Balancers User Guide*
- [Deregistration delay](#) in the *Gateway Load Balancers User Guide*

Note: If the specified target does not exist, the action returns successfully.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: Yes

### Targets.member.N

The targets. If you specified a port override when you registered a target, you must specify both the target ID and the port when you deregister it.

Type: Array of [TargetDescription](#) objects

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## InvalidTarget

The specified target does not exist, is not in the same VPC as the target group, or has an unsupported instance type.

HTTP Status Code: 400

## TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

## Examples

### Deregister an instance from a target group

This example deregisters the specified instance from the specified target group.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DeregisterTargets  
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-  
targets/73e2d6bc24d8a067  
&Targets.member.1.Id=i-0f76fade435676abd  
&Version=2015-12-01  
&AUTHPARAMS
```

### Deregister an IP address from a target group

This example deregisters the specified IP address from the specified target group.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DeregisterTargets  
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-  
targets/73e2d6bc24d8a067  
&Targets.member.1.Id=10.0.1.238  
&Version=2015-12-01  
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DescribeAccountLimits

Describes the current Elastic Load Balancing resource limits for your Amazon account.

For more information, see the following:

- [Quotas for your Application Load Balancers](#)
- [Quotas for your Network Load Balancers](#)
- [Quotas for your Gateway Load Balancers](#)

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

### PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

## Response Elements

The following elements are returned by the service.

### Limits.member.N

Information about the limits.

Type: Array of [Limit](#) objects

## NextMarker

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DescribeCapacityReservation

Describes the capacity reservation status for the specified load balancer.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

## Response Elements

The following elements are returned by the service.

### CapacityReservationState.member.N

The state of the capacity reservation.

Type: Array of [ZonalCapacityReservationState](#) objects

### DecreaseRequestsRemaining

The amount of daily capacity decreases remaining.

Type: Integer

### LastModifiedTime

The last time the capacity reservation was modified.

Type: Timestamp

### MinimumLoadBalancerCapacity

The requested minimum capacity reservation for the load balancer

Type: [MinimumLoadBalancerCapacity](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DescribeListenerAttributes

Describes the attributes for the specified listener.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### ListenerArn

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: Yes

## Response Elements

The following element is returned by the service.

### Attributes.member.N

Information about the listener attributes.

Type: Array of [ListenerAttribute](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

## Examples

### Describe listener attributes

This example describes the attributes of the specified listener.

## Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeListenerAttributes  
&ListenerArn=arn:aws:elasticloadbalancing:us-east-1:123456789012:listener/net/my-  
listener/73e2d6bc24d8a067/d5dc06411fa5bcea  
&Version=2015-12-01  
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DescribeListenerCertificates

Describes the default certificate and the certificate list for the specified HTTPS or TLS listener.

If the default certificate is also in the certificate list, it appears twice in the results (once with `IsDefault` set to true and once with `IsDefault` set to false).

For more information, see [SSL certificates](#) in the *Application Load Balancers Guide* or [Server certificates](#) in the *Network Load Balancers Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### ListenerArn

The Amazon Resource Names (ARN) of the listener.

Type: String

Required: Yes

### Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

### PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

## Response Elements

The following elements are returned by the service.

## Certificates.member.N

Information about the certificates.

Type: Array of [Certificate](#) objects

## NextMarker

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

## Examples

### Describe the certificate list for a listener

This example describes the certificate list for the specified listener.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeListenerCertificates
&ListenerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-load-
balancer/50dc6c495c0c9188/f2f7dc8efc522ab2
&Version=2015-12-01
&AUTHPARAMS
```

#### Sample Response

```
<DescribeListenerCertificatesResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
```

```
<DescribeListenerCertificatesResult>
  <Certificates>
    <member>
      <CertificateArn>arn:aws:acm:us-
west-2:123456789012:certificate/1bf70a25-6914-495a-92f8-e27feEXAMPLE</CertificateArn>
        <IsDefault>true</IsDefault>
    </member>
    <member>
      <CertificateArn>arn:aws:acm:us-
west-2:123456789012:certificate/68c11a12-39de-44dd-b329-fe64aEXAMPLE</CertificateArn>
        <IsDefault>false</IsDefault>
    </member>
    <member>
      <CertificateArn>arn:aws:acm:us-
west-2:123456789012:certificate/1bf70a25-6914-495a-92f8-e27feEXAMPLE</CertificateArn>
        <IsDefault>false</IsDefault>
    </member>
  </Certificates>
</DescribeListenerCertificatesResult>
<ResponseMetadata>
  <RequestId>18e470d3-f39c-11e5-a53c-67205c0d10fd</RequestId>
</ResponseMetadata>
</DescribeListenerCertificatesResponse>
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)



# DescribeListeners

Describes the specified listeners or the listeners for the specified Application Load Balancer, Network Load Balancer, or Gateway Load Balancer. You must specify either a load balancer or one or more listeners.

For an HTTPS or TLS listener, the output includes the default certificate for the listener. To describe the certificate list for the listener, use [DescribeListenerCertificates](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### ListenerArns.member.N

The Amazon Resource Names (ARN) of the listeners.

Type: Array of strings

Required: No

### LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: No

### Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

### PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

## Response Elements

The following elements are returned by the service.

### **Listeners.member.N**

Information about the listeners.

Type: Array of [Listener](#) objects

### **NextMarker**

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ListenerNotFound**

The specified listener does not exist.

HTTP Status Code: 400

### **LoadBalancerNotFound**

The specified load balancer does not exist.

HTTP Status Code: 400

### **UnsupportedProtocol**

The specified protocol is not supported.

HTTP Status Code: 400

# Examples

## Describe an HTTP listener

This example describes the specified HTTP listener.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeListeners
&ListenerArns.member.1=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/
app/my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2
&Version=2015-12-01
&AUTHPARAMS
```

### Sample Response

```
<DescribeListenersResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <DescribeListenersResult>
    <Listeners>
      <member>
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</
LoadBalancerArn>
        <Protocol>HTTP</Protocol>
        <Port>80</Port>
        <ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2</ListenerArn>
        <DefaultActions>
          <member>
            <Type>forward</Type>
            <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
          </member>
        </DefaultActions>
      </member>
    </Listeners>
  </DescribeListenersResult>
  <ResponseMetadata>
    <RequestId>18e470d3-f39c-11e5-a53c-67205c0d10fd</RequestId>
  </ResponseMetadata>
</DescribeListenersResponse>
```

## Describe an HTTPS listener

This example describes the specified HTTPS listener.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeListeners
&ListenerArns.member.1=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/
app/my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2
&Version=2015-12-01
&AUTHPARAMS
```

### Sample Response

```
<DescribeListenersResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <DescribeListenersResult>
    <Listeners>
      <member>
        <Port>443</Port>
        <Protocol>HTTPS</Protocol>
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</
LoadBalancerArn>
        <ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2</ListenerArn>
        <DefaultActions>
          <member>
            <Type>forward</Type>
            <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
          </member>
        </DefaultActions>
        <SslPolicy>ELBSecurityPolicy-2016-08</SslPolicy>
        <Certificates>
          <member>
            <CertificateArn>arn:aws:acm:us-
west-2:123456789012:certificate/68c11a12-39de-44dd-b329-fe64aEXAMPLE</CertificateArn>
          </member>
        </Certificates>
      </member>
    </Listeners>
  </DescribeListenersResult>
```

```
<ResponseMetadata>
  <RequestId>18e470d3-f39c-11e5-a53c-67205c0d10fd</RequestId>
</ResponseMetadata>
</DescribeListenersResponse>
```

## Describe the listeners for a load balancer

This example describe the listeners for the specified load balancer.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeListeners
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-
load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2
&Version=2015-12-01
&AUTHPARAMS
```

### Sample Response

```
<DescribeLoadBalancersResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <DescribeListenersResult>
    <Listeners>
      <member>
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</
LoadBalancerArn>
        <Protocol>HTTPS</Protocol>
        <Certificates>
          <member>
            <CertificateArn>arn:aws:iam::123456789012:server-certificate/my-server-
cert</CertificateArn>
          </member>
        </Certificates>
        <Port>443</Port>
        <SslPolicy>ELBSecurityPolicy-2016-08</SslPolicy>
        <ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/
my-load-balancer/50dc6c495c0c9188/0467ef3c8400ae65</ListenerArn>
        <DefaultActions>
          <member>
            <Type>forward</Type>
            <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
```

```
</member>
</DefaultActions>
</member>
<member>
  <LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</
LoadBalancerArn>
  <Protocol>HTTP</Protocol>
  <Port>80</Port>
  <ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2</ListenerArn>
  <DefaultActions>
    <member>
      <Type>forward</Type>
      <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
    </member>
  </DefaultActions>
</member>
</Listeners>
</DescribeListenersResult>
<ResponseMetadata>
  <RequestId>65a3a7ea-f39c-11e5-b543-9f2c3fbb9bee</RequestId>
</ResponseMetadata>
</DescribeLoadBalancersResponse>
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)

- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DescribeLoadBalancerAttributes

Describes the attributes for the specified Application Load Balancer, Network Load Balancer, or Gateway Load Balancer.

For more information, see the following:

- [Load balancer attributes](#) in the *Application Load Balancers Guide*
- [Load balancer attributes](#) in the *Network Load Balancers Guide*
- [Load balancer attributes](#) in the *Gateway Load Balancers Guide*

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

## Response Elements

The following element is returned by the service.

### Attributes.member.N

Information about the load balancer attributes.

Type: Array of [LoadBalancerAttribute](#) objects

Array Members: Maximum number of 20 items.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

## Examples

### Describe load balancer attributes

This example describes the attributes of the specified load balancer.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeLoadBalancerAttributes
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
&Version=2015-12-01
&AUTHPARAMS
```

#### Sample Response

```
<DescribeLoadBalancerAttributesResponse xmlns="http://
elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
<DescribeLoadBalancerAttributesResult>
<Attributes>
<member>
<Value>false</Value>
<Key>access_logs.s3.enabled</Key>
</member>
<member>
<Value>60</Value>
<Key>idle_timeout.timeout_seconds</Key>
</member>
<member>
<Value />
<Key>access_logs.s3.prefix</Key>
</member>
<member>
<Value>false</Value>
<Key>deletion_protection.enabled</Key>
</member>
```

```
<member>
  <Value />
  <Key>access_logs.s3.bucket</Key>
</member>
</Attributes>
</DescribeLoadBalancerAttributesResult>
<ResponseMetadata>
  <RequestId>1528a9a4-f38e-11e5-8ead-f1e91be31786</RequestId>
</ResponseMetadata>
</DescribeLoadBalancerAttributesResponse>
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DescribeLoadBalancers

Describes the specified load balancers or all of your load balancers.

To describe the listeners for a load balancer, use [DescribeListeners](#). To describe the attributes for a load balancer, use [DescribeLoadBalancerAttributes](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### LoadBalancerArns.member.N

The Amazon Resource Names (ARN) of the load balancers. You can specify up to 20 load balancers in a single call.

Type: Array of strings

Required: No

### Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

### Names.member.N

The names of the load balancers.

Type: Array of strings

Required: No

### PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

## Response Elements

The following elements are returned by the service.

### **LoadBalancers.member.N**

Information about the load balancers.

Type: Array of [LoadBalancer](#) objects

### **NextMarker**

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **LoadBalancerNotFound**

The specified load balancer does not exist.

HTTP Status Code: 400

## Examples

### **Describe a load balancer**

This example describes the specified load balancer.

#### **Sample Request**

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeLoadBalancers
&LoadBalancerArns.member.1=arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188
```

&amp;Version=2015-12-01

&amp;AUTHPARAMS

## Sample Response

```
<DescribeLoadBalancersResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <DescribeLoadBalancersResult>
    <LoadBalancers>
      <member>
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</LoadBalancerArn>
        <Scheme>internet-facing</Scheme>
        <LoadBalancerName>my-load-balancer</LoadBalancerName>
        <VpcId>vpc-3ac0fb5f</VpcId>
        <CanonicalHostedZoneId>Z2P70J7EXAMPLE</CanonicalHostedZoneId>
        <CreatedTime>2016-03-25T21:26:12.920Z</CreatedTime>
        <AvailabilityZones>
          <member>
            <SubnetId>subnet-8360a9e7</SubnetId>
            <ZoneName>us-west-2a</ZoneName>
          </member>
          <member>
            <SubnetId>subnet-b7d581c0</SubnetId>
            <ZoneName>us-west-2b</ZoneName>
          </member>
        </AvailabilityZones>
        <SecurityGroups>
          <member>sg-5943793c</member>
        </SecurityGroups>
        <DNSName>my-load-balancer-424835706.us-west-2.elb.amazonaws.com</DNSName>
        <State>
          <Code>active</Code>
        </State>
        <Type>application</Type>
      </member>
    </LoadBalancers>
  </DescribeLoadBalancersResult>
  <ResponseMetadata>
    <RequestId>6581c0ac-f39f-11e5-bb98-57195a6eb84a</RequestId>
  </ResponseMetadata>
</DescribeLoadBalancersResponse>
```

## Describe all load balancers

This example describes all of your load balancers.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeLoadBalancers  
&Version=2015-12-01  
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

## DescribeRules

Describes the specified rules or the rules for the specified listener. You must specify either a listener or one or more rules.

### Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

#### ListenerArn

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: No

#### Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

#### PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

#### RuleArns.member.N

The Amazon Resource Names (ARN) of the rules.

Type: Array of strings

Required: No

### Response Elements

The following elements are returned by the service.

## NextMarker

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

## Rules.member.N

Information about the rules.

Type: Array of [Rule](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

### RuleNotFound

The specified rule does not exist.

HTTP Status Code: 400

### UnsupportedProtocol

The specified protocol is not supported.

HTTP Status Code: 400

## Examples

### Describe a rule

This example describes the specified rule.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeRules
```

```
&RuleArns.member.1=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener-rule/
app/my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2/9683b2d02a6cabee
&Version=2015-12-01
&AUTHPARAMS
```

## Sample Response

```
<DescribeRulesResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <DescribeRulesResult>
    <Rules>
      <member>
        <IsDefault>false</IsDefault>
        <Conditions>
          <member>
            <Field>path-pattern</Field>
            <Values>
              <member>/img/*</member>
            </Values>
          </member>
        </Conditions>
        <Priority>10</Priority>
        <Actions>
          <member>
            <Type>forward</Type>
            <TargetGroupArn>arn:aws:elasticloadbalancing:ua-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
          </member>
        </Actions>
        <RuleArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener-rule/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2/9683b2d02a6cabee</RuleArn>
      </member>
    </Rules>
  </DescribeRulesResult>
  <ResponseMetadata>
    <RequestId>74926cf3-f3a3-11e5-b543-9f2c3fb9bee</RequestId>
  </ResponseMetadata>
</DescribeRulesResponse>
```

## Describe the rules for a listener

This example describes the rules for the specified listener. The output includes the default rule and any other rules that you've defined.

## Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeRules
&ListenerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-load-
balancer/50dc6c495c0c9188/f2f7dc8efc522ab2
&Version=2015-12-01
&AUTHPARAMS
```

## Sample Response

```
<DescribeRulesResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
<DescribeRulesResult>
  <Rules>
    <member>
      <IsDefault>false</IsDefault>
      <Conditions>
        <member>
          <Field>path-pattern</Field>
          <Values>
            <member>/img/*</member>
          </Values>
        </member>
      </Conditions>
      <Priority>10</Priority>
      <Actions>
        <member>
          <Type>forward</Type>
          <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
        </member>
      </Actions>
      <RuleArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener-rule/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2/9683b2d02a6cabee</RuleArn>
    </member>
    <member>
      <IsDefault>true</IsDefault>
      <Conditions />
      <Priority>default</Priority>
      <Actions>
        <member>
          <Type>forward</Type>
```

```
<TargetGroupArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
</member>
</Actions>
<RuleArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener-rule/app/my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2/fd906cf3d7a9d36d</RuleArn>
</member>
</Rules>
</DescribeRulesResult>
<ResponseMetadata>
<RequestId>d8581c8d-f3a3-11e5-8a24-ffe2bf8623ae</RequestId>
</ResponseMetadata>
</DescribeRulesResponse>
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DescribeSSL Policies

Describes the specified policies or all policies used for SSL negotiation.

For more information, see [Security policies](#) in the *Application Load Balancers Guide* and [Security policies](#) in the *Network Load Balancers Guide*.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### LoadBalancerType

The type of load balancer. The default lists the SSL policies for all load balancers.

Type: String

Valid Values: application | network | gateway

Required: No

### Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

### Names.member.N

The names of the policies.

Type: Array of strings

Required: No

### PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

## Response Elements

The following elements are returned by the service.

### NextMarker

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

### SslPolicies.member.N

Information about the security policies.

Type: Array of [SslPolicy](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### SSLPolicyNotFound

The specified SSL policy does not exist.

HTTP Status Code: 400

## Examples

### Describe the specified policy used for SSL negotiation

This example describes the specified policy used for SSL negotiation.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeSSLPolicies
&Names.member.1=ELBSecurityPolicy-2016-08
&Version=2015-12-01
&AUTHPARAMS
```

## Sample Response

```
<DescribeSSLPoliciesResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <DescribeSSLPoliciesResult>
    <SslPolicies>
      <member>
        <Ciphers>
          <member>
            <Name>ECDHE-ECDSA-AES128-GCM-SHA256</Name>
            <Priority>1</Priority>
          </member>
          <member>
            <Name>ECDHE-RSA-AES128-GCM-SHA256</Name>
            <Priority>2</Priority>
          </member>
          <member>
            <Name>ECDHE-ECDSA-AES128-SHA256</Name>
            <Priority>3</Priority>
          </member>
          ...
          <member>
            <Name>AES256-SHA</Name>
            <Priority>19</Priority>
          </member>
        </Ciphers>
        <Name>ELBSecurityPolicy-2016-08</Name>
        <SslProtocols>
          <member>TLSv1</member>
          <member>TLSv1.1</member>
          <member>TLSv1.2</member>
        </SslProtocols>
      </member>
    </SslPolicies>
  </DescribeSSLPoliciesResult>
  <ResponseMetadata>
    <RequestId>a78c9aee-f2aa-11e5-8a24-ffe2bf8623ae</RequestId>
  </ResponseMetadata>
</DescribeSSLPoliciesResponse>
```

## Describe all policies used for SSL negotiation

This example describes all the policies that you can use for SSL negotiation.

## Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeSSLPolicies  
&Version=2015-12-01  
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

## DescribeTags

Describes the tags for the specified Elastic Load Balancing resources. You can describe the tags for one or more Application Load Balancers, Network Load Balancers, Gateway Load Balancers, target groups, listeners, or rules.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### ResourceArns.member.N

The Amazon Resource Names (ARN) of the resources. You can specify up to 20 resources in a single call.

Type: Array of strings

Required: Yes

## Response Elements

The following element is returned by the service.

### TagDescriptions.member.N

Information about the tags.

Type: Array of [TagDescription](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

### LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

### RuleNotFound

The specified rule does not exist.

HTTP Status Code: 400

### TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

### TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

## Examples

### Describe the tags assigned to a load balancer

This example describes the tags assigned to the specified load balancer.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTags  
&ResourceArns.member.1=arn:aws:elasticloadbalancing:us-  
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188  
&Version=2015-12-01  
&AUTHPARAMS
```

#### Sample Response

```
<DescribeTagsResponse xmlns="http://elasticloadbalancing.amazonaws.com/  
doc/2015-12-01/">  
  <DescribeTagsResult>  
    <TagDescriptions>  
      <member>  
        <ResourceArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/  
app/my-load-balancer/50dc6c495c0c9188</ResourceArn>
```

```
<Tags>
  <member>
    <Value>lima</Value>
    <Key>project</Key>
  </member>
  <member>
    <Value>digital-media</Value>
    <Key>department</Key>
  </member>
</Tags>
</member>
</TagDescriptions>
</DescribeTagsResult>
<ResponseMetadata>
  <RequestId>34f144db-f2d9-11e5-a53c-67205c0d10fd</RequestId>
</ResponseMetadata>
</DescribeTagsResponse>
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DescribeTargetGroupAttributes

Describes the attributes for the specified target group.

For more information, see the following:

- [Target group attributes](#) in the *Application Load Balancers Guide*
- [Target group attributes](#) in the *Network Load Balancers Guide*
- [Target group attributes](#) in the *Gateway Load Balancers Guide*

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: Yes

## Response Elements

The following element is returned by the service.

### Attributes.member.N

Information about the target group attributes

Type: Array of [TargetGroupAttribute](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

## Examples

### Describe target group attributes

This example describes the attributes of the specified target group.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTargetGroupAttributes
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-
targets/73e2d6bc24d8a067
&Version=2015-12-01
&AUTHPARAMS
```

#### Sample Response

```
<DescribeTargetGroupAttributesResponse xmlns="http://
elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
<DescribeTargetGroupAttributesResult>
<Attributes>
<member>
<Value>300</Value>
<Key>deregistration_delay.timeout_seconds</Key>
</member>
</Attributes>
</DescribeTargetGroupAttributesResult>
<ResponseMetadata>
<RequestId>54618294-f3a8-11e5-bb98-57195a6eb84a</RequestId>
</ResponseMetadata>
</DescribeTargetGroupAttributesResponse>
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)

- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DescribeTargetGroups

Describes the specified target groups or all of your target groups. By default, all target groups are described. Alternatively, you can specify one of the following to filter the results: the ARN of the load balancer, the names of one or more target groups, or the ARNs of one or more target groups.

To describe the targets for a target group, use [DescribeTargetHealth](#). To describe the attributes of a target group, use [DescribeTargetGroupAttributes](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: No

### Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

### Names.member.N

The names of the target groups.

Type: Array of strings

Required: No

### PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

### **TargetGroupArns.member.N**

The Amazon Resource Names (ARN) of the target groups.

Type: Array of strings

Required: No

## **Response Elements**

The following elements are returned by the service.

### **NextMarker**

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

### **TargetGroups.member.N**

Information about the target groups.

Type: Array of [TargetGroup](#) objects

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **LoadBalancerNotFound**

The specified load balancer does not exist.

HTTP Status Code: 400

### **TargetGroupNotFound**

The specified target group does not exist.

HTTP Status Code: 400

# Examples

## Describe a target group

This example describes the specified target group.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTargetGroups
&TargetGroupArns.member.1=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067
&Version=2015-12-01
&AUTHPARAMS
```

### Sample Response

```
<DescribeTargetGroupsResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
<DescribeTargetGroupsResult>
  <TargetGroups>
    <member>
      <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
      <HealthCheckTimeoutSeconds>5</HealthCheckTimeoutSeconds>
      <HealthCheckPort>traffic-port</HealthCheckPort>
      <Matcher>
        <HttpCode>200</HttpCode>
      </Matcher>
      <TargetGroupName>my-targets</TargetGroupName>
      <HealthCheckProtocol>HTTP</HealthCheckProtocol>
      <HealthCheckPath>/</HealthCheckPath>
      <Protocol>HTTP</Protocol>
      <Port>80</Port>
      <VpcId>vpc-3ac0fb5f</VpcId>
      <HealthyThresholdCount>5</HealthyThresholdCount>
      <HealthCheckIntervalSeconds>30</HealthCheckIntervalSeconds>
      <LoadBalancerArns>
        <member>arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188</member>
      </LoadBalancerArns>
      <UnhealthyThresholdCount>2</UnhealthyThresholdCount>
    </member>
  </TargetGroups>
</DescribeTargetGroupsResult>
</DescribeTargetGroupsResponse>
```

```
</DescribeTargetGroupsResult>
<ResponseMetadata>
    <RequestId>70092c0e-f3a9-11e5-ae48-cff02092876b</RequestId>
</ResponseMetadata>
</DescribeTargetGroupsResponse>
```

## Describe all target groups for a load balancer

This example describes all target groups for the specified load balancer.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTargetGroups
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
&Version=2015-12-01
&AUTHPARAMS
```

## Describe all target groups

This example describes all of your target groups.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTargetGroups
&Version=2015-12-01
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DescribeTargetHealth

Describes the health of the specified targets or all of your targets.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### Include.member.N

Used to include anomaly detection information.

Type: Array of strings

Valid Values: AnomalyDetection | All

Required: No

### TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: Yes

### Targets.member.N

The targets.

Type: Array of [TargetDescription](#) objects

Required: No

## Response Elements

The following element is returned by the service.

### TargetHealthDescriptions.member.N

Information about the health of the targets.

Type: Array of [TargetHealthDescription](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### HealthUnavailable

The health of the specified targets could not be retrieved due to an internal error.

HTTP Status Code: 500

### InvalidTarget

The specified target does not exist, is not in the same VPC as the target group, or has an unsupported instance type.

HTTP Status Code: 400

### TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

## Examples

### Describe the health of the targets for a target group

This example describes the health of the targets for the specified target group. These targets are healthy.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTargetHealth  
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-  
targets/73e2d6bc24d8a067  
&Version=2015-12-01  
&AUTHPARAMS
```

#### Sample Response

```
<DescribeTargetHealthResponse xmlns="http://elasticloadbalancing.amazonaws.com/  
doc/2015-12-01/">
```

```
<DescribeTargetHealthResult>
  <TargetHealthDescriptions>
    <member>
      <HealthCheckPort>80</HealthCheckPort>
      <TargetHealth>
        <State>healthy</State>
      </TargetHealth>
      <Target>
        <Port>80</Port>
        <Id>i-0f76fade</Id>
      </Target>
    </member>
    <member>
      <HealthCheckPort>80</HealthCheckPort>
      <TargetHealth>
        <State>healthy</State>
      </TargetHealth>
      <Target>
        <Port>80</Port>
        <Id>i-0f76fade</Id>
      </Target>
    </member>
  </TargetHealthDescriptions>
</DescribeTargetHealthResult>
<ResponseMetadata>
  <RequestId>c534f810-f389-11e5-9192-3fff33344cfa</RequestId>
</ResponseMetadata>
</DescribeTargetHealthResponse>
```

## Describe the health of the specified target

This example describes the health of the specified target. This target is healthy.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTargetHealth
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-
targets/73e2d6bc24d8a067
&Targets.member.1.Id=i-0f76fade
&Targets.member.1.Port=80
&Version=2015-12-01
&AUTHPARAMS
```

## Sample Response

```
<DescribeTargetHealthResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <DescribeTargetHealthResult>
    <TargetHealthDescriptions>
      <member>
        <HealthCheckPort>80</HealthCheckPort>
        <TargetHealth>
          <State>healthy</State>
        </TargetHealth>
        <Target>
          <Port>80</Port>
          <Id>i-0f76fade</Id>
        </Target>
      </member>
    </TargetHealthDescriptions>
  </DescribeTargetHealthResult>
  <ResponseMetadata>
    <RequestId>c534f810-f389-11e5-9192-3fff33344cfa</RequestId>
  </ResponseMetadata>
</DescribeTargetHealthResponse>
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)



# DescribeTrustStoreAssociations

Describes all resources associated with the specified trust store.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

### PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

### TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

## Response Elements

The following elements are returned by the service.

### NextMarker

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

### TrustStoreAssociations.member.N

Information about the resources the trust store is associated to.

Type: Array of [TrustStoreAssociation](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

## Examples

### Describe all resources associated with a trust store.

This example describes all resources associated to the specified trust store.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTrustStoreAssociations  
&TrustStoreArn=arn:aws:elasticloadbalancing:us-east-1:111122223333:truststore/my-trust-  
store/3ym756xh7yj  
&Version=2015-12-01  
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)

- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DescribeTrustStoreRevocations

Describes the revocation files in use by the specified trust store or revocation files.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

### PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

### RevocationIds.member.N

The revocation IDs of the revocation files you want to describe.

Type: Array of longs

Required: No

### TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

## Response Elements

The following elements are returned by the service.

## NextMarker

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

## TrustStoreRevocations.member.N

Information about the revocation file in the trust store.

Type: Array of [DescribeTrustStoreRevocation](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### RevocationIdNotFound

The specified revocation ID does not exist.

HTTP Status Code: 400

### TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

## Examples

### Describe revocation file contents from a trust store.

This example describes the specified certificate revocation IDs list contents from the specified trust store.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTrustStoreRevocations
&TrustStoreArn=arn:aws:elasticloadbalancing:us-east-1:111122223333:truststore/my-trust-
store/3ym756xh7yj
&RevocationIds.member.1.RevocationId=1
```

&Version=2015-12-01

&AUTHPARAMS

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# DescribeTrustStores

Describes all trust stores for the specified account.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### Marker

The marker for the next set of results. (You received this marker from a previous call.)

Type: String

Required: No

### Names.member.N

The names of the trust stores.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: ^([a-zA-Z0-9]+-)\*[a-zA-Z0-9]+\\$

Required: No

### PageSize

The maximum number of results to return with this call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 400.

Required: No

### TrustStoreArns.member.N

The Amazon Resource Name (ARN) of the trust store.

Type: Array of strings

Required: No

## Response Elements

The following elements are returned by the service.

### NextMarker

If there are additional results, this is the marker for the next set of results. Otherwise, this is null.

Type: String

### TrustStores.member.N

Information about the trust stores.

Type: Array of [TrustStore](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

## Examples

### Describe a trust store.

This example describes the specified trust store.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=DescribeTrustStores
&TrustStoreArns.member.1.TrustStoreArn=arn:aws:elasticloadbalancing:us-
east-1:111122223333:truststore/my-trust-store/3ym756xh7yj
&Version=2015-12-01
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetResourcePolicy

Retrieves the resource policy for a specified resource.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### ResourceArn

The Amazon Resource Name (ARN) of the resource.

Type: String

Required: Yes

## Response Elements

The following element is returned by the service.

### Policy

The content of the resource policy.

Type: String

Length Constraints: Minimum length of 1.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ResourceNotFound

The specified resource does not exist.

HTTP Status Code: 400

## Examples

### Retrieve a resource policy

This example retrieves the resource policy for the specified trust store.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=GetResourcePolicy  
&ResourceArn=arn:aws:elasticloadbalancing:us-east-1:123456789012:truststore/my-trust-  
store/73e2d6bc24d8a067  
&Version=2015-12-01  
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetTrustStoreCaCertificatesBundle

Retrieves the ca certificate bundle.

This action returns a pre-signed S3 URI which is active for ten minutes.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

## Response Elements

The following element is returned by the service.

### Location

The ca certificate bundles Amazon S3 URI.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# GetTrustStoreRevocationContent

Retrieves the specified revocation file.

This action returns a pre-signed S3 URI which is active for ten minutes.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### RevocationId

The revocation ID of the revocation file.

Type: Long

Required: Yes

### TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

## Response Elements

The following element is returned by the service.

### Location

The revocation files Amazon S3 URI.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### RevocationIdNotFound

The specified revocation ID does not exist.

HTTP Status Code: 400

## TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

## Examples

### Retrieve a certificate revocation list.

This example retrieves the specified certificate revocation IDs list contents from the specified trust store and provides a pre-signed S3 URI.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=GetTrustStoreRevocationContent  
&TrustStoreArn=arn:aws:elasticloadbalancing:us-east-1:111122223333:truststore/my-trust-  
store/3ym756xh7yj  
&RevocationId=1  
&Version=2015-12-01  
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

# ModifyCapacityReservation

Modifies the capacity reservation of the specified load balancer.

When modifying capacity reservation, you must include at least one MinimumLoadBalancerCapacity or ResetCapacityReservation.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

### MinimumLoadBalancerCapacity

The minimum load balancer capacity reserved.

Type: [MinimumLoadBalancerCapacity](#) object

Required: No

### ResetCapacityReservation

Resets the capacity reservation.

Type: Boolean

Required: No

## Response Elements

The following elements are returned by the service.

### CapacityReservationState.member.N

The state of the capacity reservation.

Type: Array of [ZonalCapacityReservationState](#) objects

### DecreaseRequestsRemaining

The amount of daily capacity decreases remaining.

Type: Integer

### LastModifiedTime

The last time the capacity reservation was modified.

Type: Timestamp

### MinimumLoadBalancerCapacity

The requested minimum capacity reservation for the load balancer

Type: [MinimumLoadBalancerCapacity](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### CapacityDecreaseRequestLimitExceeded

You've exceeded the daily capacity decrease limit for this reservation.

HTTP Status Code: 400

### CapacityReservationPending

There is a pending capacity reservation.

HTTP Status Code: 400

### CapacityUnitsLimitExceeded

You've exceeded the capacity units limit.

HTTP Status Code: 400

### InsufficientCapacity

There is insufficient capacity to reserve.

HTTP Status Code: 500

## InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

## LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

## OperationNotPermitted

This operation is not allowed.

HTTP Status Code: 400

## PriorRequestNotComplete

This operation is not allowed while a prior request has not been completed.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# ModifyIpPools

[Application Load Balancers] Modify the IP pool associated to a load balancer.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### IpamPools

The IPAM pools to be modified.

Type: [IpamPools](#) object

Required: No

### LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

### RemovelpamPools.member.N

Remove the IP pools in use by the load balancer.

Type: Array of strings

Valid Values: ipv4

Required: No

## Response Elements

The following element is returned by the service.

### IpamPools

The IPAM pool ID.

Type: [IpamPools](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# ModifyListener

Replaces the specified properties of the specified listener. Any properties that you do not specify remain unchanged.

Changing the protocol from HTTPS to HTTP, or from TLS to TCP, removes the security policy and default certificate properties. If you change the protocol from HTTP to HTTPS, or from TCP to TLS, you must add the security policy and default certificate properties.

To add an item to a list, remove an item from a list, or update an item in a list, you must provide the entire list. For example, to add an action, specify a list with the current actions plus the new action.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### AlpnPolicy.member.N

[TLS listeners] The name of the Application-Layer Protocol Negotiation (ALPN) policy. You can specify one policy name. The following are the possible values:

- HTTP1Only
- HTTP2Only
- HTTP2Optional
- HTTP2Preferred
- None

For more information, see [ALPN policies](#) in the *Network Load Balancers Guide*.

Type: Array of strings

Required: No

### Certificates.member.N

[HTTPS and TLS listeners] The default certificate for the listener. You must provide exactly one certificate. Set CertificateArn to the certificate ARN but do not set IsDefault.

To create a certificate list, use [AddListenerCertificates](#).

Type: Array of [Certificate](#) objects

Required: No

### **DefaultActions.member.N**

The actions for the default rule.

Type: Array of [Action](#) objects

Required: No

### **ListenerArn**

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: Yes

### **MutualAuthentication**

The mutual authentication configuration information.

Type: [MutualAuthenticationAttributes](#) object

Required: No

### **Port**

The port for connections from clients to the load balancer. You can't specify a port for a Gateway Load Balancer.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

### **Protocol**

The protocol for connections from clients to the load balancer. Application Load Balancers support the HTTP and HTTPS protocols. Network Load Balancers support the TCP, TLS, UDP, and TCP\_UDP protocols. You can't change the protocol to UDP or TCP\_UDP if dual-stack mode is enabled. You can't specify a protocol for a Gateway Load Balancer.

Type: String

Valid Values: HTTP | HTTPS | TCP | TLS | UDP | TCP\_UDP | GENEVE

Required: No

## SslPolicy

[HTTPS and TLS listeners] The security policy that defines which protocols and ciphers are supported.

For more information, see [Security policies](#) in the *Application Load Balancers Guide* or [Security policies](#) in the *Network Load Balancers Guide*.

Type: String

Required: No

## Response Elements

The following element is returned by the service.

### Listeners.member.N

Information about the modified listener.

Type: Array of [Listener](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ALPNPolicyNotFound

The specified ALPN policy is not supported.

HTTP Status Code: 400

### CertificateNotFound

The specified certificate does not exist.

HTTP Status Code: 400

**DuplicateListener**

A listener with the specified port already exists.

HTTP Status Code: 400

**IncompatibleProtocols**

The specified configuration is not valid with this protocol.

HTTP Status Code: 400

**InvalidConfigurationRequest**

The requested configuration is not valid.

HTTP Status Code: 400

**InvalidLoadBalancerAction**

The requested action is not valid.

HTTP Status Code: 400

**ListenerNotFound**

The specified listener does not exist.

HTTP Status Code: 400

**SSLPolicyNotFound**

The specified SSL policy does not exist.

HTTP Status Code: 400

**TargetGroupAssociationLimit**

You've reached the limit on the number of load balancers per target group.

HTTP Status Code: 400

**TargetGroupNotFound**

The specified target group does not exist.

HTTP Status Code: 400

**TooManyActions**

You've reached the limit on the number of actions per rule.

HTTP Status Code: 400

**TooManyCertificates**

You've reached the limit on the number of certificates per load balancer.

HTTP Status Code: 400

**TooManyListeners**

You've reached the limit on the number of listeners per load balancer.

HTTP Status Code: 400

**TooManyRegistrationsForTargetId**

You've reached the limit on the number of times a target can be registered with a load balancer.

HTTP Status Code: 400

**TooManyTargets**

You've reached the limit on the number of targets.

HTTP Status Code: 400

**TooManyUniqueTargetGroupsPerLoadBalancer**

You've reached the limit on the number of unique target groups per load balancer across all listeners. If a target group is used by multiple actions for a load balancer, it is counted as only one use.

HTTP Status Code: 400

**TrustStoreNotFound**

The specified trust store does not exist.

HTTP Status Code: 400

**TrustStoreNotReady**

The specified trust store is not active.

HTTP Status Code: 400

## UnsupportedProtocol

The specified protocol is not supported.

HTTP Status Code: 400

## Examples

### Change the default action

This example changes the default action for the specified listener.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=ModifyListener
&ListenerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-load-
balancer/50dc6c495c0c9188/f2f7dc8efc522ab2
&DefaultActions.member.1.Type=forward
&DefaultActions.member.1.TargetGroupArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-new-targets/2453ed029918f21f
&Version=2015-12-01
&AUTHPARAMS
```

#### Sample Response

```
<ModifyListenerResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <ModifyListenerResult>
    <Listeners>
      <member>
        <LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</
LoadBalancerArn>
        <Protocol>HTTP</Protocol>
        <Port>80</Port>
        <ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2</ListenerArn>
        <DefaultActions>
          <member>
            <Type>forward</Type>
```

```
<TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-new-targets/2453ed029918f21f</TargetGroupArn>
</member>
</DefaultActions>
</member>
</Listeners>
</ModifyListenerResult>
<ResponseMetadata>
<RequestId>9759b8df-f462-11e5-8a24-ffe2bf8623ae</RequestId>
</ResponseMetadata>
</ModifyListenerResponse>
```

## Change the default certificate

This example changes the default certificate for the specified HTTPS listener.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=ModifyListener
&ListenerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-load-
balancer/50dc6c495c0c9188/0467ef3c8400ae65
&Certificates.member.1.CertificateArn=arn:aws:iam::123456789012:server-certificate/my-
new-server-cert
&Version=2015-12-01
&AUTHPARAMS
```

### Sample Response

```
<ModifyListenerResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
<ModifyListenerResult>
<Listeners>
<member>
<LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</
LoadBalancerArn>
<Protocol>HTTPS</Protocol>
<Certificates>
<member>
<CertificateArn>arn:aws:iam::123456789012:server-certificate/my-new-server-
cert</CertificateArn>
</member>
</Certificates>
```

```
<Port>443</Port>
<SslPolicy>ELBSecurityPolicy-2016-08</SslPolicy>
<ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/
my-load-balancer/50dc6c495c0c9188/0467ef3c8400ae65</ListenerArn>
<DefaultActions>
  <member>
    <Type>forward</Type>
    <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
  </member>
</DefaultActions>
</member>
</Listeners>
</ModifyListenerResult>
<ResponseMetadata>
  <RequestId>3f72dcb2-f463-11e5-b95d-3b2c1831fc26</RequestId>
</ResponseMetadata> </ModifyListenerResponse>
```

## Change the security policy

This example changes the security policy for the specified HTTPS listener.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=ModifyListener
&ListenerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-load-
balancer/50dc6c495c0c9188/0467ef3c8400ae65
&SslPolicy=ELBSecurityPolicy-2016-08
&Version=2015-12-01
&AUTHPARAMS
```

### Sample Response

```
<ModifyListenerResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
<ModifyListenerResult>
  <Listeners>
    <member>
      <LoadBalancerArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188</
LoadBalancerArn>
        <Protocol>HTTPS</Protocol>
        <Certificates>
```

```
<member>
    <CertificateArn>arn:aws:iam::123456789012:server-certificate/my-server-cert</CertificateArn>
    </member>
</Certificates>
<Port>443</Port>
<SslPolicy>ELBSecurityPolicy-2016-08</SslPolicy>
<ListenerArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener/app/my-load-balancer/50dc6c495c0c9188/0467ef3c8400ae65</ListenerArn>
<DefaultActions>
    <member>
        <Type>forward</Type>
        <TargetGroupArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
    </member>
</DefaultActions>
</member>
</Listeners>
</ModifyListenerResult>
<ResponseMetadata>
    <RequestId>3f72dcbb-f463-11e5-b95d-3b2c1831fc26</RequestId>
</ResponseMetadata>
</ModifyListenerResponse>
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)



# ModifyListenerAttributes

Modifies the specified attributes of the specified listener.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### Attributes.member.N

The listener attributes.

Type: Array of [ListenerAttribute](#) objects

Required: Yes

### ListenerArn

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: Yes

## Response Elements

The following element is returned by the service.

### Attributes.member.N

Information about the listener attributes.

Type: Array of [ListenerAttribute](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

## ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# ModifyLoadBalancerAttributes

Modifies the specified attributes of the specified Application Load Balancer, Network Load Balancer, or Gateway Load Balancer.

If any of the specified attributes can't be modified as requested, the call fails. Any existing attributes that you do not modify retain their current values.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### Attributes.member.N

The load balancer attributes.

Type: Array of [LoadBalancerAttribute](#) objects

Array Members: Maximum number of 20 items.

Required: Yes

### LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

## Response Elements

The following element is returned by the service.

### Attributes.member.N

Information about the load balancer attributes.

Type: Array of [LoadBalancerAttribute](#) objects

Array Members: Maximum number of 20 items.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

### LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

## Examples

### Enable deletion protection

This example enables deletion protection for the specified load balancer.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=ModifyLoadBalancerAttributes
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
&Attributes.member.1.Key=deletion_protection.enabled
&Attributes.member.1.Value=true
&Version=2015-12-01
&AUTHPARAMS
```

#### Sample Response

```
<ModifyLoadBalancerAttributesResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <ModifyLoadBalancerAttributesResult>
    <Attributes>
      <member>
        <Value>true</Value>
        <Key>deletion_protection.enabled</Key>
      </member>
      <member>
```

```
<Value>false</Value>
<Key>access_logs.s3.enabled</Key>
</member>
<member>
<Value>60</Value>
<Key>idle_timeout.timeout_seconds</Key>
</member>
<member>
<Value />
<Key>access_logs.s3.prefix</Key>
</member>
<member>
<Value />
<Key>access_logs.s3.bucket</Key>
</member>
</Attributes>
</ModifyLoadBalancerAttributesResult>
<ResponseMetadata>
<RequestId>b2066529-f42c-11e5-b543-9f2c3fbb9bee</RequestId>
</ResponseMetadata>
</ModifyLoadBalancerAttributesResponse>
```

## Change the idle timeout

This example changes the idle timeout value for the specified Application Load Balancer.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=ModifyLoadBalancerAttributes
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
&Attributes.member.1.Key=idle_timeout.timeout_seconds
&Attributes.member.1.Value=30
&Version=2015-12-01
&AUTHPARAMS
```

### Sample Response

```
<ModifyLoadBalancerAttributesResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
<ModifyLoadBalancerAttributesResult>
<Attributes>
<member>
```

```
<Value>30</Value>
<Key>idle_timeout.timeout_seconds</Key>
</member>
<member>
<Value>false</Value>
<Key>access_logs.s3.enabled</Key>
</member>
<member>
<Value />
<Key>access_logs.s3.prefix</Key>
</member>
<member>
<Value>false</Value>
<Key>deletion_protection.enabled</Key>
</member>
<member>
<Value />
<Key>access_logs.s3.bucket</Key>
</member>
</Attributes>
</ModifyLoadBalancerAttributesResult>
<ResponseMetadata>
<RequestId>d3f6e6dc-f42c-11e5-b5ae-8bfaf16614ac</RequestId>
</ResponseMetadata>
</ModifyLoadBalancerAttributesResponse>
```

## Enable access logs

This example enables access logs for the specified Application Load Balancer. The S3 bucket must exist in the same Region as the load balancer and must have a bucket policy that grants Elastic Load Balancing permissions to write to the bucket.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=ModifyLoadBalancerAttributes
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
&Attributes.member.1.Key=access_logs.s3.enabled
&Attributes.member.1.Value=true
&Attributes.member.2.Key=access_logs.s3.bucket
&Attributes.member.2.Value=my-loadbalancer-logs
&Attributes.member.3.Key=access_logs.s3.prefix
&Attributes.member.3.Value=myapp
```

&Version=2015-12-01  
&AUTHPARAMS

## Sample Response

```
<ModifyLoadBalancerAttributesResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">
  <ModifyLoadBalancerAttributesResult>
    <Attributes>
      <member>
        <Value>true</Value>
        <Key>access_logs.s3.enabled</Key>
      </member>
      <member>
        <Value>my-loadbalancer-logs</Value>
        <Key>access_logs.s3.bucket</Key>
      </member>
      <member>
        <Value>myapp</Value>
        <Key>access_logs.s3.prefix</Key>
      </member>
      <member>
        <Value>60</Value>
        <Key>idle_timeout.timeout_seconds</Key>
      </member>
      <member>
        <Value>false</Value>
        <Key>deletion_protection.enabled</Key>
      </member>
    </Attributes>
  </ModifyLoadBalancerAttributesResult>
  <ResponseMetadata>
    <RequestId>095cb76d-f52e-11e5-bb98-57195a6eb84a</RequestId>
  </ResponseMetadata>
</ModifyLoadBalancerAttributesResponse>
```

## Enable connection logs.

This example enables connection logs, setting the specified S3 bucket and prefix location.

## Sample Request

<https://elasticloadbalancing.amazonaws.com/?Action=ModifyLoadBalancerAttributes>

```
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/  
my-load-balancer/50dc6c495c0c9188  
&Attributes.member.1.Key=connection_logs.s3.enabled  
&Attributes.member.1.Value=true  
&Attributes.member.2.Key=connection_logs.s3.bucket  
&Attributes.member.2.Value=my-loadbalancer-connection-logs  
&Attributes.member.3.Key=connection_logs.s3.prefix  
&Attributes.member.3.Value=myapp-connections  
&Version=2015-12-01  
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

## ModifyRule

Replaces the specified properties of the specified rule. Any properties that you do not specify are unchanged.

To add an item to a list, remove an item from a list, or update an item in a list, you must provide the entire list. For example, to add an action, specify a list with the current actions plus the new action.

To modify the actions for the default rule, use [ModifyListener](#).

### Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

#### **Actions.member.N**

The actions.

Type: Array of [Action](#) objects

Required: No

#### **Conditions.member.N**

The conditions.

Type: Array of [RuleCondition](#) objects

Required: No

#### **RuleArn**

The Amazon Resource Name (ARN) of the rule.

Type: String

Required: Yes

### Response Elements

The following element is returned by the service.

## Rules.member.N

Information about the modified rule.

Type: Array of [Rule](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### IncompatibleProtocols

The specified configuration is not valid with this protocol.

HTTP Status Code: 400

### InvalidLoadBalancerAction

The requested action is not valid.

HTTP Status Code: 400

### OperationNotPermitted

This operation is not allowed.

HTTP Status Code: 400

### RuleNotFound

The specified rule does not exist.

HTTP Status Code: 400

### TargetGroupAssociationLimit

You've reached the limit on the number of load balancers per target group.

HTTP Status Code: 400

### TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

## TooManyActions

You've reached the limit on the number of actions per rule.

HTTP Status Code: 400

## TooManyRegistrationsForTargetId

You've reached the limit on the number of times a target can be registered with a load balancer.

HTTP Status Code: 400

## TooManyTargets

You've reached the limit on the number of targets.

HTTP Status Code: 400

## TooManyUniqueTargetGroupsPerLoadBalancer

You've reached the limit on the number of unique target groups per load balancer across all listeners. If a target group is used by multiple actions for a load balancer, it is counted as only one use.

HTTP Status Code: 400

## UnsupportedProtocol

The specified protocol is not supported.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# ModifyTargetGroup

Modifies the health checks used when evaluating the health state of the targets in the specified target group.

To monitor the health of the targets, use [DescribeTargetHealth](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### HealthCheckEnabled

Indicates whether health checks are enabled.

Type: Boolean

Required: No

### HealthCheckIntervalSeconds

The approximate amount of time, in seconds, between health checks of an individual target.

Type: Integer

Valid Range: Minimum value of 5. Maximum value of 300.

Required: No

### HealthCheckPath

[HTTP/HTTPS health checks] The destination for health checks on the targets.

[HTTP1 or HTTP2 protocol version] The ping path. The default is /.

[GRPC protocol version] The path of a custom health check method with the format / package.service/method. The default is /Amazon.ALB/healthcheck.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

## HealthCheckPort

The port the load balancer uses when performing health checks on targets.

Type: String

Required: No

## HealthCheckProtocol

The protocol the load balancer uses when performing health checks on targets. For Application Load Balancers, the default is HTTP. For Network Load Balancers and Gateway Load Balancers, the default is TCP. The TCP protocol is not supported for health checks if the protocol of the target group is HTTP or HTTPS. It is supported for health checks only if the protocol of the target group is TCP, TLS, UDP, or TCP\_UDP. The GENEVE, TLS, UDP, and TCP\_UDP protocols are not supported for health checks.

Type: String

Valid Values: HTTP | HTTPS | TCP | TLS | UDP | TCP\_UDP | GENEVE

Required: No

## HealthCheckTimeoutSeconds

[HTTP/HTTPS health checks] The amount of time, in seconds, during which no response means a failed health check.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 120.

Required: No

## HealthyThresholdCount

The number of consecutive health checks successes required before considering an unhealthy target healthy.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 10.

Required: No

## Matcher

[HTTP/HTTPS health checks] The HTTP or gRPC codes to use when checking for a successful response from a target. For target groups with a protocol of TCP, TCP\_UDP, UDP or TLS the range is 200-599. For target groups with a protocol of HTTP or HTTPS, the range is 200-499. For target groups with a protocol of GENEVE, the range is 200-399.

Type: [Matcher](#) object

Required: No

## TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: Yes

## UnhealthyThresholdCount

The number of consecutive health check failures required before considering the target unhealthy.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 10.

Required: No

## Response Elements

The following element is returned by the service.

### TargetGroups.member.N

Information about the modified target group.

Type: Array of [TargetGroup](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

## TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

## Examples

### Modify the health check configuration for a target group

This example changes the configuration of the health checks used to evaluate the health of the targets for the specified target group.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=ModifyTargetGroup
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-
https-targets/2453ed029918f21f
&HealthCheckProtocol=HTTPS
&HealthCheckPort=443
&Version=2015-12-01
&AUTHPARAMS
```

#### Sample Response

```
<ModifyTargetGroupResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <ModifyTargetGroupResult>
    <TargetGroups>
      <member>
        <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-https-targets/2453ed029918f21f</TargetGroupArn>
        <HealthCheckTimeoutSeconds>5</HealthCheckTimeoutSeconds>
        <HealthCheckPort>443</HealthCheckPort>
        <Matcher>
          <HttpCode>200</HttpCode>
```

```
</Matcher>
<TargetGroupName>my-https-targets</TargetGroupName>
<HealthCheckProtocol>HTTPS</HealthCheckProtocol>
<Protocol>HTTPS</Protocol>
<Port>443</Port>
<HealthyThresholdCount>5</HealthyThresholdCount>
<VpcId>vpc-3ac0fb5f</VpcId>
<HealthCheckIntervalSeconds>30</HealthCheckIntervalSeconds>
<LoadBalancerArns>
    <member>arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188</member>
</LoadBalancerArns>
<UnhealthyThresholdCount>2</UnhealthyThresholdCount>
</member>
</TargetGroups>
</ModifyTargetGroupResult>
<ResponseMetadata>
    <RequestId>8525b334-f466-11e5-aa04-33bf366f62e2</RequestId>
</ResponseMetadata>
</ModifyTargetGroupResponse>
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# ModifyTargetGroupAttributes

Modifies the specified attributes of the specified target group.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### Attributes.member.N

The target group attributes.

Type: Array of [TargetGroupAttribute](#) objects

Required: Yes

### TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: Yes

## Response Elements

The following element is returned by the service.

### Attributes.member.N

Information about the target group attributes.

Type: Array of [TargetGroupAttribute](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

## TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

## Examples

### Modify the deregistration delay timeout

This example sets the deregistration delay timeout for the specified target group to the specified value.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=ModifyTargetGroupAttributes
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-
targets/73e2d6bc24d8a067
&Attributes.member.1.Key=deregistration_delay.timeout_seconds
&Attributes.member.1.Value=600
&Version=2015-12-01
&AUTHPARAMS
```

#### Sample Response

```
<ModifyTargetGroupAttributesResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <ModifyTargetGroupAttributesResult>
    <Attributes>
      <member>
        <Value>600</Value>
        <Key>deregistration_delay.timeout_seconds</Key>
      </member>
    </Attributes>
  </ModifyTargetGroupAttributesResult>
  <ResponseMetadata>
    <RequestId>bb8c272b-f455-11e5-a53c-67205c0d10fd</RequestId>
  </ResponseMetadata>
</ModifyTargetGroupAttributesResponse>
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# ModifyTrustStore

Update the ca certificate bundle for the specified trust store.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### CaCertificatesBundleS3Bucket

The Amazon S3 bucket for the ca certificates bundle.

Type: String

Required: Yes

### CaCertificatesBundleS3Key

The Amazon S3 path for the ca certificates bundle.

Type: String

Required: Yes

### CaCertificatesBundleS3ObjectVersion

The Amazon S3 object version for the ca certificates bundle. If undefined the current version is used.

Type: String

Required: No

### TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

## Response Elements

The following element is returned by the service.

## TrustStores.member.N

Information about the modified trust store.

Type: Array of [TrustStore](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### CaCertificatesBundleNotFound

The specified ca certificate bundle does not exist.

HTTP Status Code: 400

### InvalidCaCertificatesBundle

The specified ca certificate bundle is in an invalid format, or corrupt.

HTTP Status Code: 400

### TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

## Examples

### Modify a trust store.

This example replaces the ca certificate bundle in the specified trust store.

### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=ModifyTrustStore
&TrustStoreArn=arn:aws:elasticloadbalancing:us-east-1:111122223333:truststore/my-trust-
store/d5f637c79df8c943
&CaCertificatesBundleS3Bucket=amzn-s3-demo-bucket
&CaCertificatesBundleS3Key=CACertBundle.pem
&Version=2015-12-01
```

&amp;AUTHPARAMS

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# RegisterTargets

Registers the specified targets with the specified target group.

If the target is an EC2 instance, it must be in the `running` state when you register it.

By default, the load balancer routes requests to registered targets using the protocol and port for the target group. Alternatively, you can override the port for a target when you register it. You can register each EC2 instance or IP address with the same target group multiple times using different ports.

For more information, see the following:

- [Register targets for your Application Load Balancer](#)
- [Register targets for your Network Load Balancer](#)
- [Register targets for your Gateway Load Balancer](#)

To remove a target from a target group, use [DeregisterTargets](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: Yes

### Targets.member.N

The targets.

Type: Array of [TargetDescription](#) objects

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## InvalidTarget

The specified target does not exist, is not in the same VPC as the target group, or has an unsupported instance type.

HTTP Status Code: 400

## TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

## TooManyRegistrationsForTargetId

You've reached the limit on the number of times a target can be registered with a load balancer.

HTTP Status Code: 400

## TooManyTargets

You've reached the limit on the number of targets.

HTTP Status Code: 400

## Examples

### Register targets by instance ID

This example registers the specified instance IDs with the specified target group.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=RegisterTargets  
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-  
targets/73e2d6bc24d8a067  
&Targets.member.1.Id=i-80c8dd94  
&Targets.member.2.Id=i-ceddc4d  
&Version=2015-12-01  
&AUTHPARAMS
```

### Register targets by IP address

This example registers the specified IP addresses with the specified target group.

## Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=RegisterTargets  
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-  
targets/73e2d6bc24d8a067  
&Targets.member.1.Id=10.0.42.17  
&Targets.member.2.Id=192.168.0.3  
&Targets.member.2.AvailabilityZone=all  
&Version=2015-12-01  
&AUTHPARAMS
```

## Register targets by instance ID using port overrides

This example registers the specified instance with the specified target group using multiple ports. This enables you to register microservices on the same instance as targets in the target group.

## Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=RegisterTargets  
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-  
targets/73e2d6bc24d8a067  
&Targets.member.1.Id=i-80c8dd94  
&Targets.member.1.Port=80  
&Targets.member.2.Id=i-80c8dd94  
&Targets.member.2.Port=766  
&Version=2015-12-01  
&AUTHPARAMS
```

## Register a Lambda function as a target

This example registers the specified Lambda function with the specified target group. You must grant Elastic Load Balancing permission to invoke the Lambda function. For more information, see [Lambda functions as targets](#) in the *Application Load Balancers Guide*.

## Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=RegisterTargets  
&TargetGroupArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:targetgroup/my-  
targets/73e2d6bc24d8a067  
&Targets.member.1.Id=aws:lambda:us-west-2:123456789012:function:my-function  
&Version=2015-12-01
```

&amp;AUTHPARAMS

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# RemoveListenerCertificates

Removes the specified certificate from the certificate list for the specified HTTPS or TLS listener.

You can't remove the default certificate for a listener. To replace the default certificate, call [ModifyListener](#).

To list the certificates for your listener, use [DescribeListenerCertificates](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### Certificates.member.N

The certificate to remove. You can specify one certificate per call. Set `CertificateArn` to the certificate ARN but do not set `IsDefault`.

Type: Array of [Certificate](#) objects

Required: Yes

### ListenerArn

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

### OperationNotPermitted

This operation is not allowed.

## HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

## RemoveTags

Removes the specified tags from the specified Elastic Load Balancing resources. You can remove the tags for one or more Application Load Balancers, Network Load Balancers, Gateway Load Balancers, target groups, listeners, or rules.

To list the current tags for your resources, use [DescribeTags](#).

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### ResourceArns.member.N

The Amazon Resource Name (ARN) of the resource.

Type: Array of strings

Required: Yes

### TagKeys.member.N

The tag keys for the tags to remove.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^([\p{L}\p{Z}\p{N}\_.:/-@]+)\*\$

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ListenerNotFound

The specified listener does not exist.

HTTP Status Code: 400

## LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

## RuleNotFound

The specified rule does not exist.

HTTP Status Code: 400

## TargetGroupNotFound

The specified target group does not exist.

HTTP Status Code: 400

## TooManyTags

You've reached the limit on the number of tags for this resource.

HTTP Status Code: 400

## TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

## Examples

### Remove tags from a load balancer

This example removes the specified tags from the specified load balancer.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=RemoveTags  
&ResourceArns.member.1=arn:aws:elasticloadbalancing:us-  
west-2:123456789012:loadbalancer/app/my-load-balancer/50dc6c495c0c9188  
&TagKeys.member.1=project  
&TagKeys.member.2=department  
&Version=2015-12-01
```

&amp;AUTHPARAMS

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# RemoveTrustStoreRevocations

Removes the specified revocation file from the specified trust store.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### RevocationIds.member.N

The revocation IDs of the revocation files you want to remove.

Type: Array of longs

Required: Yes

### TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: Yes

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### RevocationIdNotFound

The specified revocation ID does not exist.

HTTP Status Code: 400

### TrustStoreNotFound

The specified trust store does not exist.

HTTP Status Code: 400

## Examples

### Remove a revocation file from a trust store.

This example removes the specified certificate revocation ID from the specified trust store.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=RemoveTrustStoreRevocations  
&TrustStoreArn=arn:aws:elasticloadbalancing:us-east-1:111122223333:truststore/my-trust-  
store/3ym756xh7yj  
&RevocationIds.member.1.RevocationID=1  
&Version=2015-12-01  
&AUTHPARAMS
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# SetIpAddressType

Sets the type of IP addresses used by the subnets of the specified load balancer.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### IpAddressType

The IP address type. Internal load balancers must use `ipv4`.

[Application Load Balancers] The possible values are `ipv4` (IPv4 addresses), `dualstack` (IPv4 and IPv6 addresses), and `dualstack-without-public-ipv4` (public IPv6 addresses and private IPv4 and IPv6 addresses).

Application Load Balancer authentication supports IPv4 addresses only when connecting to an Identity Provider (IdP) or Amazon Cognito endpoint. Without a public IPv4 address the load balancer can't complete the authentication process, resulting in HTTP 500 errors.

[Network Load Balancers and Gateway Load Balancers] The possible values are `ipv4` (IPv4 addresses) and `dualstack` (IPv4 and IPv6 addresses).

Type: String

Valid Values: `ipv4` | `dualstack` | `dualstack-without-public-ipv4`

Required: Yes

### LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

## Response Elements

The following element is returned by the service.

## IpAddressType

The IP address type.

Type: String

Valid Values: ipv4 | dualstack | dualstack-without-public-ipv4

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

### InvalidSubnet

The specified subnet is out of available addresses.

HTTP Status Code: 400

### LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

## Examples

### Set the IP address type of a load balancer

This example sets the IP address type of the specified load balancer to dualstack to support IPv4 and IPv6 addresses. The load balancer subnets must have associated IPv6 CIDR blocks.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=SetIpAddressType  
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/  
my-load-balancer/50dc6c495c0c9188
```

```
&IpAddressType=dualstack  
&Version=2015-12-01  
&AUTHPARAMS
```

## Sample Response

```
<SetIpAddressTypeResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">  
  <SetIpAddressTypeResult>  
    <IpAddressType>dualstack</IpAddressType>  
  </SetIpAddressTypeResult>  
  <ResponseMetadata>  
    <RequestId>a127426b-f3ab-11e5-9192-3fff33344cfa</RequestId>  
  </ResponseMetadata>  
</SetIpAddressTypeResponse>
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# SetRulePriorities

Sets the priorities of the specified rules.

You can reorder the rules as long as there are no priority conflicts in the new order. Any existing rules that you do not specify retain their current priority.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### RulePriorities.member.N

The rule priorities.

Type: Array of [RulePriorityPair](#) objects

Required: Yes

## Response Elements

The following element is returned by the service.

### Rules.member.N

Information about the rules.

Type: Array of [Rule](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### OperationNotPermitted

This operation is not allowed.

HTTP Status Code: 400

### PriorityInUse

The specified priority is in use.

HTTP Status Code: 400

## RuleNotFound

The specified rule does not exist.

HTTP Status Code: 400

## Examples

### Set the rule priority

This example sets the priority of the specified rule.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=SetRulePriorities
&RulePriorities.member.1.RuleArn=arn:aws:elasticloadbalancing:us-
west-2:123456789012:listener-rule/app/my-load-balancer/50dc6c495c0c9188/
f2f7dc8efc522ab2/1291d13826f405c3
&RulePriorities.member.1.Priority=5
&Version=2015-12-01
&AUTHPARAMS
```

#### Sample Response

```
<SetRulePrioritiesResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
<SetRulePrioritiesResult>
<Rules>
<member>
<IsDefault>false</IsDefault>
<Conditions>
<member>
<Field>path-pattern</Field>
<Values>
<member>/img/*</member>
</Values>
</member>
</Conditions>
<Priority>5</Priority>
<Actions>
```

```
<member>
  <Type>forward</Type>
  <TargetGroupArn>arn:aws:elasticloadbalancing:us-
west-2:123456789012:targetgroup/my-targets/73e2d6bc24d8a067</TargetGroupArn>
</member>
</Actions>
<RuleArn>arn:aws:elasticloadbalancing:us-west-2:123456789012:listener-rule/app/
my-load-balancer/50dc6c495c0c9188/f2f7dc8efc522ab2/1291d13826f405c3</RuleArn>
</member>
</Rules>
</SetRulePrioritiesResult>
<ResponseMetadata>
  <RequestId>4d7a8036-f3a7-11e5-9c02-8fd20490d5a6</RequestId>
</ResponseMetadata>
</SetRulePrioritiesResponse>
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# SetSecurityGroups

Associates the specified security groups with the specified Application Load Balancer or Network Load Balancer. The specified security groups override the previously associated security groups.

You can't perform this operation on a Network Load Balancer unless you specified a security group for the load balancer when you created it.

You can't associate a security group with a Gateway Load Balancer.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### EnforceSecurityGroupInboundRulesOnPrivateLinkTraffic

Indicates whether to evaluate inbound security group rules for traffic sent to a Network Load Balancer through Amazon PrivateLink. The default is on.

Type: String

Valid Values: on | off

Required: No

### LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

### SecurityGroups.member.N

The IDs of the security groups.

Type: Array of strings

Required: Yes

## Response Elements

The following elements are returned by the service.

## **EnforceSecurityGroupInboundRulesOnPrivateLinkTraffic**

Indicates whether to evaluate inbound security group rules for traffic sent to a Network Load Balancer through Amazon PrivateLink.

Type: String

Valid Values: on | off

## **SecurityGroupIds.member.N**

The IDs of the security groups associated with the load balancer.

Type: Array of strings

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **InvalidConfigurationRequest**

The requested configuration is not valid.

HTTP Status Code: 400

### **InvalidSecurityGroup**

The specified security group does not exist.

HTTP Status Code: 400

### **LoadBalancerNotFound**

The specified load balancer does not exist.

HTTP Status Code: 400

## **Examples**

### **Associate a security group with a load balancer**

This example associates the specified security group with the specified load balancer.

## Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=SetSecurityGroups
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/
my-load-balancer/50dc6c495c0c9188
&SecurityGroups.member.1=sg-5943793c
&Version=2015-12-01
&AUTHPARAMS
```

## Sample Response

```
<SetSecurityGroupsResponse xmlns="http://elasticloadbalancing.amazonaws.com/
doc/2015-12-01/">
  <SetSecurityGroupsResult>
    <SecurityGroupIds>
      <member>sg-5943793c</member>
    </SecurityGroupIds>
  </SetSecurityGroupsResult>
  <ResponseMetadata>
    <RequestId>a127426b-f3ab-11e5-9192-3fff33344cfa</RequestId>
  </ResponseMetadata>
</SetSecurityGroupsResponse>
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)



# SetSubnets

Enables the Availability Zones for the specified public subnets for the specified Application Load Balancer, Network Load Balancer or Gateway Load Balancer. The specified subnets replace the previously enabled subnets.

When you specify subnets for a Network Load Balancer, or Gateway Load Balancer you must include all subnets that were enabled previously, with their existing configurations, plus any additional subnets.

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

### EnablePrefixForIpv6SourceNat

[Network Load Balancers with UDP listeners] Indicates whether to use an IPv6 prefix from each subnet for source NAT. The IP address type must be dualstack. The default value is off.

Type: String

Valid Values: on | off

Required: No

### IpAddressType

The IP address type.

[Application Load Balancers] The possible values are ipv4 (IPv4 addresses), dualstack (IPv4 and IPv6 addresses), and dualstack-without-public-ipv4 (public IPv6 addresses and private IPv4 and IPv6 addresses).

[Network Load Balancers and Gateway Load Balancers] The possible values are ipv4 (IPv4 addresses) and dualstack (IPv4 and IPv6 addresses).

Type: String

Valid Values: ipv4 | dualstack | dualstack-without-public-ipv4

Required: No

## LoadBalancerArn

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: Yes

## SubnetMappings.member.N

The IDs of the public subnets. You can specify only one subnet per Availability Zone. You must specify either subnets or subnet mappings.

[Application Load Balancers] You must specify subnets from at least two Availability Zones. You can't specify Elastic IP addresses for your subnets.

[Application Load Balancers on Outposts] You must specify one Outpost subnet.

[Application Load Balancers on Local Zones] You can specify subnets from one or more Local Zones.

[Network Load Balancers] You can specify subnets from one or more Availability Zones. You can specify one Elastic IP address per subnet if you need static IP addresses for your internet-facing load balancer. For internal load balancers, you can specify one private IP address per subnet from the IPv4 range of the subnet. For internet-facing load balancer, you can specify one IPv6 address per subnet.

[Gateway Load Balancers] You can specify subnets from one or more Availability Zones.

Type: Array of [SubnetMapping](#) objects

Required: No

## Subnets.member.N

The IDs of the public subnets. You can specify only one subnet per Availability Zone. You must specify either subnets or subnet mappings.

[Application Load Balancers] You must specify subnets from at least two Availability Zones.

[Application Load Balancers on Outposts] You must specify one Outpost subnet.

[Application Load Balancers on Local Zones] You can specify subnets from one or more Local Zones.

[Network Load Balancers and Gateway Load Balancers] You can specify subnets from one or more Availability Zones.

Type: Array of strings

Required: No

## Response Elements

The following elements are returned by the service.

### **AvailabilityZones.member.N**

Information about the subnets.

Type: Array of [AvailabilityZone](#) objects

### **EnablePrefixForIpv6SourceNat**

[Network Load Balancers] Indicates whether to use an IPv6 prefix from each subnet for source NAT.

Type: String

Valid Values: on | off

### **IpAddressType**

The IP address type.

Type: String

Valid Values: ipv4 | dualstack | dualstack-without-public-ipv4

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AllocationIdNotFound**

The specified allocation ID does not exist.

HTTP Status Code: 400

## AvailabilityZoneNotSupported

The specified Availability Zone is not supported.

HTTP Status Code: 400

## CapacityReservationPending

There is a pending capacity reservation.

HTTP Status Code: 400

## InvalidConfigurationRequest

The requested configuration is not valid.

HTTP Status Code: 400

## InvalidSubnet

The specified subnet is out of available addresses.

HTTP Status Code: 400

## LoadBalancerNotFound

The specified load balancer does not exist.

HTTP Status Code: 400

## SubnetNotFound

The specified subnet does not exist.

HTTP Status Code: 400

## Examples

### Enable Availability Zones for a load balancer

This example enables the Availability Zone for the specified subnet for the specified load balancer.

#### Sample Request

```
https://elasticloadbalancing.amazonaws.com/?Action=SetSubnets
```

```
&LoadBalancerArn=arn:aws:elasticloadbalancing:us-west-2:123456789012:loadbalancer/app/  
my-load-balancer/50dc6c495c0c9188  
&Subnets.member.1=subnet-8360a9e7  
&Subnets.member.2=subnet-b7d581c0  
&Version=2015-12-01  
&AUTHPARAMS
```

## Sample Response

```
<SetSubnetsResponse xmlns="http://elasticloadbalancing.amazonaws.com/doc/2015-12-01/">  
  <SetSubnetsResult>  
    <AvailabilityZones>  
      <member>  
        <SubnetId>subnet-8360a9e7</SubnetId>  
        <ZoneName>us-west-2a</ZoneName>  
      </member>  
      <member>  
        <SubnetId>subnet-b7d581c0</SubnetId>  
        <ZoneName>us-west-2b</ZoneName>  
      </member>  
    </AvailabilityZones>  
  </SetSubnetsResult>  
  <ResponseMetadata>  
    <RequestId>c1a80803-f3ab-11e5-b673-8d4a8a9e6f48</RequestId>  
  </ResponseMetadata>  
</SetSubnetsResponse>
```

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)

- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

# Data Types

The Elastic Load Balancing API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Action](#)
- [AdministrativeOverride](#)
- [AnomalyDetection](#)
- [AuthenticateCognitoActionConfig](#)
- [AuthenticateOidcActionConfig](#)
- [AvailabilityZone](#)
- [CapacityReservationStatus](#)
- [Certificate](#)
- [Cipher](#)
- [DescribeTrustStoreRevocation](#)
- [FixedResponseActionConfig](#)
- [ForwardActionConfig](#)
- [HostHeaderConditionConfig](#)
- [HttpHeaderConditionConfig](#)
- [HttpRequestMethodConditionConfig](#)
- [IpamPools](#)
- [Limit](#)
- [Listener](#)
- [ListenerAttribute](#)
- [LoadBalancer](#)

- [LoadBalancerAddress](#)
- [LoadBalancerAttribute](#)
- [LoadBalancerState](#)
- [Matcher](#)
- [MinimumLoadBalancerCapacity](#)
- [MutualAuthenticationAttributes](#)
- [PathPatternConditionConfig](#)
- [QueryStringConditionConfig](#)
- [QueryStringKeyValuePair](#)
- [RedirectActionConfig](#)
- [RevocationContent](#)
- [Rule](#)
- [RuleCondition](#)
- [RulePriorityPair](#)
- [SourceIpConditionConfig](#)
- [SslPolicy](#)
- [SubnetMapping](#)
- [Tag](#)
- [TagDescription](#)
- [TargetDescription](#)
- [TargetGroup](#)
- [TargetGroupAttribute](#)
- [TargetGroupStickinessConfig](#)
- [TargetGroupTuple](#)
- [TargetHealth](#)
- [TargetHealthDescription](#)
- [TrustStore](#)
- [TrustStoreAssociation](#)
- [TrustStoreRevocation](#)
- [ZonalCapacityReservationState](#)



# Action

Information about an action.

Each rule must include exactly one of the following types of actions: `forward`, `fixed-response`, or `redirect`, and it must be the last action to be performed.

## Contents

### Type

The type of action.

Type: String

Valid Values: `forward` | `authenticate-oidc` | `authenticate-cognito` | `redirect` | `fixed-response`

Required: Yes

### AuthenticateCognitoConfig

[HTTPS listeners] Information for using Amazon Cognito to authenticate users. Specify only when Type is `authenticate-cognito`.

Type: [AuthenticateCognitoActionConfig](#) object

Required: No

### AuthenticateOidcConfig

[HTTPS listeners] Information about an identity provider that is compliant with OpenID Connect (OIDC). Specify only when Type is `authenticate-oidc`.

Type: [AuthenticateOidcActionConfig](#) object

Required: No

### FixedResponseConfig

[Application Load Balancer] Information for creating an action that returns a custom HTTP response. Specify only when Type is `fixed-response`.

Type: [FixedResponseActionConfig](#) object

Required: No

## ForwardConfig

Information for creating an action that distributes requests among one or more target groups. For Network Load Balancers, you can specify a single target group. Specify only when Type is forward. If you specify both ForwardConfig and TargetGroupArn, you can specify only one target group using ForwardConfig and it must be the same target group specified in TargetGroupArn.

Type: [ForwardActionConfig](#) object

Required: No

## Order

The order for the action. This value is required for rules with multiple actions. The action with the lowest value for order is performed first.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50000.

Required: No

## RedirectConfig

[Application Load Balancer] Information for creating a redirect action. Specify only when Type is redirect.

Type: [RedirectActionConfig](#) object

Required: No

## TargetGroupArn

The Amazon Resource Name (ARN) of the target group. Specify only when Type is forward and you want to route to a single target group. To route to one or more target groups, use ForwardConfig instead.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# AdministrativeOverride

Information about the override status applied to a target.

## Contents

### Description

A description of the override state that provides additional details.

Type: String

Required: No

### Reason

The reason code for the state.

Type: String

Valid Values: AdministrativeOverride.Unknown |  
AdministrativeOverride.NoOverride |  
AdministrativeOverride.ZonalShiftActive |  
AdministrativeOverride.ZonalShiftDelegatedToDns

Required: No

### State

The state of the override.

Type: String

Valid Values: unknown | no\_override | zonal\_shift\_active |  
zonal\_shift\_delegated\_to\_dns

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# AnomalyDetection

Information about anomaly detection and mitigation.

## Contents

### MitigationInEffect

Indicates whether anomaly mitigation is in progress.

Type: String

Valid Values: yes | no

Required: No

### Result

The latest anomaly detection result.

Type: String

Valid Values: anomalous | normal

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# AuthenticateCognitoActionConfig

Request parameters to use when integrating with Amazon Cognito to authenticate users.

## Contents

### UserPoolArn

The Amazon Resource Name (ARN) of the Amazon Cognito user pool.

Type: String

Required: Yes

### UserPoolClientId

The ID of the Amazon Cognito user pool client.

Type: String

Required: Yes

### UserPoolDomain

The domain prefix or fully-qualified domain name of the Amazon Cognito user pool.

Type: String

Required: Yes

### AuthenticationRequestExtraParams , AuthenticationRequestExtraParams.entry.N.key (key) , AuthenticationRequestExtraParams.entry.N.value (value)

The query parameters (up to 10) to include in the redirect request to the authorization endpoint.

Type: String to string map

Required: No

### OnUnauthenticatedRequest

The behavior if the user is not authenticated. The following are possible values:

- deny - Return an HTTP 401 Unauthorized error.

- **allow** - Allow the request to be forwarded to the target.
- **authenticate** - Redirect the request to the IdP authorization endpoint. This is the default value.

Type: String

Valid Values: deny | allow | authenticate

Required: No

## Scope

The set of user claims to be requested from the IdP. The default is openid.

To verify which scope values your IdP supports and how to separate multiple values, see the documentation for your IdP.

Type: String

Required: No

## SessionCookieName

The name of the cookie used to maintain session information. The default is AWSELBAuthSessionCookie.

Type: String

Required: No

## SessionTimeout

The maximum duration of the authentication session, in seconds. The default is 604800 seconds (7 days).

Type: Long

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# AuthenticateOidcActionConfig

Request parameters when using an identity provider (IdP) that is compliant with OpenID Connect (OIDC) to authenticate users.

## Contents

### AuthorizationEndpoint

The authorization endpoint of the IdP. This must be a full URL, including the HTTPS protocol, the domain, and the path.

Type: String

Required: Yes

### ClientId

The OAuth 2.0 client identifier.

Type: String

Required: Yes

### Issuer

The OIDC issuer identifier of the IdP. This must be a full URL, including the HTTPS protocol, the domain, and the path.

Type: String

Required: Yes

### TokenEndpoint

The token endpoint of the IdP. This must be a full URL, including the HTTPS protocol, the domain, and the path.

Type: String

Required: Yes

### UserinfoEndpoint

The user info endpoint of the IdP. This must be a full URL, including the HTTPS protocol, the domain, and the path.

Type: String

Required: Yes

**AuthenticationRequestExtraParams** , AuthenticationRequestExtraParams.entry.N.key (key) , AuthenticationRequestExtraParams.entry.N.value (value)

The query parameters (up to 10) to include in the redirect request to the authorization endpoint.

Type: String to string map

Required: No

## ClientSecret

The OAuth 2.0 client secret. This parameter is required if you are creating a rule. If you are modifying a rule, you can omit this parameter if you set UseExistingClientSecret to true.

Type: String

Required: No

## OnUnauthenticatedRequest

The behavior if the user is not authenticated. The following are possible values:

- deny - Return an HTTP 401 Unauthorized error.
- allow - Allow the request to be forwarded to the target.
- authenticate - Redirect the request to the IdP authorization endpoint. This is the default value.

Type: String

Valid Values: deny | allow | authenticate

Required: No

## Scope

The set of user claims to be requested from the IdP. The default is openid.

To verify which scope values your IdP supports and how to separate multiple values, see the documentation for your IdP.

Type: String

Required: No

### SessionCookieName

The name of the cookie used to maintain session information. The default is AWSELBAuthSessionCookie.

Type: String

Required: No

### SessionTimeout

The maximum duration of the authentication session, in seconds. The default is 604800 seconds (7 days).

Type: Long

Required: No

### UseExistingClientSecret

Indicates whether to use the existing client secret when modifying a rule. If you are creating a rule, you can omit this parameter or set it to false.

Type: Boolean

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# AvailabilityZone

Information about an Availability Zone.

## Contents

### LoadBalancerAddresses.member.N

[Network Load Balancers] If you need static IP addresses for your load balancer, you can specify one Elastic IP address per Availability Zone when you create an internal-facing load balancer. For internal load balancers, you can specify a private IP address from the IPv4 range of the subnet.

Type: Array of [LoadBalancerAddress](#) objects

Required: No

### OutpostId

[Application Load Balancers on Outposts] The ID of the Outpost.

Type: String

Required: No

### SourceNatIpv6Prefixes.member.N

[Network Load Balancers with UDP listeners] The IPv6 prefixes to use for source NAT. For each subnet, specify an IPv6 prefix (/80 netmask) from the subnet CIDR block or auto\_assigned to use an IPv6 prefix selected at random from the subnet CIDR block.

Type: Array of strings

Required: No

### SubnetId

The ID of the subnet. You can specify one subnet per Availability Zone.

Type: String

Required: No

## ZoneName

The name of the Availability Zone.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# CapacityReservationStatus

The status of a capacity reservation.

## Contents

### Code

The status code.

Type: String

Valid Values: provisioned | pending | rebalancing | failed

Required: No

### Reason

The reason code for the status.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# Certificate

Information about an SSL server certificate.

## Contents

### **CertificateArn**

The Amazon Resource Name (ARN) of the certificate.

Type: String

Required: No

### **IsDefault**

Indicates whether the certificate is the default certificate. Do not set this value when specifying a certificate as an input. This value is not included in the output when describing a listener, but is included when describing listener certificates.

Type: Boolean

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# Cipher

Information about a cipher used in a policy.

## Contents

### Name

The name of the cipher.

Type: String

Required: No

### Priority

The priority of the cipher.

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# DescribeTrustStoreRevocation

Information about the revocations used by a trust store.

## Contents

### NumberOfRevokedEntries

The number of revoked certificates.

Type: Long

Required: No

### RevocationId

The revocation ID of a revocation file in use.

Type: Long

Required: No

### RevocationType

The type of revocation file.

Type: String

Valid Values: CRL

Required: No

### TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# FixedResponseActionConfig

Information about an action that returns a custom HTTP response.

## Contents

### StatusCode

The HTTP response code (2XX, 4XX, or 5XX).

Type: String

Pattern: ^(2|4|5)\d\d\$

Required: Yes

### ContentType

The content type.

Valid Values: text/plain | text/css | text/html | application/javascript | application/json

Type: String

Length Constraints: Minimum length of 0. Maximum length of 32.

Required: No

### MessageBody

The message.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ForwardActionConfig

Information about a forward action.

## Contents

### TargetGroups.member.N

The target groups. For Network Load Balancers, you can specify a single target group.

Type: Array of [TargetGroupTuple](#) objects

Required: No

### TargetGroupStickinessConfig

The target group stickiness for the rule.

Type: [TargetGroupStickinessConfig](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# HostHeaderConditionConfig

Information about a host header condition.

## Contents

### Values.member.N

The host names. The maximum size of each name is 128 characters. The comparison is case insensitive. The following wildcard characters are supported: \* (matches 0 or more characters) and ? (matches exactly 1 character). You must include at least one "." character. You can include only alphabetical characters after the final "." character.

If you specify multiple strings, the condition is satisfied if one of the strings matches the host name.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# HttpHeaderConditionConfig

Information about an HTTP header condition.

There is a set of standard HTTP header fields. You can also define custom HTTP header fields.

## Contents

### HttpHeaderName

The name of the HTTP header field. The maximum size is 40 characters. The header name is case insensitive. The allowed characters are specified by RFC 7230. Wildcards are not supported.

You can't use an HTTP header condition to specify the host header. Instead, use a [host condition](#).

Type: String

Required: No

### Values.member.N

The strings to compare against the value of the HTTP header. The maximum size of each string is 128 characters. The comparison strings are case insensitive. The following wildcard characters are supported: \* (matches 0 or more characters) and ? (matches exactly 1 character).

If the same header appears multiple times in the request, we search them in order until a match is found.

If you specify multiple strings, the condition is satisfied if one of the strings matches the value of the HTTP header. To require that all of the strings are a match, create one condition per string.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# HttpRequestMethodConditionConfig

Information about an HTTP method condition.

HTTP defines a set of request methods, also referred to as HTTP verbs. For more information, see the [HTTP Method Registry](#). You can also define custom HTTP methods.

## Contents

### Values.member.N

The name of the request method. The maximum size is 40 characters. The allowed characters are A-Z, hyphen (-), and underscore (\_). The comparison is case sensitive. Wildcards are not supported; therefore, the method name must be an exact match.

If you specify multiple strings, the condition is satisfied if one of the strings matches the HTTP request method. We recommend that you route GET and HEAD requests in the same way, because the response to a HEAD request may be cached.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# IpamPools

An IPAM pool is a collection of IP address CIDRs. IPAM pools enable you to organize your IP addresses according to your routing and security needs.

## Contents

### Ipv4IpamPoolId

The ID of the IPv4 IPAM pool.

Type: String

Length Constraints: Maximum length of 1000.

Pattern: ^(ipam-pool-)[a-zA-Z0-9]+\$

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# Limit

Information about an Elastic Load Balancing resource limit for your Amazon account.

For more information, see the following:

- [Quotas for your Application Load Balancers](#)
- [Quotas for your Network Load Balancers](#)
- [Quotas for your Gateway Load Balancers](#)

## Contents

### Max

The maximum value of the limit.

Type: String

Required: No

### Name

The name of the limit. The possible values are:

- application-load-balancers
- condition-values-per-alb-rule
- condition-wildcards-per-alb-rule
- gateway-load-balancers
- gateway-load-balancers-per-vpc
- geneve-target-groups
- listeners-per-application-load-balancer
- listeners-per-network-load-balancer
- network-load-balancers
- rules-per-application-load-balancer
- target-groups
- target-groups-per-action-on-application-load-balancer
- target-groups-per-action-on-network-load-balancer

- target-groups-per-application-load-balancer
- targets-per-application-load-balancer
- targets-per-availability-zone-per-gateway-load-balancer
- targets-per-availability-zone-per-network-load-balancer
- targets-per-network-load-balancer

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# Listener

Information about a listener.

## Contents

### **AlpnPolicy.member.N**

[TLS listener] The name of the Application-Layer Protocol Negotiation (ALPN) policy.

Type: Array of strings

Required: No

### **Certificates.member.N**

[HTTPS or TLS listener] The default certificate for the listener.

Type: Array of [Certificate](#) objects

Required: No

### **DefaultActions.member.N**

The default actions for the listener.

Type: Array of [Action](#) objects

Required: No

### **ListenerArn**

The Amazon Resource Name (ARN) of the listener.

Type: String

Required: No

### **LoadBalancerArn**

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: No

## MutualAuthentication

The mutual authentication configuration information.

Type: [MutualAuthenticationAttributes](#) object

Required: No

## Port

The port on which the load balancer is listening.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

## Protocol

The protocol for connections from clients to the load balancer.

Type: String

Valid Values: HTTP | HTTPS | TCP | TLS | UDP | TCP\_UDP | GENEVE

Required: No

## SslPolicy

[HTTPS or TLS listener] The security policy that defines which protocols and ciphers are supported.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

# ListenerAttribute

Information about a listener attribute.

## Contents

### Key

The name of the attribute.

The following attribute is supported by Network Load Balancers, and Gateway Load Balancers.

- `tcp.idle_timeout.seconds` - The tcp idle timeout value, in seconds. The valid range is 60-6000 seconds. The default is 350 seconds.

The following attributes are only supported by Application Load Balancers.

- `routing.http.request.x_amzn_mtls_clientcert_serial_number.header_name` - Enables you to modify the header name of the **X-Amzn-Mtls-Clientcert-Serial-Number** HTTP request header.
- `routing.http.request.x_amzn_mtls_clientcert_issuer.header_name` - Enables you to modify the header name of the **X-Amzn-Mtls-Clientcert-Issuer** HTTP request header.
- `routing.http.request.x_amzn_mtls_clientcert_subject.header_name` - Enables you to modify the header name of the **X-Amzn-Mtls-Clientcert-Subject** HTTP request header.
- `routing.http.request.x_amzn_mtls_clientcert_validity.header_name` - Enables you to modify the header name of the **X-Amzn-Mtls-Clientcert-Validity** HTTP request header.
- `routing.http.request.x_amzn_mtls_clientcert_leaf.header_name` - Enables you to modify the header name of the **X-Amzn-Mtls-Clientcert-Leaf** HTTP request header.
- `routing.http.request.x_amzn_mtls_clientcert.header_name` - Enables you to modify the header name of the **X-Amzn-Mtls-Clientcert** HTTP request header.
- `routing.http.request.x_amzn_tls_version.header_name` - Enables you to modify the header name of the **X-Amzn-Tls-Version** HTTP request header.
- `routing.http.request.x_amzn_tls_cipher_suite.header_name` - Enables you to modify the header name of the **X-Amzn-Tls-Cipher-Suite** HTTP request header.
- `routing.http.response.server.enabled` - Enables you to allow or remove the HTTP response server header.

- `routing.http.response.strict_transport_security.header_value` - Informs browsers that the site should only be accessed using HTTPS, and that any future attempts to access it using HTTP should automatically be converted to HTTPS.
- `routing.http.response.access_control_allow_origin.header_value` - Specifies which origins are allowed to access the server.
- `routing.http.response.access_control_allow_methods.header_value` - Returns which HTTP methods are allowed when accessing the server from a different origin.
- `routing.http.response.access_control_allow_headers.header_value` - Specifies which headers can be used during the request.
- `routing.http.response.access_control_allow_credentials.header_value` - Indicates whether the browser should include credentials such as cookies or authentication when making requests.
- `routing.http.response.access_control_expose_headers.header_value` - Returns which headers the browser can expose to the requesting client.
- `routing.http.response.access_control_max_age.header_value` - Specifies how long the results of a preflight request can be cached, in seconds.
- `routing.http.response.content_security_policy.header_value` - Specifies restrictions enforced by the browser to help minimize the risk of certain types of security threats.
- `routing.http.response.x_content_type_options.header_value` - Indicates whether the MIME types advertised in the **Content-Type** headers should be followed and not be changed.
- `routing.http.response.x_frame_options.header_value` - Indicates whether the browser is allowed to render a page in a **frame**, **iframe**, **embed** or **object**.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `^[a-zA-Z0-9._]+$`

Required: No

## Value

The value of the attribute.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# LoadBalancer

Information about a load balancer.

## Contents

### AvailabilityZones.member.N

The subnets for the load balancer.

Type: Array of [AvailabilityZone](#) objects

Required: No

### CanonicalHostedZoneId

The ID of the Amazon Route 53 hosted zone associated with the load balancer.

Type: String

Required: No

### CreatedTime

The date and time the load balancer was created.

Type: Timestamp

Required: No

### CustomerOwnedIpv4Pool

[Application Load Balancers on Outposts] The ID of the customer-owned address pool.

Type: String

Length Constraints: Maximum length of 256.

Pattern: ^(ipv4pool-coip-)[a-zA-Z0-9]+\$

Required: No

### DNSName

The public DNS name of the load balancer.

Type: String

Required: No

### **EnablePrefixForIpv6SourceNat**

[Network Load Balancers with UDP listeners] Indicates whether to use an IPv6 prefix from each subnet for source NAT. The IP address type must be dualstack. The default value is off.

Type: String

Valid Values: on | off

Required: No

### **EnforceSecurityGroupInboundRulesOnPrivateLinkTraffic**

Indicates whether to evaluate inbound security group rules for traffic sent to a Network Load Balancer through Amazon PrivateLink.

Type: String

Required: No

### **IpAddressType**

The type of IP addresses used for public or private connections by the subnets attached to your load balancer.

[Application Load Balancers] The possible values are ipv4 (IPv4 addresses), dualstack (IPv4 and IPv6 addresses), and dualstack-without-public-ipv4 (public IPv6 addresses and private IPv4 and IPv6 addresses).

[Network Load Balancers and Gateway Load Balancers] The possible values are ipv4 (IPv4 addresses) and dualstack (IPv4 and IPv6 addresses).

Type: String

Valid Values: ipv4 | dualstack | dualstack-without-public-ipv4

Required: No

### **IpamPools**

[Application Load Balancers] The IPAM pool in use by the load balancer, if configured.

Type: [IpamPools](#) object

Required: No

### **LoadBalancerArn**

The Amazon Resource Name (ARN) of the load balancer.

Type: String

Required: No

### **LoadBalancerName**

The name of the load balancer.

Type: String

Required: No

### **Scheme**

The nodes of an Internet-facing load balancer have public IP addresses. The DNS name of an Internet-facing load balancer is publicly resolvable to the public IP addresses of the nodes. Therefore, Internet-facing load balancers can route requests from clients over the internet.

The nodes of an internal load balancer have only private IP addresses. The DNS name of an internal load balancer is publicly resolvable to the private IP addresses of the nodes. Therefore, internal load balancers can route requests only from clients with access to the VPC for the load balancer.

Type: String

Valid Values: `internet-facing` | `internal`

Required: No

### **SecurityGroups.member.N**

The IDs of the security groups for the load balancer.

Type: Array of strings

Required: No

## State

The state of the load balancer.

Type: [LoadBalancerState](#) object

Required: No

## Type

The type of load balancer.

Type: String

Valid Values: application | network | gateway

Required: No

## VpcId

The ID of the VPC for the load balancer.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# LoadBalancerAddress

Information about a static IP address for a load balancer.

## Contents

### AllocationId

[Network Load Balancers] The allocation ID of the Elastic IP address for an internal-facing load balancer.

Type: String

Required: No

### IpAddress

The static IP address.

Type: String

Required: No

### IPv6Address

[Network Load Balancers] The IPv6 address.

Type: String

Required: No

### PrivateIpv4Address

[Network Load Balancers] The private IPv4 address for an internal load balancer.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# LoadBalancerAttribute

Information about a load balancer attribute.

## Contents

### Key

The name of the attribute.

The following attributes are supported by all load balancers:

- `deletion_protection.enabled` - Indicates whether deletion protection is enabled. The value is `true` or `false`. The default is `false`.
- `load_balancing.cross_zone.enabled` - Indicates whether cross-zone load balancing is enabled. The possible values are `true` and `false`. The default for Network Load Balancers and Gateway Load Balancers is `false`. The default for Application Load Balancers is `true`, and can't be changed.

The following attributes are supported by both Application Load Balancers and Network Load Balancers:

- `access_logs.s3.enabled` - Indicates whether access logs are enabled. The value is `true` or `false`. The default is `false`.
- `access_logs.s3.bucket` - The name of the S3 bucket for the access logs. This attribute is required if access logs are enabled. The bucket must exist in the same region as the load balancer and have a bucket policy that grants Elastic Load Balancing permissions to write to the bucket.
- `access_logs.s3.prefix` - The prefix for the location in the S3 bucket for the access logs.
- `ipv6.deny_all_igw_traffic` - Blocks internet gateway (IGW) access to the load balancer. It is set to `false` for internet-facing load balancers and `true` for internal load balancers, preventing unintended access to your internal load balancer through an internet gateway.
- `zonal_shift.config.enabled` - Indicates whether zonal shift is enabled. The possible values are `true` and `false`. The default is `false`.

The following attributes are supported by only Application Load Balancers:

- `idle_timeout.timeout_seconds` - The idle timeout value, in seconds. The valid range is 1-4000 seconds. The default is 60 seconds.

- `client_keep_alive.seconds` - The client keep alive value, in seconds. The valid range is 60-604800 seconds. The default is 3600 seconds.
- `connection_logs.s3.enabled` - Indicates whether connection logs are enabled. The value is true or false. The default is false.
- `connection_logs.s3.bucket` - The name of the S3 bucket for the connection logs. This attribute is required if connection logs are enabled. The bucket must exist in the same region as the load balancer and have a bucket policy that grants Elastic Load Balancing permissions to write to the bucket.
- `connection_logs.s3.prefix` - The prefix for the location in the S3 bucket for the connection logs.
- `routing.http.desync_mitigation_mode` - Determines how the load balancer handles requests that might pose a security risk to your application. The possible values are monitor, defensive, and strictest. The default is defensive.
- `routing.http.drop_invalid_header_fields.enabled` - Indicates whether HTTP headers with invalid header fields are removed by the load balancer (true) or routed to targets (false). The default is false.
- `routing.http.preserve_host_header.enabled` - Indicates whether the Application Load Balancer should preserve the Host header in the HTTP request and send it to the target without any change. The possible values are true and false. The default is false.
- `routing.http.x_amzn_tls_version_and_cipher_suite.enabled` - Indicates whether the two headers (x-amzn-tls-version and x-amzn-tls-cipher-suite), which contain information about the negotiated TLS version and cipher suite, are added to the client request before sending it to the target. The x-amzn-tls-version header has information about the TLS protocol version negotiated with the client, and the x-amzn-tls-cipher-suite header has information about the cipher suite negotiated with the client. Both headers are in OpenSSL format. The possible values for the attribute are true and false. The default is false.
- `routing.http.xff_client_port.enabled` - Indicates whether the X-Forwarded-For header should preserve the source port that the client used to connect to the load balancer. The possible values are true and false. The default is false.
- `routing.http.xff_header_processing.mode` - Enables you to modify, preserve, or remove the X-Forwarded-For header in the HTTP request before the Application Load Balancer sends the request to the target. The possible values are append, preserve, and remove. The default is append.

- If the value is `append`, the Application Load Balancer adds the client IP address (of the last hop) to the `X-Forwarded-For` header in the HTTP request before it sends it to targets.
  - If the value is `preserve` the Application Load Balancer preserves the `X-Forwarded-For` header in the HTTP request, and sends it to targets without any change.
  - If the value is `remove`, the Application Load Balancer removes the `X-Forwarded-For` header in the HTTP request before it sends it to targets.
- `routing.http2.enabled` - Indicates whether HTTP/2 is enabled. The possible values are `true` and `false`. The default is `true`. Elastic Load Balancing requires that message header names contain only alphanumeric characters and hyphens.
  - `waf.fail_open.enabled` - Indicates whether to allow a WAF-enabled load balancer to route requests to targets if it is unable to forward the request to Amazon WAF. The possible values are `true` and `false`. The default is `false`.

The following attributes are supported by only Network Load Balancers:

- `dns_record.client_routing_policy` - Indicates how traffic is distributed among the load balancer Availability Zones. The possible values are `availability_zone_affinity` with 100 percent zonal affinity, `partial_availability_zone_affinity` with 85 percent zonal affinity, and `any_availability_zone` with 0 percent zonal affinity.

Type: String

Length Constraints: Maximum length of 256.

Pattern: `^[a-zA-Z0-9._]+$`

Required: No

## Value

The value of the attribute.

Type: String

Length Constraints: Maximum length of 1024.

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# LoadBalancerState

Information about the state of the load balancer.

## Contents

### Code

The state code. The initial state of the load balancer is provisioning. After the load balancer is fully set up and ready to route traffic, its state is active. If load balancer is routing traffic but does not have the resources it needs to scale, its state is active\_impaired. If the load balancer could not be set up, its state is failed.

Type: String

Valid Values: active | provisioning | active\_impaired | failed

Required: No

### Reason

A description of the state.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# Matcher

The codes to use when checking for a successful response from a target. If the protocol version is gRPC, these are gRPC codes. Otherwise, these are HTTP codes.

## Contents

### GrpcCode

You can specify values between 0 and 99. You can specify multiple values (for example, "0,1") or a range of values (for example, "0-5"). The default value is 12.

Type: String

Required: No

### HttpCode

For Application Load Balancers, you can specify values between 200 and 499, with the default value being 200. You can specify multiple values (for example, "200,202") or a range of values (for example, "200-299").

For Network Load Balancers, you can specify values between 200 and 599, with the default value being 200-399. You can specify multiple values (for example, "200,202") or a range of values (for example, "200-299").

For Gateway Load Balancers, this must be "200–399".

Note that when using shorthand syntax, some values such as commas need to be escaped.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

# MinimumLoadBalancerCapacity

The minimum capacity for a load balancer.

## Contents

### CapacityUnits

The number of capacity units.

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# MutualAuthenticationAttributes

Information about the mutual authentication attributes of a listener.

## Contents

### AdvertiseTrustStoreCaNames

Indicates whether trust store CA certificate names are advertised.

Type: String

Valid Values: on | off

Required: No

### IgnoreClientCertificateExpiry

Indicates whether expired client certificates are ignored.

Type: Boolean

Required: No

### Mode

The client certificate handling method. Options are off, passthrough or verify. The default value is off.

Type: String

Required: No

### TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: No

### TrustStoreAssociationStatus

Indicates a shared trust stores association status.

Type: String

Valid Values: active | removed

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# PathPatternConditionConfig

Information about a path pattern condition.

## Contents

### Values.member.N

The path patterns to compare against the request URL. The maximum size of each string is 128 characters. The comparison is case sensitive. The following wildcard characters are supported: \* (matches 0 or more characters) and ? (matches exactly 1 character).

If you specify multiple strings, the condition is satisfied if one of them matches the request URL. The path pattern is compared only to the path of the URL, not to its query string. To compare against the query string, use a [query string condition](#).

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# QueryStringConditionConfig

Information about a query string condition.

The query string component of a URI starts after the first '?' character and is terminated by either a '#' character or the end of the URI. A typical query string contains key/value pairs separated by '&' characters. The allowed characters are specified by RFC 3986. Any character can be percentage encoded.

## Contents

### Values.member.N

The key/value pairs or values to find in the query string. The maximum size of each string is 128 characters. The comparison is case insensitive. The following wildcard characters are supported: \* (matches 0 or more characters) and ? (matches exactly 1 character). To search for a literal '\*' or '?' character in a query string, you must escape these characters in Values using a '\' character.

If you specify multiple key/value pairs or values, the condition is satisfied if one of them is found in the query string.

Type: Array of [QueryStringKeyValuePair](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# QueryStringKeyValuePair

Information about a key/value pair.

## Contents

### Key

The key. You can omit the key.

Type: String

Required: No

### Value

The value.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RedirectActionConfig

Information about a redirect action.

A URI consists of the following components: protocol://hostname:port/path?query. You must modify at least one of the following components to avoid a redirect loop: protocol, hostname, port, or path. Any components that you do not modify retain their original values.

You can reuse URI components using the following reserved keywords:

- #{protocol}
- #{host}
- #{port}
- #{path} (the leading "/" is removed)
- #{query}

For example, you can change the path to "/new/#{path}", the hostname to "example.#{host}", or the query to "#{query}&value=xyz".

## Contents

### Status Code

The HTTP redirect code. The redirect is either permanent (HTTP 301) or temporary (HTTP 302).

Type: String

Valid Values: HTTP\_301 | HTTP\_302

Required: Yes

### Host

The hostname. This component is not percent-encoded. The hostname can contain #{host}.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

## Path

The absolute path, starting with the leading "/". This component is not percent-encoded. The path can contain #{host}, #{path}, and #{port}.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

## Port

The port. You can specify a value from 1 to 65535 or #{port}.

Type: String

Required: No

## Protocol

The protocol. You can specify HTTP, HTTPS, or #{protocol}. You can redirect HTTP to HTTP, HTTP to HTTPS, and HTTPS to HTTPS. You can't redirect HTTPS to HTTP.

Type: String

Pattern: ^(HTTPS?|#{protocol}\})\$

Required: No

## Query

The query parameters, URL-encoded when necessary, but not percent-encoded. Do not include the leading "?", as it is automatically added. You can specify any of the reserved keywords.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RevocationContent

Information about a revocation file.

## Contents

### RevocationType

The type of revocation file.

Type: String

Valid Values: CRL

Required: No

### S3Bucket

The Amazon S3 bucket for the revocation file.

Type: String

Required: No

### S3Key

The Amazon S3 path for the revocation file.

Type: String

Required: No

### S3ObjectVersion

The Amazon S3 object version of the revocation file.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# Rule

Information about a rule.

## Contents

### **Actions.member.N**

The actions. Each rule must include exactly one of the following types of actions: forward, redirect, or fixed-response, and it must be the last action to be performed.

Type: Array of [Action](#) objects

Required: No

### **Conditions.member.N**

The conditions. Each rule can include zero or one of the following conditions: http-request-method, host-header, path-pattern, and source-ip, and zero or more of the following conditions: http-header and query-string.

Type: Array of [RuleCondition](#) objects

Required: No

### **IsDefault**

Indicates whether this is the default rule.

Type: Boolean

Required: No

### **Priority**

The priority.

Type: String

Required: No

### **RuleArn**

The Amazon Resource Name (ARN) of the rule.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RuleCondition

Information about a condition for a rule.

Each rule can optionally include up to one of each of the following conditions: `http-request-method`, `host-header`, `path-pattern`, and `source-ip`. Each rule can also optionally include one or more of each of the following conditions: `http-header` and `query-string`. Note that the value for a condition can't be empty.

For more information, see [Quotas for your Application Load Balancers](#).

## Contents

### Field

The field in the HTTP request. The following are the possible values:

- `http-header`
- `http-request-method`
- `host-header`
- `path-pattern`
- `query-string`
- `source-ip`

Type: String

Length Constraints: Maximum length of 64.

Required: No

### HostHeaderConfig

Information for a host header condition. Specify only when Field is `host-header`.

Type: [HostHeaderConditionConfig](#) object

Required: No

### HttpHeaderConfig

Information for an HTTP header condition. Specify only when Field is `http-header`.

Type: [HttpHeaderConditionConfig](#) object

Required: No

## HttpRequestMethodConfig

Information for an HTTP method condition. Specify only when Field is http-request-method.

Type: [HttpRequestMethodConditionConfig](#) object

Required: No

## PathPatternConfig

Information for a path pattern condition. Specify only when Field is path-pattern.

Type: [PathPatternConditionConfig](#) object

Required: No

## QueryStringConfig

Information for a query string condition. Specify only when Field is query-string.

Type: [QueryStringConditionConfig](#) object

Required: No

## SourcelpConfig

Information for a source IP condition. Specify only when Field is source-ip.

Type: [SourcelpConditionConfig](#) object

Required: No

## Values.member.N

The condition value. Specify only when Field is host-header or path-pattern.

Alternatively, to specify multiple host names or multiple path patterns, use HostHeaderConfig or PathPatternConfig.

If Field is host-header and you are not using HostHeaderConfig, you can specify a single host name (for example, my.example.com) in Values. A host name is case insensitive, can be up to 128 characters in length, and can contain any of the following characters.

- A-Z, a-z, 0-9
- - .
- \* (matches 0 or more characters)
- ? (matches exactly 1 character)

If `Field` is `path-pattern` and you are not using `PathPatternConfig`, you can specify a single path pattern (for example, `/img/*`) in `Values`. A path pattern is case-sensitive, can be up to 128 characters in length, and can contain any of the following characters.

- A-Z, a-z, 0-9
- \_ - . \$ / ~ " ' @ : +
- & (using &amp;)
- \* (matches 0 or more characters)
- ? (matches exactly 1 character)

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# RulePriorityPair

Information about the priorities for the rules for a listener.

## Contents

### Priority

The rule priority.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50000.

Required: No

### RuleArn

The Amazon Resource Name (ARN) of the rule.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# SourcelpConditionConfig

Information about a source IP condition.

You can use this condition to route based on the IP address of the source that connects to the load balancer. If a client is behind a proxy, this is the IP address of the proxy not the IP address of the client.

## Contents

### Values.member.N

The source IP addresses, in CIDR format. You can use both IPv4 and IPv6 addresses. Wildcards are not supported.

If you specify multiple addresses, the condition is satisfied if the source IP address of the request matches one of the CIDR blocks. This condition is not satisfied by the addresses in the X-Forwarded-For header. To search for addresses in the X-Forwarded-For header, use an [HTTP header condition](#).

The total number of values must be less than, or equal to five.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# SslPolicy

Information about a policy used for SSL negotiation.

## Contents

### Ciphers.member.N

The ciphers.

Type: Array of [Cipher](#) objects

Required: No

### Name

The name of the policy.

Type: String

Required: No

### SslProtocols.member.N

The protocols.

Type: Array of strings

Required: No

### SupportedLoadBalancerTypes.member.N

The supported load balancers.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# SubnetMapping

Information about a subnet mapping.

## Contents

### AllocationId

[Network Load Balancers] The allocation ID of the Elastic IP address for an internet-facing load balancer.

Type: String

Required: No

### IPv6Address

[Network Load Balancers] The IPv6 address.

Type: String

Required: No

### PrivateIpv4Address

[Network Load Balancers] The private IPv4 address for an internal load balancer.

Type: String

Required: No

### SourceNatIpv6Prefix

[Network Load Balancers with UDP listeners] The IPv6 prefix to use for source NAT. Specify an IPv6 prefix (/80 netmask) from the subnet CIDR block or auto\_assigned to use an IPv6 prefix selected at random from the subnet CIDR block.

Type: String

Required: No

### SubnetId

The ID of the subnet.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# Tag

Information about a tag.

## Contents

### Key

The key of the tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/-@]*)$`

Required: Yes

### Value

The value of the tag.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/-@]*)$`

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# TagDescription

The tags associated with a resource.

## Contents

### ResourceArn

The Amazon Resource Name (ARN) of the resource.

Type: String

Required: No

### Tags.member.N

Information about the tags.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item.

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# TargetDescription

Information about a target.

## Contents

### **Id**

The ID of the target. If the target type of the target group is `instance`, specify an instance ID. If the target type is `ip`, specify an IP address. If the target type is `lambda`, specify the ARN of the Lambda function. If the target type is `alb`, specify the ARN of the Application Load Balancer target.

Type: String

Required: Yes

### **AvailabilityZone**

An Availability Zone or `all`. This determines whether the target receives traffic from the load balancer nodes in the specified Availability Zone or from all enabled Availability Zones for the load balancer.

For Application Load Balancer target groups, the specified Availability Zone value is only applicable when cross-zone load balancing is off. Otherwise the parameter is ignored and treated as `all`.

This parameter is not supported if the target type of the target group is `instance` or `alb`.

If the target type is `ip` and the IP address is in a subnet of the VPC for the target group, the Availability Zone is automatically detected and this parameter is optional. If the IP address is outside the VPC, this parameter is required.

For Application Load Balancer target groups with cross-zone load balancing off, if the target type is `ip` and the IP address is outside of the VPC for the target group, this should be an Availability Zone inside the VPC for the target group.

If the target type is `lambda`, this parameter is optional and the only supported value is `all`.

Type: String

Required: No

## Port

The port on which the target is listening. If the target group protocol is GENEVE, the supported port is 6081. If the target type is alb, the targeted Application Load Balancer must have at least one listener whose port matches the target group port. This parameter is not used if the target is a Lambda function.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# TargetGroup

Information about a target group.

## Contents

### HealthCheckEnabled

The value indicates whether health checks are enabled.

Type: Boolean

Required: No

### HealthCheckIntervalSeconds

The approximate amount of time, in seconds, between health checks of an individual target.

Type: Integer

Valid Range: Minimum value of 5. Maximum value of 300.

Required: No

### HealthCheckPath

The destination for health checks on the targets.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

### HealthCheckPort

The port to use to connect with the target.

Type: String

Required: No

### HealthCheckProtocol

The protocol to use to connect with the target. The GENEVE, TLS, UDP, and TCP\_UDP protocols are not supported for health checks.

Type: String

Valid Values: HTTP | HTTPS | TCP | TLS | UDP | TCP\_UDP | GENEVE

Required: No

### **HealthCheckTimeoutSeconds**

The amount of time, in seconds, during which no response means a failed health check.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 120.

Required: No

### **HealthyThresholdCount**

The number of consecutive health checks successes required before considering an unhealthy target healthy.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 10.

Required: No

### **IpAddressType**

The IP address type. The default value is `ipv4`.

Type: String

Valid Values: `ipv4` | `ipv6`

Required: No

### **LoadBalancerArns.member.N**

The Amazon Resource Name (ARN) of the load balancer that routes traffic to this target group. You can use each target group with only one load balancer.

Type: Array of strings

Required: No

## Matcher

The HTTP or gRPC codes to use when checking for a successful response from a target.

Type: [Matcher](#) object

Required: No

## Port

The port on which the targets are listening. This parameter is not used if the target is a Lambda function.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

## Protocol

The protocol to use for routing traffic to the targets.

Type: String

Valid Values: HTTP | HTTPS | TCP | TLS | UDP | TCP\_UDP | GENEVE

Required: No

## ProtocolVersion

[HTTP/HTTPS protocol] The protocol version. The possible values are GRPC, HTTP1, and HTTP2.

Type: String

Required: No

## TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: No

## TargetGroupName

The name of the target group.

Type: String

Required: No

### TargetType

The type of target that you must specify when registering targets with this target group.

The possible values are `instance` (register targets by instance ID), `ip` (register targets by IP address), `lambda` (register a single Lambda function as a target), or `alb` (register a single Application Load Balancer as a target).

Type: String

Valid Values: `instance` | `ip` | `lambda` | `alb`

Required: No

### UnhealthyThresholdCount

The number of consecutive health check failures required before considering the target unhealthy.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 10.

Required: No

### VpcId

The ID of the VPC for the targets.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

# TargetGroupAttribute

Information about a target group attribute.

## Contents

### Key

The name of the attribute.

The following attributes are supported by all load balancers:

- `deregistration_delay.timeout_seconds` - The amount of time, in seconds, for Elastic Load Balancing to wait before changing the state of a deregistering target from `draining` to `unused`. The range is 0-3600 seconds. The default value is 300 seconds. If the target is a Lambda function, this attribute is not supported.
- `stickiness.enabled` - Indicates whether target stickiness is enabled. The value is `true` or `false`. The default is `false`.
- `stickiness.type` - Indicates the type of stickiness. The possible values are:
  - `lb_cookie` and `app_cookie` for Application Load Balancers.
  - `source_ip` for Network Load Balancers.
  - `source_ip_dest_ip` and `source_ip_dest_ip_proto` for Gateway Load Balancers.

The following attributes are supported by Application Load Balancers and Network Load Balancers:

- `load_balancing.cross_zone.enabled` - Indicates whether cross zone load balancing is enabled. The value is `true`, `false` or `use_load_balancer_configuration`. The default is `use_load_balancer_configuration`.
- `target_group_health.dns_failover.minimum_healthy_targets.count` - The minimum number of targets that must be healthy. If the number of healthy targets is below this value, mark the zone as unhealthy in DNS, so that traffic is routed only to healthy zones. The possible values are `off` or an integer from 1 to the maximum number of targets. The default is 1.
- `target_group_health.dns_failover.minimum_healthy_targets.percentage` - The minimum percentage of targets that must be healthy. If the percentage of healthy targets is below this value, mark the zone as unhealthy in DNS, so that traffic is routed only to healthy zones. The possible values are `off` or an integer from 1 to 100. The default is `off`.

- `target_group_health.unhealthy_state_routing.minimum_healthy_targets.count`  
- The minimum number of targets that must be healthy. If the number of healthy targets is below this value, send traffic to all targets, including unhealthy targets. The possible values are 1 to the maximum number of targets. The default is 1.
- `target_group_health.unhealthy_state_routing.minimum_healthy_targets.percent`  
- The minimum percentage of targets that must be healthy. If the percentage of healthy targets is below this value, send traffic to all targets, including unhealthy targets. The possible values are off or an integer from 1 to 100. The default is off.

The following attributes are supported only if the load balancer is an Application Load Balancer and the target is an instance or an IP address:

- `load_balancing.algorithm.type` - The load balancing algorithm determines how the load balancer selects targets when routing requests. The value is `round_robin`, `least_outstanding_requests`, or `weighted_random`. The default is `round_robin`.
- `load_balancing.algorithm.anomaly_mitigation` - Only available when `load_balancing.algorithm.type` is `weighted_random`. Indicates whether anomaly mitigation is enabled. The value is on or off. The default is off.
- `slow_start.duration_seconds` - The time period, in seconds, during which a newly registered target receives an increasing share of the traffic to the target group. After this time period ends, the target receives its full share of traffic. The range is 30-900 seconds (15 minutes). The default is 0 seconds (disabled).
- `stickiness.app_cookie.cookie_name` - Indicates the name of the application-based cookie. Names that start with the following prefixes are not allowed: AWSALB, AWSALBAPP, and AWSALBTG; they're reserved for use by the load balancer.
- `stickiness.app_cookie.duration_seconds` - The time period, in seconds, during which requests from a client should be routed to the same target. After this time period expires, the application-based cookie is considered stale. The range is 1 second to 1 week (604800 seconds). The default value is 1 day (86400 seconds).
- `stickiness.lb_cookie.duration_seconds` - The time period, in seconds, during which requests from a client should be routed to the same target. After this time period expires, the load balancer-generated cookie is considered stale. The range is 1 second to 1 week (604800 seconds). The default value is 1 day (86400 seconds).

The following attribute is supported only if the load balancer is an Application Load Balancer and the target is a Lambda function:

- `lambda.multi_value_headers.enabled` - Indicates whether the request and response headers that are exchanged between the load balancer and the Lambda function include arrays of values or strings. The value is true or false. The default is false. If the value is false and the request contains a duplicate header field name or query parameter key, the load balancer uses the last value sent by the client.

The following attributes are supported only by Network Load Balancers:

- `deregistration_delay.connection_termination.enabled` - Indicates whether the load balancer terminates connections at the end of the deregistration timeout. The value is true or false. For new UDP/TCP\_UDP target groups the default is true. Otherwise, the default is false.
- `preserve_client_ip.enabled` - Indicates whether client IP preservation is enabled. The value is true or false. The default is disabled if the target group type is IP address and the target group protocol is TCP or TLS. Otherwise, the default is enabled. Client IP preservation can't be disabled for UDP and TCP\_UDP target groups.
- `proxy_protocol_v2.enabled` - Indicates whether Proxy Protocol version 2 is enabled. The value is true or false. The default is false.
- `target_health_state.unhealthy.connection_termination.enabled` - Indicates whether the load balancer terminates connections to unhealthy targets. The value is true or false. The default is true. This attribute can't be enabled for UDP and TCP\_UDP target groups.
- `target_health_state.unhealthy.draining_interval_seconds` - The amount of time for Elastic Load Balancing to wait before changing the state of an unhealthy target from unhealthy.draining to unhealthy. The range is 0-360000 seconds. The default value is 0 seconds.

Note: This attribute can only be configured when

`target_health_state.unhealthy.connection_termination.enabled` is false.

The following attributes are supported only by Gateway Load Balancers:

- `target_failover.on_deregistration` - Indicates how the Gateway Load Balancer handles existing flows when a target is deregistered. The possible values are rebalance and no\_rebalance. The default is no\_rebalance. The two attributes (`target_failover.on_deregistration` and `target_failover.on_unhealthy`) can't be set independently. The value you set for both attributes must be the same.

- **target\_failover.on\_unhealthy** - Indicates how the Gateway Load Balancer handles existing flows when a target is unhealthy. The possible values are rebalance and no\_rebalance. The default is no\_rebalance. The two attributes (target\_failover.on\_deregistration and target\_failover.on\_unhealthy) can't be set independently. The value you set for both attributes must be the same.

Type: String

Length Constraints: Maximum length of 256.

Pattern: ^[a-zA-Z0-9.\_]+\$

Required: No

## Value

The value of the attribute.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# TargetGroupStickinessConfig

Information about the target group stickiness for a rule.

## Contents

### DurationSeconds

The time period, in seconds, during which requests from a client should be routed to the same target group. The range is 1-604800 seconds (7 days). You must specify this value when enabling target group stickiness.

Type: Integer

Required: No

### Enabled

Indicates whether target group stickiness is enabled.

Type: Boolean

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# TargetGroupTuple

Information about how traffic will be distributed between multiple target groups in a forward rule.

## Contents

### TargetGroupArn

The Amazon Resource Name (ARN) of the target group.

Type: String

Required: No

### Weight

The weight. The range is 0 to 999.

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# TargetHealth

Information about the current health of a target.

## Contents

### Description

A description of the target health that provides additional details. If the state is healthy, a description is not provided.

Type: String

Required: No

### Reason

The reason code.

If the target state is healthy, a reason code is not provided.

If the target state is initial, the reason code can be one of the following values:

- Elb.RegistrationInProgress - The target is in the process of being registered with the load balancer.
- Elb.InitialHealthChecking - The load balancer is still sending the target the minimum number of health checks required to determine its health status.

If the target state is unhealthy, the reason code can be one of the following values:

- Target.ResponseCodeMismatch - The health checks did not return an expected HTTP code. Applies only to Application Load Balancers and Gateway Load Balancers.
- Target.Timeout - The health check requests timed out. Applies only to Application Load Balancers and Gateway Load Balancers.
- Target.FailedHealthChecks - The load balancer received an error while establishing a connection to the target or the target response was malformed.
- Elb.InternalError - The health checks failed due to an internal error. Applies only to Application Load Balancers.

If the target state is unused, the reason code can be one of the following values:

- Target.NotRegistered - The target is not registered with the target group.

- `Target.NotInUse` - The target group is not used by any load balancer or the target is in an Availability Zone that is not enabled for its load balancer.
- `Target.InvalidState` - The target is in the stopped or terminated state.
- `Target.IpUnusable` - The target IP address is reserved for use by a load balancer.

If the target state is draining, the reason code can be the following value:

- `Target.DeregistrationInProgress` - The target is in the process of being deregistered and the deregistration delay period has not expired.

If the target state is unavailable, the reason code can be the following value:

- `Target.HealthCheckDisabled` - Health checks are disabled for the target group. Applies only to Application Load Balancers.
- `Elb.InternalError` - Target health is unavailable due to an internal error. Applies only to Network Load Balancers.

Type: String

Valid Values: `Elb.RegistrationInProgress` | `Elb.InitialHealthChecking` | `Target.ResponseCodeMismatch` | `Target.Timeout` | `Target.FailedHealthChecks` | `Target.NotRegistered` | `Target.NotInUse` | `Target.DeregistrationInProgress` | `Target.InvalidState` | `Target.IpUnusable` | `Target.HealthCheckDisabled` | `Elb.InternalError`

Required: No

## State

The state of the target.

Type: String

Valid Values: `initial` | `healthy` | `unhealthy` | `unhealthy.draining` | `unused` | `draining` | `unavailable`

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# TargetHealthDescription

Information about the health of a target.

## Contents

### AdministrativeOverride

The administrative override information for the target.

Type: [AdministrativeOverride](#) object

Required: No

### AnomalyDetection

The anomaly detection result for the target.

If no anomalies were detected, the result is normal.

If anomalies were detected, the result is anomalous.

Type: [AnomalyDetection](#) object

Required: No

### HealthCheckPort

The port to use to connect with the target.

Type: String

Required: No

### Target

The description of the target.

Type: [TargetDescription](#) object

Required: No

### TargetHealth

The health information for the target.

Type: [TargetHealth](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# TrustStore

Information about a trust store.

## Contents

### Name

The name of the trust store.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: ^([a-zA-Z0-9]+-)\*[a-zA-Z0-9]+\\$

Required: No

### NumberOfCaCertificates

The number of ca certificates in the trust store.

Type: Integer

Required: No

### Status

The current status of the trust store.

Type: String

Valid Values: ACTIVE | CREATING

Required: No

### TotalRevokedEntries

The number of revoked certificates in the trust store.

Type: Long

Required: No

### TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# TrustStoreAssociation

Information about the resources a trust store is associated with.

## Contents

### ResourceArn

The Amazon Resource Name (ARN) of the resource.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# TrustStoreRevocation

Information about a revocation file in use by a trust store.

## Contents

### NumberOfRevokedEntries

The number of revoked certificates.

Type: Long

Required: No

### RevocationId

The revocation ID of the revocation file.

Type: Long

Required: No

### RevocationType

The type of revocation file.

Type: String

Valid Values: CRL

Required: No

### TrustStoreArn

The Amazon Resource Name (ARN) of the trust store.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# ZonalCapacityReservationState

The capacity reservation status for each Availability Zone.

## Contents

### AvailabilityZone

Information about the Availability Zone.

Type: String

Required: No

### EffectiveCapacityUnits

The number of effective capacity units.

Type: Double

Required: No

### State

The state of the capacity reservation.

Type: [CapacityReservationStatus](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

# Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing Amazon API requests](#) in the *IAM User Guide*.

## Action

The action to be performed.

Type: string

Required: Yes

## Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

## X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

## X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request").

The value is expressed in the following format: *access\_key/YYYYMMDD/region/service/aws4\_request*.

For more information, see [Create a signed Amazon API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

#### X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an Amazon API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

#### X-Amz-Security-Token

The temporary security token that was obtained through a call to Amazon Security Token Service (Amazon STS). For a list of services that support temporary security credentials from Amazon STS, see [Amazon Web Services services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from Amazon STS, you must include the security token.

Type: string

Required: Conditional

#### X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed Amazon API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

# Common Errors

This section lists the errors common to the API actions of all Amazon services. For errors specific to an API action for this service, see the topic for that API action.

## **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

## **IncompleteSignature**

The request signature does not conform to Amazon standards.

HTTP Status Code: 400

## **InternalFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## **InvalidAction**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

## **InvalidClientTokenId**

The X.509 certificate or Amazon access key ID provided does not exist in our records.

HTTP Status Code: 403

## **InvalidParameterCombination**

Parameters that must not be used together were used together.

HTTP Status Code: 400

## **InvalidParameterValue**

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

## **InvalidQueryParameter**

The Amazon query string is malformed or does not adhere to Amazon standards.

HTTP Status Code: 400

## **MalformedQueryString**

The query string contains a syntax error.

HTTP Status Code: 404

## **MissingAction**

The request is missing an action or a required parameter.

HTTP Status Code: 400

## **MissingAuthenticationToken**

The request must contain either a valid (registered) Amazon access key ID or X.509 certificate.

HTTP Status Code: 403

## **MissingParameter**

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

## **NotAuthorized**

You do not have permission to perform this action.

HTTP Status Code: 400

## **OptInRequired**

The Amazon access key ID needs a subscription for the service.

HTTP Status Code: 403

## **RequestExpired**

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

### **ServiceUnavailable**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

### **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

### **ValidationException**

The input fails to satisfy the constraints specified by an Amazon service.

HTTP Status Code: 400