

Amazon Data Firehose



Amazon Data Firehose: API Reference

Table of Contents

Welcome	1
Actions	2
CreateDeliveryStream	3
Request Syntax	4
Request Parameters	18
Response Syntax	22
Response Elements	22
Errors	22
Examples	23
See Also	25
DeleteDeliveryStream	26
Request Syntax	26
Request Parameters	26
Response Elements	27
Errors	27
Examples	27
See Also	28
DescribeDeliveryStream	29
Request Syntax	29
Request Parameters	29
Response Syntax	30
Response Elements	44
Errors	45
Examples	45
See Also	47
ListDeliveryStreams	48
Request Syntax	48
Request Parameters	48
Response Syntax	49
Response Elements	49
Errors	50
Examples	50
See Also	51
ListTagsForDeliveryStream	52

Request Syntax	52
Request Parameters	52
Response Syntax	53
Response Elements	53
Errors	54
Examples	54
See Also	55
PutRecord	57
Request Syntax	58
Request Parameters	58
Response Syntax	58
Response Elements	59
Errors	59
Examples	60
See Also	61
PutRecordBatch	62
Request Syntax	63
Request Parameters	63
Response Syntax	64
Response Elements	64
Errors	65
Examples	66
See Also	67
StartDeliveryStreamEncryption	69
Request Syntax	70
Request Parameters	70
Response Elements	70
Errors	71
Examples	71
See Also	72
StopDeliveryStreamEncryption	73
Request Syntax	73
Request Parameters	73
Response Elements	74
Errors	74
Examples	74

See Also	75
TagDeliveryStream	76
Request Syntax	76
Request Parameters	76
Response Elements	77
Errors	77
Examples	78
See Also	79
UntagDeliveryStream	80
Request Syntax	80
Request Parameters	80
Response Elements	81
Errors	81
Examples	81
See Also	82
UpdateDestination	83
Request Syntax	83
Request Parameters	97
Response Elements	99
Errors	99
Examples	100
See Also	101
Data Types	102
AmazonOpenSearchServerlessBufferingHints	106
Contents	106
See Also	106
AmazonOpenSearchServerlessDestinationConfiguration	108
Contents	108
See Also	110
AmazonOpenSearchServerlessDestinationDescription	111
Contents	111
See Also	113
AmazonOpenSearchServerlessDestinationUpdate	114
Contents	114
See Also	115
AmazonOpenSearchServerlessRetryOptions	117

Contents	117
See Also	117
AmazonopensearchserviceBufferingHints	118
Contents	118
See Also	118
AmazonopensearchserviceDestinationConfiguration	120
Contents	120
See Also	123
AmazonopensearchserviceDestinationDescription	124
Contents	124
See Also	127
AmazonopensearchserviceDestinationUpdate	128
Contents	128
See Also	131
AmazonopensearchserviceRetryOptions	132
Contents	132
See Also	132
AuthenticationConfiguration	133
Contents	133
See Also	133
BufferingHints	134
Contents	134
See Also	134
CloudWatchLoggingOptions	136
Contents	136
See Also	136
CopyCommand	138
Contents	138
See Also	139
DataFormatConversionConfiguration	140
Contents	140
See Also	141
DeliveryStreamDescription	142
Contents	142
See Also	144
DeliveryStreamEncryptionConfiguration	146

Contents	146
See Also	147
DeliveryStreamEncryptionConfigurationInput	148
Contents	148
See Also	149
Deserializer	150
Contents	150
See Also	150
DestinationDescription	151
Contents	151
See Also	152
DocumentIdOptions	154
Contents	154
See Also	154
DynamicPartitioningConfiguration	155
Contents	155
See Also	155
ElasticsearchBufferingHints	156
Contents	156
See Also	156
ElasticsearchDestinationConfiguration	158
Contents	158
See Also	161
ElasticsearchDestinationDescription	162
Contents	162
See Also	165
ElasticsearchDestinationUpdate	166
Contents	166
See Also	169
ElasticsearchRetryOptions	170
Contents	170
See Also	170
EncryptionConfiguration	171
Contents	171
See Also	171
ExtendedS3DestinationConfiguration	172

Contents	172
See Also	175
ExtendedS3DestinationDescription	176
Contents	176
See Also	179
ExtendedS3DestinationUpdate	180
Contents	180
See Also	183
FailureDescription	184
Contents	184
See Also	184
HiveJsonSerDe	186
Contents	186
See Also	186
HttpEndpointBufferingHints	187
Contents	187
See Also	187
HttpEndpointCommonAttribute	189
Contents	189
See Also	189
HttpEndpointConfiguration	190
Contents	190
See Also	191
HttpEndpointDescription	192
Contents	192
See Also	192
HttpEndpointDestinationConfiguration	193
Contents	193
See Also	195
HttpEndpointDestinationDescription	196
Contents	196
See Also	198
HttpEndpointDestinationUpdate	199
Contents	199
See Also	201
HttpEndpointRequestConfiguration	202

Contents	202
See Also	202
HttpEndpointRetryOptions	203
Contents	203
See Also	203
InputFormatConfiguration	204
Contents	204
See Also	204
KinesisStreamSourceConfiguration	205
Contents	205
See Also	205
KinesisStreamSourceDescription	207
Contents	207
See Also	207
KMSEncryptionConfig	209
Contents	209
See Also	209
MSKSourceConfiguration	210
Contents	210
See Also	210
MSKSourceDescription	212
Contents	212
See Also	213
OpenXJsonSerDe	214
Contents	214
See Also	215
OrcSerDe	216
Contents	216
See Also	218
OutputFormatConfiguration	219
Contents	219
See Also	219
ParquetSerDe	220
Contents	220
See Also	221
ProcessingConfiguration	222

Contents	222
See Also	222
Processor	223
Contents	223
See Also	223
ProcessorParameter	225
Contents	225
See Also	225
PutRecordBatchResponseEntry	227
Contents	227
See Also	227
Record	229
Contents	229
See Also	229
RedshiftDestinationConfiguration	230
Contents	230
See Also	232
RedshiftDestinationDescription	233
Contents	233
See Also	235
RedshiftDestinationUpdate	236
Contents	236
See Also	238
RedshiftRetryOptions	239
Contents	239
See Also	239
RetryOptions	240
Contents	240
See Also	240
S3DestinationConfiguration	241
Contents	241
See Also	243
S3DestinationDescription	244
Contents	244
See Also	246
S3DestinationUpdate	247

Contents	247
See Also	249
SchemaConfiguration	250
Contents	250
See Also	252
Serializer	253
Contents	253
See Also	253
SnowflakeDestinationConfiguration	254
Contents	254
See Also	258
SnowflakeDestinationDescription	259
Contents	259
See Also	262
SnowflakeDestinationUpdate	263
Contents	263
See Also	267
SnowflakeRetryOptions	268
Contents	268
See Also	268
SnowflakeRoleConfiguration	269
Contents	269
See Also	269
SnowflakeVpcConfiguration	270
Contents	270
See Also	270
SourceDescription	271
Contents	271
See Also	271
SplunkBufferingHints	272
Contents	272
See Also	272
SplunkDestinationConfiguration	273
Contents	273
See Also	275
SplunkDestinationDescription	276

Contents	276
See Also	278
SplunkDestinationUpdate	279
Contents	279
See Also	281
SplunkRetryOptions	282
Contents	282
See Also	282
Tag	283
Contents	283
See Also	283
VpcConfiguration	284
Contents	284
See Also	286
VpcConfigurationDescription	287
Contents	287
See Also	289
Common Errors	290

Welcome

Note

Amazon Data Firehose was previously known as Amazon Kinesis Data Firehose.

Amazon Data Firehose is a fully managed service that delivers real-time streaming data to destinations such as Amazon Simple Storage Service (Amazon S3), Amazon OpenSearch Service, Amazon Redshift, Splunk, and various other supported destinations.

This document was last published on April 25, 2024.

Actions

The following actions are supported:

- [CreateDeliveryStream](#)
- [DeleteDeliveryStream](#)
- [DescribeDeliveryStream](#)
- [ListDeliveryStreams](#)
- [ListTagsForDeliveryStream](#)
- [PutRecord](#)
- [PutRecordBatch](#)
- [StartDeliveryStreamEncryption](#)
- [StopDeliveryStreamEncryption](#)
- [TagDeliveryStream](#)
- [UntagDeliveryStream](#)
- [UpdateDestination](#)

CreateDeliveryStream

Creates a Firehose delivery stream.

By default, you can create up to 50 delivery streams per Amazon Region.

This is an asynchronous operation that immediately returns. The initial status of the delivery stream is `CREATING`. After the delivery stream is created, its status is `ACTIVE` and it now accepts data. If the delivery stream creation fails, the status transitions to `CREATING_FAILED`. Attempts to send data to a delivery stream that is not in the `ACTIVE` state cause an exception. To check the state of a delivery stream, use [DescribeDeliveryStream](#).

If the status of a delivery stream is `CREATING_FAILED`, this status doesn't change, and you can't invoke `CreateDeliveryStream` again on it. However, you can invoke the [DeleteDeliveryStream](#) operation to delete it.

A Firehose delivery stream can be configured to receive records directly from providers using [PutRecord](#) or [PutRecordBatch](#), or it can be configured to use an existing Kinesis stream as its source. To specify a Kinesis data stream as input, set the `DeliveryStreamType` parameter to `KinesisStreamAsSource`, and provide the Kinesis stream Amazon Resource Name (ARN) and role ARN in the `KinesisStreamSourceConfiguration` parameter.

To create a delivery stream with server-side encryption (SSE) enabled, include [DeliveryStreamEncryptionConfigurationInput](#) in your request. This is optional. You can also invoke [StartDeliveryStreamEncryption](#) to turn on SSE for an existing delivery stream that doesn't have SSE enabled.

A delivery stream is configured with a single destination, such as Amazon Simple Storage Service (Amazon S3), Amazon Redshift, Amazon OpenSearch Service, Amazon OpenSearch Serverless, Splunk, and any custom HTTP endpoint or HTTP endpoints owned by or supported by third-party service providers, including Datadog, Dynatrace, LogicMonitor, MongoDB, New Relic, and Sumo Logic. You must specify only one of the following destination configuration parameters: `ExtendedS3DestinationConfiguration`, `S3DestinationConfiguration`, `ElasticsearchDestinationConfiguration`, `RedshiftDestinationConfiguration`, or `SplunkDestinationConfiguration`.

When you specify `S3DestinationConfiguration`, you can also provide the following optional values: `BufferingHints`, `EncryptionConfiguration`, and `CompressionFormat`. By default, if no `BufferingHints` value is provided, Firehose buffers data up to 5 MB or for 5 minutes, whichever condition is satisfied first. `BufferingHints` is a hint, so there are some cases where the service

cannot adhere to these conditions strictly. For example, record boundaries might be such that the size is a little over or under the configured buffering size. By default, no encryption is performed. We strongly recommend that you enable encryption to ensure secure data storage in Amazon S3.

A few notes about Amazon Redshift as a destination:

- An Amazon Redshift destination requires an S3 bucket as intermediate location. Firehose first delivers data to Amazon S3 and then uses COPY syntax to load data into an Amazon Redshift table. This is specified in the `RedshiftDestinationConfiguration.S3Configuration` parameter.
- The compression formats SNAPPY or ZIP cannot be specified in `RedshiftDestinationConfiguration.S3Configuration` because the Amazon Redshift COPY operation that reads from the S3 bucket doesn't support these compression formats.
- We strongly recommend that you use the user name and password you provide exclusively with Firehose, and that the permissions for the account are restricted for Amazon Redshift INSERT permissions.

Firehose assumes the IAM role that is configured as part of the destination. The role should allow the Firehose principal to assume the role, and the role should have permissions that allow the service to deliver the data. For more information, see [Grant Firehose Access to an Amazon S3 Destination](#) in the *Amazon Firehose Developer Guide*.

Request Syntax

```
{
  "AmazonOpenSearchServerlessDestinationConfiguration": {
    "BufferingHints": {
      "IntervalInSeconds": number,
      "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
      "Enabled": boolean,
      "LogGroupName": "string",
      "LogStreamName": "string"
    },
    "CollectionEndpoint": "string",
    "IndexName": "string",
    "ProcessingConfiguration": {
      "Enabled": boolean,
```



```

    "Processors": [
      {
        "Parameters": [
          {
            "ParameterName": "string",
            "ParameterValue": "string"
          }
        ],
        "Type": "string"
      }
    ],
    "RetryOptions": {
      "DurationInSeconds": number
    },
    "RoleARN": "string",
    "S3BackupMode": "string",
    "S3Configuration": {
      "BucketARN": "string",
      "BufferingHints": {
        "IntervalInSeconds": number,
        "SizeInMBs": number
      },
      "CloudWatchLoggingOptions": {
        "Enabled": boolean,
        "LogGroupName": "string",
        "LogStreamName": "string"
      },
      "CompressionFormat": "string",
      "EncryptionConfiguration": {
        "KMSEncryptionConfig": {
          "AWSKMSKeyARN": "string"
        },
        "NoEncryptionConfig": "string"
      },
      "ErrorOutputPrefix": "string",
      "Prefix": "string",
      "RoleARN": "string"
    },
    "VpcConfiguration": {
      "RoleARN": "string",
      "SecurityGroupIds": [ "string" ],
      "SubnetIds": [ "string" ]
    }
  }

```

```
},
"AmazonopensearchserviceDestinationConfiguration": {
  "BufferingHints": {
    "IntervalInSeconds": number,
    "SizeInMBs": number
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "ClusterEndpoint": "string",
  "DocumentIdOptions": {
    "DefaultDocumentIdFormat": "string"
  },
  "DomainARN": "string",
  "IndexName": "string",
  "IndexRotationPeriod": "string",
  "ProcessingConfiguration": {
    "Enabled": boolean,
    "Processors": [
      {
        "Parameters": [
          {
            "ParameterName": "string",
            "ParameterValue": "string"
          }
        ],
        "Type": "string"
      }
    ]
  },
  "RetryOptions": {
    "DurationInSeconds": number
  },
  "RoleARN": "string",
  "S3BackupMode": "string",
  "S3Configuration": {
    "BucketARN": "string",
    "BufferingHints": {
      "IntervalInSeconds": number,
      "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
```

```

        "Enabled": boolean,
        "LogGroupName": "string",
        "LogStreamName": "string"
    },
    "CompressionFormat": "string",
    "EncryptionConfiguration": {
        "KMSEncryptionConfig": {
            "AWSKMSKeyARN": "string"
        },
        "NoEncryptionConfig": "string"
    },
    "ErrorOutputPrefix": "string",
    "Prefix": "string",
    "RoleARN": "string"
},
"TypeName": "string",
"VpcConfiguration": {
    "RoleARN": "string",
    "SecurityGroupIds": [ "string" ],
    "SubnetIds": [ "string" ]
}
},
"DeliveryStreamEncryptionConfigurationInput": {
    "KeyARN": "string",
    "KeyType": "string"
},
"DeliveryStreamName": "string",
"DeliveryStreamType": "string",
"ElasticsearchDestinationConfiguration": {
    "BufferingHints": {
        "IntervalInSeconds": number,
        "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
        "Enabled": boolean,
        "LogGroupName": "string",
        "LogStreamName": "string"
    },
    "ClusterEndpoint": "string",
    "DocumentIdOptions": {
        "DefaultDocumentIdFormat": "string"
    },
    "DomainARN": "string",
    "IndexName": "string",

```

```

    "IndexRotationPeriod": "string",
    "ProcessingConfiguration": {
        "Enabled": boolean,
        "Processors": [
            {
                "Parameters": [
                    {
                        "ParameterName": "string",
                        "ParameterValue": "string"
                    }
                ],
                "Type": "string"
            }
        ]
    },
    "RetryOptions": {
        "DurationInSeconds": number
    },
    "RoleARN": "string",
    "S3BackupMode": "string",
    "S3Configuration": {
        "BucketARN": "string",
        "BufferingHints": {
            "IntervalInSeconds": number,
            "SizeInMBs": number
        },
        "CloudWatchLoggingOptions": {
            "Enabled": boolean,
            "LogGroupName": "string",
            "LogStreamName": "string"
        },
        "CompressionFormat": "string",
        "EncryptionConfiguration": {
            "KMSEncryptionConfig": {
                "AWSKMSKeyARN": "string"
            },
            "NoEncryptionConfig": "string"
        },
        "ErrorOutputPrefix": "string",
        "Prefix": "string",
        "RoleARN": "string"
    },
    "TypeName": "string",
    "VpcConfiguration": {

```

```

    "RoleARN": "string",
    "SecurityGroupIds": [ "string" ],
    "SubnetIds": [ "string" ]
  }
},
"ExtendedS3DestinationConfiguration": {
  "BucketARN": "string",
  "BufferingHints": {
    "IntervalInSeconds": number,
    "SizeInMBs": number
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "CompressionFormat": "string",
  "CustomTimeZone": "string",
  "DataFormatConversionConfiguration": {
    "Enabled": boolean,
    "InputFormatConfiguration": {
      "Deserializer": {
        "HiveJsonSerDe": {
          "TimestampFormats": [ "string" ]
        },
        "OpenXJsonSerDe": {
          "CaseInsensitive": boolean,
          "ColumnToJsonKeyMappings": {
            "string" : "string"
          },
          "ConvertDotsInJsonKeysToUnderscores": boolean
        }
      }
    },
    "OutputFormatConfiguration": {
      "Serializer": {
        "OrcSerDe": {
          "BlockSizeBytes": number,
          "BloomFilterColumns": [ "string" ],
          "BloomFilterFalsePositiveProbability": number,
          "Compression": "string",
          "DictionaryKeyThreshold": number,
          "EnablePadding": boolean,
          "FormatVersion": "string",

```

```

        "PaddingTolerance": number,
        "RowIndexStride": number,
        "StripeSizeBytes": number
    },
    "ParquetSerDe": {
        "BlockSizeBytes": number,
        "Compression": "string",
        "EnableDictionaryCompression": boolean,
        "MaxPaddingBytes": number,
        "PageSizeBytes": number,
        "WriterVersion": "string"
    }
},
"SchemaConfiguration": {
    "CatalogId": "string",
    "DatabaseName": "string",
    "Region": "string",
    "RoleARN": "string",
    "TableName": "string",
    "VersionId": "string"
},
"DynamicPartitioningConfiguration": {
    "Enabled": boolean,
    "RetryOptions": {
        "DurationInSeconds": number
    }
},
"EncryptionConfiguration": {
    "KMSEncryptionConfig": {
        "AWSKMSKeyARN": "string"
    },
    "NoEncryptionConfig": "string"
},
"ErrorOutputPrefix": "string",
"FileExtension": "string",
"Prefix": "string",
"ProcessingConfiguration": {
    "Enabled": boolean,
    "Processors": [
        {
            "Parameters": [

```

```

        "ParameterName": "string",
        "ParameterValue": "string"
    }
],
    "Type": "string"
}
]
},
"RoleARN": "string",
"S3BackupConfiguration": {
    "BucketARN": "string",
    "BufferingHints": {
        "IntervalInSeconds": number,
        "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
        "Enabled": boolean,
        "LogGroupName": "string",
        "LogStreamName": "string"
    },
    "CompressionFormat": "string",
    "EncryptionConfiguration": {
        "KMSEncryptionConfig": {
            "AWSKMSKeyARN": "string"
        },
        "NoEncryptionConfig": "string"
    },
    "ErrorOutputPrefix": "string",
    "Prefix": "string",
    "RoleARN": "string"
},
"S3BackupMode": "string"
},
"HttpEndpointDestinationConfiguration": {
    "BufferingHints": {
        "IntervalInSeconds": number,
        "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
        "Enabled": boolean,
        "LogGroupName": "string",
        "LogStreamName": "string"
    },
    "EndpointConfiguration": {

```

```
    "AccessKey": "string",
    "Name": "string",
    "Url": "string"
  },
  "ProcessingConfiguration": {
    "Enabled": boolean,
    "Processors": [
      {
        "Parameters": [
          {
            "ParameterName": "string",
            "ParameterValue": "string"
          }
        ],
        "Type": "string"
      }
    ]
  },
  "RequestConfiguration": {
    "CommonAttributes": [
      {
        "AttributeName": "string",
        "AttributeValue": "string"
      }
    ],
    "ContentEncoding": "string"
  },
  "RetryOptions": {
    "DurationInSeconds": number
  },
  "RoleARN": "string",
  "S3BackupMode": "string",
  "S3Configuration": {
    "BucketARN": "string",
    "BufferingHints": {
      "IntervalInSeconds": number,
      "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
      "Enabled": boolean,
      "LogGroupName": "string",
      "LogStreamName": "string"
    },
    "CompressionFormat": "string",
```



```

    "EncryptionConfiguration": {
      "KMSEncryptionConfig": {
        "AWSKMSKeyARN": "string"
      },
      "NoEncryptionConfig": "string"
    },
    "ErrorOutputPrefix": "string",
    "Prefix": "string",
    "RoleARN": "string"
  }
},
"KinesisStreamSourceConfiguration": {
  "KinesisStreamARN": "string",
  "RoleARN": "string"
},
"MSKSourceConfiguration": {
  "AuthenticationConfiguration": {
    "Connectivity": "string",
    "RoleARN": "string"
  },
  "MSKClusterARN": "string",
  "TopicName": "string"
},
"RedshiftDestinationConfiguration": {
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "ClusterJDBCURL": "string",
  "CopyCommand": {
    "CopyOptions": "string",
    "DataTableColumns": "string",
    "DataTableName": "string"
  },
  "Password": "string",
  "ProcessingConfiguration": {
    "Enabled": boolean,
    "Processors": [
      {
        "Parameters": [
          {
            "ParameterName": "string",
            "ParameterValue": "string"
          }
        ]
      }
    ]
  }
}

```

```

        }
      ],
      "Type": "string"
    }
  ]
},
"RetryOptions": {
  "DurationInSeconds": number
},
"RoleARN": "string",
"S3BackupConfiguration": {
  "BucketARN": "string",
  "BufferingHints": {
    "IntervalInSeconds": number,
    "SizeInMBs": number
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "CompressionFormat": "string",
  "EncryptionConfiguration": {
    "KMSEncryptionConfig": {
      "AWSKMSKeyARN": "string"
    },
    "NoEncryptionConfig": "string"
  },
  "ErrorOutputPrefix": "string",
  "Prefix": "string",
  "RoleARN": "string"
},
"S3BackupMode": "string",
"S3Configuration": {
  "BucketARN": "string",
  "BufferingHints": {
    "IntervalInSeconds": number,
    "SizeInMBs": number
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },

```

```

    "CompressionFormat": "string",
    "EncryptionConfiguration": {
      "KMSEncryptionConfig": {
        "AWSKMSKeyARN": "string"
      },
      "NoEncryptionConfig": "string"
    },
    "ErrorOutputPrefix": "string",
    "Prefix": "string",
    "RoleARN": "string"
  },
  "Username": "string"
},
"S3DestinationConfiguration": {
  "BucketARN": "string",
  "BufferingHints": {
    "IntervalInSeconds": number,
    "SizeInMBs": number
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "CompressionFormat": "string",
  "EncryptionConfiguration": {
    "KMSEncryptionConfig": {
      "AWSKMSKeyARN": "string"
    },
    "NoEncryptionConfig": "string"
  },
  "ErrorOutputPrefix": "string",
  "Prefix": "string",
  "RoleARN": "string"
},
"SnowflakeDestinationConfiguration": {
  "AccountUrl": "string",
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "ContentColumnName": "string",
  "Database": "string",

```

```
"DataLoadingOption": "string",
"KeyPassphrase": "string",
"MetaDataColumnName": "string",
"PrivateKey": "string",
"ProcessingConfiguration": {
  "Enabled": boolean,
  "Processors": [
    {
      "Parameters": [
        {
          "ParameterName": "string",
          "ParameterValue": "string"
        }
      ],
      "Type": "string"
    }
  ]
},
"RetryOptions": {
  "DurationInSeconds": number
},
"RoleARN": "string",
"S3BackupMode": "string",
"S3Configuration": {
  "BucketARN": "string",
  "BufferingHints": {
    "IntervalInSeconds": number,
    "SizeInMBs": number
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "CompressionFormat": "string",
  "EncryptionConfiguration": {
    "KMSEncryptionConfig": {
      "AWSKMSKeyARN": "string"
    },
    "NoEncryptionConfig": "string"
  },
  "ErrorOutputPrefix": "string",
  "Prefix": "string",
  "RoleARN": "string"
```

```
    },
    "Schema": "string",
    "SnowflakeRoleConfiguration": {
      "Enabled": boolean,
      "SnowflakeRole": "string"
    },
    "SnowflakeVpcConfiguration": {
      "PrivateLinkVpceId": "string"
    },
    "Table": "string",
    "User": "string"
  },
  "SplunkDestinationConfiguration": {
    "BufferingHints": {
      "IntervalInSeconds": number,
      "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
      "Enabled": boolean,
      "LogGroupName": "string",
      "LogStreamName": "string"
    },
    "HECAcknowledgmentTimeoutInSeconds": number,
    "HECEndpoint": "string",
    "HECEndpointType": "string",
    "HECToken": "string",
    "ProcessingConfiguration": {
      "Enabled": boolean,
      "Processors": [
        {
          "Parameters": [
            {
              "ParameterName": "string",
              "ParameterValue": "string"
            }
          ],
          "Type": "string"
        }
      ]
    },
    "RetryOptions": {
      "DurationInSeconds": number
    },
    "S3BackupMode": "string",
```

```

    "S3Configuration": {
      "BucketARN": "string",
      "BufferingHints": {
        "IntervalInSeconds": number,
        "SizeInMBs": number
      },
      "CloudWatchLoggingOptions": {
        "Enabled": boolean,
        "LogGroupName": "string",
        "LogStreamName": "string"
      },
      "CompressionFormat": "string",
      "EncryptionConfiguration": {
        "KMSEncryptionConfig": {
          "AWSKMSKeyARN": "string"
        },
        "NoEncryptionConfig": "string"
      },
      "ErrorOutputPrefix": "string",
      "Prefix": "string",
      "RoleARN": "string"
    },
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ]
  }
}

```

Request Parameters

The request accepts the following data in JSON format.

AmazonOpenSearchServerlessDestinationConfiguration

The destination in the Serverless offering for Amazon OpenSearch Service. You can specify only one destination.

Type: [AmazonOpenSearchServerlessDestinationConfiguration](#) object

Required: No

AmazonopensearchserviceDestinationConfiguration

The destination in Amazon OpenSearch Service. You can specify only one destination.

Type: [AmazonopensearchserviceDestinationConfiguration](#) object

Required: No

DeliveryStreamEncryptionConfigurationInput

Used to specify the type and Amazon Resource Name (ARN) of the KMS key needed for Server-Side Encryption (SSE).

Type: [DeliveryStreamEncryptionConfigurationInput](#) object

Required: No

DeliveryStreamName

The name of the delivery stream. This name must be unique per Amazon account in the same Amazon Region. If the delivery streams are in different accounts or different Regions, you can have multiple delivery streams with the same name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

DeliveryStreamType

The delivery stream type. This parameter can be one of the following values:

- **DirectPut**: Provider applications access the delivery stream directly.
- **KinesisStreamAsSource**: The delivery stream uses a Kinesis data stream as a source.

Type: String

Valid Values: `DirectPut` | `KinesisStreamAsSource` | `MSKAsSource`

Required: No

ElasticsearchDestinationConfiguration

The destination in Amazon ES. You can specify only one destination.

Type: [ElasticsearchDestinationConfiguration](#) object

Required: No

ExtendedS3DestinationConfiguration

The destination in Amazon S3. You can specify only one destination.

Type: [ExtendedS3DestinationConfiguration](#) object

Required: No

HttpEndpointDestinationConfiguration

Enables configuring Kinesis Firehose to deliver data to any HTTP endpoint destination. You can specify only one destination.

Type: [HttpEndpointDestinationConfiguration](#) object

Required: No

KinesisStreamSourceConfiguration

When a Kinesis data stream is used as the source for the delivery stream, a [KinesisStreamSourceConfiguration](#) containing the Kinesis data stream Amazon Resource Name (ARN) and the role ARN for the source stream.

Type: [KinesisStreamSourceConfiguration](#) object

Required: No

MSKSourceConfiguration

The configuration for the Amazon MSK cluster to be used as the source for a delivery stream.

Type: [MSKSourceConfiguration](#) object

Required: No

RedshiftDestinationConfiguration

The destination in Amazon Redshift. You can specify only one destination.

Type: [RedshiftDestinationConfiguration](#) object

Required: No

[S3DestinationConfiguration](#)

[Deprecated] The destination in Amazon S3. You can specify only one destination.

Type: [S3DestinationConfiguration](#) object

Required: No

[SnowflakeDestinationConfiguration](#)

Configure Snowflake destination

Type: [SnowflakeDestinationConfiguration](#) object

Required: No

[SplunkDestinationConfiguration](#)

The destination in Splunk. You can specify only one destination.

Type: [SplunkDestinationConfiguration](#) object

Required: No

[Tags](#)

A set of tags to assign to the delivery stream. A tag is a key-value pair that you can define and assign to Amazon resources. Tags are metadata. For example, you can add friendly names and descriptions or other types of information that can help you distinguish the delivery stream. For more information about tags, see [Using Cost Allocation Tags](#) in the Amazon Billing and Cost Management User Guide.

You can specify up to 50 tags when creating a delivery stream.

If you specify tags in the `CreateDeliveryStream` action, Amazon Data Firehose performs an additional authorization on the `firehose:TagDeliveryStream` action to verify if users have permissions to create tags. If you do not provide this permission, requests to create new Firehose delivery streams with IAM resource tags will fail with an `AccessDeniedException` such as following.

AccessDeniedException

User: `arn:aws:sts::x:assumed-role/x/x` is not authorized to perform: `firehose:TagDeliveryStream` on resource: `arn:aws:firehose:us-east-1:x:deliverystream/x` with an explicit deny in an identity-based policy.

For an example IAM policy, see [Tag example](#).

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: No

Response Syntax

```
{
  "DeliveryStreamARN": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[DeliveryStreamARN](#)

The ARN of the delivery stream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidArgumentException

The specified input parameter has a value that is not valid.

HTTP Status Code: 400

InvalidKMSResourceException

Firehose throws this exception when an attempt to put records or to start or stop delivery stream encryption fails. This happens when the KMS service throws one of the following exception types: `AccessDeniedException`, `InvalidStateException`, `DisabledException`, or `NotFoundException`.

HTTP Status Code: 400

LimitExceededException

You have already reached the limit for a requested resource.

HTTP Status Code: 400

ResourceInUseException

The resource is already in use and not available for this operation.

HTTP Status Code: 400

Examples

Example

The following JSON example creates a delivery stream named `exampleStreamName` with an Amazon S3 destination. To use this example, first replace the placeholders for the `RoleARN` and `BucketARN` keys with valid strings. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Sample Request

```
POST / HTTP/1.1
Host: firehose.<region>.<domain>
Content-Length: <PayloadSizeBytes>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Authorization: <AuthParams>
Connection: Keep-Alive
X-Amz-Date: <Date>
X-Amz-Target: Firehose_20150804.CreateDeliveryStream
```

```
{
  "DeliveryStreamName": "exampleStreamName",
  "S3DestinationConfiguration": {
    "RoleARN": "insert-role-ARN",
    "BucketARN": "insert-bucket-ARN",
    "BufferingHints": {
      "SizeInMBs": 3,
      "IntervalInSeconds": 60
    },
    "CompressionFormat": "ZIP"
  }
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>
{
  "DeliveryStreamARN": "arn:aws:firehose:us-east-1:814985986679:deliverystream/
exampleStreamName"
}
```

Example IAM policy to create a delivery stream and apply tags

The following example demonstrates a policy that allows users to create a delivery stream and apply tags.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "firehose:CreateDeliveryStream",
      "Resource": "*",
    },
    {
      "Effect": "Allow",
      "Action": "firehose:TagDeliveryStream",
```

```
        "Resource": "*",
      }
    ]
  }
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteDeliveryStream

Deletes a delivery stream and its data.

You can delete a delivery stream only if it is in one of the following states: ACTIVE, DELETING, CREATING_FAILED, or DELETING_FAILED. You can't delete a delivery stream that is in the CREATING state. To check the state of a delivery stream, use [DescribeDeliveryStream](#).

DeleteDeliveryStream is an asynchronous API. When an API request to DeleteDeliveryStream succeeds, the delivery stream is marked for deletion, and it goes into the DELETING state. While the delivery stream is in the DELETING state, the service might continue to accept records, but it doesn't make any guarantees with respect to delivering the data. Therefore, as a best practice, first stop any applications that are sending records before you delete a delivery stream.

Removal of a delivery stream that is in the DELETING state is a low priority operation for the service. A stream may remain in the DELETING state for several minutes. Therefore, as a best practice, applications should not wait for streams in the DELETING state to be removed.

Request Syntax

```
{
  "AllowForceDelete": boolean,
  "DeliveryStreamName": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

[AllowForceDelete](#)

Set this to true if you want to delete the delivery stream even if Firehose is unable to retire the grant for the CMK. Firehose might be unable to retire the grant due to a customer error, such as when the CMK or the grant are in an invalid state. If you force deletion, you can then use the [RevokeGrant](#) operation to revoke the grant you gave to Firehose. If a failure to retire the grant happens due to an Amazon KMS issue, Firehose keeps retrying the delete operation.

The default value is false.

Type: Boolean

Required: No

DeliveryStreamName

The name of the delivery stream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceInUseException

The resource is already in use and not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 400

Examples

Example

The following JSON example deletes a delivery stream named `exampleStreamName`.

Sample Request

```
POST / HTTP/1.1
```

```
Host: firehose.<region>.<domain>
Content-Length: <PayloadSizeBytes>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Authorization: <AuthParams>
Connection: Keep-Alive
X-Amz-Date: <Date>
X-Amz-Target: Firehose_20150804.DeleteDeliveryStream
{
  "DeliveryStreamName": "exampleStreamName"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeDeliveryStream

Describes the specified delivery stream and its status. For example, after your delivery stream is created, call `DescribeDeliveryStream` to see whether the delivery stream is `ACTIVE` and therefore ready for data to be sent to it.

If the status of a delivery stream is `CREATING_FAILED`, this status doesn't change, and you can't invoke [CreateDeliveryStream](#) again on it. However, you can invoke the [DeleteDeliveryStream](#) operation to delete it. If the status is `DELETING_FAILED`, you can force deletion by invoking [DeleteDeliveryStream](#) again but with [DeleteDeliveryStream:AllowForceDelete](#) set to `true`.

Request Syntax

```
{
  "DeliveryStreamName": "string",
  "ExclusiveStartDestinationId": "string",
  "Limit": number
}
```

Request Parameters

The request accepts the following data in JSON format.

[DeliveryStreamName](#)

The name of the delivery stream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

[ExclusiveStartDestinationId](#)

The ID of the destination to start returning the destination information. Firehose supports one destination per delivery stream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-]+

Required: No

Limit

The limit on the number of destinations to return. You can have one destination per delivery stream.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10000.

Required: No

Response Syntax

```
{
  "DeliveryStreamDescription": {
    "CreateTimestamp": number,
    "DeliveryStreamARN": "string",
    "DeliveryStreamEncryptionConfiguration": {
      "FailureDescription": {
        "Details": "string",
        "Type": "string"
      },
      "KeyARN": "string",
      "KeyType": "string",
      "Status": "string"
    },
    "DeliveryStreamName": "string",
    "DeliveryStreamStatus": "string",
    "DeliveryStreamType": "string",
    "Destinations": [
      {
        "AmazonOpenSearchServerlessDestinationDescription": {
          "BufferingHints": {
            "IntervalInSeconds": number,
            "SizeInMBs": number
          },
          "CloudWatchLoggingOptions": {
            "Enabled": boolean,
            "LogGroupName": "string",
            "LogStreamName": "string"
          }
        }
      }
    ]
  }
}
```

```
},
"CollectionEndpoint": "string",
"IndexName": "string",
"ProcessingConfiguration": {
  "Enabled": boolean,
  "Processors": [
    {
      "Parameters": [
        {
          "ParameterName": "string",
          "ParameterValue": "string"
        }
      ],
      "Type": "string"
    }
  ]
},
"RetryOptions": {
  "DurationInSeconds": number
},
"RoleARN": "string",
"S3BackupMode": "string",
"S3DestinationDescription": {
  "BucketARN": "string",
  "BufferingHints": {
    "IntervalInSeconds": number,
    "SizeInMBs": number
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "CompressionFormat": "string",
  "EncryptionConfiguration": {
    "KMSEncryptionConfig": {
      "AWSKMSKeyARN": "string"
    },
    "NoEncryptionConfig": "string"
  },
  "ErrorOutputPrefix": "string",
  "Prefix": "string",
  "RoleARN": "string"
},
```

```

    "VpcConfigurationDescription": {
      "RoleARN": "string",
      "SecurityGroupIds": [ "string" ],
      "SubnetIds": [ "string" ],
      "VpcId": "string"
    }
  },
  "AmazonopensearchserviceDestinationDescription": {
    "BufferingHints": {
      "IntervalInSeconds": number,
      "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
      "Enabled": boolean,
      "LogGroupName": "string",
      "LogStreamName": "string"
    },
    "ClusterEndpoint": "string",
    "DocumentIdOptions": {
      "DefaultDocumentIdFormat": "string"
    },
    "DomainARN": "string",
    "IndexName": "string",
    "IndexRotationPeriod": "string",
    "ProcessingConfiguration": {
      "Enabled": boolean,
      "Processors": [
        {
          "Parameters": [
            {
              "ParameterName": "string",
              "ParameterValue": "string"
            }
          ],
          "Type": "string"
        }
      ]
    },
    "RetryOptions": {
      "DurationInSeconds": number
    },
    "RoleARN": "string",
    "S3BackupMode": "string",
    "S3DestinationDescription": {

```

```

    "BucketARN": "string",
    "BufferingHints": {
      "IntervalInSeconds": number,
      "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
      "Enabled": boolean,
      "LogGroupName": "string",
      "LogStreamName": "string"
    },
    "CompressionFormat": "string",
    "EncryptionConfiguration": {
      "KMSEncryptionConfig": {
        "AWSKMSKeyARN": "string"
      },
      "NoEncryptionConfig": "string"
    },
    "ErrorOutputPrefix": "string",
    "Prefix": "string",
    "RoleARN": "string"
  },
  "TypeName": "string",
  "VpcConfigurationDescription": {
    "RoleARN": "string",
    "SecurityGroupIds": [ "string" ],
    "SubnetIds": [ "string" ],
    "VpcId": "string"
  }
},
"DestinationId": "string",
"ElasticsearchDestinationDescription": {
  "BufferingHints": {
    "IntervalInSeconds": number,
    "SizeInMBs": number
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "ClusterEndpoint": "string",
  "DocumentIdOptions": {
    "DefaultDocumentIdFormat": "string"
  }
},

```

```
"DomainARN": "string",
"IndexName": "string",
"IndexRotationPeriod": "string",
"ProcessingConfiguration": {
  "Enabled": boolean,
  "Processors": [
    {
      "Parameters": [
        {
          "ParameterName": "string",
          "ParameterValue": "string"
        }
      ],
      "Type": "string"
    }
  ]
},
"RetryOptions": {
  "DurationInSeconds": number
},
"RoleARN": "string",
"S3BackupMode": "string",
"S3DestinationDescription": {
  "BucketARN": "string",
  "BufferingHints": {
    "IntervalInSeconds": number,
    "SizeInMBs": number
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "CompressionFormat": "string",
  "EncryptionConfiguration": {
    "KMSEncryptionConfig": {
      "AWSKMSKeyARN": "string"
    },
    "NoEncryptionConfig": "string"
  },
  "ErrorOutputPrefix": "string",
  "Prefix": "string",
  "RoleARN": "string"
},
```

```

    "TypeName": "string",
    "VpcConfigurationDescription": {
      "RoleARN": "string",
      "SecurityGroupIds": [ "string" ],
      "SubnetIds": [ "string" ],
      "VpcId": "string"
    }
  },
  "ExtendedS3DestinationDescription": {
    "BucketARN": "string",
    "BufferingHints": {
      "IntervalInSeconds": number,
      "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
      "Enabled": boolean,
      "LogGroupName": "string",
      "LogStreamName": "string"
    },
    "CompressionFormat": "string",
    "CustomTimeZone": "string",
    "DataFormatConversionConfiguration": {
      "Enabled": boolean,
      "InputFormatConfiguration": {
        "Deserializer": {
          "HiveJsonSerDe": {
            "TimestampFormats": [ "string" ]
          },
          "OpenXJsonSerDe": {
            "CaseInsensitive": boolean,
            "ColumnToJsonKeyMappings": {
              "string" : "string"
            },
            "ConvertDotsInJsonKeysToUnderscores": boolean
          }
        }
      },
      "OutputFormatConfiguration": {
        "Serializer": {
          "OrcSerDe": {
            "BlockSizeBytes": number,
            "BloomFilterColumns": [ "string" ],
            "BloomFilterFalsePositiveProbability": number,
            "Compression": "string",

```

```

        "DictionaryKeyThreshold": number,
        "EnablePadding": boolean,
        "FormatVersion": "string",
        "PaddingTolerance": number,
        "RowIndexStride": number,
        "StripeSizeBytes": number
    },
    "ParquetSerDe": {
        "BlockSizeBytes": number,
        "Compression": "string",
        "EnableDictionaryCompression": boolean,
        "MaxPaddingBytes": number,
        "PageSizeBytes": number,
        "WriterVersion": "string"
    }
},
"SchemaConfiguration": {
    "CatalogId": "string",
    "DatabaseName": "string",
    "Region": "string",
    "RoleARN": "string",
    "TableName": "string",
    "VersionId": "string"
},
"DynamicPartitioningConfiguration": {
    "Enabled": boolean,
    "RetryOptions": {
        "DurationInSeconds": number
    }
},
"EncryptionConfiguration": {
    "KMSEncryptionConfig": {
        "AWSKMSKeyARN": "string"
    },
    "NoEncryptionConfig": "string"
},
"ErrorOutputPrefix": "string",
"FileExtension": "string",
"Prefix": "string",
"ProcessingConfiguration": {
    "Enabled": boolean,
    "Processors": [

```



```

        {
            "Parameters": [
                {
                    "ParameterName": "string",
                    "ParameterValue": "string"
                }
            ],
            "Type": "string"
        }
    ],
    "RoleARN": "string",
    "S3BackupDescription": {
        "BucketARN": "string",
        "BufferingHints": {
            "IntervalInSeconds": number,
            "SizeInMBs": number
        },
        "CloudWatchLoggingOptions": {
            "Enabled": boolean,
            "LogGroupName": "string",
            "LogStreamName": "string"
        },
        "CompressionFormat": "string",
        "EncryptionConfiguration": {
            "KMSEncryptionConfig": {
                "AWSKMSKeyARN": "string"
            },
            "NoEncryptionConfig": "string"
        },
        "ErrorOutputPrefix": "string",
        "Prefix": "string",
        "RoleARN": "string"
    },
    "S3BackupMode": "string"
},
"HttpEndpointDestinationDescription": {
    "BufferingHints": {
        "IntervalInSeconds": number,
        "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
        "Enabled": boolean,
        "LogGroupName": "string",

```

```
    "LogStreamName": "string"
  },
  "EndpointConfiguration": {
    "Name": "string",
    "Url": "string"
  },
  "ProcessingConfiguration": {
    "Enabled": boolean,
    "Processors": [
      {
        "Parameters": [
          {
            "ParameterName": "string",
            "ParameterValue": "string"
          }
        ],
        "Type": "string"
      }
    ]
  },
  "RequestConfiguration": {
    "CommonAttributes": [
      {
        "AttributeName": "string",
        "AttributeValue": "string"
      }
    ],
    "ContentEncoding": "string"
  },
  "RetryOptions": {
    "DurationInSeconds": number
  },
  "RoleARN": "string",
  "S3BackupMode": "string",
  "S3DestinationDescription": {
    "BucketARN": "string",
    "BufferingHints": {
      "IntervalInSeconds": number,
      "SizeInMBs": number
    }
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  }
}
```

```

    },
    "CompressionFormat": "string",
    "EncryptionConfiguration": {
      "KMSEncryptionConfig": {
        "AWSKMSKeyARN": "string"
      },
      "NoEncryptionConfig": "string"
    },
    "ErrorOutputPrefix": "string",
    "Prefix": "string",
    "RoleARN": "string"
  }
},
"RedshiftDestinationDescription": {
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "ClusterJDBCURL": "string",
  "CopyCommand": {
    "CopyOptions": "string",
    "DataTableColumns": "string",
    "DataTableName": "string"
  },
  "ProcessingConfiguration": {
    "Enabled": boolean,
    "Processors": [
      {
        "Parameters": [
          {
            "ParameterName": "string",
            "ParameterValue": "string"
          }
        ],
        "Type": "string"
      }
    ]
  },
  "RetryOptions": {
    "DurationInSeconds": number
  },
  "RoleARN": "string",
  "S3BackupDescription": {

```

```
    "BucketARN": "string",
    "BufferingHints": {
      "IntervalInSeconds": number,
      "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
      "Enabled": boolean,
      "LogGroupName": "string",
      "LogStreamName": "string"
    },
    "CompressionFormat": "string",
    "EncryptionConfiguration": {
      "KMSEncryptionConfig": {
        "AWSKMSKeyARN": "string"
      },
      "NoEncryptionConfig": "string"
    },
    "ErrorOutputPrefix": "string",
    "Prefix": "string",
    "RoleARN": "string"
  },
  "S3BackupMode": "string",
  "S3DestinationDescription": {
    "BucketARN": "string",
    "BufferingHints": {
      "IntervalInSeconds": number,
      "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
      "Enabled": boolean,
      "LogGroupName": "string",
      "LogStreamName": "string"
    },
    "CompressionFormat": "string",
    "EncryptionConfiguration": {
      "KMSEncryptionConfig": {
        "AWSKMSKeyARN": "string"
      },
      "NoEncryptionConfig": "string"
    },
    "ErrorOutputPrefix": "string",
    "Prefix": "string",
    "RoleARN": "string"
  },
```

```
    "Username": "string"
  },
  "S3DestinationDescription": {
    "BucketARN": "string",
    "BufferingHints": {
      "IntervalInSeconds": number,
      "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
      "Enabled": boolean,
      "LogGroupName": "string",
      "LogStreamName": "string"
    },
    "CompressionFormat": "string",
    "EncryptionConfiguration": {
      "KMSEncryptionConfig": {
        "AWSKMSKeyARN": "string"
      },
      "NoEncryptionConfig": "string"
    },
    "ErrorOutputPrefix": "string",
    "Prefix": "string",
    "RoleARN": "string"
  },
  "SnowflakeDestinationDescription": {
    "AccountUrl": "string",
    "CloudWatchLoggingOptions": {
      "Enabled": boolean,
      "LogGroupName": "string",
      "LogStreamName": "string"
    },
    "ContentColumnName": "string",
    "Database": "string",
    "DataLoadingOption": "string",
    "MetadataColumnName": "string",
    "ProcessingConfiguration": {
      "Enabled": boolean,
      "Processors": [
        {
          "Parameters": [
            {
              "ParameterName": "string",
              "ParameterValue": "string"
            }
          ]
        }
      ]
    }
  }
}
```

```

        ],
        "Type": "string"
    }
]
},
"RetryOptions": {
    "DurationInSeconds": number
},
"RoleARN": "string",
"S3BackupMode": "string",
"S3DestinationDescription": {
    "BucketARN": "string",
    "BufferingHints": {
        "IntervalInSeconds": number,
        "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
        "Enabled": boolean,
        "LogGroupName": "string",
        "LogStreamName": "string"
    },
    "CompressionFormat": "string",
    "EncryptionConfiguration": {
        "KMSEncryptionConfig": {
            "AWSKMSKeyARN": "string"
        },
        "NoEncryptionConfig": "string"
    },
    "ErrorOutputPrefix": "string",
    "Prefix": "string",
    "RoleARN": "string"
},
"Schema": "string",
"SnowflakeRoleConfiguration": {
    "Enabled": boolean,
    "SnowflakeRole": "string"
},
"SnowflakeVpcConfiguration": {
    "PrivateLinkVpcId": "string"
},
"Table": "string",
"User": "string"
},
"SplunkDestinationDescription": {

```

```
"BufferingHints": {
  "IntervalInSeconds": number,
  "SizeInMBs": number
},
"CloudWatchLoggingOptions": {
  "Enabled": boolean,
  "LogGroupName": "string",
  "LogStreamName": "string"
},
"HECAcknowledgmentTimeoutInSeconds": number,
"HECEndpoint": "string",
"HECEndpointType": "string",
"HECToken": "string",
"ProcessingConfiguration": {
  "Enabled": boolean,
  "Processors": [
    {
      "Parameters": [
        {
          "ParameterName": "string",
          "ParameterValue": "string"
        }
      ],
      "Type": "string"
    }
  ]
},
"RetryOptions": {
  "DurationInSeconds": number
},
"S3BackupMode": "string",
"S3DestinationDescription": {
  "BucketARN": "string",
  "BufferingHints": {
    "IntervalInSeconds": number,
    "SizeInMBs": number
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "CompressionFormat": "string",
  "EncryptionConfiguration": {
```

```

        "KMSEncryptionConfig": {
            "AWSKMSKeyARN": "string"
        },
        "NoEncryptionConfig": "string"
    },
    "ErrorOutputPrefix": "string",
    "Prefix": "string",
    "RoleARN": "string"
}
}
],
"FailureDescription": {
    "Details": "string",
    "Type": "string"
},
"HasMoreDestinations": boolean,
"LastUpdateTimestamp": number,
"Source": {
    "KinesisStreamSourceDescription": {
        "DeliveryStartTimestamp": number,
        "KinesisStreamARN": "string",
        "RoleARN": "string"
    },
    "MSKSourceDescription": {
        "AuthenticationConfiguration": {
            "Connectivity": "string",
            "RoleARN": "string"
        },
        "DeliveryStartTimestamp": number,
        "MSKClusterARN": "string",
        "TopicName": "string"
    }
},
"VersionId": "string"
}
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DeliveryStreamDescription

Information about the delivery stream.

Type: [DeliveryStreamDescription](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 400

Examples

Example

The following JSON example describes a delivery stream.

Sample Request

```
POST / HTTP/1.1
Host: firehose.<region>.<domain>
Content-Length: <PayloadSizeBytes>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Authorization: <AuthParams>
Connection: Keep-Alive
X-Amz-Date: <Date>
X-Amz-Target: Firehose_20150804.DescribeDeliveryStream
{
  "DeliveryStreamName": "exampleStreamName"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
```

```
Content-Length: <PayloadSizeBytes>
Date: <Date>
{
  "DeliveryStreamDescription": {
    "DeliveryStreamType": "DirectPut",
    "HasMoreDestinations": false,
    "VersionId": "1",
    "CreateTimestamp": 1517595920.596,
    "DeliveryStreamARN": "arn:aws:firehose:us-east-1:111222333444:deliverystream/
exampleStreamName",
    "DeliveryStreamStatus": "ACTIVE",
    "DeliveryStreamName": "exampleStreamName",
    "DeliveryStreamEncryptionConfiguration": {
      "Status": "DISABLED"
    },
    "Destinations": [
      {
        "DestinationId": "destinationId-0000000000001",
        "ExtendedS3DestinationDescription": {
          "RoleARN": "arn:aws:iam::111222333444:role/exampleStreamName",
          "Prefix": "",
          "BufferingHints": {
            "IntervalInSeconds": 60,
            "SizeInMBs": 1
          },
          "EncryptionConfiguration": {
            "NoEncryptionConfig": "NoEncryption"
          },
          "CompressionFormat": "UNCOMPRESSED",
          "S3BackupMode": "Disabled",
          "CloudWatchLoggingOptions": {
            "Enabled": true,
            "LogStreamName": "S3Delivery",
            "LogGroupName": "/aws/kinesisfirehose/exampleStreamName"
          },
          "BucketARN": "arn:aws:s3:::somebucket",
          "ProcessingConfiguration": {
            "Enabled": false,
            "Processors": []
          }
        },
        "S3DestinationDescription": {
          "RoleARN": "arn:aws:iam::111222333444:role/exampleStreamName",
          "Prefix": "",
```

```
"BufferingHints": {
  "IntervalInSeconds": 60,
  "SizeInMBs": 1
},
"EncryptionConfiguration": {
  "NoEncryptionConfig": "NoEncryption"
},
"CompressionFormat": "UNCOMPRESSED",
"CloudWatchLoggingOptions": {
  "Enabled": true,
  "LogStreamName": "S3Delivery",
  "LogGroupName": "/aws/kinesisfirehose/exampleStreamName"
},
"BucketARN": "arn:aws:s3:::somebucket"
}
}
]
}
}
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListDeliveryStreams

Lists your delivery streams in alphabetical order of their names.

The number of delivery streams might be too large to return using a single call to `ListDeliveryStreams`. You can limit the number of delivery streams returned, using the `Limit` parameter. To determine whether there are more delivery streams to list, check the value of `HasMoreDeliveryStreams` in the output. If there are more delivery streams to list, you can request them by calling this operation again and setting the `ExclusiveStartDeliveryStreamName` parameter to the name of the last delivery stream returned in the last call.

Request Syntax

```
{
  "DeliveryStreamType": "string",
  "ExclusiveStartDeliveryStreamName": "string",
  "Limit": number
}
```

Request Parameters

The request accepts the following data in JSON format.

DeliveryStreamType

The delivery stream type. This can be one of the following values:

- `DirectPut`: Provider applications access the delivery stream directly.
- `KinesisStreamAsSource`: The delivery stream uses a Kinesis data stream as a source.

This parameter is optional. If this parameter is omitted, delivery streams of all types are returned.

Type: String

Valid Values: `DirectPut` | `KinesisStreamAsSource` | `MSKAsSource`

Required: No

ExclusiveStartDeliveryStreamName

The list of delivery streams returned by this call to `ListDeliveryStreams` will start with the delivery stream whose name comes alphabetically immediately after the name you specify in `ExclusiveStartDeliveryStreamName`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9_.-]+`

Required: No

Limit

The maximum number of delivery streams to list. The default value is 10.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10000.

Required: No

Response Syntax

```
{
  "DeliveryStreamNames": [ "string" ],
  "HasMoreDeliveryStreams": boolean
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DeliveryStreamNames

The names of the delivery streams.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_.-]+

HasMoreDeliveryStreams

Indicates whether there are more delivery streams available to list.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

Examples

Example

The following JSON example lists up to three delivery streams configured for DirectPut. The response indicates that there are more DirectPut delivery streams to be listed. To list the remaining DirectPut delivery streams, set `DeliveryStreamType` to `DirectPut` and `ExclusiveStartDeliveryStreamName` to `last_stream_in_first_listing`, and then run the operation again.

Sample Request

```
POST / HTTP/1.1
Host: firehose.<region>.<domain>
Content-Length: <PayloadSizeBytes>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Authorization: <AuthParams>
Connection: Keep-Alive
X-Amz-Date: <Date>
X-Amz-Target: Firehose_20150804.ListDeliveryStreams
{
  "DeliveryStreamType": "DirectPut",
  "Limit": 3
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>
{
  "DeliveryStreamNames": [
    "some_delivery_stream",
    "another_example_delivery_stream",
    "last_stream_in_first_listing"
  ],
  "HasMoreDeliveryStreams": true
}
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListTagsForDeliveryStream

Lists the tags for the specified delivery stream. This operation has a limit of five transactions per second per account.

Request Syntax

```
{  
  "DeliveryStreamName": "string",  
  "ExclusiveStartTagKey": "string",  
  "Limit": number  
}
```

Request Parameters

The request accepts the following data in JSON format.

DeliveryStreamName

The name of the delivery stream whose tags you want to list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

ExclusiveStartTagKey

The key to use as the starting point for the list of tags. If you set this parameter, ListTagsForDeliveryStream gets all tags that occur after ExclusiveStartTagKey.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^(?!aws:)[\p{L}\p{Z}\p{N}_.:\/=+\-@%]*\$

Required: No

Limit

The number of tags to return. If this number is less than the total number of tags associated with the delivery stream, `HasMoreTags` is set to `true` in the response. To list additional tags, set `ExclusiveStartTagKey` to the last key in the response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

Response Syntax

```
{
  "HasMoreTags": boolean,
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

HasMoreTags

If this is `true` in the response, more tags are available. To list the remaining tags, set `ExclusiveStartTagKey` to the key of the last tag returned and call `ListTagsForDeliveryStream` again.

Type: Boolean

Tags

A list of tags associated with `DeliveryStreamName`, starting with the first tag after `ExclusiveStartTagKey` and up to the specified `Limit`.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidArgumentException

The specified input parameter has a value that is not valid.

HTTP Status Code: 400

LimitExceededException

You have already reached the limit for a requested resource.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 400

Examples

To list the tags for a stream

The following JSON example lists the tags for the specified delivery stream.

Sample Request

```
POST / HTTP/1.1
Host: firehose.<region>.<domain>
Content-Length: <PayloadSizeBytes>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Authorization: <AuthParams>
Connection: Keep-Alive
X-Amz-Date: <Date>
```

```
X-Amz-Target: Firehose_20150804.ListTagsForDeliveryStream
{
  "DeliveryStreamName": "exampleDeliveryStreamName"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>
{
  "HasMoreTags": "false",
  "Tags" : [
    {
      "Key": "Project",
      "Value": "myProject"
    },
    {
      "Key": "Environment",
      "Value": "Production"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

PutRecord

Writes a single data record into an Amazon Firehose delivery stream. To write multiple data records into a delivery stream, use [PutRecordBatch](#). Applications using these operations are referred to as producers.

By default, each delivery stream can take in up to 2,000 transactions per second, 5,000 records per second, or 5 MB per second. If you use [PutRecord](#) and [PutRecordBatch](#), the limits are an aggregate across these two operations for each delivery stream. For more information about limits and how to request an increase, see [Amazon Firehose Limits](#).

Firehose accumulates and publishes a particular metric for a customer account in one minute intervals. It is possible that the bursts of incoming bytes/records ingested to a delivery stream last only for a few seconds. Due to this, the actual spikes in the traffic might not be fully visible in the customer's 1 minute CloudWatch metrics.

You must specify the name of the delivery stream and the data record when using [PutRecord](#). The data record consists of a data blob that can be up to 1,000 KiB in size, and any kind of data. For example, it can be a segment from a log file, geographic location data, website clickstream data, and so on.

Firehose buffers records before delivering them to the destination. To disambiguate the data blobs at the destination, a common solution is to use delimiters in the data, such as a newline (\n) or some other character unique within the data. This allows the consumer application to parse individual data items when reading the data from the destination.

The PutRecord operation returns a RecordId, which is a unique string assigned to each record. Producer applications can use this ID for purposes such as auditability and investigation.

If the PutRecord operation throws a ServiceUnavailableException, the API is automatically reinvoked (retried) 3 times. If the exception persists, it is possible that the throughput limits have been exceeded for the delivery stream.

Re-invoking the Put API operations (for example, PutRecord and PutRecordBatch) can result in data duplicates. For larger data assets, allow for a longer time out before retrying Put API operations.

Data records sent to Firehose are stored for 24 hours from the time they are added to a delivery stream as it tries to send the records to the destination. If the destination is unreachable for more than 24 hours, the data is no longer available.

⚠ Important

Don't concatenate two or more base64 strings to form the data fields of your records. Instead, concatenate the raw data, then perform base64 encoding.

Request Syntax

```
{  
  "DeliveryStreamName": "string",  
  "Record": {  
    "Data": blob  
  }  
}
```

Request Parameters

The request accepts the following data in JSON format.

DeliveryStreamName

The name of the delivery stream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

Record

The record.

Type: [Record](#) object

Required: Yes

Response Syntax

```
{
```

```
"Encrypted": boolean,  
"RecordId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Encrypted](#)

Indicates whether server-side encryption (SSE) was enabled during this operation.

Type: Boolean

[RecordId](#)

The ID of the record.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidArgumentException

The specified input parameter has a value that is not valid.

HTTP Status Code: 400

InvalidKMSResourceException

Firehose throws this exception when an attempt to put records or to start or stop delivery stream encryption fails. This happens when the KMS service throws one of the following exception types: `AccessDeniedException`, `InvalidStateException`, `DisabledException`, or `NotFoundException`.

HTTP Status Code: 400

InvalidSourceException

Only requests from CloudWatch Logs are supported when CloudWatch Logs decompression is enabled.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 400

ServiceUnavailableException

The service is unavailable. Back off and retry the operation. If you continue to see the exception, throughput limits for the delivery stream may have been exceeded. For more information about limits and how to request an increase, see [Amazon Firehose Limits](#).

HTTP Status Code: 500

Examples

Example

The following JSON puts a record in the delivery stream named `some_delivery_stream`:

Sample Request

```
POST / HTTP/1.1
Host: firehose.<region>.<domain>
Content-Length: <PayloadSizeBytes>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Authorization: <AuthParams>
Connection: Keep-Alive
X-Amz-Date: <Date>
X-Amz-Target: Firehose_20150804.PutRecord
{
  "DeliveryStreamName": "some_delivery_stream",
  "Record": {
    "Data": "..."
```



```
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>
{
  "RecordId": "CGojNMJq3msHbGoc+1mgSpifCmfFm7lFhuts//4Ft6sFVokyE6t+5ioEAjNm+sgQ6iVf/
YePEXBK6epIW4QeXqJp2xsbfZUNXsf0Y1QrYXgRBCKzknjMMTP0BqJG0bM3fB//dHgEE0XDTc4wW065i/
tJyYI1Vy8qn8FMhpkZuh5bvG482XkkBxFmMGnhPTQwQ4A1IOP0sE0X99YnBK8RECdeQ2zxynvZ"
}
```

Example

The following example shows how you can use the [Amazon CLI](#) to put a record in a delivery stream.

```
aws firehose put-record --delivery-stream-name mystream --record="{\"Data\": \"1\"}"
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

PutRecordBatch

Writes multiple data records into a delivery stream in a single call, which can achieve higher throughput per producer than when writing single records. To write single data records into a delivery stream, use [PutRecord](#). Applications using these operations are referred to as producers.

Firehose accumulates and publishes a particular metric for a customer account in one minute intervals. It is possible that the bursts of incoming bytes/records ingested to a delivery stream last only for a few seconds. Due to this, the actual spikes in the traffic might not be fully visible in the customer's 1 minute CloudWatch metrics.

For information about service quota, see [Amazon Firehose Quota](#).

Each [PutRecordBatch](#) request supports up to 500 records. Each record in the request can be as large as 1,000 KB (before base64 encoding), up to a limit of 4 MB for the entire request. These limits cannot be changed.

You must specify the name of the delivery stream and the data record when using [PutRecord](#). The data record consists of a data blob that can be up to 1,000 KB in size, and any kind of data. For example, it could be a segment from a log file, geographic location data, website clickstream data, and so on.

Firehose buffers records before delivering them to the destination. To disambiguate the data blobs at the destination, a common solution is to use delimiters in the data, such as a newline (\n) or some other character unique within the data. This allows the consumer application to parse individual data items when reading the data from the destination.

The [PutRecordBatch](#) response includes a count of failed records, `FailedPutCount`, and an array of responses, `RequestResponses`. Even if the [PutRecordBatch](#) call succeeds, the value of `FailedPutCount` may be greater than 0, indicating that there are records for which the operation didn't succeed. Each entry in the `RequestResponses` array provides additional information about the processed record. It directly correlates with a record in the request array using the same ordering, from the top to the bottom. The response array always includes the same number of records as the request array. `RequestResponses` includes both successfully and unsuccessfully processed records. Firehose tries to process all records in each [PutRecordBatch](#) request. A single record failure does not stop the processing of subsequent records.

A successfully processed record includes a `RecordId` value, which is unique for the record. An unsuccessfully processed record includes `ErrorCode` and `ErrorMessage` values. `ErrorCode`

reflects the type of error, and is one of the following values: `ServiceUnavailableException` or `InternalFailure`. `ErrorMessage` provides more detailed information about the error.

If there is an internal server error or a timeout, the write might have completed or it might have failed. If `FailedPutCount` is greater than 0, retry the request, resending only those records that might have failed processing. This minimizes the possible duplicate records and also reduces the total bytes sent (and corresponding charges). We recommend that you handle any duplicates at the destination.

If [PutRecordBatch](#) throws `ServiceUnavailableException`, the API is automatically reinvoked (retried) 3 times. If the exception persists, it is possible that the throughput limits have been exceeded for the delivery stream.

Re-invoking the Put API operations (for example, `PutRecord` and `PutRecordBatch`) can result in data duplicates. For larger data assets, allow for a longer time out before retrying Put API operations.

Data records sent to Firehose are stored for 24 hours from the time they are added to a delivery stream as it attempts to send the records to the destination. If the destination is unreachable for more than 24 hours, the data is no longer available.

Important

Don't concatenate two or more base64 strings to form the data fields of your records. Instead, concatenate the raw data, then perform base64 encoding.

Request Syntax

```
{
  "DeliveryStreamName": "string",
  "Records": [
    {
      "Data": blob
    }
  ]
}
```

Request Parameters

The request accepts the following data in JSON format.

DeliveryStreamName

The name of the delivery stream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

Records

One or more records.

Type: Array of [Record](#) objects

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Required: Yes

Response Syntax

```
{
  "Encrypted": boolean,
  "FailedPutCount": number,
  "RequestResponses": [
    {
      "ErrorCode": "string",
      "ErrorMessage": "string",
      "RecordId": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Encrypted

Indicates whether server-side encryption (SSE) was enabled during this operation.

Type: Boolean

FailedPutCount

The number of records that might have failed processing. This number might be greater than 0 even if the [PutRecordBatch](#) call succeeds. Check FailedPutCount to determine whether there are records that you need to resend.

Type: Integer

Valid Range: Minimum value of 0.

RequestResponses

The results array. For each record, the index of the response element is the same as the index used in the request array.

Type: Array of [PutRecordBatchResponseEntry](#) objects

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidArgumentException

The specified input parameter has a value that is not valid.

HTTP Status Code: 400

InvalidKMSResourceException

Firehose throws this exception when an attempt to put records or to start or stop delivery stream encryption fails. This happens when the KMS service throws one of the following exception types: `AccessDeniedException`, `InvalidStateException`, `DisabledException`, or `NotFoundException`.

HTTP Status Code: 400

InvalidSourceException

Only requests from CloudWatch Logs are supported when CloudWatch Logs decompression is enabled.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 400

ServiceUnavailableException

The service is unavailable. Back off and retry the operation. If you continue to see the exception, throughput limits for the delivery stream may have been exceeded. For more information about limits and how to request an increase, see [Amazon Firehose Limits](#).

HTTP Status Code: 500

Examples

Example

The following JSON puts two records in the delivery stream named `some_delivery_stream`:

Sample Request

```
POST / HTTP/1.1
Host: firehose.<region>.<domain>
Content-Length: <PayloadSizeBytes>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Authorization: <AuthParams>
Connection: Keep-Alive
X-Amz-Date: <Date>
X-Amz-Target: Firehose_20150804.PutRecordBatch
{
  "DeliveryStreamName": "some_delivery_stream",
  "Records": [
    {
      "Data": "Some data blob."
```

```
    },  
    {  
      "Data": "Another blob of data."  
    }  
  ]  
}
```

Sample Response

```
HTTP/1.1 200 OK  
x-amzn-RequestId: <RequestId>  
Content-Type: application/x-amz-json-1.1  
Content-Length: <PayloadSizeBytes>  
Date: <Date>  
{  
  "FailedPutCount": 0,  
  "RequestResponses": [  
    {  
      "RecordId": "AJJBAL1fiFN9HyhPj6Dc+XqcR1TjqyIbr927TsEmWWpN39EK/  
JbRTbXDZFNCCrWIs/4YUd3gjYUs6giZn76TuI4vv0ljDOMFJvLzqLuupu93RscZRmpW1CP8DeiFzJJGvqIr1LRE/  
MDozYen0z  
+v1ZIQeJEcvfMwIz6silvDaGuYtIhVzwd8yWaDGFCX40Des6W07W9W7Q5ViMPUKSt6F0nn70hVkJ3/"  
    },  
    {  
      "RecordId": "goGaFS919Mmv7lYET0oMaw+UL9iFpzi100o  
+csoIc31SmvkqpWzQuT0RPqZ7QqfR1FJ  
+HxJciW/8paFMWPByJ6qVDhiE7TtJxARKaP4YDccvWHXhD7x6Y4bc9AHZ0uzy  
+BEuTTnH5Zsip1IrEPgu8lj8a7fd6sluTe/kZ54GVG+Sc105IrxIu08kPbRiUTWL  
+Wg0A3Hz0QeePqokRKKqmoXLG0pzx/80"  
    }  
  ]  
}
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)

- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

StartDeliveryStreamEncryption

Enables server-side encryption (SSE) for the delivery stream.

This operation is asynchronous. It returns immediately. When you invoke it, Firehose first sets the encryption status of the stream to `ENABLING`, and then to `ENABLED`. The encryption status of a delivery stream is the `Status` property in [DeliveryStreamEncryptionConfiguration](#). If the operation fails, the encryption status changes to `ENABLING_FAILED`. You can continue to read and write data to your delivery stream while the encryption status is `ENABLING`, but the data is not encrypted. It can take up to 5 seconds after the encryption status changes to `ENABLED` before all records written to the delivery stream are encrypted. To find out whether a record or a batch of records was encrypted, check the response elements [PutRecord:Encrypted](#) and [PutRecordBatch:Encrypted](#), respectively.

To check the encryption status of a delivery stream, use [DescribeDeliveryStream](#).

Even if encryption is currently enabled for a delivery stream, you can still invoke this operation on it to change the ARN of the CMK or both its type and ARN. If you invoke this method to change the CMK, and the old CMK is of type `CUSTOMER_MANAGED_CMK`, Firehose schedules the grant it had on the old CMK for retirement. If the new CMK is of type `CUSTOMER_MANAGED_CMK`, Firehose creates a grant that enables it to use the new CMK to encrypt and decrypt data and to manage the grant.

For the KMS grant creation to be successful, the Firehose API operations `StartDeliveryStreamEncryption` and `CreateDeliveryStream` should not be called with session credentials that are more than 6 hours old.

If a delivery stream already has encryption enabled and then you invoke this operation to change the ARN of the CMK or both its type and ARN and you get `ENABLING_FAILED`, this only means that the attempt to change the CMK failed. In this case, encryption remains enabled with the old CMK.

If the encryption status of your delivery stream is `ENABLING_FAILED`, you can invoke this operation again with a valid CMK. The CMK must be enabled and the key policy mustn't explicitly deny the permission for Firehose to invoke KMS encrypt and decrypt operations.

You can enable SSE for a delivery stream only if it's a delivery stream that uses `DirectPut` as its source.

The `StartDeliveryStreamEncryption` and `StopDeliveryStreamEncryption` operations have a combined limit of 25 calls per delivery stream per 24 hours. For

example, you reach the limit if you call `StartDeliveryStreamEncryption` 13 times and `StopDeliveryStreamEncryption` 12 times for the same delivery stream in a 24-hour period.

Request Syntax

```
{
  "DeliveryStreamEncryptionConfigurationInput": {
    "KeyARN": "string",
    "KeyType": "string"
  },
  "DeliveryStreamName": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

[DeliveryStreamEncryptionConfigurationInput](#)

Used to specify the type and Amazon Resource Name (ARN) of the KMS key needed for Server-Side Encryption (SSE).

Type: [DeliveryStreamEncryptionConfigurationInput](#) object

Required: No

[DeliveryStreamName](#)

The name of the delivery stream for which you want to enable server-side encryption (SSE).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidArgumentException

The specified input parameter has a value that is not valid.

HTTP Status Code: 400

InvalidKMSResourceException

Firehose throws this exception when an attempt to put records or to start or stop delivery stream encryption fails. This happens when the KMS service throws one of the following exception types: `AccessDeniedException`, `InvalidStateException`, `DisabledException`, or `NotFoundException`.

HTTP Status Code: 400

LimitExceededException

You have already reached the limit for a requested resource.

HTTP Status Code: 400

ResourceInUseException

The resource is already in use and not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 400

Examples

To start server-side encryption for a stream

The following JSON example starts server-side encryption (SSE) for the specified stream.

Sample Request

```
POST / HTTP/1.1
Host: firehose.<region>.<domain>
Content-Length: <PayloadSizeBytes>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Authorization: <AuthParams>
Connection: Keep-Alive
X-Amz-Date: <Date>
X-Amz-Target: Firehose_20150804.StartDeliveryStreamEncryption
{
  "DeliveryStreamName": "exampleDeliveryStreamName"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

StopDeliveryStreamEncryption

Disables server-side encryption (SSE) for the delivery stream.

This operation is asynchronous. It returns immediately. When you invoke it, Firehose first sets the encryption status of the stream to `DISABLING`, and then to `DISABLED`. You can continue to read and write data to your stream while its status is `DISABLING`. It can take up to 5 seconds after the encryption status changes to `DISABLED` before all records written to the delivery stream are no longer subject to encryption. To find out whether a record or a batch of records was encrypted, check the response elements [PutRecord:Encrypted](#) and [PutRecordBatch:Encrypted](#), respectively.

To check the encryption state of a delivery stream, use [DescribeDeliveryStream](#).

If SSE is enabled using a customer managed CMK and then you invoke `StopDeliveryStreamEncryption`, Firehose schedules the related KMS grant for retirement and then retires it after it ensures that it is finished delivering records to the destination.

The `StartDeliveryStreamEncryption` and `StopDeliveryStreamEncryption` operations have a combined limit of 25 calls per delivery stream per 24 hours. For example, you reach the limit if you call `StartDeliveryStreamEncryption` 13 times and `StopDeliveryStreamEncryption` 12 times for the same delivery stream in a 24-hour period.

Request Syntax

```
{
  "DeliveryStreamName": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

[DeliveryStreamName](#)

The name of the delivery stream for which you want to disable server-side encryption (SSE).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9_.-]+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidArgumentException

The specified input parameter has a value that is not valid.

HTTP Status Code: 400

LimitExceededException

You have already reached the limit for a requested resource.

HTTP Status Code: 400

ResourceInUseException

The resource is already in use and not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 400

Examples

To stop server-side encryption for a stream

The following JSON example stops server-side encryption (SSE) for the specified stream.

Sample Request

```
POST / HTTP/1.1
```

```
Host: firehose.<region>.<domain>
Content-Length: <PayloadSizeBytes>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Authorization: <AuthParams>
Connection: Keep-Alive
X-Amz-Date: <Date>
X-Amz-Target: Firehose_20150804.StopDeliveryStreamEncryption
{
  "DeliveryStreamName": "exampleDeliveryStreamName"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

TagDeliveryStream

Adds or updates tags for the specified delivery stream. A tag is a key-value pair that you can define and assign to Amazon resources. If you specify a tag that already exists, the tag value is replaced with the value that you specify in the request. Tags are metadata. For example, you can add friendly names and descriptions or other types of information that can help you distinguish the delivery stream. For more information about tags, see [Using Cost Allocation Tags](#) in the *Amazon Billing and Cost Management User Guide*.

Each delivery stream can have up to 50 tags.

This operation has a limit of five transactions per second per account.

Request Syntax

```
{
  "DeliveryStreamName": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

The request accepts the following data in JSON format.

[DeliveryStreamName](#)

The name of the delivery stream to which you want to add the tags.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

Tags

A set of key-value pairs to use to create the tags.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidArgumentException

The specified input parameter has a value that is not valid.

HTTP Status Code: 400

LimitExceededException

You have already reached the limit for a requested resource.

HTTP Status Code: 400

ResourceInUseException

The resource is already in use and not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 400

Examples

To add tags to a stream

The following JSON example adds two tags to the specified stream.

Sample Request

```
POST / HTTP/1.1
Host: firehose.<region>.<domain>
Content-Length: <PayloadSizeBytes>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Authorization: <AuthParams>
Connection: Keep-Alive
X-Amz-Date: <Date>
X-Amz-Target: Firehose_20150804.TagDeliveryStream
{
  "DeliveryStreamName": "exampleDeliveryStreamName",
  "Tags": [
    {
      "Key": "Project",
      "Value": "myProject"
    },
    {
      "Key": "Environment",
      "Value": "Production"
    }
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UntagDeliveryStream

Removes tags from the specified delivery stream. Removed tags are deleted, and you can't recover them after this operation successfully completes.

If you specify a tag that doesn't exist, the operation ignores it.

This operation has a limit of five transactions per second per account.

Request Syntax

```
{  
  "DeliveryStreamName": "string",  
  "TagKeys": [ "string" ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

[DeliveryStreamName](#)

The name of the delivery stream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

[TagKeys](#)

A list of tag keys. Each corresponding tag is removed from the delivery stream.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^(?!(aws:)[\p{L}\p{Z}\p{N}_.:\/=+\\-@%]*\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidArgumentException

The specified input parameter has a value that is not valid.

HTTP Status Code: 400

LimitExceededException

You have already reached the limit for a requested resource.

HTTP Status Code: 400

ResourceInUseException

The resource is already in use and not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 400

Examples

To remove tags from a stream

The following JSON example removes the specified tag from the specified stream.

Sample Request

```
POST / HTTP/1.1
```

```
Host: firehose.<region>.<domain>
Content-Length: <PayloadSizeBytes>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Authorization: <AuthParams>
Connection: Keep-Alive
X-Amz-Date: <Date>
X-Amz-Target: Firehose_20150804.UntagDeliveryStream
{
  "DeliveryStreamName": "exampleDeliveryStreamName",
  "TagKeys": ["Project", "Environment"]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateDestination

Updates the specified destination of the specified delivery stream.

Use this operation to change the destination type (for example, to replace the Amazon S3 destination with Amazon Redshift) or change the parameters associated with a destination (for example, to change the bucket name of the Amazon S3 destination). The update might not occur immediately. The target delivery stream remains active while the configurations are updated, so data writes to the delivery stream can continue during this process. The updated configurations are usually effective within a few minutes.

Switching between Amazon OpenSearch Service and other services is not supported. For an Amazon OpenSearch Service destination, you can only update to another Amazon OpenSearch Service destination.

If the destination type is the same, Firehose merges the configuration parameters specified with the destination configuration that already exists on the delivery stream. If any of the parameters are not specified in the call, the existing values are retained. For example, in the Amazon S3 destination, if [EncryptionConfiguration](#) is not specified, then the existing `EncryptionConfiguration` is maintained on the destination.

If the destination type is not the same, for example, changing the destination from Amazon S3 to Amazon Redshift, Firehose does not merge any parameters. In this case, all parameters must be specified.

Firehose uses `CurrentDeliveryStreamVersionId` to avoid race conditions and conflicting merges. This is a required field, and the service updates the configuration only if the existing configuration has a version ID that matches. After the update is applied successfully, the version ID is updated, and can be retrieved using [DescribeDeliveryStream](#). Use the new version ID to set `CurrentDeliveryStreamVersionId` in the next call.

Request Syntax

```
{
  "AmazonOpenSearchServerlessDestinationUpdate": {
    "BufferingHints": {
      "IntervalInSeconds": number,
      "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
```

```
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "CollectionEndpoint": "string",
  "IndexName": "string",
  "ProcessingConfiguration": {
    "Enabled": boolean,
    "Processors": [
      {
        "Parameters": [
          {
            "ParameterName": "string",
            "ParameterValue": "string"
          }
        ],
        "Type": "string"
      }
    ]
  },
  "RetryOptions": {
    "DurationInSeconds": number
  },
  "RoleARN": "string",
  "S3Update": {
    "BucketARN": "string",
    "BufferingHints": {
      "IntervalInSeconds": number,
      "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
      "Enabled": boolean,
      "LogGroupName": "string",
      "LogStreamName": "string"
    },
    "CompressionFormat": "string",
    "EncryptionConfiguration": {
      "KMSEncryptionConfig": {
        "AWSKMSKeyARN": "string"
      },
      "NoEncryptionConfig": "string"
    },
    "ErrorOutputPrefix": "string",
    "Prefix": "string",
```



```
    "RoleARN": "string"
  },
},
"AmazonopensearchserviceDestinationUpdate": {
  "BufferingHints": {
    "IntervalInSeconds": number,
    "SizeInMBs": number
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "ClusterEndpoint": "string",
  "DocumentIdOptions": {
    "DefaultDocumentIdFormat": "string"
  },
  "DomainARN": "string",
  "IndexName": "string",
  "IndexRotationPeriod": "string",
  "ProcessingConfiguration": {
    "Enabled": boolean,
    "Processors": [
      {
        "Parameters": [
          {
            "ParameterName": "string",
            "ParameterValue": "string"
          }
        ],
        "Type": "string"
      }
    ]
  },
  "RetryOptions": {
    "DurationInSeconds": number
  },
  "RoleARN": "string",
  "S3Update": {
    "BucketARN": "string",
    "BufferingHints": {
      "IntervalInSeconds": number,
      "SizeInMBs": number
    }
  },
},
```

```

    "CloudWatchLoggingOptions": {
        "Enabled": boolean,
        "LogGroupName": "string",
        "LogStreamName": "string"
    },
    "CompressionFormat": "string",
    "EncryptionConfiguration": {
        "KMSEncryptionConfig": {
            "AWSKMSKeyARN": "string"
        },
        "NoEncryptionConfig": "string"
    },
    "ErrorOutputPrefix": "string",
    "Prefix": "string",
    "RoleARN": "string"
},
"TypeName": "string"
},
"CurrentDeliveryStreamVersionId": "string",
"DeliveryStreamName": "string",
"DestinationId": "string",
"ElasticsearchDestinationUpdate": {
    "BufferingHints": {
        "IntervalInSeconds": number,
        "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
        "Enabled": boolean,
        "LogGroupName": "string",
        "LogStreamName": "string"
    },
    "ClusterEndpoint": "string",
    "DocumentIdOptions": {
        "DefaultDocumentIdFormat": "string"
    },
    "DomainARN": "string",
    "IndexName": "string",
    "IndexRotationPeriod": "string",
    "ProcessingConfiguration": {
        "Enabled": boolean,
        "Processors": [
            {
                "Parameters": [

```

```

        "ParameterName": "string",
        "ParameterValue": "string"
    }
],
    "Type": "string"
}
]
},
"RetryOptions": {
    "DurationInSeconds": number
},
"RoleARN": "string",
"S3Update": {
    "BucketARN": "string",
    "BufferingHints": {
        "IntervalInSeconds": number,
        "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
        "Enabled": boolean,
        "LogGroupName": "string",
        "LogStreamName": "string"
    },
    "CompressionFormat": "string",
    "EncryptionConfiguration": {
        "KMSEncryptionConfig": {
            "AWSKMSKeyARN": "string"
        },
        "NoEncryptionConfig": "string"
    },
    "ErrorOutputPrefix": "string",
    "Prefix": "string",
    "RoleARN": "string"
},
"TypeName": "string"
},
"ExtendedS3DestinationUpdate": {
    "BucketARN": "string",
    "BufferingHints": {
        "IntervalInSeconds": number,
        "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
        "Enabled": boolean,

```

```

    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "CompressionFormat": "string",
  "CustomTimeZone": "string",
  "DataFormatConversionConfiguration": {
    "Enabled": boolean,
    "InputFormatConfiguration": {
      "Deserializer": {
        "HiveJsonSerDe": {
          "TimestampFormats": [ "string" ]
        },
        "OpenXJsonSerDe": {
          "CaseInsensitive": boolean,
          "ColumnToJsonKeyMappings": {
            "string" : "string"
          },
          "ConvertDotsInJsonKeysToUnderscores": boolean
        }
      }
    },
    "OutputFormatConfiguration": {
      "Serializer": {
        "OrcSerDe": {
          "BlockSizeBytes": number,
          "BloomFilterColumns": [ "string" ],
          "BloomFilterFalsePositiveProbability": number,
          "Compression": "string",
          "DictionaryKeyThreshold": number,
          "EnablePadding": boolean,
          "FormatVersion": "string",
          "PaddingTolerance": number,
          "RowIndexStride": number,
          "StripeSizeBytes": number
        },
        "ParquetSerDe": {
          "BlockSizeBytes": number,
          "Compression": "string",
          "EnableDictionaryCompression": boolean,
          "MaxPaddingBytes": number,
          "PageSizeBytes": number,
          "WriterVersion": "string"
        }
      }
    }
  }
}

```

```
    },
    "SchemaConfiguration": {
      "CatalogId": "string",
      "DatabaseName": "string",
      "Region": "string",
      "RoleARN": "string",
      "TableName": "string",
      "VersionId": "string"
    }
  },
  "DynamicPartitioningConfiguration": {
    "Enabled": boolean,
    "RetryOptions": {
      "DurationInSeconds": number
    }
  },
  "EncryptionConfiguration": {
    "KMSEncryptionConfig": {
      "AWSKMSKeyARN": "string"
    },
    "NoEncryptionConfig": "string"
  },
  "ErrorOutputPrefix": "string",
  "FileExtension": "string",
  "Prefix": "string",
  "ProcessingConfiguration": {
    "Enabled": boolean,
    "Processors": [
      {
        "Parameters": [
          {
            "ParameterName": "string",
            "ParameterValue": "string"
          }
        ],
        "Type": "string"
      }
    ]
  },
  "RoleARN": "string",
  "S3BackupMode": "string",
  "S3BackupUpdate": {
    "BucketARN": "string",
    "BufferingHints": {
```

```
    "IntervalInSeconds": number,
    "SizeInMBs": number
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "CompressionFormat": "string",
  "EncryptionConfiguration": {
    "KMSEncryptionConfig": {
      "AWSKMSKeyARN": "string"
    },
    "NoEncryptionConfig": "string"
  },
  "ErrorOutputPrefix": "string",
  "Prefix": "string",
  "RoleARN": "string"
}
},
"HttpEndpointDestinationUpdate": {
  "BufferingHints": {
    "IntervalInSeconds": number,
    "SizeInMBs": number
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "EndpointConfiguration": {
    "AccessKey": "string",
    "Name": "string",
    "Url": "string"
  },
  "ProcessingConfiguration": {
    "Enabled": boolean,
    "Processors": [
      {
        "Parameters": [
          {
            "ParameterName": "string",
            "ParameterValue": "string"
          }
        ]
      }
    ]
  }
}
```

```

        ],
        "Type": "string"
    }
]
},
"RequestConfiguration": {
    "CommonAttributes": [
        {
            "AttributeName": "string",
            "AttributeValue": "string"
        }
    ],
    "ContentEncoding": "string"
},
"RetryOptions": {
    "DurationInSeconds": number
},
"RoleARN": "string",
"S3BackupMode": "string",
"S3Update": {
    "BucketARN": "string",
    "BufferingHints": {
        "IntervalInSeconds": number,
        "SizeInMBs": number
    },
},
"CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
},
"CompressionFormat": "string",
"EncryptionConfiguration": {
    "KMSEncryptionConfig": {
        "AWSKMSKeyARN": "string"
    },
    "NoEncryptionConfig": "string"
},
"ErrorOutputPrefix": "string",
"Prefix": "string",
"RoleARN": "string"
},
},
"RedshiftDestinationUpdate": {
    "CloudWatchLoggingOptions": {

```

```
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "ClusterJDBCURL": "string",
  "CopyCommand": {
    "CopyOptions": "string",
    "DataTableColumns": "string",
    "DataTableName": "string"
  },
  "Password": "string",
  "ProcessingConfiguration": {
    "Enabled": boolean,
    "Processors": [
      {
        "Parameters": [
          {
            "ParameterName": "string",
            "ParameterValue": "string"
          }
        ],
        "Type": "string"
      }
    ]
  },
  "RetryOptions": {
    "DurationInSeconds": number
  },
  "RoleARN": "string",
  "S3BackupMode": "string",
  "S3BackupUpdate": {
    "BucketARN": "string",
    "BufferingHints": {
      "IntervalInSeconds": number,
      "SizeInMBs": number
    }
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "CompressionFormat": "string",
  "EncryptionConfiguration": {
    "KMSEncryptionConfig": {
```



```
    "AWSKMSKeyARN": "string"
  },
  "NoEncryptionConfig": "string"
},
"ErrorOutputPrefix": "string",
"Prefix": "string",
"RoleARN": "string"
},
"S3Update": {
  "BucketARN": "string",
  "BufferingHints": {
    "IntervalInSeconds": number,
    "SizeInMBs": number
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "CompressionFormat": "string",
  "EncryptionConfiguration": {
    "KMSEncryptionConfig": {
      "AWSKMSKeyARN": "string"
    },
    "NoEncryptionConfig": "string"
  },
  "ErrorOutputPrefix": "string",
  "Prefix": "string",
  "RoleARN": "string"
},
"Username": "string"
},
"S3DestinationUpdate": {
  "BucketARN": "string",
  "BufferingHints": {
    "IntervalInSeconds": number,
    "SizeInMBs": number
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "CompressionFormat": "string",
```

```

    "EncryptionConfiguration": {
      "KMSEncryptionConfig": {
        "AWSKMSKeyARN": "string"
      },
      "NoEncryptionConfig": "string"
    },
    "ErrorOutputPrefix": "string",
    "Prefix": "string",
    "RoleARN": "string"
  },
  "SnowflakeDestinationUpdate": {
    "AccountUrl": "string",
    "CloudWatchLoggingOptions": {
      "Enabled": boolean,
      "LogGroupName": "string",
      "LogStreamName": "string"
    },
    "ContentColumnName": "string",
    "Database": "string",
    "DataLoadingOption": "string",
    "KeyPassphrase": "string",
    "MetaDataColumnName": "string",
    "PrivateKey": "string",
    "ProcessingConfiguration": {
      "Enabled": boolean,
      "Processors": [
        {
          "Parameters": [
            {
              "ParameterName": "string",
              "ParameterValue": "string"
            }
          ],
          "Type": "string"
        }
      ]
    },
    "RetryOptions": {
      "DurationInSeconds": number
    },
    "RoleARN": "string",
    "S3BackupMode": "string",
    "S3Update": {
      "BucketARN": "string",

```

```
    "BufferingHints": {
      "IntervalInSeconds": number,
      "SizeInMBs": number
    },
    "CloudWatchLoggingOptions": {
      "Enabled": boolean,
      "LogGroupName": "string",
      "LogStreamName": "string"
    },
    "CompressionFormat": "string",
    "EncryptionConfiguration": {
      "KMSEncryptionConfig": {
        "AWSKMSKeyARN": "string"
      },
      "NoEncryptionConfig": "string"
    },
    "ErrorOutputPrefix": "string",
    "Prefix": "string",
    "RoleARN": "string"
  },
  "Schema": "string",
  "SnowflakeRoleConfiguration": {
    "Enabled": boolean,
    "SnowflakeRole": "string"
  },
  "Table": "string",
  "User": "string"
},
"SplunkDestinationUpdate": {
  "BufferingHints": {
    "IntervalInSeconds": number,
    "SizeInMBs": number
  },
  "CloudWatchLoggingOptions": {
    "Enabled": boolean,
    "LogGroupName": "string",
    "LogStreamName": "string"
  },
  "HECAcknowledgmentTimeoutInSeconds": number,
  "HECEndpoint": "string",
  "HECEndpointType": "string",
  "HECToken": "string",
  "ProcessingConfiguration": {
    "Enabled": boolean,
```

```
    "Processors": [
      {
        "Parameters": [
          {
            "ParameterName": "string",
            "ParameterValue": "string"
          }
        ],
        "Type": "string"
      }
    ],
    "RetryOptions": {
      "DurationInSeconds": number
    },
    "S3BackupMode": "string",
    "S3Update": {
      "BucketARN": "string",
      "BufferingHints": {
        "IntervalInSeconds": number,
        "SizeInMBs": number
      },
      "CloudWatchLoggingOptions": {
        "Enabled": boolean,
        "LogGroupName": "string",
        "LogStreamName": "string"
      },
      "CompressionFormat": "string",
      "EncryptionConfiguration": {
        "KMSEncryptionConfig": {
          "AWSKMSKeyARN": "string"
        },
        "NoEncryptionConfig": "string"
      },
      "ErrorOutputPrefix": "string",
      "Prefix": "string",
      "RoleARN": "string"
    }
  }
}
```

Request Parameters

The request accepts the following data in JSON format.

AmazonOpenSearchServerlessDestinationUpdate

Describes an update for a destination in the Serverless offering for Amazon OpenSearch Service.

Type: [AmazonOpenSearchServerlessDestinationUpdate](#) object

Required: No

AmazonopensearchserviceDestinationUpdate

Describes an update for a destination in Amazon OpenSearch Service.

Type: [AmazonopensearchserviceDestinationUpdate](#) object

Required: No

CurrentDeliveryStreamVersionId

Obtain this value from the VersionId result of [DeliveryStreamDescription](#). This value is required, and helps the service perform conditional operations. For example, if there is an interleaving update and this value is null, then the update destination fails. After the update is successful, the VersionId value is updated. The service then performs a merge of the old configuration with the new configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [0-9]+

Required: Yes

DeliveryStreamName

The name of the delivery stream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

DestinationId

The ID of the destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-]+

Required: Yes

ElasticsearchDestinationUpdate

Describes an update for a destination in Amazon ES.

Type: [ElasticsearchDestinationUpdate](#) object

Required: No

ExtendedS3DestinationUpdate

Describes an update for a destination in Amazon S3.

Type: [ExtendedS3DestinationUpdate](#) object

Required: No

HttpEndpointDestinationUpdate

Describes an update to the specified HTTP endpoint destination.

Type: [HttpEndpointDestinationUpdate](#) object

Required: No

RedshiftDestinationUpdate

Describes an update for a destination in Amazon Redshift.

Type: [RedshiftDestinationUpdate](#) object

Required: No

S3DestinationUpdate

[Deprecated] Describes an update for a destination in Amazon S3.

Type: [S3DestinationUpdate](#) object

Required: No

SnowflakeDestinationUpdate

Update to the Snowflake destination configuration settings.

Type: [SnowflakeDestinationUpdate](#) object

Required: No

SplunkDestinationUpdate

Describes an update for a destination in Splunk.

Type: [SplunkDestinationUpdate](#) object

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

Another modification has already happened. Fetch `VersionId` again and use it to update the destination.

HTTP Status Code: 400

InvalidArgumentException

The specified input parameter has a value that is not valid.

HTTP Status Code: 400

ResourceInUseException

The resource is already in use and not available for this operation.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 400

Examples

Example

The following JSON updates the buffering hints for the destination to 150 seconds and 2 MiB. You can obtain the other values that you need to use in this example from the response to a [DescribeDeliveryStream](#) invocation for the delivery stream in question.

Sample Request

```
POST / HTTP/1.1
Host: firehose.<region>.<domain>
Content-Length: <PayloadSizeBytes>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Authorization: <AuthParams>
Connection: Keep-Alive
X-Amz-Date: <Date>
X-Amz-Target: Firehose_20150804.UpdateDestination
{
  "CurrentDeliveryStreamVersionId": "1",
  "DeliveryStreamName": "exampleStreamName",
  "DestinationId": "destinationId-0000000000001",
  "ExtendedS3DestinationUpdate": {
    "BucketARN": "arn:aws:s3:::somebucket",
    "BufferingHints": {
      "IntervalInSeconds": 150,
      "SizeInMBs": 2
    },
    "RoleARN": "arn:aws:iam::111222333444:role/exampleStreamName"
  }
}
```



```
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

Data Types

The Amazon Kinesis Firehose API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AmazonOpenSearchServerlessBufferingHints](#)
- [AmazonOpenSearchServerlessDestinationConfiguration](#)
- [AmazonOpenSearchServerlessDestinationDescription](#)
- [AmazonOpenSearchServerlessDestinationUpdate](#)
- [AmazonOpenSearchServerlessRetryOptions](#)
- [AmazonopensearchserviceBufferingHints](#)
- [AmazonopensearchserviceDestinationConfiguration](#)
- [AmazonopensearchserviceDestinationDescription](#)
- [AmazonopensearchserviceDestinationUpdate](#)
- [AmazonopensearchserviceRetryOptions](#)
- [AuthenticationConfiguration](#)
- [BufferingHints](#)
- [CloudWatchLoggingOptions](#)
- [CopyCommand](#)
- [DataFormatConversionConfiguration](#)
- [DeliveryStreamDescription](#)
- [DeliveryStreamEncryptionConfiguration](#)
- [DeliveryStreamEncryptionConfigurationInput](#)
- [Deserializer](#)
- [DestinationDescription](#)

- [DocumentIdOptions](#)
- [DynamicPartitioningConfiguration](#)
- [ElasticsearchBufferingHints](#)
- [ElasticsearchDestinationConfiguration](#)
- [ElasticsearchDestinationDescription](#)
- [ElasticsearchDestinationUpdate](#)
- [ElasticsearchRetryOptions](#)
- [EncryptionConfiguration](#)
- [ExtendedS3DestinationConfiguration](#)
- [ExtendedS3DestinationDescription](#)
- [ExtendedS3DestinationUpdate](#)
- [FailureDescription](#)
- [HiveJsonSerDe](#)
- [HttpEndpointBufferingHints](#)
- [HttpEndpointCommonAttribute](#)
- [HttpEndpointConfiguration](#)
- [HttpEndpointDescription](#)
- [HttpEndpointDestinationConfiguration](#)
- [HttpEndpointDestinationDescription](#)
- [HttpEndpointDestinationUpdate](#)
- [HttpEndpointRequestConfiguration](#)
- [HttpEndpointRetryOptions](#)
- [InputFormatConfiguration](#)
- [KinesisStreamSourceConfiguration](#)
- [KinesisStreamSourceDescription](#)
- [KMSEncryptionConfig](#)
- [MSKSourceConfiguration](#)
- [MSKSourceDescription](#)
- [OpenXJsonSerDe](#)
- [OrcSerDe](#)

- [OutputFormatConfiguration](#)
- [ParquetSerDe](#)
- [ProcessingConfiguration](#)
- [Processor](#)
- [ProcessorParameter](#)
- [PutRecordBatchResponseEntry](#)
- [Record](#)
- [RedshiftDestinationConfiguration](#)
- [RedshiftDestinationDescription](#)
- [RedshiftDestinationUpdate](#)
- [RedshiftRetryOptions](#)
- [RetryOptions](#)
- [S3DestinationConfiguration](#)
- [S3DestinationDescription](#)
- [S3DestinationUpdate](#)
- [SchemaConfiguration](#)
- [Serializer](#)
- [SnowflakeDestinationConfiguration](#)
- [SnowflakeDestinationDescription](#)
- [SnowflakeDestinationUpdate](#)
- [SnowflakeRetryOptions](#)
- [SnowflakeRoleConfiguration](#)
- [SnowflakeVpcConfiguration](#)
- [SourceDescription](#)
- [SplunkBufferingHints](#)
- [SplunkDestinationConfiguration](#)
- [SplunkDestinationDescription](#)
- [SplunkDestinationUpdate](#)
- [SplunkRetryOptions](#)
- [Tag](#)

- [VpcConfiguration](#)
- [VpcConfigurationDescription](#)

AmazonOpenSearchServerlessBufferingHints

Describes the buffering to perform before delivering data to the Serverless offering for Amazon OpenSearch Service destination.

Contents

IntervalInSeconds

Buffer incoming data for the specified period of time, in seconds, before delivering it to the destination. The default value is 300 (5 minutes).

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 900.

Required: No

SizeInMBs

Buffer incoming data to the specified size, in MBs, before delivering it to the destination. The default value is 5.

We recommend setting this parameter to a value greater than the amount of data you typically ingest into the delivery stream in 10 seconds. For example, if you typically ingest data at 1 MB/sec, the value should be 10 MB or higher.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AmazonOpenSearchServerlessDestinationConfiguration

Describes the configuration of a destination in the Serverless offering for Amazon OpenSearch Service.

Contents

IndexName

The Serverless offering for Amazon OpenSearch Service index name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 80.

Pattern: `.*`

Required: Yes

RoleARN

The Amazon Resource Name (ARN) of the IAM role to be assumed by Firehose for calling the Serverless offering for Amazon OpenSearch Service Configuration API and for indexing documents.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: Yes

S3Configuration

Describes the configuration of a destination in Amazon S3.

Type: [S3DestinationConfiguration](#) object

Required: Yes

BufferingHints

The buffering options. If no value is specified, the default values for `AmazonopensearchserviceBufferingHints` are used.

Type: [AmazonOpenSearchServerlessBufferingHints](#) object

Required: No

CloudWatchLoggingOptions

Describes the Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

CollectionEndpoint

The endpoint to use when communicating with the collection in the Serverless offering for Amazon OpenSearch Service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `https:.*`

Required: No

ProcessingConfiguration

Describes a data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

The retry behavior in case Firehose is unable to deliver documents to the Serverless offering for Amazon OpenSearch Service. The default value is 300 (5 minutes).

Type: [AmazonOpenSearchServerlessRetryOptions](#) object

Required: No

S3BackupMode

Defines how documents should be delivered to Amazon S3. When it is set to `FailedDocumentsOnly`, Firehose writes any documents that could not be indexed to the

configured Amazon S3 destination, with `AmazonOpenSearchService-failed/` appended to the key prefix. When set to `AllDocuments`, Firehose delivers all incoming records to Amazon S3, and also writes failed documents with `AmazonOpenSearchService-failed/` appended to the prefix.

Type: String

Valid Values: `FailedDocumentsOnly` | `AllDocuments`

Required: No

VpcConfiguration

The details of the VPC of the Amazon OpenSearch or Amazon OpenSearch Serverless destination.

Type: [VpcConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AmazonOpenSearchServerlessDestinationDescription

The destination description in the Serverless offering for Amazon OpenSearch Service.

Contents

BufferingHints

The buffering options.

Type: [AmazonOpenSearchServerlessBufferingHints](#) object

Required: No

CloudWatchLoggingOptions

Describes the Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

CollectionEndpoint

The endpoint to use when communicating with the collection in the Serverless offering for Amazon OpenSearch Service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `https:.*`

Required: No

IndexName

The Serverless offering for Amazon OpenSearch Service index name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 80.

Pattern: `.*`

Required: No

ProcessingConfiguration

Describes a data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

The Serverless offering for Amazon OpenSearch Service retry options.

Type: [AmazonOpenSearchServerlessRetryOptions](#) object

Required: No

RoleARN

The Amazon Resource Name (ARN) of the Amazon credentials.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

S3BackupMode

The Amazon S3 backup mode.

Type: String

Valid Values: `FailedDocumentsOnly` | `AllDocuments`

Required: No

S3DestinationDescription

Describes a destination in Amazon S3.

Type: [S3DestinationDescription](#) object

Required: No

VpcConfigurationDescription

The details of the VPC of the Amazon ES destination.

Type: [VpcConfigurationDescription](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AmazonOpenSearchServerlessDestinationUpdate

Describes an update for a destination in the Serverless offering for Amazon OpenSearch Service.

Contents

BufferingHints

The buffering options. If no value is specified, AmazonopensearchBufferingHints object default values are used.

Type: [AmazonOpenSearchServerlessBufferingHints](#) object

Required: No

CloudWatchLoggingOptions

Describes the Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

CollectionEndpoint

The endpoint to use when communicating with the collection in the Serverless offering for Amazon OpenSearch Service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: https:.*

Required: No

IndexName

The Serverless offering for Amazon OpenSearch Service index name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 80.

Pattern: .*

Required: No

ProcessingConfiguration

Describes a data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

The retry behavior in case Firehose is unable to deliver documents to the Serverless offering for Amazon OpenSearch Service. The default value is 300 (5 minutes).

Type: [AmazonOpenSearchServerlessRetryOptions](#) object

Required: No

RoleARN

The Amazon Resource Name (ARN) of the IAM role to be assumed by Firehose for calling the Serverless offering for Amazon OpenSearch Service Configuration API and for indexing documents.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

S3Update

Describes an update for a destination in Amazon S3.

Type: [S3DestinationUpdate](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AmazonOpenSearchServerlessRetryOptions

Configures retry behavior in case Firehose is unable to deliver documents to the Serverless offering for Amazon OpenSearch Service.

Contents

DurationInSeconds

After an initial failure to deliver to the Serverless offering for Amazon OpenSearch Service, the total amount of time during which Firehose retries delivery (including the first attempt). After this time has elapsed, the failed documents are written to Amazon S3. Default value is 300 seconds (5 minutes). A value of 0 (zero) results in no retries.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 7200.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AmazonopensearchserviceBufferingHints

Describes the buffering to perform before delivering data to the Amazon OpenSearch Service destination.

Contents

IntervalInSeconds

Buffer incoming data for the specified period of time, in seconds, before delivering it to the destination. The default value is 300 (5 minutes).

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 900.

Required: No

SizeInMBs

Buffer incoming data to the specified size, in MBs, before delivering it to the destination. The default value is 5.

We recommend setting this parameter to a value greater than the amount of data you typically ingest into the delivery stream in 10 seconds. For example, if you typically ingest data at 1 MB/sec, the value should be 10 MB or higher.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AmazonopensearchserviceDestinationConfiguration

Describes the configuration of a destination in Amazon OpenSearch Service

Contents

IndexName

The Elasticsearch Amazon OpenSearch Service index name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 80.

Pattern: `. *`

Required: Yes

RoleARN

The Amazon Resource Name (ARN) of the IAM role to be assumed by Firehose for calling the Amazon OpenSearch Service Configuration API and for indexing documents.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: Yes

S3Configuration

Describes the configuration of a destination in Amazon S3.

Type: [S3DestinationConfiguration](#) object

Required: Yes

BufferingHints

The buffering options. If no value is specified, the default values for AmazonopensearchserviceBufferingHints are used.

Type: [AmazonopensearchserviceBufferingHints](#) object

Required: No

CloudWatchLoggingOptions

Describes the Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

ClusterEndpoint

The endpoint to use when communicating with the cluster. Specify either this ClusterEndpoint or the DomainARN field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `https:.*`

Required: No

DocumentIdOptions

Indicates the method for setting up document ID. The supported methods are Firehose generated document ID and OpenSearch Service generated document ID.

Type: [DocumentIdOptions](#) object

Required: No

DomainARN

The ARN of the Amazon OpenSearch Service domain. The IAM role must have permissions for DescribeElasticsearchDomain, DescribeElasticsearchDomains, and DescribeElasticsearchDomainConfig after assuming the role specified in RoleARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

IndexRotationPeriod

The Amazon OpenSearch Service index rotation period. Index rotation appends a timestamp to the IndexName to facilitate the expiration of old data.

Type: String

Valid Values: NoRotation | OneHour | OneDay | OneWeek | OneMonth

Required: No

ProcessingConfiguration

Describes a data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

The retry behavior in case Firehose is unable to deliver documents to Amazon OpenSearch Service. The default value is 300 (5 minutes).

Type: [AmazonopensearchserviceRetryOptions](#) object

Required: No

S3BackupMode

Defines how documents should be delivered to Amazon S3. When it is set to FailedDocumentsOnly, Firehose writes any documents that could not be indexed to the configured Amazon S3 destination, with AmazonOpenSearchService-failed/ appended to the key prefix. When set to AllDocuments, Firehose delivers all incoming records to Amazon S3, and also writes failed documents with AmazonOpenSearchService-failed/ appended to the prefix.

Type: String

Valid Values: FailedDocumentsOnly | AllDocuments

Required: No

TypeName

The Amazon OpenSearch Service type name. For Elasticsearch 6.x, there can be only one type per index. If you try to specify a new type for an existing index that already has another type, Firehose returns an error during run time.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: . *

Required: No

VpcConfiguration

The details of the VPC of the Amazon OpenSearch or Amazon OpenSearch Serverless destination.

Type: [VpcConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AmazonopensearchserviceDestinationDescription

The destination description in Amazon OpenSearch Service.

Contents

BufferingHints

The buffering options.

Type: [AmazonopensearchserviceBufferingHints](#) object

Required: No

CloudWatchLoggingOptions

Describes the Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

ClusterEndpoint

The endpoint to use when communicating with the cluster. Firehose uses either this ClusterEndpoint or the DomainARN field to send data to Amazon OpenSearch Service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: https:.*

Required: No

DocumentIdOptions

Indicates the method for setting up document ID. The supported methods are Firehose generated document ID and OpenSearch Service generated document ID.

Type: [DocumentIdOptions](#) object

Required: No

DomainARN

The ARN of the Amazon OpenSearch Service domain.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

IndexName

The Amazon OpenSearch Service index name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 80.

Pattern: `.*`

Required: No

IndexRotationPeriod

The Amazon OpenSearch Service index rotation period

Type: String

Valid Values: `NoRotation` | `OneHour` | `OneDay` | `OneWeek` | `OneMonth`

Required: No

ProcessingConfiguration

Describes a data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

The Amazon OpenSearch Service retry options.

Type: [AmazonopensearchserviceRetryOptions](#) object

Required: No

RoleARN

The Amazon Resource Name (ARN) of the Amazon credentials.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

S3BackupMode

The Amazon S3 backup mode.

Type: String

Valid Values: `FailedDocumentsOnly` | `AllDocuments`

Required: No

S3DestinationDescription

Describes a destination in Amazon S3.

Type: [S3DestinationDescription](#) object

Required: No

TypeName

The Amazon OpenSearch Service type name. This applies to Elasticsearch 6.x and lower versions. For Elasticsearch 7.x and OpenSearch Service 1.x, there's no value for TypeName.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `.*`

Required: No

VpcConfigurationDescription

The details of the VPC of the Amazon ES destination.

Type: [VpcConfigurationDescription](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AmazonopensearchserviceDestinationUpdate

Describes an update for a destination in Amazon OpenSearch Service.

Contents

BufferingHints

The buffering options. If no value is specified, AmazonopensearchBufferingHints object default values are used.

Type: [AmazonopensearchserviceBufferingHints](#) object

Required: No

CloudWatchLoggingOptions

Describes the Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

ClusterEndpoint

The endpoint to use when communicating with the cluster. Specify either this ClusterEndpoint or the DomainARN field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: https:.*

Required: No

DocumentIdOptions

Indicates the method for setting up document ID. The supported methods are Firehose generated document ID and OpenSearch Service generated document ID.

Type: [DocumentIdOptions](#) object

Required: No

DomainARN

The ARN of the Amazon OpenSearch Service domain. The IAM role must have permissions for DescribeDomain, DescribeDomains, and DescribeDomainConfig after assuming the IAM role specified in RoleARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: arn:.*

Required: No

IndexName

The Amazon OpenSearch Service index name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 80.

Pattern: .*

Required: No

IndexRotationPeriod

The Amazon OpenSearch Service index rotation period. Index rotation appends a timestamp to IndexName to facilitate the expiration of old data.

Type: String

Valid Values: NoRotation | OneHour | OneDay | OneWeek | OneMonth

Required: No

ProcessingConfiguration

Describes a data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

The retry behavior in case Firehose is unable to deliver documents to Amazon OpenSearch Service. The default value is 300 (5 minutes).

Type: [AmazonopensearchserviceRetryOptions](#) object

Required: No

RoleARN

The Amazon Resource Name (ARN) of the IAM role to be assumed by Firehose for calling the Amazon OpenSearch Service Configuration API and for indexing documents.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

S3Update

Describes an update for a destination in Amazon S3.

Type: [S3DestinationUpdate](#) object

Required: No

TypeName

The Amazon OpenSearch Service type name. For Elasticsearch 6.x, there can be only one type per index. If you try to specify a new type for an existing index that already has another type, Firehose returns an error during runtime.

If you upgrade Elasticsearch from 6.x to 7.x and don't update your delivery stream, Firehose still delivers data to Elasticsearch with the old index name and type name. If you want to update your delivery stream with a new index name, provide an empty string for TypeName.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AmazonopensearchserviceRetryOptions

Configures retry behavior in case Firehose is unable to deliver documents to Amazon OpenSearch Service.

Contents

DurationInSeconds

After an initial failure to deliver to Amazon OpenSearch Service, the total amount of time during which Firehose retries delivery (including the first attempt). After this time has elapsed, the failed documents are written to Amazon S3. Default value is 300 seconds (5 minutes). A value of 0 (zero) results in no retries.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 7200.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AuthenticationConfiguration

The authentication configuration of the Amazon MSK cluster.

Contents

Connectivity

The type of connectivity used to access the Amazon MSK cluster.

Type: String

Valid Values: PUBLIC | PRIVATE

Required: Yes

RoleARN

The ARN of the role used to access the Amazon MSK cluster.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: arn:.*

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BufferingHints

Describes hints for the buffering to perform before delivering data to the destination. These options are treated as hints, and therefore Firehose might choose to use different values when it is optimal. The `SizeInMBs` and `IntervalInSeconds` parameters are optional. However, if specify a value for one of them, you must also provide a value for the other.

Contents

IntervalInSeconds

Buffer incoming data for the specified period of time, in seconds, before delivering it to the destination. The default value is 300. This parameter is optional but if you specify a value for it, you must also specify a value for `SizeInMBs`, and vice versa.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 900.

Required: No

SizeInMBs

Buffer incoming data to the specified size, in MiBs, before delivering it to the destination. The default value is 5. This parameter is optional but if you specify a value for it, you must also specify a value for `IntervalInSeconds`, and vice versa.

We recommend setting this parameter to a value greater than the amount of data you typically ingest into the delivery stream in 10 seconds. For example, if you typically ingest data at 1 MiB/sec, the value should be 10 MiB or higher.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 128.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

CloudWatchLoggingOptions

Describes the Amazon CloudWatch logging options for your delivery stream.

Contents

Enabled

Enables or disables CloudWatch logging.

Type: Boolean

Required: No

LogGroupName

The CloudWatch group name for logging. This value is required if CloudWatch logging is enabled.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Pattern: `[\.\-_\/#A-Za-z0-9]*`

Required: No

LogStreamName

The CloudWatch log stream name for logging. This value is required if CloudWatch logging is enabled.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Pattern: `^[^:]*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

CopyCommand

Describes a COPY command for Amazon Redshift.

Contents

DataTableName

The name of the target table. The table must already exist in the database.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: . *

Required: Yes

CopyOptions

Optional parameters to use with the Amazon Redshift COPY command. For more information, see the "Optional Parameters" section of [Amazon Redshift COPY command](#). Some possible examples that would apply to Firehose are as follows:

`delimiter '\t' lzop`; - fields are delimited with "\t" (TAB character) and compressed using lzop.

`delimiter '|'` - fields are delimited with "|" (this is the default delimiter).

`delimiter '|' escape` - the delimiter should be escaped.

`fixedwidth`

`'venueid:3,venueid:25,venueid:12,venueid:2,venueid:6'` - fields are fixed width in the source, with each width specified after every column in the table.

`JSON 's3://mybucket/jsonpaths.txt'` - data is in JSON format, and the path specified is the format of the data.

For more examples, see [Amazon Redshift COPY command examples](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 204800.

Pattern: . *

Required: No

DataTableColumns

A comma-separated list of column names.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 204800.

Pattern: . *

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DataFormatConversionConfiguration

Specifies that you want Firehose to convert data from the JSON format to the Parquet or ORC format before writing it to Amazon S3. Firehose uses the serializer and deserializer that you specify, in addition to the column information from the Amazon Glue table, to deserialize your input data from JSON and then serialize it to the Parquet or ORC format. For more information, see [Firehose Record Format Conversion](#).

Contents

Enabled

Defaults to `true`. Set it to `false` if you want to disable format conversion while preserving the configuration details.

Type: Boolean

Required: No

InputFormatConfiguration

Specifies the deserializer that you want Firehose to use to convert the format of your data from JSON. This parameter is required if `Enabled` is set to `true`.

Type: [InputFormatConfiguration](#) object

Required: No

OutputFormatConfiguration

Specifies the serializer that you want Firehose to use to convert the format of your data to the Parquet or ORC format. This parameter is required if `Enabled` is set to `true`.

Type: [OutputFormatConfiguration](#) object

Required: No

SchemaConfiguration

Specifies the Amazon Glue Data Catalog table that contains the column information. This parameter is required if `Enabled` is set to `true`.

Type: [SchemaConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DeliveryStreamDescription

Contains information about a delivery stream.

Contents

DeliveryStreamARN

The Amazon Resource Name (ARN) of the delivery stream. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: arn:.*

Required: Yes

DeliveryStreamName

The name of the delivery stream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

DeliveryStreamStatus

The status of the delivery stream. If the status of a delivery stream is `CREATING_FAILED`, this status doesn't change, and you can't invoke `CreateDeliveryStream` again on it. However, you can invoke the [DeleteDeliveryStream](#) operation to delete it.

Type: String

Valid Values: `CREATING` | `CREATING_FAILED` | `DELETING` | `DELETING_FAILED` | `ACTIVE`

Required: Yes

DeliveryStreamType

The delivery stream type. This can be one of the following values:

- `DirectPut`: Provider applications access the delivery stream directly.
- `KinesisStreamAsSource`: The delivery stream uses a Kinesis data stream as a source.

Type: String

Valid Values: `DirectPut` | `KinesisStreamAsSource` | `MSKAsSource`

Required: Yes

Destinations

The destinations.

Type: Array of [DestinationDescription](#) objects

Required: Yes

HasMoreDestinations

Indicates whether there are more destinations available to list.

Type: Boolean

Required: Yes

VersionId

Each time the destination is updated for a delivery stream, the version ID is changed, and the current version ID is required when updating the destination. This is so that the service knows it is applying the changes to the correct version of the delivery stream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[0-9]+`

Required: Yes

CreateTimestamp

The date and time that the delivery stream was created.

Type: Timestamp

Required: No

DeliveryStreamEncryptionConfiguration

Indicates the server-side encryption (SSE) status for the delivery stream.

Type: [DeliveryStreamEncryptionConfiguration](#) object

Required: No

FailureDescription

Provides details in case one of the following operations fails due to an error related to KMS: [CreateDeliveryStream](#), [DeleteDeliveryStream](#), [StartDeliveryStreamEncryption](#), [StopDeliveryStreamEncryption](#).

Type: [FailureDescription](#) object

Required: No

LastUpdateTimestamp

The date and time that the delivery stream was last updated.

Type: Timestamp

Required: No

Source

If the `DeliveryStreamType` parameter is `KinesisStreamAsSource`, a [SourceDescription](#) object describing the source Kinesis data stream.

Type: [SourceDescription](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DeliveryStreamEncryptionConfiguration

Contains information about the server-side encryption (SSE) status for the delivery stream, the type customer master key (CMK) in use, if any, and the ARN of the CMK. You can get `DeliveryStreamEncryptionConfiguration` by invoking the [DescribeDeliveryStream](#) operation.

Contents

FailureDescription

Provides details in case one of the following operations fails due to an error related to KMS: [CreateDeliveryStream](#), [DeleteDeliveryStream](#), [StartDeliveryStreamEncryption](#), [StopDeliveryStreamEncryption](#).

Type: [FailureDescription](#) object

Required: No

KeyARN

If `KeyType` is `CUSTOMER_MANAGED_CMK`, this field contains the ARN of the customer managed CMK. If `KeyType` is `Amazon_OWNED_CMK`, `DeliveryStreamEncryptionConfiguration` doesn't contain a value for `KeyARN`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

KeyType

Indicates the type of customer master key (CMK) that is used for encryption. The default setting is `Amazon_OWNED_CMK`. For more information about CMKs, see [Customer Master Keys \(CMKs\)](#).

Type: String

Valid Values: `AWS_OWNED_CMK` | `CUSTOMER_MANAGED_CMK`

Required: No

Status

This is the server-side encryption (SSE) status for the delivery stream. For a full description of the different values of this status, see [StartDeliveryStreamEncryption](#) and [StopDeliveryStreamEncryption](#). If this status is `ENABLING_FAILED` or `DISABLING_FAILED`, it is the status of the most recent attempt to enable or disable SSE, respectively.

Type: String

Valid Values: `ENABLED` | `ENABLING` | `ENABLING_FAILED` | `DISABLED` | `DISABLING` | `DISABLING_FAILED`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DeliveryStreamEncryptionConfigurationInput

Specifies the type and Amazon Resource Name (ARN) of the CMK to use for Server-Side Encryption (SSE).

Contents

KeyType

Indicates the type of customer master key (CMK) to use for encryption. The default setting is `Amazon_OWNED_CMK`. For more information about CMKs, see [Customer Master Keys \(CMKs\)](#). When you invoke [CreateDeliveryStream](#) or [StartDeliveryStreamEncryption](#) with `KeyType` set to `CUSTOMER_MANAGED_CMK`, Firehose invokes the Amazon KMS operation [CreateGrant](#) to create a grant that allows the Firehose service to use the customer managed CMK to perform encryption and decryption. Firehose manages that grant.

When you invoke [StartDeliveryStreamEncryption](#) to change the CMK for a delivery stream that is encrypted with a customer managed CMK, Firehose schedules the grant it had on the old CMK for retirement.

You can use a CMK of type `CUSTOMER_MANAGED_CMK` to encrypt up to 500 delivery streams. If a [CreateDeliveryStream](#) or [StartDeliveryStreamEncryption](#) operation exceeds this limit, Firehose throws a `LimitExceededException`.

Important

To encrypt your delivery stream, use symmetric CMKs. Firehose doesn't support asymmetric CMKs. For information about symmetric and asymmetric CMKs, see [About Symmetric and Asymmetric CMKs](#) in the Amazon Key Management Service developer guide.

Type: String

Valid Values: `AWS_OWNED_CMK` | `CUSTOMER_MANAGED_CMK`

Required: Yes

KeyARN

If you set `KeyType` to `CUSTOMER_MANAGED_CMK`, you must specify the Amazon Resource Name (ARN) of the CMK. If you set `KeyType` to `Amazon_OWNED_CMK`, Firehose uses a service-account CMK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Deserializer

The deserializer you want Firehose to use for converting the input data from JSON. Firehose then serializes the data to its final format using the [Serializer](#). Firehose supports two types of deserializers: the [Apache Hive JSON SerDe](#) and the [OpenX JSON SerDe](#).

Contents

HiveJsonSerDe

The native Hive / HCatalog JsonSerDe. Used by Firehose for deserializing data, which means converting it from the JSON format in preparation for serializing it to the Parquet or ORC format. This is one of two deserializers you can choose, depending on which one offers the functionality you need. The other option is the OpenX SerDe.

Type: [HiveJsonSerDe](#) object

Required: No

OpenXJsonSerDe

The OpenX SerDe. Used by Firehose for deserializing data, which means converting it from the JSON format in preparation for serializing it to the Parquet or ORC format. This is one of two deserializers you can choose, depending on which one offers the functionality you need. The other option is the native Hive / HCatalog JsonSerDe.

Type: [OpenXJsonSerDe](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DestinationDescription

Describes the destination for a delivery stream.

Contents

DestinationId

The ID of the destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9-]+

Required: Yes

AmazonOpenSearchServerlessDestinationDescription

The destination in the Serverless offering for Amazon OpenSearch Service.

Type: [AmazonOpenSearchServerlessDestinationDescription](#) object

Required: No

AmazonopensearchserviceDestinationDescription

The destination in Amazon OpenSearch Service.

Type: [AmazonopensearchserviceDestinationDescription](#) object

Required: No

ElasticsearchDestinationDescription

The destination in Amazon ES.

Type: [ElasticsearchDestinationDescription](#) object

Required: No

ExtendedS3DestinationDescription

The destination in Amazon S3.

Type: [ExtendedS3DestinationDescription](#) object

Required: No

HttpEndpointDestinationDescription

Describes the specified HTTP endpoint destination.

Type: [HttpEndpointDestinationDescription](#) object

Required: No

RedshiftDestinationDescription

The destination in Amazon Redshift.

Type: [RedshiftDestinationDescription](#) object

Required: No

S3DestinationDescription

[Deprecated] The destination in Amazon S3.

Type: [S3DestinationDescription](#) object

Required: No

SnowflakeDestinationDescription

Optional description for the destination

Type: [SnowflakeDestinationDescription](#) object

Required: No

SplunkDestinationDescription

The destination in Splunk.

Type: [SplunkDestinationDescription](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DocumentIdOptions

Indicates the method for setting up document ID. The supported methods are Firehose generated document ID and OpenSearch Service generated document ID.

Contents

DefaultDocumentIdFormat

When the `FIREHOSE_DEFAULT` option is chosen, Firehose generates a unique document ID for each record based on a unique internal identifier. The generated document ID is stable across multiple delivery attempts, which helps prevent the same record from being indexed multiple times with different document IDs.

When the `NO_DOCUMENT_ID` option is chosen, Firehose does not include any document IDs in the requests it sends to the Amazon OpenSearch Service. This causes the Amazon OpenSearch Service domain to generate document IDs. In case of multiple delivery attempts, this may cause the same record to be indexed more than once with different document IDs. This option enables write-heavy operations, such as the ingestion of logs and observability data, to consume less resources in the Amazon OpenSearch Service domain, resulting in improved performance.

Type: String

Valid Values: `FIREHOSE_DEFAULT` | `NO_DOCUMENT_ID`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DynamicPartitioningConfiguration

The configuration of the dynamic partitioning mechanism that creates smaller data sets from the streaming data by partitioning it based on partition keys. Currently, dynamic partitioning is only supported for Amazon S3 destinations.

Contents

Enabled

Specifies that the dynamic partitioning is enabled for this Firehose delivery stream.

Type: Boolean

Required: No

RetryOptions

The retry behavior in case Firehose is unable to deliver data to an Amazon S3 prefix.

Type: [RetryOptions](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ElasticsearchBufferingHints

Describes the buffering to perform before delivering data to the Amazon ES destination.

Contents

IntervalInSeconds

Buffer incoming data for the specified period of time, in seconds, before delivering it to the destination. The default value is 300 (5 minutes).

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 900.

Required: No

SizeInMBs

Buffer incoming data to the specified size, in MBs, before delivering it to the destination. The default value is 5.

We recommend setting this parameter to a value greater than the amount of data you typically ingest into the delivery stream in 10 seconds. For example, if you typically ingest data at 1 MB/sec, the value should be 10 MB or higher.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ElasticsearchDestinationConfiguration

Describes the configuration of a destination in Amazon ES.

Contents

IndexName

The Elasticsearch index name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 80.

Pattern: `.*`

Required: Yes

RoleARN

The Amazon Resource Name (ARN) of the IAM role to be assumed by Firehose for calling the Amazon ES Configuration API and for indexing documents. For more information, see [Grant Firehose Access to an Amazon S3 Destination](#) and [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: Yes

S3Configuration

The configuration for the backup Amazon S3 location.

Type: [S3DestinationConfiguration](#) object

Required: Yes

BufferingHints

The buffering options. If no value is specified, the default values for `ElasticsearchBufferingHints` are used.

Type: [ElasticsearchBufferingHints](#) object

Required: No

CloudWatchLoggingOptions

The Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

ClusterEndpoint

The endpoint to use when communicating with the cluster. Specify either this `ClusterEndpoint` or the `DomainARN` field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `https:.*`

Required: No

DocumentIdOptions

Indicates the method for setting up document ID. The supported methods are Firehose generated document ID and OpenSearch Service generated document ID.

Type: [DocumentIdOptions](#) object

Required: No

DomainARN

The ARN of the Amazon ES domain. The IAM role must have permissions for `DescribeDomain`, `DescribeDomains`, and `DescribeDomainConfig` after assuming the role specified in **RoleARN**. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Specify either `ClusterEndpoint` or `DomainARN`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

IndexRotationPeriod

The Elasticsearch index rotation period. Index rotation appends a timestamp to the `IndexName` to facilitate the expiration of old data. For more information, see [Index Rotation for the Amazon ES Destination](#). The default value is `OneDay`.

Type: String

Valid Values: `NoRotation` | `OneHour` | `OneDay` | `OneWeek` | `OneMonth`

Required: No

ProcessingConfiguration

The data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

The retry behavior in case Firehose is unable to deliver documents to Amazon ES. The default value is 300 (5 minutes).

Type: [ElasticsearchRetryOptions](#) object

Required: No

S3BackupMode

Defines how documents should be delivered to Amazon S3. When it is set to `FailedDocumentsOnly`, Firehose writes any documents that could not be indexed to the configured Amazon S3 destination, with `AmazonOpenSearchService-failed/` appended to the key prefix. When set to `AllDocuments`, Firehose delivers all incoming records to Amazon S3, and also writes failed documents with `AmazonOpenSearchService-failed/` appended to the prefix. For more information, see [Amazon S3 Backup for the Amazon ES Destination](#). Default value is `FailedDocumentsOnly`.

You can't change this backup mode after you create the delivery stream.

Type: String

Valid Values: FailedDocumentsOnly | AllDocuments

Required: No

TypeName

The Elasticsearch type name. For Elasticsearch 6.x, there can be only one type per index. If you try to specify a new type for an existing index that already has another type, Firehose returns an error during run time.

For Elasticsearch 7.x, don't specify a TypeName.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: .*

Required: No

VpcConfiguration

The details of the VPC of the Amazon destination.

Type: [VpcConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ElasticsearchDestinationDescription

The destination description in Amazon ES.

Contents

BufferingHints

The buffering options.

Type: [ElasticsearchBufferingHints](#) object

Required: No

CloudWatchLoggingOptions

The Amazon CloudWatch logging options.

Type: [CloudWatchLoggingOptions](#) object

Required: No

ClusterEndpoint

The endpoint to use when communicating with the cluster. Firehose uses either this `ClusterEndpoint` or the `DomainARN` field to send data to Amazon ES.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `https:.*`

Required: No

DocumentIdOptions

Indicates the method for setting up document ID. The supported methods are Firehose generated document ID and OpenSearch Service generated document ID.

Type: [DocumentIdOptions](#) object

Required: No

DomainARN

The ARN of the Amazon ES domain. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Firehose uses either `ClusterEndpoint` or `DomainARN` to send data to Amazon ES.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

IndexName

The Elasticsearch index name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 80.

Pattern: `.*`

Required: No

IndexRotationPeriod

The Elasticsearch index rotation period

Type: String

Valid Values: `NoRotation` | `OneHour` | `OneDay` | `OneWeek` | `OneMonth`

Required: No

ProcessingConfiguration

The data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

The Amazon ES retry options.

Type: [ElasticsearchRetryOptions](#) object

Required: No

RoleARN

The Amazon Resource Name (ARN) of the Amazon credentials. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: arn:.*

Required: No

S3BackupMode

The Amazon S3 backup mode.

Type: String

Valid Values: FailedDocumentsOnly | AllDocuments

Required: No

S3DestinationDescription

The Amazon S3 destination.

Type: [S3DestinationDescription](#) object

Required: No

TypeName

The Elasticsearch type name. This applies to Elasticsearch 6.x and lower versions. For Elasticsearch 7.x and OpenSearch Service 1.x, there's no value for TypeName.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: . *

Required: No

VpcConfigurationDescription

The details of the VPC of the Amazon OpenSearch or the Amazon OpenSearch Serverless destination.

Type: [VpcConfigurationDescription](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ElasticsearchDestinationUpdate

Describes an update for a destination in Amazon ES.

Contents

BufferingHints

The buffering options. If no value is specified, `ElasticsearchBufferingHints` object default values are used.

Type: [ElasticsearchBufferingHints](#) object

Required: No

CloudWatchLoggingOptions

The CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

ClusterEndpoint

The endpoint to use when communicating with the cluster. Specify either this `ClusterEndpoint` or the `DomainARN` field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `https:.*`

Required: No

DocumentIdOptions

Indicates the method for setting up document ID. The supported methods are Firehose generated document ID and OpenSearch Service generated document ID.

Type: [DocumentIdOptions](#) object

Required: No

DomainARN

The ARN of the Amazon ES domain. The IAM role must have permissions for `DescribeDomain`, `DescribeDomains`, and `DescribeDomainConfig` after assuming the IAM role specified in `RoleARN`. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Specify either `ClusterEndpoint` or `DomainARN`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

IndexName

The Elasticsearch index name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 80.

Pattern: `.*`

Required: No

IndexRotationPeriod

The Elasticsearch index rotation period. Index rotation appends a timestamp to `IndexName` to facilitate the expiration of old data. For more information, see [Index Rotation for the Amazon ES Destination](#). Default value is `OneDay`.

Type: String

Valid Values: `NoRotation` | `OneHour` | `OneDay` | `OneWeek` | `OneMonth`

Required: No

ProcessingConfiguration

The data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

The retry behavior in case Firehose is unable to deliver documents to Amazon ES. The default value is 300 (5 minutes).

Type: [ElasticsearchRetryOptions](#) object

Required: No

RoleARN

The Amazon Resource Name (ARN) of the IAM role to be assumed by Firehose for calling the Amazon ES Configuration API and for indexing documents. For more information, see [Grant Firehose Access to an Amazon S3 Destination](#) and [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

S3Update

The Amazon S3 destination.

Type: [S3DestinationUpdate](#) object

Required: No

TypeName

The Elasticsearch type name. For Elasticsearch 6.x, there can be only one type per index. If you try to specify a new type for an existing index that already has another type, Firehose returns an error during runtime.

If you upgrade Elasticsearch from 6.x to 7.x and don't update your delivery stream, Firehose still delivers data to Elasticsearch with the old index name and type name. If you want to update your delivery stream with a new index name, provide an empty string for TypeName.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: . *

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ElasticsearchRetryOptions

Configures retry behavior in case Firehose is unable to deliver documents to Amazon ES.

Contents

DurationInSeconds

After an initial failure to deliver to Amazon ES, the total amount of time during which Firehose retries delivery (including the first attempt). After this time has elapsed, the failed documents are written to Amazon S3. Default value is 300 seconds (5 minutes). A value of 0 (zero) results in no retries.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 7200.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

EncryptionConfiguration

Describes the encryption for a destination in Amazon S3.

Contents

KMSEncryptionConfig

The encryption key.

Type: [KMSEncryptionConfig](#) object

Required: No

NoEncryptionConfig

Specifically override existing encryption information to ensure that no encryption is used.

Type: String

Valid Values: NoEncryption

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ExtendedS3DestinationConfiguration

Describes the configuration of a destination in Amazon S3.

Contents

BucketARN

The ARN of the S3 bucket. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

RoleARN

The Amazon Resource Name (ARN) of the Amazon credentials. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: Yes

BufferingHints

The buffering option.

Type: [BufferingHints](#) object

Required: No

CloudWatchLoggingOptions

The Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

CompressionFormat

The compression format. If no value is specified, the default is UNCOMPRESSED.

Type: String

Valid Values: UNCOMPRESSED | GZIP | ZIP | Snappy | HADOOP_SNAPPY

Required: No

CustomTimeZone

The time zone you prefer. UTC is the default.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Required: No

DataFormatConversionConfiguration

The serializer, deserializer, and schema for converting data from the JSON format to the Parquet or ORC format before writing it to Amazon S3.

Type: [DataFormatConversionConfiguration](#) object

Required: No

DynamicPartitioningConfiguration

The configuration of the dynamic partitioning mechanism that creates smaller data sets from the streaming data by partitioning it based on partition keys. Currently, dynamic partitioning is only supported for Amazon S3 destinations.

Type: [DynamicPartitioningConfiguration](#) object

Required: No

EncryptionConfiguration

The encryption configuration. If no value is specified, the default is no encryption.

Type: [EncryptionConfiguration](#) object

Required: No

ErrorOutputPrefix

A prefix that Firehose evaluates and adds to failed records before writing them to S3. This prefix appears immediately following the bucket name. For information about how to specify this prefix, see [Custom Prefixes for Amazon S3 Objects](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: .*

Required: No

FileExtension

Specify a file extension. It will override the default file extension

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: ^\$|\.[0-9a-z!\-_.*'()]+

Required: No

Prefix

The "YYYY/MM/DD/HH" time format prefix is automatically used for delivered Amazon S3 files. You can also specify a custom prefix, as described in [Custom Prefixes for Amazon S3 Objects](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: .*

Required: No

ProcessingConfiguration

The data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

S3BackupConfiguration

The configuration for backup in Amazon S3.

Type: [S3DestinationConfiguration](#) object

Required: No

S3BackupMode

The Amazon S3 backup mode. After you create a delivery stream, you can update it to enable Amazon S3 backup if it is disabled. If backup is enabled, you can't update the delivery stream to disable it.

Type: String

Valid Values: Disabled | Enabled

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ExtendedS3DestinationDescription

Describes a destination in Amazon S3.

Contents

BucketARN

The ARN of the S3 bucket. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: arn:.*

Required: Yes

BufferingHints

The buffering option.

Type: [BufferingHints](#) object

Required: Yes

CompressionFormat

The compression format. If no value is specified, the default is UNCOMPRESSED.

Type: String

Valid Values: UNCOMPRESSED | GZIP | ZIP | Snappy | HADOOP_SNAPPY

Required: Yes

EncryptionConfiguration

The encryption configuration. If no value is specified, the default is no encryption.

Type: [EncryptionConfiguration](#) object

Required: Yes

RoleARN

The Amazon Resource Name (ARN) of the Amazon credentials. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: arn:.*

Required: Yes

CloudWatchLoggingOptions

The Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

CustomTimeZone

The time zone you prefer. UTC is the default.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Required: No

DataFormatConversionConfiguration

The serializer, deserializer, and schema for converting data from the JSON format to the Parquet or ORC format before writing it to Amazon S3.

Type: [DataFormatConversionConfiguration](#) object

Required: No

DynamicPartitioningConfiguration

The configuration of the dynamic partitioning mechanism that creates smaller data sets from the streaming data by partitioning it based on partition keys. Currently, dynamic partitioning is only supported for Amazon S3 destinations.

Type: [DynamicPartitioningConfiguration](#) object

Required: No

ErrorOutputPrefix

A prefix that Firehose evaluates and adds to failed records before writing them to S3. This prefix appears immediately following the bucket name. For information about how to specify this prefix, see [Custom Prefixes for Amazon S3 Objects](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: .*

Required: No

FileExtension

Specify a file extension. It will override the default file extension

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: ^\$|\.[0-9a-z!\-_.*'()]+

Required: No

Prefix

The "YYYY/MM/DD/HH" time format prefix is automatically used for delivered Amazon S3 files. You can also specify a custom prefix, as described in [Custom Prefixes for Amazon S3 Objects](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: .*

Required: No

ProcessingConfiguration

The data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

S3BackupDescription

The configuration for backup in Amazon S3.

Type: [S3DestinationDescription](#) object

Required: No

S3BackupMode

The Amazon S3 backup mode.

Type: String

Valid Values: Disabled | Enabled

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ExtendedS3DestinationUpdate

Describes an update for a destination in Amazon S3.

Contents

BucketARN

The ARN of the S3 bucket. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: arn:.*

Required: No

BufferingHints

The buffering option.

Type: [BufferingHints](#) object

Required: No

CloudWatchLoggingOptions

The Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

CompressionFormat

The compression format. If no value is specified, the default is UNCOMPRESSED.

Type: String

Valid Values: UNCOMPRESSED | GZIP | ZIP | Snappy | HADOOP_SNAPPY

Required: No

CustomTimeZone

The time zone you prefer. UTC is the default.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 50.

Required: No

DataFormatConversionConfiguration

The serializer, deserializer, and schema for converting data from the JSON format to the Parquet or ORC format before writing it to Amazon S3.

Type: [DataFormatConversionConfiguration](#) object

Required: No

DynamicPartitioningConfiguration

The configuration of the dynamic partitioning mechanism that creates smaller data sets from the streaming data by partitioning it based on partition keys. Currently, dynamic partitioning is only supported for Amazon S3 destinations.

Type: [DynamicPartitioningConfiguration](#) object

Required: No

EncryptionConfiguration

The encryption configuration. If no value is specified, the default is no encryption.

Type: [EncryptionConfiguration](#) object

Required: No

ErrorOutputPrefix

A prefix that Firehose evaluates and adds to failed records before writing them to S3. This prefix appears immediately following the bucket name. For information about how to specify this prefix, see [Custom Prefixes for Amazon S3 Objects](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: . *

Required: No

FileExtension

Specify a file extension. It will override the default file extension

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: ^\$|\.[0-9a-z!\-_.*'()]+

Required: No

Prefix

The "YYYY/MM/DD/HH" time format prefix is automatically used for delivered Amazon S3 files. You can also specify a custom prefix, as described in [Custom Prefixes for Amazon S3 Objects](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: . *

Required: No

ProcessingConfiguration

The data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RoleARN

The Amazon Resource Name (ARN) of the Amazon credentials. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

S3BackupMode

You can update a delivery stream to enable Amazon S3 backup if it is disabled. If backup is enabled, you can't update the delivery stream to disable it.

Type: String

Valid Values: Disabled | Enabled

Required: No

S3BackupUpdate

The Amazon S3 destination for backup.

Type: [S3DestinationUpdate](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

FailureDescription

Provides details in case one of the following operations fails due to an error related to KMS: [CreateDeliveryStream](#), [DeleteDeliveryStream](#), [StartDeliveryStreamEncryption](#), [StopDeliveryStreamEncryption](#).

Contents

Details

A message providing details about the error that caused the failure.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^(?!\\s*$).+`

Required: Yes

Type

The type of error that caused the failure.

Type: String

Valid Values: RETIRE_KMS_GRANT_FAILED | CREATE_KMS_GRANT_FAILED | KMS_ACCESS_DENIED | DISABLED_KMS_KEY | INVALID_KMS_KEY | KMS_KEY_NOT_FOUND | KMS_OPT_IN_REQUIRED | CREATE_ENI_FAILED | DELETE_ENI_FAILED | SUBNET_NOT_FOUND | SECURITY_GROUP_NOT_FOUND | ENI_ACCESS_DENIED | SUBNET_ACCESS_DENIED | SECURITY_GROUP_ACCESS_DENIED | UNKNOWN_ERROR

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

HiveJsonSerDe

The native Hive / HCatalog JsonSerDe. Used by Firehose for deserializing data, which means converting it from the JSON format in preparation for serializing it to the Parquet or ORC format. This is one of two deserializers you can choose, depending on which one offers the functionality you need. The other option is the OpenX SerDe.

Contents

TimestampFormats

Indicates how you want Firehose to parse the date and timestamps that may be present in your input data JSON. To specify these format strings, follow the pattern syntax of JodaTime's `DateTimeFormat` format strings. For more information, see [Class DateTimeFormat](#). You can also use the special value `millis` to parse timestamps in epoch milliseconds. If you don't specify a format, Firehose uses `java.sql.Timestamp::valueOf` by default.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^(?!\\s*$).+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

HttpEndpointBufferingHints

Describes the buffering options that can be applied before data is delivered to the HTTP endpoint destination. Firehose treats these options as hints, and it might choose to use more optimal values. The `SizeInMBs` and `IntervalInSeconds` parameters are optional. However, if specify a value for one of them, you must also provide a value for the other.

Contents

IntervalInSeconds

Buffer incoming data for the specified period of time, in seconds, before delivering it to the destination. The default value is 300 (5 minutes).

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 900.

Required: No

SizeInMBs

Buffer incoming data to the specified size, in MBs, before delivering it to the destination. The default value is 5.

We recommend setting this parameter to a value greater than the amount of data you typically ingest into the delivery stream in 10 seconds. For example, if you typically ingest data at 1 MB/sec, the value should be 10 MB or higher.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 64.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

HttpEndpointCommonAttribute

Describes the metadata that's delivered to the specified HTTP endpoint destination.

Contents

AttributeName

The name of the HTTP endpoint common attribute.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^(?!\\s*$).+`

Required: Yes

AttributeValue

The value of the HTTP endpoint common attribute.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: `.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

HttpEndpointConfiguration

Describes the configuration of the HTTP endpoint to which Kinesis Firehose delivers data.

Contents

Url

The URL of the HTTP endpoint selected as the destination.

Important

If you choose an HTTP endpoint as your destination, review and follow the instructions in the [Appendix - HTTP Endpoint Delivery Request and Response Specifications](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `https://.*`

Required: Yes

AccessKey

The access key required for Kinesis Firehose to authenticate with the HTTP endpoint selected as the destination.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 4096.

Pattern: `.*`

Required: No

Name

The name of the HTTP endpoint selected as the destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^(?!\\s*$).+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

HttpEndpointDescription

Describes the HTTP endpoint selected as the destination.

Contents

Name

The name of the HTTP endpoint selected as the destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^(?!\\s*$).+`

Required: No

Url

The URL of the HTTP endpoint selected as the destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `https://.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

HttpEndpointDestinationConfiguration

Describes the configuration of the HTTP endpoint destination.

Contents

EndpointConfiguration

The configuration of the HTTP endpoint selected as the destination.

Type: [HttpEndpointConfiguration](#) object

Required: Yes

S3Configuration

Describes the configuration of a destination in Amazon S3.

Type: [S3DestinationConfiguration](#) object

Required: Yes

BufferingHints

The buffering options that can be used before data is delivered to the specified destination. Firehose treats these options as hints, and it might choose to use more optimal values. The `SizeInMBs` and `IntervalInSeconds` parameters are optional. However, if you specify a value for one of them, you must also provide a value for the other.

Type: [HttpEndpointBufferingHints](#) object

Required: No

CloudWatchLoggingOptions

Describes the Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

ProcessingConfiguration

Describes a data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RequestConfiguration

The configuration of the request sent to the HTTP endpoint that is specified as the destination.

Type: [HttpEndpointRequestConfiguration](#) object

Required: No

RetryOptions

Describes the retry behavior in case Firehose is unable to deliver data to the specified HTTP endpoint destination, or if it doesn't receive a valid acknowledgment of receipt from the specified HTTP endpoint destination.

Type: [HttpEndpointRetryOptions](#) object

Required: No

RoleARN

Firehose uses this IAM role for all the permissions that the delivery stream needs.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

S3BackupMode

Describes the S3 bucket backup options for the data that Firehose delivers to the HTTP endpoint destination. You can back up all documents (`AllData`) or only the documents that Firehose could not deliver to the specified HTTP endpoint destination (`FailedDataOnly`).

Type: String

Valid Values: `FailedDataOnly` | `AllData`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

HttpEndpointDestinationDescription

Describes the HTTP endpoint destination.

Contents

BufferingHints

Describes buffering options that can be applied to the data before it is delivered to the HTTPS endpoint destination. Firehose treats these options as hints, and it might choose to use more optimal values. The `SizeInMBs` and `IntervalInSeconds` parameters are optional. However, if specify a value for one of them, you must also provide a value for the other.

Type: [HttpEndpointBufferingHints](#) object

Required: No

CloudWatchLoggingOptions

Describes the Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

EndpointConfiguration

The configuration of the specified HTTP endpoint destination.

Type: [HttpEndpointDescription](#) object

Required: No

ProcessingConfiguration

Describes a data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RequestConfiguration

The configuration of request sent to the HTTP endpoint specified as the destination.

Type: [HttpEndpointRequestConfiguration](#) object

Required: No

RetryOptions

Describes the retry behavior in case Firehose is unable to deliver data to the specified HTTP endpoint destination, or if it doesn't receive a valid acknowledgment of receipt from the specified HTTP endpoint destination.

Type: [HttpEndpointRetryOptions](#) object

Required: No

RoleARN

Firehose uses this IAM role for all the permissions that the delivery stream needs.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

S3BackupMode

Describes the S3 bucket backup options for the data that Kinesis Firehose delivers to the HTTP endpoint destination. You can back up all documents (`AllData`) or only the documents that Firehose could not deliver to the specified HTTP endpoint destination (`FailedDataOnly`).

Type: String

Valid Values: `FailedDataOnly` | `AllData`

Required: No

S3DestinationDescription

Describes a destination in Amazon S3.

Type: [S3DestinationDescription](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

HttpEndpointDestinationUpdate

Updates the specified HTTP endpoint destination.

Contents

BufferingHints

Describes buffering options that can be applied to the data before it is delivered to the HTTPS endpoint destination. Firehose treats these options as hints, and it might choose to use more optimal values. The `SizeInMBs` and `IntervalInSeconds` parameters are optional. However, if specify a value for one of them, you must also provide a value for the other.

Type: [HttpEndpointBufferingHints](#) object

Required: No

CloudWatchLoggingOptions

Describes the Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

EndpointConfiguration

Describes the configuration of the HTTP endpoint destination.

Type: [HttpEndpointConfiguration](#) object

Required: No

ProcessingConfiguration

Describes a data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RequestConfiguration

The configuration of the request sent to the HTTP endpoint specified as the destination.

Type: [HttpEndpointRequestConfiguration](#) object

Required: No

RetryOptions

Describes the retry behavior in case Firehose is unable to deliver data to the specified HTTP endpoint destination, or if it doesn't receive a valid acknowledgment of receipt from the specified HTTP endpoint destination.

Type: [HttpEndpointRetryOptions](#) object

Required: No

RoleARN

Firehose uses this IAM role for all the permissions that the delivery stream needs.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

S3BackupMode

Describes the S3 bucket backup options for the data that Kinesis Firehose delivers to the HTTP endpoint destination. You can back up all documents (`AllData`) or only the documents that Firehose could not deliver to the specified HTTP endpoint destination (`FailedDataOnly`).

Type: String

Valid Values: `FailedDataOnly` | `AllData`

Required: No

S3Update

Describes an update for a destination in Amazon S3.

Type: [S3DestinationUpdate](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

HttpEndpointRequestConfiguration

The configuration of the HTTP endpoint request.

Contents

CommonAttributes

Describes the metadata sent to the HTTP endpoint destination.

Type: Array of [HttpEndpointCommonAttribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

ContentEncoding

Firehose uses the content encoding to compress the body of a request before sending the request to the destination. For more information, see [Content-Encoding](#) in MDN Web Docs, the official Mozilla documentation.

Type: String

Valid Values: NONE | GZIP

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

HttpEndpointRetryOptions

Describes the retry behavior in case Firehose is unable to deliver data to the specified HTTP endpoint destination, or if it doesn't receive a valid acknowledgment of receipt from the specified HTTP endpoint destination.

Contents

DurationInSeconds

The total amount of time that Firehose spends on retries. This duration starts after the initial attempt to send data to the custom destination via HTTPS endpoint fails. It doesn't include the periods during which Firehose waits for acknowledgment from the specified destination after each attempt.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 7200.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

InputFormatConfiguration

Specifies the deserializer you want to use to convert the format of the input data. This parameter is required if Enabled is set to true.

Contents

Deserializer

Specifies which deserializer to use. You can choose either the Apache Hive JSON SerDe or the OpenX JSON SerDe. If both are non-null, the server rejects the request.

Type: [Deserializer](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

KinesisStreamSourceConfiguration

The stream and role Amazon Resource Names (ARNs) for a Kinesis data stream used as the source for a delivery stream.

Contents

KinesisStreamARN

The ARN of the source Kinesis data stream. For more information, see [Amazon Kinesis Data Streams ARN Format](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: Yes

RoleARN

The ARN of the role that provides access to the source Kinesis data stream. For more information, see [Amazon Identity and Access Management \(IAM\) ARN Format](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

KinesisStreamSourceDescription

Details about a Kinesis data stream used as the source for a Firehose delivery stream.

Contents

DeliveryStartTimestamp

Firehose starts retrieving records from the Kinesis data stream starting with this timestamp.

Type: Timestamp

Required: No

KinesisStreamARN

The Amazon Resource Name (ARN) of the source Kinesis data stream. For more information, see [Amazon Kinesis Data Streams ARN Format](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: arn:.*

Required: No

RoleARN

The ARN of the role used by the source Kinesis data stream. For more information, see [Amazon Identity and Access Management \(IAM\) ARN Format](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: arn:.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

KMSEncryptionConfig

Describes an encryption key for a destination in Amazon S3.

Contents

AWSKMSKeyARN

The Amazon Resource Name (ARN) of the encryption key. Must belong to the same Amazon Region as the destination Amazon S3 bucket. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

MSKSourceConfiguration

The configuration for the Amazon MSK cluster to be used as the source for a delivery stream.

Contents

AuthenticationConfiguration

The authentication configuration of the Amazon MSK cluster.

Type: [AuthenticationConfiguration](#) object

Required: Yes

MSKClusterARN

The ARN of the Amazon MSK cluster.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: Yes

TopicName

The topic name within the Amazon MSK cluster.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[a-zA-Z0-9\\._\\-]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

MSKSourceDescription

Details about the Amazon MSK cluster used as the source for a Firehose delivery stream.

Contents

AuthenticationConfiguration

The authentication configuration of the Amazon MSK cluster.

Type: [AuthenticationConfiguration](#) object

Required: No

DeliveryStartTimestamp

Firehose starts retrieving records from the topic within the Amazon MSK cluster starting with this timestamp.

Type: Timestamp

Required: No

MSKClusterARN

The ARN of the Amazon MSK cluster.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

TopicName

The topic name within the Amazon MSK cluster.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[a-zA-Z0-9\\._\\-]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

OpenXJsonSerDe

The OpenX SerDe. Used by Firehose for deserializing data, which means converting it from the JSON format in preparation for serializing it to the Parquet or ORC format. This is one of two deserializers you can choose, depending on which one offers the functionality you need. The other option is the native Hive / HCatalog JsonSerDe.

Contents

CaseInsensitive

When set to `true`, which is the default, Firehose converts JSON keys to lowercase before deserializing them.

Type: Boolean

Required: No

ColumnToJsonKeyMappings

Maps column names to JSON keys that aren't identical to the column names. This is useful when the JSON contains keys that are Hive keywords. For example, `timestamp` is a Hive keyword. If you have a JSON key named `timestamp`, set this parameter to `{"ts": "timestamp"}` to map this key to a column named `ts`.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 1024.

Key Pattern: `^\S+$`

Value Length Constraints: Minimum length of 1. Maximum length of 1024.

Value Pattern: `^(?!\\s*$)\\.+`

Required: No

ConvertDotsInJsonKeysToUnderscores

When set to `true`, specifies that the names of the keys include dots and that you want Firehose to replace them with underscores. This is useful because Apache Hive does not allow dots in column names. For example, if the JSON contains a key whose name is `"a.b"`, you can define the column name to be `"a_b"` when using this option.

The default is false.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

OrcSerDe

A serializer to use for converting data to the ORC format before storing it in Amazon S3. For more information, see [Apache ORC](#).

Contents

BlockSizeBytes

The Hadoop Distributed File System (HDFS) block size. This is useful if you intend to copy the data from Amazon S3 to HDFS before querying. The default is 256 MiB and the minimum is 64 MiB. Firehose uses this value for padding calculations.

Type: Integer

Valid Range: Minimum value of 67108864.

Required: No

BloomFilterColumns

The column names for which you want Firehose to create bloom filters. The default is `null`.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^\S+$`

Required: No

BloomFilterFalsePositiveProbability

The Bloom filter false positive probability (FPP). The lower the FPP, the bigger the Bloom filter. The default value is 0.05, the minimum is 0, and the maximum is 1.

Type: Double

Valid Range: Minimum value of 0. Maximum value of 1.

Required: No

Compression

The compression code to use over data blocks. The default is SNAPPY.

Type: String

Valid Values: NONE | ZLIB | SNAPPY

Required: No

DictionaryKeyThreshold

Represents the fraction of the total number of non-null rows. To turn off dictionary encoding, set this fraction to a number that is less than the number of distinct keys in a dictionary. To always use dictionary encoding, set this threshold to 1.

Type: Double

Valid Range: Minimum value of 0. Maximum value of 1.

Required: No

EnablePadding

Set this to `true` to indicate that you want stripes to be padded to the HDFS block boundaries. This is useful if you intend to copy the data from Amazon S3 to HDFS before querying. The default is `false`.

Type: Boolean

Required: No

FormatVersion

The version of the file to write. The possible values are `V0_11` and `V0_12`. The default is `V0_12`.

Type: String

Valid Values: `V0_11` | `V0_12`

Required: No

PaddingTolerance

A number between 0 and 1 that defines the tolerance for block padding as a decimal fraction of stripe size. The default value is 0.05, which means 5 percent of stripe size.

For the default values of 64 MiB ORC stripes and 256 MiB HDFS blocks, the default block padding tolerance of 5 percent reserves a maximum of 3.2 MiB for padding within the 256 MiB

block. In such a case, if the available size within the block is more than 3.2 MiB, a new, smaller stripe is inserted to fit within that space. This ensures that no stripe crosses block boundaries and causes remote reads within a node-local task.

Firehose ignores this parameter when [OrcSerDe:EnablePadding](#) is false.

Type: Double

Valid Range: Minimum value of 0. Maximum value of 1.

Required: No

RowIndexStride

The number of rows between index entries. The default is 10,000 and the minimum is 1,000.

Type: Integer

Valid Range: Minimum value of 1000.

Required: No

StripeSizeBytes

The number of bytes in each stripe. The default is 64 MiB and the minimum is 8 MiB.

Type: Integer

Valid Range: Minimum value of 8388608.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

OutputFormatConfiguration

Specifies the serializer that you want Firehose to use to convert the format of your data before it writes it to Amazon S3. This parameter is required if Enabled is set to true.

Contents

Serializer

Specifies which serializer to use. You can choose either the ORC SerDe or the Parquet SerDe. If both are non-null, the server rejects the request.

Type: [Serializer](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ParquetSerDe

A serializer to use for converting data to the Parquet format before storing it in Amazon S3. For more information, see [Apache Parquet](#).

Contents

BlockSizeBytes

The Hadoop Distributed File System (HDFS) block size. This is useful if you intend to copy the data from Amazon S3 to HDFS before querying. The default is 256 MiB and the minimum is 64 MiB. Firehose uses this value for padding calculations.

Type: Integer

Valid Range: Minimum value of 67108864.

Required: No

Compression

The compression code to use over data blocks. The possible values are UNCOMPRESSED, SNAPPY, and GZIP, with the default being SNAPPY. Use SNAPPY for higher decompression speed. Use GZIP if the compression ratio is more important than speed.

Type: String

Valid Values: UNCOMPRESSED | GZIP | SNAPPY

Required: No

EnableDictionaryCompression

Indicates whether to enable dictionary compression.

Type: Boolean

Required: No

MaxPaddingBytes

The maximum amount of padding to apply. This is useful if you intend to copy the data from Amazon S3 to HDFS before querying. The default is 0.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

PageSizeBytes

The Parquet page size. Column chunks are divided into pages. A page is conceptually an indivisible unit (in terms of compression and encoding). The minimum value is 64 KiB and the default is 1 MiB.

Type: Integer

Valid Range: Minimum value of 65536.

Required: No

WriterVersion

Indicates the version of row format to output. The possible values are V1 and V2. The default is V1.

Type: String

Valid Values: V1 | V2

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ProcessingConfiguration

Describes a data processing configuration.

Contents

Enabled

Enables or disables data processing.

Type: Boolean

Required: No

Processors

The data processors.

Type: Array of [Processor](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Processor

Describes a data processor.

Note

If you want to add a new line delimiter between records in objects that are delivered to Amazon S3, choose `AppendDelimiterToRecord` as a processor type. You don't have to put a processor parameter when you select `AppendDelimiterToRecord`.

Contents

Type

The type of processor.

Type: String

Valid Values: `RecordDeAggregation` | `Decompression` | `Lambda` | `MetadataExtraction` | `AppendDelimiterToRecord`

Required: Yes

Parameters

The processor parameters.

Type: Array of [ProcessorParameter](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ProcessorParameter

Describes the processor parameter.

Contents

ParameterName

The name of the parameter. Currently the following default values are supported: 3 for `NumberOfRetries` and 60 for the `BufferIntervalInSeconds`. The `BufferSizeInMBs` ranges between 0.2 MB and up to 3MB. The default buffering hint is 1MB for all destinations, except Splunk. For Splunk, the default buffering hint is 256 KB.

Type: String

Valid Values: `LambdaArn` | `NumberOfRetries` | `MetadataExtractionQuery` | `JsonParsingEngine` | `RoleArn` | `BufferSizeInMBs` | `BufferIntervalInSeconds` | `SubRecordType` | `Delimiter` | `CompressionFormat`

Required: Yes

ParameterValue

The parameter value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5120.

Pattern: `^(?!\\s*$).+`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PutRecordBatchResponseEntry

Contains the result for an individual record from a [PutRecordBatch](#) request. If the record is successfully added to your delivery stream, it receives a record ID. If the record fails to be added to your delivery stream, the result includes an error code and an error message.

Contents

ErrorCode

The error code for an individual record result.

Type: String

Required: No

ErrorMessage

The error message for an individual record result.

Type: String

Required: No

RecordId

The ID of the record.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Record

The unit of data in a delivery stream.

Contents

Data

The data blob, which is base64-encoded when the blob is serialized. The maximum size of the data blob, before base64-encoding, is 1,000 KiB.

Type: Base64-encoded binary data object

Length Constraints: Minimum length of 0. Maximum length of 1024000.

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RedshiftDestinationConfiguration

Describes the configuration of a destination in Amazon Redshift.

Contents

ClusterJDBCURL

The database connection string.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: jdbc:(redshift|postgresql)://((?!-)[A-Za-z0-9-]{1,63}(<!--)\.)+(redshift(-serverless)?)\.([a-zA-Z0-9\.]++):\d{1,5}/[a-zA-Z0-9_\$\$-]+

Required: Yes

CopyCommand

The COPY command.

Type: [CopyCommand](#) object

Required: Yes

Password

The user password.

Type: String

Length Constraints: Minimum length of 6. Maximum length of 512.

Pattern: .*

Required: Yes

RoleARN

The Amazon Resource Name (ARN) of the Amazon credentials. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: Yes

S3Configuration

The configuration for the intermediate Amazon S3 location from which Amazon Redshift obtains data. Restrictions are described in the topic for [CreateDeliveryStream](#).

The compression formats SNAPPY or ZIP cannot be specified in `RedshiftDestinationConfiguration.S3Configuration` because the Amazon Redshift COPY operation that reads from the S3 bucket doesn't support these compression formats.

Type: [S3DestinationConfiguration](#) object

Required: Yes

Username

The name of the user.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `.*`

Required: Yes

CloudWatchLoggingOptions

The CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

ProcessingConfiguration

The data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

The retry behavior in case Firehose is unable to deliver documents to Amazon Redshift. Default value is 3600 (60 minutes).

Type: [RedshiftRetryOptions](#) object

Required: No

S3BackupConfiguration

The configuration for backup in Amazon S3.

Type: [S3DestinationConfiguration](#) object

Required: No

S3BackupMode

The Amazon S3 backup mode. After you create a delivery stream, you can update it to enable Amazon S3 backup if it is disabled. If backup is enabled, you can't update the delivery stream to disable it.

Type: String

Valid Values: Disabled | Enabled

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RedshiftDestinationDescription

Describes a destination in Amazon Redshift.

Contents

ClusterJDBCURL

The database connection string.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: jdbc:(redshift|postgresql)://((?!-)[A-Za-z0-9-]{1,63}(?
<!--)\.)+(redshift(-serverless)?)\.([a-zA-Z0-9\.]++):\d{1,5}/[a-zA-Z0-9_
\$-]+

Required: Yes

CopyCommand

The COPY command.

Type: [CopyCommand](#) object

Required: Yes

RoleARN

The Amazon Resource Name (ARN) of the Amazon credentials. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: arn:.*

Required: Yes

S3DestinationDescription

The Amazon S3 destination.

Type: [S3DestinationDescription](#) object

Required: Yes

Username

The name of the user.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: . *

Required: Yes

CloudWatchLoggingOptions

The Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

ProcessingConfiguration

The data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

The retry behavior in case Firehose is unable to deliver documents to Amazon Redshift. Default value is 3600 (60 minutes).

Type: [RedshiftRetryOptions](#) object

Required: No

S3BackupDescription

The configuration for backup in Amazon S3.

Type: [S3DestinationDescription](#) object

Required: No

S3BackupMode

The Amazon S3 backup mode.

Type: String

Valid Values: Disabled | Enabled

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RedshiftDestinationUpdate

Describes an update for a destination in Amazon Redshift.

Contents

CloudWatchLoggingOptions

The Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

ClusterJDBCURL

The database connection string.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: jdbc:(redshift|postgresql)://((?!-)[A-Za-z0-9-]{1,63}(?
<!--)\.)+(redshift(-serverless)?)\.([a-zA-Z0-9\.:]{1,5})/[a-zA-Z0-9_
\$-]+

Required: No

CopyCommand

The COPY command.

Type: [CopyCommand](#) object

Required: No

Password

The user password.

Type: String

Length Constraints: Minimum length of 6. Maximum length of 512.

Pattern: .*

Required: No

ProcessingConfiguration

The data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

The retry behavior in case Firehose is unable to deliver documents to Amazon Redshift. Default value is 3600 (60 minutes).

Type: [RedshiftRetryOptions](#) object

Required: No

RoleARN

The Amazon Resource Name (ARN) of the Amazon credentials. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: arn:.*

Required: No

S3BackupMode

You can update a delivery stream to enable Amazon S3 backup if it is disabled. If backup is enabled, you can't update the delivery stream to disable it.

Type: String

Valid Values: Disabled | Enabled

Required: No

S3BackupUpdate

The Amazon S3 destination for backup.

Type: [S3DestinationUpdate](#) object

Required: No

S3Update

The Amazon S3 destination.

The compression formats SNAPPY or ZIP cannot be specified in `RedshiftDestinationUpdate.S3Update` because the Amazon Redshift COPY operation that reads from the S3 bucket doesn't support these compression formats.

Type: [S3DestinationUpdate](#) object

Required: No

Username

The name of the user.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: . *

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RedshiftRetryOptions

Configures retry behavior in case Firehose is unable to deliver documents to Amazon Redshift.

Contents

DurationInSeconds

The length of time during which Firehose retries delivery after a failure, starting from the initial request and including the first attempt. The default value is 3600 seconds (60 minutes). Firehose does not retry if the value of `DurationInSeconds` is 0 (zero) or if the first delivery attempt takes longer than the current value.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 7200.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RetryOptions

The retry behavior in case Firehose is unable to deliver data to an Amazon S3 prefix.

Contents

DurationInSeconds

The period of time during which Firehose retries to deliver data to the specified Amazon S3 prefix.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 7200.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

S3DestinationConfiguration

Describes the configuration of a destination in Amazon S3.

Contents

BucketARN

The ARN of the S3 bucket. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

RoleARN

The Amazon Resource Name (ARN) of the Amazon credentials. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: Yes

BufferingHints

The buffering option. If no value is specified, BufferingHints object default values are used.

Type: [BufferingHints](#) object

Required: No

CloudWatchLoggingOptions

The CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

CompressionFormat

The compression format. If no value is specified, the default is UNCOMPRESSED.

The compression formats SNAPPY or ZIP cannot be specified for Amazon Redshift destinations because they are not supported by the Amazon Redshift COPY operation that reads from the S3 bucket.

Type: String

Valid Values: UNCOMPRESSED | GZIP | ZIP | Snappy | HADOOP_SNAPPY

Required: No

EncryptionConfiguration

The encryption configuration. If no value is specified, the default is no encryption.

Type: [EncryptionConfiguration](#) object

Required: No

ErrorOutputPrefix

A prefix that Firehose evaluates and adds to failed records before writing them to S3. This prefix appears immediately following the bucket name. For information about how to specify this prefix, see [Custom Prefixes for Amazon S3 Objects](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: .*

Required: No

Prefix

The "YYYY/MM/DD/HH" time format prefix is automatically used for delivered Amazon S3 files. You can also specify a custom prefix, as described in [Custom Prefixes for Amazon S3 Objects](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: .*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

S3DestinationDescription

Describes a destination in Amazon S3.

Contents

BucketARN

The ARN of the S3 bucket. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: arn:.*

Required: Yes

BufferingHints

The buffering option. If no value is specified, BufferingHints object default values are used.

Type: [BufferingHints](#) object

Required: Yes

CompressionFormat

The compression format. If no value is specified, the default is UNCOMPRESSED.

Type: String

Valid Values: UNCOMPRESSED | GZIP | ZIP | Snappy | HADOOP_SNAPPY

Required: Yes

EncryptionConfiguration

The encryption configuration. If no value is specified, the default is no encryption.

Type: [EncryptionConfiguration](#) object

Required: Yes

RoleARN

The Amazon Resource Name (ARN) of the Amazon credentials. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: Yes

CloudWatchLoggingOptions

The Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

ErrorOutputPrefix

A prefix that Firehose evaluates and adds to failed records before writing them to S3. This prefix appears immediately following the bucket name. For information about how to specify this prefix, see [Custom Prefixes for Amazon S3 Objects](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: `.*`

Required: No

Prefix

The "YYYY/MM/DD/HH" time format prefix is automatically used for delivered Amazon S3 files. You can also specify a custom prefix, as described in [Custom Prefixes for Amazon S3 Objects](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: `.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

S3DestinationUpdate

Describes an update for a destination in Amazon S3.

Contents

BucketARN

The ARN of the S3 bucket. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: arn:.*

Required: No

BufferingHints

The buffering option. If no value is specified, BufferingHints object default values are used.

Type: [BufferingHints](#) object

Required: No

CloudWatchLoggingOptions

The CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

CompressionFormat

The compression format. If no value is specified, the default is UNCOMPRESSED.

The compression formats SNAPPY or ZIP cannot be specified for Amazon Redshift destinations because they are not supported by the Amazon Redshift COPY operation that reads from the S3 bucket.

Type: String

Valid Values: UNCOMPRESSED | GZIP | ZIP | Snappy | HADOOP_SNAPPY

Required: No

EncryptionConfiguration

The encryption configuration. If no value is specified, the default is no encryption.

Type: [EncryptionConfiguration](#) object

Required: No

ErrorOutputPrefix

A prefix that Firehose evaluates and adds to failed records before writing them to S3. This prefix appears immediately following the bucket name. For information about how to specify this prefix, see [Custom Prefixes for Amazon S3 Objects](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: . *

Required: No

Prefix

The "YYYY/MM/DD/HH" time format prefix is automatically used for delivered Amazon S3 files. You can also specify a custom prefix, as described in [Custom Prefixes for Amazon S3 Objects](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: . *

Required: No

RoleARN

The Amazon Resource Name (ARN) of the Amazon credentials. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SchemaConfiguration

Specifies the schema to which you want Firehose to configure your data before it writes it to Amazon S3. This parameter is required if Enabled is set to true.

Contents

CatalogId

The ID of the Amazon Glue Data Catalog. If you don't supply this, the Amazon account ID is used by default.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^\S+$`

Required: No

DatabaseName

Specifies the name of the Amazon Glue database that contains the schema for the output data.

Important

If the SchemaConfiguration request parameter is used as part of invoking the CreateDeliveryStream API, then the DatabaseName property is required and its value must be specified.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^\S+$`

Required: No

Region

If you don't specify an Amazon Region, the default is the current Region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^\S+$`

Required: No

RoleARN

The role that Firehose can use to access Amazon Glue. This role must be in the same account you use for Firehose. Cross-account roles aren't allowed.

Important

If the `SchemaConfiguration` request parameter is used as part of invoking the `CreateDeliveryStream` API, then the `RoleARN` property is required and its value must be specified.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^\S+$`

Required: No

TableName

Specifies the Amazon Glue table that contains the column information that constitutes your data schema.

Important

If the `SchemaConfiguration` request parameter is used as part of invoking the `CreateDeliveryStream` API, then the `TableName` property is required and its value must be specified.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^\S+$`

Required: No

VersionId

Specifies the table version for the output data schema. If you don't specify this version ID, or if you set it to LATEST, Firehose uses the most recent version. This means that any updates to the table are automatically picked up.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^\S+$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Serializer

The serializer that you want Firehose to use to convert data to the target format before writing it to Amazon S3. Firehose supports two types of serializers: the [ORC SerDe](#) and the [Parquet SerDe](#).

Contents

OrcSerDe

A serializer to use for converting data to the ORC format before storing it in Amazon S3. For more information, see [Apache ORC](#).

Type: [OrcSerDe](#) object

Required: No

ParquetSerDe

A serializer to use for converting data to the Parquet format before storing it in Amazon S3. For more information, see [Apache Parquet](#).

Type: [ParquetSerDe](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SnowflakeDestinationConfiguration

Configure Snowflake destination

Contents

AccountUrl

URL for accessing your Snowflake account. This URL must include your [account identifier](#). Note that the protocol (https://) and port number are optional.

Type: String

Length Constraints: Minimum length of 24. Maximum length of 2048.

Pattern: `.+?\.(snowflakecomputing)\.com`

Required: Yes

Database

All data in Snowflake is maintained in databases.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

PrivateKey

The private key used to encrypt your Snowflake client. For information, see [Using Key Pair Authentication & Key Rotation](#).

Type: String

Length Constraints: Minimum length of 256. Maximum length of 4096.

Pattern: `^(?:[A-Za-z0-9+\/]{4})*(?:[A-Za-z0-9+\/]{2}=|[A-Za-z0-9+\/]{3}=)?$`

Required: Yes

RoleARN

The Amazon Resource Name (ARN) of the Snowflake role

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: Yes

S3Configuration

Describes the configuration of a destination in Amazon S3.

Type: [S3DestinationConfiguration](#) object

Required: Yes

Schema

Each database consists of one or more schemas, which are logical groupings of database objects, such as tables and views

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Table

All data in Snowflake is stored in database tables, logically structured as collections of columns and rows.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

User

User login name for the Snowflake account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

CloudWatchLoggingOptions

Describes the Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

ContentColumnName

The name of the record content column

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

DataLoadingOption

Choose to load JSON keys mapped to table column names or choose to split the JSON payload where content is mapped to a record content column and source metadata is mapped to a record metadata column.

Type: String

Valid Values: JSON_MAPPING | VARIANT_CONTENT_MAPPING |
VARIANT_CONTENT_AND_METADATA_MAPPING

Required: No

KeyPassphrase

Passphrase to decrypt the private key when the key is encrypted. For information, see [Using Key Pair Authentication & Key Rotation](#).

Type: String

Length Constraints: Minimum length of 7. Maximum length of 255.

Required: No

MetaDataColumnName

The name of the record metadata column

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

ProcessingConfiguration

Describes a data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

The time period where Firehose will retry sending data to the chosen HTTP endpoint.

Type: [SnowflakeRetryOptions](#) object

Required: No

S3BackupMode

Choose an S3 backup mode

Type: String

Valid Values: FailedDataOnly | AllData

Required: No

SnowflakeRoleConfiguration

Optionally configure a Snowflake role. Otherwise the default user role will be used.

Type: [SnowflakeRoleConfiguration](#) object

Required: No

SnowflakeVpcConfiguration

The VPCE ID for Firehose to privately connect with Snowflake. The ID format is `com.amazonaws.vpce.[region].vpce-svc-<[id]>`. For more information, see [Amazon PrivateLink & Snowflake](#)

Type: [SnowflakeVpcConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SnowflakeDestinationDescription

Optional Snowflake destination description

Contents

AccountUrl

URL for accessing your Snowflake account. This URL must include your [account identifier](#). Note that the protocol (https://) and port number are optional.

Type: String

Length Constraints: Minimum length of 24. Maximum length of 2048.

Pattern: .+?\snowflakecomputing\.com

Required: No

CloudWatchLoggingOptions

Describes the Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

ContentColumnName

The name of the record content column

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

Database

All data in Snowflake is maintained in databases.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

DataLoadingOption

Choose to load JSON keys mapped to table column names or choose to split the JSON payload where content is mapped to a record content column and source metadata is mapped to a record metadata column.

Type: String

Valid Values: JSON_MAPPING | VARIANT_CONTENT_MAPPING |
VARIANT_CONTENT_AND_METADATA_MAPPING

Required: No

MetaDataColumnName

The name of the record metadata column

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

ProcessingConfiguration

Describes a data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

The time period where Firehose will retry sending data to the chosen HTTP endpoint.

Type: [SnowflakeRetryOptions](#) object

Required: No

RoleARN

The Amazon Resource Name (ARN) of the Snowflake role

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

S3BackupMode

Choose an S3 backup mode

Type: String

Valid Values: `FailedDataOnly` | `AllData`

Required: No

S3DestinationDescription

Describes a destination in Amazon S3.

Type: [S3DestinationDescription](#) object

Required: No

Schema

Each database consists of one or more schemas, which are logical groupings of database objects, such as tables and views

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

SnowflakeRoleConfiguration

Optionally configure a Snowflake role. Otherwise the default user role will be used.

Type: [SnowflakeRoleConfiguration](#) object

Required: No

SnowflakeVpcConfiguration

The VPCE ID for Firehose to privately connect with Snowflake. The ID format is `com.amazonaws.vpce.[region].vpce-svc-<[id]>`. For more information, see [Amazon PrivateLink & Snowflake](#)

Type: [SnowflakeVpcConfiguration](#) object

Required: No

Table

All data in Snowflake is stored in database tables, logically structured as collections of columns and rows.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

User

User login name for the Snowflake account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SnowflakeDestinationUpdate

Update to configuration settings

Contents

AccountUrl

URL for accessing your Snowflake account. This URL must include your [account identifier](#). Note that the protocol (https://) and port number are optional.

Type: String

Length Constraints: Minimum length of 24. Maximum length of 2048.

Pattern: .+?\snowflakecomputing\.com

Required: No

CloudWatchLoggingOptions

Describes the Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

ContentColumnName

The name of the content metadata column

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

Database

All data in Snowflake is maintained in databases.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

DataLoadingOption

JSON keys mapped to table column names or choose to split the JSON payload where content is mapped to a record content column and source metadata is mapped to a record metadata column.

Type: String

Valid Values: JSON_MAPPING | VARIANT_CONTENT_MAPPING |
VARIANT_CONTENT_AND_METADATA_MAPPING

Required: No

KeyPassphrase

Passphrase to decrypt the private key when the key is encrypted. For information, see [Using Key Pair Authentication & Key Rotation](#).

Type: String

Length Constraints: Minimum length of 7. Maximum length of 255.

Required: No

MetaDataColumnName

The name of the record metadata column

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

PrivateKey

The private key used to encrypt your Snowflake client. For information, see [Using Key Pair Authentication & Key Rotation](#).

Type: String

Length Constraints: Minimum length of 256. Maximum length of 4096.

Pattern: `^(?:[A-Za-z0-9+\-\/]{4})*(?:[A-Za-z0-9+\-\/]{2}==|[A-Za-z0-9+\-\/]{3}=)?`
\$

Required: No

ProcessingConfiguration

Describes a data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

Specify how long Firehose retries sending data to the New Relic HTTP endpoint. After sending data, Firehose first waits for an acknowledgment from the HTTP endpoint. If an error occurs or the acknowledgment doesn't arrive within the acknowledgment timeout period, Firehose starts the retry duration counter. It keeps retrying until the retry duration expires. After that, Firehose considers it a data delivery failure and backs up the data to your Amazon S3 bucket. Every time that Firehose sends data to the HTTP endpoint (either the initial attempt or a retry), it restarts the acknowledgement timeout counter and waits for an acknowledgement from the HTTP endpoint. Even if the retry duration expires, Firehose still waits for the acknowledgment until it receives it or the acknowledgement timeout period is reached. If the acknowledgment times out, Firehose determines whether there's time left in the retry counter. If there is time left, it retries again and repeats the logic until it receives an acknowledgment or determines that the retry time has expired. If you don't want Firehose to retry sending data, set this value to 0.

Type: [SnowflakeRetryOptions](#) object

Required: No

RoleARN

The Amazon Resource Name (ARN) of the Snowflake role

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

S3BackupMode

Choose an S3 backup mode

Type: String

Valid Values: FailedDataOnly | AllData

Required: No

S3Update

Describes an update for a destination in Amazon S3.

Type: [S3DestinationUpdate](#) object

Required: No

Schema

Each database consists of one or more schemas, which are logical groupings of database objects, such as tables and views

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

SnowflakeRoleConfiguration

Optionally configure a Snowflake role. Otherwise the default user role will be used.

Type: [SnowflakeRoleConfiguration](#) object

Required: No

Table

All data in Snowflake is stored in database tables, logically structured as collections of columns and rows.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

User

User login name for the Snowflake account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SnowflakeRetryOptions

Specify how long Firehose retries sending data to the New Relic HTTP endpoint. After sending data, Firehose first waits for an acknowledgment from the HTTP endpoint. If an error occurs or the acknowledgment doesn't arrive within the acknowledgment timeout period, Firehose starts the retry duration counter. It keeps retrying until the retry duration expires. After that, Firehose considers it a data delivery failure and backs up the data to your Amazon S3 bucket. Every time that Firehose sends data to the HTTP endpoint (either the initial attempt or a retry), it restarts the acknowledgement timeout counter and waits for an acknowledgement from the HTTP endpoint. Even if the retry duration expires, Firehose still waits for the acknowledgment until it receives it or the acknowledgement timeout period is reached. If the acknowledgment times out, Firehose determines whether there's time left in the retry counter. If there is time left, it retries again and repeats the logic until it receives an acknowledgment or determines that the retry time has expired. If you don't want Firehose to retry sending data, set this value to 0.

Contents

DurationInSeconds

the time period where Firehose will retry sending data to the chosen HTTP endpoint.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 7200.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SnowflakeRoleConfiguration

Optionally configure a Snowflake role. Otherwise the default user role will be used.

Contents

Enabled

Enable Snowflake role

Type: Boolean

Required: No

SnowflakeRole

The Snowflake role you wish to configure

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SnowflakeVpcConfiguration

Configure a Snowflake VPC

Contents

PrivateLinkVpcId

The VPCE ID for Firehose to privately connect with Snowflake. The ID format is `com.amazonaws.vpce.[region].vpce-svc-<[id]>`. For more information, see [Amazon PrivateLink & Snowflake](#)

Type: String

Length Constraints: Minimum length of 47. Maximum length of 255.

Pattern: `([a-zA-Z0-9\-_\.]{2,3}vpce\[a-zA-Z0-9\-_]*\.vpce-svc\[a-zA-Z0-9\-_]{17})$`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SourceDescription

Details about a Kinesis data stream used as the source for a Firehose delivery stream.

Contents

KinesisStreamSourceDescription

The [KinesisStreamSourceDescription](#) value for the source Kinesis data stream.

Type: [KinesisStreamSourceDescription](#) object

Required: No

MSKSourceDescription

The configuration description for the Amazon MSK cluster to be used as the source for a delivery stream.

Type: [MSKSourceDescription](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SplunkBufferingHints

The buffering options. If no value is specified, the default values for Splunk are used.

Contents

IntervalInSeconds

Buffer incoming data for the specified period of time, in seconds, before delivering it to the destination. The default value is 60 (1 minute).

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 60.

Required: No

SizeInMBs

Buffer incoming data to the specified size, in MBs, before delivering it to the destination. The default value is 5.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 5.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SplunkDestinationConfiguration

Describes the configuration of a destination in Splunk.

Contents

HECEndpoint

The HTTP Event Collector (HEC) endpoint to which Firehose sends your data.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: .*

Required: Yes

HECEndpointType

This type can be either "Raw" or "Event."

Type: String

Valid Values: Raw | Event

Required: Yes

HECToken

This is a GUID that you obtain from your Splunk cluster when you create a new HEC endpoint.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: .*

Required: Yes

S3Configuration

The configuration for the backup Amazon S3 location.

Type: [S3DestinationConfiguration](#) object

Required: Yes

BufferingHints

The buffering options. If no value is specified, the default values for Splunk are used.

Type: [SplunkBufferingHints](#) object

Required: No

CloudWatchLoggingOptions

The Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

HECAcknowledgmentTimeoutInSeconds

The amount of time that Firehose waits to receive an acknowledgment from Splunk after it sends it data. At the end of the timeout period, Firehose either tries to send the data again or considers it an error, based on your retry settings.

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 600.

Required: No

ProcessingConfiguration

The data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

The retry behavior in case Firehose is unable to deliver data to Splunk, or if it doesn't receive an acknowledgment of receipt from Splunk.

Type: [SplunkRetryOptions](#) object

Required: No

S3BackupMode

Defines how documents should be delivered to Amazon S3. When set to `FailedEventsOnly`, Firehose writes any data that could not be indexed to the configured Amazon S3 destination. When set to `AllEvents`, Firehose delivers all incoming records to Amazon S3, and also writes failed documents to Amazon S3. The default value is `FailedEventsOnly`.

You can update this backup mode from `FailedEventsOnly` to `AllEvents`. You can't update it from `AllEvents` to `FailedEventsOnly`.

Type: String

Valid Values: `FailedEventsOnly` | `AllEvents`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SplunkDestinationDescription

Describes a destination in Splunk.

Contents

BufferingHints

The buffering options. If no value is specified, the default values for Splunk are used.

Type: [SplunkBufferingHints](#) object

Required: No

CloudWatchLoggingOptions

The Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

HECAcknowledgmentTimeoutInSeconds

The amount of time that Firehose waits to receive an acknowledgment from Splunk after it sends it data. At the end of the timeout period, Firehose either tries to send the data again or considers it an error, based on your retry settings.

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 600.

Required: No

HECEndpoint

The HTTP Event Collector (HEC) endpoint to which Firehose sends your data.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: . *

Required: No

HECEndpointType

This type can be either "Raw" or "Event."

Type: String

Valid Values: Raw | Event

Required: No

HECToken

A GUID you obtain from your Splunk cluster when you create a new HEC endpoint.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: . *

Required: No

ProcessingConfiguration

The data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

The retry behavior in case Firehose is unable to deliver data to Splunk or if it doesn't receive an acknowledgment of receipt from Splunk.

Type: [SplunkRetryOptions](#) object

Required: No

S3BackupMode

Defines how documents should be delivered to Amazon S3. When set to `FailedDocumentsOnly`, Firehose writes any data that could not be indexed to the configured Amazon S3 destination. When set to `AllDocuments`, Firehose delivers all incoming records to Amazon S3, and also writes failed documents to Amazon S3. Default value is `FailedDocumentsOnly`.

Type: String

Valid Values: FailedEventsOnly | AllEvents

Required: No

S3DestinationDescription

The Amazon S3 destination.>

Type: [S3DestinationDescription](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SplunkDestinationUpdate

Describes an update for a destination in Splunk.

Contents

BufferingHints

The buffering options. If no value is specified, the default values for Splunk are used.

Type: [SplunkBufferingHints](#) object

Required: No

CloudWatchLoggingOptions

The Amazon CloudWatch logging options for your delivery stream.

Type: [CloudWatchLoggingOptions](#) object

Required: No

HECAcknowledgmentTimeoutInSeconds

The amount of time that Firehose waits to receive an acknowledgment from Splunk after it sends data. At the end of the timeout period, Firehose either tries to send the data again or considers it an error, based on your retry settings.

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 600.

Required: No

HECEndpoint

The HTTP Event Collector (HEC) endpoint to which Firehose sends your data.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: . *

Required: No

HECEndpointType

This type can be either "Raw" or "Event."

Type: String

Valid Values: Raw | Event

Required: No

HECToken

A GUID that you obtain from your Splunk cluster when you create a new HEC endpoint.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: . *

Required: No

ProcessingConfiguration

The data processing configuration.

Type: [ProcessingConfiguration](#) object

Required: No

RetryOptions

The retry behavior in case Firehose is unable to deliver data to Splunk or if it doesn't receive an acknowledgment of receipt from Splunk.

Type: [SplunkRetryOptions](#) object

Required: No

S3BackupMode

Specifies how you want Firehose to back up documents to Amazon S3. When set to `FailedDocumentsOnly`, Firehose writes any data that could not be indexed to the configured Amazon S3 destination. When set to `AllEvents`, Firehose delivers all incoming records to Amazon S3, and also writes failed documents to Amazon S3. The default value is `FailedEventsOnly`.

You can update this backup mode from `FailedEventsOnly` to `AllEvents`. You can't update it from `AllEvents` to `FailedEventsOnly`.

Type: String

Valid Values: `FailedEventsOnly` | `AllEvents`

Required: No

S3Update

Your update to the configuration of the backup Amazon S3 location.

Type: [S3DestinationUpdate](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SplunkRetryOptions

Configures retry behavior in case Firehose is unable to deliver documents to Splunk, or if it doesn't receive an acknowledgment from Splunk.

Contents

DurationInSeconds

The total amount of time that Firehose spends on retries. This duration starts after the initial attempt to send data to Splunk fails. It doesn't include the periods during which Firehose waits for acknowledgment from Splunk after each attempt.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 7200.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Tag

Metadata that you can assign to a delivery stream, consisting of a key-value pair.

Contents

Key

A unique identifier for the tag. Maximum length: 128 characters. Valid characters: Unicode letters, digits, white space, `_` `.` `/` `=` `+` `-` `%` `@`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!aws:)[\p{L}\p{Z}\p{N}_.:\/=+\\-@%]*$`

Required: Yes

Value

An optional string, which you can use to describe or define the tag. Maximum length: 256 characters. Valid characters: Unicode letters, digits, white space, `_` `.` `/` `=` `+` `-` `%` `@`

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `^[\p{L}\p{Z}\p{N}_.:\/=+\\-@%]*$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

VpcConfiguration

The details of the VPC of the Amazon OpenSearch or Amazon OpenSearch Serverless destination.

Contents

RoleARN

The ARN of the IAM role that you want the delivery stream to use to create endpoints in the destination VPC. You can use your existing Firehose delivery role or you can specify a new role. In either case, make sure that the role trusts the Firehose service principal and that it grants the following permissions:

- `ec2:DescribeVpcs`
- `ec2:DescribeVpcAttribute`
- `ec2:DescribeSubnets`
- `ec2:DescribeSecurityGroups`
- `ec2:DescribeNetworkInterfaces`
- `ec2:CreateNetworkInterface`
- `ec2:CreateNetworkInterfacePermission`
- `ec2>DeleteNetworkInterface`

Important

When you specify subnets for delivering data to the destination in a private VPC, make sure you have enough number of free IP addresses in chosen subnets. If there is no available free IP address in a specified subnet, Firehose cannot create or add ENIs for the data delivery in the private VPC, and the delivery will be degraded or fail.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: Yes

SecurityGroupIds

The IDs of the security groups that you want Firehose to use when it creates ENIs in the VPC of the Amazon ES destination. You can use the same security group that the Amazon ES domain uses or different ones. If you specify different security groups here, ensure that they allow outbound HTTPS traffic to the Amazon ES domain's security group. Also ensure that the Amazon ES domain's security group allows HTTPS traffic from the security groups specified here. If you use the same security group for both your delivery stream and the Amazon ES domain, make sure the security group inbound rule allows HTTPS traffic. For more information about security group rules, see [Security group rules](#) in the Amazon VPC documentation.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^\S+$`

Required: Yes

SubnetIds

The IDs of the subnets that you want Firehose to use to create ENIs in the VPC of the Amazon ES destination. Make sure that the routing tables and inbound and outbound rules allow traffic to flow from the subnets whose IDs are specified here to the subnets that have the destination Amazon ES endpoints. Firehose creates at least one ENI in each of the subnets that are specified here. Do not delete or modify these ENIs.

The number of ENIs that Firehose creates in the subnets specified here scales up and down automatically based on throughput. To enable Firehose to scale up the number of ENIs to match throughput, ensure that you have sufficient quota. To help you calculate the quota you need, assume that Firehose can create up to three ENIs for this delivery stream for each of the subnets specified here. For more information about ENI quota, see [Network Interfaces](#) in the Amazon VPC Quotas topic.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 16 items.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^\S+$`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

VpcConfigurationDescription

The details of the VPC of the Amazon ES destination.

Contents

RoleARN

The ARN of the IAM role that the delivery stream uses to create endpoints in the destination VPC. You can use your existing Firehose delivery role or you can specify a new role. In either case, make sure that the role trusts the Firehose service principal and that it grants the following permissions:

- `ec2:DescribeVpcs`
- `ec2:DescribeVpcAttribute`
- `ec2:DescribeSubnets`
- `ec2:DescribeSecurityGroups`
- `ec2:DescribeNetworkInterfaces`
- `ec2:CreateNetworkInterface`
- `ec2:CreateNetworkInterfacePermission`
- `ec2>DeleteNetworkInterface`

If you revoke these permissions after you create the delivery stream, Firehose can't scale out by creating more ENIs when necessary. You might therefore see a degradation in performance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: Yes

SecurityGroupIds

The IDs of the security groups that Firehose uses when it creates ENIs in the VPC of the Amazon ES destination. You can use the same security group that the Amazon ES domain uses or different ones. If you specify different security groups, ensure that they allow outbound HTTPS traffic to the Amazon ES domain's security group. Also ensure that the Amazon ES domain's

security group allows HTTPS traffic from the security groups specified here. If you use the same security group for both your delivery stream and the Amazon ES domain, make sure the security group inbound rule allows HTTPS traffic. For more information about security group rules, see [Security group rules](#) in the Amazon VPC documentation.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^\S+$`

Required: Yes

SubnetIds

The IDs of the subnets that Firehose uses to create ENIs in the VPC of the Amazon ES destination. Make sure that the routing tables and inbound and outbound rules allow traffic to flow from the subnets whose IDs are specified here to the subnets that have the destination Amazon ES endpoints. Firehose creates at least one ENI in each of the subnets that are specified here. Do not delete or modify these ENIs.

The number of ENIs that Firehose creates in the subnets specified here scales up and down automatically based on throughput. To enable Firehose to scale up the number of ENIs to match throughput, ensure that you have sufficient quota. To help you calculate the quota you need, assume that Firehose can create up to three ENIs for this delivery stream for each of the subnets specified here. For more information about ENI quota, see [Network Interfaces](#) in the Amazon VPC Quotas topic.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 16 items.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^\S+$`

Required: Yes

VpcId

The ID of the Amazon ES destination's VPC.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^\S+$`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Common Errors

This section lists the errors common to the API actions of all Amazon services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to Amazon standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or Amazon access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The Amazon access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an Amazon service.

HTTP Status Code: 400