

Amazon IoT SiteWise



Amazon IoT SiteWise: API Reference

Table of Contents

Welcome	1
Actions	2
AssociateAssets	6
Request Syntax	6
URI Request Parameters	6
Request Body	6
Response Syntax	8
Response Elements	8
Errors	8
See Also	9
AssociateTimeSeriesToAssetProperty	10
Request Syntax	10
URI Request Parameters	10
Request Body	11
Response Syntax	11
Response Elements	11
Errors	11
See Also	12
BatchAssociateProjectAssets	14
Request Syntax	14
URI Request Parameters	14
Request Body	14
Response Syntax	15
Response Elements	15
Errors	16
See Also	17
BatchDisassociateProjectAssets	18
Request Syntax	18
URI Request Parameters	18
Request Body	18
Response Syntax	19
Response Elements	19
Errors	20
See Also	20

BatchGetAssetPropertyAggregates	22
Request Syntax	22
URI Request Parameters	22
Request Body	22
Response Syntax	23
Response Elements	24
Errors	25
Examples	26
See Also	28
BatchGetAssetPropertyValue	29
Request Syntax	29
URI Request Parameters	29
Request Body	29
Response Syntax	30
Response Elements	31
Errors	32
Examples	33
See Also	34
BatchGetAssetPropertyValueHistory	36
Request Syntax	36
URI Request Parameters	36
Request Body	36
Response Syntax	37
Response Elements	38
Errors	39
Examples	40
See Also	43
BatchPutAssetPropertyValue	44
Request Syntax	44
URI Request Parameters	45
Request Body	45
Response Syntax	46
Response Elements	46
Errors	47
See Also	48
CreateAccessPolicy	49

Request Syntax	49
URI Request Parameters	50
Request Body	50
Response Syntax	51
Response Elements	51
Errors	52
See Also	53
CreateAsset	54
Request Syntax	54
URI Request Parameters	54
Request Body	54
Response Syntax	56
Response Elements	57
Errors	58
See Also	59
CreateAssetModel	60
Request Syntax	60
URI Request Parameters	64
Request Body	64
Response Syntax	67
Response Elements	68
Errors	69
See Also	70
CreateAssetModelCompositeModel	71
Request Syntax	71
URI Request Parameters	73
Request Body	74
Response Syntax	77
Response Elements	77
Errors	78
See Also	79
CreateBulkImportJob	81
Request Syntax	81
URI Request Parameters	82
Request Body	82
Response Syntax	83

Response Elements	84
Errors	85
See Also	86
CreateDashboard	87
Request Syntax	87
URI Request Parameters	87
Request Body	87
Response Syntax	89
Response Elements	89
Errors	90
See Also	91
CreateDataset	92
Request Syntax	92
URI Request Parameters	92
Request Body	92
Response Syntax	94
Response Elements	95
Errors	95
See Also	97
CreateGateway	98
Request Syntax	98
URI Request Parameters	98
Request Body	98
Response Syntax	100
Response Elements	100
Errors	101
See Also	102
CreatePortal	103
Request Syntax	103
URI Request Parameters	104
Request Body	104
Response Syntax	107
Response Elements	108
Errors	109
See Also	110
CreateProject	111

Request Syntax	111
URI Request Parameters	111
Request Body	111
Response Syntax	113
Response Elements	113
Errors	114
See Also	115
DeleteAccessPolicy	116
Request Syntax	116
URI Request Parameters	116
Request Body	116
Response Syntax	116
Response Elements	117
Errors	117
See Also	117
DeleteAsset	119
Request Syntax	119
URI Request Parameters	119
Request Body	120
Response Syntax	120
Response Elements	120
Errors	120
See Also	121
DeleteAssetModel	123
Request Syntax	123
URI Request Parameters	123
Request Body	124
Response Syntax	124
Response Elements	125
Errors	125
See Also	126
DeleteAssetModelCompositeModel	127
Request Syntax	127
URI Request Parameters	127
Request Body	128
Response Syntax	128

Response Elements	129
Errors	129
See Also	130
DeleteDashboard	132
Request Syntax	132
URI Request Parameters	132
Request Body	132
Response Syntax	132
Response Elements	133
Errors	133
See Also	133
DeleteDataset	135
Request Syntax	135
URI Request Parameters	135
Request Body	135
Response Syntax	135
Response Elements	136
Errors	136
See Also	137
DeleteGateway	139
Request Syntax	139
URI Request Parameters	139
Request Body	139
Response Syntax	139
Response Elements	139
Errors	139
See Also	140
DeletePortal	142
Request Syntax	142
URI Request Parameters	142
Request Body	142
Response Syntax	142
Response Elements	143
Errors	143
See Also	144
DeleteProject	145

Request Syntax	145
URI Request Parameters	145
Request Body	145
Response Syntax	145
Response Elements	146
Errors	146
See Also	146
DeleteTimeSeries	148
Request Syntax	148
URI Request Parameters	148
Request Body	149
Response Syntax	149
Response Elements	149
Errors	150
See Also	150
DescribeAccessPolicy	152
Request Syntax	152
URI Request Parameters	152
Request Body	152
Response Syntax	152
Response Elements	153
Errors	154
See Also	155
DescribeAction	157
Request Syntax	157
URI Request Parameters	157
Request Body	157
Response Syntax	157
Response Elements	158
Errors	159
See Also	159
DescribeAsset	161
Request Syntax	161
URI Request Parameters	161
Request Body	161
Response Syntax	161

Response Elements	164
Errors	166
See Also	167
DescribeAssetCompositeModel	168
Request Syntax	168
URI Request Parameters	168
Request Body	169
Response Syntax	169
Response Elements	170
Errors	172
See Also	173
DescribeAssetModel	174
Request Syntax	174
URI Request Parameters	174
Request Body	174
Response Syntax	175
Response Elements	180
Errors	183
See Also	183
DescribeAssetModelCompositeModel	185
Request Syntax	185
URI Request Parameters	185
Request Body	186
Response Syntax	186
Response Elements	189
Errors	191
See Also	192
DescribeAssetProperty	193
Request Syntax	193
URI Request Parameters	193
Request Body	194
Response Syntax	194
Response Elements	198
Errors	199
See Also	200
DescribeBulkImportJob	202

Request Syntax	202
URI Request Parameters	202
Request Body	202
Response Syntax	202
Response Elements	203
Errors	205
See Also	206
DescribeDashboard	208
Request Syntax	208
URI Request Parameters	208
Request Body	208
Response Syntax	208
Response Elements	209
Errors	210
See Also	211
DescribeDataset	213
Request Syntax	213
URI Request Parameters	213
Request Body	213
Response Syntax	213
Response Elements	214
Errors	216
See Also	217
DescribeDefaultEncryptionConfiguration	218
Request Syntax	218
URI Request Parameters	218
Request Body	218
Response Syntax	218
Response Elements	218
Errors	219
See Also	220
DescribeGateway	221
Request Syntax	221
URI Request Parameters	221
Request Body	221
Response Syntax	221

Response Elements	222
Errors	224
See Also	224
DescribeGatewayCapabilityConfiguration	226
Request Syntax	226
URI Request Parameters	226
Request Body	226
Response Syntax	227
Response Elements	227
Errors	228
See Also	229
DescribeLoggingOptions	230
Request Syntax	230
URI Request Parameters	230
Request Body	230
Response Syntax	230
Response Elements	230
Errors	231
See Also	231
DescribePortal	233
Request Syntax	233
URI Request Parameters	233
Request Body	233
Response Syntax	233
Response Elements	234
Errors	238
See Also	238
DescribeProject	240
Request Syntax	240
URI Request Parameters	240
Request Body	240
Response Syntax	240
Response Elements	241
Errors	242
See Also	243
DescribeStorageConfiguration	244

Request Syntax	244
URI Request Parameters	244
Request Body	244
Response Syntax	244
Response Elements	245
Errors	247
See Also	248
DescribeTimeSeries	249
Request Syntax	249
URI Request Parameters	249
Request Body	250
Response Syntax	250
Response Elements	250
Errors	252
See Also	253
DisassociateAssets	255
Request Syntax	255
URI Request Parameters	255
Request Body	255
Response Syntax	257
Response Elements	257
Errors	257
See Also	258
DisassociateTimeSeriesFromAssetProperty	259
Request Syntax	259
URI Request Parameters	259
Request Body	260
Response Syntax	260
Response Elements	260
Errors	260
See Also	261
ExecuteAction	263
Request Syntax	263
URI Request Parameters	263
Request Body	263
Response Syntax	264

Response Elements	264
Errors	265
See Also	266
ExecuteQuery	267
Request Syntax	267
URI Request Parameters	267
Request Body	267
Response Syntax	268
Response Elements	269
Errors	269
See Also	271
GetAssetPropertyAggregates	272
Request Syntax	272
URI Request Parameters	272
Request Body	274
Response Syntax	274
Response Elements	275
Errors	275
See Also	276
GetAssetPropertyValue	278
Request Syntax	278
URI Request Parameters	278
Request Body	279
Response Syntax	279
Response Elements	279
Errors	280
See Also	280
GetAssetPropertyValueHistory	282
Request Syntax	282
URI Request Parameters	282
Request Body	284
Response Syntax	284
Response Elements	284
Errors	285
See Also	286
GetInterpolatedAssetPropertyValues	287

Request Syntax	287
URI Request Parameters	287
Request Body	290
Response Syntax	291
Response Elements	291
Errors	292
Examples	293
See Also	294
InvokeAssistant	295
Request Syntax	295
URI Request Parameters	295
Request Body	295
Response Syntax	296
Response Elements	297
Errors	299
See Also	300
ListAccessPolicies	302
Request Syntax	302
URI Request Parameters	302
Request Body	303
Response Syntax	303
Response Elements	304
Errors	305
See Also	305
ListActions	307
Request Syntax	307
URI Request Parameters	307
Request Body	308
Response Syntax	308
Response Elements	308
Errors	309
See Also	309
ListAssetModelCompositeModels	311
Request Syntax	311
URI Request Parameters	311
Request Body	312

Response Syntax	312
Response Elements	312
Errors	313
See Also	314
ListAssetModelProperties	315
Request Syntax	315
URI Request Parameters	315
Request Body	316
Response Syntax	316
Response Elements	318
Errors	319
See Also	319
ListAssetModels	321
Request Syntax	321
URI Request Parameters	321
Request Body	322
Response Syntax	322
Response Elements	323
Errors	323
See Also	324
ListAssetProperties	325
Request Syntax	325
URI Request Parameters	325
Request Body	326
Response Syntax	326
Response Elements	327
Errors	327
See Also	328
ListAssetRelationships	329
Request Syntax	329
URI Request Parameters	329
Request Body	330
Response Syntax	330
Response Elements	330
Errors	331
See Also	332

ListAssets	333
Request Syntax	333
URI Request Parameters	333
Request Body	334
Response Syntax	334
Response Elements	335
Errors	336
See Also	336
ListAssociatedAssets	338
Request Syntax	338
URI Request Parameters	338
Request Body	339
Response Syntax	339
Response Elements	340
Errors	341
See Also	342
ListBulkImportJobs	343
Request Syntax	343
URI Request Parameters	343
Request Body	343
Response Syntax	343
Response Elements	344
Errors	344
See Also	345
ListCompositionRelationships	347
Request Syntax	347
URI Request Parameters	347
Request Body	348
Response Syntax	348
Response Elements	348
Errors	349
See Also	349
ListDashboards	351
Request Syntax	351
URI Request Parameters	351
Request Body	351

Response Syntax	352
Response Elements	352
Errors	352
See Also	353
ListDatasets	354
Request Syntax	354
URI Request Parameters	354
Request Body	354
Response Syntax	354
Response Elements	355
Errors	356
See Also	356
ListGateways	358
Request Syntax	358
URI Request Parameters	358
Request Body	358
Response Syntax	358
Response Elements	359
Errors	360
See Also	360
ListPortals	362
Request Syntax	362
URI Request Parameters	362
Request Body	362
Response Syntax	362
Response Elements	363
Errors	363
See Also	364
ListProjectAssets	365
Request Syntax	365
URI Request Parameters	365
Request Body	365
Response Syntax	366
Response Elements	366
Errors	366
See Also	367

ListProjects	368
Request Syntax	368
URI Request Parameters	368
Request Body	368
Response Syntax	369
Response Elements	369
Errors	369
See Also	370
ListTagsForResource	371
Request Syntax	371
URI Request Parameters	371
Request Body	371
Response Syntax	371
Response Elements	371
Errors	372
See Also	373
ListTimeSeries	375
Request Syntax	375
URI Request Parameters	375
Request Body	376
Response Syntax	376
Response Elements	376
Errors	377
See Also	378
PutDefaultEncryptionConfiguration	379
Request Syntax	379
URI Request Parameters	379
Request Body	379
Response Syntax	380
Response Elements	380
Errors	381
See Also	382
PutLoggingOptions	383
Request Syntax	383
URI Request Parameters	383
Request Body	383

Response Syntax	383
Response Elements	383
Errors	384
See Also	384
PutStorageConfiguration	386
Request Syntax	386
URI Request Parameters	386
Request Body	386
Response Syntax	388
Response Elements	389
Errors	391
See Also	392
TagResource	394
Request Syntax	394
URI Request Parameters	394
Request Body	394
Response Syntax	395
Response Elements	395
Errors	395
See Also	396
UntagResource	398
Request Syntax	398
URI Request Parameters	398
Request Body	398
Response Syntax	398
Response Elements	398
Errors	399
See Also	400
UpdateAccessPolicy	401
Request Syntax	401
URI Request Parameters	401
Request Body	402
Response Syntax	403
Response Elements	403
Errors	403
See Also	404

UpdateAsset	405
Request Syntax	405
URI Request Parameters	405
Request Body	405
Response Syntax	407
Response Elements	407
Errors	407
See Also	408
UpdateAssetModel	410
Request Syntax	410
URI Request Parameters	414
Request Body	415
Response Syntax	418
Response Elements	418
Errors	418
See Also	420
UpdateAssetModelCompositeModel	421
Request Syntax	421
URI Request Parameters	423
Request Body	424
Response Syntax	426
Response Elements	427
Errors	427
See Also	428
UpdateAssetProperty	430
Request Syntax	430
URI Request Parameters	430
Request Body	431
Response Syntax	432
Response Elements	432
Errors	432
See Also	433
UpdateDashboard	435
Request Syntax	435
URI Request Parameters	435
Request Body	435

Response Syntax	437
Response Elements	437
Errors	437
See Also	438
UpdateDataset	439
Request Syntax	439
URI Request Parameters	439
Request Body	440
Response Syntax	441
Response Elements	441
Errors	442
See Also	443
UpdateGateway	445
Request Syntax	445
URI Request Parameters	445
Request Body	445
Response Syntax	446
Response Elements	446
Errors	446
See Also	447
UpdateGatewayCapabilityConfiguration	448
Request Syntax	448
URI Request Parameters	448
Request Body	448
Response Syntax	449
Response Elements	449
Errors	450
See Also	451
UpdatePortal	453
Request Syntax	453
URI Request Parameters	453
Request Body	454
Response Syntax	456
Response Elements	457
Errors	457
See Also	458

UpdateProject	459
Request Syntax	459
URI Request Parameters	459
Request Body	459
Response Syntax	460
Response Elements	460
Errors	460
See Also	461
Data Types	462
AccessPolicySummary	467
Contents	467
See Also	468
ActionDefinition	469
Contents	469
See Also	470
ActionPayload	471
Contents	471
See Also	471
ActionSummary	472
Contents	472
See Also	472
AggregatedValue	474
Contents	474
See Also	474
Aggregates	475
Contents	475
See Also	476
Alarms	477
Contents	477
See Also	477
AssetCompositeModel	479
Contents	479
See Also	480
AssetCompositeModelPathSegment	481
Contents	481
See Also	481

AssetCompositeModelSummary	482
Contents	482
See Also	483
AssetErrorDetails	485
Contents	485
See Also	485
AssetHierarchy	487
Contents	487
See Also	488
AssetHierarchyInfo	489
Contents	489
See Also	489
AssetModelCompositeModel	490
Contents	490
See Also	491
AssetModelCompositeModelDefinition	493
Contents	493
See Also	494
AssetModelCompositeModelPathSegment	496
Contents	496
See Also	496
AssetModelCompositeModelSummary	497
Contents	497
See Also	498
AssetModelHierarchy	499
Contents	499
See Also	500
AssetModelHierarchyDefinition	502
Contents	502
See Also	503
AssetModelProperty	504
Contents	504
See Also	506
AssetModelPropertyDefinition	507
Contents	507
See Also	509

AssetModelPropertyPathSegment	510
Contents	510
See Also	510
AssetModelPropertySummary	511
Contents	511
See Also	513
AssetModelStatus	514
Contents	514
See Also	514
AssetModelSummary	515
Contents	515
See Also	517
AssetProperty	518
Contents	518
See Also	520
AssetPropertyPathSegment	521
Contents	521
See Also	521
AssetPropertySummary	522
Contents	522
See Also	524
AssetPropertyValue	525
Contents	525
See Also	525
AssetRelationshipSummary	526
Contents	526
See Also	526
AssetStatus	527
Contents	527
See Also	527
AssetSummary	528
Contents	528
See Also	530
AssociatedAssetsSummary	531
Contents	531
See Also	533

Attribute	534
Contents	534
See Also	534
BatchGetAssetPropertyAggregatesEntry	535
Contents	535
See Also	537
BatchGetAssetPropertyAggregatesErrorEntry	539
Contents	539
See Also	539
BatchGetAssetPropertyAggregatesErrorInfo	541
Contents	541
See Also	541
BatchGetAssetPropertyAggregatesSkippedEntry	542
Contents	542
See Also	542
BatchGetAssetPropertyAggregatesSuccessEntry	544
Contents	544
See Also	544
BatchGetAssetPropertyValueEntry	545
Contents	545
See Also	546
BatchGetAssetPropertyValueErrorEntry	547
Contents	547
See Also	547
BatchGetAssetPropertyValueErrorInfo	549
Contents	549
See Also	549
BatchGetAssetPropertyValueHistoryEntry	550
Contents	550
See Also	552
BatchGetAssetPropertyValueHistoryErrorEntry	553
Contents	553
See Also	553
BatchGetAssetPropertyValueHistoryErrorInfo	555
Contents	555
See Also	555

BatchGetAssetPropertyValueHistorySkippedEntry	556
Contents	556
See Also	556
BatchGetAssetPropertyValueHistorySuccessEntry	558
Contents	558
See Also	558
BatchGetAssetPropertyValueSkippedEntry	559
Contents	559
See Also	559
BatchGetAssetPropertyValueSuccessEntry	561
Contents	561
See Also	561
BatchPutAssetPropertyError	562
Contents	562
See Also	562
BatchPutAssetPropertyErrorEntry	564
Contents	564
See Also	564
Citation	565
Contents	565
See Also	565
ColumnInfo	566
Contents	566
See Also	566
ColumnType	567
Contents	567
See Also	567
CompositeModelProperty	568
Contents	568
See Also	569
CompositionDetails	570
Contents	570
See Also	570
CompositionRelationshipItem	571
Contents	571
See Also	571

CompositionRelationshipSummary	572
Contents	572
See Also	573
ConfigurationErrorDetails	574
Contents	574
See Also	574
ConfigurationStatus	575
Contents	575
See Also	575
Content	576
Contents	576
See Also	576
Csv	577
Contents	577
See Also	577
CustomerManagedS3Storage	578
Contents	578
See Also	578
DashboardSummary	579
Contents	579
See Also	580
DataSetReference	581
Contents	581
See Also	581
DatasetSource	582
Contents	582
See Also	582
DatasetStatus	584
Contents	584
See Also	584
DatasetSummary	585
Contents	585
See Also	586
Datum	588
Contents	588
See Also	588

DetailedError	590
Contents	590
See Also	590
ErrorDetails	591
Contents	591
See Also	591
ErrorReportLocation	592
Contents	592
See Also	592
ExpressionVariable	593
Contents	593
See Also	593
File	594
Contents	594
See Also	594
FileFormat	596
Contents	596
See Also	596
ForwardingConfig	597
Contents	597
See Also	597
GatewayCapabilitySummary	598
Contents	598
See Also	599
GatewayPlatform	600
Contents	600
See Also	600
GatewaySummary	601
Contents	601
See Also	602
Greengrass	603
Contents	603
See Also	603
GreengrassV2	604
Contents	604
See Also	604

GroupIdentity	606
Contents	606
See Also	606
IAMRoleIdentity	607
Contents	607
See Also	607
IAMUserIdentity	608
Contents	608
See Also	608
Identity	609
Contents	609
See Also	610
Image	611
Contents	611
See Also	611
ImageFile	612
Contents	612
See Also	612
ImageLocation	613
Contents	613
See Also	613
InterpolatedAssetPropertyValue	614
Contents	614
See Also	614
InvocationOutput	615
Contents	615
See Also	615
JobConfiguration	616
Contents	616
See Also	616
JobSummary	617
Contents	617
See Also	618
KendraSourceDetail	619
Contents	619
See Also	619

Location	620
Contents	620
See Also	620
LoggingOptions	621
Contents	621
See Also	621
Measurement	622
Contents	622
See Also	622
MeasurementProcessingConfig	623
Contents	623
See Also	623
Metric	624
Contents	624
See Also	625
MetricProcessingConfig	626
Contents	626
See Also	626
MetricWindow	627
Contents	627
See Also	627
MonitorErrorDetails	628
Contents	628
See Also	628
MultiLayerStorage	629
Contents	629
See Also	629
Parquet	630
Contents	630
See Also	630
PortalResource	631
Contents	631
See Also	631
PortalStatus	632
Contents	632
See Also	632

PortalSummary	633
Contents	633
See Also	635
PortalTypeEntry	636
Contents	636
See Also	636
ProjectResource	637
Contents	637
See Also	637
ProjectSummary	638
Contents	638
See Also	639
Property	640
Contents	640
See Also	642
PropertyNotification	643
Contents	643
See Also	643
PropertyType	644
Contents	644
See Also	645
PropertyValueNullValue	646
Contents	646
See Also	646
PutAssetPropertyValueEntry	647
Contents	647
See Also	648
Reference	649
Contents	649
See Also	649
Resource	650
Contents	650
See Also	650
ResponseStream	651
Contents	651
See Also	653

RetentionPeriod	654
Contents	654
See Also	654
Row	656
Contents	656
See Also	656
SiemensIE	657
Contents	657
See Also	657
Source	658
Contents	658
See Also	658
SourceDetail	659
Contents	659
See Also	659
TargetResource	660
Contents	660
See Also	660
TimeInNanos	661
Contents	661
See Also	661
TimeSeriesSummary	662
Contents	662
See Also	664
Trace	665
Contents	665
See Also	665
Transform	666
Contents	666
See Also	667
TransformProcessingConfig	668
Contents	668
See Also	668
TumblingWindow	669
Contents	669
See Also	670

UserIdentity	672
Contents	672
See Also	672
VariableValue	673
Contents	673
See Also	674
Variant	675
Contents	675
See Also	676
WarmTierRetentionPeriod	677
Contents	677
See Also	677
Common Parameters	678
Common Errors	681

Welcome

Welcome to the Amazon IoT SiteWise API Reference. Amazon IoT SiteWise is an Amazon service that connects [Industrial Internet of Things \(IIoT\)](#) devices to the power of the Amazon Cloud. For more information, see the [Amazon IoT SiteWise User Guide](#). For information about Amazon IoT SiteWise quotas, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

This document was last published on May 16, 2025.

Actions

The following actions are supported:

- [AssociateAssets](#)
- [AssociateTimeSeriesToAssetProperty](#)
- [BatchAssociateProjectAssets](#)
- [BatchDisassociateProjectAssets](#)
- [BatchGetAssetPropertyAggregates](#)
- [BatchGetAssetPropertyValue](#)
- [BatchGetAssetPropertyValueHistory](#)
- [BatchPutAssetPropertyValue](#)
- [CreateAccessPolicy](#)
- [CreateAsset](#)
- [CreateAssetModel](#)
- [CreateAssetModelCompositeModel](#)
- [CreateBulkImportJob](#)
- [CreateDashboard](#)
- [CreateDataset](#)
- [CreateGateway](#)
- [CreatePortal](#)
- [CreateProject](#)
- [DeleteAccessPolicy](#)
- [DeleteAsset](#)
- [DeleteAssetModel](#)
- [DeleteAssetModelCompositeModel](#)
- [DeleteDashboard](#)
- [DeleteDataset](#)
- [DeleteGateway](#)
- [DeletePortal](#)
- [DeleteProject](#)

- [DeleteTimeSeries](#)
- [DescribeAccessPolicy](#)
- [DescribeAction](#)
- [DescribeAsset](#)
- [DescribeAssetCompositeModel](#)
- [DescribeAssetModel](#)
- [DescribeAssetModelCompositeModel](#)
- [DescribeAssetProperty](#)
- [DescribeBulkImportJob](#)
- [DescribeDashboard](#)
- [DescribeDataset](#)
- [DescribeDefaultEncryptionConfiguration](#)
- [DescribeGateway](#)
- [DescribeGatewayCapabilityConfiguration](#)
- [DescribeLoggingOptions](#)
- [DescribePortal](#)
- [DescribeProject](#)
- [DescribeStorageConfiguration](#)
- [DescribeTimeSeries](#)
- [DisassociateAssets](#)
- [DisassociateTimeSeriesFromAssetProperty](#)
- [ExecuteAction](#)
- [ExecuteQuery](#)
- [GetAssetPropertyAggregates](#)
- [GetAssetPropertyValue](#)
- [GetAssetPropertyValueHistory](#)
- [GetInterpolatedAssetPropertyValues](#)
- [InvokeAssistant](#)
- [ListAccessPolicies](#)
- [ListActions](#)

- [ListAssetModelCompositeModels](#)
- [ListAssetModelProperties](#)
- [ListAssetModels](#)
- [ListAssetProperties](#)
- [ListAssetRelationships](#)
- [ListAssets](#)
- [ListAssociatedAssets](#)
- [ListBulkImportJobs](#)
- [ListCompositionRelationships](#)
- [ListDashboards](#)
- [ListDatasets](#)
- [ListGateways](#)
- [ListPortals](#)
- [ListProjectAssets](#)
- [ListProjects](#)
- [ListTagsForResource](#)
- [ListTimeSeries](#)
- [PutDefaultEncryptionConfiguration](#)
- [PutLoggingOptions](#)
- [PutStorageConfiguration](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateAccessPolicy](#)
- [UpdateAsset](#)
- [UpdateAssetModel](#)
- [UpdateAssetModelCompositeModel](#)
- [UpdateAssetProperty](#)
- [UpdateDashboard](#)
- [UpdateDataset](#)
- [UpdateGateway](#)

- [UpdateGatewayCapabilityConfiguration](#)
- [UpdatePortal](#)
- [UpdateProject](#)

AssociateAssets

Associates a child asset with the given parent asset through a hierarchy defined in the parent asset's model. For more information, see [Associating assets](#) in the *Amazon IoT SiteWise User Guide*.

Request Syntax

```
POST /assets/assetId/associate HTTP/1.1
Content-type: application/json
```

```
{
  "childAssetId": "string",
  "clientToken": "string",
  "hierarchyId": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

[assetId](#)

The ID of the parent asset. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|
^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

Request Body

The request accepts the following data in JSON format.

childAssetId

The ID of the child asset to be associated. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

hierarchyId

The ID of a hierarchy in the parent asset's model. (This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.) Hierarchies allow different groupings of assets to be formed that all come from the same asset model. For more information, see [Asset hierarchies](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceAlreadyExistsException

The resource already exists.

HTTP Status Code: 409

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

AssociateTimeSeriesToAssetProperty

Associates a time series (data stream) with an asset property.

Request Syntax

```
POST /timeseries/associate/?alias=alias&assetId=assetId&propertyId=propertyId HTTP/1.1  
Content-type: application/json
```

```
{  
  "clientToken": "string"  
}
```

URI Request Parameters

The request uses the following URI parameters.

alias

The alias that identifies the time series.

Length Constraints: Minimum length of 1.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

assetId

The ID of the asset in which the asset property was created. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|`

`^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.]*[a-zA-Z0-9]+`

Required: Yes

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)

- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

BatchAssociateProjectAssets

Associates a group (batch) of assets with an Amazon IoT SiteWise Monitor project.

Request Syntax

```
POST /projects/projectId/assets/associate HTTP/1.1
Content-type: application/json
```

```
{
  "assetIds": [ "string" ],
  "clientToken": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

projectId

The ID of the project to which to associate the assets.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

assetIds

The IDs of the assets to be associated to the project.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "errors": [
    {
      "assetId": "string",
      "code": "string",
      "message": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

errors

A list of associated error information, if any.

Type: Array of [AssetErrorDetails](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

BatchDisassociateProjectAssets

Disassociates a group (batch) of assets from an Amazon IoT SiteWise Monitor project.

Request Syntax

```
POST /projects/projectId/assets/disassociate HTTP/1.1
Content-type: application/json
```

```
{
  "assetIds": [ "string" ],
  "clientToken": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

projectId

The ID of the project from which to disassociate the assets.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

assetIds

The IDs of the assets to be disassociated from the project.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "errors": [
    {
      "assetId": "string",
      "code": "string",
      "message": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

errors

A list of associated error information, if any.

Type: Array of [AssetErrorDetails](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyAggregates

Gets aggregated values (for example, average, minimum, and maximum) for one or more asset properties. For more information, see [Querying aggregates](#) in the *Amazon IoT SiteWise User Guide*.

Request Syntax

```
POST /properties/batch/aggregates HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "entries": [
    {
      "aggregateTypes": [ "string" ],
      "assetId": "string",
      "endDate": number,
      "entryId": "string",
      "propertyAlias": "string",
      "propertyId": "string",
      "qualities": [ "string" ],
      "resolution": "string",
      "startDate": number,
      "timeOrdering": "string"
    }
  ],
  "maxResults": number,
  "nextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

entries

The list of asset property aggregate entries for the batch get request. You can specify up to 16 entries per request.

Type: Array of [BatchGetAssetPropertyAggregatesEntry](#) objects

Required: Yes

[maxResults](#)

The maximum number of results to return for each paginated request. A result set is returned in the two cases, whichever occurs first.

- The size of the result set is equal to 1 MB.
- The number of data points in the result set is equal to the value of `maxResults`. The maximum value of `maxResults` is 4000.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

[nextToken](#)

The token to be used for the next set of paginated results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `[A-Za-z0-9+/=]+`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "errorEntries": [
    {
      "entryId": "string",
      "errorCode": "string",
      "errorMessage": "string"
    }
  ]
}
```

```

],
"nextToken": "string",
"skippedEntries": [
  {
    "completionStatus": "string",
    "entryId": "string",
    "errorInfo": {
      "errorCode": "string",
      "errorTimestamp": number
    }
  }
],
"successEntries": [
  {
    "aggregatedValues": [
      {
        "quality": "string",
        "timestamp": number,
        "value": {
          "average": number,
          "count": number,
          "maximum": number,
          "minimum": number,
          "standardDeviation": number,
          "sum": number
        }
      }
    ],
    "entryId": "string"
  }
]
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

errorEntries

A list of the errors (if any) associated with the batch request. Each error entry contains the `entryId` of the entry that failed.

Type: Array of [BatchGetAssetPropertyAggregatesErrorEntry](#) objects

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

skippedEntries

A list of entries that were not processed by this batch request. because these entries had been completely processed by previous paginated requests. Each skipped entry contains the `entryId` of the entry that skipped.

Type: Array of [BatchGetAssetPropertyAggregatesSkippedEntry](#) objects

successEntries

A list of entries that were processed successfully by this batch request. Each success entry contains the `entryId` of the entry that succeeded and the latest query result.

Type: Array of [BatchGetAssetPropertyAggregatesSuccessEntry](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ServiceUnavailableException

The requested service is unavailable.

HTTP Status Code: 503

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

Examples

Example

The following example uses the Amazon Command Line Interface (Amazon CLI) to retrieve the average temperature value for two wind turbines between April 26, 2021 at midnight and May 3, 2021 at midnight in Pacific Time (PT). The following also shows the contents of the `batch-get-asset-property-aggregates.json` file.

Sample Request

```
aws iotsitewise batch-get-asset-property-aggregates --cli-input-json file://batch-get-asset-property-aggregates.json
```

```
{
  "entries": [
    {
      "entryId": "1",
      "aggregateTypes": [
        "AVERAGE"
      ],
      "assetId": "a1b2c3d4-5678-90ab-cdef-11111EXAMPLE",
      "propertyId": "a1b2c3d4-5678-90ab-cdef-22222EXAMPLE",
      "startDate": 1619420400,
      "endDate": 1620025200,
    }
  ]
}
```

```
    "qualities":[
      "GOOD"
    ],
    "resolution":"1h"
  },
  {
    "entryId":"2",
    "aggregateTypes":[
      "AVERAGE"
    ],
    "assetId":"a1b2c3d4-5678-90ab-cdef-33333EXAMPLE",
    "propertyId":"a1b2c3d4-5678-90ab-cdef-44444EXAMPLE",
    "startDate":1619420400,
    "endDate":1620025200,
    "qualities":[
      "GOOD"
    ],
    "resolution":"1h"
  }
]
```

Sample Response

```
{
  "errorEntries" :[ ],
  "successEntries" :[
    {
      "entryId" : "1",
      "aggregatedValues" :[
        {
          "timestamp" :1649348973.0,
          "quality" : "GOOD",
          "value" :{
            "average" :1430.7175
          }
        }
      ]
    },
    {
      "entryId" : "2",
      "aggregatedValues" :[
        {
```

```
        "timestamp" :1649348973.0,  
        "quality" : "GOOD",  
        "value" :{  
            "average" :1425.9525  
        }  
    }  
]  
},  
"skippedEntries" :[ ]  
}
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyValue

Gets the current value for one or more asset properties. For more information, see [Querying current values](#) in the *Amazon IoT SiteWise User Guide*.

Request Syntax

```
POST /properties/batch/latest HTTP/1.1
Content-type: application/json
```

```
{
  "entries": [
    {
      "assetId": "string",
      "entryId": "string",
      "propertyAlias": "string",
      "propertyId": "string"
    }
  ],
  "nextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

entries

The list of asset property value entries for the batch get request. You can specify up to 128 entries per request.

Type: Array of [BatchGetAssetPropertyValueEntry](#) objects

Required: Yes

nextToken

The token to be used for the next set of paginated results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Required: No

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "errorEntries": [
    {
      "entryId": "string",
      "errorCode": "string",
      "errorMessage": "string"
    }
  ],
  "nextToken": "string",
  "skippedEntries": [
    {
      "completionStatus": "string",
      "entryId": "string",
      "errorInfo": {
        "errorCode": "string",
        "errorTimestamp": number
      }
    }
  ],
  "successEntries": [
    {
      "assetPropertyValue": {
        "quality": "string",
        "timestamp": {
          "offsetInNanos": number,
          "timeInSeconds": number
        }
      },
      "value": {
        "booleanValue": boolean,
        "doubleValue": number,
```



```
        "integerValue": number,
        "nullValue": {
            "valueType": "string"
        },
        "stringValue": "string"
    }
},
"entryId": "string"
}
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

errorEntries

A list of the errors (if any) associated with the batch request. Each error entry contains the entryId of the entry that failed.

Type: Array of [BatchGetAssetPropertyValueErrorEntry](#) objects

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

skippedEntries

A list of entries that were not processed by this batch request. because these entries had been completely processed by previous paginated requests. Each skipped entry contains the entryId of the entry that skipped.

Type: Array of [BatchGetAssetPropertyValueSkippedEntry](#) objects

[successEntries](#)

A list of entries that were processed successfully by this batch request. Each success entry contains the `entryId` of the entry that succeeded and the latest query result.

Type: Array of [BatchGetAssetPropertyValueSuccessEntry](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ServiceUnavailableException

The requested service is unavailable.

HTTP Status Code: 503

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

Examples

Example

The following example uses the Amazon Command Line Interface (Amazon CLI) to retrieve the current temperature value for two wind turbines. The following also shows the contents of the `batch-get-asset-property-value.json` file.

Sample Request

```
aws iotsitewise batch-get-asset-property-value --cli-input-json file://batch-get-asset-property-value.json
```

```
{
  "entries": [
    {
      "entryId": "1",
      "assetId": "a1b2c3d4-5678-90ab-cdef-11111EXAMPLE",
      "propertyId": "a1b2c3d4-5678-90ab-cdef-22222EXAMPLE"
    },
    {
      "entryId": "2",
      "assetId": "a1b2c3d4-5678-90ab-cdef-33333EXAMPLE",
      "propertyId": "a1b2c3d4-5678-90ab-cdef-44444EXAMPLE"
    }
  ]
}
```

Sample Response

```
{
  "errorEntries": [
  ],
  "successEntries": [
    {
      "entryId": "1",
      "propertyValue": {
        "value": {
          "doubleValue": 1426.66
        }
      }
    }
  ]
}
```

```
    },
    "timestamp":{
      "timeInSeconds":1580853000,
      "offsetInNanos":0
    },
    "quality":"GOOD"
  }
},
{
  "entryId":"2",
  "propertyValue":{
    "value":{
      "doubleValue":1429.44
    },
    "timestamp":{
      "timeInSeconds":1580853000,
      "offsetInNanos":0
    },
    "quality":"GOOD"
  }
}
]
}
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyValueHistory

Gets the historical values for one or more asset properties. For more information, see [Querying historical values](#) in the *Amazon IoT SiteWise User Guide*.

Request Syntax

```
POST /properties/batch/history HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "entries": [
    {
      "assetId": "string",
      "endDate": number,
      "entryId": "string",
      "propertyAlias": "string",
      "propertyId": "string",
      "qualities": [ "string" ],
      "startDate": number,
      "timeOrdering": "string"
    }
  ],
  "maxResults": number,
  "nextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

entries

The list of asset property historical value entries for the batch get request. You can specify up to 16 entries per request.

Type: Array of [BatchGetAssetPropertyValueHistoryEntry](#) objects

Required: Yes

maxResults

The maximum number of results to return for each paginated request. A result set is returned in the two cases, whichever occurs first.

- The size of the result set is equal to 4 MB.
- The number of data points in the result set is equal to the value of `maxResults`. The maximum value of `maxResults` is 20000.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

nextToken

The token to be used for the next set of paginated results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `[A-Za-z0-9+/=]+`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "errorEntries": [
    {
      "entryId": "string",
      "errorCode": "string",
      "errorMessage": "string"
    }
  ],
  "nextToken": "string",
  "skippedEntries": [
    {
```

```

    "completionStatus": "string",
    "entryId": "string",
    "errorInfo": {
      "errorCode": "string",
      "errorTimestamp": number
    }
  },
],
"successEntries": [
  {
    "assetPropertyValueHistory": [
      {
        "quality": "string",
        "timestamp": {
          "offsetInNanos": number,
          "timeInSeconds": number
        },
        "value": {
          "booleanValue": boolean,
          "doubleValue": number,
          "integerValue": number,
          "nullValue": {
            "valueType": "string"
          },
          "stringValue": "string"
        }
      }
    ],
    "entryId": "string"
  }
]
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

errorEntries

A list of the errors (if any) associated with the batch request. Each error entry contains the `entryId` of the entry that failed.

Type: Array of [BatchGetAssetPropertyValueHistoryErrorEntry](#) objects

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

skippedEntries

A list of entries that were not processed by this batch request. because these entries had been completely processed by previous paginated requests. Each skipped entry contains the entryId of the entry that skipped.

Type: Array of [BatchGetAssetPropertyValueHistorySkippedEntry](#) objects

successEntries

A list of entries that were processed successfully by this batch request. Each success entry contains the entryId of the entry that succeeded and the latest query result.

Type: Array of [BatchGetAssetPropertyValueHistorySuccessEntry](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ServiceUnavailableException

The requested service is unavailable.

HTTP Status Code: 503

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

Examples

Example

The following example uses the Amazon Command Line Interface (Amazon CLI) to retrieve the historical temperature values for two wind turbines between April 26, 2021 at midnight and May 3, 2021 at midnight in Pacific Time (PT). The following also shows the contents of the `batch-get-asset-property-value-history.json` file.

Sample Request

```
aws iotsitewise batch-get-asset-property-value-history --cli-input-json file://batch-get-asset-property-value-history.json
```

```
{
  "entries": [
    {
      "entryId": "1",
      "assetId": "a1b2c3d4-5678-90ab-cdef-11111EXAMPLE",
      "propertyId": "a1b2c3d4-5678-90ab-cdef-22222EXAMPLE",
      "startDate": 1619420400,
      "endDate": 1620025200
    },
    {
      "entryId": "2",
```

```
    "assetId":"a1b2c3d4-5678-90ab-cdef-33333EXAMPLE",
    "propertyId":"a1b2c3d4-5678-90ab-cdef-44444EXAMPLE",
    "startDate":1619420400,
    "endDate":1620025200
  }
]
}
```

Sample Response

```
{
  "errorEntries":[],
  "successEntries":[
    {
      "entryId":"1",
      "assetPropertyValueHistory":[
        {
          "value":{
            "doubleValue":1426.55
          },
          "timestamp":{
            "timeInSeconds":1619420400,
            "offsetInNanos":0
          },
          "quality":"GOOD"
        },
        {
          "value":{
            "doubleValue":1429.23
          },
          "timestamp":{
            "timeInSeconds":1619620700,
            "offsetInNanos":0
          },
          "quality":"GOOD"
        },
        {
          "value":{
            "doubleValue":1431.43
          },
          "timestamp":{
            "timeInSeconds":1619820400,
            "offsetInNanos":0
          }
        }
      ]
    }
  ]
}
```

```
    },
    "quality":"GOOD"
  },
  {
    "value":{
      "doubleValue":1435.66
    },
    "timestamp":{
      "timeInSeconds":1620025200,
      "offsetInNanos":0
    },
    "quality":"GOOD"
  }
]
},
{
  "entryId":"2",
  "assetPropertyValueHistory":[
    {
      "value":{
        "doubleValue":1424.17
      },
      "timestamp":{
        "timeInSeconds":1619420400,
        "offsetInNanos":0
      },
      "quality":"GOOD"
    },
    {
      "value":{
        "doubleValue":1424.23
      },
      "timestamp":{
        "timeInSeconds":1619620700,
        "offsetInNanos":0
      },
      "quality":"GOOD"
    },
    {
      "value":{
        "doubleValue":1425.24
      },
      "timestamp":{
        "timeInSeconds":1619820400,
```

```
        "offsetInNanos":0
      },
      "quality":"GOOD"
    },
    {
      "value":{
        "doubleValue":1430.17
      },
      "timestamp":{
        "timeInSeconds":1620025200,
        "offsetInNanos":0
      },
      "quality":"GOOD"
    }
  ]
}
],
"skippedEntries":[]
}
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

BatchPutAssetPropertyValue

Sends a list of asset property values to Amazon IoT SiteWise. Each value is a timestamp-quality-value (TQV) data point. For more information, see [Ingesting data using the API](#) in the *Amazon IoT SiteWise User Guide*.

To identify an asset property, you must specify one of the following:

- The `assetId` and `propertyId` of an asset property.
- A `propertyAlias`, which is a data stream alias (for example, `/company/windfarm/3/turbine/7/temperature`). To define an asset property's alias, see [UpdateAssetProperty](#).

Important

With respect to Unix epoch time, Amazon IoT SiteWise accepts only TQVs that have a timestamp of no more than 7 days in the past and no more than 10 minutes in the future. Amazon IoT SiteWise rejects timestamps outside of the inclusive range of [-7 days, +10 minutes] and returns a `TimestampOutOfRangeException` error.

For each asset property, Amazon IoT SiteWise overwrites TQVs with duplicate timestamps unless the newer TQV has a different quality. For example, if you store a TQV {T1, GOOD, V1}, then storing {T1, GOOD, V2} replaces the existing TQV.

Amazon IoT SiteWise authorizes access to each `BatchPutAssetPropertyValue` entry individually. For more information, see [BatchPutAssetPropertyValue authorization](#) in the *Amazon IoT SiteWise User Guide*.

Request Syntax

```
POST /properties HTTP/1.1
Content-type: application/json

{
  "enablePartialEntryProcessing": boolean,
  "entries": [
    {
      "assetId": "string",
      "entryId": "string",
```

```
"propertyAlias": "string",
"propertyId": "string",
"propertyValues": [
  {
    "quality": "string",
    "timestamp": {
      "offsetInNanos": number,
      "timeInSeconds": number
    },
    "value": {
      "booleanValue": boolean,
      "doubleValue": number,
      "integerValue": number,
      "nullValue": {
        "valueType": "string"
      },
      "stringValue": "string"
    }
  }
]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[enablePartialEntryProcessing](#)

This setting enables partial ingestion at entry-level. If set to `true`, we ingest all TQVs not resulting in an error. If set to `false`, an invalid TQV fails ingestion of the entire entry that contains it.

Type: Boolean

Required: No

entries

The list of asset property value entries for the batch put request. You can specify up to 10 entries per request.

Type: Array of [PutAssetPropertyValueEntry](#) objects

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "errorEntries": [
    {
      "entryId": "string",
      "errors": [
        {
          "errorCode": "string",
          "errorMessage": "string",
          "timestamps": [
            {
              "offsetInNanos": number,
              "timeInSeconds": number
            }
          ]
        }
      ]
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

errorEntries

A list of the errors (if any) associated with the batch put request. Each error entry contains the `entryId` of the entry that failed.

Type: Array of [BatchPutAssetPropertyErrorEntry](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ServiceUnavailableException

The requested service is unavailable.

HTTP Status Code: 503

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateAccessPolicy

Creates an access policy that grants the specified identity (IAM Identity Center user, IAM Identity Center group, or IAM user) access to the specified Amazon IoT SiteWise Monitor portal or project resource.

Request Syntax

```
POST /access-policies HTTP/1.1
Content-type: application/json

{
  "accessPolicyIdentity": {
    "group": {
      "id": "string"
    },
    "iamRole": {
      "arn": "string"
    },
    "iamUser": {
      "arn": "string"
    },
    "user": {
      "id": "string"
    }
  },
  "accessPolicyPermission": "string",
  "accessPolicyResource": {
    "portal": {
      "id": "string"
    },
    "project": {
      "id": "string"
    }
  },
  "clientToken": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[accessPolicyIdentity](#)

The identity for this access policy. Choose an IAM Identity Center user, an IAM Identity Center group, or an IAM user.

Type: [Identity](#) object

Required: Yes

[accessPolicyPermission](#)

The permission level for this access policy. Note that a project ADMINISTRATOR is also known as a project owner.

Type: String

Valid Values: ADMINISTRATOR | VIEWER

Required: Yes

[accessPolicyResource](#)

The Amazon IoT SiteWise Monitor resource for this access policy. Choose either a portal or a project.

Type: [Resource](#) object

Required: Yes

[clientToken](#)

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

tags

A list of key-value pairs that contain metadata for the access policy. For more information, see [Tagging your Amazon IoT SiteWise resources](#) in the *Amazon IoT SiteWise User Guide*.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "accessPolicyArn": "string",
  "accessPolicyId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

[accessPolicyArn](#)

The [ARN](#) of the access policy, which has the following format.

```
arn:${Partition}:iotsitewise:${Region}:${Account}:access-policy/
${AccessPolicyId}
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

[accessPolicyId](#)

The ID of the access policy.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateAsset

Creates an asset from an existing asset model. For more information, see [Creating assets](#) in the *Amazon IoT SiteWise User Guide*.

Request Syntax

```
POST /assets HTTP/1.1
Content-type: application/json

{
  "assetDescription": "string",
  "assetExternalId": "string",
  "assetId": "string",
  "assetModelId": "string",
  "assetName": "string",
  "clientToken": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

assetDescription

A description for the asset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

assetExternalId

An external ID to assign to the asset. The external ID must be unique within your Amazon Web Services account. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

assetId

The ID to assign to the asset, if desired. Amazon IoT SiteWise automatically generates a unique ID for you, so this parameter is never required. However, if you prefer to supply your own ID instead, you can specify it here in UUID format. If you specify your own ID, it must be globally unique.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

assetModelId

The ID of the asset model from which to create the asset. This can be either the actual ID in UUID format, or else `externalId:` followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|
^externalId:[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: Yes

assetName

A friendly name for the asset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

tags

A list of key-value pairs that contain metadata for the asset. For more information, see [Tagging your Amazon IoT SiteWise resources](#) in the *Amazon IoT SiteWise User Guide*.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 202
```

Content-type: application/json

```
{
  "assetArn": "string",
  "assetId": "string",
  "assetStatus": {
    "error": {
      "code": "string",
      "details": [
        {
          "code": "string",
          "message": "string"
        }
      ],
      "message": "string"
    },
    "state": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

assetArn

The [ARN](#) of the asset, which has the following format.

```
arn:${Partition}:iotsitewise:${Region}:${Account}:asset/${AssetId}
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: ^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+\$

assetId

The ID of the asset, in UUID format. This ID uniquely identifies the asset within Amazon IoT SiteWise and can be used with other Amazon IoT SiteWise API operations.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

assetStatus

The status of the asset, which contains a state (CREATING after successfully calling this operation) and any error message.

Type: [AssetStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceAlreadyExistsException

The resource already exists.

HTTP Status Code: 409

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateAssetModel

Creates an asset model from specified property and hierarchy definitions. You create assets from asset models. With asset models, you can easily create assets of the same type that have standardized definitions. Each asset created from a model inherits the asset model's property and hierarchy definitions. For more information, see [Defining asset models](#) in the *Amazon IoT SiteWise User Guide*.

You can create two types of asset models, ASSET_MODEL or COMPONENT_MODEL.

- **ASSET_MODEL** – (default) An asset model that you can use to create assets. Can't be included as a component in another asset model.
- **COMPONENT_MODEL** – A reusable component that you can include in the composite models of other asset models. You can't create assets directly from this type of asset model.

Request Syntax

```
POST /asset-models HTTP/1.1
Content-type: application/json
```

```
{
  "assetModelCompositeModels": [
    {
      "description": "string",
      "externalId": "string",
      "id": "string",
      "name": "string",
      "properties": [
        {
          "dataType": "string",
          "dataTypeSpec": "string",
          "externalId": "string",
          "id": "string",
          "name": "string",
          "type": {
            "attribute": {
              "defaultValue": "string"
            },
            "measurement": {
              "processingConfig": {
```

```
        "forwardingConfig": {
            "state": "string"
        }
    },
    "metric": {
        "expression": "string",
        "processingConfig": {
            "computeLocation": "string"
        },
        "variables": [
            {
                "name": "string",
                "value": {
                    "hierarchyId": "string",
                    "propertyId": "string",
                    "propertyPath": [
                        {
                            "id": "string",
                            "name": "string"
                        }
                    ]
                }
            }
        ]
    },
    "window": {
        "tumbling": {
            "interval": "string",
            "offset": "string"
        }
    },
    "transform": {
        "expression": "string",
        "processingConfig": {
            "computeLocation": "string",
            "forwardingConfig": {
                "state": "string"
            }
        },
        "variables": [
            {
                "name": "string",
                "value": {
```

```

        "hierarchyId": "string",
        "propertyId": "string",
        "propertyPath": [
            {
                "id": "string",
                "name": "string"
            }
        ]
    },
    ],
    "unit": "string"
}
],
"type": "string"
}
],
"assetModelDescription": "string",
"assetModelExternalId": "string",
"assetModelHierarchies": [
    {
        "childAssetModelId": "string",
        "externalId": "string",
        "id": "string",
        "name": "string"
    }
],
"assetModelId": "string",
"assetModelName": "string",
"assetModelProperties": [
    {
        "dataType": "string",
        "dataTypeSpec": "string",
        "externalId": "string",
        "id": "string",
        "name": "string",
        "type": {
            "attribute": {
                "defaultValue": "string"
            },
            "measurement": {
                "processingConfig": {

```



```
        "forwardingConfig": {
            "state": "string"
        }
    },
    "metric": {
        "expression": "string",
        "processingConfig": {
            "computeLocation": "string"
        },
        "variables": [
            {
                "name": "string",
                "value": {
                    "hierarchyId": "string",
                    "propertyId": "string",
                    "propertyPath": [
                        {
                            "id": "string",
                            "name": "string"
                        }
                    ]
                }
            }
        ],
        "window": {
            "tumbling": {
                "interval": "string",
                "offset": "string"
            }
        }
    },
    "transform": {
        "expression": "string",
        "processingConfig": {
            "computeLocation": "string",
            "forwardingConfig": {
                "state": "string"
            }
        },
        "variables": [
            {
                "name": "string",
                "value": {
```

```
    "hierarchyId": "string",
    "propertyId": "string",
    "propertyPath": [
      {
        "id": "string",
        "name": "string"
      }
    ]
  },
  "unit": "string"
},
"assetModelType": "string",
"clientToken": "string",
"tags": {
  "string" : "string"
}
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[assetModelCompositeModels](#)

The composite models that are part of this asset model. It groups properties (such as attributes, measurements, transforms, and metrics) and child composite models that model parts of your industrial equipment. Each composite model has a type that defines the properties that the composite model supports. Use composite models to define alarms on this asset model.

Note

When creating custom composite models, you need to use [CreateAssetModelCompositeModel](#). For more information, see [Creating custom composite models \(Components\)](#) in the *Amazon IoT SiteWise User Guide*.

Type: Array of [AssetModelCompositeModelDefinition](#) objects

Required: No

[assetModelDescription](#)

A description for the asset model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

[assetModelExternalId](#)

An external ID to assign to the asset model. The external ID must be unique within your Amazon Web Services account. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

[assetModelHierarchies](#)

The hierarchy definitions of the asset model. Each hierarchy specifies an asset model whose assets can be children of any other assets created from this asset model. For more information, see [Asset hierarchies](#) in the *Amazon IoT SiteWise User Guide*.

You can specify up to 10 hierarchies per asset model. For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

Type: Array of [AssetModelHierarchyDefinition](#) objects

Required: No

[assetModelId](#)

The ID to assign to the asset model, if desired. Amazon IoT SiteWise automatically generates a unique ID for you, so this parameter is never required. However, if you prefer to supply your own ID instead, you can specify it here in UUID format. If you specify your own ID, it must be globally unique.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

[assetModelName](#)

A unique name for the asset model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

[assetModelProperties](#)

The property definitions of the asset model. For more information, see [Asset properties](#) in the *Amazon IoT SiteWise User Guide*.

You can specify up to 200 properties per asset model. For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

Type: Array of [AssetModelPropertyDefinition](#) objects

Required: No

[assetModelType](#)

The type of asset model.

- **ASSET_MODEL** – (default) An asset model that you can use to create assets. Can't be included as a component in another asset model.
- **COMPONENT_MODEL** – A reusable component that you can include in the composite models of other asset models. You can't create assets directly from this type of asset model.

Type: String

Valid Values: ASSET_MODEL | COMPONENT_MODEL

Required: No

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

tags

A list of key-value pairs that contain metadata for the asset model. For more information, see [Tagging your Amazon IoT SiteWise resources](#) in the *Amazon IoT SiteWise User Guide*.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 202
Content-type: application/json
```

```
{
  "assetModelArn": "string",
  "assetModelId": "string",
  "assetModelStatus": {
    "error": {
      "code": "string",
      "details": [
        {
          "code": "string",
          "message": "string"
        }
      ],
      "message": "string"
    },
    "state": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

assetModelArn

The [ARN](#) of the asset model, which has the following format.

```
arn:${Partition}:iotsitewise:${Region}:${Account}:asset-model/
${AssetModelId}
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: ^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+\$

assetModelId

The ID of the asset model, in UUID format. You can use this ID when you call other Amazon IoT SiteWise API operations.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

assetModelStatus

The status of the asset model, which contains a state (CREATING after successfully calling this operation) and any error message.

Type: [AssetModelStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceAlreadyExistsException

The resource already exists.

HTTP Status Code: 409

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateAssetModelCompositeModel

Creates a custom composite model from specified property and hierarchy definitions. There are two types of custom composite models, `inline` and `component-model-based`.

Use `component-model-based` custom composite models to define standard, reusable components. A `component-model-based` custom composite model consists of a name, a description, and the ID of the component model it references. A `component-model-based` custom composite model has no properties of its own; its referenced component model provides its associated properties to any created assets. For more information, see [Custom composite models \(Components\)](#) in the *Amazon IoT SiteWise User Guide*.

Use `inline` custom composite models to organize the properties of an asset model. The properties of `inline` custom composite models are local to the asset model where they are included and can't be used to create multiple assets.

To create a `component-model-based` model, specify the `composedAssetModelId` of an existing asset model with `assetModelType` of `COMPONENT_MODEL`.

To create an `inline` model, specify the `assetModelCompositeModelProperties` and don't include an `composedAssetModelId`.

Request Syntax

```
POST /asset-models/assetModelId/composite-models HTTP/1.1
```

```
If-Match: ifMatch
```

```
If-None-Match: ifNoneMatch
```

```
Match-For-Version-Type: matchForVersionType
```

```
Content-type: application/json
```

```
{
  "assetModelCompositeModelDescription": "string",
  "assetModelCompositeModelExternalId": "string",
  "assetModelCompositeModelId": "string",
  "assetModelCompositeModelName": "string",
  "assetModelCompositeModelProperties": [
    {
      "dataType": "string",
      "dataTypeSpec": "string",
      "externalId": "string",
      "id": "string",

```

```
"name": "string",
"type": {
  "attribute": {
    "defaultValue": "string"
  },
  "measurement": {
    "processingConfig": {
      "forwardingConfig": {
        "state": "string"
      }
    }
  },
  "metric": {
    "expression": "string",
    "processingConfig": {
      "computeLocation": "string"
    },
    "variables": [
      {
        "name": "string",
        "value": {
          "hierarchyId": "string",
          "propertyId": "string",
          "propertyPath": [
            {
              "id": "string",
              "name": "string"
            }
          ]
        }
      }
    ]
  },
  "window": {
    "tumbling": {
      "interval": "string",
      "offset": "string"
    }
  }
},
"transform": {
  "expression": "string",
  "processingConfig": {
    "computeLocation": "string",
    "forwardingConfig": {
```

```

        "state": "string"
    }
},
"variables": [
    {
        "name": "string",
        "value": {
            "hierarchyId": "string",
            "propertyId": "string",
            "propertyPath": [
                {
                    "id": "string",
                    "name": "string"
                }
            ]
        }
    }
]
},
"unit": "string"
}
],
"assetModelCompositeModelType": "string",
"clientToken": "string",
"composedAssetModelId": "string",
"parentAssetModelCompositeModelId": "string"
}

```

URI Request Parameters

The request uses the following URI parameters.

assetModelId

The ID of the asset model this composite model is a part of.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|`

`^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

ifMatch

The expected current entity tag (ETag) for the asset model's latest or active version (specified using `matchForVersionType`). The create request is rejected if the tag does not match the latest or active version's current entity tag. See [Optimistic locking for asset model writes](#) in the *Amazon IoT SiteWise User Guide*.

Pattern: `^\[\w-\]{43}$`

ifNoneMatch

Accepts `*` to reject the create request if an active version (specified using `matchForVersionType` as `ACTIVE`) already exists for the asset model.

Pattern: `*`

matchForVersionType

Specifies the asset model version type (`LATEST` or `ACTIVE`) used in conjunction with `If-Match` or `If-None-Match` headers to determine the target ETag for the create operation.

Valid Values: `LATEST` | `ACTIVE`

Request Body

The request accepts the following data in JSON format.

assetModelCompositeModelDescription

A description for the composite model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

assetModelCompositeModelExternalId

An external ID to assign to the composite model.

If the composite model is a derived composite model, or one nested inside a component model, you can only set the external ID using `UpdateAssetModelCompositeModel` and specifying the derived ID of the model or property from the created model it's a part of.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9. :]*[a-zA-Z0-9_]+`

Required: No

[assetModelCompositeModelId](#)

The ID of the composite model. Amazon IoT SiteWise automatically generates a unique ID for you, so this parameter is never required. However, if you prefer to supply your own ID instead, you can specify it here in UUID format. If you specify your own ID, it must be globally unique.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

[assetModelCompositeModelName](#)

A unique name for the composite model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

[assetModelCompositeModelProperties](#)

The property definitions of the composite model. For more information, see [Inline custom composite models](#) in the *Amazon IoT SiteWise User Guide*.

You can specify up to 200 properties per composite model. For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

Type: Array of [AssetModelPropertyDefinition](#) objects

Required: No

[assetModelCompositeModelType](#)

The composite model type. Valid values are AWS/ALARM, CUSTOM, or AWS/L4E_ANOMALY.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

[clientToken](#)

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

[composedAssetModelId](#)

The ID of a component model which is reused to create this composite model.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$ | ^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: No

[parentAssetModelCompositeModelId](#)

The ID of the parent composite model in this asset model relationship.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: No

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "assetModelCompositeModelId": "string",
  "assetModelCompositeModelPath": [
    {
      "id": "string",
      "name": "string"
    }
  ],
  "assetModelStatus": {
    "error": {
      "code": "string",
      "details": [
        {
          "code": "string",
          "message": "string"
        }
      ],
      "message": "string"
    },
    "state": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

assetModelCompositeModelId

The ID of the composed asset model. You can use this ID when you call other Amazon IoT SiteWise APIs.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

assetModelCompositeModelPath

The path to the composite model listing the parent composite models.

Type: Array of [AssetModelCompositeModelPathSegment](#) objects

assetModelStatus

Contains current status information for an asset model. For more information, see [Asset and model states](#) in the *Amazon IoT SiteWise User Guide*.

Type: [AssetModelStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

PreconditionFailedException

The precondition in one or more of the request-header fields evaluated to FALSE.

HTTP Status Code: 412

ResourceAlreadyExistsException

The resource already exists.

HTTP Status Code: 409

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateBulkImportJob

Defines a job to ingest data to Amazon IoT SiteWise from Amazon S3. For more information, see [Create a bulk import job \(Amazon CLI\)](#) in the *Amazon Simple Storage Service User Guide*.

Important

Before you create a bulk import job, you must enable Amazon IoT SiteWise warm tier or Amazon IoT SiteWise cold tier. For more information about how to configure storage settings, see [PutStorageConfiguration](#).

Bulk import is designed to store historical data to Amazon IoT SiteWise. It does not trigger computations or notifications on Amazon IoT SiteWise warm or cold tier storage.

Request Syntax

```
POST /jobs HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "adaptiveIngestion": boolean,
  "deleteFilesAfterImport": boolean,
  "errorReportLocation": {
    "bucket": "string",
    "prefix": "string"
  },
  "files": [
    {
      "bucket": "string",
      "key": "string",
      "versionId": "string"
    }
  ],
  "jobConfiguration": {
    "fileFormat": {
      "csv": {
        "columnNames": [ "string" ]
      },
      "parquet": {
      }
    }
  }
}
```

```
},  
  "jobName": "string",  
  "jobRoleArn": "string"  
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

adaptiveIngestion

If set to true, ingest new data into Amazon IoT SiteWise storage. Measurements with notifications, metrics and transforms are computed. If set to false, historical data is ingested into Amazon IoT SiteWise as is.

Type: Boolean

Required: No

deleteFilesAfterImport

If set to true, your data files is deleted from S3, after ingestion into Amazon IoT SiteWise storage.

Type: Boolean

Required: No

errorReportLocation

The Amazon S3 destination where errors associated with the job creation request are saved.

Type: [ErrorReportLocation](#) object

Required: Yes

files

The files in the specified Amazon S3 bucket that contain your data.

Type: Array of [File](#) objects

Required: Yes

[jobConfiguration](#)

Contains the configuration information of a job, such as the file format used to save data in Amazon S3.

Type: [JobConfiguration](#) object

Required: Yes

[jobName](#)

The unique name that helps identify the job request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

[jobRoleArn](#)

The [ARN](#) of the IAM role that allows Amazon IoT SiteWise to read Amazon S3 data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

Required: Yes

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "jobId": "string",
```

```
"jobName": "string",  
"jobStatus": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

jobId

The ID of the job.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

jobName

The unique name that helps identify the job request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

jobStatus

The status of the bulk import job can be one of following values:

- PENDING – Amazon IoT SiteWise is waiting for the current bulk import job to finish.
- CANCELLED – The bulk import job has been canceled.
- RUNNING – Amazon IoT SiteWise is processing your request to import your data from Amazon S3.
- COMPLETED – Amazon IoT SiteWise successfully completed your request to import data from Amazon S3.
- FAILED – Amazon IoT SiteWise couldn't process your request to import data from Amazon S3. You can use logs saved in the specified error report location in Amazon S3 to troubleshoot issues.

- `COMPLETED_WITH_FAILURES` – Amazon IoT SiteWise completed your request to import data from Amazon S3 with errors. You can use logs saved in the specified error report location in Amazon S3 to troubleshoot issues.

Type: String

Valid Values: `PENDING` | `CANCELLED` | `RUNNING` | `COMPLETED` | `FAILED` | `COMPLETED_WITH_FAILURES`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceAlreadyExistsException

The resource already exists.

HTTP Status Code: 409

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateDashboard

Creates a dashboard in an Amazon IoT SiteWise Monitor project.

Request Syntax

```
POST /dashboards HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "dashboardDefinition": "string",
  "dashboardDescription": "string",
  "dashboardName": "string",
  "projectId": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

dashboardDefinition

The dashboard definition specified in a JSON literal.

- Amazon IoT SiteWise Monitor (Classic) see [Create dashboards \(Amazon CLI\)](#)
- Amazon IoT SiteWise Monitor (AI-aware) see [Create dashboards \(Amazon CLI\)](#)

in the *Amazon IoT SiteWise User Guide*

Type: String

Length Constraints: Minimum length of 0. Maximum length of 204800.

Pattern: .+

Required: Yes

dashboardDescription

A description for the dashboard.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [^\u0000-\u001F\u007F]+

Required: No

dashboardName

A friendly name for the dashboard.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [^\u0000-\u001F\u007F]+

Required: Yes

projectId

The ID of the project in which to create the dashboard.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

tags

A list of key-value pairs that contain metadata for the dashboard. For more information, see [Tagging your Amazon IoT SiteWise resources](#) in the *Amazon IoT SiteWise User Guide*.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "dashboardArn": "string",
  "dashboardId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

dashboardArn

The [ARN](#) of the dashboard, which has the following format.

```
arn:${Partition}:iotsitewise:${Region}:${Account}:dashboard/  
${DashboardId}
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

dashboardId

The ID of the dashboard.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateDataset

Creates a dataset to connect an external datasource.

Request Syntax

```
POST /datasets HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "datasetDescription": "string",
  "datasetId": "string",
  "datasetName": "string",
  "datasetSource": {
    "sourceDetail": {
      "kendra": {
        "knowledgeBaseArn": "string",
        "roleArn": "string"
      }
    },
    "sourceFormat": "string",
    "sourceType": "string"
  },
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

datasetDescription

A description about the dataset, and its functionality.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9 _\-#$$*!@]+`

Required: No

datasetId

The ID of the dataset.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: No

datasetName

The name of the dataset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^[a-zA-Z0-9 _\-#$$*!@]+`

Required: Yes

datasetSource

The data source for the dataset.

Type: [DatasetSource](#) object

Required: Yes

tags

A list of key-value pairs that contain metadata for the access policy. For more information, see [Tagging your Amazon IoT SiteWise resources](#) in the *Amazon IoT SiteWise User Guide*.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "datasetArn": "string",
  "datasetId": "string",
  "datasetStatus": {
    "error": {
      "code": "string",
      "details": [
        {
          "code": "string",
          "message": "string"
        }
      ],
      "message": "string"
    }
  },
  "message": "string"
},
```



```
    "state": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

datasetArn

The [ARN](#) of the dataset. The format is `arn:${Partition}:iotsitewise:${Region}:${Account}:dataset/${DatasetId}`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+`

datasetId

The ID of the dataset.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

datasetStatus

The status of the dataset. This contains the state and any error messages. State is `CREATING` after a successful call to this API, and any associated error message. The state is `ACTIVE` when ready to use.

Type: [DatasetStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceAlreadyExistsException

The resource already exists.

HTTP Status Code: 409

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateGateway

Creates a gateway, which is a virtual or edge device that delivers industrial data streams from local servers to Amazon IoT SiteWise. For more information, see [Ingesting data using a gateway](#) in the *Amazon IoT SiteWise User Guide*.

Request Syntax

```
POST /20200301/gateways HTTP/1.1
Content-type: application/json

{
  "gatewayName": "string",
  "gatewayPlatform": {
    "greengrass": {
      "groupArn": "string"
    },
    "greengrassV2": {
      "coreDeviceOperatingSystem": "string",
      "coreDeviceThingName": "string"
    },
    "siemensIE": {
      "iotCoreThingName": "string"
    }
  },
  "gatewayVersion": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

gatewayName

A unique name for the gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

gatewayPlatform

The gateway's platform. You can only specify one platform in a gateway.

Type: [GatewayPlatform](#) object

Required: Yes

gatewayVersion

The version of the gateway to create. Specify 3 to create an MQTT-enabled, V3 gateway and 2 To create a Classic streams, V2 gateway. If the version isn't specified, a Classic streams, V2 gateway is created by default.

We recommend creating an MQTT-enabled, V3 gateway for self-hosted gateways. SiteWise Edge gateways on Siemens Industrial Edge should use gateway version 2. For more information on gateway versions, see [Self-host a SiteWise Edge gateway with Amazon IoT Greengrass V2](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^[0-9]+$`

Required: No

tags

A list of key-value pairs that contain metadata for the gateway. For more information, see [Tagging your Amazon IoT SiteWise resources](#) in the *Amazon IoT SiteWise User Guide*.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "gatewayArn": "string",
  "gatewayId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

[gatewayArn](#)

The [ARN](#) of the gateway, which has the following format.

```
arn:${Partition}:iotsitewise:${Region}:${Account}:gateway/${GatewayId}
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+`

[gatewayId](#)

The ID of the gateway device. You can use this ID when you call other Amazon IoT SiteWise API operations.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceAlreadyExistsException

The resource already exists.

HTTP Status Code: 409

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreatePortal

Creates a portal, which can contain projects and dashboards. Amazon IoT SiteWise Monitor uses IAM Identity Center or IAM to authenticate portal users and manage user permissions.

Note

Before you can sign in to a new portal, you must add at least one identity to that portal. For more information, see [Adding or removing portal administrators](#) in the *Amazon IoT SiteWise User Guide*.

Request Syntax

```
POST /portals HTTP/1.1
Content-type: application/json

{
  "alarms": {
    "alarmRoleArn": "string",
    "notificationLambdaArn": "string"
  },
  "clientToken": "string",
  "notificationSenderEmail": "string",
  "portalAuthMode": "string",
  "portalContactEmail": "string",
  "portalDescription": "string",
  "portalLogoImageFile": {
    "data": blob,
    "type": "string"
  },
  "portalName": "string",
  "portalType": "string",
  "portalTypeConfiguration": {
    "string" : {
      "portalTools": [ "string" ]
    }
  },
  "roleArn": "string",
  "tags": {
    "string" : "string"
  }
}
```

```
}  
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

alarms

Contains the configuration information of an alarm created in an Amazon IoT SiteWise Monitor portal. You can use the alarm to monitor an asset property and get notified when the asset property value is outside a specified range. For more information, see [Monitoring with alarms](#) in the *Amazon IoT SiteWise Application Guide*.

Type: [Alarms](#) object

Required: No

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

notificationSenderEmail

The email address that sends alarm notifications.

Important

If you use the [Amazon IoT Events managed Lambda function](#) to manage your emails, you must [verify the sender email address in Amazon SES](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9_\-\.\\+]+@[a-zA-Z0-9_\-\.\\+]+\.[a-zA-Z]{2,}$`

Required: No

portalAuthMode

The service to use to authenticate users to the portal. Choose from the following options:

- **SSO** – The portal uses Amazon IAM Identity Center to authenticate users and manage user permissions. Before you can create a portal that uses IAM Identity Center, you must enable IAM Identity Center. For more information, see [Enabling IAM Identity Center](#) in the *Amazon IoT SiteWise User Guide*. This option is only available in Amazon Regions other than the China Regions.
- **IAM** – The portal uses Amazon Identity and Access Management to authenticate users and manage user permissions.

You can't change this value after you create a portal.

Default: SSO

Type: String

Valid Values: IAM | SSO

Required: No

portalContactEmail

The Amazon administrator's contact email address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9_\-\.\\+]+@[a-zA-Z0-9_\-\.\\+]+\.[a-zA-Z]{2,}$`

Required: Yes

portalDescription

A description for the portal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

portalLogoImageFile

A logo image to display in the portal. Upload a square, high-resolution image. The image is displayed on a dark background.

Type: [ImageFile](#) object

Required: No

portalName

A friendly name for the portal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

portalType

Define the type of portal. The value for Amazon IoT SiteWise Monitor (Classic) is `SITWISE_PORTAL_V1`. The value for Amazon IoT SiteWise Monitor (AI-aware) is `SITWISE_PORTAL_V2`.

Type: String

Valid Values: `SITWISE_PORTAL_V1` | `SITWISE_PORTAL_V2`

Required: No

portalTypeConfiguration

The configuration entry associated with the specific portal type. The value for Amazon IoT SiteWise Monitor (Classic) is `SITWISE_PORTAL_V1`. The value for Amazon IoT SiteWise Monitor (AI-aware) is `SITWISE_PORTAL_V2`.

Type: String to [PortalTypeEntry](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

[roleArn](#)

The [ARN](#) of a service role that allows the portal's users to access your Amazon IoT SiteWise resources on your behalf. For more information, see [Using service roles for Amazon IoT SiteWise Monitor](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.\\+=, @]+$`

Required: Yes

[tags](#)

A list of key-value pairs that contain metadata for the portal. For more information, see [Tagging your Amazon IoT SiteWise resources](#) in the *Amazon IoT SiteWise User Guide*.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "portalArn": "string",
  "portalId": "string",
```

```
"portalStartUrl": "string",
"portalStatus": {
  "error": {
    "code": "string",
    "message": "string"
  },
  "state": "string"
},
"ssoApplicationId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

portalArn

The [ARN](#) of the portal, which has the following format.

```
arn:${Partition}:iotsitewise:${Region}:${Account}:portal/${PortalId}
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

portalId

The ID of the created portal.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

portalStartUrl

The URL for the Amazon IoT SiteWise Monitor portal. You can use this URL to access portals that use IAM Identity Center for authentication. For portals that use IAM for authentication, you must use the Amazon IoT SiteWise console to get a URL that you can use to access the portal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^(http|https)\:\/\S+`

portalStatus

The status of the portal, which contains a state (CREATING after successfully calling this operation) and any error message.

Type: [PortalStatus](#) object

ssoApplicationId

The associated IAM Identity Center application ID, if the portal uses IAM Identity Center.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[!-~]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateProject

Creates a project in the specified portal.

Note

Make sure that the project name and description don't contain confidential information.

Request Syntax

```
POST /projects HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "portalId": "string",
  "projectDescription": "string",
  "projectName": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

portalId

The ID of the portal in which to create the project.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

projectDescription

A description for the project.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

projectName

A friendly name for the project.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

tags

A list of key-value pairs that contain metadata for the project. For more information, see [Tagging your Amazon IoT SiteWise resources](#) in the *Amazon IoT SiteWise User Guide*.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "projectArn": "string",
  "projectId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

projectArn

The [ARN](#) of the project, which has the following format.

arn:\${Partition}:iotsitewise:\${Region}:\${Account}:project/\${ProjectId}

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: ^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+\$

projectId

The ID of the project.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteAccessPolicy

Deletes an access policy that grants the specified identity access to the specified Amazon IoT SiteWise Monitor resource. You can use this operation to revoke access to an Amazon IoT SiteWise Monitor resource.

Request Syntax

```
DELETE /access-policies/accessPolicyId?clientToken=clientToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

accessPolicyId

The ID of the access policy to be deleted.

Length Constraints: Fixed length of 36.

Pattern: $^{[0-9a-f]\{8\}-[0-9a-f]\{4\}-[0-9a-f]\{4\}-[0-9a-f]\{4\}-[0-9a-f]\{12\}}\$$

Required: Yes

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: $\backslash S\{36,64\}$

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteAsset

Deletes an asset. This action can't be undone. For more information, see [Deleting assets and models](#) in the *Amazon IoT SiteWise User Guide*.

Note

You can't delete an asset that's associated to another asset. For more information, see [DisassociateAssets](#).

Request Syntax

```
DELETE /assets/assetId?clientToken=clientToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

assetId

The ID of the asset to delete. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|
^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.]*[a-zA-Z0-9]+`

Required: Yes

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "assetStatus": {
    "error": {
      "code": "string",
      "details": [
        {
          "code": "string",
          "message": "string"
        }
      ],
      "message": "string"
    },
    "state": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

assetStatus

The status of the asset, which contains a state (DELETING after successfully calling this operation) and any error message.

Type: [AssetStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)

- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteAssetModel

Deletes an asset model. This action can't be undone. You must delete all assets created from an asset model before you can delete the model. Also, you can't delete an asset model if a parent asset model exists that contains a property formula expression that depends on the asset model that you want to delete. For more information, see [Deleting assets and models](#) in the *Amazon IoT SiteWise User Guide*.

Request Syntax

```
DELETE /asset-models/assetModelId?clientToken=clientToken HTTP/1.1  
If-Match: ifMatch  
If-None-Match: ifNoneMatch  
Match-For-Version-Type: matchForVersionType
```

URI Request Parameters

The request uses the following URI parameters.

[assetModelId](#)

The ID of the asset model to delete. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|
^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.]*[a-zA-Z0-9]+`

Required: Yes

[clientToken](#)

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

ifMatch

The expected current entity tag (ETag) for the asset model's latest or active version (specified using `matchForVersionType`). The delete request is rejected if the tag does not match the latest or active version's current entity tag. See [Optimistic locking for asset model writes](#) in the *Amazon IoT SiteWise User Guide*.

Pattern: `^\[\w-\]{43}$`

ifNoneMatch

Accepts `*` to reject the delete request if an active version (specified using `matchForVersionType` as `ACTIVE`) already exists for the asset model.

Pattern: `*`

matchForVersionType

Specifies the asset model version type (`LATEST` or `ACTIVE`) used in conjunction with `If-Match` or `If-None-Match` headers to determine the target ETag for the delete operation.

Valid Values: `LATEST` | `ACTIVE`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "assetModelStatus": {
    "error": {
      "code": "string",
      "details": [
        {
          "code": "string",
          "message": "string"
        }
      ]
    }
  },
}
```

```
    "message": "string"  
  },  
  "state": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

assetModelStatus

The status of the asset model, which contains a state (DELETING after successfully calling this operation) and any error message.

Type: [AssetModelStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

PreconditionFailedException

The precondition in one or more of the request-header fields evaluated to FALSE.

HTTP Status Code: 412

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteAssetModelCompositeModel

Deletes a composite model. This action can't be undone. You must delete all assets created from a composite model before you can delete the model. Also, you can't delete a composite model if a parent asset model exists that contains a property formula expression that depends on the asset model that you want to delete. For more information, see [Deleting assets and models](#) in the *Amazon IoT SiteWise User Guide*.

Request Syntax

```
DELETE /asset-models/assetModelId/composite-models/assetModelCompositeModelId?
clientToken=clientToken HTTP/1.1
If-Match: ifMatch
If-None-Match: ifNoneMatch
Match-For-Version-Type: matchForVersionType
```

URI Request Parameters

The request uses the following URI parameters.

[assetModelCompositeModelId](#)

The ID of a composite model on this asset model.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$ | ^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

[assetModelId](#)

The ID of the asset model, in UUID format.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$ | ^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

ifMatch

The expected current entity tag (ETag) for the asset model's latest or active version (specified using `matchForVersionType`). The delete request is rejected if the tag does not match the latest or active version's current entity tag. See [Optimistic locking for asset model writes](#) in the *Amazon IoT SiteWise User Guide*.

Pattern: `^\[\w-\]{43}$`

ifNoneMatch

Accepts `*` to reject the delete request if an active version (specified using `matchForVersionType` as `ACTIVE`) already exists for the asset model.

Pattern: `*`

matchForVersionType

Specifies the asset model version type (`LATEST` or `ACTIVE`) used in conjunction with `If-Match` or `If-None-Match` headers to determine the target ETag for the delete operation.

Valid Values: `LATEST` | `ACTIVE`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
```

```
"assetModelStatus": {
  "error": {
    "code": "string",
    "details": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "message": "string"
  },
  "state": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

assetModelStatus

Contains current status information for an asset model. For more information, see [Asset and model states](#) in the *Amazon IoT SiteWise User Guide*.

Type: [AssetModelStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

PreconditionFailedException

The precondition in one or more of the request-header fields evaluated to FALSE.

HTTP Status Code: 412

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteDashboard

Deletes a dashboard from Amazon IoT SiteWise Monitor.

Request Syntax

```
DELETE /dashboards/dashboardId?clientToken=clientToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: $\backslash S\{36, 64\}$

dashboardId

The ID of the dashboard to delete.

Length Constraints: Fixed length of 36.

Pattern: $^{\wedge}[0-9a-f]\{8\}-[0-9a-f]\{4\}-[0-9a-f]\{4\}-[0-9a-f]\{4\}-[0-9a-f]\{12\}\$$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteDataset

Deletes a dataset. This cannot be undone.

Request Syntax

```
DELETE /datasets/datasetId?clientToken=clientToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

datasetId

The ID of the dataset.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 202  
Content-type: application/json
```

```
{
  "datasetStatus": {
    "error": {
      "code": "string",
      "details": [
        {
          "code": "string",
          "message": "string"
        }
      ],
      "message": "string"
    },
    "state": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

datasetStatus

The status of the dataset. This contains the state and any error messages. State is DELETING after a successful call to this API, and any associated error message.

Type: [DatasetStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteGateway

Deletes a gateway from Amazon IoT SiteWise. When you delete a gateway, some of the gateway's files remain in your gateway's file system.

Request Syntax

```
DELETE /20200301/gateways/gatewayId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

gatewayId

The ID of the gateway to delete.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)

- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeletePortal

Deletes a portal from Amazon IoT SiteWise Monitor.

Request Syntax

```
DELETE /portals/portalId?clientToken=clientToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

portalId

The ID of the portal to delete.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
```



```
"portalStatus": {
  "error": {
    "code": "string",
    "message": "string"
  },
  "state": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

portalStatus

The status of the portal, which contains a state (DELETING after successfully calling this operation) and any error message.

Type: [PortalStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteProject

Deletes a project from Amazon IoT SiteWise Monitor.

Request Syntax

```
DELETE /projects/projectId?clientToken=clientToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

projectId

The ID of the project.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteTimeSeries

Deletes a time series (data stream). If you delete a time series that's associated with an asset property, the asset property still exists, but the time series will no longer be associated with this asset property.

To identify a time series, do one of the following:

- If the time series isn't associated with an asset property, specify the `alias` of the time series.
- If the time series is associated with an asset property, specify one of the following:
 - The `alias` of the time series.
 - The `assetId` and `propertyId` that identifies the asset property.

Request Syntax

```
POST /timeseries/delete/?alias=alias&assetId=assetId&propertyId=propertyId HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

alias

The alias that identifies the time series.

Length Constraints: Minimum length of 1.

Pattern: `[^\u0000-\u001F\u007F]+`

assetId

The ID of the asset in which the asset property was created. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

propertyId

The ID of the asset property. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Request Body

The request accepts the following data in JSON format.

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeAccessPolicy

Describes an access policy, which specifies an identity's access to an Amazon IoT SiteWise Monitor portal or project.

Request Syntax

```
GET /access-policies/accessPolicyId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[accessPolicyId](#)

The ID of the access policy.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "accessPolicyArn": "string",
  "accessPolicyCreationDate": number,
  "accessPolicyId": "string",
  "accessPolicyIdentity": {
    "group": {
      "id": "string"
    }
  },
}
```

```

    "iamRole": {
      "arn": "string"
    },
    "iamUser": {
      "arn": "string"
    },
    "user": {
      "id": "string"
    }
  },
  "accessPolicyLastUpdateDate": number,
  "accessPolicyPermission": "string",
  "accessPolicyResource": {
    "portal": {
      "id": "string"
    },
    "project": {
      "id": "string"
    }
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

accessPolicyArn

The [ARN](#) of the access policy, which has the following format.

```
arn:${Partition}:iotsitewise:${Region}:${Account}:access-policy/
${AccessPolicyId}
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: ^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+\$

accessPolicyCreationDate

The date the access policy was created, in Unix epoch time.

Type: Timestamp

[accessPolicyId](#)

The ID of the access policy.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

[accessPolicyIdentity](#)

The identity (IAM Identity Center user, IAM Identity Center group, or IAM user) to which this access policy applies.

Type: [Identity](#) object

[accessPolicyLastUpdateDate](#)

The date the access policy was last updated, in Unix epoch time.

Type: Timestamp

[accessPolicyPermission](#)

The access policy permission. Note that a project ADMINISTRATOR is also known as a project owner.

Type: String

Valid Values: ADMINISTRATOR | VIEWER

[accessPolicyResource](#)

The Amazon IoT SiteWise Monitor resource (portal or project) to which this access policy provides access.

Type: [Resource](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)

- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeAction

Retrieves information about an action.

Request Syntax

```
GET /actions/actionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

actionId

The ID of the action.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "actionDefinitionId": "string",
  "actionId": "string",
  "actionPayload": {
    "stringValue": "string"
  },
  "executionTime": number,
  "targetResource": {
    "assetId": "string"
  }
}
```

```
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

actionDefinitionId

The ID of the action definition.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

actionId

The ID of the action.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

actionPayload

The JSON payload of the action.

Type: [ActionPayload](#) object

executionTime

The time the action was executed.

Type: Timestamp

targetResource

The resource the action will be taken on.

Type: [TargetResource](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeAsset

Retrieves information about an asset.

Request Syntax

```
GET /assets/assetId?excludeProperties=excludeProperties HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

assetId

The ID of the asset. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|
^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.]*[a-zA-Z0-9]+`

Required: Yes

excludeProperties

Whether or not to exclude asset properties from the response.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "assetArn": "string",
  "assetCompositeModels": [
    {
```

```
"description": "string",
"externalId": "string",
"id": "string",
"name": "string",
"properties": [
  {
    "alias": "string",
    "dataType": "string",
    "dataTypeSpec": "string",
    "externalId": "string",
    "id": "string",
    "name": "string",
    "notification": {
      "state": "string",
      "topic": "string"
    },
    "path": [
      {
        "id": "string",
        "name": "string"
      }
    ],
    "unit": "string"
  }
],
"type": "string"
},
"assetCompositeModelSummaries": [
  {
    "description": "string",
    "externalId": "string",
    "id": "string",
    "name": "string",
    "path": [
      {
        "id": "string",
        "name": "string"
      }
    ],
    "type": "string"
  }
],
"assetCreationDate": number,
```

```
"assetDescription": "string",
"assetExternalId": "string",
"assetHierarchies": [
  {
    "externalId": "string",
    "id": "string",
    "name": "string"
  }
],
"assetId": "string",
"assetLastUpdateDate": number,
"assetModelId": "string",
"assetName": "string",
"assetProperties": [
  {
    "alias": "string",
    "dataType": "string",
    "dataTypeSpec": "string",
    "externalId": "string",
    "id": "string",
    "name": "string",
    "notification": {
      "state": "string",
      "topic": "string"
    },
    "path": [
      {
        "id": "string",
        "name": "string"
      }
    ],
    "unit": "string"
  }
],
"assetStatus": {
  "error": {
    "code": "string",
    "details": [
      {
        "code": "string",
        "message": "string"
      }
    ]
  },
  "message": "string"
}
```

```
    },  
    "state": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assetArn

The [ARN](#) of the asset, which has the following format.

```
arn:${Partition}:iotsitewise:${Region}:${Account}:asset/${AssetId}
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

assetCompositeModels

The composite models for the asset.

Type: Array of [AssetCompositeModel](#) objects

assetCompositeModelSummaries

The list of the immediate child custom composite model summaries for the asset.

Type: Array of [AssetCompositeModelSummary](#) objects

assetCreationDate

The date the asset was created, in Unix epoch time.

Type: Timestamp

assetDescription

A description for the asset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

assetExternalId

The external ID of the asset, if any.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

assetHierarchies

A list of asset hierarchies that each contain a `hierarchyId`. A hierarchy specifies allowed parent/child asset relationships.

Type: Array of [AssetHierarchy](#) objects

assetId

The ID of the asset, in UUID format.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

assetLastUpdateDate

The date the asset was last updated, in Unix epoch time.

Type: Timestamp

assetModelId

The ID of the asset model that was used to create the asset.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

assetName

The name of the asset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

assetProperties

The list of asset properties for the asset.

This object doesn't include properties that you define in composite models. You can find composite model properties in the `assetCompositeModels` object.

Type: Array of [AssetProperty](#) objects

assetStatus

The current status of the asset, which contains a state and any error message.

Type: [AssetStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeAssetCompositeModel

Retrieves information about an asset composite model (also known as an asset component). An `AssetCompositeModel` is an instance of an `AssetModelCompositeModel`. If you want to see information about the model this is based on, call [DescribeAssetModelCompositeModel](#).

Request Syntax

```
GET /assets/assetId/composite-models/assetCompositeModelId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[assetCompositeModelId](#)

The ID of a composite model on this asset. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$ | ^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.]*[a-zA-Z0-9]+`

Required: Yes

[assetId](#)

The ID of the asset. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$ | ^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.]*[a-zA-Z0-9]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "actionDefinitions": [
    {
      "actionDefinitionId": "string",
      "actionName": "string",
      "actionType": "string"
    }
  ],
  "assetCompositeModelDescription": "string",
  "assetCompositeModelExternalId": "string",
  "assetCompositeModelId": "string",
  "assetCompositeModelName": "string",
  "assetCompositeModelPath": [
    {
      "id": "string",
      "name": "string"
    }
  ],
  "assetCompositeModelProperties": [
    {
      "alias": "string",
      "dataType": "string",
      "dataTypeSpec": "string",
      "externalId": "string",
      "id": "string",
      "name": "string",
      "notification": {
        "state": "string",
        "topic": "string"
      },
      "path": [
        {
          "id": "string",
          "name": "string"
        }
      ]
    }
  ]
}
```

```
    }
  ],
  "unit": "string"
}
],
"assetCompositeModelSummaries": [
  {
    "description": "string",
    "externalId": "string",
    "id": "string",
    "name": "string",
    "path": [
      {
        "id": "string",
        "name": "string"
      }
    ],
    "type": "string"
  }
],
"assetCompositeModelType": "string",
"assetId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

actionDefinitions

The available actions for a composite model on this asset.

Type: Array of [ActionDefinition](#) objects

assetCompositeModelDescription

A description for the composite model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

[assetCompositeModelExternalId](#)

An external ID to assign to the asset model.

If the composite model is a component-based composite model, or one nested inside a component model, you can only set the external ID using `UpdateAssetModelCompositeModel` and specifying the derived ID of the model or property from the created model it's a part of.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

[assetCompositeModelId](#)

The ID of a composite model on this asset.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

[assetCompositeModelName](#)

The unique, friendly name for the composite model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

[assetCompositeModelPath](#)

The path to the composite model listing the parent composite models.

Type: Array of [AssetCompositeModelPathSegment](#) objects

[assetCompositeModelProperties](#)

The property definitions of the composite model that was used to create the asset.

Type: Array of [AssetProperty](#) objects

[assetCompositeModelSummaries](#)

The list of composite model summaries.

Type: Array of [AssetCompositeModelSummary](#) objects

[assetCompositeModelType](#)

The composite model type. Valid values are AWS/ALARM, CUSTOM, or AWS/L4E_ANOMALY.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

[assetId](#)

The ID of the asset, in UUID format. This ID uniquely identifies the asset within Amazon IoT SiteWise and can be used with other Amazon IoT SiteWise APIs.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeAssetModel

Retrieves information about an asset model.

Request Syntax

```
GET /asset-models/assetModelId?  
assetModelVersion=assetModelVersion&excludeProperties=excludeProperties HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

assetModelId

The ID of the asset model. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$ | ^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

assetModelVersion

The version alias that specifies the latest or active version of the asset model. The details are returned in the response. The default value is LATEST. See [Asset model versions](#) in the *Amazon IoT SiteWise User Guide*.

Pattern: `^(LATEST|ACTIVE)$`

excludeProperties

Whether or not to exclude asset model properties from the response.

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

ETag: *eTag*

Content-type: application/json

```
{
  "assetModelArn": "string",
  "assetModelCompositeModels": [
    {
      "description": "string",
      "externalId": "string",
      "id": "string",
      "name": "string",
      "properties": [
        {
          "dataType": "string",
          "dataTypeSpec": "string",
          "externalId": "string",
          "id": "string",
          "name": "string",
          "path": [
            {
              "id": "string",
              "name": "string"
            }
          ],
          "type": {
            "attribute": {
              "defaultValue": "string"
            },
            "measurement": {
              "processingConfig": {
                "forwardingConfig": {
                  "state": "string"
                }
              }
            },
            "metric": {
              "expression": "string",
              "processingConfig": {
                "computeLocation": "string"
              }
            }
          }
        }
      ]
    }
  ]
}
```

```
"variables": [
  {
    "name": "string",
    "value": {
      "hierarchyId": "string",
      "propertyId": "string",
      "propertyPath": [
        {
          "id": "string",
          "name": "string"
        }
      ]
    }
  }
],
"window": {
  "tumbling": {
    "interval": "string",
    "offset": "string"
  }
},
"transform": {
  "expression": "string",
  "processingConfig": {
    "computeLocation": "string",
    "forwardingConfig": {
      "state": "string"
    }
  }
},
"variables": [
  {
    "name": "string",
    "value": {
      "hierarchyId": "string",
      "propertyId": "string",
      "propertyPath": [
        {
          "id": "string",
          "name": "string"
        }
      ]
    }
  }
]
```

```

        ]
      }
    },
    "unit": "string"
  }
],
"type": "string"
}
],
"assetModelCompositeModelSummaries": [
  {
    "description": "string",
    "externalId": "string",
    "id": "string",
    "name": "string",
    "path": [
      {
        "id": "string",
        "name": "string"
      }
    ],
    "type": "string"
  }
],
"assetModelCreationDate": number,
"assetModelDescription": "string",
"assetModelExternalId": "string",
"assetModelHierarchies": [
  {
    "childAssetModelId": "string",
    "externalId": "string",
    "id": "string",
    "name": "string"
  }
],
"assetModelId": "string",
"assetModelLastUpdateDate": number,
"assetModelName": "string",
"assetModelProperties": [
  {
    "dataType": "string",
    "dataTypeSpec": "string",
    "externalId": "string",
    "id": "string",

```

```
"name": "string",
"path": [
  {
    "id": "string",
    "name": "string"
  }
],
"type": {
  "attribute": {
    "defaultValue": "string"
  },
  "measurement": {
    "processingConfig": {
      "forwardingConfig": {
        "state": "string"
      }
    }
  },
  "metric": {
    "expression": "string",
    "processingConfig": {
      "computeLocation": "string"
    },
    "variables": [
      {
        "name": "string",
        "value": {
          "hierarchyId": "string",
          "propertyId": "string",
          "propertyPath": [
            {
              "id": "string",
              "name": "string"
            }
          ]
        }
      }
    ]
  },
  "window": {
    "tumbling": {
      "interval": "string",
      "offset": "string"
    }
  }
}
```

```
    },
    "transform": {
      "expression": "string",
      "processingConfig": {
        "computeLocation": "string",
        "forwardingConfig": {
          "state": "string"
        }
      }
    },
    "variables": [
      {
        "name": "string",
        "value": {
          "hierarchyId": "string",
          "propertyId": "string",
          "propertyPath": [
            {
              "id": "string",
              "name": "string"
            }
          ]
        }
      }
    ]
  },
  "unit": "string"
}
],
"assetModelStatus": {
  "error": {
    "code": "string",
    "details": [
      {
        "code": "string",
        "message": "string"
      }
    ]
  },
  "message": "string"
},
"state": "string"
},
"assetModelType": "string",
"assetModelVersion": "string"
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The response returns the following HTTP headers.

eTag

The entity tag (ETag) is a hash of the retrieved version of the asset model. It's used to make concurrent updates safely to the resource. See [Optimistic locking for asset model writes](#) in the *Amazon IoT SiteWise User Guide*.

See [Optimistic locking for asset model writes](#) in the *Amazon IoT SiteWise User Guide*.

Pattern: `^[\w-]{43}$`

The following data is returned in JSON format by the service.

assetModelArn

The [ARN](#) of the asset model, which has the following format.

```
arn:${Partition}:iotsitewise:${Region}:${Account}:asset-model/  
${AssetModelId}
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

assetModelCompositeModels

The list of built-in composite models for the asset model, such as those with those of type AWS/ALARMS.

Type: Array of [AssetModelCompositeModel](#) objects

assetModelCompositeModelSummaries

The list of the immediate child custom composite model summaries for the asset model.

Type: Array of [AssetModelCompositeModelSummary](#) objects

[assetModelCreationDate](#)

The date the asset model was created, in Unix epoch time.

Type: Timestamp

[assetModelDescription](#)

The asset model's description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

[assetModelExternalId](#)

The external ID of the asset model, if any.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

[assetModelHierarchies](#)

A list of asset model hierarchies that each contain a `childAssetModelId` and a `hierarchyId` (named `id`). A hierarchy specifies allowed parent/child asset relationships for an asset model.

Type: Array of [AssetModelHierarchy](#) objects

[assetModelId](#)

The ID of the asset model, in UUID format.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

[assetModelLastUpdateDate](#)

The date the asset model was last updated, in Unix epoch time.

Type: Timestamp

assetModelName

The name of the asset model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

assetModelProperties

The list of asset properties for the asset model.

This object doesn't include properties that you define in composite models. You can find composite model properties in the `assetModelCompositeModels` object.

Type: Array of [AssetModelProperty](#) objects

assetModelStatus

The current status of the asset model, which contains a state and any error message.

Type: [AssetModelStatus](#) object

assetModelType

The type of asset model.

- **ASSET_MODEL** – (default) An asset model that you can use to create assets. Can't be included as a component in another asset model.
- **COMPONENT_MODEL** – A reusable component that you can include in the composite models of other asset models. You can't create assets directly from this type of asset model.

Type: String

Valid Values: ASSET_MODEL | COMPONENT_MODEL

assetModelVersion

The version of the asset model. See [Asset model versions](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: `^(0|([1-9]{1}\d*))$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeAssetModelCompositeModel

Retrieves information about an asset model composite model (also known as an asset model component). For more information, see [Custom composite models \(Components\)](#) in the *Amazon IoT SiteWise User Guide*.

Request Syntax

```
GET /asset-models/assetModelId/composite-models/assetModelCompositeModelId?  
assetModelVersion=assetModelVersion HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

assetModelCompositeModelId

The ID of a composite model on this asset model. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$ |
^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

assetModelId

The ID of the asset model. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$ |
^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

assetModelVersion

The version alias that specifies the latest or active version of the asset model. The details are returned in the response. The default value is LATEST. See [Asset model versions](#) in the *Amazon IoT SiteWise User Guide*.

Pattern: `^(LATEST|ACTIVE)$`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "actionDefinitions": [
    {
      "actionDefinitionId": "string",
      "actionName": "string",
      "actionType": "string"
    }
  ],
  "assetModelCompositeModelDescription": "string",
  "assetModelCompositeModelExternalId": "string",
  "assetModelCompositeModelId": "string",
  "assetModelCompositeModelName": "string",
  "assetModelCompositeModelPath": [
    {
      "id": "string",
      "name": "string"
    }
  ],
  "assetModelCompositeModelProperties": [
    {
      "dataType": "string",
      "dataTypeSpec": "string",
      "externalId": "string",
      "id": "string",
      "name": "string",
```

```
"path": [
  {
    "id": "string",
    "name": "string"
  }
],
"type": {
  "attribute": {
    "defaultValue": "string"
  },
  "measurement": {
    "processingConfig": {
      "forwardingConfig": {
        "state": "string"
      }
    }
  },
  "metric": {
    "expression": "string",
    "processingConfig": {
      "computeLocation": "string"
    }
  },
  "variables": [
    {
      "name": "string",
      "value": {
        "hierarchyId": "string",
        "propertyId": "string",
        "propertyPath": [
          {
            "id": "string",
            "name": "string"
          }
        ]
      }
    }
  ],
  "window": {
    "tumbling": {
      "interval": "string",
      "offset": "string"
    }
  }
},
```

```

    "transform": {
      "expression": "string",
      "processingConfig": {
        "computeLocation": "string",
        "forwardingConfig": {
          "state": "string"
        }
      },
      "variables": [
        {
          "name": "string",
          "value": {
            "hierarchyId": "string",
            "propertyId": "string",
            "propertyPath": [
              {
                "id": "string",
                "name": "string"
              }
            ]
          }
        }
      ]
    },
    "unit": "string"
  ],
  "assetModelCompositeModelSummaries": [
    {
      "description": "string",
      "externalId": "string",
      "id": "string",
      "name": "string",
      "path": [
        {
          "id": "string",
          "name": "string"
        }
      ],
      "type": "string"
    }
  ],
  "assetModelCompositeModelType": "string",

```

```
"assetModelId": "string",
"compositionDetails": {
  "compositionRelationship": [
    {
      "id": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[actionDefinitions](#)

The available actions for a composite model on this asset model.

Type: Array of [ActionDefinition](#) objects

[assetModelCompositeModelDescription](#)

The description for the composite model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

[assetModelCompositeModelExternalId](#)

The external ID of a composite model on this asset model.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

[assetModelCompositeModelId](#)

The ID of a composite model on this asset model.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

[assetModelCompositeModelName](#)

The unique, friendly name for the composite model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

[assetModelCompositeModelPath](#)

The path to the composite model listing the parent composite models.

Type: Array of [AssetModelCompositeModelPathSegment](#) objects

[assetModelCompositeModelProperties](#)

The property definitions of the composite model.

Type: Array of [AssetModelProperty](#) objects

[assetModelCompositeModelSummaries](#)

The list of composite model summaries for the composite model.

Type: Array of [AssetModelCompositeModelSummary](#) objects

[assetModelCompositeModelType](#)

The composite model type. Valid values are AWS/ALARM, CUSTOM, or AWS/L4E_ANOMALY.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

[assetModelId](#)

The ID of the asset model, in UUID format.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

compositionDetails

Metadata for the composition relationship established by using `composedAssetModelId` in [CreateAssetModelCompositeModel](#). For instance, an array detailing the path of the composition relationship for this composite model.

Type: [CompositionDetails](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeAssetProperty

Retrieves information about an asset property.

Note

When you call this operation for an attribute property, this response includes the default attribute value that you define in the asset model. If you update the default value in the model, this operation's response includes the new default value.

This operation doesn't return the value of the asset property. To get the value of an asset property, use [GetAssetPropertyValue](#).

Request Syntax

```
GET /assets/assetId/properties/propertyId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

assetId

The ID of the asset. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$ | ^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.]*[a-zA-Z0-9]+`

Required: Yes

propertyId

The ID of the asset property. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|
^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.]*[a-zA-Z0-9]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "assetExternalId": "string",
  "assetId": "string",
  "assetModelId": "string",
  "assetName": "string",
  "assetProperty": {
    "alias": "string",
    "dataType": "string",
    "externalId": "string",
    "id": "string",
    "name": "string",
    "notification": {
      "state": "string",
      "topic": "string"
    },
    "path": [
      {
        "id": "string",
        "name": "string"
      }
    ],
    "type": {
      "attribute": {
        "defaultValue": "string"
      },
      "measurement": {
```

```
    "processingConfig": {
      "forwardingConfig": {
        "state": "string"
      }
    },
    "metric": {
      "expression": "string",
      "processingConfig": {
        "computeLocation": "string"
      },
      "variables": [
        {
          "name": "string",
          "value": {
            "hierarchyId": "string",
            "propertyId": "string",
            "propertyPath": [
              {
                "id": "string",
                "name": "string"
              }
            ]
          }
        }
      ],
      "window": {
        "tumbling": {
          "interval": "string",
          "offset": "string"
        }
      }
    },
    "transform": {
      "expression": "string",
      "processingConfig": {
        "computeLocation": "string",
        "forwardingConfig": {
          "state": "string"
        }
      },
      "variables": [
        {
          "name": "string",
```

```
        "value": {
            "hierarchyId": "string",
            "propertyId": "string",
            "propertyPath": [
                {
                    "id": "string",
                    "name": "string"
                }
            ]
        }
    ],
    "unit": "string"
},
"compositeModel": {
    "assetProperty": {
        "alias": "string",
        "dataType": "string",
        "externalId": "string",
        "id": "string",
        "name": "string",
        "notification": {
            "state": "string",
            "topic": "string"
        },
        "path": [
            {
                "id": "string",
                "name": "string"
            }
        ],
        "type": {
            "attribute": {
                "defaultValue": "string"
            },
            "measurement": {
                "processingConfig": {
                    "forwardingConfig": {
                        "state": "string"
                    }
                }
            }
        }
    },

```

```
"metric": {
  "expression": "string",
  "processingConfig": {
    "computeLocation": "string"
  },
  "variables": [
    {
      "name": "string",
      "value": {
        "hierarchyId": "string",
        "propertyId": "string",
        "propertyPath": [
          {
            "id": "string",
            "name": "string"
          }
        ]
      }
    }
  ],
  "window": {
    "tumbling": {
      "interval": "string",
      "offset": "string"
    }
  }
},
"transform": {
  "expression": "string",
  "processingConfig": {
    "computeLocation": "string",
    "forwardingConfig": {
      "state": "string"
    }
  },
  "variables": [
    {
      "name": "string",
      "value": {
        "hierarchyId": "string",
        "propertyId": "string",
        "propertyPath": [
          {
            "id": "string",
```

```
        "name": "string"
      }
    ]
  }
},
"unit": "string"
},
"externalId": "string",
"id": "string",
"name": "string",
"type": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assetExternalId

The external ID of the asset. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

assetId

The ID of the asset, in UUID format.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

assetModelId

The ID of the asset model, in UUID format.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

assetName

The name of the asset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

assetProperty

The asset property's definition, alias, and notification state.

This response includes this object for normal asset properties. If you describe an asset property in a composite model, this response includes the asset property information in `compositeModel`.

Type: [Property](#) object

compositeModel

The composite model that declares this asset property, if this asset property exists in a composite model.

Type: [CompositeModelProperty](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeBulkImportJob

Retrieves information about a bulk import job request. For more information, see [Describe a bulk import job \(Amazon CLI\)](#) in the *Amazon Simple Storage Service User Guide*.

Request Syntax

```
GET /jobs/jobId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

jobId

The ID of the job.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "adaptiveIngestion": boolean,
  "deleteFilesAfterImport": boolean,
  "errorReportLocation": {
    "bucket": "string",
    "prefix": "string"
  },
  "files": [
```

```
{
  "bucket": "string",
  "key": "string",
  "versionId": "string"
},
"jobConfiguration": {
  "fileFormat": {
    "csv": {
      "columnNames": [ "string" ]
    },
    "parquet": {
    }
  }
},
"jobCreationDate": number,
"jobId": "string",
"jobLastUpdateDate": number,
"jobName": "string",
"jobRoleArn": "string",
"jobStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

adaptiveIngestion

If set to true, ingest new data into Amazon IoT SiteWise storage. Measurements with notifications, metrics and transforms are computed. If set to false, historical data is ingested into Amazon IoT SiteWise as is.

Type: Boolean

deleteFilesAfterImport

If set to true, your data files is deleted from S3, after ingestion into Amazon IoT SiteWise storage.

Type: Boolean

errorReportLocation

The Amazon S3 destination where errors associated with the job creation request are saved.

Type: [ErrorReportLocation](#) object

files

The files in the specified Amazon S3 bucket that contain your data.

Type: Array of [File](#) objects

jobConfiguration

Contains the configuration information of a job, such as the file format used to save data in Amazon S3.

Type: [JobConfiguration](#) object

jobCreationDate

The date the job was created, in Unix epoch TIME.

Type: Timestamp

jobId

The ID of the job.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

jobLastUpdateDate

The date the job was last updated, in Unix epoch time.

Type: Timestamp

jobName

The unique name that helps identify the job request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

jobRoleArn

The [ARN](#) of the IAM role that allows Amazon IoT SiteWise to read Amazon S3 data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

jobStatus

The status of the bulk import job can be one of following values:

- PENDING – Amazon IoT SiteWise is waiting for the current bulk import job to finish.
- CANCELLED – The bulk import job has been canceled.
- RUNNING – Amazon IoT SiteWise is processing your request to import your data from Amazon S3.
- COMPLETED – Amazon IoT SiteWise successfully completed your request to import data from Amazon S3.
- FAILED – Amazon IoT SiteWise couldn't process your request to import data from Amazon S3. You can use logs saved in the specified error report location in Amazon S3 to troubleshoot issues.
- COMPLETED_WITH_FAILURES – Amazon IoT SiteWise completed your request to import data from Amazon S3 with errors. You can use logs saved in the specified error report location in Amazon S3 to troubleshoot issues.

Type: String

Valid Values: PENDING | CANCELLED | RUNNING | COMPLETED | FAILED | COMPLETED_WITH_FAILURES

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeDashboard

Retrieves information about a dashboard.

Request Syntax

```
GET /dashboards/dashboardId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

dashboardId

The ID of the dashboard.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "dashboardArn": "string",
  "dashboardCreationDate": number,
  "dashboardDefinition": "string",
  "dashboardDescription": "string",
  "dashboardId": "string",
  "dashboardLastUpdateDate": number,
  "dashboardName": "string",
  "projectId": "string"
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

dashboardArn

The [ARN](#) of the dashboard, which has the following format.

```
arn:${Partition}:iotsitewise:${Region}:${Account}:dashboard/  
${DashboardId}
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: ^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+\$

dashboardCreationDate

The date the dashboard was created, in Unix epoch time.

Type: Timestamp

dashboardDefinition

The dashboard's definition JSON literal. For detailed information, see [Creating dashboards \(CLI\)](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 204800.

Pattern: .+

dashboardDescription

The dashboard's description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

dashboardId

The ID of the dashboard.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

dashboardLastUpdateDate

The date the dashboard was last updated, in Unix epoch time.

Type: Timestamp

dashboardName

The name of the dashboard.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

projectId

The ID of the project that the dashboard is in.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeDataset

Retrieves information about a dataset.

Request Syntax

```
GET /datasets/datasetId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

datasetId

The ID of the dataset.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.]*[a-zA-Z0-9]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "datasetArn": "string",
  "datasetCreationDate": number,
  "datasetDescription": "string",
  "datasetId": "string",
  "datasetLastUpdateDate": number,
  "datasetName": "string",
  "datasetSource": {
    "sourceDetail": {
```

```
    "kendra": {
      "knowledgeBaseArn": "string",
      "roleArn": "string"
    }
  },
  "sourceFormat": "string",
  "sourceType": "string"
},
"datasetStatus": {
  "error": {
    "code": "string",
    "details": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "message": "string"
  },
  "state": "string"
},
"datasetVersion": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

datasetArn

The [ARN](#) of the dataset. The format is `arn:${Partition}:iotsitewise:${Region}:${Account}:dataset/${DatasetId}`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+`

datasetCreationDate

The dataset creation date, in Unix epoch time.

Type: Timestamp

datasetDescription

A description about the dataset, and its functionality.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9 _\-#*$!@]+$`

datasetId

The ID of the dataset.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

datasetLastUpdateDate

The date the dataset was last updated, in Unix epoch time.

Type: Timestamp

datasetName

The name of the dataset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^[a-zA-Z0-9 _\-#*$!@]+$`

datasetSource

The data source for the dataset.

Type: [DatasetSource](#) object

datasetStatus

The status of the dataset. This contains the state and any error messages. State is CREATING after a successful call to this API, and any associated error message. The state is ACTIVE when ready to use.

Type: [DatasetStatus](#) object

[datasetVersion](#)

The version of the dataset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: `^(0|([1-9]{1}\d*))$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeDefaultEncryptionConfiguration

Retrieves information about the default encryption configuration for the Amazon account in the default or specified Region. For more information, see [Key management](#) in the *Amazon IoT SiteWise User Guide*.

Request Syntax

```
GET /configuration/account/encryption HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "configurationStatus": {
    "error": {
      "code": "string",
      "message": "string"
    },
    "state": "string"
  },
  "encryptionType": "string",
  "kmsKeyArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configurationStatus

The status of the account configuration. This contains the `ConfigurationState`. If there's an error, it also contains the `ErrorDetails`.

Type: [ConfigurationStatus](#) object

encryptionType

The type of encryption used for the encryption configuration.

Type: String

Valid Values: SITEWISE_DEFAULT_ENCRYPTION | KMS_BASED_ENCRYPTION

kmsKeyArn

The key ARN of the customer managed key used for Amazon KMS encryption if you use `KMS_BASED_ENCRYPTION`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeGateway

Retrieves information about a gateway.

Request Syntax

```
GET /20200301/gateways/gatewayId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

gatewayId

The ID of the gateway device.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "creationDate": number,
  "gatewayArn": "string",
  "gatewayCapabilitySummaries": [
    {
      "capabilityNamespace": "string",
      "capabilitySyncStatus": "string"
    }
  ],
  "gatewayId": "string",
  "gatewayName": "string",
```

```
"gatewayPlatform": {
  "greengrass": {
    "groupArn": "string"
  },
  "greengrassV2": {
    "coreDeviceOperatingSystem": "string",
    "coreDeviceThingName": "string"
  },
  "siemensIE": {
    "iotCoreThingName": "string"
  }
},
"gatewayVersion": "string",
"lastUpdateDate": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

creationDate

The date the gateway was created, in Unix epoch time.

Type: Timestamp

gatewayArn

The [ARN](#) of the gateway, which has the following format.

```
arn:${Partition}:iotsitewise:${Region}:${Account}:gateway/${GatewayId}
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: ^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+\$

gatewayCapabilitySummaries

A list of gateway capability summaries that each contain a namespace and status. Each gateway capability defines data sources for the gateway. To retrieve a capability configuration's definition, use [DescribeGatewayCapabilityConfiguration](#).

Type: Array of [GatewayCapabilitySummary](#) objects

gatewayId

The ID of the gateway device.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

gatewayName

The name of the gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

gatewayPlatform

The gateway's platform.

Type: [GatewayPlatform](#) object

gatewayVersion

The version of the gateway. A value of 3 indicates an MQTT-enabled, V3 gateway, while 2 indicates a Classic streams, V2 gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^[0-9]+$`

lastUpdateDate

The date the gateway was last updated, in Unix epoch time.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeGatewayCapabilityConfiguration

Retrieves information about a gateway capability configuration. Each gateway capability defines data sources for a gateway. A capability configuration can contain multiple data source configurations. If you define OPC-UA sources for a gateway in the Amazon IoT SiteWise console, all of your OPC-UA sources are stored in one capability configuration. To list all capability configurations for a gateway, use [DescribeGateway](#).

Request Syntax

```
GET /20200301/gateways/gatewayId/capability/capabilityNamespace HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[capabilityNamespace](#)

The namespace of the capability configuration. For example, if you configure OPC-UA sources from the Amazon IoT SiteWise console, your OPC-UA capability configuration has the namespace `iotsitewise:opcuacollector:version`, where `version` is a number such as 1.

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `^[a-zA-Z]+:[a-zA-Z]+:[0-9]+$`

Required: Yes

[gatewayId](#)

The ID of the gateway that defines the capability configuration.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "capabilityConfiguration": "string",
  "capabilityNamespace": "string",
  "capabilitySyncStatus": "string",
  "gatewayId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

capabilityConfiguration

The JSON document that defines the gateway capability's configuration. For more information, see [Configuring data sources \(CLI\)](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10000000.

capabilityNamespace

The namespace of the gateway capability.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `^[a-zA-Z]+:[a-zA-Z]+:[0-9]+$`

capabilitySyncStatus

The synchronization status of the capability configuration. The sync status can be one of the following:

- IN_SYNC – The gateway is running the capability configuration.

- NOT_APPLICABLE – Synchronization is not required for this capability configuration. This is most common when integrating partner data sources, because the data integration is handled externally by the partner.
- OUT_OF_SYNC – The gateway hasn't received the capability configuration.
- SYNC_FAILED – The gateway rejected the capability configuration.
- UNKNOWN – The synchronization status is currently unknown due to an undetermined or temporary error.

Type: String

Valid Values: IN_SYNC | OUT_OF_SYNC | SYNC_FAILED | UNKNOWN | NOT_APPLICABLE

gatewayId

The ID of the gateway that defines the capability configuration.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeLoggingOptions

Retrieves the current Amazon IoT SiteWise logging options.

Request Syntax

```
GET /logging HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "loggingOptions": {
    "level": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

loggingOptions

The current logging options.

Type: [LoggingOptions](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribePortal

Retrieves information about a portal.

Request Syntax

```
GET /portals/portalId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

portalId

The ID of the portal.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "alarms": {
    "alarmRoleArn": "string",
    "notificationLambdaArn": "string"
  },
  "notificationSenderEmail": "string",
  "portalArn": "string",
  "portalAuthMode": "string",
  "portalClientId": "string",
  "portalContactEmail": "string",
```

```
"portalCreationDate": number,
"portalDescription": "string",
"portalId": "string",
"portalLastUpdateDate": number,
"portalLogoImageLocation": {
  "id": "string",
  "url": "string"
},
"portalName": "string",
"portalStartUrl": "string",
"portalStatus": {
  "error": {
    "code": "string",
    "message": "string"
  },
  "state": "string"
},
"portalType": "string",
"portalTypeConfiguration": {
  "string" : {
    "portalTools": [ "string" ]
  }
},
"roleArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

alarms

Contains the configuration information of an alarm created in an Amazon IoT SiteWise Monitor portal.

Type: [Alarms](#) object

notificationSenderEmail

The email address that sends alarm notifications.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9_\-\.\\+]+@[a-zA-Z0-9_\-\.\\+]+\.[a-zA-Z]{2,}$`

portalArn

The [ARN](#) of the portal, which has the following format.

`arn:${Partition}:iotsitewise:${Region}:${Account}:portal/${PortalId}`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\\.]+$`

portalAuthMode

The service to use to authenticate users to the portal.

Type: String

Valid Values: IAM | SSO

portalClientId

The IAM Identity Center application generated client ID (used with IAM Identity Center API operations). Amazon IoT SiteWise includes `portalClientId` for only portals that use IAM Identity Center to authenticate users.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^[!-~]*`

portalContactEmail

The Amazon administrator's contact email address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9_\-\.\\+]+@[a-zA-Z0-9_\-\.\\+]+\.[a-zA-Z]{2,}$`

portalCreationDate

The date the portal was created, in Unix epoch time.

Type: Timestamp

portalDescription

The portal's description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

portalId

The ID of the portal.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

portalLastUpdateDate

The date the portal was last updated, in Unix epoch time.

Type: Timestamp

portalLogoImageLocation

The portal's logo image, which is available at a URL.

Type: [ImageLocation](#) object

portalName

The name of the portal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

[portalStartUrl](#)

The URL for the Amazon IoT SiteWise Monitor portal. You can use this URL to access portals that use IAM Identity Center for authentication. For portals that use IAM for authentication, you must use the Amazon IoT SiteWise console to get a URL that you can use to access the portal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^(http|https)\:\/\S+`

[portalStatus](#)

The current status of the portal, which contains a state and any error message.

Type: [PortalStatus](#) object

[portalType](#)

Define the type of portal. The value for Amazon IoT SiteWise Monitor (Classic) is `SITWISE_PORTAL_V1`. The value for Amazon IoT SiteWise Monitor (AI-aware) is `SITWISE_PORTAL_V2`.

Type: String

Valid Values: `SITWISE_PORTAL_V1` | `SITWISE_PORTAL_V2`

[portalTypeConfiguration](#)

The configuration entry associated with the specific portal type. The value for Amazon IoT SiteWise Monitor (Classic) is `SITWISE_PORTAL_V1`. The value for Amazon IoT SiteWise Monitor (AI-aware) is `SITWISE_PORTAL_V2`.

Type: String to [PortalTypeEntry](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

[roleArn](#)

The [ARN](#) of the service role that allows the portal's users to access your Amazon IoT SiteWise resources on your behalf. For more information, see [Using service roles for Amazon IoT SiteWise Monitor](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.\\+=, @]+$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeProject

Retrieves information about a project.

Request Syntax

```
GET /projects/projectId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[projectId](#)

The ID of the project.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "portalId": "string",
  "projectArn": "string",
  "projectCreationDate": number,
  "projectDescription": "string",
  "projectId": "string",
  "projectLastUpdateDate": number,
  "projectName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

portalId

The ID of the portal that the project is in.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

projectArn

The [ARN](#) of the project, which has the following format.

`arn:${Partition}:iotsitewise:${Region}:${Account}:project/${ProjectId}`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

projectCreationDate

The date the project was created, in Unix epoch time.

Type: Timestamp

projectDescription

The project's description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

projectId

The ID of the project.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

projectLastUpdateDate

The date the project was last updated, in Unix epoch time.

Type: Timestamp

projectName

The name of the project.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeStorageConfiguration

Retrieves information about the storage configuration for Amazon IoT SiteWise.

Request Syntax

```
GET /configuration/account/storage HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "configurationStatus": {
    "error": {
      "code": "string",
      "message": "string"
    },
    "state": "string"
  },
  "disallowIngestNullNaN": boolean,
  "disassociatedDataStorage": "string",
  "lastUpdateDate": number,
  "multiLayerStorage": {
    "customerManagedS3Storage": {
      "roleArn": "string",
      "s3ResourceArn": "string"
    }
  },
  "retentionPeriod": {
    "numberOfDays": number,
    "unlimited": boolean
  }
}
```

```
  },
  "storageType": "string",
  "warmTier": "string",
  "warmTierRetentionPeriod": {
    "numberOfDays": number,
    "unlimited": boolean
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configurationStatus

Contains current status information for the configuration.

Type: [ConfigurationStatus](#) object

disallowIngestNullNaN

Describes the configuration for ingesting NULL and NaN data. By default the feature is allowed. The feature is disallowed if the value is `true`.

Type: Boolean

disassociatedDataStorage

Contains the storage configuration for time series (data streams) that aren't associated with asset properties. The `disassociatedDataStorage` can be one of the following values:

- **ENABLED** – Amazon IoT SiteWise accepts time series that aren't associated with asset properties.

Important

After the `disassociatedDataStorage` is enabled, you can't disable it.

- **DISABLED** – Amazon IoT SiteWise doesn't accept time series (data streams) that aren't associated with asset properties.

For more information, see [Data streams](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Valid Values: ENABLED | DISABLED

lastUpdateDate

The date the storage configuration was last updated, in Unix epoch time.

Type: Timestamp

multiLayerStorage

Contains information about the storage destination.

Type: [MultiLayerStorage](#) object

retentionPeriod

The number of days your data is kept in the hot tier. By default, your data is kept indefinitely in the hot tier.

Type: [RetentionPeriod](#) object

storageType

The storage tier that you specified for your data. The `storageType` parameter can be one of the following values:

- `SITWISE_DEFAULT_STORAGE` – Amazon IoT SiteWise saves your data into the hot tier. The hot tier is a service-managed database.
- `MULTI_LAYER_STORAGE` – Amazon IoT SiteWise saves your data in both the cold tier and the hot tier. The cold tier is a customer-managed Amazon S3 bucket.

Type: String

Valid Values: `SITWISE_DEFAULT_STORAGE` | `MULTI_LAYER_STORAGE`

warmTier

A service managed storage tier optimized for analytical queries. It stores periodically uploaded, buffered and historical data ingested with the `CreaeBulkImportJob` API.

Type: String

Valid Values: ENABLED | DISABLED

warmTierRetentionPeriod

Set this period to specify how long your data is stored in the warm tier before it is deleted. You can set this only if cold tier is enabled.

Type: [WarmTierRetentionPeriod](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeTimeSeries

Retrieves information about a time series (data stream).

To identify a time series, do one of the following:

- If the time series isn't associated with an asset property, specify the `alias` of the time series.
- If the time series is associated with an asset property, specify one of the following:
 - The `alias` of the time series.
 - The `assetId` and `propertyId` that identifies the asset property.

Request Syntax

```
GET /timeseries/describe/?alias=alias&assetId=assetId&propertyId=propertyId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

alias

The alias that identifies the time series.

Length Constraints: Minimum length of 1.

Pattern: `[^\u0000-\u001F\u007F]+`

assetId

The ID of the asset in which the asset property was created. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.]*[a-zA-Z0-9]+`

propertyId

The ID of the asset property. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "alias": "string",
  "assetId": "string",
  "dataType": "string",
  "dataTypeSpec": "string",
  "propertyId": "string",
  "timeSeriesArn": "string",
  "timeSeriesCreationDate": number,
  "timeSeriesId": "string",
  "timeSeriesLastUpdateDate": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

alias

The alias that identifies the time series.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[^\u0000-\u001F\u007F]+`

assetId

The ID of the asset in which the asset property was created.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

dataType

The data type of the time series.

If you specify STRUCT, you must also specify `dataTypeSpec` to identify the type of the structure for this time series.

Type: String

Valid Values: STRING | INTEGER | DOUBLE | BOOLEAN | STRUCT

dataTypeSpec

The data type of the structure for this time series. This parameter is required for time series that have the STRUCT data type.

The options for this parameter depend on the type of the composite model in which you created the asset property that is associated with your time series. Use `AWS/ALARM_STATE` for alarm state in alarm composite models.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

propertyId

The ID of the asset property, in UUID format.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

timeSeriesArn

The [ARN](#) of the time series, which has the following format.

```
arn:${Partition}:iotsitewise:${Region}:${Account}:time-series/  
${TimeSeriesId}
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

timeSeriesCreationDate

The date that the time series was created, in Unix epoch time.

Type: Timestamp

timeSeriesId

The ID of the time series.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 73.

timeSeriesLastUpdateDate

The date that the time series was last updated, in Unix epoch time.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DisassociateAssets

Disassociates a child asset from the given parent asset through a hierarchy defined in the parent asset's model.

Request Syntax

```
POST /assets/assetId/disassociate HTTP/1.1
Content-type: application/json
```

```
{
  "childAssetId": "string",
  "clientToken": "string",
  "hierarchyId": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

assetId

The ID of the parent asset from which to disassociate the child asset. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|
^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.]*[a-zA-Z0-9]+`

Required: Yes

Request Body

The request accepts the following data in JSON format.

childAssetId

The ID of the child asset to disassociate. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

hierarchyId

The ID of a hierarchy in the parent asset's model. (This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.) Hierarchies allow different groupings of assets to be formed that all come from the same asset model. You can use the hierarchy ID to identify the correct asset to disassociate. For more information, see [Asset hierarchies](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DisassociateTimeSeriesFromAssetProperty

Disassociates a time series (data stream) from an asset property.

Request Syntax

```
POST /timeseries/disassociate/?alias=alias&assetId=assetId&propertyId=propertyId
HTTP/1.1
Content-type: application/json

{
  "clientToken": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

alias

The alias that identifies the time series.

Length Constraints: Minimum length of 1.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

assetId

The ID of the asset in which the asset property was created. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:\-]*[a-zA-Z0-9]+`

Required: Yes

propertyId

The ID of the asset property. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)

- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ExecuteAction

Executes an action on a target resource.

Request Syntax

```
POST /actions HTTP/1.1
Content-type: application/json

{
  "actionDefinitionId": "string",
  "actionPayload": {
    "stringValue": "string"
  },
  "clientToken": "string",
  "targetResource": {
    "assetId": "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

actionDefinitionId

The ID of the action definition.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

actionPayload

The JSON payload of the action.

Type: [ActionPayload](#) object

Required: Yes

[clientToken](#)

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

[targetResource](#)

The resource the action will be taken on.

Type: [TargetResource](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "actionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

[actionId](#)

The ID of the action.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ExecuteQuery

Run SQL queries to retrieve metadata and time-series data from asset models, assets, measurements, metrics, transforms, and aggregates.

Request Syntax

```
POST /queries/execution HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "maxResults": number,
  "nextToken": "string",
  "queryStatement": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

maxResults

The maximum number of results to return at one time. The default is 25.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

nextToken

The string that specifies the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

queryStatement

The Amazon IoT SiteWise query statement.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `^\[s\S]+\$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "columns": [
    {
      "name": "string",
      "type": {
        "scalarType": "string"
      }
    }
  ],
  "nextToken": "string",
  "rows": [
```

```
{
  "data": [
    {
      "arrayValue": [
        "Datum"
      ],
      "nullValue": boolean,
      "rowValue": "Row",
      "scalarValue": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

columns

Represents a single column in the query results.

Type: Array of [ColumnInfo](#) objects

nextToken

The string that specifies the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

rows

Represents a single row in the query results.

Type: Array of [Row](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

QueryTimeoutException

The query timed out.

HTTP Status Code: 400

ServiceUnavailableException

The requested service is unavailable.

HTTP Status Code: 503

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

ValidationException

The validation failed for this query.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetAssetPropertyAggregates

Gets aggregated values for an asset property. For more information, see [Querying aggregates](#) in the *Amazon IoT SiteWise User Guide*.

To identify an asset property, you must specify one of the following:

- The `assetId` and `propertyId` of an asset property.
- A `propertyAlias`, which is a data stream alias (for example, `/company/windfarm/3/turbine/7/temperature`). To define an asset property's alias, see [UpdateAssetProperty](#).

Request Syntax

```
GET /properties/aggregates?  
aggregateTypes=aggregateTypes&assetId=assetId&endDate=endDate&maxResults=maxResults&nextToken=nextToken  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[aggregateTypes](#)

The data aggregating function.

Array Members: Minimum number of 1 item.

Valid Values: AVERAGE | COUNT | MAXIMUM | MINIMUM | SUM | STANDARD_DEVIATION

Required: Yes

[assetId](#)

The ID of the asset, in UUID format.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

[endDate](#)

The inclusive end of the range from which to query historical data, expressed in seconds in Unix epoch time.

Required: Yes

maxResults

The maximum number of results to return for each paginated request. A result set is returned in the two cases, whichever occurs first.

- The size of the result set is equal to 1 MB.
- The number of data points in the result set is equal to the value of `maxResults`. The maximum value of `maxResults` is 2500.

Valid Range: Minimum value of 1.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `[A-Za-z0-9+/=]+`

propertyAlias

The alias that identifies the property, such as an OPC-UA server data stream path (for example, `/company/windfarm/3/turbine/7/temperature`). For more information, see [Mapping industrial data streams to asset properties](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `[\u0000-\u001F\u007F]+`

propertyId

The ID of the asset property, in UUID format.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

qualities

The quality by which to filter asset data.

Array Members: Fixed number of 1 item.

Valid Values: GOOD | BAD | UNCERTAIN

resolution

The time interval over which to aggregate data.

Length Constraints: Minimum length of 2. Maximum length of 3.

Pattern: 1m|15m|1h|1d

Required: Yes

startDate

The exclusive start of the range from which to query historical data, expressed in seconds in Unix epoch time.

Required: Yes

timeOrdering

The chronological sorting order of the requested information.

Default: ASCENDING

Valid Values: ASCENDING | DESCENDING

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "aggregatedValues": [
    {
      "quality": "string",
      "timestamp": number,
      "value": {
        "average": number,
        "count": number,
        "maximum": number,
        "minimum": number,

```

```
        "standardDeviation": number,
        "sum": number
    }
}
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

aggregatedValues

The requested aggregated values.

Type: Array of [AggregatedValue](#) objects

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ServiceUnavailableException

The requested service is unavailable.

HTTP Status Code: 503

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetAssetPropertyValue

Gets an asset property's current value. For more information, see [Querying current values](#) in the *Amazon IoT SiteWise User Guide*.

To identify an asset property, you must specify one of the following:

- The `assetId` and `propertyId` of an asset property.
- A `propertyAlias`, which is a data stream alias (for example, `/company/windfarm/3/turbine/7/temperature`). To define an asset property's alias, see [UpdateAssetProperty](#).

Request Syntax

```
GET /properties/latest?  
assetId=assetId&propertyAlias=propertyAlias&propertyId=propertyId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[assetId](#)

The ID of the asset, in UUID format.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

[propertyAlias](#)

The alias that identifies the property, such as an OPC-UA server data stream path (for example, `/company/windfarm/3/turbine/7/temperature`). For more information, see [Mapping industrial data streams to asset properties](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `[^\u0000-\u001F\u007F]+`

[propertyId](#)

The ID of the asset property, in UUID format.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "propertyValue": {
    "quality": "string",
    "timestamp": {
      "offsetInNanos": number,
      "timeInSeconds": number
    },
    "value": {
      "booleanValue": boolean,
      "doubleValue": number,
      "integerValue": number,
      "nullValue": {
        "valueType": "string"
      },
      "stringValue": "string"
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

propertyValue

The current asset property value.

Type: [AssetPropertyValue](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ServiceUnavailableException

The requested service is unavailable.

HTTP Status Code: 503

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetAssetPropertyValueHistory

Gets the history of an asset property's values. For more information, see [Querying historical values](#) in the *Amazon IoT SiteWise User Guide*.

To identify an asset property, you must specify one of the following:

- The `assetId` and `propertyId` of an asset property.
- A `propertyAlias`, which is a data stream alias (for example, `/company/windfarm/3/turbine/7/temperature`). To define an asset property's alias, see [UpdateAssetProperty](#).

Request Syntax

```
GET /properties/history?  
assetId=assetId&endDate=endDate&maxResults=maxResults&nextToken=nextToken&propertyAlias=propertyAlias  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[assetId](#)

The ID of the asset, in UUID format.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

[endDate](#)

The inclusive end of the range from which to query historical data, expressed in seconds in Unix epoch time.

[maxResults](#)

The maximum number of results to return for each paginated request. A result set is returned in the two cases, whichever occurs first.

- The size of the result set is equal to 4 MB.
- The number of data points in the result set is equal to the value of `maxResults`. The maximum value of `maxResults` is 20000.

Valid Range: Minimum value of 1.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `[A-Za-z0-9+/=]+`

propertyAlias

The alias that identifies the property, such as an OPC-UA server data stream path (for example, `/company/windfarm/3/turbine/7/temperature`). For more information, see [Mapping industrial data streams to asset properties](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `[\u0000-\u001F\u007F]+`

propertyId

The ID of the asset property, in UUID format.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

qualities

The quality by which to filter asset data.

Array Members: Fixed number of 1 item.

Valid Values: GOOD | BAD | UNCERTAIN

startDate

The exclusive start of the range from which to query historical data, expressed in seconds in Unix epoch time.

timeOrdering

The chronological sorting order of the requested information.

Default: ASCENDING

Valid Values: ASCENDING | DESCENDING

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "assetPropertyValueHistory": [
    {
      "quality": "string",
      "timestamp": {
        "offsetInNanos": number,
        "timeInSeconds": number
      },
      "value": {
        "booleanValue": boolean,
        "doubleValue": number,
        "integerValue": number,
        "nullValue": {
          "valueType": "string"
        },
        "stringValue": "string"
      }
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assetPropertyValueHistory](#)

The asset property's value history.

Type: Array of [AssetPropertyValue](#) objects

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ServiceUnavailableException

The requested service is unavailable.

HTTP Status Code: 503

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetInterpolatedAssetPropertyValues

Get interpolated values for an asset property for a specified time interval, during a period of time. If your time series is missing data points during the specified time interval, you can use interpolation to estimate the missing data.

For example, you can use this operation to return the interpolated temperature values for a wind turbine every 24 hours over a duration of 7 days.

To identify an asset property, you must specify one of the following:

- The `assetId` and `propertyId` of an asset property.
- A `propertyAlias`, which is a data stream alias (for example, `/company/windfarm/3/turbine/7/temperature`). To define an asset property's alias, see [UpdateAssetProperty](#).

Request Syntax

```
GET /properties/interpolated?  
assetId=assetId&endTimeInSeconds=endTimeInSeconds&endTimeOffsetInNanos=endTimeOffsetInNanos&int  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

assetId

The ID of the asset, in UUID format.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

endTimeInSeconds

The inclusive end of the range from which to interpolate data, expressed in seconds in Unix epoch time.

Valid Range: Minimum value of 1. Maximum value of 9223372036854774.

Required: Yes

endTimeOffsetInNanos

The nanosecond offset converted from endTimeInSeconds.

Valid Range: Minimum value of 0. Maximum value of 999999999.

intervalInSeconds

The time interval in seconds over which to interpolate data. Each interval starts when the previous one ends.

Valid Range: Minimum value of 1. Maximum value of 320000000.

Required: Yes

intervalWindowInSeconds

The query interval for the window, in seconds. Amazon IoT SiteWise computes each interpolated value by using data points from the timestamp of each interval, minus the window to the timestamp of each interval plus the window. If not specified, the window ranges between the start time minus the interval and the end time plus the interval.

Note

- If you specify a value for the `intervalWindowInSeconds` parameter, the value for the `type` parameter must be `LINEAR_INTERPOLATION`.
- If a data point isn't found during the specified query window, Amazon IoT SiteWise won't return an interpolated value for the interval. This indicates that there's a gap in the ingested data points.

For example, you can get the interpolated temperature values for a wind turbine every 24 hours over a duration of 7 days. If the interpolation starts on July 1, 2021, at 9 AM with a window of 2 hours, Amazon IoT SiteWise uses the data points from 7 AM (9 AM minus 2 hours) to 11 AM (9 AM plus 2 hours) on July 2, 2021 to compute the first interpolated value. Next, Amazon IoT SiteWise uses the data points from 7 AM (9 AM minus 2 hours) to 11 AM (9 AM plus 2 hours) on July 3, 2021 to compute the second interpolated value, and so on.

Valid Range: Minimum value of 1. Maximum value of 320000000.

maxResults

The maximum number of results to return for each paginated request. If not specified, the default value is 10.

Valid Range: Minimum value of 1.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

propertyAlias

The alias that identifies the property, such as an OPC-UA server data stream path (for example, /company/windfarm/3/turbine/7/temperature). For more information, see [Mapping industrial data streams to asset properties](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: [^\u0000-\u001F\u007F]+

propertyId

The ID of the asset property, in UUID format.

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}\$

quality

The quality of the asset property value. You can use this parameter as a filter to choose only the asset property values that have a specific quality.

Valid Values: GOOD | BAD | UNCERTAIN

Required: Yes

startTimeInSeconds

The exclusive start of the range from which to interpolate data, expressed in seconds in Unix epoch time.

Valid Range: Minimum value of 1. Maximum value of 9223372036854774.

Required: Yes

startTimeOffsetInNanos

The nanosecond offset converted from `startTimeInSeconds`.

Valid Range: Minimum value of 0. Maximum value of 999999999.

type

The interpolation type.

Valid values: `LINEAR_INTERPOLATION` | `LOCF_INTERPOLATION`

- `LINEAR_INTERPOLATION` – Estimates missing data using [linear interpolation](#).

For example, you can use this operation to return the interpolated temperature values for a wind turbine every 24 hours over a duration of 7 days. If the interpolation starts July 1, 2021, at 9 AM, Amazon IoT SiteWise returns the first interpolated value on July 2, 2021, at 9 AM, the second interpolated value on July 3, 2021, at 9 AM, and so on.

- `LOCF_INTERPOLATION` – Estimates missing data using last observation carried forward interpolation

If no data point is found for an interval, Amazon IoT SiteWise returns the last observed data point for the previous interval and carries forward this interpolated value until a new data point is found.

For example, you can get the state of an on-off valve every 24 hours over a duration of 7 days. If the interpolation starts July 1, 2021, at 9 AM, Amazon IoT SiteWise returns the last observed data point between July 1, 2021, at 9 AM and July 2, 2021, at 9 AM as the first interpolated value. If a data point isn't found after 9 AM on July 2, 2021, Amazon IoT SiteWise uses the same interpolated value for the rest of the days.

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "interpolatedAssetPropertyValues": [
    {
      "timestamp": {
        "offsetInNanos": number,
        "timeInSeconds": number
      },
      "value": {
        "booleanValue": boolean,
        "doubleValue": number,
        "integerValue": number,
        "nullValue": {
          "valueType": "string"
        },
        "stringValue": "string"
      }
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[interpolatedAssetPropertyValues](#)

The requested interpolated values.

Type: Array of [InterpolatedAssetPropertyValue](#) objects

[nextToken](#)

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ServiceUnavailableException

The requested service is unavailable.

HTTP Status Code: 503

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

Examples

Example

The following example uses the Amazon Command Line Interface (Amazon CLI) to retrieve the interpolated temperature values for a wind turbine every 24 hours between April 26, 2021 at midnight and May 3, 2021 at midnight in Pacific Time (PT).

Note

- Replace `<asset-ID>` and `<property-ID>` with your asset ID and property ID.
- The `--start-time-offset-in-nanos` and `--end-time-offset-in-nanos` parameters are optional. You can use these parameters to specify the nanosecond offsets for `startTimeInSeconds` and `endTimeInSeconds`.

Sample Request

```
aws iotsitewise get-interpolated-asset-property-values --asset-id <asset-ID> --
property-id <property-ID> --start-time-in-seconds 1619420400 --start-time-offset-in-
nanos 0 --end-time-in-seconds 1620025200
--end-time-offset-in-nanos 0 --end-time-offset-in-nanos 1 --quality GOOD --
interval-in-seconds 3600 --type LINEAR_INTERPOLATION
```

Sample Response

```
{
  "interpolatedAssetPropertyValues": [
    {
      "timestamp": {
        "timeInSeconds": 1619420400,
        "offsetInNanos": 0
      },
      "value": {
        "doubleValue": 30.0
      }
    },
    {
      "timestamp": {
        "timeInSeconds": 1619424000,
```

```
        "offsetInNanos": 0
      },
      "value": {
        "doubleValue": 41.25
      }
    },
    {
      "timestamp": {
        "timeInSeconds": 1619427600,
        "offsetInNanos": 0
      },
      "value": {
        "doubleValue": 35.85
      }
    },
    ...
  ],
  ...
}
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

InvokeAssistant

Invokes SiteWise Assistant to start or continue a conversation.

Request Syntax

```
POST /assistant/invocation HTTP/1.1
Content-type: application/json

{
  "conversationId": "string",
  "enableTrace": boolean,
  "message": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

conversationId

The ID assigned to a conversation. Amazon IoT SiteWise automatically generates a unique ID for you, and this parameter is never required. However, if you prefer to have your own ID, you must specify it here in UUID format. If you specify your own ID, it must be globally unique.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: No

enableTrace

Specifies if to turn trace on or not. It is used to track the SiteWise Assistant's reasoning, and data access process.

Type: Boolean

Required: No

message

A text message sent to the SiteWise Assistant by the user.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10000.

Required: Yes

Response Syntax

```
HTTP/1.1 200
x-amz-iotsitewise-assistant-conversation-id: conversationId
Content-type: application/json
```

```
{
  "accessDeniedException": {
  },
  "conflictingOperationException": {
  },
  "internalFailureException": {
  },
  "invalidRequestException": {
  },
  "limitExceededException": {
  },
  "output": {
    "citations": [
      {
        "content": {
          "text": "string"
        },
        "reference": {
          "dataset": {
            "datasetArn": "string",
            "source": {
              "arn": "string",
              "location": {
```

```
        "uri": "string"
      }
    }
  },
  ],
  "message": "string"
},
"resourceNotFoundException": {
},
"throttlingException": {
},
"trace": {
  "text": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The response returns the following HTTP headers.

conversationId

The ID of the conversation, in UUID format. This ID uniquely identifies the conversation within Amazon IoT SiteWise.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

The following data is returned in JSON format by the service.

accessDeniedException

Access is denied.

Type: Exception

HTTP Status Code: 403

conflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

Type: Exception
HTTP Status Code: 409

internalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

Type: Exception
HTTP Status Code: 500

invalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

Type: Exception
HTTP Status Code: 400

limitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

Type: Exception
HTTP Status Code: 410

output

Contains the SiteWise Assistant's response.

Type: [InvocationOutput](#) object

resourceNotFoundException

The requested resource can't be found.

Type: Exception
HTTP Status Code: 404

throttlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

Type: Exception

HTTP Status Code: 429

trace

Contains tracing information of the SiteWise Assistant's reasoning and data access.

Type: [Trace](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)

- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListAccessPolicies

Retrieves a paginated list of access policies for an identity (an IAM Identity Center user, an IAM Identity Center group, or an IAM user) or an Amazon IoT SiteWise Monitor resource (a portal or project).

Request Syntax

```
GET /access-policies?  
iamArn=iamArn&identityId=identityId&identityType=identityType&maxResults=maxResults&nextToken=nextToken  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

iamArn

The ARN of the IAM user. For more information, see [IAM ARNs](#) in the *IAM User Guide*. This parameter is required if you specify IAM for `identityType`.

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.\+=,@]+$`

identityId

The ID of the identity. This parameter is required if you specify USER or GROUP for `identityType`.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `\S+`

identityType

The type of identity (IAM Identity Center user, IAM Identity Center group, or IAM user). This parameter is required if you specify `identityId`.

Valid Values: USER | GROUP | IAM

maxResults

The maximum number of results to return for each paginated request.

Default: 50

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `[A-Za-z0-9+/=]+`

resourceId

The ID of the resource. This parameter is required if you specify `resourceType`.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

resourceType

The type of resource (portal or project). This parameter is required if you specify `resourceId`.

Valid Values: PORTAL | PROJECT

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "accessPolicySummaries": [
    {
      "creationDate": number,
      "id": "string",
      "identity": {
        "group": {
          "id": "string"
        }
      }
    }
  ],
}
```

```
    "iamRole": {
      "arn": "string"
    },
    "iamUser": {
      "arn": "string"
    },
    "user": {
      "id": "string"
    }
  },
  "lastUpdateDate": number,
  "permission": "string",
  "resource": {
    "portal": {
      "id": "string"
    },
    "project": {
      "id": "string"
    }
  }
}
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

accessPolicySummaries

A list that summarizes each access policy.

Type: Array of [AccessPolicySummary](#) objects

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListActions

Retrieves a paginated list of actions for a specific target resource.

Request Syntax

```
GET /actions?  
maxResults=maxResults&nextToken=nextToken&targetResourceId=targetResourceId&targetResourceType=  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return for each paginated request.

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `[A-Za-z0-9+/=]+`

targetResourceId

The ID of the target resource.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

targetResourceType

The type of resource.

Valid Values: ASSET

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "actionSummaries": [
    {
      "actionDefinitionId": "string",
      "actionId": "string",
      "targetResource": {
        "assetId": "string"
      }
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

actionSummaries

A list that summarizes the actions associated with the specified asset.

Type: Array of [ActionSummary](#) objects

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListAssetModelCompositeModels

Retrieves a paginated list of composite models associated with the asset model

Request Syntax

```
GET /asset-models/assetModelId/composite-models?  
assetModelVersion=assetModelVersion&maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

assetModelId

The ID of the asset model. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$ | ^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

assetModelVersion

The version alias that specifies the latest or active version of the asset model. The details are returned in the response. The default value is LATEST. See [Asset model versions](#) in the *Amazon IoT SiteWise User Guide*.

Pattern: `^(LATEST|ACTIVE)$`

maxResults

The maximum number of results to return for each paginated request.

Default: 50

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "assetModelCompositeModelSummaries": [
    {
      "description": "string",
      "externalId": "string",
      "id": "string",
      "name": "string",
      "path": [
        {
          "id": "string",
          "name": "string"
        }
      ],
      "type": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assetModelCompositeModelSummaries](#)

A list that summarizes each composite model.

Type: Array of [AssetModelCompositeModelSummary](#) objects

[nextToken](#)

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

- **BASE** – The list includes only base asset model properties for a given asset model ID.

Default: BASE

Valid Values: ALL | BASE

maxResults

The maximum number of results to return for each paginated request. If not specified, the default value is 50.

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "assetModelPropertySummaries": [
    {
      "assetModelCompositeModelId": "string",
      "dataType": "string",
      "dataTypeSpec": "string",
      "externalId": "string",
      "id": "string",
      "name": "string",
      "path": [
        {
          "id": "string",
          "name": "string"
        }
      ]
    }
  ]
}
```

```
],
  "type": {
    "attribute": {
      "defaultValue": "string"
    },
    "measurement": {
      "processingConfig": {
        "forwardingConfig": {
          "state": "string"
        }
      }
    },
    "metric": {
      "expression": "string",
      "processingConfig": {
        "computeLocation": "string"
      }
    },
    "variables": [
      {
        "name": "string",
        "value": {
          "hierarchyId": "string",
          "propertyId": "string",
          "propertyPath": [
            {
              "id": "string",
              "name": "string"
            }
          ]
        }
      }
    ],
    "window": {
      "tumbling": {
        "interval": "string",
        "offset": "string"
      }
    }
  },
  "transform": {
    "expression": "string",
    "processingConfig": {
      "computeLocation": "string",
      "forwardingConfig": {
```

```

        "state": "string"
    }
},
"variables": [
    {
        "name": "string",
        "value": {
            "hierarchyId": "string",
            "propertyId": "string",
            "propertyPath": [
                {
                    "id": "string",
                    "name": "string"
                }
            ]
        }
    }
]
},
"unit": "string"
}
],
"nextToken": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assetModelPropertySummaries](#)

A list that summarizes the properties associated with the specified asset model.

Type: Array of [AssetModelPropertySummary](#) objects

[nextToken](#)

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `[A-Za-z0-9+/=]+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListAssetModels

Retrieves a paginated list of summaries of all asset models.

Request Syntax

```
GET /asset-models?  
assetModelTypes=assetModelTypes&assetModelVersion=assetModelVersion&maxResults=maxResults&nextToken=nextToken  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

assetModelTypes

The type of asset model. If you don't provide an `assetModelTypes`, all types of asset models are returned.

- **ASSET_MODEL** – An asset model that you can use to create assets. Can't be included as a component in another asset model.
- **COMPONENT_MODEL** – A reusable component that you can include in the composite models of other asset models. You can't create assets directly from this type of asset model.

Valid Values: ASSET_MODEL | COMPONENT_MODEL

assetModelVersion

The version alias that specifies the latest or active version of the asset model. The details are returned in the response. The default value is LATEST. See [Asset model versions](#) in the *Amazon IoT SiteWise User Guide*.

Pattern: `^(LATEST|ACTIVE)$`

maxResults

The maximum number of results to return for each paginated request.

Default: 50

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "assetModelSummaries": [
    {
      "arn": "string",
      "assetModelType": "string",
      "creationDate": number,
      "description": "string",
      "externalId": "string",
      "id": "string",
      "lastUpdateDate": number,
      "name": "string",
      "status": {
        "error": {
          "code": "string",
          "details": [
            {
              "code": "string",
              "message": "string"
            }
          ],
          "message": "string"
        },
        "state": "string"
      },
      "version": "string"
    }
  ]
}
```

```
    }  
  ],  
  "nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assetModelSummaries

A list that summarizes each asset model.

Type: Array of [AssetModelSummary](#) objects

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListAssetProperties

Retrieves a paginated list of properties associated with an asset. If you update properties associated with the model before you finish listing all the properties, you need to start all over again.

Request Syntax

```
GET /assets/assetId/properties?filter=filter&maxResults=maxResults&nextToken=nextToken
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

assetId

The ID of the asset. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|
^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.]*[a-zA-Z0-9]+`

Required: Yes

filter

Filters the requested list of asset properties. You can choose one of the following options:

- ALL – The list includes all asset properties for a given asset model ID.
- BASE – The list includes only base asset properties for a given asset model ID.

Default: BASE

Valid Values: ALL | BASE

maxResults

The maximum number of results to return for each paginated request. If not specified, the default value is 50.

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "assetPropertySummaries": [
    {
      "alias": "string",
      "assetCompositeModelId": "string",
      "externalId": "string",
      "id": "string",
      "notification": {
        "state": "string",
        "topic": "string"
      },
      "path": [
        {
          "id": "string",
          "name": "string"
        }
      ],
      "unit": "string"
    }
  ],
  "nextToken": "string"
}
```


Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assetPropertySummaries

A list that summarizes the properties associated with the specified asset.

Type: Array of [AssetPropertySummary](#) objects

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListAssetRelationships

Retrieves a paginated list of asset relationships for an asset. You can use this operation to identify an asset's root asset and all associated assets between that asset and its root.

Request Syntax

```
GET /assets/assetId/assetRelationships?  
maxResults=maxResults&nextToken=nextToken&traversalType=traversalType HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

assetId

The ID of the asset. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

maxResults

The maximum number of results to return for each paginated request.

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `[A-Za-z0-9+/=]+`

traversalType

The type of traversal to use to identify asset relationships. Choose the following option:

- `PATH_TO_ROOT` – Identify the asset's parent assets up to the root asset. The asset that you specify in `assetId` is the first result in the list of `assetRelationshipSummaries`, and the root asset is the last result.

Valid Values: `PATH_TO_ROOT`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "assetRelationshipSummaries": [
    {
      "hierarchyInfo": {
        "childAssetId": "string",
        "parentAssetId": "string"
      },
      "relationshipType": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assetRelationshipSummaries](#)

A list that summarizes each asset relationship.

Type: Array of [AssetRelationshipSummary](#) objects

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `[A-Za-z0-9+/=]+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListAssets

Retrieves a paginated list of asset summaries.

You can use this operation to do the following:

- List assets based on a specific asset model.
- List top-level assets.

You can't use this operation to list all assets. To retrieve summaries for all of your assets, use [ListAssetModels](#) to get all of your asset model IDs. Then, use ListAssets to get all assets for each asset model.

Request Syntax

```
GET /assets?  
assetModelId=assetModelId&filter=filter&maxResults=maxResults&nextToken=nextToken  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[assetModelId](#)

The ID of the asset model by which to filter the list of assets. This parameter is required if you choose ALL for `filter`. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|
^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

[filter](#)

The filter for the requested list of assets. Choose one of the following options:

- ALL – The list includes all assets for a given asset model ID. The `assetModelId` parameter is required if you filter by ALL.

- TOP_LEVEL – The list includes only top-level assets in the asset hierarchy tree.

Default: ALL

Valid Values: ALL | TOP_LEVEL

maxResults

The maximum number of results to return for each paginated request.

Default: 50

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "assetSummaries": [
    {
      "arn": "string",
      "assetModelId": "string",
      "creationDate": number,
      "description": "string",
      "externalId": "string",
      "hierarchies": [
        {
          "externalId": "string",
          "id": "string",
          "name": "string"
        }
      ]
    }
  ]
}
```



```
    }
  ],
  "id": "string",
  "lastUpdateDate": number,
  "name": "string",
  "status": {
    "error": {
      "code": "string",
      "details": [
        {
          "code": "string",
          "message": "string"
        }
      ],
      "message": "string"
    },
    "state": "string"
  }
}
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assetSummaries

A list that summarizes each asset.

Type: Array of [AssetSummary](#) objects

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListAssociatedAssets

Retrieves a paginated list of associated assets.

You can use this operation to do the following:

- CHILD - List all child assets associated to the asset.
- PARENT - List the asset's parent asset.

Request Syntax

```
GET /assets/assetId/hierarchies?  
hierarchyId=hierarchyId&maxResults=maxResults&nextToken=nextToken&traversalDirection=traversalD  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

assetId

The ID of the asset to query. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|
^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.]*[a-zA-Z0-9]+`

Required: Yes

hierarchyId

(Optional) If you don't provide a `hierarchyId`, all the immediate assets in the `traversalDirection` will be returned.

The ID of the hierarchy by which child assets are associated to the asset. (This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.)


```
{
  "arn": "string",
  "assetModelId": "string",
  "creationDate": number,
  "description": "string",
  "externalId": "string",
  "hierarchies": [
    {
      "externalId": "string",
      "id": "string",
      "name": "string"
    }
  ],
  "id": "string",
  "lastUpdateDate": number,
  "name": "string",
  "status": {
    "error": {
      "code": "string",
      "details": [
        {
          "code": "string",
          "message": "string"
        }
      ],
      "message": "string"
    },
    "state": "string"
  }
}
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assetSummaries

A list that summarizes the associated assets.

Type: Array of [AssociatedAssetsSummary](#) objects

[nextToken](#)

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListBulkImportJobs

Retrieves a paginated list of bulk import job requests. For more information, see [List bulk import jobs \(Amazon CLI\)](#) in the *Amazon IoT SiteWise User Guide*.

Request Syntax

```
GET /jobs?filter=filter&maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

filter

You can use a filter to select the bulk import jobs that you want to retrieve.

Valid Values: ALL | PENDING | RUNNING | CANCELLED | FAILED | COMPLETED_WITH_FAILURES | COMPLETED

maxResults

The maximum number of results to return for each paginated request.

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "jobSummaries": [
    {
      "id": "string",
      "name": "string",
      "status": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

jobSummaries

One or more job summaries to list.

Type: Array of [JobSummary](#) objects

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListCompositionRelationships

Retrieves a paginated list of composition relationships for an asset model of type COMPONENT_MODEL.

Request Syntax

```
GET /asset-models/assetModelId/composition-relationships?  
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

assetModelId

The ID of the asset model. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

maxResults

The maximum number of results to return for each paginated request.

Default: 50

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `[A-Za-z0-9+/=]+`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "compositionRelationshipSummaries": [
    {
      "assetModelCompositeModelId": "string",
      "assetModelCompositeModelType": "string",
      "assetModelId": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[compositionRelationshipSummaries](#)

A list that summarizes each composition relationship.

Type: Array of [CompositionRelationshipSummary](#) objects

[nextToken](#)

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListDashboards

Retrieves a paginated list of dashboards for an Amazon IoT SiteWise Monitor project.

Request Syntax

```
GET /dashboards?maxResults=maxResults&nextToken=nextToken&projectId=projectId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return for each paginated request.

Default: 50

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

projectId

The ID of the project.

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "dashboardSummaries": [
    {
      "creationDate": number,
      "description": "string",
      "id": "string",
      "lastUpdateDate": number,
      "name": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

dashboardSummaries

A list that summarizes each dashboard in the project.

Type: Array of [DashboardSummary](#) objects

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListDatasets

Retrieves a paginated list of datasets for a specific target resource.

Request Syntax

```
GET /datasets?maxResults=maxResults&nextToken=nextToken&sourceType=sourceType HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return for each paginated request.

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token for the next set of results, or null if there are no additional results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

sourceType

The type of data source for the dataset.

Valid Values: KENDRA

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{
  "datasetSummaries": [
    {
      "arn": "string",
      "creationDate": number,
      "description": "string",
      "id": "string",
      "lastUpdateDate": number,
      "name": "string",
      "status": {
        "error": {
          "code": "string",
          "details": [
            {
              "code": "string",
              "message": "string"
            }
          ],
          "message": "string"
        },
        "state": "string"
      }
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

datasetSummaries

A list that summarizes the dataset response.

Type: Array of [DatasetSummary](#) objects

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)

- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListGateways

Retrieves a paginated list of gateways.

Request Syntax

```
GET /20200301/gateways?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return for each paginated request.

Default: 50

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "gatewaySummaries": [
    {
      "creationDate": number,
```



```
    "gatewayCapabilitySummaries": [  
      {  
        "capabilityNamespace": "string",  
        "capabilitySyncStatus": "string"  
      }  
    ],  
    "gatewayId": "string",  
    "gatewayName": "string",  
    "gatewayPlatform": {  
      "greengrass": {  
        "groupArn": "string"  
      },  
      "greengrassV2": {  
        "coreDeviceOperatingSystem": "string",  
        "coreDeviceThingName": "string"  
      },  
      "siemensIE": {  
        "iotCoreThingName": "string"  
      }  
    },  
    "gatewayVersion": "string",  
    "lastUpdateDate": number  
  }  
],  
"nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

gatewaySummaries

A list that summarizes each gateway.

Type: Array of [GatewaySummary](#) objects

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListPortals

Retrieves a paginated list of Amazon IoT SiteWise Monitor portals.

Request Syntax

```
GET /portals?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return for each paginated request.

Default: 50

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "portalSummaries": [
    {
      "creationDate": number,
```

```
"description": "string",
"id": "string",
"lastUpdateDate": number,
"name": "string",
"portalType": "string",
"roleArn": "string",
"startUrl": "string",
"status": {
  "error": {
    "code": "string",
    "message": "string"
  },
  "state": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

portalSummaries

A list that summarizes each portal.

Type: Array of [PortalSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListProjectAssets

Retrieves a paginated list of assets associated with an Amazon IoT SiteWise Monitor project.

Request Syntax

```
GET /projects/projectId/assets?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return for each paginated request.

Default: 50

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

projectId

The ID of the project.

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "assetIds": [ "string" ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assetIds

A list that contains the IDs of each asset associated with the project.

Type: Array of strings

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `[A-Za-z0-9+/=]+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListProjects

Retrieves a paginated list of projects for an Amazon IoT SiteWise Monitor portal.

Request Syntax

```
GET /projects?maxResults=maxResults&nextToken=nextToken&portalId=portalId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return for each paginated request.

Default: 50

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

portalId

The ID of the portal.

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "projectSummaries": [
    {
      "creationDate": number,
      "description": "string",
      "id": "string",
      "lastUpdateDate": number,
      "name": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

projectSummaries

A list that summarizes each project in the portal.

Type: Array of [ProjectSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListTagsForResource

Retrieves the list of tags for an Amazon IoT SiteWise resource.

Request Syntax

```
GET /tags?resourceArn=resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The [ARN](#) of the resource.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

The list of key-value pairs that contain metadata for the resource. For more information, see [Tagging your Amazon IoT SiteWise resources](#) in the *Amazon IoT SiteWise User Guide*.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

UnauthorizedException

You are not authorized.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListTimeSeries

Retrieves a paginated list of time series (data streams).

Request Syntax

```
GET /timeseries/?
aliasPrefix=aliasPrefix&assetId=assetId&maxResults=maxResults&nextToken=nextToken&timeSeriesType=timeSeriesType
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

aliasPrefix

The alias prefix of the time series.

Length Constraints: Minimum length of 1.

Pattern: `[^\u0000-\u001F\u007F]+`

assetId

The ID of the asset in which the asset property was created. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

maxResults

The maximum number of results to return for each paginated request.

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token to be used for the next set of paginated results.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

timeSeriesType

The type of the time series. The time series type can be one of the following values:

- ASSOCIATED – The time series is associated with an asset property.
- DISASSOCIATED – The time series isn't associated with any asset property.

Valid Values: ASSOCIATED | DISASSOCIATED

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "TimeSeriesSummaries": [
    {
      "alias": "string",
      "assetId": "string",
      "dataType": "string",
      "dataTypeSpec": "string",
      "propertyId": "string",
      "timeSeriesArn": "string",
      "timeSeriesCreationDate": number,
      "timeSeriesId": "string",
      "timeSeriesLastUpdateDate": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token for the next set of results, or null if there are no additional results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: [A-Za-z0-9+/=]+

TimeSeriesSummaries

One or more time series summaries to list.

Type: Array of [TimeSeriesSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

PutDefaultEncryptionConfiguration

Sets the default encryption configuration for the Amazon account. For more information, see [Key management](#) in the *Amazon IoT SiteWise User Guide*.

Request Syntax

```
POST /configuration/account/encryption HTTP/1.1
Content-type: application/json

{
  "encryptionType": "string",
  "kmsKeyId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[encryptionType](#)

The type of encryption used for the encryption configuration.

Type: String

Valid Values: SITEWISE_DEFAULT_ENCRYPTION | KMS_BASED_ENCRYPTION

Required: Yes

[kmsKeyId](#)

The Key ID of the customer managed key used for Amazon KMS encryption. This is required if you use KMS_BASED_ENCRYPTION.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "configurationStatus": {
    "error": {
      "code": "string",
      "message": "string"
    },
    "state": "string"
  },
  "encryptionType": "string",
  "kmsKeyArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configurationStatus

The status of the account configuration. This contains the ConfigurationState. If there is an error, it also contains the ErrorDetails.

Type: [ConfigurationStatus](#) object

encryptionType

The type of encryption used for the encryption configuration.

Type: String

Valid Values: SITEWISE_DEFAULT_ENCRYPTION | KMS_BASED_ENCRYPTION

kmsKeyArn

The Key ARN of the Amazon KMS key used for Amazon KMS encryption if you use KMS_BASED_ENCRYPTION.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

PutLoggingOptions

Sets logging options for Amazon IoT SiteWise.

Request Syntax

```
PUT /logging HTTP/1.1
Content-type: application/json

{
  "loggingOptions": {
    "level": "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

loggingOptions

The logging options to set.

Type: [LoggingOptions](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

PutStorageConfiguration

Configures storage settings for Amazon IoT SiteWise.

Request Syntax

```
POST /configuration/account/storage HTTP/1.1
Content-type: application/json
```

```
{
  "disallowIngestNullNaN": boolean,
  "disassociatedDataStorage": "string",
  "multiLayerStorage": {
    "customerManagedS3Storage": {
      "roleArn": "string",
      "s3ResourceArn": "string"
    }
  },
  "retentionPeriod": {
    "numberOfDays": number,
    "unlimited": boolean
  },
  "storageType": "string",
  "warmTier": "string",
  "warmTierRetentionPeriod": {
    "numberOfDays": number,
    "unlimited": boolean
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

disallowIngestNullNaN

Describes the configuration for ingesting NULL and NaN data. By default the feature is allowed. The feature is disallowed if the value is `true`.

Type: Boolean

Required: No

disassociatedDataStorage

Contains the storage configuration for time series (data streams) that aren't associated with asset properties. The `disassociatedDataStorage` can be one of the following values:

- **ENABLED** – Amazon IoT SiteWise accepts time series that aren't associated with asset properties.

Important

After the `disassociatedDataStorage` is enabled, you can't disable it.

- **DISABLED** – Amazon IoT SiteWise doesn't accept time series (data streams) that aren't associated with asset properties.

For more information, see [Data streams](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

multiLayerStorage

Identifies a storage destination. If you specified `MULTI_LAYER_STORAGE` for the storage type, you must specify a `MultiLayerStorage` object.

Type: [MultiLayerStorage](#) object

Required: No

retentionPeriod

The number of days your data is kept in the hot tier. By default, your data is kept indefinitely in the hot tier.

Type: [RetentionPeriod](#) object

Required: No

storageType

The storage tier that you specified for your data. The `storageType` parameter can be one of the following values:

- `SITWISE_DEFAULT_STORAGE` – Amazon IoT SiteWise saves your data into the hot tier. The hot tier is a service-managed database.
- `MULTI_LAYER_STORAGE` – Amazon IoT SiteWise saves your data in both the cold tier and the hot tier. The cold tier is a customer-managed Amazon S3 bucket.

Type: String

Valid Values: `SITWISE_DEFAULT_STORAGE` | `MULTI_LAYER_STORAGE`

Required: Yes

warmTier

A service managed storage tier optimized for analytical queries. It stores periodically uploaded, buffered and historical data ingested with the `CreaeBulkImportJob` API.

Type: String

Valid Values: `ENABLED` | `DISABLED`

Required: No

warmTierRetentionPeriod

Set this period to specify how long your data is stored in the warm tier before it is deleted. You can set this only if cold tier is enabled.

Type: [WarmTierRetentionPeriod](#) object

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "configurationStatus": {
```

```
    "error": {
      "code": "string",
      "message": "string"
    },
    "state": "string"
  },
  "disallowIngestNullNaN": boolean,
  "disassociatedDataStorage": "string",
  "multiLayerStorage": {
    "customerManagedS3Storage": {
      "roleArn": "string",
      "s3ResourceArn": "string"
    }
  },
  "retentionPeriod": {
    "numberOfDays": number,
    "unlimited": boolean
  },
  "storageType": "string",
  "warmTier": "string",
  "warmTierRetentionPeriod": {
    "numberOfDays": number,
    "unlimited": boolean
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configurationStatus

Contains current status information for the configuration.

Type: [ConfigurationStatus](#) object

disallowIngestNullNaN

Describes the configuration for ingesting NULL and NaN data. By default the feature is allowed. The feature is disallowed if the value is `true`.

Type: Boolean

disassociatedDataStorage

Contains the storage configuration for time series (data streams) that aren't associated with asset properties. The `disassociatedDataStorage` can be one of the following values:

- **ENABLED** – Amazon IoT SiteWise accepts time series that aren't associated with asset properties.

Important

After the `disassociatedDataStorage` is enabled, you can't disable it.

- **DISABLED** – Amazon IoT SiteWise doesn't accept time series (data streams) that aren't associated with asset properties.

For more information, see [Data streams](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Valid Values: ENABLED | DISABLED

multiLayerStorage

Contains information about the storage destination.

Type: [MultiLayerStorage](#) object

retentionPeriod

The number of days your data is kept in the hot tier. By default, your data is kept indefinitely in the hot tier.

Type: [RetentionPeriod](#) object

storageType

The storage tier that you specified for your data. The `storageType` parameter can be one of the following values:

- **SITWISE_DEFAULT_STORAGE** – Amazon IoT SiteWise saves your data into the hot tier. The hot tier is a service-managed database.
- **MULTI_LAYER_STORAGE** – Amazon IoT SiteWise saves your data in both the cold tier and the hot tier. The cold tier is a customer-managed Amazon S3 bucket.

Type: String

Valid Values: SITEWISE_DEFAULT_STORAGE | MULTI_LAYER_STORAGE

warmTier

A service managed storage tier optimized for analytical queries. It stores periodically uploaded, buffered and historical data ingested with the CreateBulkImportJob API.

Type: String

Valid Values: ENABLED | DISABLED

warmTierRetentionPeriod

Set this period to specify how long your data is stored in the warm tier before it is deleted. You can set this only if cold tier is enabled.

Type: [WarmTierRetentionPeriod](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceAlreadyExistsException

The resource already exists.

HTTP Status Code: 409

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

TagResource

Adds tags to an Amazon IoT SiteWise resource. If a tag already exists for the resource, this operation updates the tag's value.

Request Syntax

```
POST /tags?resourceArn=resourceArn HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The [ARN](#) of the resource to tag.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

A list of key-value pairs that contain metadata for the resource. For more information, see [Tagging your Amazon IoT SiteWise resources](#) in the *Amazon IoT SiteWise User Guide*.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

TooManyTagsException

You've reached the quota for the number of tags allowed for a resource. For more information, see [Tag naming limits and requirements](#) in the *Amazon General Reference*.

HTTP Status Code: 400

UnauthorizedException

You are not authorized.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UntagResource

Removes a tag from an Amazon IoT SiteWise resource.

Request Syntax

```
DELETE /tags?resourceArn=resourceArn&tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The [ARN](#) of the resource to untag.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

tagKeys

A list of keys for tags to remove from the resource.

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

UnauthorizedException

You are not authorized.

HTTP Status Code: 401

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateAccessPolicy

Updates an existing access policy that specifies an identity's access to an Amazon IoT SiteWise Monitor portal or project resource.

Request Syntax

```
PUT /access-policies/accessPolicyId HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "accessPolicyIdentity": {
    "group": {
      "id": "string"
    },
    "iamRole": {
      "arn": "string"
    },
    "iamUser": {
      "arn": "string"
    },
    "user": {
      "id": "string"
    }
  },
  "accessPolicyPermission": "string",
  "accessPolicyResource": {
    "portal": {
      "id": "string"
    },
    "project": {
      "id": "string"
    }
  },
  "clientToken": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

accessPolicyId

The ID of the access policy.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

accessPolicyIdentity

The identity for this access policy. Choose an IAM Identity Center user, an IAM Identity Center group, or an IAM user.

Type: [Identity](#) object

Required: Yes

accessPolicyPermission

The permission level for this access policy. Note that a project ADMINISTRATOR is also known as a project owner.

Type: String

Valid Values: ADMINISTRATOR | VIEWER

Required: Yes

accessPolicyResource

The Amazon IoT SiteWise Monitor resource for this access policy. Choose either a portal or a project.

Type: [Resource](#) object

Required: Yes

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

assetExternalId

An external ID to assign to the asset. The asset must not already have an external ID. The external ID must be unique within your Amazon Web Services account. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

assetName

A friendly name for the asset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "assetStatus": {
    "error": {
      "code": "string",
      "details": [
        {
          "code": "string",
          "message": "string"
        }
      ],
      "message": "string"
    },
    "state": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

assetStatus

The status of the asset, which contains a state (UPDATING after successfully calling this operation) and any error message.

Type: [AssetStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceAlreadyExistsException

The resource already exists.

HTTP Status Code: 409

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)

- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateAssetModel

Updates an asset model and all of the assets that were created from the model. Each asset created from the model inherits the updated asset model's property and hierarchy definitions. For more information, see [Updating assets and models](#) in the *Amazon IoT SiteWise User Guide*.

Important

If you remove a property from an asset model, Amazon IoT SiteWise deletes all previous data for that property. You can't change the type or data type of an existing property. To replace an existing asset model property with a new one with the same name, do the following:

1. Submit an `UpdateAssetModel` request with the entire existing property removed.
2. Submit a second `UpdateAssetModel` request that includes the new property. The new asset property will have the same name as the previous one and Amazon IoT SiteWise will generate a new unique `id`.

Request Syntax

```
PUT /asset-models/assetModelId HTTP/1.1
If-Match: ifMatch
If-None-Match: ifNoneMatch
Match-For-Version-Type: matchForVersionType
Content-type: application/json
```

```
{
  "assetModelCompositeModels": [
    {
      "description": "string",
      "externalId": "string",
      "id": "string",
      "name": "string",
      "properties": [
        {
          "dataType": "string",
          "dataTypeSpec": "string",
          "externalId": "string",
          "id": "string",
```

```
"name": "string",
"path": [
  {
    "id": "string",
    "name": "string"
  }
],
"type": {
  "attribute": {
    "defaultValue": "string"
  },
  "measurement": {
    "processingConfig": {
      "forwardingConfig": {
        "state": "string"
      }
    }
  },
  "metric": {
    "expression": "string",
    "processingConfig": {
      "computeLocation": "string"
    }
  },
  "variables": [
    {
      "name": "string",
      "value": {
        "hierarchyId": "string",
        "propertyId": "string",
        "propertyPath": [
          {
            "id": "string",
            "name": "string"
          }
        ]
      }
    }
  ],
  "window": {
    "tumbling": {
      "interval": "string",
      "offset": "string"
    }
  }
}
```

```

    },
    "transform": {
      "expression": "string",
      "processingConfig": {
        "computeLocation": "string",
        "forwardingConfig": {
          "state": "string"
        }
      }
    },
    "variables": [
      {
        "name": "string",
        "value": {
          "hierarchyId": "string",
          "propertyId": "string",
          "propertyPath": [
            {
              "id": "string",
              "name": "string"
            }
          ]
        }
      }
    ]
  },
  "unit": "string"
}
],
"type": "string"
}
],
"assetModelDescription": "string",
"assetModelExternalId": "string",
"assetModelHierarchies": [
  {
    "childAssetModelId": "string",
    "externalId": "string",
    "id": "string",
    "name": "string"
  }
],
"assetModelName": "string",
"assetModelProperties": [

```

```
{
  "dataType": "string",
  "dataTypeSpec": "string",
  "externalId": "string",
  "id": "string",
  "name": "string",
  "path": [
    {
      "id": "string",
      "name": "string"
    }
  ],
  "type": {
    "attribute": {
      "defaultValue": "string"
    },
    "measurement": {
      "processingConfig": {
        "forwardingConfig": {
          "state": "string"
        }
      }
    },
    "metric": {
      "expression": "string",
      "processingConfig": {
        "computeLocation": "string"
      }
    },
    "variables": [
      {
        "name": "string",
        "value": {
          "hierarchyId": "string",
          "propertyId": "string",
          "propertyPath": [
            {
              "id": "string",
              "name": "string"
            }
          ]
        }
      }
    ]
  },
  "window": {
```

```
        "tumbling": {
            "interval": "string",
            "offset": "string"
        }
    },
    "transform": {
        "expression": "string",
        "processingConfig": {
            "computeLocation": "string",
            "forwardingConfig": {
                "state": "string"
            }
        }
    },
    "variables": [
        {
            "name": "string",
            "value": {
                "hierarchyId": "string",
                "propertyId": "string",
                "propertyPath": [
                    {
                        "id": "string",
                        "name": "string"
                    }
                ]
            }
        }
    ]
},
"unit": "string"
}
],
"clientToken": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

assetModelId

The ID of the asset model to update. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

ifMatch

The expected current entity tag (ETag) for the asset model's latest or active version (specified using `matchForVersionType`). The update request is rejected if the tag does not match the latest or active version's current entity tag. See [Optimistic locking for asset model writes](#) in the *Amazon IoT SiteWise User Guide*.

Pattern: `^[\\w-]{43}$`

ifNoneMatch

Accepts `*` to reject the update request if an active version (specified using `matchForVersionType` as `ACTIVE`) already exists for the asset model.

Pattern: `*`

matchForVersionType

Specifies the asset model version type (`LATEST` or `ACTIVE`) used in conjunction with `If-Match` or `If-None-Match` headers to determine the target ETag for the update operation.

Valid Values: `LATEST` | `ACTIVE`

Request Body

The request accepts the following data in JSON format.

assetModelCompositeModels

The composite models that are part of this asset model. It groups properties (such as attributes, measurements, transforms, and metrics) and child composite models that model parts of your

industrial equipment. Each composite model has a type that defines the properties that the composite model supports. Use composite models to define alarms on this asset model.

Note

When creating custom composite models, you need to use [CreateAssetModelCompositeModel](#). For more information, see [Creating custom composite models \(Components\)](#) in the *Amazon IoT SiteWise User Guide*.

Type: Array of [AssetModelCompositeModel](#) objects

Required: No

assetModelDescription

A description for the asset model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

assetModelExternalId

An external ID to assign to the asset model. The asset model must not already have an external ID. The external ID must be unique within your Amazon Web Services account. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

assetModelHierarchies

The updated hierarchy definitions of the asset model. Each hierarchy specifies an asset model whose assets can be children of any other assets created from this asset model. For more information, see [Asset hierarchies](#) in the *Amazon IoT SiteWise User Guide*.

You can specify up to 10 hierarchies per asset model. For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

Type: Array of [AssetModelHierarchy](#) objects

Required: No

[assetModelName](#)

A unique name for the asset model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

[assetModelProperties](#)

The updated property definitions of the asset model. For more information, see [Asset properties](#) in the *Amazon IoT SiteWise User Guide*.

You can specify up to 200 properties per asset model. For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

Type: Array of [AssetModelProperty](#) objects

Required: No

[clientToken](#)

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "assetModelStatus": {
    "error": {
      "code": "string",
      "details": [
        {
          "code": "string",
          "message": "string"
        }
      ],
      "message": "string"
    },
    "state": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

assetModelStatus

The status of the asset model, which contains a state (UPDATING after successfully calling this operation) and any error message.

Type: [AssetModelStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

PreconditionFailedException

The precondition in one or more of the request-header fields evaluated to FALSE.

HTTP Status Code: 412

ResourceAlreadyExistsException

The resource already exists.

HTTP Status Code: 409

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateAssetModelCompositeModel

Updates a composite model and all of the assets that were created from the model. Each asset created from the model inherits the updated asset model's property and hierarchy definitions. For more information, see [Updating assets and models](#) in the *Amazon IoT SiteWise User Guide*.

Important

If you remove a property from a composite asset model, Amazon IoT SiteWise deletes all previous data for that property. You can't change the type or data type of an existing property.

To replace an existing composite asset model property with a new one with the same name, do the following:

1. Submit an `UpdateAssetModelCompositeModel` request with the entire existing property removed.
2. Submit a second `UpdateAssetModelCompositeModel` request that includes the new property. The new asset property will have the same name as the previous one and Amazon IoT SiteWise will generate a new unique id.

Request Syntax

```
PUT /asset-models/assetModelId/composite-models/assetModelCompositeModelId HTTP/1.1
```

```
If-Match: ifMatch
```

```
If-None-Match: ifNoneMatch
```

```
Match-For-Version-Type: matchForVersionType
```

```
Content-type: application/json
```

```
{
  "assetModelCompositeModelDescription": "string",
  "assetModelCompositeModelExternalId": "string",
  "assetModelCompositeModelName": "string",
  "assetModelCompositeModelProperties": [
    {
      "dataType": "string",
      "dataTypeSpec": "string",
      "externalId": "string",
      "id": "string",
      "name": "string",
```

```
"path": [
  {
    "id": "string",
    "name": "string"
  }
],
"type": {
  "attribute": {
    "defaultValue": "string"
  },
  "measurement": {
    "processingConfig": {
      "forwardingConfig": {
        "state": "string"
      }
    }
  },
  "metric": {
    "expression": "string",
    "processingConfig": {
      "computeLocation": "string"
    },
    "variables": [
      {
        "name": "string",
        "value": {
          "hierarchyId": "string",
          "propertyId": "string",
          "propertyPath": [
            {
              "id": "string",
              "name": "string"
            }
          ]
        }
      }
    ]
  },
  "window": {
    "tumbling": {
      "interval": "string",
      "offset": "string"
    }
  }
},
```



```

    "transform": {
      "expression": "string",
      "processingConfig": {
        "computeLocation": "string",
        "forwardingConfig": {
          "state": "string"
        }
      },
      "variables": [
        {
          "name": "string",
          "value": {
            "hierarchyId": "string",
            "propertyId": "string",
            "propertyPath": [
              {
                "id": "string",
                "name": "string"
              }
            ]
          }
        }
      ]
    },
    "unit": "string"
  },
  "clientToken": "string"
}

```

URI Request Parameters

The request uses the following URI parameters.

assetModelCompositeModelId

The ID of a composite model on this asset model.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

assetModelCompositeModelExternalId

An external ID to assign to the asset model. You can only set the external ID of the asset model if it wasn't set when it was created, or you're setting it to the exact same thing as when it was created.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

assetModelCompositeModelName

A unique name for the composite model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

assetModelCompositeModelProperties

The property definitions of the composite model. For more information, see [Inline custom composite models](#) in the *Amazon IoT SiteWise User Guide*.

You can specify up to 200 properties per composite model. For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

Type: Array of [AssetModelProperty](#) objects

Required: No

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "assetModelCompositeModelPath": [
    {
      "id": "string",
      "name": "string"
    }
  ],
  "assetModelStatus": {
    "error": {
      "code": "string",
      "details": [
        {
          "code": "string",
          "message": "string"
        }
      ],
      "message": "string"
    },
    "state": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

[assetModelCompositeModelPath](#)

The path to the composite model listing the parent composite models.

Type: Array of [AssetModelCompositeModelPathSegment](#) objects

[assetModelStatus](#)

Contains current status information for an asset model. For more information, see [Asset and model states](#) in the *Amazon IoT SiteWise User Guide*.

Type: [AssetModelStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

PreconditionFailedException

The precondition in one or more of the request-header fields evaluated to FALSE.

HTTP Status Code: 412

ResourceAlreadyExistsException

The resource already exists.

HTTP Status Code: 409

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

propertyId

The ID of the asset property to be updated. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

propertyAlias

The alias that identifies the property, such as an OPC-UA server data stream path (for example, `/company/windfarm/3/turbine/7/temperature`). For more information, see [Mapping industrial data streams to asset properties](#) in the *Amazon IoT SiteWise User Guide*.

If you omit this parameter, the alias is removed from the property.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

propertyNotificationState

The MQTT notification state (enabled or disabled) for this asset property. When the notification state is enabled, Amazon IoT SiteWise publishes property value updates to a unique MQTT topic. For more information, see [Interacting with other services](#) in the *Amazon IoT SiteWise User Guide*.

If you omit this parameter, the notification state is set to DISABLED.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

propertyUnit

The unit of measure (such as Newtons or RPM) of the asset property. If you don't specify a value for this parameter, the service uses the value of the `assetModelProperty` in the asset model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)

- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateDashboard

Updates an Amazon IoT SiteWise Monitor dashboard.

Request Syntax

```
PUT /dashboards/dashboardId HTTP/1.1  
Content-type: application/json
```

```
{  
  "clientToken": "string",  
  "dashboardDefinition": "string",  
  "dashboardDescription": "string",  
  "dashboardName": "string"  
}
```

URI Request Parameters

The request uses the following URI parameters.

dashboardId

The ID of the dashboard to update.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

dashboardDefinition

The new dashboard definition, as specified in a JSON literal.

- Amazon IoT SiteWise Monitor (Classic) see [Create dashboards \(Amazon CLI\)](#)
- Amazon IoT SiteWise Monitor (AI-aware) see [Create dashboards \(Amazon CLI\)](#)

in the *Amazon IoT SiteWise User Guide*

Type: String

Length Constraints: Minimum length of 0. Maximum length of 204800.

Pattern: `.+`

Required: Yes

dashboardDescription

A new description for the dashboard.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

dashboardName

A new friendly name for the dashboard.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateDataset

Updates a dataset.

Request Syntax

```
PUT /datasets/datasetId HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "datasetDescription": "string",
  "datasetName": "string",
  "datasetSource": {
    "sourceDetail": {
      "kendra": {
        "knowledgeBaseArn": "string",
        "roleArn": "string"
      }
    },
    "sourceFormat": "string",
    "sourceType": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

datasetId

The ID of the dataset.

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

datasetDescription

A description about the dataset, and its functionality.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9 _\-\#\$*!@]+`

Required: No

datasetName

The name of the dataset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^[a-zA-Z0-9 _\-\#\$*!@]+`

Required: Yes

datasetSource

The data source for the dataset.

Type: [DatasetSource](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "datasetArn": "string",
  "datasetId": "string",
  "datasetStatus": {
    "error": {
      "code": "string",
      "details": [
        {
          "code": "string",
          "message": "string"
        }
      ],
      "message": "string"
    },
    "state": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

[datasetArn](#)

The [ARN](#) of the dataset. The format is `arn:${Partition}:iotsitewise:${Region}:${Account}:dataset/${DatasetId}`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

datasetId

The ID of the dataset.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|
^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

datasetStatus

The status of the dataset. This contains the state and any error messages. State is UPDATING after a successful call to this API, and any associated error message. The state is ACTIVE when ready to use.

Type: [DatasetStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

UpdateGateway

Updates a gateway's name.

Request Syntax

```
PUT /20200301/gateways/gatewayId HTTP/1.1
Content-type: application/json
```

```
{
  "gatewayName": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

gatewayId

The ID of the gateway to update.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

gatewayName

A unique name for the gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateGatewayCapabilityConfiguration

Updates a gateway capability configuration or defines a new capability configuration. Each gateway capability defines data sources for a gateway. A capability configuration can contain multiple data source configurations. If you define OPC-UA sources for a gateway in the Amazon IoT SiteWise console, all of your OPC-UA sources are stored in one capability configuration. To list all capability configurations for a gateway, use [DescribeGateway](#).

Request Syntax

```
POST /20200301/gateways/gatewayId/capability HTTP/1.1
Content-type: application/json

{
  "capabilityConfiguration": "string",
  "capabilityNamespace": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

[gatewayId](#)

The ID of the gateway to be updated.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

[capabilityConfiguration](#)

The JSON document that defines the configuration for the gateway capability. For more information, see [Configuring data sources \(CLI\)](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10000000.

Required: Yes

capabilityNamespace

The namespace of the gateway capability configuration to be updated. For example, if you configure OPC-UA sources from the Amazon IoT SiteWise console, your OPC-UA capability configuration has the namespace `iotsitewise:opcuacollector:version`, where `version` is a number such as 1.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `^[a-zA-Z]+:[a-zA-Z]+:[0-9]+$`

Required: Yes

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "capabilityNamespace": "string",
  "capabilitySyncStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

capabilityNamespace

The namespace of the gateway capability.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `^[a-zA-Z]+:[a-zA-Z]+:[0-9]+$`

capabilitySyncStatus

The synchronization status of the capability configuration. The sync status can be one of the following:

- `IN_SYNC` – The gateway is running the capability configuration.
- `NOT_APPLICABLE` – Synchronization is not required for this capability configuration. This is most common when integrating partner data sources, because the data integration is handled externally by the partner.
- `OUT_OF_SYNC` – The gateway hasn't received the capability configuration.
- `SYNC_FAILED` – The gateway rejected the capability configuration.
- `UNKNOWN` – The synchronization status is currently unknown due to an undetermined or temporary error.

After you update a capability configuration, its sync status is `OUT_OF_SYNC` until the gateway receives and applies or rejects the updated configuration.

Type: String

Valid Values: `IN_SYNC` | `OUT_OF_SYNC` | `SYNC_FAILED` | `UNKNOWN` | `NOT_APPLICABLE`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

LimitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 410

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdatePortal

Updates an Amazon IoT SiteWise Monitor portal.

Request Syntax

```
PUT /portals/portalId HTTP/1.1
Content-type: application/json

{
  "alarms": {
    "alarmRoleArn": "string",
    "notificationLambdaArn": "string"
  },
  "clientToken": "string",
  "notificationSenderEmail": "string",
  "portalContactEmail": "string",
  "portalDescription": "string",
  "portalLogoImage": {
    "file": {
      "data": blob,
      "type": "string"
    },
    "id": "string"
  },
  "portalName": "string",
  "portalType": "string",
  "portalTypeConfiguration": {
    "string" : {
      "portalTools": [ "string" ]
    }
  },
  "roleArn": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

portalId

The ID of the portal to update.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

alarms

Contains the configuration information of an alarm created in an Amazon IoT SiteWise Monitor portal. You can use the alarm to monitor an asset property and get notified when the asset property value is outside a specified range. For more information, see [Monitoring with alarms](#) in the *Amazon IoT SiteWise Application Guide*.

Type: [Alarms](#) object

Required: No

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

notificationSenderEmail

The email address that sends alarm notifications.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9_\-\.]+@[a-zA-Z0-9_\-\.]+\.[a-zA-Z]{2,}$`

Required: No

portalContactEmail

The Amazon administrator's contact email address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9_\-\.\\+]+@[a-zA-Z0-9_\-\.\\+]+\.[a-zA-Z]{2,}$`

Required: Yes

portalDescription

A new description for the portal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

portalLogoImage

Contains an image that is one of the following:

- An image file. Choose this option to upload a new image.
- The ID of an existing image. Choose this option to keep an existing image.

Type: [Image](#) object

Required: No

portalName

A new friendly name for the portal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

portalType

Define the type of portal. The value for Amazon IoT SiteWise Monitor (Classic) is SITEWISE_PORTAL_V1. The value for Amazon IoT SiteWise Monitor (AI-aware) is SITEWISE_PORTAL_V2.

Type: String

Valid Values: SITEWISE_PORTAL_V1 | SITEWISE_PORTAL_V2

Required: No

portalTypeConfiguration

The configuration entry associated with the specific portal type. The value for Amazon IoT SiteWise Monitor (Classic) is SITEWISE_PORTAL_V1. The value for Amazon IoT SiteWise Monitor (AI-aware) is SITEWISE_PORTAL_V2.

Type: String to [PortalTypeEntry](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

roleArn

The [ARN](#) of a service role that allows the portal's users to access your Amazon IoT SiteWise resources on your behalf. For more information, see [Using service roles for Amazon IoT SiteWise Monitor](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.\\+=,@]+$`

Required: Yes

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
```

```
"portalStatus": {
  "error": {
    "code": "string",
    "message": "string"
  },
  "state": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

portalStatus

The status of the portal, which contains a state (UPDATING after successfully calling this operation) and any error message.

Type: [PortalStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

HTTP Status Code: 409

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateProject

Updates an Amazon IoT SiteWise Monitor project.

Request Syntax

```
PUT /projects/projectId HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "projectDescription": "string",
  "projectName": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

projectId

The ID of the project to update.

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

A unique case-sensitive identifier that you can provide to ensure the idempotency of the request. Don't reuse this client token if a new idempotent request is required.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 64.

Pattern: `\S{36,64}`

Required: No

projectDescription

A new description for the project.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

projectName

A new friendly name for the project.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

HTTP Status Code: 500

InvalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

HTTP Status Code: 400

ResourceNotFoundException

The requested resource can't be found.

HTTP Status Code: 404

ThrottlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

Data Types

The Amazon IoT SiteWise API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccessPolicySummary](#)
- [ActionDefinition](#)
- [ActionPayload](#)
- [ActionSummary](#)
- [AggregatedValue](#)
- [Aggregates](#)
- [Alarms](#)
- [AssetCompositeModel](#)
- [AssetCompositeModelPathSegment](#)
- [AssetCompositeModelSummary](#)
- [AssetErrorDetails](#)
- [AssetHierarchy](#)
- [AssetHierarchyInfo](#)
- [AssetModelCompositeModel](#)
- [AssetModelCompositeModelDefinition](#)
- [AssetModelCompositeModelPathSegment](#)
- [AssetModelCompositeModelSummary](#)
- [AssetModelHierarchy](#)
- [AssetModelHierarchyDefinition](#)
- [AssetModelProperty](#)

- [AssetModelPropertyDefinition](#)
- [AssetModelPropertyPathSegment](#)
- [AssetModelPropertySummary](#)
- [AssetModelStatus](#)
- [AssetModelSummary](#)
- [AssetProperty](#)
- [AssetPropertyPathSegment](#)
- [AssetPropertySummary](#)
- [AssetPropertyValue](#)
- [AssetRelationshipSummary](#)
- [AssetStatus](#)
- [AssetSummary](#)
- [AssociatedAssetsSummary](#)
- [Attribute](#)
- [BatchGetAssetPropertyAggregatesEntry](#)
- [BatchGetAssetPropertyAggregatesErrorEntry](#)
- [BatchGetAssetPropertyAggregatesErrorInfo](#)
- [BatchGetAssetPropertyAggregatesSkippedEntry](#)
- [BatchGetAssetPropertyAggregatesSuccessEntry](#)
- [BatchGetAssetPropertyValueEntry](#)
- [BatchGetAssetPropertyValueErrorEntry](#)
- [BatchGetAssetPropertyValueErrorInfo](#)
- [BatchGetAssetPropertyValueHistoryEntry](#)
- [BatchGetAssetPropertyValueHistoryErrorEntry](#)
- [BatchGetAssetPropertyValueHistoryErrorInfo](#)
- [BatchGetAssetPropertyValueHistorySkippedEntry](#)
- [BatchGetAssetPropertyValueHistorySuccessEntry](#)
- [BatchGetAssetPropertyValueSkippedEntry](#)
- [BatchGetAssetPropertyValueSuccessEntry](#)
- [BatchPutAssetPropertyError](#)

- [BatchPutAssetPropertyErrorEntry](#)
- [Citation](#)
- [ColumnInfo](#)
- [ColumnType](#)
- [CompositeModelProperty](#)
- [CompositionDetails](#)
- [CompositionRelationshipItem](#)
- [CompositionRelationshipSummary](#)
- [ConfigurationErrorDetails](#)
- [ConfigurationStatus](#)
- [Content](#)
- [Csv](#)
- [CustomerManagedS3Storage](#)
- [DashboardSummary](#)
- [DataSetReference](#)
- [DatasetSource](#)
- [DatasetStatus](#)
- [DatasetSummary](#)
- [Datum](#)
- [DetailedError](#)
- [ErrorDetails](#)
- [ErrorReportLocation](#)
- [ExpressionVariable](#)
- [File](#)
- [FileFormat](#)
- [ForwardingConfig](#)
- [GatewayCapabilitySummary](#)
- [GatewayPlatform](#)
- [GatewaySummary](#)
- [Greengrass](#)

- [GreengrassV2](#)
- [GroupIdentity](#)
- [IAMRoleIdentity](#)
- [IAMUserIdentity](#)
- [Identity](#)
- [Image](#)
- [ImageFile](#)
- [ImageLocation](#)
- [InterpolatedAssetPropertyValue](#)
- [InvocationOutput](#)
- [JobConfiguration](#)
- [JobSummary](#)
- [KendraSourceDetail](#)
- [Location](#)
- [LoggingOptions](#)
- [Measurement](#)
- [MeasurementProcessingConfig](#)
- [Metric](#)
- [MetricProcessingConfig](#)
- [MetricWindow](#)
- [MonitorErrorDetails](#)
- [MultiLayerStorage](#)
- [Parquet](#)
- [PortalResource](#)
- [PortalStatus](#)
- [PortalSummary](#)
- [PortalTypeEntry](#)
- [ProjectResource](#)
- [ProjectSummary](#)
- [Property](#)

- [PropertyNotification](#)
- [PropertyType](#)
- [PropertyValueNullValue](#)
- [PutAssetPropertyValueEntry](#)
- [Reference](#)
- [Resource](#)
- [ResponseStream](#)
- [RetentionPeriod](#)
- [Row](#)
- [SiemensE](#)
- [Source](#)
- [SourceDetail](#)
- [TargetResource](#)
- [TimeInNanos](#)
- [TimeSeriesSummary](#)
- [Trace](#)
- [Transform](#)
- [TransformProcessingConfig](#)
- [TumblingWindow](#)
- [UserIdentity](#)
- [VariableValue](#)
- [Variant](#)
- [WarmTierRetentionPeriod](#)

AccessPolicySummary

Contains an access policy that defines an identity's access to an Amazon IoT SiteWise Monitor resource.

Contents

id

The ID of the access policy.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

identity

The identity (an IAM Identity Center user, an IAM Identity Center group, or an IAM user).

Type: [Identity](#) object

Required: Yes

permission

The permissions for the access policy. Note that a project ADMINISTRATOR is also known as a project owner.

Type: String

Valid Values: ADMINISTRATOR | VIEWER

Required: Yes

resource

The Amazon IoT SiteWise Monitor resource (a portal or project).

Type: [Resource](#) object

Required: Yes

creationDate

The date the access policy was created, in Unix epoch time.

Type: Timestamp

Required: No

lastUpdateDate

The date the access policy was last updated, in Unix epoch time.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ActionDefinition

Contains a definition for an action.

Contents

actionDefinitionId

The ID of the action definition.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

actionName

The name of the action definition.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

actionType

The type of the action definition.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ActionPayload

The JSON payload of the action.

Contents

stringValue

The payload of the action in a JSON string.

Type: String

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ActionSummary

Contains the summary of the actions.

Contents

actionDefinitionId

The ID of the action definition.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

actionId

The ID of the action.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

targetResource

The resource the action will be taken on.

Type: [TargetResource](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AggregatedValue

Contains aggregated asset property values (for example, average, minimum, and maximum).

Contents

timestamp

The date the aggregating computations occurred, in Unix epoch time.

Type: Timestamp

Required: Yes

value

The value of the aggregates.

Type: [Aggregates](#) object

Required: Yes

quality

The quality of the aggregated data.

Type: String

Valid Values: GOOD | BAD | UNCERTAIN

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Aggregates

Contains the (pre-calculated) aggregate values for an asset property.

Contents

average

The average (mean) value of the time series over a time interval window.

Type: Double

Required: No

count

The count of data points in the time series over a time interval window.

Type: Double

Required: No

maximum

The maximum value of the time series over a time interval window.

Type: Double

Required: No

minimum

The minimum value of the time series over a time interval window.

Type: Double

Required: No

standardDeviation

The standard deviation of the time series over a time interval window.

Type: Double

Required: No

sum

The sum of the time series over a time interval window.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Alarms

Contains the configuration information of an alarm created in an Amazon IoT SiteWise Monitor portal. You can use the alarm to monitor an asset property and get notified when the asset property value is outside a specified range. For more information, see [Monitoring with alarms](#) in the *Amazon IoT SiteWise Application Guide*.

Contents

alarmRoleArn

The [ARN](#) of the IAM role that allows the alarm to perform actions and access Amazon resources and services, such as Amazon IoT Events.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.\\+=, @]+`

Required: Yes

notificationLambdaArn

The [ARN](#) of the Lambda function that manages alarm notifications. For more information, see [Managing alarm notifications](#) in the *Amazon IoT Events Developer Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetCompositeModel

Contains information about a composite model in an asset. This object contains the asset's properties that you define in the composite model.

Contents

name

The name of the composite model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

properties

The asset properties that this composite model defines.

Type: Array of [AssetProperty](#) objects

Required: Yes

type

The type of the composite model. For alarm composite models, this type is `AWS/ALARM`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

description

The description of the composite model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

externalId

The external ID of the asset composite model. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:\-]*[a-zA-Z0-9_]+`

Required: No

id

The ID of the asset composite model.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetCompositeModelPathSegment

Represents one level between a composite model and the root of the asset.

Contents

id

The ID of the path segment.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

name

The name of the path segment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetCompositeModelSummary

Contains a summary of the composite model for a specific asset.

Contents

description

A description of the composite model that this summary describes.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

id

The ID of the composite model that this summary describes.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

name

The name of the composite model that this summary describes.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

path

The path that includes all the components of the asset model for the asset.

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetErrorDetails

Contains error details for the requested associate project asset action.

Contents

assetId

The ID of the asset, in UUID format.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

code

The error code.

Type: String

Valid Values: INTERNAL_FAILURE

Required: Yes

message

The error message.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AssetHierarchy

Describes an asset hierarchy that contains a hierarchy's name and ID.

Contents

name

The hierarchy name provided in the [CreateAssetModel](#) or [UpdateAssetModel](#) API operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

externalId

The external ID of the hierarchy, if it has one. When you update an asset hierarchy, you may assign an external ID if it doesn't already have one. You can't change the external ID of an asset hierarchy that already has one. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

id

The ID of the hierarchy. This ID is a `hierarchyId`.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetHierarchyInfo

Contains information about a parent asset and a child asset that are related through an asset hierarchy.

Contents

childAssetId

The ID of the child asset in this asset relationship.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

parentAssetId

The ID of the parent asset in this asset relationship.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetModelCompositeModel

Contains information about a composite model in an asset model. This object contains the asset property definitions that you define in the composite model.

Contents

name

The name of the composite model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

type

The type of the composite model. For alarm composite models, this type is `AWS/ALARM`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

description

The description of the composite model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

externalId

The external ID of the asset model composite model. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

id

The ID of the asset model composite model.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: No

properties

The asset property definitions for this composite model.

Type: Array of [AssetModelProperty](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetModelCompositeModelDefinition

Contains a composite model definition in an asset model. This composite model definition is applied to all assets created from the asset model.

Contents

name

The name of the composite model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

type

The type of the composite model. For alarm composite models, this type is `AWS/ALARM`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

description

The description of the composite model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

externalId

An external ID to assign to the composite model. The external ID must be unique among composite models within this asset model. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9. :]*[a-zA-Z0-9_]+`

Required: No

id

The ID to assign to the composite model, if desired. Amazon IoT SiteWise automatically generates a unique ID for you, so this parameter is never required. However, if you prefer to supply your own ID instead, you can specify it here in UUID format. If you specify your own ID, it must be globally unique.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

properties

The asset property definitions for this composite model.

Type: Array of [AssetModelPropertyDefinition](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetModelCompositeModelPathSegment

Represents one level between a composite model and the root of the asset model.

Contents

id

The ID of the path segment.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

name

The name of the path segment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetModelCompositeModelSummary

Contains a summary of the composite model.

Contents

id

The ID of the composite model that this summary describes..

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

name

The name of the composite model that this summary describes..

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

type

The composite model type. Valid values are `AWS/ALARM`, `CUSTOM`, or `AWS/L4E_ANOMALY`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

description

The description of the composite model that this summary describes..

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

externalId

The external ID of a composite model on this asset model. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

path

The path that includes all the pieces that make up the composite model.

Type: Array of [AssetModelCompositeModelPathSegment](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetModelHierarchy

Describes an asset hierarchy that contains a hierarchy's name, ID, and child asset model ID that specifies the type of asset that can be in this hierarchy.

Contents

childAssetModelId

The ID of the asset model, in UUID format. All assets in this hierarchy must be instances of the `childAssetModelId` asset model. Amazon IoT SiteWise will always return the actual asset model ID for this value. However, when you are specifying this value as part of a call to [UpdateAssetModel](#), you may provide either the asset model ID or else `externalId`: followed by the asset model's external ID. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$ | ^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: Yes

name

The name of the asset model hierarchy that you specify by using the [CreateAssetModel](#) or [UpdateAssetModel](#) API operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

externalId

The external ID (if any) provided in the [CreateAssetModel](#) or [UpdateAssetModel](#) operation. You can assign an external ID by specifying this value as part of a call to [UpdateAssetModel](#).

However, you can't change the external ID if one is already assigned. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

id

The ID of the asset model hierarchy. This ID is a `hierarchyId`.

- If you are calling [UpdateAssetModel](#) to create a *new* hierarchy: You can specify its ID here, if desired. Amazon IoT SiteWise automatically generates a unique ID for you, so this parameter is never required. However, if you prefer to supply your own ID instead, you can specify it here in UUID format. If you specify your own ID, it must be globally unique.
- If you are calling `UpdateAssetModel` to modify an *existing* hierarchy: This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.:]*[a-zA-Z0-9]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetModelHierarchyDefinition

Contains an asset model hierarchy used in asset model creation. An asset model hierarchy determines the kind (or type) of asset that can belong to a hierarchy.

Contents

childAssetModelId

The ID of an asset model for this hierarchy. This can be either the actual ID in UUID format, or else `externalId`: followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$|^externalId:[a-zA-Z0-9][a-zA-Z_\-0-9.]*[a-zA-Z0-9]+`

Required: Yes

name

The name of the asset model hierarchy definition (as specified in the [CreateAssetModel](#) or [UpdateAssetModel](#) API operation).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

externalId

An external ID to assign to the asset model hierarchy. The external ID must be unique among asset model hierarchies within this asset model. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

id

The ID to assign to the asset model hierarchy, if desired. Amazon IoT SiteWise automatically generates a unique ID for you, so this parameter is never required. However, if you prefer to supply your own ID instead, you can specify it here in UUID format. If you specify your own ID, it must be globally unique.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetModelProperty

Contains information about an asset model property.

Contents

dataType

The data type of the asset model property.

If you specify STRUCT, you must also specify dataTypeSpec to identify the type of the structure for this property.

Type: String

Valid Values: STRING | INTEGER | DOUBLE | BOOLEAN | STRUCT

Required: Yes

name

The name of the asset model property.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

type

The property type (see PropertyType).

Type: [PropertyType](#) object

Required: Yes

dataTypeSpec

The data type of the structure for this property. This parameter exists on properties that have the STRUCT data type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

externalId

The external ID (if any) provided in the [CreateAssetModel](#) or [UpdateAssetModel](#) operation. You can assign an external ID by specifying this value as part of a call to [UpdateAssetModel](#). However, you can't change the external ID if one is already assigned. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

id

The ID of the asset model property.

- If you are calling [UpdateAssetModel](#) to create a *new* property: You can specify its ID here, if desired. Amazon IoT SiteWise automatically generates a unique ID for you, so this parameter is never required. However, if you prefer to supply your own ID instead, you can specify it here in UUID format. If you specify your own ID, it must be globally unique.
- If you are calling [UpdateAssetModel](#) to modify an *existing* property: This can be either the actual ID in UUID format, or else `externalId:` followed by the external ID, if it has one. For more information, see [Referencing objects with external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 139.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$ | ^externalId:[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

path

The structured path to the property from the root of the asset model.

Type: Array of [AssetModelPropertyPathSegment](#) objects

Required: No

unit

The unit of the asset model property, such as Newtons or RPM.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetModelPropertyDefinition

Contains an asset model property definition. This property definition is applied to all assets created from the asset model.

Contents

dataType

The data type of the property definition.

If you specify STRUCT, you must also specify dataTypeSpec to identify the type of the structure for this property.

Type: String

Valid Values: STRING | INTEGER | DOUBLE | BOOLEAN | STRUCT

Required: Yes

name

The name of the property definition.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [^\u0000-\u001F\u007F]+

Required: Yes

type

The property definition type (see [PropertyType](#)). You can only specify one type in a property definition.

Type: [PropertyType](#) object

Required: Yes

dataTypeSpec

The data type of the structure for this property. This parameter is required on properties that have the STRUCT data type.

The options for this parameter depend on the type of the composite model in which you define this property. Use `AWS/ALARM_STATE` for alarm state in alarm composite models.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

externalId

An external ID to assign to the property definition. The external ID must be unique among property definitions within this asset model. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

id

The ID to assign to the asset model property, if desired. Amazon IoT SiteWise automatically generates a unique ID for you, so this parameter is never required. However, if you prefer to supply your own ID instead, you can specify it here in UUID format. If you specify your own ID, it must be globally unique.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

unit

The unit of the property definition, such as Newtons or RPM.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetModelPropertyPathSegment

Represents one level between a property and the root of the asset model.

Contents

id

The ID of the path segment.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

name

The name of the path segment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetModelPropertySummary

Contains a summary of a property associated with a model.

Contents

dataType

The data type of the property.

Type: String

Valid Values: STRING | INTEGER | DOUBLE | BOOLEAN | STRUCT

Required: Yes

name

The name of the property.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

type

Contains a property type, which can be one of `attribute`, `measurement`, `metric`, or `transform`.

Type: [PropertyType](#) object

Required: Yes

assetModelCompositeModelId

The ID of the composite model that contains the asset model property.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

dataTypeSpec

The data type of the structure for this property. This parameter exists on properties that have the STRUCT data type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

externalId

The external ID of the property. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

id

The ID of the property.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

path

The structured path to the property from the root of the asset model.

Type: Array of [AssetModelPropertyPathSegment](#) objects

Required: No

unit

The unit (such as Newtons or RPM) of the property.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetModelStatus

Contains current status information for an asset model. For more information, see [Asset and model states](#) in the *Amazon IoT SiteWise User Guide*.

Contents

state

The current state of the asset model.

Type: String

Valid Values: CREATING | ACTIVE | UPDATING | PROPAGATING | DELETING | FAILED

Required: Yes

error

Contains associated error information, if any.

Type: [ErrorDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetModelSummary

Contains a summary of an asset model.

Contents

arn

The [ARN](#) of the asset model, which has the following format.

```
arn:${Partition}:iotsitewise:${Region}:${Account}:asset-model/  
${AssetModelId}
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

Required: Yes

creationDate

The date the asset model was created, in Unix epoch time.

Type: Timestamp

Required: Yes

description

The asset model description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

id

The ID of the asset model (used with Amazon IoT SiteWise API operations).

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

lastUpdateDate

The date the asset model was last updated, in Unix epoch time.

Type: Timestamp

Required: Yes

name

The name of the asset model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

status

The current status of the asset model.

Type: [AssetModelStatus](#) object

Required: Yes

assetModelType

The type of asset model.

- **ASSET_MODEL** – (default) An asset model that you can use to create assets. Can't be included as a component in another asset model.
- **COMPONENT_MODEL** – A reusable component that you can include in the composite models of other asset models. You can't create assets directly from this type of asset model.

Type: String

Valid Values: ASSET_MODEL | COMPONENT_MODEL

Required: No

externalId

The external ID of the asset model. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

version

The version number of the asset model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: `^(0|([1-9]{1}\d*))$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetProperty

Contains asset property information.

Contents

dataType

The data type of the asset property.

Type: String

Valid Values: STRING | INTEGER | DOUBLE | BOOLEAN | STRUCT

Required: Yes

id

The ID of the asset property.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

name

The name of the property.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

alias

The alias that identifies the property, such as an OPC-UA server data stream path (for example, `/company/windfarm/3/turbine/7/temperature`). For more information, see [Mapping industrial data streams to asset properties](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

dataTypeSpec

The data type of the structure for this property. This parameter exists on properties that have the STRUCT data type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

externalId

The external ID of the asset property. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

notification

The asset property's notification topic and state. For more information, see [UpdateAssetProperty](#).

Type: [PropertyNotification](#) object

Required: No

path

The structured path to the property from the root of the asset.

Type: Array of [AssetPropertyPathSegment](#) objects

Required: No

unit

The unit (such as Newtons or RPM) of the asset property.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetPropertyPathSegment

Represents one level between a property and the root of the asset.

Contents

id

The ID of the path segment.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

name

The name of the path segment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetPropertySummary

Contains a summary of a property associated with an asset.

Contents

id

The ID of the property.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

alias

The alias that identifies the property, such as an OPC-UA server data stream path (for example, `/company/windfarm/3/turbine/7/temperature`). For more information, see [Mapping industrial data streams to asset properties](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

assetCompositeModelId

The ID of the composite model that contains the asset property.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

externalId

The external ID of the property. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

notification

Contains asset property value notification information. When the notification state is enabled, Amazon IoT SiteWise publishes property value updates to a unique MQTT topic. For more information, see [Interacting with other services](#) in the *Amazon IoT SiteWise User Guide*.

Type: [PropertyNotification](#) object

Required: No

path

The structured path to the property from the root of the asset.

Type: Array of [AssetPropertyPathSegment](#) objects

Required: No

unit

The unit of measure (such as Newtons or RPM) of the asset property.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetPropertyValue

Contains asset property value information.

Contents

timestamp

The timestamp of the asset property value.

Type: [TimeInNanos](#) object

Required: Yes

value

The value of the asset property (see [Variant](#)).

Type: [Variant](#) object

Required: Yes

quality

The quality of the asset property value.

Type: String

Valid Values: GOOD | BAD | UNCERTAIN

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetRelationshipSummary

Contains information about assets that are related to one another.

Contents

relationshipType

The relationship type of the assets in this relationship. This value is one of the following:

- HIERARCHY – The assets are related through an asset hierarchy. If you specify this relationship type, this asset relationship includes the `hierarchyInfo` object.

Type: String

Valid Values: HIERARCHY

Required: Yes

hierarchyInfo

The assets that are related through an asset hierarchy.

This object is present if the `relationshipType` is HIERARCHY.

Type: [AssetHierarchyInfo](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetStatus

Contains information about the current status of an asset. For more information, see [Asset and model states](#) in the *Amazon IoT SiteWise User Guide*.

Contents

state

The current status of the asset.

Type: String

Valid Values: CREATING | ACTIVE | UPDATING | DELETING | FAILED

Required: Yes

error

Contains associated error information, if any.

Type: [ErrorDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssetSummary

Contains a summary of an asset.

Contents

arn

The [ARN](#) of the asset, which has the following format.

```
arn:${Partition}:iotsitewise:${Region}:${Account}:asset/${AssetId}
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

Required: Yes

assetModelId

The ID of the asset model used to create this asset.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

creationDate

The date the asset was created, in Unix epoch time.

Type: Timestamp

Required: Yes

hierarchies

A list of asset hierarchies that each contain a `hierarchyId`. A hierarchy specifies allowed parent/child asset relationships.

Type: Array of [AssetHierarchy](#) objects

Required: Yes

id

The ID of the asset, in UUID format.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

lastUpdateDate

The date the asset was last updated, in Unix epoch time.

Type: Timestamp

Required: Yes

name

The name of the asset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

status

The current status of the asset.

Type: [AssetStatus](#) object

Required: Yes

description

A description for the asset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

externalId

The external ID of the asset. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssociatedAssetsSummary

Contains a summary of an associated asset.

Contents

arn

The [ARN](#) of the asset, which has the following format.

```
arn:${Partition}:iotsitewise:${Region}:${Account}:asset/${AssetId}
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

Required: Yes

assetModelId

The ID of the asset model used to create the asset.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

creationDate

The date the asset was created, in Unix epoch time.

Type: Timestamp

Required: Yes

hierarchies

A list of asset hierarchies that each contain a `hierarchyId`. A hierarchy specifies allowed parent/child asset relationships.

Type: Array of [AssetHierarchy](#) objects

Required: Yes

id

The ID of the asset, in UUID format.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

lastUpdateDate

The date the asset was last updated, in Unix epoch time.

Type: Timestamp

Required: Yes

name

The name of the asset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

status

The current status of the asset.

Type: [AssetStatus](#) object

Required: Yes

description

A description for the asset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

externalId

The external ID of the asset. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Attribute

Contains an asset attribute property. For more information, see [Attributes](#) in the *Amazon IoT SiteWise User Guide*.

Contents

defaultValue

The default value of the asset model property attribute. All assets that you create from the asset model contain this attribute value. You can update an attribute's value after you create an asset. For more information, see [Updating attribute values](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyAggregatesEntry

Contains information for an asset property aggregate entry that is associated with the [BatchGetAssetPropertyAggregates](#) API.

To identify an asset property, you must specify one of the following:

- The `assetId` and `propertyId` of an asset property.
- A `propertyAlias`, which is a data stream alias (for example, `/company/windfarm/3/turbine/7/temperature`). To define an asset property's alias, see [UpdateAssetProperty](#).

Contents

aggregateTypes

The data aggregating function.

Type: Array of strings

Array Members: Minimum number of 1 item.

Valid Values: AVERAGE | COUNT | MAXIMUM | MINIMUM | SUM | STANDARD_DEVIATION

Required: Yes

endDate

The inclusive end of the range from which to query historical data, expressed in seconds in Unix epoch time.

Type: Timestamp

Required: Yes

entryId

The ID of the entry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9_-]+$`

Required: Yes

resolution

The time interval over which to aggregate data.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 3.

Pattern: 1m|15m|1h|1d

Required: Yes

startDate

The exclusive start of the range from which to query historical data, expressed in seconds in Unix epoch time.

Type: Timestamp

Required: Yes

assetId

The ID of the asset in which the asset property was created.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

propertyAlias

The alias that identifies the property, such as an OPC-UA server data stream path (for example, `/company/windfarm/3/turbine/7/temperature`). For more information, see [Mapping industrial data streams to asset properties](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

propertyId

The ID of the asset property, in UUID format.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

qualities

The quality by which to filter asset data.

Type: Array of strings

Array Members: Fixed number of 1 item.

Valid Values: GOOD | BAD | UNCERTAIN

Required: No

timeOrdering

The chronological sorting order of the requested information.

Default: ASCENDING

Type: String

Valid Values: ASCENDING | DESCENDING

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyAggregatesErrorEntry

Contains error information for an asset property aggregate entry that is associated with the [BatchGetAssetPropertyAggregates](#) API.

Contents

entryId

The ID of the entry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9_-]+$`

Required: Yes

errorCode

The error code.

Type: String

Valid Values: `ResourceNotFoundException` | `InvalidRequestException` | `AccessDeniedException`

Required: Yes

errorMessage

The associated error message.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyAggregatesErrorInfo

Contains the error code and the timestamp for an asset property aggregate entry that is associated with the [BatchGetAssetPropertyAggregates](#) API.

Contents

errorCode

The error code.

Type: String

Valid Values: `ResourceNotFoundException` | `InvalidRequestException` | `AccessDeniedException`

Required: Yes

errorTimestamp

The date the error occurred, in Unix epoch time.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyAggregatesSkippedEntry

Contains information for an entry that has been processed by the previous [BatchGetAssetPropertyAggregates](#) request.

Contents

completionStatus

The completion status of each entry that is associated with the [BatchGetAssetPropertyAggregates](#) API.

Type: String

Valid Values: SUCCESS | ERROR

Required: Yes

entryId

The ID of the entry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9_-]+$`

Required: Yes

errorInfo

The error information, such as the error code and the timestamp.

Type: [BatchGetAssetPropertyAggregatesErrorInfo](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyAggregatesSuccessEntry

Contains success information for an entry that is associated with the [BatchGetAssetPropertyAggregates](#) API.

Contents

aggregatedValues

The requested aggregated asset property values (for example, average, minimum, and maximum).

Type: Array of [AggregatedValue](#) objects

Required: Yes

entryId

The ID of the entry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9_-]+$`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyValueEntry

Contains information for an asset property value entry that is associated with the [BatchGetAssetPropertyValue](#) API.

To identify an asset property, you must specify one of the following:

- The `assetId` and `propertyId` of an asset property.
- A `propertyAlias`, which is a data stream alias (for example, `/company/windfarm/3/turbine/7/temperature`). To define an asset property's alias, see [UpdateAssetProperty](#).

Contents

entryId

The ID of the entry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9_-]+$`

Required: Yes

assetId

The ID of the asset in which the asset property was created.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

propertyAlias

The alias that identifies the property, such as an OPC-UA server data stream path (for example, `/company/windfarm/3/turbine/7/temperature`). For more information, see [Mapping industrial data streams to asset properties](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

propertyId

The ID of the asset property, in UUID format.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyValueErrorEntry

Contains error information for an asset property value entry that is associated with the [BatchGetAssetPropertyValue](#) API.

Contents

entryId

The ID of the entry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9_-]+$`

Required: Yes

errorCode

The error code.

Type: String

Valid Values: `ResourceNotFoundException` | `InvalidRequestException` | `AccessDeniedException`

Required: Yes

errorMessage

The associated error message.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyValueErrorInfo

The error information, such as the error code and the timestamp.

Contents

errorCode

The error code.

Type: String

Valid Values: ResourceNotFoundException | InvalidRequestException | AccessDeniedException

Required: Yes

errorTimestamp

The date the error occurred, in Unix epoch time.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyValueHistoryEntry

Contains information for an asset property historical value entry that is associated with the [BatchGetAssetPropertyValueHistory](#) API.

To identify an asset property, you must specify one of the following:

- The `assetId` and `propertyId` of an asset property.
- A `propertyAlias`, which is a data stream alias (for example, `/company/windfarm/3/turbine/7/temperature`). To define an asset property's alias, see [UpdateAssetProperty](#).

Contents

entryId

The ID of the entry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9_-]+$`

Required: Yes

assetId

The ID of the asset in which the asset property was created.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

endDate

The inclusive end of the range from which to query historical data, expressed in seconds in Unix epoch time.

Type: Timestamp

Required: No

propertyAlias

The alias that identifies the property, such as an OPC-UA server data stream path (for example, /company/windfarm/3/turbine/7/temperature). For more information, see [Mapping industrial data streams to asset properties](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

propertyId

The ID of the asset property, in UUID format.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

qualities

The quality by which to filter asset data.

Type: Array of strings

Array Members: Fixed number of 1 item.

Valid Values: GOOD | BAD | UNCERTAIN

Required: No

startDate

The exclusive start of the range from which to query historical data, expressed in seconds in Unix epoch time.

Type: Timestamp

Required: No

timeOrdering

The chronological sorting order of the requested information.

Default: ASCENDING

Type: String

Valid Values: ASCENDING | DESCENDING

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyValueHistoryErrorEntry

A list of the errors (if any) associated with the batch request. Each error entry contains the `entryId` of the entry that failed.

Contents

entryId

The ID of the entry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9_-]+$`

Required: Yes

errorCode

The error code.

Type: String

Valid Values: `ResourceNotFoundException` | `InvalidRequestException` | `AccessDeniedException`

Required: Yes

errorMessage

The associated error message.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyValueHistoryErrorInfo

The error information, such as the error code and the timestamp.

Contents

errorCode

The error code.

Type: String

Valid Values: ResourceNotFoundException | InvalidRequestException | AccessDeniedException

Required: Yes

errorTimestamp

The date the error occurred, in Unix epoch time.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyValueHistorySkippedEntry

Contains information for an entry that has been processed by the previous [BatchGetAssetPropertyValueHistory](#) request.

Contents

completionStatus

The completion status of each entry that is associated with the [BatchGetAssetPropertyValueHistory](#) API.

Type: String

Valid Values: SUCCESS | ERROR

Required: Yes

entryId

The ID of the entry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9_-]+$`

Required: Yes

errorInfo

The error information, such as the error code and the timestamp.

Type: [BatchGetAssetPropertyValueHistoryErrorInfo](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyValueHistorySuccessEntry

Contains success information for an entry that is associated with the [BatchGetAssetPropertyValueHistory](#) API.

Contents

assetPropertyValueHistory

The requested historical values for the specified asset property.

Type: Array of [AssetPropertyValue](#) objects

Required: Yes

entryId

The ID of the entry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9_-]+$`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyValueSkippedEntry

Contains information for an entry that has been processed by the previous [BatchGetAssetPropertyValue](#) request.

Contents

completionStatus

The completion status of each entry that is associated with the [BatchGetAssetPropertyValue](#) request.

Type: String

Valid Values: SUCCESS | ERROR

Required: Yes

entryId

The ID of the entry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9_-]+$`

Required: Yes

errorInfo

The error information, such as the error code and the timestamp.

Type: [BatchGetAssetPropertyValueErrorInfo](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAssetPropertyValueSuccessEntry

Contains success information for an entry that is associated with the [BatchGetAssetPropertyValue](#) API.

Contents

entryId

The ID of the entry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9_-]+$`

Required: Yes

assetPropertyValue

Contains asset property value information.

Type: [AssetPropertyValue](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchPutAssetPropertyError

Contains error information from updating a batch of asset property values.

Contents

errorCode

The error code.

Type: String

Valid Values: `ResourceNotFoundException` | `InvalidRequestException` | `InternalFailureException` | `ServiceUnavailableException` | `ThrottlingException` | `LimitExceededException` | `ConflictingOperationException` | `TimestampOutOfRangeException` | `AccessDeniedException`

Required: Yes

errorMessage

The associated error message.

Type: String

Required: Yes

timestamps

A list of timestamps for each error, if any.

Type: Array of [TimeInNanos](#) objects

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchPutAssetPropertyErrorEntry

Contains error information for asset property value entries that are associated with the [BatchPutAssetPropertyValue](#) API.

Contents

entryId

The ID of the failed entry.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9_-]+$`

Required: Yes

errors

The list of update property value errors.

Type: Array of [BatchPutAssetPropertyError](#) objects

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Citation

Contains text content to which the SiteWise Assistant refers to, and generate the final response. It also contains information about the source.

Contents

content

Contains the cited text from the data source.

Type: [Content](#) object

Required: No

reference

Contains information about the data source.

Type: [Reference](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ColumnInfo

A description of the column in the query results.

Contents

name

The name of the column description.

Type: String

Required: No

type

The type of the column description.

Type: [ColumnType](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ColumnType

The data type of the column.

Contents

scalarType

The allowed data types that the column has as its value.

Type: String

Valid Values: BOOLEAN | INT | DOUBLE | TIMESTAMP | STRING

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

CompositeModelProperty

Contains information about a composite model property on an asset.

Contents

assetProperty

Contains asset property information.

Type: [Property](#) object

Required: Yes

name

The name of the property.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

type

The type of the composite model that defines this property.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

externalId

The external ID of the composite model that contains the property. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9. :]*[a-zA-Z0-9_]+`

Required: No

id

The ID of the composite model that contains the property.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

CompositionDetails

Metadata for the composition relationship established by using `composedAssetModelId` in [CreateAssetModelCompositeModel](#).

Contents

`compositionRelationship`

An array detailing the composition relationship for this composite model.

Type: Array of [CompositionRelationshipItem](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

CompositionRelationshipItem

Represents a composite model that composed an asset model of type COMPONENT_MODEL.

Contents

id

The ID of the component.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

CompositionRelationshipSummary

Contains a summary of the components of the composite model.

Contents

assetModelCompositeModelId

The ID of a composite model on this asset model.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

assetModelCompositeModelType

The composite model type. Valid values are `AWS/ALARM`, `CUSTOM`, or `AWS/L4E_ANOMALY`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\^\u0000-\u001F\u007F]+`

Required: Yes

assetModelId

The ID of the asset model, in UUID format.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ConfigurationErrorDetails

Contains the details of an Amazon IoT SiteWise configuration error.

Contents

code

The error code.

Type: String

Valid Values: VALIDATION_ERROR | INTERNAL_FAILURE

Required: Yes

message

The error message.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ConfigurationStatus

Contains current status information for the configuration.

Contents

state

The current state of the configuration.

Type: String

Valid Values: ACTIVE | UPDATE_IN_PROGRESS | UPDATE_FAILED

Required: Yes

error

Contains associated error information, if any.

Type: [ConfigurationErrorDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Content

Contains the cited text from the data source.

Contents

text

The cited text from the data source.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Csv

A .CSV file.

Contents

columnNames

The column names specified in the .csv file.

Type: Array of strings

Valid Values: ALIAS | ASSET_ID | PROPERTY_ID | DATA_TYPE | TIMESTAMP_SECONDS
| TIMESTAMP_NANO_OFFSET | QUALITY | VALUE

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

CustomerManagedS3Storage

Contains information about a customer managed Amazon S3 bucket.

Contents

roleArn

The [ARN](#) of the Amazon Identity and Access Management role that allows Amazon IoT SiteWise to send data to Amazon S3.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

Required: Yes

s3ResourceArn

The [ARN](#) of the Amazon S3 object. For more information about how to find the ARN for an Amazon S3 object, see [Amazon S3 resources](#) in the *Amazon Simple Storage Service User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DashboardSummary

Contains a dashboard summary.

Contents

id

The ID of the dashboard.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

name

The name of the dashboard

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

creationDate

The date the dashboard was created, in Unix epoch time.

Type: Timestamp

Required: No

description

The dashboard's description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [^\u0000-\u001F\u007F]+

Required: No

lastUpdateDate

The date the dashboard was last updated, in Unix epoch time.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DataSetReference

Contains information about the dataset use and its source.

Contents

datasetArn

The [ARN](#) of the dataset. The format is `arn:${Partition}:iotsitewise:${Region}:${Account}:dataset/${DatasetId}`.

Type: String

Required: No

source

The data source for the dataset.

Type: [Source](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DatasetSource

The data source for the dataset.

Contents

sourceFormat

The format of the dataset source associated with the dataset.

Type: String

Valid Values: KNOWLEDGE_BASE

Required: Yes

sourceType

The type of data source for the dataset.

Type: String

Valid Values: KENDRA

Required: Yes

sourceDetail

The details of the dataset source associated with the dataset.

Type: [SourceDetail](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DatasetStatus

The status of the dataset. This contains the state and any error messages. The state is ACTIVE when ready to use.

Contents

state

The current status of the dataset.

Type: String

Valid Values: CREATING | ACTIVE | UPDATING | DELETING | FAILED

Required: Yes

error

Contains the details of an Amazon IoT SiteWise error.

Type: [ErrorDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DatasetSummary

The summary details for the dataset.

Contents

arn

The [ARN](#) of the dataset. The format is `arn:${Partition}:iotsitewise:${Region}:${Account}:dataset/${DatasetId}`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

Required: Yes

creationDate

The dataset creation date, in Unix epoch time.

Type: Timestamp

Required: Yes

description

A description about the dataset, and its functionality.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9 _\-#*$!@]+$`

Required: Yes

id

The ID of the dataset.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

lastUpdateDate

The date the dataset was last updated, in Unix epoch time.

Type: Timestamp

Required: Yes

name

The name of the dataset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^[a-zA-Z0-9 _\-\#\$*!\@]+\$\`

Required: Yes

status

The status of the dataset. This contains the state and any error messages. The state is ACTIVE when ready to use.

Type: [DatasetStatus](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Datum

Represents a single data point in a query result.

Contents

arrayValue

Indicates if the data point is an array.

Type: Array of [Datum](#) objects

Required: No

nullValue

Indicates if the data point is null.

Type: Boolean

Required: No

rowValue

Indicates if the data point is a row.

Type: [Row](#) object

Required: No

scalarValue

Indicates if the data point is a scalar value such as integer, string, double, or Boolean.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DetailedError

Contains detailed error information.

Contents

code

The error code.

Type: String

Valid Values: INCOMPATIBLE_COMPUTE_LOCATION |
INCOMPATIBLE_FORWARDING_CONFIGURATION

Required: Yes

message

The error message.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ErrorDetails

Contains the details of an Amazon IoT SiteWise error.

Contents

code

The error code.

Type: String

Valid Values: VALIDATION_ERROR | INTERNAL_FAILURE

Required: Yes

message

The error message.

Type: String

Required: Yes

details

A list of detailed errors.

Type: Array of [DetailedError](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ErrorReportLocation

The Amazon S3 destination where errors associated with the job creation request are saved.

Contents

bucket

The name of the Amazon S3 bucket to which errors associated with the bulk import job are sent.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Required: Yes

prefix

Amazon S3 uses the prefix as a folder name to organize data in the bucket. Each Amazon S3 object has a key that is its unique identifier in the bucket. Each object in a bucket has exactly one key. The prefix must end with a forward slash (/). For more information, see [Organizing objects using prefixes](#) in the *Amazon Simple Storage Service User Guide*.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ExpressionVariable

Contains expression variable information.

Contents

name

The friendly name of the variable to be used in the expression.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-z][a-z0-9_]*$`

Required: Yes

value

The variable that identifies an asset property from which to use values.

Type: [VariableValue](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

File

The file in Amazon S3 where your data is saved.

Contents

bucket

The name of the Amazon S3 bucket from which data is imported.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Required: Yes

key

The key of the Amazon S3 object that contains your data. Each object has a key that is a unique identifier. Each object has exactly one key.

Type: String

Required: Yes

versionId

The version ID to identify a specific version of the Amazon S3 object that contains your data.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

FileFormat

The file format of the data in S3.

Contents

csv

The file is in .CSV format.

Type: [Csv](#) object

Required: No

parquet

The file is in parquet format.

Type: [Parquet](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ForwardingConfig

The forwarding configuration for a given property.

Contents

state

The forwarding state for the given property.

Type: String

Valid Values: DISABLED | ENABLED

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

GatewayCapabilitySummary

Contains a summary of a gateway capability configuration.

Contents

capabilityNamespace

The namespace of the capability configuration. For example, if you configure OPC-UA sources from the Amazon IoT SiteWise console, your OPC-UA capability configuration has the namespace `iotsitewise:opcuacollector:version`, where `version` is a number such as 1.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `^[a-zA-Z]+:[a-zA-Z]+:[0-9]+$`

Required: Yes

capabilitySyncStatus

The synchronization status of the capability configuration. The sync status can be one of the following:

- `IN_SYNC` – The gateway is running the capability configuration.
- `NOT_APPLICABLE` – Synchronization is not required for this capability configuration. This is most common when integrating partner data sources, because the data integration is handled externally by the partner.
- `OUT_OF_SYNC` – The gateway hasn't received the capability configuration.
- `SYNC_FAILED` – The gateway rejected the capability configuration.
- `UNKNOWN` – The synchronization status is currently unknown due to an undetermined or temporary error.

Type: String

Valid Values: `IN_SYNC` | `OUT_OF_SYNC` | `SYNC_FAILED` | `UNKNOWN` | `NOT_APPLICABLE`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

GatewayPlatform

Contains a gateway's platform information.

Contents

greengrass

A gateway that runs on Amazon IoT Greengrass.

Type: [Greengrass](#) object

Required: No

greengrassV2

A gateway that runs on Amazon IoT Greengrass V2.

Type: [GreengrassV2](#) object

Required: No

siemensIE

A SiteWise Edge gateway that runs on a Siemens Industrial Edge Device.

Type: [SiemensIE](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

GatewaySummary

Contains a summary of a gateway.

Contents

creationDate

The date the gateway was created, in Unix epoch time.

Type: Timestamp

Required: Yes

gatewayId

The ID of the gateway device.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

gatewayName

The name of the gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

lastUpdateDate

The date the gateway was last updated, in Unix epoch time.

Type: Timestamp

Required: Yes

gatewayCapabilitySummaries

A list of gateway capability summaries that each contain a namespace and status. Each gateway capability defines data sources for the gateway. To retrieve a capability configuration's definition, use [DescribeGatewayCapabilityConfiguration](#).

Type: Array of [GatewayCapabilitySummary](#) objects

Required: No

gatewayPlatform

Contains a gateway's platform information.

Type: [GatewayPlatform](#) object

Required: No

gatewayVersion

The version of the gateway. A value of 3 indicates an MQTT-enabled, V3 gateway, while 2 indicates a Classic streams, V2 gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^[0-9]+$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Greengrass

Contains details for a gateway that runs on Amazon IoT Greengrass. To create a gateway that runs on Amazon IoT Greengrass, you must add the IoT SiteWise connector to a Greengrass group and deploy it. Your Greengrass group must also have permissions to upload data to Amazon IoT SiteWise. For more information, see [Ingesting data using a gateway](#) in the *Amazon IoT SiteWise User Guide*.

Contents

groupArn

The [ARN](#) of the Greengrass group. For more information about how to find a group's ARN, see [ListGroup](#)s and [GetGroup](#) in the *Amazon IoT Greengrass V1 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

GreengrassV2

Contains details for a gateway that runs on Amazon IoT Greengrass V2. To create a gateway that runs on Amazon IoT Greengrass V2, you must deploy the IoT SiteWise Edge component to your gateway device. Your [Greengrass device role](#) must use the `AWSIoTSiteWiseEdgeAccess` policy. For more information, see [Using Amazon IoT SiteWise at the edge](#) in the *Amazon IoT SiteWise User Guide*.

Contents

`coreDeviceThingName`

The name of the Amazon IoT thing for your Amazon IoT Greengrass V2 core device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9:_-]+$`

Required: Yes

`coreDeviceOperatingSystem`

The operating system of the core device in Amazon IoT Greengrass V2. Specifying the operating system is required for MQTT-enabled, V3 gateways (`gatewayVersion 3`) and not applicable for Classic stream, V2 gateways (`gatewayVersion 2`).

Type: String

Valid Values: `LINUX_AARCH64` | `LINUX_AMD64` | `WINDOWS_AMD64`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

GroupIdentity

Contains information for a group identity in an access policy.

Contents

id

The IAM Identity Center ID of the group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: \S+

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

IAMRoleIdentity

Contains information about an Amazon Identity and Access Management role. For more information, see [IAM roles](#) in the *IAM User Guide*.

Contents

arn

The ARN of the IAM role. For more information, see [IAM ARNs](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.\+=,@]+$`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

IAMUserIdentity

Contains information about an Amazon Identity and Access Management user.

Contents

arn

The ARN of the IAM user. For more information, see [IAM ARNs](#) in the *IAM User Guide*.

Note

If you delete the IAM user, access policies that contain this identity include an empty `arn`. You can delete the access policy for the IAM user that no longer exists.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.\+=,@]+$`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Identity

Contains an identity that can access an Amazon IoT SiteWise Monitor resource.

Note

Currently, you can't use Amazon API operations to retrieve IAM Identity Center identity IDs. You can find the IAM Identity Center identity IDs in the URL of user and group pages in the [IAM Identity Center console](#).

Contents

group

An IAM Identity Center group identity.

Type: [GroupIdentity](#) object

Required: No

iamRole

An IAM role identity.

Type: [IAMRoleIdentity](#) object

Required: No

iamUser

An IAM user identity.

Type: [IAMUserIdentity](#) object

Required: No

user

An IAM Identity Center user identity.

Type: [UserIdentity](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Image

Contains an image that is one of the following:

- An image file. Choose this option to upload a new image.
- The ID of an existing image. Choose this option to keep an existing image.

Contents

file

Contains an image file.

Type: [ImageFile](#) object

Required: No

id

The ID of an existing image. Specify this parameter to keep an existing image.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ImageFile

Contains an image file.

Contents

data

The image file contents, represented as a base64-encoded string. The file size must be less than 1 MB.

Type: Base64-encoded binary data object

Length Constraints: Minimum length of 1. Maximum length of 1500000.

Required: Yes

type

The file type of the image.

Type: String

Valid Values: PNG

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ImageLocation

Contains an image that is uploaded to Amazon IoT SiteWise and available at a URL.

Contents

id

The ID of the image.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

url

The URL where the image is available. The URL is valid for 15 minutes so that you can view and download the image

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^(http|https)\:\/\/\S+`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

InterpolatedAssetPropertyValue

Contains information about an interpolated asset property value.

Contents

timestamp

Contains a timestamp with optional nanosecond granularity.

Type: [TimeInNanos](#) object

Required: Yes

value

Contains an asset property value (of a single type only).

Type: [Variant](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

InvocationOutput

This contains the SiteWise Assistant's response and the corresponding citation.

Contents

citations

A list of citations, and related information for the SiteWise Assistant's response.

Type: Array of [Citation](#) objects

Required: No

message

The text message of the SiteWise Assistant's response.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

JobConfiguration

Contains the configuration information of a job, such as the file format used to save data in Amazon S3.

Contents

fileFormat

The file format of the data in S3.

Type: [FileFormat](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

JobSummary

Contains the job summary information.

Contents

id

The ID of the job.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

name

The unique name that helps identify the job request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

status

The status of the bulk import job can be one of following values:

- **PENDING** – Amazon IoT SiteWise is waiting for the current bulk import job to finish.
- **CANCELLED** – The bulk import job has been canceled.
- **RUNNING** – Amazon IoT SiteWise is processing your request to import your data from Amazon S3.
- **COMPLETED** – Amazon IoT SiteWise successfully completed your request to import data from Amazon S3.
- **FAILED** – Amazon IoT SiteWise couldn't process your request to import data from Amazon S3. You can use logs saved in the specified error report location in Amazon S3 to troubleshoot issues.

- `COMPLETED_WITH_FAILURES` – Amazon IoT SiteWise completed your request to import data from Amazon S3 with errors. You can use logs saved in the specified error report location in Amazon S3 to troubleshoot issues.

Type: String

Valid Values: `PENDING` | `CANCELLED` | `RUNNING` | `COMPLETED` | `FAILED` | `COMPLETED_WITH_FAILURES`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

KendraSourceDetail

The source details for the Kendra dataset source.

Contents

knowledgeBaseArn

The knowledgeBaseArn details for the Kendra dataset source.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

Required: Yes

roleArn

The roleARN details for the Kendra dataset source.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Location

Contains location information about the cited text and where it's stored.

Contents

uri

The URI of the location.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

LoggingOptions

Contains logging options.

Contents

level

The Amazon IoT SiteWise logging verbosity level.

Type: String

Valid Values: ERROR | INFO | OFF

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Measurement

Contains an asset measurement property. For more information, see [Measurements](#) in the *Amazon IoT SiteWise User Guide*.

Contents

processingConfig

The processing configuration for the given measurement property. You can configure measurements to be kept at the edge or forwarded to the Amazon Cloud. By default, measurements are forwarded to the cloud.

Type: [MeasurementProcessingConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

MeasurementProcessingConfig

The processing configuration for the given measurement property. You can configure measurements to be kept at the edge or forwarded to the Amazon Cloud. By default, measurements are forwarded to the cloud.

Contents

forwardingConfig

The forwarding configuration for the given measurement property.

Type: [ForwardingConfig](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Metric

Contains an asset metric property. With metrics, you can calculate aggregate functions, such as an average, maximum, or minimum, as specified through an expression. A metric maps several values to a single value (such as a sum).

The maximum number of dependent/cascading variables used in any one metric calculation is 10. Therefore, a *root* metric can have up to 10 cascading metrics in its computational dependency tree. Additionally, a metric can only have a data type of DOUBLE and consume properties with data types of INTEGER or DOUBLE.

For more information, see [Metrics](#) in the *Amazon IoT SiteWise User Guide*.

Contents

expression

The mathematical expression that defines the metric aggregation function. You can specify up to 10 variables per expression. You can specify up to 10 functions per expression.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

variables

The list of variables used in the expression.

Type: Array of [ExpressionVariable](#) objects

Required: Yes

window

The window (time interval) over which Amazon IoT SiteWise computes the metric's aggregation expression. Amazon IoT SiteWise computes one data point per window.

Type: [MetricWindow](#) object

Required: Yes

processingConfig

The processing configuration for the given metric property. You can configure metrics to be computed at the edge or in the Amazon Cloud. By default, metrics are forwarded to the cloud.

Type: [MetricProcessingConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

MetricProcessingConfig

The processing configuration for the given metric property. You can configure metrics to be computed at the edge or in the Amazon Cloud. By default, metrics are forwarded to the cloud.

Contents

computeLocation

The compute location for the given metric property.

Type: String

Valid Values: EDGE | CLOUD

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

MetricWindow

Contains a time interval window used for data aggregate computations (for example, average, sum, count, and so on).

Contents

tumbling

The tumbling time interval window.

Type: [TumblingWindow](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

MonitorErrorDetails

Contains Amazon IoT SiteWise Monitor error details.

Contents

code

The error code.

Type: String

Valid Values: INTERNAL_FAILURE | VALIDATION_ERROR | LIMIT_EXCEEDED

Required: No

message

The error message.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

MultiLayerStorage

Contains information about the storage destination.

Contents

customerManagedS3Storage

Contains information about a customer managed Amazon S3 bucket.

Type: [CustomerManagedS3Storage](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Parquet

A parquet file.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PortalResource

Identifies an Amazon IoT SiteWise Monitor portal.

Contents

id

The ID of the portal.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PortalStatus

Contains information about the current status of a portal.

Contents

state

The current state of the portal.

Type: String

Valid Values: CREATING | PENDING | UPDATING | DELETING | ACTIVE | FAILED

Required: Yes

error

Contains associated error information, if any.

Type: [MonitorErrorDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PortalSummary

Contains a portal summary.

Contents

id

The ID of the portal.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

name

The name of the portal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

startUrl

The URL for the Amazon IoT SiteWise Monitor portal. You can use this URL to access portals that use IAM Identity Center for authentication. For portals that use IAM for authentication, you must use the Amazon IoT SiteWise console to get a URL that you can use to access the portal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^(http|https)\:\/\/\S+`

Required: Yes

status

Contains information about the current status of a portal.

Type: [PortalStatus](#) object

Required: Yes

creationDate

The date the portal was created, in Unix epoch time.

Type: Timestamp

Required: No

description

The portal's description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

lastUpdateDate

The date the portal was last updated, in Unix epoch time.

Type: Timestamp

Required: No

portalType

Define the type of portal. The value for Amazon IoT SiteWise Monitor (Classic) is `SITWISE_PORTAL_V1`. The value for Amazon IoT SiteWise Monitor (AI-aware) is `SITWISE_PORTAL_V2`.

Type: String

Valid Values: `SITWISE_PORTAL_V1` | `SITWISE_PORTAL_V2`

Required: No

roleArn

The [ARN](#) of the service role that allows the portal's users to access your Amazon IoT SiteWise resources on your behalf. For more information, see [Using service roles for Amazon IoT SiteWise Monitor](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.\+=, @]+$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PortalTypeEntry

The configuration entry associated with the specific portal type. The `portalTypeConfiguration` is a map of the `portalTypeKey` to the `PortalTypeEntry`.

Contents

`portalTools`

The array of tools associated with the specified portal type. The possible values are `ASSISTANT` and `DASHBOARD`.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ProjectResource

Identifies a specific Amazon IoT SiteWise Monitor project.

Contents

id

The ID of the project.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ProjectSummary

Contains project summary information.

Contents

id

The ID of the project.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

name

The name of the project.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

creationDate

The date the project was created, in Unix epoch time.

Type: Timestamp

Required: No

description

The project's description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [^\u0000-\u001F\u007F]+

Required: No

lastUpdateDate

The date the project was last updated, in Unix epoch time.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Property

Contains asset property information.

Contents

dataType

The property data type.

Type: String

Valid Values: STRING | INTEGER | DOUBLE | BOOLEAN | STRUCT

Required: Yes

id

The ID of the asset property.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: Yes

name

The name of the property.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: Yes

alias

The alias that identifies the property, such as an OPC-UA server data stream path (for example, `/company/windfarm/3/turbine/7/temperature`). For more information, see [Mapping industrial data streams to asset properties](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

externalId

The external ID of the asset property. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Pattern: `[a-zA-Z0-9_][a-zA-Z_\-0-9.:]*[a-zA-Z0-9_]+`

Required: No

notification

The asset property's notification topic and state. For more information, see [UpdateAssetProperty](#).

Type: [PropertyNotification](#) object

Required: No

path

The structured path to the property from the root of the asset.

Type: Array of [AssetPropertyPathSegment](#) objects

Required: No

type

The property type (see [PropertyType](#)). A property contains one type.

Type: [PropertyType](#) object

Required: No

unit

The unit (such as Newtons or RPM) of the asset property.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PropertyNotification

Contains asset property value notification information. When the notification state is enabled, Amazon IoT SiteWise publishes property value updates to a unique MQTT topic. For more information, see [Interacting with other services](#) in the *Amazon IoT SiteWise User Guide*.

Contents

state

The current notification state.

Type: String

Valid Values: ENABLED | DISABLED

Required: Yes

topic

The MQTT topic to which Amazon IoT SiteWise publishes property value update notifications.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PropertyType

Contains a property type, which can be one of `attribute`, `measurement`, `metric`, or `transform`.

Contents

attribute

Specifies an asset attribute property. An attribute generally contains static information, such as the serial number of an [IIoT](#) wind turbine.

Type: [Attribute](#) object

Required: No

measurement

Specifies an asset measurement property. A measurement represents a device's raw sensor data stream, such as timestamped temperature values or timestamped power values.

Type: [Measurement](#) object

Required: No

metric

Specifies an asset metric property. A metric contains a mathematical expression that uses aggregate functions to process all input data points over a time interval and output a single data point, such as to calculate the average hourly temperature.

Type: [Metric](#) object

Required: No

transform

Specifies an asset transform property. A transform contains a mathematical expression that maps a property's data points from one form to another, such as a unit conversion from Celsius to Fahrenheit.

Type: [Transform](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PropertyValueNullValue

The value type of null asset property data with BAD and UNCERTAIN qualities.

Contents

valueType

The type of null asset property data.

Type: String

Valid Values: D | B | S | I | U

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PutAssetPropertyValueEntry

Contains a list of value updates for an asset property in the list of asset entries consumed by the [BatchPutAssetPropertyValue](#) API operation.

Contents

entryId

The user specified ID for the entry. You can use this ID to identify which entries failed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9_-]+$`

Required: Yes

propertyValues

The list of property values to upload. You can specify up to 10 `propertyValues` array elements.

Type: Array of [AssetPropertyValue](#) objects

Required: Yes

assetId

The ID of the asset to update.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

propertyAlias

The alias that identifies the property, such as an OPC-UA server data stream path (for example, `/company/windfarm/3/turbine/7/temperature`). For more information, see [Mapping industrial data streams to asset properties](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

propertyId

The ID of the asset property for this entry.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Reference

Contains the reference information.

Contents

dataset

Contains the dataset reference information.

Type: [DataSetReference](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Resource

Contains an Amazon IoT SiteWise Monitor resource ID for a portal or project.

Contents

portal

A portal resource.

Type: [PortalResource](#) object

Required: No

project

A project resource.

Type: [ProjectResource](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ResponseStream

Contains the response, citation, and trace from the SiteWise Assistant.

Contents

accessDeniedException

Access is denied.

Type: Exception

HTTP Status Code: 403

Required: No

conflictingOperationException

Your request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

Type: Exception

HTTP Status Code: 409

Required: No

internalFailureException

Amazon IoT SiteWise can't process your request right now. Try again later.

Type: Exception

HTTP Status Code: 500

Required: No

invalidRequestException

The request isn't valid. This can occur if your request contains malformed JSON or unsupported characters. Check your request and try again.

Type: Exception

HTTP Status Code: 400

Required: No

limitExceededException

You've reached the quota for a resource. For example, this can occur if you're trying to associate more than the allowed number of child assets or attempting to create more than the allowed number of properties for an asset model.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

Type: Exception

HTTP Status Code: 410

Required: No

output

Contains the SiteWise Assistant's response.

Type: [InvocationOutput](#) object

Required: No

resourceNotFoundException

The requested resource can't be found.

Type: Exception

HTTP Status Code: 404

Required: No

throttlingException

Your request exceeded a rate limit. For example, you might have exceeded the number of Amazon IoT SiteWise assets that can be created per second, the allowed number of messages per second, and so on.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

Type: Exception

HTTP Status Code: 429

Required: No

trace

Contains tracing information of the SiteWise Assistant's reasoning and data access.

Type: [Trace](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RetentionPeriod

The number of days your data is kept in the hot tier. By default, your data is kept indefinitely in the hot tier.

Contents

numberOfDays

The number of days that your data is kept.

Note

If you specified a value for this parameter, the `unlimited` parameter must be `false`.

Type: Integer

Required: No

unlimited

If `true`, your data is kept indefinitely.

Note

If configured to `true`, you must not specify a value for the `numberOfDays` parameter.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

Row

Represents a single row in the query results.

Contents

data

List of data points in a single row of the result set.

Type: Array of [Datum](#) objects

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SiemensIE

Contains details for a SiteWise Edge gateway that runs on a Siemens Industrial Edge Device.

Contents

`iotCoreThingName`

The name of the Amazon IoT Thing for your SiteWise Edge gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9:_-]+$`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Source

The data source for the dataset.

Contents

arn

Contains the ARN of the dataset. If the source is Kendra, it's the ARN of the Kendra index.

Type: String

Required: No

location

Contains the location information where the cited text is originally stored. For example, if the data source is Kendra, and the text synchronized is from an S3 bucket, then the location refers to an S3 object.

Type: [Location](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SourceDetail

The details of the dataset source associated with the dataset.

Contents

kendra

Contains details about the Kendra dataset source.

Type: [KendraSourceDetail](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

TimeInNanos

Contains a timestamp with optional nanosecond granularity.

Contents

timeInSeconds

The timestamp date, in seconds, in the Unix epoch format. Fractional nanosecond data is provided by `offsetInNanos`.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 9223372036854774.

Required: Yes

offsetInNanos

The nanosecond offset from `timeInSeconds`.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 999999999.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

TimeSeriesSummary

Contains a summary of a time series (data stream).

Contents

dataType

The data type of the time series.

If you specify STRUCT, you must also specify dataTypeSpec to identify the type of the structure for this time series.

Type: String

Valid Values: STRING | INTEGER | DOUBLE | BOOLEAN | STRUCT

Required: Yes

timeSeriesArn

The [ARN](#) of the time series, which has the following format.

```
arn:${Partition}:iotsitewise:${Region}:${Account}:time-series/  
${TimeSeriesId}
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^arn:aws(-cn|-us-gov)?:[a-zA-Z0-9-:\/_\.]+$`

Required: Yes

timeSeriesCreationDate

The date that the time series was created, in Unix epoch time.

Type: Timestamp

Required: Yes

timeSeriesId

The ID of the time series.

Type: String

Length Constraints: Minimum length of 36. Maximum length of 73.

Required: Yes

timeSeriesLastUpdateDate

The date that the time series was last updated, in Unix epoch time.

Type: Timestamp

Required: Yes

alias

The alias that identifies the time series.

Type: String

Length Constraints: Minimum length of 1.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

assetId

The ID of the asset in which the asset property was created.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

dataTypeSpec

The data type of the structure for this time series. This parameter is required for time series that have the STRUCT data type.

The options for this parameter depend on the type of the composite model in which you created the asset property that is associated with your time series. Use `AWS/ALARM_STATE` for alarm state in alarm composite models.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

propertyId

The ID of the asset property, in UUID format.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Trace

Contains tracing information of the SiteWise Assistant's reasoning and data access.

Contents

text

The cited text from the data source.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Transform

Contains an asset transform property. A transform is a one-to-one mapping of a property's data points from one form to another. For example, you can use a transform to convert a Celsius data stream to Fahrenheit by applying the transformation expression to each data point of the Celsius stream. A transform can only have a data type of DOUBLE and consume properties with data types of INTEGER or DOUBLE.

For more information, see [Transforms](#) in the *Amazon IoT SiteWise User Guide*.

Contents

expression

The mathematical expression that defines the transformation function. You can specify up to 10 variables per expression. You can specify up to 10 functions per expression.

For more information, see [Quotas](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

variables

The list of variables used in the expression.

Type: Array of [ExpressionVariable](#) objects

Required: Yes

processingConfig

The processing configuration for the given transform property. You can configure transforms to be kept at the edge or forwarded to the Amazon Cloud. You can also configure transforms to be computed at the edge or in the cloud.

Type: [TransformProcessingConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

TransformProcessingConfig

The processing configuration for the given transform property. You can configure transforms to be kept at the edge or forwarded to the Amazon Cloud. You can also configure transforms to be computed at the edge or in the cloud.

Contents

computeLocation

The compute location for the given transform property.

Type: String

Valid Values: EDGE | CLOUD

Required: Yes

forwardingConfig

The forwarding configuration for a given property.

Type: [ForwardingConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

TumblingWindow

Contains a tumbling window, which is a repeating fixed-sized, non-overlapping, and contiguous time window. You can use this window in metrics to aggregate data from properties and other assets.

You can use `m`, `h`, `d`, and `w` when you specify an interval or offset. Note that `m` represents minutes, `h` represents hours, `d` represents days, and `w` represents weeks. You can also use `s` to represent seconds in offset.

The `interval` and `offset` parameters support the [ISO 8601 format](#). For example, `PT5S` represents 5 seconds, `PT5M` represents 5 minutes, and `PT5H` represents 5 hours.

Contents

interval

The time interval for the tumbling window. The interval time must be between 1 minute and 1 week.

Amazon IoT SiteWise computes the `1w` interval the end of Sunday at midnight each week (UTC), the `1d` interval at the end of each day at midnight (UTC), the `1h` interval at the end of each hour, and so on.

When Amazon IoT SiteWise aggregates data points for metric computations, the start of each interval is exclusive and the end of each interval is inclusive. Amazon IoT SiteWise places the computed data point at the end of the interval.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 23.

Required: Yes

offset

The offset for the tumbling window. The `offset` parameter accepts the following:

- The offset time.

For example, if you specify `18h` for `offset` and `1d` for `interval`, Amazon IoT SiteWise aggregates data in one of the following ways:

- If you create the metric before or at 6 PM (UTC), you get the first aggregation result at 6 PM (UTC) on the day when you create the metric.
- If you create the metric after 6 PM (UTC), you get the first aggregation result at 6 PM (UTC) the next day.
- The ISO 8601 format.

For example, if you specify `PT18H` for `offset` and `1d` for `interval`, Amazon IoT SiteWise aggregates data in one of the following ways:

- If you create the metric before or at 6 PM (UTC), you get the first aggregation result at 6 PM (UTC) on the day when you create the metric.
- If you create the metric after 6 PM (UTC), you get the first aggregation result at 6 PM (UTC) the next day.
- The 24-hour clock.

For example, if you specify `00:03:00` for `offset`, `5m` for `interval`, and you create the metric at 2 PM (UTC), you get the first aggregation result at 2:03 PM (UTC). You get the second aggregation result at 2:08 PM (UTC).

- The offset time zone.

For example, if you specify `2021-07-23T18:00-08` for `offset` and `1d` for `interval`, Amazon IoT SiteWise aggregates data in one of the following ways:

- If you create the metric before or at 6 PM (PST), you get the first aggregation result at 6 PM (PST) on the day when you create the metric.
- If you create the metric after 6 PM (PST), you get the first aggregation result at 6 PM (PST) the next day.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 25.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

UserIdentity

Contains information for a user identity in an access policy.

Contents

id

The IAM Identity Center ID of the user.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: \S+

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

VariableValue

Identifies a property value used in an expression.

Contents

hierarchyId

The ID of the hierarchy to query for the property ID. You can use the hierarchy's name instead of the hierarchy's ID. If the hierarchy has an external ID, you can specify `externalId`: followed by the external ID. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

You use a hierarchy ID instead of a model ID because you can have several hierarchies using the same model and therefore the same `propertyId`. For example, you might have separately grouped assets that come from the same asset model. For more information, see [Asset hierarchies](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

propertyId

The ID of the property to use as the variable. You can use the property name if it's from the same asset model. If the property has an external ID, you can specify `externalId`: followed by the external ID. For more information, see [Using external IDs](#) in the *Amazon IoT SiteWise User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

propertyPath

The path of the property.

Type: Array of [AssetModelPropertyPathSegment](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Variant

Contains an asset property value (of a single type only).

Contents

booleanValue

Asset property data of type Boolean (true or false).

Type: Boolean

Required: No

doubleValue

Asset property data of type double (floating point number). The min value is -10^{10} . The max value is 10^{10} . Double.NaN is allowed.

Type: Double

Required: No

integerValue

Asset property data of type integer (whole number).

Type: Integer

Required: No

nullValue

The type of null asset property data with BAD and UNCERTAIN qualities.

Type: [PropertyValueNullValue](#) object

Required: No

stringValue

Asset property data of type string (sequence of characters). The allowed pattern: " $^{\$}[[^{\u0000-\u001F\u007F}]^{+}$ ". The max length is 1024.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

WarmTierRetentionPeriod

Set this period to specify how long your data is stored in the warm tier before it is deleted. You can set this only if cold tier is enabled.

Contents

numberOfDays

The number of days the data is stored in the warm tier.

Type: Integer

Required: No

unlimited

If set to true, the data is stored indefinitely in the warm tier.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing Amazon API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed Amazon API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an Amazon API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to Amazon Security Token Service (Amazon STS). For a list of services that support temporary security credentials from Amazon STS, see [Amazon Web Services services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from Amazon STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed Amazon API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all Amazon services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to Amazon standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientId

The X.509 certificate or Amazon access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The Amazon access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an Amazon service.

HTTP Status Code: 400