

Amazon License Manager



Amazon License Manager: API Reference

Table of Contents

Welcome	1
Actions	2
AcceptGrant	5
Request Syntax	5
Request Parameters	5
Response Syntax	5
Response Elements	5
Errors	6
See Also	7
CheckInLicense	9
Request Syntax	9
Request Parameters	9
Response Elements	9
Errors	9
See Also	11
CheckoutBorrowLicense	12
Request Syntax	12
Request Parameters	12
Response Syntax	14
Response Elements	14
Errors	16
See Also	17
CheckoutLicense	19
Request Syntax	19
Request Parameters	19
Response Syntax	21
Response Elements	21
Errors	23
See Also	24
CreateGrant	25
Request Syntax	25
Request Parameters	25
Response Syntax	27
Response Elements	27

Errors	28
See Also	29
CreateGrantVersion	31
Request Syntax	31
Request Parameters	31
Response Syntax	33
Response Elements	33
Errors	34
See Also	35
CreateLicense	37
Request Syntax	37
Request Parameters	38
Response Syntax	40
Response Elements	40
Errors	41
See Also	42
CreateLicenseAssetGroup	43
Request Syntax	43
Request Parameters	43
Response Syntax	45
Response Elements	45
Errors	45
See Also	46
CreateLicenseAssetRuleset	48
Request Syntax	48
Request Parameters	51
Response Syntax	52
Response Elements	52
Errors	52
See Also	53
CreateLicenseConfiguration	55
Request Syntax	55
Request Parameters	56
Response Syntax	58
Response Elements	58
Errors	58

See Also	59
CreateLicenseConversionTaskForResource	61
Request Syntax	61
Request Parameters	61
Response Syntax	62
Response Elements	62
Errors	63
See Also	64
CreateLicenseManagerReportGenerator	65
Request Syntax	65
Request Parameters	65
Response Syntax	67
Response Elements	67
Errors	67
See Also	68
CreateLicenseVersion	70
Request Syntax	70
Request Parameters	71
Response Syntax	73
Response Elements	73
Errors	74
See Also	75
CreateToken	77
Request Syntax	77
Request Parameters	77
Response Syntax	78
Response Elements	79
Errors	79
See Also	80
DeleteGrant	82
Request Syntax	82
Request Parameters	82
Response Syntax	83
Response Elements	83
Errors	84
See Also	85

DeleteLicense	86
Request Syntax	86
Request Parameters	86
Response Syntax	86
Response Elements	87
Errors	87
See Also	88
DeleteLicenseAssetGroup	90
Request Syntax	90
Request Parameters	90
Response Syntax	90
Response Elements	90
Errors	91
See Also	92
DeleteLicenseAssetRuleset	93
Request Syntax	93
Request Parameters	93
Response Elements	93
Errors	93
See Also	94
DeleteLicenseConfiguration	96
Request Syntax	96
Request Parameters	96
Response Elements	96
Errors	96
See Also	97
DeleteLicenseManagerReportGenerator	99
Request Syntax	99
Request Parameters	99
Response Elements	99
Errors	99
See Also	100
DeleteToken	102
Request Syntax	102
Request Parameters	102
Response Elements	102

Errors	102
See Also	103
ExtendLicenseConsumption	105
Request Syntax	105
Request Parameters	105
Response Syntax	105
Response Elements	106
Errors	106
See Also	107
GetAccessToken	109
Request Syntax	109
Request Parameters	109
Response Syntax	109
Response Elements	110
Errors	110
See Also	111
GetGrant	112
Request Syntax	112
Request Parameters	112
Response Syntax	112
Response Elements	113
Errors	113
See Also	114
GetLicense	116
Request Syntax	116
Request Parameters	116
Response Syntax	116
Response Elements	118
Errors	118
See Also	119
GetLicenseAssetGroup	120
Request Syntax	120
Request Parameters	120
Response Syntax	120
Response Elements	121
Errors	121

See Also	122
GetLicenseAssetRuleset	124
Request Syntax	124
Request Parameters	124
Response Syntax	124
Response Elements	127
Errors	128
See Also	128
GetLicenseConfiguration	130
Request Syntax	130
Request Parameters	130
Response Syntax	130
Response Elements	131
Errors	134
See Also	134
GetLicenseConversionTask	136
Request Syntax	136
Request Parameters	136
Response Syntax	136
Response Elements	137
Errors	138
See Also	139
GetLicenseManagerReportGenerator	141
Request Syntax	141
Request Parameters	141
Response Syntax	141
Response Elements	142
Errors	142
See Also	143
GetLicenseUsage	145
Request Syntax	145
Request Parameters	145
Response Syntax	145
Response Elements	146
Errors	146
See Also	147

GetServiceSettings	148
Response Syntax	148
Response Elements	148
Errors	149
See Also	150
ListAssetsForLicenseAssetGroup	152
Request Syntax	152
Request Parameters	152
Response Syntax	153
Response Elements	153
Errors	153
See Also	154
ListAssociationsForLicenseConfiguration	156
Request Syntax	156
Request Parameters	156
Response Syntax	157
Response Elements	157
Errors	157
See Also	158
ListDistributedGrants	160
Request Syntax	160
Request Parameters	160
Response Syntax	161
Response Elements	162
Errors	162
See Also	163
ListFailuresForLicenseConfigurationOperations	165
Request Syntax	165
Request Parameters	165
Response Syntax	166
Response Elements	166
Errors	167
See Also	167
ListLicenseAssetGroups	169
Request Syntax	169
Request Parameters	169

Response Syntax	170
Response Elements	170
Errors	171
See Also	172
ListLicenseAssetRulesets	173
Request Syntax	173
Request Parameters	173
Response Syntax	174
Response Elements	177
Errors	177
See Also	178
ListLicenseConfigurations	180
Request Syntax	180
Request Parameters	180
Response Syntax	181
Response Elements	182
Errors	183
See Also	183
ListLicenseConfigurationsForOrganization	185
Request Syntax	185
Request Parameters	185
Response Syntax	186
Response Elements	187
Errors	187
See Also	188
ListLicenseConversionTasks	190
Request Syntax	190
Request Parameters	190
Response Syntax	191
Response Elements	191
Errors	192
See Also	193
ListLicenseManagerReportGenerators	194
Request Syntax	194
Request Parameters	194
Response Syntax	195

Response Elements	196
Errors	196
See Also	197
ListLicenses	199
Request Syntax	199
Request Parameters	199
Response Syntax	200
Response Elements	201
Errors	202
See Also	203
ListLicenseSpecificationsForResource	204
Request Syntax	204
Request Parameters	204
Response Syntax	205
Response Elements	205
Errors	205
See Also	206
ListLicenseVersions	207
Request Syntax	207
Request Parameters	207
Response Syntax	208
Response Elements	209
Errors	209
See Also	210
ListReceivedGrants	212
Request Syntax	212
Request Parameters	212
Response Syntax	213
Response Elements	214
Errors	214
See Also	215
ListReceivedGrantsForOrganization	217
Request Syntax	217
Request Parameters	217
Response Syntax	218
Response Elements	219

Errors	219
See Also	220
ListReceivedLicenses	221
Request Syntax	221
Request Parameters	221
Response Syntax	222
Response Elements	224
Errors	224
See Also	225
ListReceivedLicensesForOrganization	226
Request Syntax	226
Request Parameters	226
Response Syntax	227
Response Elements	228
Errors	229
See Also	230
ListResourceInventory	231
Request Syntax	231
Request Parameters	231
Response Syntax	232
Response Elements	233
Errors	233
See Also	234
ListTagsForResource	235
Request Syntax	235
Request Parameters	235
Response Syntax	235
Response Elements	235
Errors	236
See Also	237
ListTokens	238
Request Syntax	238
Request Parameters	238
Response Syntax	239
Response Elements	239
Errors	240

See Also	240
ListUsageForLicenseConfiguration	242
Request Syntax	242
Request Parameters	242
Response Syntax	243
Response Elements	243
Errors	244
See Also	245
RejectGrant	246
Request Syntax	246
Request Parameters	246
Response Syntax	246
Response Elements	246
Errors	247
See Also	248
TagResource	250
Request Syntax	250
Request Parameters	250
Response Elements	251
Errors	251
See Also	252
UntagResource	253
Request Syntax	253
Request Parameters	253
Response Elements	253
Errors	253
See Also	254
UpdateLicenseAssetGroup	256
Request Syntax	256
Request Parameters	256
Response Syntax	258
Response Elements	258
Errors	259
See Also	260
UpdateLicenseAssetRuleset	261
Request Syntax	261

Request Parameters	264
Response Syntax	265
Response Elements	265
Errors	265
See Also	266
UpdateLicenseConfiguration	268
Request Syntax	268
Request Parameters	268
Response Elements	270
Errors	270
See Also	271
UpdateLicenseManagerReportGenerator	273
Request Syntax	273
Request Parameters	273
Response Elements	275
Errors	275
See Also	276
UpdateLicenseSpecificationsForResource	278
Request Syntax	278
Request Parameters	278
Response Elements	279
Errors	279
See Also	280
UpdateServiceSettings	282
Request Syntax	282
Request Parameters	282
Response Elements	283
Errors	283
See Also	284
Data Types	285
AndRuleStatement	288
Contents	288
See Also	288
Asset	289
Contents	289
See Also	289

AutomatedDiscoveryInformation	290
Contents	290
See Also	290
BorrowConfiguration	291
Contents	291
See Also	291
ConsumedLicenseSummary	292
Contents	292
See Also	292
ConsumptionConfiguration	293
Contents	293
See Also	293
CrossAccountDiscoveryServiceStatus	294
Contents	294
See Also	294
CrossRegionDiscoveryStatus	295
Contents	295
See Also	295
DatetimeRange	296
Contents	296
See Also	296
Entitlement	298
Contents	298
See Also	299
EntitlementData	300
Contents	300
See Also	300
EntitlementUsage	302
Contents	302
See Also	303
Filter	304
Contents	304
See Also	304
Grant	305
Contents	305
See Also	307

GrantedLicense	309
Contents	309
See Also	312
InstanceRuleStatement	313
Contents	313
See Also	313
InventoryFilter	315
Contents	315
See Also	315
Issuer	316
Contents	316
See Also	316
IssuerDetails	317
Contents	317
See Also	317
License	318
Contents	318
See Also	320
LicenseAssetGroup	322
Contents	322
See Also	324
LicenseAssetGroupConfiguration	325
Contents	325
See Also	325
LicenseAssetGroupProperty	326
Contents	326
See Also	326
LicenseAssetRule	327
Contents	327
See Also	327
LicenseAssetRuleset	328
Contents	328
See Also	329
LicenseConfiguration	330
Contents	330
See Also	333

LicenseConfigurationAssociation	334
Contents	334
See Also	335
LicenseConfigurationRuleStatement	336
Contents	336
See Also	336
LicenseConfigurationUsage	337
Contents	337
See Also	338
LicenseConversionContext	339
Contents	339
See Also	339
LicenseConversionTask	340
Contents	340
See Also	341
LicenseOperationFailure	343
Contents	343
See Also	344
LicenseRuleStatement	345
Contents	345
See Also	345
LicenseSpecification	346
Contents	346
See Also	346
LicenseUsage	347
Contents	347
See Also	347
ManagedResourceSummary	348
Contents	348
See Also	348
MatchingRuleStatement	349
Contents	349
See Also	350
Metadata	351
Contents	351
See Also	351

Options	352
Contents	352
See Also	353
OrganizationConfiguration	354
Contents	354
See Also	354
OrRuleStatement	355
Contents	355
See Also	355
ProductCodeListItem	356
Contents	356
See Also	356
ProductInformation	357
Contents	357
See Also	358
ProductInformationFilter	359
Contents	359
See Also	359
ProvisionalConfiguration	360
Contents	360
See Also	360
ReceivedMetadata	361
Contents	361
See Also	362
RegionStatus	363
Contents	363
See Also	363
ReportContext	364
Contents	364
See Also	365
ReportFrequency	366
Contents	366
See Also	366
ReportGenerator	367
Contents	367
See Also	369

ResourceInventory	370
Contents	370
See Also	372
RuleStatement	373
Contents	373
See Also	373
S3Location	374
Contents	374
See Also	374
ScriptRuleStatement	375
Contents	375
See Also	375
ServiceStatus	376
Contents	376
See Also	376
Tag	377
Contents	377
See Also	377
TokenData	378
Contents	378
See Also	379
Common Parameters	380
Common Errors	383

Welcome

Amazon License Manager makes it easier to manage licenses from software vendors across multiple Amazon Web Services accounts and on-premises servers.

This document was last published on February 14, 2026.

Actions

The following actions are supported:

- [AcceptGrant](#)
- [CheckInLicense](#)
- [CheckoutBorrowLicense](#)
- [CheckoutLicense](#)
- [CreateGrant](#)
- [CreateGrantVersion](#)
- [CreateLicense](#)
- [CreateLicenseAssetGroup](#)
- [CreateLicenseAssetRuleset](#)
- [CreateLicenseConfiguration](#)
- [CreateLicenseConversionTaskForResource](#)
- [CreateLicenseManagerReportGenerator](#)
- [CreateLicenseVersion](#)
- [CreateToken](#)
- [DeleteGrant](#)
- [DeleteLicense](#)
- [DeleteLicenseAssetGroup](#)
- [DeleteLicenseAssetRuleset](#)
- [DeleteLicenseConfiguration](#)
- [DeleteLicenseManagerReportGenerator](#)
- [DeleteToken](#)
- [ExtendLicenseConsumption](#)
- [GetAccessToken](#)
- [GetGrant](#)
- [GetLicense](#)
- [GetLicenseAssetGroup](#)
- [GetLicenseAssetRuleset](#)

- [GetLicenseConfiguration](#)
- [GetLicenseConversionTask](#)
- [GetLicenseManagerReportGenerator](#)
- [GetLicenseUsage](#)
- [GetServiceSettings](#)
- [ListAssetsForLicenseAssetGroup](#)
- [ListAssociationsForLicenseConfiguration](#)
- [ListDistributedGrants](#)
- [ListFailuresForLicenseConfigurationOperations](#)
- [ListLicenseAssetGroups](#)
- [ListLicenseAssetRulesets](#)
- [ListLicenseConfigurations](#)
- [ListLicenseConfigurationsForOrganization](#)
- [ListLicenseConversionTasks](#)
- [ListLicenseManagerReportGenerators](#)
- [ListLicenses](#)
- [ListLicenseSpecificationsForResource](#)
- [ListLicenseVersions](#)
- [ListReceivedGrants](#)
- [ListReceivedGrantsForOrganization](#)
- [ListReceivedLicenses](#)
- [ListReceivedLicensesForOrganization](#)
- [ListResourceInventory](#)
- [ListTagsForResource](#)
- [ListTokens](#)
- [ListUsageForLicenseConfiguration](#)
- [RejectGrant](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateLicenseAssetGroup](#)

- [UpdateLicenseAssetRuleset](#)
- [UpdateLicenseConfiguration](#)
- [UpdateLicenseManagerReportGenerator](#)
- [UpdateLicenseSpecificationsForResource](#)
- [UpdateServiceSettings](#)

AcceptGrant

Accepts the specified grant.

Request Syntax

```
{  
  "GrantArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[GrantArn](#)

Amazon Resource Name (ARN) of the grant.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

Response Syntax

```
{  
  "GrantArn": "string",  
  "Status": "string",  
  "Version": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

GrantArn

Grant ARN.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Status

Grant status.

Type: String

Valid Values: PENDING_WORKFLOW | PENDING_ACCEPT | REJECTED | ACTIVE
| FAILED_WORKFLOW | DELETED | PENDING_DELETE | DISABLED |
WORKFLOW_COMPLETED

Version

Grant version.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CheckInLicense

Checks in the specified license. Check in a license when it is no longer in use.

Request Syntax

```
{  
  "Beneficiary": "string",  
  "LicenseConsumptionToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Beneficiary

License beneficiary.

Type: String

Required: No

LicenseConsumptionToken

License consumption token.

Type: String

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

ConflictException

There was a conflict processing the request. Try your request again.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CheckoutBorrowLicense

Checks out the specified license for offline use.

Request Syntax

```
{
  "CheckoutMetadata": [
    {
      "Name": "string",
      "Value": "string"
    }
  ],
  "ClientToken": "string",
  "DigitalSignatureMethod": "string",
  "Entitlements": [
    {
      "Name": "string",
      "Unit": "string",
      "Value": "string"
    }
  ],
  "LicenseArn": "string",
  "NodeId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

CheckoutMetadata

Information about constraints.

Type: Array of [Metadata](#) objects

Required: No

ClientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: \S+

Required: Yes

DigitalSignatureMethod

Digital signature method. The possible value is JSON Web Signature (JWS) algorithm PS384. For more information, see [RFC 7518 Digital Signature with RSASSA-PSS](#).

Type: String

Valid Values: JWT_PS384

Required: Yes

Entitlements

License entitlements. Partial checkouts are not supported.

Type: Array of [EntitlementData](#) objects

Required: Yes

LicenseArn

Amazon Resource Name (ARN) of the license. The license must use the borrow consumption configuration.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: ^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}\$

Required: Yes

NodeId

Node ID.

Type: String

Required: No

Response Syntax

```
{
  "CheckoutMetadata": [
    {
      "Name": "string",
      "Value": "string"
    }
  ],
  "EntitlementsAllowed": [
    {
      "Name": "string",
      "Unit": "string",
      "Value": "string"
    }
  ],
  "Expiration": "string",
  "IssuedAt": "string",
  "LicenseArn": "string",
  "LicenseConsumptionToken": "string",
  "NodeId": "string",
  "SignedToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CheckoutMetadata

Information about constraints.

Type: Array of [Metadata](#) objects

EntitlementsAllowed

Allowed license entitlements.

Type: Array of [EntitlementData](#) objects

Expiration

Date and time at which the license checkout expires.

Type: String

Length Constraints: Maximum length of 50.

Pattern: `^(-?(?:[1-9][0-9]*)?[0-9]{4})-(1[0-2]|0[1-9])-(3[0-1]|0[1-9]|[1-2][0-9])T(2[0-3]|[0-1][0-9]):([0-5][0-9]):([0-5][0-9])(\.[0-9]+)?(Z|[+-](?:2[0-3]|[0-1][0-9]):[0-5][0-9])+$`

IssuedAt

Date and time at which the license checkout is issued.

Type: String

Length Constraints: Maximum length of 50.

Pattern: `^(-?(?:[1-9][0-9]*)?[0-9]{4})-(1[0-2]|0[1-9])-(3[0-1]|0[1-9]|[1-2][0-9])T(2[0-3]|[0-1][0-9]):([0-5][0-9]):([0-5][0-9])(\.[0-9]+)?(Z|[+-](?:2[0-3]|[0-1][0-9]):[0-5][0-9])+$`

LicenseArn

Amazon Resource Name (ARN) of the license.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+ =, @ . -]{0,1023}$`

LicenseConsumptionToken

License consumption token.

Type: String

NodeId

Node ID.

Type: String

SignedToken

Signed token.

Type: String

Length Constraints: Minimum length of 4096.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

EntitlementNotAllowedException

The entitlement is not allowed.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

NoEntitlementsAllowedException

There are no entitlements found for this license, or the entitlement maximum count is reached.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

RedirectException

This is not the correct Region for the resource. Try again.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

UnsupportedDigitalSignatureMethodException

The digital signature method is unsupported. Try your request again.

HTTP Status Code: 400

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)

- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CheckoutLicense

Checks out the specified license.

Note

If the account that created the license is the same that is performing the check out, you must specify the account as the beneficiary.

Request Syntax

```
{
  "Beneficiary": "string",
  "CheckoutType": "string",
  "ClientToken": "string",
  "Entitlements": [
    {
      "Name": "string",
      "Unit": "string",
      "Value": "string"
    }
  ],
  "KeyFingerprint": "string",
  "NodeId": "string",
  "ProductSKU": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Beneficiary

License beneficiary.

Type: String

Required: No

CheckoutType

Checkout type.

Type: String

Valid Values: PROVISIONAL | PERPETUAL

Required: Yes

ClientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: \S+

Required: Yes

Entitlements

License entitlements.

Type: Array of [EntitlementData](#) objects

Required: Yes

KeyFingerprint

Key fingerprint identifying the license.

Type: String

Required: Yes

NodeId

Node ID.

Type: String

Required: No

ProductSKU

Product SKU.

Type: String

Required: Yes

Response Syntax

```
{
  "CheckoutType": "string",
  "EntitlementsAllowed": [
    {
      "Name": "string",
      "Unit": "string",
      "Value": "string"
    }
  ],
  "Expiration": "string",
  "IssuedAt": "string",
  "LicenseArn": "string",
  "LicenseConsumptionToken": "string",
  "NodeId": "string",
  "SignedToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CheckoutType

Checkout type.

Type: String

Valid Values: PROVISIONAL | PERPETUAL

EntitlementsAllowed

Allowed license entitlements.

Type: Array of [EntitlementData](#) objects

Expiration

Date and time at which the license checkout expires.

Type: String

Length Constraints: Maximum length of 50.

Pattern: `^(-?(?:[1-9][0-9]*)?[0-9]{4})-(1[0-2]|0[1-9])-(3[0-1]|0[1-9]|[1-2][0-9])T(2[0-3]|[0-1][0-9]):([0-5][0-9]):([0-5][0-9])(\.[0-9]+)?(Z|[+-](?:2[0-3]|[0-1][0-9]):[0-5][0-9])+$`

IssuedAt

Date and time at which the license checkout is issued.

Type: String

Length Constraints: Maximum length of 50.

Pattern: `^(-?(?:[1-9][0-9]*)?[0-9]{4})-(1[0-2]|0[1-9])-(3[0-1]|0[1-9]|[1-2][0-9])T(2[0-3]|[0-1][0-9]):([0-5][0-9]):([0-5][0-9])(\.[0-9]+)?(Z|[+-](?:2[0-3]|[0-1][0-9]):[0-5][0-9])+$`

LicenseArn

Amazon Resource Name (ARN) of the checkout license.

Type: String

LicenseConsumptionToken

License consumption token.

Type: String

NodeId

Node ID.

Type: String

SignedToken

Signed token.

Type: String

Length Constraints: Minimum length of 4096.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

NoEntitlementsAllowedException

There are no entitlements found for this license, or the entitlement maximum count is reached.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

RedirectException

This is not the correct Region for the resource. Try again.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

UnsupportedDigitalSignatureMethodException

The digital signature method is unsupported. Try your request again.

HTTP Status Code: 400

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateGrant

Creates a grant for the specified license. A grant shares the use of license entitlements with a specific Amazon Web Services account, an organization, or an organizational unit (OU). For more information, see [Granted licenses in License Manager](#) in the *Amazon License Manager User Guide*.

Request Syntax

```
{
  "AllowedOperations": [ "string" ],
  "ClientToken": "string",
  "GrantName": "string",
  "HomeRegion": "string",
  "LicenseArn": "string",
  "Principals": [ "string" ],
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AllowedOperations](#)

Allowed operations for the grant.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 8 items.

Valid Values: CreateGrant | CheckoutLicense | CheckoutBorrowLicense |
CheckInLicense | ExtendConsumptionLicense | ListPurchasedLicenses |
CreateToken

Required: Yes

ClientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: \S+

Required: Yes

GrantName

Grant name.

Type: String

Required: Yes

HomeRegion

Home Region of the grant.

Type: String

Required: Yes

LicenseArn

Amazon Resource Name (ARN) of the license.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.-]{0,1023}$`

Required: Yes

Principals

The grant principals. You can specify one of the following as an Amazon Resource Name (ARN):

- An Amazon account, which includes only the account specified.

- An organizational unit (OU), which includes all accounts in the OU.
- An organization, which will include all accounts across your organization.

Type: Array of strings

Array Members: Fixed number of 1 item.

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

Tags

Tags to add to the grant. For more information about tagging support in License Manager, see the [TagResource](#) operation.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
{
  "GrantArn": "string",
  "Status": "string",
  "Version": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[GrantArn](#)

Grant ARN.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Status

Grant status.

Type: String

Valid Values: PENDING_WORKFLOW | PENDING_ACCEPT | REJECTED | ACTIVE
| FAILED_WORKFLOW | DELETED | PENDING_DELETE | DISABLED |
WORKFLOW_COMPLETED

Version

Grant version.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateGrantVersion

Creates a new version of the specified grant. For more information, see [Granted licenses in License Manager](#) in the *Amazon License Manager User Guide*.

Request Syntax

```
{
  "AllowedOperations": [ "string" ],
  "ClientToken": "string",
  "GrantArn": "string",
  "GrantName": "string",
  "Options": {
    "ActivationOverrideBehavior": "string"
  },
  "SourceVersion": "string",
  "Status": "string",
  "StatusReason": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AllowedOperations](#)

Allowed operations for the grant.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 8 items.

Valid Values: CreateGrant | CheckoutLicense | CheckoutBorrowLicense |
CheckInLicense | ExtendConsumptionLicense | ListPurchasedLicenses |
CreateToken

Required: No

[ClientToken](#)

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: \S+

Required: Yes

GrantArn

Amazon Resource Name (ARN) of the grant.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: ^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.-]{0,1023}\$

Required: Yes

GrantName

Grant name.

Type: String

Required: No

Options

The options specified for the grant.

Type: [Options](#) object

Required: No

SourceVersion

Current version of the grant.

Type: String

Required: No

Status

Grant status.

Type: String

Valid Values: PENDING_WORKFLOW | PENDING_ACCEPT | REJECTED | ACTIVE
| FAILED_WORKFLOW | DELETED | PENDING_DELETE | DISABLED |
WORKFLOW_COMPLETED

Required: No

StatusReason

Grant status reason.

Type: String

Length Constraints: Maximum length of 400.

Pattern: [\s\S]+

Required: No

Response Syntax

```
{  
  "GrantArn": "string",  
  "Status": "string",  
  "Version": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

GrantArn

Grant ARN.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Status

Grant status.

Type: String

Valid Values: PENDING_WORKFLOW | PENDING_ACCEPT | REJECTED | ACTIVE
| FAILED_WORKFLOW | DELETED | PENDING_DELETE | DISABLED |
WORKFLOW_COMPLETED

Version

New version of the grant.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateLicense

Creates a license.

Request Syntax

```
{
  "Beneficiary": "string",
  "ClientToken": "string",
  "ConsumptionConfiguration": {
    "BorrowConfiguration": {
      "AllowEarlyCheckIn": boolean,
      "MaxTimeToLiveInMinutes": number
    },
    "ProvisionalConfiguration": {
      "MaxTimeToLiveInMinutes": number
    },
    "RenewType": "string"
  },
  "Entitlements": [
    {
      "AllowCheckIn": boolean,
      "MaxCount": number,
      "Name": "string",
      "Overage": boolean,
      "Unit": "string",
      "Value": "string"
    }
  ],
  "HomeRegion": "string",
  "Issuer": {
    "Name": "string",
    "SignKey": "string"
  },
  "LicenseMetadata": [
    {
      "Name": "string",
      "Value": "string"
    }
  ],
  "LicenseName": "string",
  "ProductName": "string",
  "ProductSKU": "string",
```



```
"Tags": [
  {
    "Key": "string",
    "Value": "string"
  }
],
"Validity": {
  "Begin": "string",
  "End": "string"
}
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Beneficiary

License beneficiary.

Type: String

Required: Yes

ClientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: \S+

Required: Yes

ConsumptionConfiguration

Configuration for consumption of the license. Choose a provisional configuration for workloads running with continuous connectivity. Choose a borrow configuration for workloads with offline usage.

Type: [ConsumptionConfiguration](#) object

Required: Yes

Entitlements

License entitlements.

Type: Array of [Entitlement](#) objects

Required: Yes

HomeRegion

Home Region for the license.

Type: String

Required: Yes

Issuer

License issuer.

Type: [Issuer](#) object

Required: Yes

LicenseMetadata

Information about the license.

Type: Array of [Metadata](#) objects

Required: No

LicenseName

License name.

Type: String

Required: Yes

ProductName

Product name.

Type: String

Required: Yes

ProductSKU

Product SKU.

Type: String

Required: Yes

Tags

Tags to add to the license. For more information about tagging support in License Manager, see the [TagResource](#) operation.

Type: Array of [Tag](#) objects

Required: No

Validity

Date and time range during which the license is valid, in ISO8601-UTC format.

Type: [DatetimeRange](#) object

Required: Yes

Response Syntax

```
{
  "LicenseArn": "string",
  "Status": "string",
  "Version": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LicenseArn

Amazon Resource Name (ARN) of the license.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Status

License status.

Type: String

Valid Values: AVAILABLE | PENDING_AVAILABLE | DEACTIVATED | SUSPENDED | EXPIRED | PENDING_DELETE | DELETED

Version

License version.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

RedirectException

This is not the correct Region for the resource. Try again.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateLicenseAssetGroup

Creates a license asset group.

Request Syntax

```
{
  "AssociatedLicenseAssetRulesetARNs": [ "string" ],
  "ClientToken": "string",
  "Description": "string",
  "LicenseAssetGroupConfigurations": [
    {
      "UsageDimension": "string"
    }
  ],
  "Name": "string",
  "Properties": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AssociatedLicenseAssetRulesetARNs

ARNs of associated license asset rulesets.

Type: Array of strings

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

ClientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request.

Type: String

Required: Yes

Description

License asset group description.

Type: String

Length Constraints: Maximum length of 1024.

Required: No

LicenseAssetGroupConfigurations

License asset group configurations.

Type: Array of [LicenseAssetGroupConfiguration](#) objects

Required: Yes

Name

License asset group name.

Type: String

Length Constraints: Maximum length of 128.

Required: Yes

Properties

License asset group properties.

Type: Array of [LicenseAssetGroupProperty](#) objects

Required: No

Tags

Tags to add to the license asset group.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
{  
  "LicenseAssetGroupArn": "string",  
  "Status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LicenseAssetGroupArn

Amazon Resource Name (ARN) of the license asset group.

Type: String

Status

License asset group status.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateLicenseAssetRuleset

Creates a license asset ruleset.

Request Syntax

```
{
  "ClientToken": "string",
  "Description": "string",
  "Name": "string",
  "Rules": [
    {
      "RuleStatement": {
        "InstanceRuleStatement": {
          "AndRuleStatement": {
            "MatchingRuleStatements": [
              {
                "Constraint": "string",
                "KeyToMatch": "string",
                "ValueToMatch": [ "string" ]
              }
            ],
            "ScriptRuleStatements": [
              {
                "KeyToMatch": "string",
                "Script": "string"
              }
            ]
          },
          "MatchingRuleStatement": {
            "Constraint": "string",
            "KeyToMatch": "string",
            "ValueToMatch": [ "string" ]
          },
          "OrRuleStatement": {
            "MatchingRuleStatements": [
              {
                "Constraint": "string",
                "KeyToMatch": "string",
                "ValueToMatch": [ "string" ]
              }
            ],
            "ScriptRuleStatements": [
```

```

        {
            "KeyToMatch": "string",
            "Script": "string"
        }
    ],
    },
    "ScriptRuleStatement": {
        "KeyToMatch": "string",
        "Script": "string"
    }
},
"LicenseConfigurationRuleStatement": {
    "AndRuleStatement": {
        "MatchingRuleStatements": [
            {
                "Constraint": "string",
                "KeyToMatch": "string",
                "ValueToMatch": [ "string" ]
            }
        ],
        "ScriptRuleStatements": [
            {
                "KeyToMatch": "string",
                "Script": "string"
            }
        ]
    },
    "MatchingRuleStatement": {
        "Constraint": "string",
        "KeyToMatch": "string",
        "ValueToMatch": [ "string" ]
    },
    "OrRuleStatement": {
        "MatchingRuleStatements": [
            {
                "Constraint": "string",
                "KeyToMatch": "string",
                "ValueToMatch": [ "string" ]
            }
        ],
        "ScriptRuleStatements": [
            {
                "KeyToMatch": "string",
                "Script": "string"
            }
        ]
    }
}

```

```

    }
  ]
}
},
"LicenseRuleStatement": {
  "AndRuleStatement": {
    "MatchingRuleStatements": [
      {
        "Constraint": "string",
        "KeyToMatch": "string",
        "ValueToMatch": [ "string" ]
      }
    ],
    "ScriptRuleStatements": [
      {
        "KeyToMatch": "string",
        "Script": "string"
      }
    ]
  },
  "MatchingRuleStatement": {
    "Constraint": "string",
    "KeyToMatch": "string",
    "ValueToMatch": [ "string" ]
  },
  "OrRuleStatement": {
    "MatchingRuleStatements": [
      {
        "Constraint": "string",
        "KeyToMatch": "string",
        "ValueToMatch": [ "string" ]
      }
    ],
    "ScriptRuleStatements": [
      {
        "KeyToMatch": "string",
        "Script": "string"
      }
    ]
  }
}
}
}
},
],

```

```
"Tags": [  
  {  
    "Key": "string",  
    "Value": "string"  
  }  
]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request.

Type: String

Required: Yes

Description

License asset ruleset description.

Type: String

Length Constraints: Maximum length of 1024.

Required: No

Name

License asset ruleset name.

Type: String

Length Constraints: Maximum length of 128.

Required: Yes

Rules

License asset rules.

Type: Array of [LicenseAssetRule](#) objects

Required: Yes

Tags

Tags to add to the license asset ruleset.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
{  
  "LicenseAssetRulesetArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LicenseAssetRulesetArn

Amazon Resource Name (ARN) of the license asset ruleset.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateLicenseConfiguration

Creates a license configuration.

A license configuration is an abstraction of a customer license agreement that can be consumed and enforced by License Manager. Components include specifications for the license type (licensing by instance, socket, CPU, or vCPU), allowed tenancy (shared tenancy, Dedicated Instance, Dedicated Host, or all of these), license affinity to host (how long a license must be associated with a host), and the number of licenses purchased and used.

Request Syntax

```
{
  "Description": "string",
  "DisassociateWhenNotFound": boolean,
  "LicenseCount": number,
  "LicenseCountHardLimit": boolean,
  "LicenseCountingType": "string",
  "LicenseExpiry": number,
  "LicenseRules": [ "string" ],
  "Name": "string",
  "ProductInformationList": [
    {
      "ProductInformationFilterList": [
        {
          "ProductInformationFilterComparator": "string",
          "ProductInformationFilterName": "string",
          "ProductInformationFilterValue": [ "string" ]
        }
      ],
      "ResourceType": "string"
    }
  ],
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Description

Description of the license configuration.

Type: String

Required: No

DisassociateWhenNotFound

When true, disassociates a resource when software is uninstalled.

Type: Boolean

Required: No

LicenseCount

Number of licenses managed by the license configuration.

Type: Long

Required: No

LicenseCountHardLimit

Indicates whether hard or soft license enforcement is used. Exceeding a hard limit blocks the launch of new instances.

Type: Boolean

Required: No

LicenseCountingType

Dimension used to track the license inventory.

Type: String

Valid Values: vCPU | Instance | Core | Socket

Required: Yes

LicenseExpiry

License configuration expiry.

Type: Long

Required: No

LicenseRules

License rules. The syntax is #name=value (for example, #allowedTenancy=EC2-DedicatedHost). The available rules vary by dimension, as follows.

- Cores dimension: allowedTenancy | licenseAffinityToHost | maximumCores | minimumCores
- Instances dimension: allowedTenancy | maximumVcpus | minimumVcpus
- Sockets dimension: allowedTenancy | licenseAffinityToHost | maximumSockets | minimumSockets
- vCPUs dimension: allowedTenancy | honorVcpuOptimization | maximumVcpus | minimumVcpus

The unit for licenseAffinityToHost is days and the range is 1 to 180. The possible values for allowedTenancy are EC2-Default, EC2-DedicatedHost, and EC2-DedicatedInstance. The possible values for honorVcpuOptimization are True and False.

Type: Array of strings

Required: No

Name

Name of the license configuration.

Type: String

Required: Yes

ProductInformationList

Product information.

Type: Array of [ProductInformation](#) objects

Required: No

Tags

Tags to add to the license configuration.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
{  
  "LicenseConfigurationArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LicenseConfigurationArn

Amazon Resource Name (ARN) of the license configuration.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateLicenseConversionTaskForResource

Creates a new license conversion task.

Request Syntax

```
{
  "DestinationLicenseContext": {
    "ProductCodes": [
      {
        "ProductCodeId": "string",
        "ProductCodeType": "string"
      }
    ],
    "UsageOperation": "string"
  },
  "ResourceArn": "string",
  "SourceLicenseContext": {
    "ProductCodes": [
      {
        "ProductCodeId": "string",
        "ProductCodeType": "string"
      }
    ],
    "UsageOperation": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DestinationLicenseContext

Information that identifies the license type you are converting to. For the structure of the destination license, see [Convert a license type using the Amazon CLI](#) in the *Amazon License Manager User Guide*.

Type: [LicenseConversionContext](#) object

Required: Yes

ResourceArn

Amazon Resource Name (ARN) of the resource you are converting the license type for.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.-]{0,1023}$`

Required: Yes

SourceLicenseContext

Information that identifies the license type you are converting from. For the structure of the source license, see [Convert a license type using the Amazon CLI](#) in the *Amazon License Manager User Guide*.

Type: [LicenseConversionContext](#) object

Required: Yes

Response Syntax

```
{
  "LicenseConversionTaskId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LicenseConversionTaskId

The ID of the created license type conversion task.

Type: String

Length Constraints: Maximum length of 50.

Pattern: `^[a-z0-9]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateLicenseManagerReportGenerator

Creates a report generator.

Request Syntax

```
{
  "ClientToken": "string",
  "Description": "string",
  "ReportContext": {
    "licenseAssetGroupArns": [ "string" ],
    "licenseConfigurationArns": [ "string" ],
    "reportEndDate": number,
    "reportStartDate": number
  },
  "ReportFrequency": {
    "period": "string",
    "value": number
  },
  "ReportGeneratorName": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "Type": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Required: Yes

Description

Description of the report generator.

Type: String

Required: No

ReportContext

Defines the type of license configuration the report generator tracks.

Type: [ReportContext](#) object

Required: Yes

ReportFrequency

Frequency by which reports are generated. Reports can be generated daily, monthly, or weekly.

Type: [ReportFrequency](#) object

Required: Yes

ReportGeneratorName

Name of the report generator.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

Tags

Tags to add to the report generator.

Type: Array of [Tag](#) objects

Required: No

Type

Type of reports to generate. The following report types can be generated:

- License configuration report - Reports the number and details of consumed licenses for a license configuration.
- Resource report - Reports the tracked licenses and resource consumption for a license configuration.

Type: Array of strings

Valid Values: LicenseConfigurationSummaryReport | LicenseConfigurationUsageReport | LicenseAssetGroupUsageReport

Required: Yes

Response Syntax

```
{  
  "LicenseManagerReportGeneratorArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[LicenseManagerReportGeneratorArn](#)

The Amazon Resource Name (ARN) of the new report generator.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateLicenseVersion

Creates a new version of the specified license.

Request Syntax

```
{
  "ClientToken": "string",
  "ConsumptionConfiguration": {
    "BorrowConfiguration": {
      "AllowEarlyCheckIn": boolean,
      "MaxTimeToLiveInMinutes": number
    },
    "ProvisionalConfiguration": {
      "MaxTimeToLiveInMinutes": number
    },
    "RenewType": "string"
  },
  "Entitlements": [
    {
      "AllowCheckIn": boolean,
      "MaxCount": number,
      "Name": "string",
      "Overage": boolean,
      "Unit": "string",
      "Value": "string"
    }
  ],
  "HomeRegion": "string",
  "Issuer": {
    "Name": "string",
    "SignKey": "string"
  },
  "LicenseArn": "string",
  "LicenseMetadata": [
    {
      "Name": "string",
      "Value": "string"
    }
  ],
  "LicenseName": "string",
  "ProductName": "string",
  "SourceVersion": "string",
```

```
"Status": "string",
"Validity": {
  "Begin": "string",
  "End": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: \S+

Required: Yes

ConsumptionConfiguration

Configuration for consumption of the license. Choose a provisional configuration for workloads running with continuous connectivity. Choose a borrow configuration for workloads with offline usage.

Type: [ConsumptionConfiguration](#) object

Required: Yes

Entitlements

License entitlements.

Type: Array of [Entitlement](#) objects

Required: Yes

HomeRegion

Home Region of the license.

Type: String

Required: Yes

Issuer

License issuer.

Type: [Issuer](#) object

Required: Yes

LicenseArn

Amazon Resource Name (ARN) of the license.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

LicenseMetadata

Information about the license.

Type: Array of [Metadata](#) objects

Required: No

LicenseName

License name.

Type: String

Required: Yes

ProductName

Product name.

Type: String

Required: Yes

SourceVersion

Current version of the license.

Type: String

Required: No

Status

License status.

Type: String

Valid Values: AVAILABLE | PENDING_AVAILABLE | DEACTIVATED | SUSPENDED | EXPIRED | PENDING_DELETE | DELETED

Required: Yes

Validity

Date and time range during which the license is valid, in ISO8601-UTC format.

Type: [DatetimeRange](#) object

Required: Yes

Response Syntax

```
{
  "LicenseArn": "string",
  "Status": "string",
  "Version": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LicenseArn

License ARN.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Status

License status.

Type: String

Valid Values: AVAILABLE | PENDING_AVAILABLE | DEACTIVATED | SUSPENDED | EXPIRED | PENDING_DELETE | DELETED

Version

New version of the license.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

ConflictException

There was a conflict processing the request. Try your request again.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

RedirectException

This is not the correct Region for the resource. Try again.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)

- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateToken

Creates a long-lived token.

A refresh token is a JWT token used to get an access token. With an access token, you can call `AssumeRoleWithWebIdentity` to get role credentials that you can use to call License Manager to manage the specified license.

Request Syntax

```
{  
  "ClientToken": "string",  
  "ExpirationInDays": number,  
  "LicenseArn": "string",  
  "RoleArns": [ "string" ],  
  "TokenProperties": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

Idempotency token, valid for 10 minutes.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `\S+`

Required: Yes

ExpirationInDays

Token expiration, in days, counted from token creation. The default is 365 days.

Type: Integer

Required: No

LicenseArn

Amazon Resource Name (ARN) of the license. The ARN is mapped to the aud claim of the JWT token.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

RoleArns

Amazon Resource Name (ARN) of the IAM roles to embed in the token. License Manager does not check whether the roles are in use.

Type: Array of strings

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: No

TokenProperties

Data specified by the caller to be included in the JWT token. The data is mapped to the amr claim of the JWT token.

Type: Array of strings

Array Members: Maximum number of 3 items.

Required: No

Response Syntax

```
{
```

```
"Token": "string",  
"TokenId": "string",  
"TokenType": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Token

Refresh token, encoded as a JWT token.

Type: String

Length Constraints: Maximum length of 4096.

Pattern: \S+

TokenId

Token ID.

Type: String

TokenType

Token type.

Type: String

Valid Values: REFRESH_TOKEN

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

RedirectException

This is not the correct Region for the resource. Try again.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteGrant

Deletes the specified grant.

Request Syntax

```
{  
  "GrantArn": "string",  
  "StatusReason": "string",  
  "Version": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

GrantArn

Amazon Resource Name (ARN) of the grant.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

StatusReason

The Status reason for the delete request.

Type: String

Length Constraints: Maximum length of 400.

Pattern: `[\s\S]+`

Required: No

Version

Current version of the grant.

Type: String

Required: Yes

Response Syntax

```
{
  "GrantArn": "string",
  "Status": "string",
  "Version": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

GrantArn

Grant ARN.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Status

Grant status.

Type: String

Valid Values: PENDING_WORKFLOW | PENDING_ACCEPT | REJECTED | ACTIVE
| FAILED_WORKFLOW | DELETED | PENDING_DELETE | DISABLED |
WORKFLOW_COMPLETED

Version

Grant version.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteLicense

Deletes the specified license.

Request Syntax

```
{  
  "LicenseArn": "string",  
  "SourceVersion": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

LicenseArn

Amazon Resource Name (ARN) of the license.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

SourceVersion

Current version of the license.

Type: String

Required: Yes

Response Syntax

```
{
```

```
"DeletionDate": "string",  
"Status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DeletionDate

Date when the license is deleted.

Type: String

Length Constraints: Maximum length of 50.

Pattern: `^(-?(?:[1-9][0-9]*)?[0-9]{4})-(1[0-2]|0[1-9])-(3[0-1]|0[1-9]|[1-2][0-9])T(2[0-3]|[0-1][0-9]):([0-5][0-9]):([0-5][0-9])(\.[0-9]+)?(Z|[+-](?:2[0-3]|0[0-1][0-9]):[0-5][0-9])+$`

Status

License status.

Type: String

Valid Values: PENDING_DELETE | DELETED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

ConflictException

There was a conflict processing the request. Try your request again.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

RedirectException

This is not the correct Region for the resource. Try again.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)

- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteLicenseAssetGroup

Deletes a license asset group.

Request Syntax

```
{  
  "LicenseAssetGroupArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[LicenseAssetGroupArn](#)

Amazon Resource Name (ARN) of the license asset group.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

Response Syntax

```
{  
  "Status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Status

License asset group status.

Type: String

Valid Values: ACTIVE | DISABLED | DELETED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteLicenseAssetRuleset

Deletes a license asset ruleset.

Request Syntax

```
{  
  "LicenseAssetRulesetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[LicenseAssetRulesetArn](#)

Amazon Resource Name (ARN) of the license asset ruleset.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteLicenseConfiguration

Deletes the specified license configuration.

You cannot delete a license configuration that is in use.

Request Syntax

```
{  
  "LicenseConfigurationArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[LicenseConfigurationArn](#)

ID of the license configuration.

Type: String

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteLicenseManagerReportGenerator

Deletes the specified report generator.

This action deletes the report generator, which stops it from generating future reports. The action cannot be reversed. It has no effect on the previous reports from this generator.

Request Syntax

```
{  
  "LicenseManagerReportGeneratorArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[LicenseManagerReportGeneratorArn](#)

Amazon Resource Name (ARN) of the report generator to be deleted.

Type: String

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteToken

Deletes the specified token. Must be called in the license home Region.

Request Syntax

```
{  
  "TokenId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

TokenId

Token ID.

Type: String

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

RedirectException

This is not the correct Region for the resource. Try again.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ExtendLicenseConsumption

Extends the expiration date for license consumption.

Request Syntax

```
{  
  "DryRun": boolean,  
  "LicenseConsumptionToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DryRun

Checks whether you have the required permissions for the action, without actually making the request. Provides an error response if you do not have the required permissions.

Type: Boolean

Required: No

LicenseConsumptionToken

License consumption token.

Type: String

Required: Yes

Response Syntax

```
{  
  "Expiration": "string",  
  "LicenseConsumptionToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Expiration

Date and time at which the license consumption expires.

Type: String

Length Constraints: Maximum length of 50.

Pattern: `^(-(?:[1-9][0-9]*)?[0-9]{4})-(1[0-2]|0[1-9])-(3[0-1]|0[1-9]|[1-2][0-9])T(2[0-3]|0[0-9]):([0-5][0-9]):([0-5][0-9])(\.[0-9]+)?(Z|[+-](?:2[0-3]|0[0-9]):[0-5][0-9])+$`

LicenseConsumptionToken

License consumption token.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetAccessToken

Gets a temporary access token to use with AssumeRoleWithWebIdentity. Access tokens are valid for one hour.

Request Syntax

```
{  
  "Token": "string",  
  "TokenProperties": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Token

Refresh token, encoded as a JWT token.

Type: String

Length Constraints: Maximum length of 4096.

Pattern: \S+

Required: Yes

TokenProperties

Token properties to validate against those present in the JWT token.

Type: Array of strings

Array Members: Maximum number of 3 items.

Required: No

Response Syntax

```
{
```



```
"AccessToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccessToken

Temporary access token.

Type: String

Length Constraints: Maximum length of 4096.

Pattern: \S+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetGrant

Gets detailed information about the specified grant.

Request Syntax

```
{  
  "GrantArn": "string",  
  "Version": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

GrantArn

Amazon Resource Name (ARN) of the grant.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.-]{0,1023}$`

Required: Yes

Version

Grant version.

Type: String

Required: No

Response Syntax

```
{
```

```
"Grant": {
  "GrantArn": "string",
  "GrantedOperations": [ "string" ],
  "GranteePrincipalArn": "string",
  "GrantName": "string",
  "GrantStatus": "string",
  "HomeRegion": "string",
  "LicenseArn": "string",
  "Options": {
    "ActivationOverrideBehavior": "string"
  },
  "ParentArn": "string",
  "StatusReason": "string",
  "Version": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Grant

Grant details.

Type: [Grant](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetLicense

Gets detailed information about the specified license.

Request Syntax

```
{
  "LicenseArn": "string",
  "Version": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

LicenseArn

Amazon Resource Name (ARN) of the license.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

Version

License version.

Type: String

Required: No

Response Syntax

```
{
  "License": {
```

```
"Beneficiary": "string",
"ConsumptionConfiguration": {
  "BorrowConfiguration": {
    "AllowEarlyCheckIn": boolean,
    "MaxTimeToLiveInMinutes": number
  },
  "ProvisionalConfiguration": {
    "MaxTimeToLiveInMinutes": number
  },
  "RenewType": "string"
},
"CreateTime": "string",
"Entitlements": [
  {
    "AllowCheckIn": boolean,
    "MaxCount": number,
    "Name": "string",
    "Overage": boolean,
    "Unit": "string",
    "Value": "string"
  }
],
"HomeRegion": "string",
"Issuer": {
  "KeyFingerprint": "string",
  "Name": "string",
  "SignKey": "string"
},
"LicenseArn": "string",
"LicenseMetadata": [
  {
    "Name": "string",
    "Value": "string"
  }
],
"LicenseName": "string",
"ProductName": "string",
"ProductSKU": "string",
"Status": "string",
"Validity": {
  "Begin": "string",
  "End": "string"
},
"Version": "string"
```



```
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

License

License details.

Type: [License](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetLicenseAssetGroup

Gets a license asset group.

Request Syntax

```
{  
  "LicenseAssetGroupArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[LicenseAssetGroupArn](#)

Amazon Resource Name (ARN) of the license asset group.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

Response Syntax

```
{  
  "LicenseAssetGroup": {  
    "AssociatedLicenseAssetRulesetARNs": [ "string" ],  
    "Description": "string",  
    "LatestResourceDiscoveryTime": number,  
    "LatestUsageAnalysisTime": number,  
    "LicenseAssetGroupArn": "string",  
    "LicenseAssetGroupConfigurations": [  

```

```
{
  "UsageDimension": "string"
},
{
  "Name": "string",
  "Properties": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "Status": "string",
  "StatusMessage": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[LicenseAssetGroup](#)

License asset group.

Type: [LicenseAssetGroup](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetLicenseAssetRuleset

Gets a license asset ruleset.

Request Syntax

```
{  
  "LicenseAssetRulesetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[LicenseAssetRulesetArn](#)

Amazon Resource Name (ARN) of the license asset ruleset.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

Response Syntax

```
{  
  "LicenseAssetRuleset": {  
    "Description": "string",  
    "LicenseAssetRulesetArn": "string",  
    "Name": "string",  
    "Rules": [  
      {  
        "RuleStatement": {  
          "InstanceRuleStatement": {  
            "AndRuleStatement": {
```

```

    "MatchingRuleStatements": [
      {
        "Constraint": "string",
        "KeyToMatch": "string",
        "ValueToMatch": [ "string" ]
      }
    ],
    "ScriptRuleStatements": [
      {
        "KeyToMatch": "string",
        "Script": "string"
      }
    ]
  },
  "MatchingRuleStatement": {
    "Constraint": "string",
    "KeyToMatch": "string",
    "ValueToMatch": [ "string" ]
  },
  "OrRuleStatement": {
    "MatchingRuleStatements": [
      {
        "Constraint": "string",
        "KeyToMatch": "string",
        "ValueToMatch": [ "string" ]
      }
    ],
    "ScriptRuleStatements": [
      {
        "KeyToMatch": "string",
        "Script": "string"
      }
    ]
  },
  "ScriptRuleStatement": {
    "KeyToMatch": "string",
    "Script": "string"
  }
},
"LicenseConfigurationRuleStatement": {
  "AndRuleStatement": {
    "MatchingRuleStatements": [
      {
        "Constraint": "string",

```



```

        "KeyToMatch": "string",
        "ValueToMatch": [ "string" ]
    }
],
"ScriptRuleStatements": [
    {
        "KeyToMatch": "string",
        "Script": "string"
    }
]
},
"MatchingRuleStatement": {
    "Constraint": "string",
    "KeyToMatch": "string",
    "ValueToMatch": [ "string" ]
},
"OrRuleStatement": {
    "MatchingRuleStatements": [
        {
            "Constraint": "string",
            "KeyToMatch": "string",
            "ValueToMatch": [ "string" ]
        }
    ],
    "ScriptRuleStatements": [
        {
            "KeyToMatch": "string",
            "Script": "string"
        }
    ]
}
},
"LicenseRuleStatement": {
    "AndRuleStatement": {
        "MatchingRuleStatements": [
            {
                "Constraint": "string",
                "KeyToMatch": "string",
                "ValueToMatch": [ "string" ]
            }
        ],
        "ScriptRuleStatements": [
            {
                "KeyToMatch": "string",

```

```

        "Script": "string"
      }
    ]
  },
  "MatchingRuleStatement": {
    "Constraint": "string",
    "KeyToMatch": "string",
    "ValueToMatch": [ "string" ]
  },
  "OrRuleStatement": {
    "MatchingRuleStatements": [
      {
        "Constraint": "string",
        "KeyToMatch": "string",
        "ValueToMatch": [ "string" ]
      }
    ],
    "ScriptRuleStatements": [
      {
        "KeyToMatch": "string",
        "Script": "string"
      }
    ]
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LicenseAssetRuleset

License asset ruleset.

Type: [LicenseAssetRuleset](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetLicenseConfiguration

Gets detailed information about the specified license configuration.

Request Syntax

```
{  
  "LicenseConfigurationArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[LicenseConfigurationArn](#)

Amazon Resource Name (ARN) of the license configuration.

Type: String

Required: Yes

Response Syntax

```
{  
  "AutomatedDiscoveryInformation": {  
    "LastRunTime": number  
  },  
  "ConsumedLicenses": number,  
  "ConsumedLicenseSummaryList": [  
    {  
      "ConsumedLicenses": number,  
      "ResourceType": "string"  
    }  
  ],  
  "Description": "string",  
  "DisassociateWhenNotFound": boolean,  
  "LicenseConfigurationArn": "string",  
  "LicenseConfigurationId": "string",  
}
```

```

    "LicenseCount": number,
    "LicenseCountHardLimit": boolean,
    "LicenseCountingType": "string",
    "LicenseExpiry": number,
    "LicenseRules": [ "string" ],
    "ManagedResourceSummaryList": [
      {
        "AssociationCount": number,
        "ResourceType": "string"
      }
    ],
    "Name": "string",
    "OwnerAccountId": "string",
    "ProductInformationList": [
      {
        "ProductInformationFilterList": [
          {
            "ProductInformationFilterComparator": "string",
            "ProductInformationFilterName": "string",
            "ProductInformationFilterValue": [ "string" ]
          }
        ],
        "ResourceType": "string"
      }
    ],
    "Status": "string",
    "Tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ]
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AutomatedDiscoveryInformation

Automated discovery information.

Type: [AutomatedDiscoveryInformation](#) object

[ConsumedLicenses](#)

Number of licenses assigned to resources.

Type: Long

[ConsumedLicenseSummaryList](#)

Summaries of the licenses consumed by resources.

Type: Array of [ConsumedLicenseSummary](#) objects

[Description](#)

Description of the license configuration.

Type: String

[DisassociateWhenNotFound](#)

When true, disassociates a resource when software is uninstalled.

Type: Boolean

[LicenseConfigurationArn](#)

Amazon Resource Name (ARN) of the license configuration.

Type: String

[LicenseConfigurationId](#)

Unique ID for the license configuration.

Type: String

[LicenseCount](#)

Number of available licenses.

Type: Long

[LicenseCountHardLimit](#)

Sets the number of available licenses as a hard limit.

Type: Boolean

LicenseCountingType

Dimension for which the licenses are counted.

Type: String

Valid Values: vCPU | Instance | Core | Socket

LicenseExpiry

License Expiry.

Type: Long

LicenseRules

License rules.

Type: Array of strings

ManagedResourceSummaryList

Summaries of the managed resources.

Type: Array of [ManagedResourceSummary](#) objects

Name

Name of the license configuration.

Type: String

OwnerAccountId

Account ID of the owner of the license configuration.

Type: String

ProductInformationList

Product information.

Type: Array of [ProductInformation](#) objects

Status

License configuration status.

Type: String

[Tags](#)

Tags for the license configuration.

Type: Array of [Tag](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetLicenseConversionTask

Gets information about the specified license type conversion task.

Request Syntax

```
{  
  "LicenseConversionTaskId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[LicenseConversionTaskId](#)

ID of the license type conversion task to retrieve information on.

Type: String

Length Constraints: Maximum length of 50.

Pattern: `^lct-[a-zA-Z0-9]*`

Required: Yes

Response Syntax

```
{  
  "DestinationLicenseContext": {  
    "ProductCodes": [  
      {  
        "ProductCodeId": "string",  
        "ProductCodeType": "string"  
      }  
    ],  
    "UsageOperation": "string"  
  },  
  "EndTime": number,  
}
```

```
"LicenseConversionTaskId": "string",
"LicenseConversionTime": number,
"ResourceArn": "string",
"SourceLicenseContext": {
  "ProductCodes": [
    {
      "ProductCodeId": "string",
      "ProductCodeType": "string"
    }
  ],
  "UsageOperation": "string"
},
"StartTime": number,
"Status": "string",
"StatusMessage": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DestinationLicenseContext

Information about the license type converted to.

Type: [LicenseConversionContext](#) object

EndTime

Time at which the license type conversion task was completed.

Type: Timestamp

LicenseConversionTaskId

ID of the license type conversion task.

Type: String

Length Constraints: Maximum length of 50.

Pattern: `^[lct-][a-zA-Z0-9]*`

LicenseConversionTime

Amount of time to complete the license type conversion.

Type: Timestamp

ResourceArn

Amazon Resource Names (ARN) of the resources the license conversion task is associated with.

Type: String

SourceLicenseContext

Information about the license type converted from.

Type: [LicenseConversionContext](#) object

StartTime

Time at which the license type conversion task was started .

Type: Timestamp

Status

Status of the license type conversion task.

Type: String

Valid Values: IN_PROGRESS | SUCCEEDED | FAILED

StatusMessage

The status message for the conversion task.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

GetLicenseManagerReportGenerator

Gets information about the specified report generator.

Request Syntax

```
{  
  "LicenseManagerReportGeneratorArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[LicenseManagerReportGeneratorArn](#)

Amazon Resource Name (ARN) of the report generator.

Type: String

Required: Yes

Response Syntax

```
{  
  "ReportGenerator": {  
    "CreateTime": "string",  
    "Description": "string",  
    "LastReportGenerationTime": "string",  
    "LastRunFailureReason": "string",  
    "LastRunStatus": "string",  
    "LicenseManagerReportGeneratorArn": "string",  
    "ReportContext": {  
      "licenseAssetGroupArns": [ "string" ],  
      "licenseConfigurationArns": [ "string" ],  
      "reportEndDate": number,  
      "reportStartDate": number  
    },  
  },  
}
```



```
"ReportCreatorAccount": "string",
"ReportFrequency": {
  "period": "string",
  "value": number
},
"ReportGeneratorName": "string",
"ReportType": [ "string" ],
"S3Location": {
  "bucket": "string",
  "keyPrefix": "string"
},
"Tags": [
  {
    "Key": "string",
    "Value": "string"
  }
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ReportGenerator

A report generator that creates periodic reports about your license configurations.

Type: [ReportGenerator](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetLicenseUsage

Gets detailed information about the usage of the specified license.

Request Syntax

```
{  
  "LicenseArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[LicenseArn](#)

Amazon Resource Name (ARN) of the license.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.-]{0,1023}$`

Required: Yes

Response Syntax

```
{  
  "LicenseUsage": {  
    "EntitlementUsages": [  
      {  
        "ConsumedValue": "string",  
        "MaxCount": "string",  
        "Name": "string",  
        "Unit": "string"  
      }  
    ]  
  }  
}
```

```
    }  
  ]  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LicenseUsage

License usage details.

Type: [LicenseUsage](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetServiceSettings

Gets the License Manager settings for the current Region.

Response Syntax

```
{
  "CrossRegionDiscoveryHomeRegion": "string",
  "CrossRegionDiscoverySourceRegions": [ "string" ],
  "EnableCrossAccountsDiscovery": boolean,
  "LicenseManagerResourceShareArn": "string",
  "OrganizationConfiguration": {
    "EnableIntegration": boolean
  },
  "S3BucketArn": "string",
  "ServiceStatus": {
    "CrossAccountDiscovery": {
      "Message": "string"
    },
    "CrossRegionDiscovery": {
      "Message": {
        "string" : {
          "Status": "string"
        }
      }
    }
  },
  "SnsTopicArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[CrossRegionDiscoveryHomeRegion](#)

Cross region discovery home region.

Type: String

[CrossRegionDiscoverySourceRegions](#)

Cross region discovery source regions.

Type: Array of strings

[EnableCrossAccountsDiscovery](#)

Indicates whether cross-account discovery is enabled.

Type: Boolean

[LicenseManagerResourceShareArn](#)

Amazon Resource Name (ARN) of the resource share. The License Manager management account provides member accounts with access to this share.

Type: String

[OrganizationConfiguration](#)

Indicates whether Amazon Organizations is integrated with License Manager for cross-account discovery.

Type: [OrganizationConfiguration](#) object

[S3BucketArn](#)

Regional S3 bucket path for storing reports, license trail event data, discovery data, and so on.

Type: String

[ServiceStatus](#)

Service status.

Type: [ServiceStatus](#) object

[SnsTopicArn](#)

SNS topic configured to receive notifications from License Manager.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListAssetsForLicenseAssetGroup

Lists assets for a license asset group.

Request Syntax

```
{  
  "AssetType": "string",  
  "LicenseAssetGroupArn": "string",  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AssetType

Asset type. The possible values are Instance | License | LicenseConfiguration.

Type: String

Required: Yes

LicenseAssetGroupArn

Amazon Resource Name (ARN) of the license asset group.

Type: String

Required: Yes

MaxResults

Maximum number of results to return in a single call.

Type: Integer

Required: No

[NextToken](#)

Token for the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "Assets": [
    {
      "AssetArn": "string",
      "LatestAssetDiscoveryTime": number
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Assets](#)

Assets.

Type: Array of [Asset](#) objects

[NextToken](#)

Token for the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)

- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListAssociationsForLicenseConfiguration

Lists the resource associations for the specified license configuration.

Resource associations need not consume licenses from a license configuration. For example, an AMI or a stopped instance might not consume a license (depending on the license rules).

Request Syntax

```
{  
  "LicenseConfigurationArn": "string",  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[LicenseConfigurationArn](#)

Amazon Resource Name (ARN) of a license configuration.

Type: String

Required: Yes

[MaxResults](#)

Maximum number of results to return in a single call.

Type: Integer

Required: No

[NextToken](#)

Token for the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "LicenseConfigurationAssociations": [
    {
      "AmiAssociationScope": "string",
      "AssociationTime": number,
      "ResourceArn": "string",
      "ResourceOwnerId": "string",
      "ResourceType": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[LicenseConfigurationAssociations](#)

Information about the associations for the license configuration.

Type: Array of [LicenseConfigurationAssociation](#) objects

[NextToken](#)

Token for the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

FilterLimitExceededException

The request uses too many filters or too many filter values.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListDistributedGrants

Lists the grants distributed for the specified license.

Request Syntax

```
{  
  "Filters": [  
    {  
      "Name": "string",  
      "Values": [ "string" ]  
    }  
  ],  
  "GrantArns": [ "string" ],  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Filters to scope the results. The following filters are supported:

- LicenseArn
- GrantStatus
- GranteePrincipalARN
- ProductSKU
- LicenseIssuerName

Type: Array of [Filter](#) objects

Required: No

GrantArns

Amazon Resource Names (ARNs) of the grants.

Type: Array of strings

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: No

MaxResults

Maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

Token for the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "Grants": [
    {
      "GrantArn": "string",
      "GrantedOperations": [ "string" ],
      "GranteePrincipalArn": "string",
      "GrantName": "string",
      "GrantStatus": "string",
      "HomeRegion": "string",
      "LicenseArn": "string",
      "Options": {
        "ActivationOverrideBehavior": "string"
      }
    }
  ],
}
```

```
    "ParentArn": "string",
    "StatusReason": "string",
    "Version": "string"
  },
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Grants

Distributed grant details.

Type: Array of [Grant](#) objects

NextToken

Token for the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)

- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListFailuresForLicenseConfigurationOperations

Lists the license configuration operations that failed.

Request Syntax

```
{  
  "LicenseConfigurationArn": "string",  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[LicenseConfigurationArn](#)

Amazon Resource Name of the license configuration.

Type: String

Required: Yes

[MaxResults](#)

Maximum number of results to return in a single call.

Type: Integer

Required: No

[NextToken](#)

Token for the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "LicenseOperationFailureList": [
    {
      "ErrorMessage": "string",
      "FailureTime": number,
      "MetadataList": [
        {
          "Name": "string",
          "Value": "string"
        }
      ],
      "OperationName": "string",
      "OperationRequestedBy": "string",
      "ResourceArn": "string",
      "ResourceOwnerId": "string",
      "ResourceType": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[LicenseOperationFailureList](#)

License configuration operations that failed.

Type: Array of [LicenseOperationFailure](#) objects

[NextToken](#)

Token for the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)

- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListLicenseAssetGroups

Lists license asset groups.

Request Syntax

```
{
  "Filters": [
    {
      "Name": "string",
      "Values": [ "string" ]
    }
  ],
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Filters to scope the results. Following filters are supported

- LicenseAssetRulesetArn

Type: Array of [Filter](#) objects

Required: No

MaxResults

Maximum number of results to return in a single call.

Type: Integer

Required: No

NextToken

Token for the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "LicenseAssetGroups": [
    {
      "AssociatedLicenseAssetRulesetARNs": [ "string" ],
      "Description": "string",
      "LatestResourceDiscoveryTime": number,
      "LatestUsageAnalysisTime": number,
      "LicenseAssetGroupArn": "string",
      "LicenseAssetGroupConfigurations": [
        {
          "UsageDimension": "string"
        }
      ],
      "Name": "string",
      "Properties": [
        {
          "Key": "string",
          "Value": "string"
        }
      ],
      "Status": "string",
      "StatusMessage": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LicenseAssetGroups

License asset groups.

Type: Array of [LicenseAssetGroup](#) objects

NextToken

Token for the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListLicenseAssetRulesets

Lists license asset rulesets.

Request Syntax

```
{
  "Filters": [
    {
      "Name": "string",
      "Values": [ "string" ]
    }
  ],
  "MaxResults": number,
  "NextToken": "string",
  "ShowAWSManagedLicenseAssetRulesets": boolean
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Filters to scope the results. Following filters are supported

- Name

Type: Array of [Filter](#) objects

Required: No

MaxResults

Maximum number of results to return in a single call.

Type: Integer

Required: No

NextToken

Token for the next set of results.

Type: String

Required: No

[ShowAWSManagedLicenseAssetRulesets](#)

Specifies whether to show License Manager managed license asset rulesets.

Type: Boolean

Required: No

Response Syntax

```
{
  "LicenseAssetRulesets": [
    {
      "Description": "string",
      "LicenseAssetRulesetArn": "string",
      "Name": "string",
      "Rules": [
        {
          "RuleStatement": {
            "InstanceRuleStatement": {
              "AndRuleStatement": {
                "MatchingRuleStatements": [
                  {
                    "Constraint": "string",
                    "KeyToMatch": "string",
                    "ValueToMatch": [ "string" ]
                  }
                ],
                "ScriptRuleStatements": [
                  {
                    "KeyToMatch": "string",
                    "Script": "string"
                  }
                ]
              },
              "MatchingRuleStatement": {
                "Constraint": "string",
                "KeyToMatch": "string",
                "ValueToMatch": [ "string" ]
              }
            }
          }
        }
      ]
    }
  ]
}
```

```
    "OrRuleStatement": {
      "MatchingRuleStatements": [
        {
          "Constraint": "string",
          "KeyToMatch": "string",
          "ValueToMatch": [ "string" ]
        }
      ],
      "ScriptRuleStatements": [
        {
          "KeyToMatch": "string",
          "Script": "string"
        }
      ]
    },
    "ScriptRuleStatement": {
      "KeyToMatch": "string",
      "Script": "string"
    }
  },
  "LicenseConfigurationRuleStatement": {
    "AndRuleStatement": {
      "MatchingRuleStatements": [
        {
          "Constraint": "string",
          "KeyToMatch": "string",
          "ValueToMatch": [ "string" ]
        }
      ],
      "ScriptRuleStatements": [
        {
          "KeyToMatch": "string",
          "Script": "string"
        }
      ]
    },
    "MatchingRuleStatement": {
      "Constraint": "string",
      "KeyToMatch": "string",
      "ValueToMatch": [ "string" ]
    },
    "OrRuleStatement": {
      "MatchingRuleStatements": [
        {
```

```

        "Constraint": "string",
        "KeyToMatch": "string",
        "ValueToMatch": [ "string" ]
    },
],
"ScriptRuleStatements": [
    {
        "KeyToMatch": "string",
        "Script": "string"
    }
]
},
"LicenseRuleStatement": {
    "AndRuleStatement": {
        "MatchingRuleStatements": [
            {
                "Constraint": "string",
                "KeyToMatch": "string",
                "ValueToMatch": [ "string" ]
            }
        ],
        "ScriptRuleStatements": [
            {
                "KeyToMatch": "string",
                "Script": "string"
            }
        ]
    },
    "MatchingRuleStatement": {
        "Constraint": "string",
        "KeyToMatch": "string",
        "ValueToMatch": [ "string" ]
    },
    "OrRuleStatement": {
        "MatchingRuleStatements": [
            {
                "Constraint": "string",
                "KeyToMatch": "string",
                "ValueToMatch": [ "string" ]
            }
        ],
        "ScriptRuleStatements": [
            {

```

```
    "KeyToMatch": "string",  
    "Script": "string"  
  }  
]  
}  
}  
}  
}  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LicenseAssetRulesets

License asset rulesets.

Type: Array of [LicenseAssetRuleset](#) objects

NextToken

Token for the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListLicenseConfigurations

Lists the license configurations for your account.

Request Syntax

```
{
  "Filters": [
    {
      "Name": "string",
      "Values": [ "string" ]
    }
  ],
  "LicenseConfigurationArns": [ "string" ],
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Filters to scope the results. The following filters and logical operators are supported:

- `licenseCountingType` - The dimension for which licenses are counted. Possible values are `vCPU` | `Instance` | `Core` | `Socket`.
- `enforceLicenseCount` - A Boolean value that indicates whether hard license enforcement is used.
- `usageLimitExceeded` - A Boolean value that indicates whether the available licenses have been exceeded.

Type: Array of [Filter](#) objects

Required: No

LicenseConfigurationArns

Amazon Resource Names (ARN) of the license configurations.

Type: Array of strings

Required: No

MaxResults

Maximum number of results to return in a single call.

Type: Integer

Required: No

NextToken

Token for the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "LicenseConfigurations": [
    {
      "AutomatedDiscoveryInformation": {
        "LastRunTime": number
      },
      "ConsumedLicenses": number,
      "ConsumedLicenseSummaryList": [
        {
          "ConsumedLicenses": number,
          "ResourceType": "string"
        }
      ],
      "Description": "string",
      "DisassociateWhenNotFound": boolean,
      "LicenseConfigurationArn": "string",
      "LicenseConfigurationId": "string",
      "LicenseCount": number,
      "LicenseCountHardLimit": boolean,
      "LicenseCountingType": "string",
      "LicenseExpiry": number,
```



```
    "LicenseRules": [ "string" ],
    "ManagedResourceSummaryList": [
      {
        "AssociationCount": number,
        "ResourceType": "string"
      }
    ],
    "Name": "string",
    "OwnerAccountId": "string",
    "ProductInformationList": [
      {
        "ProductInformationFilterList": [
          {
            "ProductInformationFilterComparator": "string",
            "ProductInformationFilterName": "string",
            "ProductInformationFilterValue": [ "string" ]
          }
        ],
        "ResourceType": "string"
      }
    ],
    "Status": "string"
  }
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LicenseConfigurations

Information about the license configurations.

Type: Array of [LicenseConfiguration](#) objects

NextToken

Token for the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

FilterLimitExceededException

The request uses too many filters or too many filter values.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListLicenseConfigurationsForOrganization

Lists license configurations for an organization.

Request Syntax

```
{
  "Filters": [
    {
      "Name": "string",
      "Values": [ "string" ]
    }
  ],
  "LicenseConfigurationArns": [ "string" ],
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Filters to scope the results.

Type: Array of [Filter](#) objects

Required: No

LicenseConfigurationArns

License configuration ARNs.

Type: Array of strings

Required: No

MaxResults

Maximum number of results to return in a single call.

Type: Integer

Required: No

NextToken

Token for the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "LicenseConfigurations": [
    {
      "AutomatedDiscoveryInformation": {
        "LastRunTime": number
      },
      "ConsumedLicenses": number,
      "ConsumedLicenseSummaryList": [
        {
          "ConsumedLicenses": number,
          "ResourceType": "string"
        }
      ],
      "Description": "string",
      "DisassociateWhenNotFound": boolean,
      "LicenseConfigurationArn": "string",
      "LicenseConfigurationId": "string",
      "LicenseCount": number,
      "LicenseCountHardLimit": boolean,
      "LicenseCountingType": "string",
      "LicenseExpiry": number,
      "LicenseRules": [ "string" ],
      "ManagedResourceSummaryList": [
        {
          "AssociationCount": number,
          "ResourceType": "string"
        }
      ],
      "Name": "string",
```

```
    "OwnerAccountId": "string",
    "ProductInformationList": [
      {
        "ProductInformationFilterList": [
          {
            "ProductInformationFilterComparator": "string",
            "ProductInformationFilterName": "string",
            "ProductInformationFilterValue": [ "string" ]
          }
        ],
        "ResourceType": "string"
      }
    ],
    "Status": "string"
  }
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LicenseConfigurations

License configurations.

Type: Array of [LicenseConfiguration](#) objects

NextToken

Token for the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

FilterLimitExceededException

The request uses too many filters or too many filter values.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListLicenseConversionTasks

Lists the license type conversion tasks for your account.

Request Syntax

```
{  
  "Filters": [  
    {  
      "Name": "string",  
      "Values": [ "string" ]  
    }  
  ],  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Filters to scope the results. Valid filters are ResourceArns and Status.

Type: Array of [Filter](#) objects

Required: No

MaxResults

Maximum number of results to return in a single call.

Type: Integer

Required: No

NextToken

Token for the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "LicenseConversionTasks": [
    {
      "DestinationLicenseContext": {
        "ProductCodes": [
          {
            "ProductCodeId": "string",
            "ProductCodeType": "string"
          }
        ],
        "UsageOperation": "string"
      },
      "EndTime": number,
      "LicenseConversionTaskId": "string",
      "LicenseConversionTime": number,
      "ResourceArn": "string",
      "SourceLicenseContext": {
        "ProductCodes": [
          {
            "ProductCodeId": "string",
            "ProductCodeType": "string"
          }
        ],
        "UsageOperation": "string"
      },
      "StartTime": number,
      "Status": "string",
      "StatusMessage": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[LicenseConversionTasks](#)

Information about the license configuration tasks for your account.

Type: Array of [LicenseConversionTask](#) objects

[NextToken](#)

Token for the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListLicenseManagerReportGenerators

Lists the report generators for your account.

Request Syntax

```
{
  "Filters": [
    {
      "Name": "string",
      "Values": [ "string" ]
    }
  ],
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Filters to scope the results. The following filters are supported:

- LicenseConfigurationArn

Type: Array of [Filter](#) objects

Required: No

MaxResults

Maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

Token for the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "ReportGenerators": [
    {
      "CreateTime": "string",
      "Description": "string",
      "LastReportGenerationTime": "string",
      "LastRunFailureReason": "string",
      "LastRunStatus": "string",
      "LicenseManagerReportGeneratorArn": "string",
      "ReportContext": {
        "licenseAssetGroupArns": [ "string" ],
        "licenseConfigurationArns": [ "string" ],
        "reportEndDate": number,
        "reportStartDate": number
      },
      "ReportCreatorAccount": "string",
      "ReportFrequency": {
        "period": "string",
        "value": number
      },
      "ReportGeneratorName": "string",
      "ReportType": [ "string" ],
      "S3Location": {
        "bucket": "string",
        "keyPrefix": "string"
      },
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    }
  ]
}
```

```
}  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

Token for the next set of results.

Type: String

ReportGenerators

A report generator that creates periodic reports about your license configurations.

Type: Array of [ReportGenerator](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)

- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListLicenses

Lists the licenses for your account.

Request Syntax

```
{
  "Filters": [
    {
      "Name": "string",
      "Values": [ "string" ]
    }
  ],
  "LicenseArns": [ "string" ],
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Filters to scope the results. The following filters are supported:

- Beneficiary
- ProductSKU
- Fingerprint
- Status

Type: Array of [Filter](#) objects

Required: No

LicenseArns

Amazon Resource Names (ARNs) of the licenses.

Type: Array of strings

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: No

[MaxResults](#)

Maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[NextToken](#)

Token for the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "Licenses": [
    {
      "Beneficiary": "string",
      "ConsumptionConfiguration": {
        "BorrowConfiguration": {
          "AllowEarlyCheckIn": boolean,
          "MaxTimeToLiveInMinutes": number
        },
        "ProvisionalConfiguration": {
          "MaxTimeToLiveInMinutes": number
        },
        "RenewType": "string"
      },
    },
  ],
}
```

```

    "CreateTime": "string",
    "Entitlements": [
      {
        "AllowCheckIn": boolean,
        "MaxCount": number,
        "Name": "string",
        "Overage": boolean,
        "Unit": "string",
        "Value": "string"
      }
    ],
    "HomeRegion": "string",
    "Issuer": {
      "KeyFingerprint": "string",
      "Name": "string",
      "SignKey": "string"
    },
    "LicenseArn": "string",
    "LicenseMetadata": [
      {
        "Name": "string",
        "Value": "string"
      }
    ],
    "LicenseName": "string",
    "ProductName": "string",
    "ProductSKU": "string",
    "Status": "string",
    "Validity": {
      "Begin": "string",
      "End": "string"
    },
    "Version": "string"
  }
],
  "NextToken": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Licenses

License details.

Type: Array of [License](#) objects

NextToken

Token for the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListLicenseSpecificationsForResource

Describes the license configurations for the specified resource.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string",  
  "ResourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[MaxResults](#)

Maximum number of results to return in a single call.

Type: Integer

Required: No

[NextToken](#)

Token for the next set of results.

Type: String

Required: No

[ResourceArn](#)

Amazon Resource Name (ARN) of a resource that has an associated license configuration.

Type: String

Required: Yes

Response Syntax

```
{
  "LicenseSpecifications": [
    {
      "AmiAssociationScope": "string",
      "LicenseConfigurationArn": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[LicenseSpecifications](#)

License configurations associated with a resource.

Type: Array of [LicenseSpecification](#) objects

[NextToken](#)

Token for the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListLicenseVersions

Lists all versions of the specified license.

Request Syntax

```
{  
  "LicenseArn": "string",  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[LicenseArn](#)

Amazon Resource Name (ARN) of the license.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

[MaxResults](#)

Maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

Token for the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "Licenses": [
    {
      "Beneficiary": "string",
      "ConsumptionConfiguration": {
        "BorrowConfiguration": {
          "AllowEarlyCheckIn": boolean,
          "MaxTimeToLiveInMinutes": number
        },
        "ProvisionalConfiguration": {
          "MaxTimeToLiveInMinutes": number
        },
        "RenewType": "string"
      },
      "CreateTime": "string",
      "Entitlements": [
        {
          "AllowCheckIn": boolean,
          "MaxCount": number,
          "Name": "string",
          "Overage": boolean,
          "Unit": "string",
          "Value": "string"
        }
      ],
      "HomeRegion": "string",
      "Issuer": {
        "KeyFingerprint": "string",
        "Name": "string",
        "SignKey": "string"
      },
      "LicenseArn": "string",
      "LicenseMetadata": [
```

```
{
  {
    "Name": "string",
    "Value": "string"
  },
  "LicenseName": "string",
  "ProductName": "string",
  "ProductSKU": "string",
  "Status": "string",
  "Validity": {
    "Begin": "string",
    "End": "string"
  },
  "Version": "string"
},
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Licenses](#)

License details.

Type: Array of [License](#) objects

[NextToken](#)

Token for the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

ListReceivedGrants

Lists grants that are received. Received grants are grants created while specifying the recipient as this Amazon Web Services account, your organization, or an organizational unit (OU) to which this member account belongs.

Request Syntax

```
{
  "Filters": [
    {
      "Name": "string",
      "Values": [ "string" ]
    }
  ],
  "GrantArns": [ "string" ],
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Filters to scope the results. The following filters are supported:

- ProductSKU
- LicenseIssuerName
- LicenseArn
- GrantStatus
- GranterAccountId

Type: Array of [Filter](#) objects

Required: No

GrantArns

Amazon Resource Names (ARNs) of the grants.

Type: Array of strings

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: No

MaxResults

Maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

Token for the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "Grants": [
    {
      "GrantArn": "string",
      "GrantedOperations": [ "string" ],
      "GranteePrincipalArn": "string",
      "GrantName": "string",
      "GrantStatus": "string",
      "HomeRegion": "string",
      "LicenseArn": "string",
```



```
    "Options": {
      "ActivationOverrideBehavior": "string"
    },
    "ParentArn": "string",
    "StatusReason": "string",
    "Version": "string"
  },
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Grants

Received grant details.

Type: Array of [Grant](#) objects

NextToken

Token for the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListReceivedGrantsForOrganization

Lists the grants received for all accounts in the organization.

Request Syntax

```
{
  "Filters": [
    {
      "Name": "string",
      "Values": [ "string" ]
    }
  ],
  "LicenseArn": "string",
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Filters to scope the results. The following filters are supported:

- ParentArn
- GranteePrincipalArn

Type: Array of [Filter](#) objects

Required: No

LicenseArn

The Amazon Resource Name (ARN) of the received license.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

MaxResults

Maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

Token for the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "Grants": [
    {
      "GrantArn": "string",
      "GrantedOperations": [ "string" ],
      "GranteePrincipalArn": "string",
      "GrantName": "string",
      "GrantStatus": "string",
      "HomeRegion": "string",
      "LicenseArn": "string",
      "Options": {
        "ActivationOverrideBehavior": "string"
      },
      "ParentArn": "string",
      "StatusReason": "string",
      "Version": "string"
    }
  ]
}
```

```
  ],  
  "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Grants](#)

Lists the grants the organization has received.

Type: Array of [Grant](#) objects

[NextToken](#)

Token for the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListReceivedLicenses

Lists received licenses.

Request Syntax

```
{
  "Filters": [
    {
      "Name": "string",
      "Values": [ "string" ]
    }
  ],
  "LicenseArns": [ "string" ],
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Filters to scope the results. The following filters are supported:

- ProductSKU
- Status
- Fingerprint
- IssuerName
- Beneficiary

Type: Array of [Filter](#) objects

Required: No

LicenseArns

Amazon Resource Names (ARNs) of the licenses.

Type: Array of strings

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: No

MaxResults

Maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

Token for the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "Licenses": [
    {
      "Beneficiary": "string",
      "ConsumptionConfiguration": {
        "BorrowConfiguration": {
          "AllowEarlyCheckIn": boolean,
          "MaxTimeToLiveInMinutes": number
        },
        "ProvisionalConfiguration": {
          "MaxTimeToLiveInMinutes": number
        },
        "RenewType": "string"
      },
      "CreateTime": "string",
      "Entitlements": [
```

```
{
  {
    "AllowCheckIn": boolean,
    "MaxCount": number,
    "Name": "string",
    "Overage": boolean,
    "Unit": "string",
    "Value": "string"
  }
],
"HomeRegion": "string",
"Issuer": {
  "KeyFingerprint": "string",
  "Name": "string",
  "SignKey": "string"
},
"LicenseArn": "string",
"LicenseMetadata": [
  {
    "Name": "string",
    "Value": "string"
  }
],
"LicenseName": "string",
"ProductName": "string",
"ProductSKU": "string",
"ReceivedMetadata": {
  "AllowedOperations": [ "string " ],
  "ReceivedStatus": "string",
  "ReceivedStatusReason": "string"
},
"Status": "string",
"Validity": {
  "Begin": "string",
  "End": "string"
},
"Version": "string"
}
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Licenses

Received license details.

Type: Array of [GrantedLicense](#) objects

NextToken

Token for the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListReceivedLicensesForOrganization

Lists the licenses received for all accounts in the organization.

Request Syntax

```
{
  "Filters": [
    {
      "Name": "string",
      "Values": [ "string" ]
    }
  ],
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Filters to scope the results. The following filters are supported:

- Beneficiary
- ProductSKU

Type: Array of [Filter](#) objects

Required: No

MaxResults

Maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

Token for the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "Licenses": [
    {
      "Beneficiary": "string",
      "ConsumptionConfiguration": {
        "BorrowConfiguration": {
          "AllowEarlyCheckIn": boolean,
          "MaxTimeToLiveInMinutes": number
        },
        "ProvisionalConfiguration": {
          "MaxTimeToLiveInMinutes": number
        },
        "RenewType": "string"
      },
      "CreateTime": "string",
      "Entitlements": [
        {
          "AllowCheckIn": boolean,
          "MaxCount": number,
          "Name": "string",
          "Overage": boolean,
          "Unit": "string",
          "Value": "string"
        }
      ],
      "HomeRegion": "string",
      "Issuer": {
        "KeyFingerprint": "string",
        "Name": "string",
        "SignKey": "string"
      },
    },
  ],
}
```

```
"LicenseArn": "string",
"LicenseMetadata": [
  {
    "Name": "string",
    "Value": "string"
  }
],
"LicenseName": "string",
"ProductName": "string",
"ProductSKU": "string",
"ReceivedMetadata": {
  "AllowedOperations": [ "string" ],
  "ReceivedStatus": "string",
  "ReceivedStatusReason": "string"
},
"Status": "string",
"Validity": {
  "Begin": "string",
  "End": "string"
},
"Version": "string"
}
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Licenses

Lists the licenses the organization has received.

Type: Array of [GrantedLicense](#) objects

NextToken

Token for the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListResourceInventory

Lists resources managed using Systems Manager inventory.

Request Syntax

```
{
  "Filters": [
    {
      "Condition": "string",
      "Name": "string",
      "Value": "string"
    }
  ],
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Filters to scope the results. The following filters and logical operators are supported:

- `account_id` - The ID of the Amazon Web Services account that owns the resource. Logical operators are `EQUALS` | `NOT_EQUALS`.
- `application_name` - The name of the application. Logical operators are `EQUALS` | `BEGINS_WITH`.
- `license_included` - The type of license included. Logical operators are `EQUALS` | `NOT_EQUALS`. Possible values are `sql-server-enterprise` | `sql-server-standard` | `sql-server-web` | `windows-server-datacenter`.
- `platform` - The platform of the resource. Logical operators are `EQUALS` | `BEGINS_WITH`.
- `resource_id` - The ID of the resource. Logical operators are `EQUALS` | `NOT_EQUALS`.
- `tag: <key>` - The key/value combination of a tag assigned to the resource. Logical operators are `EQUALS` (single account) or `EQUALS` | `NOT_EQUALS` (cross account).

Type: Array of [InventoryFilter](#) objects

Required: No

[MaxResults](#)

Maximum number of results to return in a single call.

Type: Integer

Required: No

[NextToken](#)

Token for the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "ResourceInventoryList": [
    {
      "AmiId": "string",
      "HostId": "string",
      "InstanceType": "string",
      "MarketplaceProductCodes": [ "string" ],
      "Platform": "string",
      "PlatformVersion": "string",
      "Region": "string",
      "ResourceArn": "string",
      "ResourceId": "string",
      "ResourceOwningAccountId": "string",
      "ResourceType": "string",
      "UsageOperation": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

Token for the next set of results.

Type: String

ResourceInventoryList

Information about the resources.

Type: Array of [ResourceInventory](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

FailedDependencyException

A dependency required to run the API is missing.

HTTP Status Code: 400

FilterLimitExceededException

The request uses too many filters or too many filter values.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListTagsForResource

Lists the tags for the specified resource. For more information about tagging support in License Manager, see the [TagResource](#) operation.

Request Syntax

```
{
  "ResourceArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ResourceArn](#)

Amazon Resource Name (ARN) of the resource.

Type: String

Required: Yes

Response Syntax

```
{
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tags

Information about the tags.

Type: Array of [Tag](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListTokens

Lists your tokens.

Request Syntax

```
{  
  "Filters": [  
    {  
      "Name": "string",  
      "Values": [ "string" ]  
    }  
  ],  
  "MaxResults": number,  
  "NextToken": "string",  
  "TokenIds": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Filters to scope the results. The following filter is supported:

- LicenseArns

Type: Array of [Filter](#) objects

Required: No

MaxResults

Maximum number of results to return in a single call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

Token for the next set of results.

Type: String

Required: No

TokenIds

Token IDs.

Type: Array of strings

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "Tokens": [
    {
      "ExpirationTime": "string",
      "LicenseArn": "string",
      "RoleArns": [ "string" ],
      "Status": "string",
      "TokenId": "string",
      "TokenProperties": [ "string" ],
      "TokenType": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

Token for the next set of results.

Type: String

Tokens

Received token details.

Type: Array of [TokenData](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListUsageForLicenseConfiguration

Lists all license usage records for a license configuration, displaying license consumption details by resource at a selected point in time. Use this action to audit the current license consumption for any license inventory and configuration.

Request Syntax

```
{
  "Filters": [
    {
      "Name": "string",
      "Values": [ "string" ]
    }
  ],
  "LicenseConfigurationArn": "string",
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filters

Filters to scope the results. The following filters and logical operators are supported:

- `resourceArn` - The ARN of the license configuration resource.
- `resourceType` - The resource type (EC2_INSTANCE | EC2_HOST | EC2_AMI | SYSTEMS_MANAGER_MANAGED_INSTANCE).
- `resourceAccount` - The ID of the account that owns the resource.

Type: Array of [Filter](#) objects

Required: No

LicenseConfigurationArn

Amazon Resource Name (ARN) of the license configuration.

Type: String

Required: Yes

MaxResults

Maximum number of results to return in a single call.

Type: Integer

Required: No

NextToken

Token for the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "LicenseConfigurationUsageList": [
    {
      "AssociationTime": number,
      "ConsumedLicenses": number,
      "ResourceArn": "string",
      "ResourceOwnerId": "string",
      "ResourceStatus": "string",
      "ResourceType": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[LicenseConfigurationUsageList](#)

Information about the license configurations.

Type: Array of [LicenseConfigurationUsage](#) objects

[NextToken](#)

Token for the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

FilterLimitExceededException

The request uses too many filters or too many filter values.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

RejectGrant

Rejects the specified grant.

Request Syntax

```
{  
  "GrantArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[GrantArn](#)

Amazon Resource Name (ARN) of the grant.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

Response Syntax

```
{  
  "GrantArn": "string",  
  "Status": "string",  
  "Version": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

GrantArn

Grant ARN.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Status

Grant status.

Type: String

Valid Values: PENDING_WORKFLOW | PENDING_ACCEPT | REJECTED | ACTIVE
| FAILED_WORKFLOW | DELETED | PENDING_DELETE | DISABLED |
WORKFLOW_COMPLETED

Version

Grant version.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

TagResource

Adds the specified tags to the specified resource. The following resources support tagging in License Manager:

- Licenses
- Grants
- License configurations
- Report generators

Request Syntax

```
{
  "ResourceArn": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceArn

Amazon Resource Name (ARN) of the resource. The following examples provide an example ARN for each supported resource in License Manager:

- Licenses - `arn:aws:license-manager::111122223333:license:l-EXAMPLE2da7646d6861033667f20e895`
- Grants - `arn:aws:license-manager::111122223333:grant:g-EXAMPLE7b19f4a0ab73679b0beb52707`

- License configurations - `arn:aws:license-manager:us-east-1:111122223333:license-configuration:lic-EXAMPLE6a788d4c8acd4264ff0ecf2ed2d`
- Report generators - `arn:aws:license-manager:us-east-1:111122223333:report-generator:r-EXAMPLE825b4a4f8fe5a3e0c88824e5fc6`

Type: String

Required: Yes

Tags

One or more tags.

Type: Array of [Tag](#) objects

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UntagResource

Removes the specified tags from the specified resource.

Request Syntax

```
{  
  "ResourceArn": "string",  
  "TagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ResourceArn](#)

Amazon Resource Name (ARN) of the resource.

Type: String

Required: Yes

[TagKeys](#)

Keys identifying the tags to remove.

Type: Array of strings

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)

- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateLicenseAssetGroup

Updates a license asset group.

Request Syntax

```
{
  "AssociatedLicenseAssetRulesetARNs": [ "string" ],
  "ClientToken": "string",
  "Description": "string",
  "LicenseAssetGroupArn": "string",
  "LicenseAssetGroupConfigurations": [
    {
      "UsageDimension": "string"
    }
  ],
  "Name": "string",
  "Properties": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "Status": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AssociatedLicenseAssetRulesetARNs

ARNs of associated license asset rulesets.

Type: Array of strings

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

ClientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request.

Type: String

Required: Yes

Description

License asset group description.

Type: String

Length Constraints: Maximum length of 1024.

Required: No

LicenseAssetGroupArn

Amazon Resource Name (ARN) of the license asset group.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.-]{0,1023}$`

Required: Yes

LicenseAssetGroupConfigurations

License asset group configurations.

Type: Array of [LicenseAssetGroupConfiguration](#) objects

Required: No

Name

License asset group name.

Type: String

Length Constraints: Maximum length of 128.

Required: No

Properties

License asset group properties.

Type: Array of [LicenseAssetGroupProperty](#) objects

Required: No

Status

License asset group status. The possible values are ACTIVE | DISABLED.

Type: String

Valid Values: ACTIVE | DISABLED | DELETED

Required: No

Response Syntax

```
{
  "LicenseAssetGroupArn": "string",
  "Status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LicenseAssetGroupArn

Amazon Resource Name (ARN) of the license asset group.

Type: String

Status

License asset group status.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateLicenseAssetRuleset

Updates a license asset ruleset.

Request Syntax

```
{
  "ClientToken": "string",
  "Description": "string",
  "LicenseAssetRulesetArn": "string",
  "Name": "string",
  "Rules": [
    {
      "RuleStatement": {
        "InstanceRuleStatement": {
          "AndRuleStatement": {
            "MatchingRuleStatements": [
              {
                "Constraint": "string",
                "KeyToMatch": "string",
                "ValueToMatch": [ "string" ]
              }
            ],
            "ScriptRuleStatements": [
              {
                "KeyToMatch": "string",
                "Script": "string"
              }
            ]
          },
          "MatchingRuleStatement": {
            "Constraint": "string",
            "KeyToMatch": "string",
            "ValueToMatch": [ "string" ]
          },
          "OrRuleStatement": {
            "MatchingRuleStatements": [
              {
                "Constraint": "string",
                "KeyToMatch": "string",
                "ValueToMatch": [ "string" ]
              }
            ]
          }
        }
      }
    }
  ]
}
```



```

    "ScriptRuleStatements": [
      {
        "KeyToMatch": "string",
        "Script": "string"
      }
    ],
    "ScriptRuleStatement": {
      "KeyToMatch": "string",
      "Script": "string"
    },
    "LicenseConfigurationRuleStatement": {
      "AndRuleStatement": {
        "MatchingRuleStatements": [
          {
            "Constraint": "string",
            "KeyToMatch": "string",
            "ValueToMatch": [ "string" ]
          }
        ],
        "ScriptRuleStatements": [
          {
            "KeyToMatch": "string",
            "Script": "string"
          }
        ]
      },
      "MatchingRuleStatement": {
        "Constraint": "string",
        "KeyToMatch": "string",
        "ValueToMatch": [ "string" ]
      },
      "OrRuleStatement": {
        "MatchingRuleStatements": [
          {
            "Constraint": "string",
            "KeyToMatch": "string",
            "ValueToMatch": [ "string" ]
          }
        ],
        "ScriptRuleStatements": [
          {
            "KeyToMatch": "string",

```

```

        "Script": "string"
      }
    ]
  },
  "LicenseRuleStatement": {
    "AndRuleStatement": {
      "MatchingRuleStatements": [
        {
          "Constraint": "string",
          "KeyToMatch": "string",
          "ValueToMatch": [ "string" ]
        }
      ],
      "ScriptRuleStatements": [
        {
          "KeyToMatch": "string",
          "Script": "string"
        }
      ]
    },
    "MatchingRuleStatement": {
      "Constraint": "string",
      "KeyToMatch": "string",
      "ValueToMatch": [ "string" ]
    },
    "OrRuleStatement": {
      "MatchingRuleStatements": [
        {
          "Constraint": "string",
          "KeyToMatch": "string",
          "ValueToMatch": [ "string" ]
        }
      ],
      "ScriptRuleStatements": [
        {
          "KeyToMatch": "string",
          "Script": "string"
        }
      ]
    }
  }
}

```

```
]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request.

Type: String

Required: Yes

Description

License asset ruleset description.

Type: String

Length Constraints: Maximum length of 1024.

Required: No

LicenseAssetRulesetArn

Amazon Resource Name (ARN) of the license asset ruleset.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

Name

License asset ruleset name.

Type: String

Length Constraints: Maximum length of 128.

Required: No

Rules

License asset rules.

Type: Array of [LicenseAssetRule](#) objects

Required: Yes

Response Syntax

```
{  
  "LicenseAssetRulesetArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LicenseAssetRulesetArn

Amazon Resource Name (ARN) of the license asset ruleset.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateLicenseConfiguration

Modifies the attributes of an existing license configuration.

Request Syntax

```
{
  "Description": "string",
  "DisassociateWhenNotFound": boolean,
  "LicenseConfigurationArn": "string",
  "LicenseConfigurationStatus": "string",
  "LicenseCount": number,
  "LicenseCountHardLimit": boolean,
  "LicenseExpiry": number,
  "LicenseRules": [ "string" ],
  "Name": "string",
  "ProductInformationList": [
    {
      "ProductInformationFilterList": [
        {
          "ProductInformationFilterComparator": "string",
          "ProductInformationFilterName": "string",
          "ProductInformationFilterValue": [ "string" ]
        }
      ],
      "ResourceType": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Description

New description of the license configuration.

Type: String

Required: No

DisassociateWhenNotFound

When true, disassociates a resource when software is uninstalled.

Type: Boolean

Required: No

LicenseConfigurationArn

Amazon Resource Name (ARN) of the license configuration.

Type: String

Required: Yes

LicenseConfigurationStatus

New status of the license configuration.

Type: String

Valid Values: AVAILABLE | DISABLED

Required: No

LicenseCount

New number of licenses managed by the license configuration.

Type: Long

Required: No

LicenseCountHardLimit

New hard limit of the number of available licenses.

Type: Boolean

Required: No

LicenseExpiry

License configuration expiry time.

Type: Long

Required: No

LicenseRules

New license rule. The only rule that you can add after you create a license configuration is `licenseAffinityToHost`.

Type: Array of strings

Required: No

Name

New name of the license configuration.

Type: String

Required: No

ProductInformationList

New product information.

Type: Array of [ProductInformation](#) objects

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

ConflictException

There was a conflict processing the request. Try your request again.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateLicenseManagerReportGenerator

Updates a report generator.

After you make changes to a report generator, it starts generating new reports within 60 minutes of being updated.

Request Syntax

```
{
  "ClientToken": "string",
  "Description": "string",
  "LicenseManagerReportGeneratorArn": "string",
  "ReportContext": {
    "licenseAssetGroupArns": [ "string" ],
    "licenseConfigurationArns": [ "string" ],
    "reportEndDate": number,
    "reportStartDate": number
  },
  "ReportFrequency": {
    "period": "string",
    "value": number
  },
  "ReportGeneratorName": "string",
  "Type": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ClientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Required: Yes

Description

Description of the report generator.

Type: String

Required: No

LicenseManagerReportGeneratorArn

Amazon Resource Name (ARN) of the report generator to update.

Type: String

Required: Yes

ReportContext

The report context.

Type: [ReportContext](#) object

Required: Yes

ReportFrequency

Frequency by which reports are generated.

Type: [ReportFrequency](#) object

Required: Yes

ReportGeneratorName

Name of the report generator.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

Type

Type of reports to generate. The following report types are supported:

- License configuration report - Reports the number and details of consumed licenses for a license configuration.
- Resource report - Reports the tracked licenses and resource consumption for a license configuration.

Type: Array of strings

Valid Values: LicenseConfigurationSummaryReport | LicenseConfigurationUsageReport | LicenseAssetGroupUsageReport

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateLicenseSpecificationsForResource

Adds or removes the specified license configurations for the specified Amazon resource.

You can update the license specifications of AMIs, instances, and hosts. You cannot update the license specifications for launch templates and Amazon CloudFormation templates, as they send license configurations to the operation that creates the resource.

Request Syntax

```
{
  "AddLicenseSpecifications": [
    {
      "AmiAssociationScope": "string",
      "LicenseConfigurationArn": "string"
    }
  ],
  "RemoveLicenseSpecifications": [
    {
      "AmiAssociationScope": "string",
      "LicenseConfigurationArn": "string"
    }
  ],
  "ResourceArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AddLicenseSpecifications

ARNs of the license configurations to add.

Type: Array of [LicenseSpecification](#) objects

Required: No

RemoveLicenseSpecifications

ARNs of the license configurations to remove.

Type: Array of [LicenseSpecification](#) objects

Required: No

[ResourceArn](#)

Amazon Resource Name (ARN) of the Amazon resource.

Type: String

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

ConflictException

There was a conflict processing the request. Try your request again.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

License Manager cannot allocate a license to a resource because of its state.

For example, you cannot allocate a license to an instance in the process of shutting down.

HTTP Status Code: 400

LicenseUsageException

You do not have enough licenses available to support a new resource launch.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

UpdateServiceSettings

Updates License Manager settings for the current Region.

Request Syntax

```
{
  "EnableCrossAccountsDiscovery": boolean,
  "EnabledDiscoverySourceRegions": [ "string" ],
  "OrganizationConfiguration": {
    "EnableIntegration": boolean
  },
  "S3BucketArn": "string",
  "SnsTopicArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[EnableCrossAccountsDiscovery](#)

Activates cross-account discovery.

Type: Boolean

Required: No

[EnabledDiscoverySourceRegions](#)

Cross region discovery enabled source regions.

Type: Array of strings

Required: No

[OrganizationConfiguration](#)

Enables integration with Amazon Organizations for cross-account discovery.

Type: [OrganizationConfiguration](#) object

Required: No

S3BucketArn

Amazon Resource Name (ARN) of the Amazon S3 bucket where the License Manager information is stored.

Type: String

Required: No

SnsTopicArn

Amazon Resource Name (ARN) of the Amazon SNS topic used for License Manager alerts.

Type: String

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to resource denied.

HTTP Status Code: 400

AuthorizationException

The Amazon user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

ConflictException

There was a conflict processing the request. Try your request again.

HTTP Status Code: 400

InvalidParameterValueException

One or more parameter values are not valid.

HTTP Status Code: 400

RateLimitExceededException

Too many requests have been submitted. Try again after a brief wait.

HTTP Status Code: 400

ServerInternalException

The server experienced an internal error. Try again.

HTTP Status Code: 500

ValidationException

The provided input is not valid. Try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface V2](#)
- [Amazon SDK for .NET V4](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

Data Types

The Amazon License Manager API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AndRuleStatement](#)
- [Asset](#)
- [AutomatedDiscoveryInformation](#)
- [BorrowConfiguration](#)
- [ConsumedLicenseSummary](#)
- [ConsumptionConfiguration](#)
- [CrossAccountDiscoveryServiceStatus](#)
- [CrossRegionDiscoveryStatus](#)
- [DatetimeRange](#)
- [Entitlement](#)
- [EntitlementData](#)
- [EntitlementUsage](#)
- [Filter](#)
- [Grant](#)
- [GrantedLicense](#)
- [InstanceRuleStatement](#)
- [InventoryFilter](#)
- [Issuer](#)
- [IssuerDetails](#)
- [License](#)

- [LicenseAssetGroup](#)
- [LicenseAssetGroupConfiguration](#)
- [LicenseAssetGroupProperty](#)
- [LicenseAssetRule](#)
- [LicenseAssetRuleset](#)
- [LicenseConfiguration](#)
- [LicenseConfigurationAssociation](#)
- [LicenseConfigurationRuleStatement](#)
- [LicenseConfigurationUsage](#)
- [LicenseConversionContext](#)
- [LicenseConversionTask](#)
- [LicenseOperationFailure](#)
- [LicenseRuleStatement](#)
- [LicenseSpecification](#)
- [LicenseUsage](#)
- [ManagedResourceSummary](#)
- [MatchingRuleStatement](#)
- [Metadata](#)
- [Options](#)
- [OrganizationConfiguration](#)
- [OrRuleStatement](#)
- [ProductCodeListItem](#)
- [ProductInformation](#)
- [ProductInformationFilter](#)
- [ProvisionalConfiguration](#)
- [ReceivedMetadata](#)
- [RegionStatus](#)
- [ReportContext](#)
- [ReportFrequency](#)
- [ReportGenerator](#)

- [ResourceInventory](#)
- [RuleStatement](#)
- [S3Location](#)
- [ScriptRuleStatement](#)
- [ServiceStatus](#)
- [Tag](#)
- [TokenData](#)

AndRuleStatement

AND rule statement.

Contents

MatchingRuleStatements

Matching rule statements.

Type: Array of [MatchingRuleStatement](#) objects

Required: No

ScriptRuleStatements

Script rule statements.

Type: Array of [ScriptRuleStatement](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Asset

Asset.

Contents

AssetArn

Amazon Resource Name (ARN) of the asset.

Type: String

Required: No

LatestAssetDiscoveryTime

Latest asset discovery time.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AutomatedDiscoveryInformation

Describes automated discovery.

Contents

LastRunTime

Time that automated discovery last ran.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BorrowConfiguration

Details about a borrow configuration.

Contents

AllowEarlyCheckIn

Indicates whether early check-ins are allowed.

Type: Boolean

Required: Yes

MaxTimeToLiveInMinutes

Maximum time for the borrow configuration, in minutes.

Type: Integer

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ConsumedLicenseSummary

Details about license consumption.

Contents

ConsumedLicenses

Number of licenses consumed by the resource.

Type: Long

Required: No

ResourceType

Resource type of the resource consuming a license.

Type: String

Valid Values: EC2_INSTANCE | EC2_HOST | EC2_AMI | RDS |
SYSTEMS_MANAGER_MANAGED_INSTANCE

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ConsumptionConfiguration

Details about a consumption configuration.

Contents

BorrowConfiguration

Details about a borrow configuration.

Type: [BorrowConfiguration](#) object

Required: No

ProvisionalConfiguration

Details about a provisional configuration.

Type: [ProvisionalConfiguration](#) object

Required: No

RenewType

Renewal frequency.

Type: String

Valid Values: None | Weekly | Monthly

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

CrossAccountDiscoveryServiceStatus

Status information for cross-account discovery service.

Contents

Message

Status message for cross-account discovery service.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

CrossRegionDiscoveryStatus

Status information for cross-region discovery.

Contents

Message

Map of region status messages for cross-region discovery.

Type: String to [RegionStatus](#) object map

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DatetimeRange

Describes a time range, in ISO8601-UTC format.

Contents

Begin

Start of the time range.

Type: String

Length Constraints: Maximum length of 50.

Pattern: `^(-?(?:[1-9][0-9]*)?[0-9]{4})-(1[0-2]|0[1-9])-(3[0-1]|0[1-9]|[1-2][0-9])T(2[0-3]|0[0-9]):([0-5][0-9]):([0-5][0-9])(\.[0-9]+)?(Z|[+-](?:2[0-3]|0[0-9]):[0-5][0-9])+$`

Required: Yes

End

End of the time range.

Type: String

Length Constraints: Maximum length of 50.

Pattern: `^(-?(?:[1-9][0-9]*)?[0-9]{4})-(1[0-2]|0[1-9])-(3[0-1]|0[1-9]|[1-2][0-9])T(2[0-3]|0[0-9]):([0-5][0-9]):([0-5][0-9])(\.[0-9]+)?(Z|[+-](?:2[0-3]|0[0-9]):[0-5][0-9])+$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

Entitlement

Describes a resource entitled for use with a license.

Contents

Name

Entitlement name.

Type: String

Required: Yes

Unit

Entitlement unit.

Type: String

Valid Values: Count | None | Seconds | Microseconds | Milliseconds | Bytes | Kilobytes | Megabytes | Gigabytes | Terabytes | Bits | Kilobits | Megabits | Gigabits | Terabits | Percent | Bytes/Second | Kilobytes/Second | Megabytes/Second | Gigabytes/Second | Terabytes/Second | Bits/Second | Kilobits/Second | Megabits/Second | Gigabits/Second | Terabits/Second | Count/Second

Required: Yes

AllowCheckIn

Indicates whether check-ins are allowed.

Type: Boolean

Required: No

MaxCount

Maximum entitlement count. Use if the unit is not None.

Type: Long

Required: No

Overage

Indicates whether overages are allowed.

Type: Boolean

Required: No

Value

Entitlement resource. Use only if the unit is None.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

EntitlementData

Data associated with an entitlement resource.

Contents

Name

Entitlement data name.

Type: String

Required: Yes

Unit

Entitlement data unit.

Type: String

Valid Values: Count | None | Seconds | Microseconds | Milliseconds | Bytes | Kilobytes | Megabytes | Gigabytes | Terabytes | Bits | Kilobits | Megabits | Gigabits | Terabits | Percent | Bytes/Second | Kilobytes/Second | Megabytes/Second | Gigabytes/Second | Terabytes/Second | Bits/Second | Kilobits/Second | Megabits/Second | Gigabits/Second | Terabits/Second | Count/Second

Required: Yes

Value

Entitlement data value.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

EntitlementUsage

Usage associated with an entitlement resource.

Contents

ConsumedValue

Resource usage consumed.

Type: String

Required: Yes

Name

Entitlement usage name.

Type: String

Required: Yes

Unit

Entitlement usage unit.

Type: String

Valid Values: Count | None | Seconds | Microseconds | Milliseconds | Bytes | Kilobytes | Megabytes | Gigabytes | Terabytes | Bits | Kilobits | Megabits | Gigabits | Terabits | Percent | Bytes/Second | Kilobytes/Second | Megabytes/Second | Gigabytes/Second | Terabytes/Second | Bits/Second | Kilobits/Second | Megabits/Second | Gigabits/Second | Terabits/Second | Count/Second

Required: Yes

MaxCount

Maximum entitlement usage count.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Filter

A filter name and value pair that is used to return more specific results from a describe operation. Filters can be used to match a set of resources by specific criteria, such as tags, attributes, or IDs.

Contents

Name

Name of the filter. Filter names are case-sensitive.

Type: String

Required: No

Values

The value of the filter, which is case-sensitive. You can only specify one value for the filter.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Grant

Describes a grant.

Contents

GrantArn

Amazon Resource Name (ARN) of the grant.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.-]{0,1023}$`

Required: Yes

GrantedOperations

Granted operations.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 8 items.

Valid Values: `CreateGrant` | `CheckoutLicense` | `CheckoutBorrowLicense` | `CheckInLicense` | `ExtendConsumptionLicense` | `ListPurchasedLicenses` | `CreateToken`

Required: Yes

GranteePrincipalArn

The grantee principal ARN.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.-]{0,1023}$`

Required: Yes

GrantName

Grant name.

Type: String

Required: Yes

GrantStatus

Grant status.

Type: String

Valid Values: PENDING_WORKFLOW | PENDING_ACCEPT | REJECTED | ACTIVE
| FAILED_WORKFLOW | DELETED | PENDING_DELETE | DISABLED |
WORKFLOW_COMPLETED

Required: Yes

HomeRegion

Home Region of the grant.

Type: String

Required: Yes

LicenseArn

License ARN.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.-]{0,1023}$`

Required: Yes

ParentArn

Parent ARN.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.-]{0,1023}$`

Required: Yes

Version

Grant version.

Type: String

Required: Yes

Options

The options specified for the grant.

Type: [Options](#) object

Required: No

StatusReason

Grant status reason.

Type: String

Length Constraints: Maximum length of 400.

Pattern: `[\s\S]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

GrantedLicense

Describes a license that is granted to a grantee.

Contents

Beneficiary

Granted license beneficiary.

Type: String

Required: No

ConsumptionConfiguration

Configuration for consumption of the license.

Type: [ConsumptionConfiguration](#) object

Required: No

CreateTime

Creation time of the granted license.

Type: String

Length Constraints: Maximum length of 50.

Pattern: `^(-(?:[1-9][0-9]*)?[0-9]{4})-(1[0-2]|0[1-9])-(3[0-1]|0[1-9]|[1-2][0-9])T(2[0-3]|0[0-9]):([0-5][0-9]):([0-5][0-9])(\.[0-9]+)?(Z|[+-](?:2[0-3]|0[0-9]):[0-5][0-9])+$`

Required: No

Entitlements

License entitlements.

Type: Array of [Entitlement](#) objects

Required: No

HomeRegion

Home Region of the granted license.

Type: String

Required: No

Issuer

Granted license issuer.

Type: [IssuerDetails](#) object

Required: No

LicenseArn

Amazon Resource Name (ARN) of the license.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: No

LicenseMetadata

Granted license metadata.

Type: Array of [Metadata](#) objects

Required: No

LicenseName

License name.

Type: String

Required: No

ProductName

Product name.

Type: String

Required: No

ProductSKU

Product SKU.

Type: String

Required: No

ReceivedMetadata

Granted license received metadata.

Type: [ReceivedMetadata](#) object

Required: No

Status

Granted license status.

Type: String

Valid Values: AVAILABLE | PENDING_AVAILABLE | DEACTIVATED | SUSPENDED | EXPIRED | PENDING_DELETE | DELETED

Required: No

Validity

Date and time range during which the granted license is valid, in ISO8601-UTC format.

Type: [DatetimeRange](#) object

Required: No

Version

Version of the granted license.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

InstanceRuleStatement

Instance rule statement.

Contents

AndRuleStatement

AND rule statement.

Type: [AndRuleStatement](#) object

Required: No

MatchingRuleStatement

Matching rule statement.

Type: [MatchingRuleStatement](#) object

Required: No

OrRuleStatement

OR rule statement.

Type: [OrRuleStatement](#) object

Required: No

ScriptRuleStatement

Script rule statement.

Type: [ScriptRuleStatement](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

InventoryFilter

An inventory filter.

Contents

Condition

Condition of the filter.

Type: String

Valid Values: EQUALS | NOT_EQUALS | BEGINS_WITH | CONTAINS

Required: Yes

Name

Name of the filter.

Type: String

Required: Yes

Value

Value of the filter.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Issuer

Details about the issuer of a license.

Contents

Name

Issuer name.

Type: String

Required: Yes

SignKey

Asymmetric KMS key from Amazon Key Management Service. The KMS key must have a key usage of sign and verify, and support the RSASSA-PSS SHA-256 signing algorithm.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

IssuerDetails

Details associated with the issuer of a license.

Contents

KeyFingerprint

Issuer key fingerprint.

Type: String

Required: No

Name

Issuer name.

Type: String

Required: No

SignKey

Asymmetric KMS key from Amazon Key Management Service. The KMS key must have a key usage of sign and verify, and support the RSASSA-PSS SHA-256 signing algorithm.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

License

Software license that is managed in Amazon License Manager.

Contents

Beneficiary

License beneficiary.

Type: String

Required: No

ConsumptionConfiguration

Configuration for consumption of the license.

Type: [ConsumptionConfiguration](#) object

Required: No

CreateTime

License creation time.

Type: String

Length Constraints: Maximum length of 50.

Pattern: `^(-(?:[1-9][0-9]*)?[0-9]{4})-(1[0-2]|0[1-9])-(3[0-1]|0[1-9]|[1-2][0-9])T(2[0-3]|0[0-1][0-9]):([0-5][0-9]):([0-5][0-9])(\.[0-9]+)?(Z|[+-](?:2[0-3]|0[0-1][0-9]):[0-5][0-9])+$`

Required: No

Entitlements

License entitlements.

Type: Array of [Entitlement](#) objects

Required: No

HomeRegion

Home Region of the license.

Type: String

Required: No

Issuer

License issuer.

Type: [IssuerDetails](#) object

Required: No

LicenseArn

Amazon Resource Name (ARN) of the license.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: No

LicenseMetadata

License metadata.

Type: Array of [Metadata](#) objects

Required: No

LicenseName

License name.

Type: String

Required: No

ProductName

Product name.

Type: String

Required: No

ProductSKU

Product SKU.

Type: String

Required: No

Status

License status.

Type: String

Valid Values: AVAILABLE | PENDING_AVAILABLE | DEACTIVATED | SUSPENDED | EXPIRED | PENDING_DELETE | DELETED

Required: No

Validity

Date and time range during which the license is valid, in ISO8601-UTC format.

Type: [DatetimeRange](#) object

Required: No

Version

License version.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

LicenseAssetGroup

License asset group.

Contents

AssociatedLicenseAssetRulesetARNs

ARNs of associated license asset rulesets.

Type: Array of strings

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

LicenseAssetGroupArn

Amazon Resource Name (ARN) of the license asset group.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

Name

License asset group name.

Type: String

Required: Yes

Status

License asset group status.

Type: String

Valid Values: ACTIVE | DISABLED | DELETED

Required: Yes

Description

License asset group description.

Type: String

Required: No

LatestResourceDiscoveryTime

Latest resource discovery time.

Type: Timestamp

Required: No

LatestUsageAnalysisTime

Latest usage analysis time.

Type: Timestamp

Required: No

LicenseAssetGroupConfigurations

License asset group configurations.

Type: Array of [LicenseAssetGroupConfiguration](#) objects

Required: No

Properties

License asset group properties.

Type: Array of [LicenseAssetGroupProperty](#) objects

Required: No

StatusMessage

License asset group status message.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

LicenseAssetGroupConfiguration

License asset group configuration.

Contents

UsageDimension

License Asset Group Configuration Usage dimension.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

LicenseAssetGroupProperty

License asset group property.

Contents

Key

Property key.

Type: String

Required: Yes

Value

Property value.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

LicenseAssetRule

License asset rule.

Contents

RuleStatement

Rule statement.

Type: [RuleStatement](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

LicenseAssetRuleset

License asset ruleset.

Contents

LicenseAssetRulesetArn

Amazon Resource Name (ARN) of the license asset ruleset.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: Yes

Name

License asset ruleset name.

Type: String

Required: Yes

Rules

License asset rules.

Type: Array of [LicenseAssetRule](#) objects

Required: Yes

Description

License asset ruleset description.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

LicenseConfiguration

A license configuration is an abstraction of a customer license agreement that can be consumed and enforced by License Manager. Components include specifications for the license type (licensing by instance, socket, CPU, or vCPU), allowed tenancy (shared tenancy, Dedicated Instance, Dedicated Host, or all of these), host affinity (how long a VM must be associated with a host), and the number of licenses purchased and used.

Contents

AutomatedDiscoveryInformation

Automated discovery information.

Type: [AutomatedDiscoveryInformation](#) object

Required: No

ConsumedLicenses

Number of licenses consumed.

Type: Long

Required: No

ConsumedLicenseSummaryList

Summaries for licenses consumed by various resources.

Type: Array of [ConsumedLicenseSummary](#) objects

Required: No

Description

Description of the license configuration.

Type: String

Required: No

DisassociateWhenNotFound

When true, disassociates a resource when software is uninstalled.

Type: Boolean

Required: No

LicenseConfigurationArn

Amazon Resource Name (ARN) of the license configuration.

Type: String

Required: No

LicenseConfigurationId

Unique ID of the license configuration.

Type: String

Required: No

LicenseCount

Number of licenses managed by the license configuration.

Type: Long

Required: No

LicenseCountHardLimit

Number of available licenses as a hard limit.

Type: Boolean

Required: No

LicenseCountingType

Dimension to use to track the license inventory.

Type: String

Valid Values: vCPU | Instance | Core | Socket

Required: No

LicenseExpiry

License configuration expiry time in Unix timestamp format.

Type: Long

Required: No

LicenseRules

License rules.

Type: Array of strings

Required: No

ManagedResourceSummaryList

Summaries for managed resources.

Type: Array of [ManagedResourceSummary](#) objects

Required: No

Name

Name of the license configuration.

Type: String

Required: No

OwnerAccountId

Account ID of the license configuration's owner.

Type: String

Required: No

ProductInformationList

Product information.

Type: Array of [ProductInformation](#) objects

Required: No

Status

Status of the license configuration.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

LicenseConfigurationAssociation

Describes an association with a license configuration.

Contents

AmiAssociationScope

Scope of AMI associations. The possible value is `cross-account`.

Type: String

Required: No

AssociationTime

Time when the license configuration was associated with the resource.

Type: Timestamp

Required: No

ResourceArn

Amazon Resource Name (ARN) of the resource.

Type: String

Required: No

ResourceOwnerId

ID of the Amazon Web Services account that owns the resource consuming licenses.

Type: String

Required: No

ResourceType

Type of server resource.

Type: String

Valid Values: `EC2_INSTANCE` | `EC2_HOST` | `EC2_AMI` | `RDS` | `SYSTEMS_MANAGER_MANAGED_INSTANCE`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

LicenseConfigurationRuleStatement

License configuration rule statement.

Contents

AndRuleStatement

AND rule statement.

Type: [AndRuleStatement](#) object

Required: No

MatchingRuleStatement

Matching rule statement.

Type: [MatchingRuleStatement](#) object

Required: No

OrRuleStatement

OR rule statement.

Type: [OrRuleStatement](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

LicenseConfigurationUsage

Details about the usage of a resource associated with a license configuration.

Contents

AssociationTime

Time when the license configuration was initially associated with the resource.

Type: Timestamp

Required: No

ConsumedLicenses

Number of licenses consumed by the resource.

Type: Long

Required: No

ResourceArn

Amazon Resource Name (ARN) of the resource.

Type: String

Required: No

ResourceOwnerId

ID of the account that owns the resource.

Type: String

Required: No

ResourceStatus

Status of the resource.

Type: String

Required: No

ResourceType

Type of resource.

Type: String

Valid Values: EC2_INSTANCE | EC2_HOST | EC2_AMI | RDS |
SYSTEMS_MANAGER_MANAGED_INSTANCE

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

LicenseConversionContext

Information about a license type conversion task.

Contents

ProductCodes

Product codes referred to in the license conversion process.

Type: Array of [ProductCodeListItem](#) objects

Required: No

UsageOperation

The Usage operation value that corresponds to the license type you are converting your resource from. For more information about which platforms correspond to which usage operation values see [Sample data: usage operation by platform](#)

Type: String

Length Constraints: Maximum length of 50.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

LicenseConversionTask

Information about a license type conversion task.

Contents

DestinationLicenseContext

Information about the license type this conversion task converted to.

Type: [LicenseConversionContext](#) object

Required: No

EndTime

The time the conversion task was completed.

Type: Timestamp

Required: No

LicenseConversionTaskId

The ID of the license type conversion task.

Type: String

Length Constraints: Maximum length of 50.

Pattern: `^lct-[a-zA-Z0-9]*`

Required: No

LicenseConversionTime

The time the usage operation value of the resource was changed.

Type: Timestamp

Required: No

ResourceArn

The Amazon Resource Name (ARN) of the resource associated with the license type conversion task.

Type: String

Required: No

SourceLicenseContext

Information about the license type this conversion task converted from.

Type: [LicenseConversionContext](#) object

Required: No

StartTime

The time the conversion task was started at.

Type: Timestamp

Required: No

Status

The status of the conversion task.

Type: String

Valid Values: IN_PROGRESS | SUCCEEDED | FAILED

Required: No

StatusMessage

The status message for the conversion task.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

LicenseOperationFailure

Describes the failure of a license operation.

Contents

ErrorMessage

Error message.

Type: String

Required: No

FailureTime

Failure time.

Type: Timestamp

Required: No

MetadataList

Reserved.

Type: Array of [Metadata](#) objects

Required: No

OperationName

Name of the operation.

Type: String

Required: No

OperationRequestedBy

The requester is "License Manager Automated Discovery".

Type: String

Required: No

ResourceArn

Amazon Resource Name (ARN) of the resource.

Type: String

Required: No

ResourceOwnerId

ID of the Amazon Web Services account that owns the resource.

Type: String

Required: No

ResourceType

Resource type.

Type: String

Valid Values: EC2_INSTANCE | EC2_HOST | EC2_AMI | RDS |
SYSTEMS_MANAGER_MANAGED_INSTANCE

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

LicenseRuleStatement

License rule statement.

Contents

AndRuleStatement

AND rule statement.

Type: [AndRuleStatement](#) object

Required: No

MatchingRuleStatement

Matching rule statement.

Type: [MatchingRuleStatement](#) object

Required: No

OrRuleStatement

OR rule statement.

Type: [OrRuleStatement](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

LicenseSpecification

Details for associating a license configuration with a resource.

Contents

LicenseConfigurationArn

Amazon Resource Name (ARN) of the license configuration.

Type: String

Required: Yes

AmiAssociationScope

Scope of AMI associations. The possible value is cross-account.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

LicenseUsage

Describes the entitlement usage associated with a license.

Contents

EntitlementUsages

License entitlement usages.

Type: Array of [EntitlementUsage](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ManagedResourceSummary

Summary information about a managed resource.

Contents

AssociationCount

Number of resources associated with licenses.

Type: Long

Required: No

ResourceType

Type of resource associated with a license.

Type: String

Valid Values: EC2_INSTANCE | EC2_HOST | EC2_AMI | RDS |
SYSTEMS_MANAGER_MANAGED_INSTANCE

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

MatchingRuleStatement

Matching rule statement.

Contents

Constraint

Constraint.

Type: String

Required: Yes

KeyToMatch

Key to match.

The following keys and are supported when the RuleStatement type is Instance:

- Platform - The name of the platform. Logical operators are EQUALS and NOT_EQUALS.
- EC2BillingProduct - The billing product code. Logical operators are EQUALS and NOT_EQUALS. Possible values are: windows-server-enterprise | windows-byol | rhel | rhel-byol | rhel-high-availability | ubuntu-pro | suse-linux | sql-server-standard | sql-server-enterprise.
- MarketplaceProductCode - The Marketplace product code. Logical operators are EQUALS and NOT_EQUALS.
- AMIID - The ID of the AMI. Logical operators are EQUALS and NOT_EQUALS.
- InstanceType - The instance type. Logical operators are EQUALS and NOT_EQUALS.
- InstanceId - The ID of the instance. Logical operators are EQUALS and NOT_EQUALS.
- HostId - The ID of the host. Logical operators are EQUALS and NOT_EQUALS.
- AccountId - The ID of the account. Logical operators are EQUALS and NOT_EQUALS.

The following keys and are supported when the RuleStatement type is License:

- LicenseArn - The ARN of a Managed Entitlement License. Logical operators are EQUALS and NOT_EQUALS.
- ProductSKU - The productSKU of the license. Logical operators are EQUALS and NOT_EQUALS.

- **Issuer** - The issuer of the license. Logical operators are EQUALS and NOT_EQUALS.
- **Beneficiary** - The beneficiary of the license. Logical operators are EQUALS and NOT_EQUALS.
- **LicenseStatus** - The status of the license. Logical operators are EQUALS and NOT_EQUALS.
- **HomeRegion** - The home region of the license. Logical operators are EQUALS and NOT_EQUALS.

The following keys and are supported when the RuleStatement type is License Configuration:

- **LicenseConfigurationArn** - The ARN of a self-managed license configuration. Logical operators are EQUALS and NOT_EQUALS.
- **AccountId** - The account of the license configuration. Logical operators are EQUALS and NOT_EQUALS.

Type: String

Required: Yes

ValueToMatch

Value to match.

Type: Array of strings

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Metadata

Describes key/value pairs.

Contents

Name

The key name.

Type: String

Required: No

Value

The value.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Options

The options you can specify when you create a new version of a grant, such as activation override behavior. For more information, see [Granted licenses in License Manager](#) in the *Amazon License Manager User Guide*.

Contents

ActivationOverrideBehavior

An activation option for your grant that determines the behavior of activating a grant. Activation options can only be used with granted licenses sourced from the Amazon Web Services Marketplace. Additionally, the operation must specify the value of ACTIVE for the Status parameter.

- As a license administrator, you can optionally specify an `ActivationOverrideBehavior` when activating a grant.
- As a grantor, you can optionally specify an `ActivationOverrideBehavior` when you activate a grant for a grantee account in your organization.
- As a grantee, if the grantor creating the distributed grant doesn't specify an `ActivationOverrideBehavior`, you can optionally specify one when you are activating the grant.

DISTRIBUTED_GRANTS_ONLY

Use this value to activate a grant without replacing any member account's active grants for the same product.

ALL_GRANTS_PERMITTED_BY_ISSUER

Use this value to activate a grant and disable other active grants in any member accounts for the same product. This action will also replace their previously activated grants with this activated grant.

Type: String

Valid Values: DISTRIBUTED_GRANTS_ONLY | ALL_GRANTS_PERMITTED_BY_ISSUER

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

OrganizationConfiguration

Configuration information for Amazon Organizations.

Contents

EnableIntegration

Enables Amazon Organizations integration.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

OrRuleStatement

OR rule statement.

Contents

MatchingRuleStatements

Matching rule statements.

Type: Array of [MatchingRuleStatement](#) objects

Required: No

ScriptRuleStatements

Script rule statements.

Type: Array of [ScriptRuleStatement](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ProductCodeListItem

A list item that contains a product code.

Contents

ProductCodeId

The product code ID

Type: String

Pattern: `^[A-Za-z0-9]{1,25}$`

Required: Yes

ProductCodeType

The product code type

Type: String

Valid Values: `marketplace`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ProductInformation

Describes product information for a license configuration.

Contents

ProductInformationFilterList

A Product information filter consists of a `ProductInformationFilterComparator` which is a logical operator, a `ProductInformationFilterName` which specifies the type of filter being declared, and a `ProductInformationFilterValue` that specifies the value to filter on.

Accepted values for `ProductInformationFilterName` are listed here along with descriptions and valid options for `ProductInformationFilterComparator`.

The following filters and are supported when the resource type is `SSM_MANAGED`:

- `Application Name` - The name of the application. Logical operator is `EQUALS`.
- `Application Publisher` - The publisher of the application. Logical operator is `EQUALS`.
- `Application Version` - The version of the application. Logical operator is `EQUALS`.
- `Platform Name` - The name of the platform. Logical operator is `EQUALS`.
- `Platform Type` - The platform type. Logical operator is `EQUALS`.
- `Tag:key` - The key of a tag attached to an Amazon resource you wish to exclude from automated discovery. Logical operator is `NOT_EQUALS`. The key for your tag must be appended to `Tag:` following the example: `Tag:name-of-your-key`. `ProductInformationFilterValue` is optional if you are not using values for the key.
- `AccountId` - The 12-digit ID of an Amazon Web Services account you wish to exclude from automated discovery. Logical operator is `NOT_EQUALS`.
- `License Included` - The type of license included. Logical operators are `EQUALS` and `NOT_EQUALS`. Possible values are: `sql-server-enterprise` | `sql-server-standard` | `sql-server-web` | `windows-server-datacenter`.

The following filters and logical operators are supported when the resource type is `RDS`:

- `Engine Edition` - The edition of the database engine. Logical operator is `EQUALS`. Possible values are: `oracle-ee` | `oracle-se` | `oracle-se1` | `oracle-se2` | `db2-se` | `db2-ae`.
- `License Pack` - The license pack. Logical operator is `EQUALS`. Possible values are: `data guard` | `diagnostic pack` | `sqlt` | `tuning pack` | `sqlt` | `ols` | `olap`.

Type: Array of [ProductInformationFilter](#) objects

Required: Yes

ResourceType

Resource type. The possible values are SSM_MANAGED | RDS.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ProductInformationFilter

Describes product information filters.

Contents

ProductInformationFilterComparator

Logical operator.

Type: String

Required: Yes

ProductInformationFilterName

Filter name.

Type: String

Required: Yes

ProductInformationFilterValue

Filter value.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ProvisionalConfiguration

Details about a provisional configuration.

Contents

MaxTimeToLiveInMinutes

Maximum time for the provisional configuration, in minutes.

Type: Integer

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ReceivedMetadata

Metadata associated with received licenses and grants.

Contents

AllowedOperations

Allowed operations.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 8 items.

Valid Values: CreateGrant | CheckoutLicense | CheckoutBorrowLicense |
CheckInLicense | ExtendConsumptionLicense | ListPurchasedLicenses |
CreateToken

Required: No

ReceivedStatus

Received status.

Type: String

Valid Values: PENDING_WORKFLOW | PENDING_ACCEPT | REJECTED | ACTIVE |
FAILED_WORKFLOW | DELETED | DISABLED | WORKFLOW_COMPLETED

Required: No

ReceivedStatusReason

Received status reason.

Type: String

Length Constraints: Maximum length of 400.

Pattern: `[\s\S]+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RegionStatus

Status information for a specific region.

Contents

Status

Status value for the region.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ReportContext

Details of the license configuration that this generator reports on.

Contents

licenseAssetGroupArns

Amazon Resource Names (ARNs) of the license asset groups to include in the report.

Type: Array of strings

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: No

licenseConfigurationArns

Amazon Resource Name (ARN) of the license configuration that this generator reports on.

Type: Array of strings

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: No

reportEndDate

End date for the report data collection period.

Type: Timestamp

Required: No

reportStartDate

Start date for the report data collection period.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ReportFrequency

Details about how frequently reports are generated.

Contents

period

Time period between each report. The period can be daily, weekly, or monthly.

Type: String

Valid Values: DAY | WEEK | MONTH | ONE_TIME

Required: No

value

Number of times within the frequency period that a report is generated. The only supported value is 1.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ReportGenerator

Describe the details of a report generator.

Contents

CreateTime

Time the report was created.

Type: String

Required: No

Description

Description of the report generator.

Type: String

Required: No

LastReportGenerationTime

Time the last report was generated at.

Type: String

Required: No

LastRunFailureReason

Failure message for the last report generation attempt.

Type: String

Required: No

LastRunStatus

Status of the last report generation attempt.

Type: String

Required: No

LicenseManagerReportGeneratorArn

Amazon Resource Name (ARN) of the report generator.

Type: String

Required: No

ReportContext

License configuration type for this generator.

Type: [ReportContext](#) object

Required: No

ReportCreatorAccount

The Amazon Web Services account ID used to create the report generator.

Type: String

Required: No

ReportFrequency

Details about how frequently reports are generated.

Type: [ReportFrequency](#) object

Required: No

ReportGeneratorName

Name of the report generator.

Type: String

Required: No

ReportType

Type of reports that are generated.

Type: Array of strings

Valid Values: LicenseConfigurationSummaryReport |
LicenseConfigurationUsageReport | LicenseAssetGroupUsageReport

Required: No

S3Location

Details of the S3 bucket that report generator reports are published to.

Type: [S3Location](#) object

Required: No

Tags

Tags associated with the report generator.

Type: Array of [Tag](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ResourceInventory

Details about a resource.

Contents

Amild

Amazon Machine Image (AMI) ID associated with the resource.

Type: String

Required: No

HostId

Dedicated Host ID where the resource is running.

Type: String

Required: No

InstanceType

EC2 instance type of the resource.

Type: String

Required: No

MarketplaceProductCodes

List of Marketplace product codes associated with the resource.

Type: Array of strings

Required: No

Platform

Platform of the resource.

Type: String

Required: No

PlatformVersion

Platform version of the resource in the inventory.

Type: String

Required: No

Region

Region where the resource is located.

Type: String

Required: No

ResourceArn

Amazon Resource Name (ARN) of the resource.

Type: String

Required: No

ResourceId

ID of the resource.

Type: String

Required: No

ResourceOwningAccountId

ID of the account that owns the resource.

Type: String

Required: No

ResourceType

Type of resource.

Type: String

Valid Values: EC2_INSTANCE | EC2_HOST | EC2_AMI | RDS |
SYSTEMS_MANAGER_MANAGED_INSTANCE

Required: No

UsageOperation

Usage operation value that corresponds to the license type for billing purposes.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleStatement

Rule statement.

Contents

InstanceRuleStatement

Instance rule statement.

Type: [InstanceRuleStatement](#) object

Required: No

LicenseConfigurationRuleStatement

License configuration rule statement.

Type: [LicenseConfigurationRuleStatement](#) object

Required: No

LicenseRuleStatement

License rule statement.

Type: [LicenseRuleStatement](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

S3Location

Details of the S3 bucket that report generator reports are published to.

Contents

bucket

Name of the S3 bucket reports are published to.

Type: String

Required: No

keyPrefix

Prefix of the S3 bucket reports are published to.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ScriptRuleStatement

Rule statement that uses a script to evaluate license asset conditions.

Contents

KeyToMatch

Key name to match against in the script rule evaluation.

Type: String

Required: Yes

Script

Script code used to evaluate the rule condition.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ServiceStatus

Overall service status information for License Manager.

Contents

CrossAccountDiscovery

Status of cross-account discovery service.

Type: [CrossAccountDiscoveryServiceStatus](#) object

Required: No

CrossRegionDiscovery

Status of cross-region discovery service.

Type: [CrossRegionDiscoveryStatus](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Tag

Details about the tags for a resource. For more information about tagging support in License Manager, see the [TagResource](#) operation.

Contents

Key

The tag key.

Type: String

Required: No

Value

The tag value.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

TokenData

Describes a token.

Contents

ExpirationTime

Token expiration time, in ISO8601-UTC format.

Type: String

Length Constraints: Maximum length of 50.

Pattern: `^(-?(?:[1-9][0-9]*)?[0-9]{4})-(1[0-2]|0[1-9])-(3[0-1]|0[1-9]|[1-2][0-9])T(2[0-3]|0[0-9]):([0-5][0-9]):([0-5][0-9])(\.[0-9]+)?(Z|[+-](?:2[0-3]|0[0-9]):[0-5][0-9])+$`

Required: No

LicenseArn

Amazon Resource Name (ARN) of the license.

Type: String

Required: No

RoleArns

Amazon Resource Names (ARN) of the roles included in the token.

Type: Array of strings

Length Constraints: Maximum length of 2048.

Pattern: `^arn:aws[a-zA-Z-]*:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.-]{0,1023}$`

Required: No

Status

Token status. The possible values are AVAILABLE and DELETED.

Type: String

Required: No

TokenId

Token ID.

Type: String

Required: No

TokenProperties

Data specified by the caller.

Type: Array of strings

Array Members: Maximum number of 3 items.

Required: No

TokenType

Type of token generated. The supported value is REFRESH_TOKEN.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing Amazon API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed Amazon API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an Amazon API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to Amazon Security Token Service (Amazon STS). For a list of services that support temporary security credentials from Amazon STS, see [Amazon Web Services services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from Amazon STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed Amazon API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all Amazon services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to Amazon standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or Amazon access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The Amazon access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an Amazon service.

HTTP Status Code: 400