
Resource Groups Tagging API

API Reference

亚马逊云科技



Resource Groups Tagging API: API Reference

Table of Contents

Amazon Resource Groups Tagging API Reference	1
Supported services	2
Actions	6
DescribeReportCreation	7
Response Syntax	7
Response Elements	7
Errors	7
Examples	8
See Also	9
GetComplianceSummary	10
Request Syntax	10
Request Parameters	10
Response Syntax	12
Response Elements	12
Errors	13
Examples	14
See Also	15
GetResources	16
Request Syntax	16
Request Parameters	16
Response Syntax	19
Response Elements	20
Errors	20
Examples	21
See Also	21
GetTagKeys	23
Request Syntax	23
Request Parameters	23
Response Syntax	23
Response Elements	23
Errors	24
Examples	24
See Also	25
GetTagValues	26
Request Syntax	26
Request Parameters	26
Response Syntax	26
Response Elements	27
Errors	27
Examples	28
See Also	28
StartReportCreation	30
Request Syntax	30
Request Parameters	30
Response Elements	30
Errors	30
Examples	31
See Also	33
TagResources	34
Request Syntax	34
Request Parameters	34
Response Syntax	35
Response Elements	35
Errors	36

Examples	36
See Also	37
UntagResources	38
Request Syntax	38
Request Parameters	38
Response Syntax	39
Response Elements	39
Errors	39
Examples	40
See Also	41
Data Types	42
ComplianceDetails	43
Contents	43
See Also	43
FailureInfo	44
Contents	44
See Also	44
ResourceTagMapping	46
Contents	46
See Also	46
Summary	47
Contents	47
See Also	48
Tag	49
Contents	49
See Also	49
TagFilter	50
Contents	50
See Also	50
Common Parameters	51
Common Errors	53
Making API requests	55
Amazon Resource Groups Tagging API endpoints	55
Query parameters	55
Request identifiers	55
Query API authentication	55
Available libraries	55
Making API requests using the POST method	56

Amazon Resource Groups Tagging API Reference

This guide describes the API operations for Amazon Resource Groups Tagging.

A tag is a label that you assign to an Amazon resource. A tag consists of a key and a value, both of which you define. For example, if you have two Amazon EC2 instances, you might assign both a tag key of "Stack." But the value of "Stack" might be "Testing" for one and "Production" for the other.

Amazon supports tagging on all core infrastructure resources that incur charges. Most other Amazon resources also support tagging. Some resources support tagging only through that service's native tagging operations, and don't yet support this API. See the documentation for an individual service for information about that service's native tagging operations.

Important

Do not store personally identifiable information (PII) or other confidential or sensitive information in tags. We use tags to provide you with billing and administration services. Tags are not intended to be used for private or sensitive data.

Tagging can help you organize your resources and enables you to simplify resource management, access management and cost allocation.

For information about tagging your Amazon resources, including strategies and techniques, see [Tagging Amazon resources](#) in the *Amazon Web Services General Reference*.

You can use the Resource Groups Tagging API operations to complete the following tasks:

- Tag and untag supported resources located in the specified Region for the Amazon Web Services account.
- Use tag-based filters to search for resources located in the specified Region for the Amazon Web Services account.
- List all existing tag keys in the specified Region for the Amazon Web Services account.
- List all existing values for the specified key in the specified Region for the Amazon Web Services account.

To use Resource Groups Tagging API operations, you must add the following permissions to your IAM policy:

- `tag:GetResources`
- `tag:TagResources`
- `tag:UntagResources`
- `tag:GetTagKeys`
- `tag:GetTagValues`

You'll also need permissions to access the resources of individual services so that you can tag and untag those resources.

For more information on IAM policies, see [Managing IAM Policies](#) in the *IAM User Guide*.

Services that support the Resource Groups Tagging API

You can use the Resource Groups Tagging API to tag resources for the following Amazon services.

Note

This list includes only those Amazon services that work with the Resource Groups Tagging API. If an Amazon service isn't listed below, you might still be able to tag that service's resources by using the service's native tagging operations instead of using the Resource Groups Tagging API operations. See the documentation for an individual service for information about that service's native tagging operations.

This lets you tag resources by using the Amazon CLI version of the service's operation. For example, you could tag an IAM role by using a command similar to the following example:

```
$ aws iam tag-role --role-name ProdAppRole --tags Key=CostCenter,Value=1234
```

For a list of the Amazon services that work with Tag Editor, see [Supported Resources](#) in the *Amazon Resource Groups User Guide*.

IAM users and roles can only be used in TagResource and UntagResources operations.

- [Amazon Amplify](#)
- [Amazon API Gateway](#)
- [Amazon AppFlow](#)
- [Amazon AppStream](#)
- [Amazon AppSync](#)
- [Amazon App Mesh](#)
- [Amazon Athena](#)
- [Amazon Audit Manager](#)
- [Amazon Aurora](#)
- [Auto Scaling](#)

The TagResources and UntagResources operations of Amazon Resource Groups Tagging API work as documented with Auto Scaling Groups. However, the GetTagKey, GetTagValues and GetResources operations aren't supported at this time and return an empty response for this service.

- [Amazon Backup](#)
- [Amazon Batch](#)
- [Amazon Braket](#)
- [Amazon Certificate Manager](#)
- [Amazon Private Certificate Authority](#)
- [Amazon Cloud9](#)
- [Amazon Cloud Directory](#)
- [Amazon Cloud Map](#)
- [Amazon CloudFormation](#)
- [Amazon CloudFront](#)
- [Amazon CloudHSM](#)
- [Amazon CloudTrail](#)

- [Amazon CloudWatch \(alarms only\)](#)
- [Amazon CloudWatch Events](#)
- [Amazon CloudWatch Logs](#)
- [Amazon CloudWatch Synthetics](#)
- [Amazon CodeArtifact](#)
- [Amazon CodeBuild](#)
- [Amazon CodeCommit](#)
- [Amazon CodeDeploy](#)
- [Amazon CodeGuru Profiler](#)
- [Amazon CodeGuru Reviewer](#)
- [Amazon CodePipeline](#)
- [AWS CodeStar](#)
- [Amazon CodeStar Connections](#)
- [Amazon Cognito Identity](#)
- [Amazon Cognito user pools](#)
- [Amazon Comprehend](#)
- [Amazon Config](#)
- [Amazon Connect](#)
- [Amazon Data Exchange](#)
- [Amazon Data Lifecycle Manager](#)
- [Amazon Data Pipeline](#)
- [Amazon Database Migration Service](#)
- [Amazon DataSync](#)
- [Amazon Device Farm](#)
- [Amazon Direct Connect](#)
- [Amazon Directory Service](#)
- [Amazon DynamoDB](#)
- [Amazon Elastic Block Store \(Amazon EBS\)](#)
- [Amazon Elastic Compute Cloud \(Amazon EC2\)](#)
- [EC2 Image Builder](#)
- [Amazon Elastic Container Registry \(Amazon ECR\)](#)
- [Amazon Elastic Container Service \(Amazon ECS\)](#)
- [Amazon Elastic Kubernetes Service \(Amazon EKS\)](#)
- [Amazon Elastic Beanstalk](#)
- [Amazon Elastic File System \(Amazon EFS\)](#)
- [Elastic Load Balancing](#)
- [Amazon Elastic Inference](#)
- [Amazon ElastiCache](#)
- [AWS Elemental MediaLive](#)
- [AWS Elemental MediaPackage](#)
- [AWS Elemental MediaPackage VoD](#)
- [AWS Elemental MediaTailor](#)
- [Amazon EMR](#)
- [Amazon EMR on EKS \(EMR containers\)](#)
- [Amazon EventBridge Schema](#)
- [Amazon Firewall Manager](#)

- [Amazon Forecast](#)
- [Amazon Fraud Detector](#)
- [Amazon FSx](#)
- [Amazon GameLift](#)
- [Amazon S3 Glacier](#)
- [Amazon Global Accelerator](#)
- [Amazon Ground Station](#)
- [Amazon Glue](#)
- [Amazon GuardDuty](#)
- [Amazon Identity and Access Management \(IAM\)](#) – at this time, you can tag only the following IAM resources using the Resource Groups Tagging API:
 - instance-profile
 - mfa
 - oidc-provider
 - policy
 - role
 - saml-provider
 - server-certificate
 - user
- [IAM Access Analyzer](#)
- [Amazon Inspector](#)
- [Amazon Interactive Video Service](#)
- [Amazon IoT Analytics](#)
- [Amazon IoT Core](#)
- [Amazon IoT Device Defender](#)
- [Amazon IoT Device Management](#)
- [Amazon IoT Events](#)
- [Amazon IoT Greengrass](#)
- [Amazon IoT 1-Click](#) – at this time, you can tag only the following Amazon IoT 1-Click resources using the Resource Groups Tagging API:
 - projects
 - devices
- [Amazon IoT SiteWise IoT Sitewise](#)
- [Amazon IoT Secure Tunneling](#)
- [Amazon IoT Things Graph](#)
- [Amazon IoT Wireless](#)
- [Amazon Kendra](#)
- [Amazon Key Management Service \(Amazon KMS\)](#)
- [Amazon Kinesis](#)
- [Amazon Managed Service for Apache Flink](#)
- [Amazon Kinesis Data Firehose](#)
- [Amazon Lambda](#)
- [Amazon Lex](#)
- [Amazon Web Services Marketplace](#)
- [Amazon License Manager](#)
- [Amazon Lightsail](#)

- [Amazon Macie](#)
- [Amazon Machine Learning](#)
- [Amazon Managed Blockchain](#)
- [AWS Elemental MediaConnect](#)
- [Amazon MQ](#)
- [Amazon Managed Streaming for Apache Kafka \(Amazon MSK\)](#)
- [Amazon Neptune](#)
- [Amazon Network Manager](#)
- [Amazon OpenSearch Service](#)
- [Amazon OpsWorks](#)
- [Amazon OpsWorks CM](#)
- [Amazon Organizations](#)
- [Amazon Outposts](#)
- [Amazon Pinpoint](#)
- [Amazon Quantum Ledger Database \(Amazon QLDB\)](#)
- [Amazon Relational Database Service \(Amazon RDS\)](#)
- [Amazon Redshift](#)
- [Amazon Resource Access Manager](#)
- [Amazon Resource Groups](#)
- [Amazon RoboMaker](#)
- [Amazon Route 53](#)
- [Amazon Route 53 Resolver](#)
- [Amazon Simple Storage Service \(Amazon S3\) \(buckets only\)](#)
- [Amazon SageMaker](#)
- [Savings Plans](#)
- [Amazon Secrets Manager](#)
- [Amazon Security Hub](#)
- [Service Catalog](#)
- [Service Quotas](#)
- [Amazon Simple Email Service \(Amazon SES\)](#)
- [Amazon Simple Notification Service \(Amazon SNS\)](#)
- [Amazon Simple Queue Service \(Amazon SQS\)](#)
- [Amazon Simple Workflow Service](#)
- [Amazon Step Functions](#)
- [Amazon Storage Gateway](#)
- [Amazon Systems Manager](#)
- [Amazon Transfer for FTP](#)
- [Amazon Virtual Private Cloud \(Amazon VPC\)](#)
- [Amazon WAF](#)
- [Amazon WAF Regional](#)
- [Amazon WorkSpaces](#)
- [Amazon X-Ray](#)

Actions

The following actions are supported:

- [DescribeReportCreation \(p. 7\)](#)
- [GetComplianceSummary \(p. 10\)](#)
- [GetResources \(p. 16\)](#)
- [GetTagKeys \(p. 23\)](#)
- [GetTagValues \(p. 26\)](#)
- [StartReportCreation \(p. 30\)](#)
- [TagResources \(p. 34\)](#)
- [UntagResources \(p. 38\)](#)

DescribeReportCreation

Describes the status of the StartReportCreation operation.

You can call this operation only from the organization's management account and from the us-east-1 Region.

Response Syntax

```
{  
  "ErrorMessage": "string",  
  "S3Location": "string",  
  "Status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ErrorMessage \(p. 7\)](#)

Details of the common errors that all operations return.

Type: String

[S3Location \(p. 7\)](#)

The path to the Amazon S3 bucket where the report was stored on creation.

Type: String

[Status \(p. 7\)](#)

Reports the status of the operation.

The operation status can be one of the following:

- RUNNING - Report creation is in progress.
- SUCCEEDED - Report creation is complete. You can open the report from the Amazon S3 bucket that you specified when you ran StartReportCreation.
- FAILED - Report creation timed out or the Amazon S3 bucket is not accessible.
- NO REPORT - No report was generated in the last 90 days.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 53\)](#).

ConstraintViolationException

The request failed because performing the operation would violate a constraint.

Some of the reasons in the following list might not apply to this specific operation.

- You must meet the prerequisites for using tag policies. For information, see [Prerequisites and Permissions for Using Tag Policies](#) in the *Amazon Organizations User Guide*.
- You must enable the tag policies service principal (`tagpolicies.tag.amazonaws.com`) to integrate with Amazon Organizations. For information, see [EnableAWSServiceAccess](#).
- You must have a tag policy attached to the organization root, an OU, or an account.

HTTP Status Code: 400

InternalServerErrorException

The request processing failed because of an unknown error, exception, or failure. You can retry the request.

HTTP Status Code: 500

InvalidParameterException

The request failed because of one of the following reasons:

- A required parameter is missing.
- A provided string parameter is malformed.
- An provided parameter value is out of range.
- The target ID is invalid, unsupported, or doesn't exist.
- You can't access the Amazon S3 bucket for report storage. For more information, see [Additional Requirements for Organization-wide Tag Compliance Reports](#) in the *Amazon Organizations User Guide*.
- The partition specified in an ARN parameter in the request doesn't match the partition where you invoked the operation. The partition is specified by the second field of the ARN.

HTTP Status Code: 400

ThrottledException

The request failed because it exceeded the allowed frequency of submitted requests.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeReportCreation`.

Sample Request

```
POST / HTTP/1.1
Host: tagging.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 20
X-Amz-Target: ResourceGroupsTaggingAPI_20170126.DescribeReportCreation
X-Amz-Date: 20191201T214524Z
User-Agent: aws-cli/1.11.79 Python/2.7.9 Windows/7 botocore/1.5.42
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestID: d3cf21f0-26db-11e7-a532-75e05382c8b1
Content-Type: application/x-amz-json-1.1
Date: Sun, 1 Dec 2019 21:45:25 GMT

{
  "ErrorMessage":null,
  "S3Location":"s3://awsexamplebucket/AwsTagPolicies/o-exampleorgid/2019-12-01-
T21:45:24Z/report.csv",
  "Status":"SUCCEEDED"
}
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetComplianceSummary

Returns a table that shows counts of resources that are noncompliant with their tag policies.

For more information on tag policies, see [Tag Policies](#) in the *Amazon Organizations User Guide*.

You can call this operation only from the organization's management account and from the us-east-1 Region.

This operation supports pagination, where the response can be sent in multiple pages. You should check the `PaginationToken` response parameter to determine if there are additional results available to return. Repeat the query, passing the `PaginationToken` response parameter value as an input to the next request until you receive a null value. A null value for `PaginationToken` indicates that there are no more results waiting to be returned.

Request Syntax

```
{
  "GroupBy": [ "string" ],
  "MaxResults": number,
  "PaginationToken": "string",
  "RegionFilters": [ "string" ],
  "ResourceTypeFilters": [ "string" ],
  "TagKeyFilters": [ "string" ],
  "TargetIdFilters": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 51\)](#).

The request accepts the following data in JSON format.

[GroupBy \(p. 10\)](#)

Specifies a list of attributes to group the counts of noncompliant resources by. If supplied, the counts are sorted by those attributes.

Type: Array of strings

Valid Values: TARGET_ID | REGION | RESOURCE_TYPE

Required: No

[MaxResults \(p. 10\)](#)

Specifies the maximum number of results to be returned in each page. A query can return fewer than this maximum, even if there are more results still to return. You should always check the `PaginationToken` response value to see if there are more results. You can specify a minimum of 1 and a maximum value of 100.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

[PaginationToken \(p. 10\)](#)

Specifies a `PaginationToken` response value from a previous request to indicate that you want the next page of results. Leave this parameter empty in your initial request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Required: No

[RegionFilters \(p. 10\)](#)

Specifies a list of Amazon Regions to limit the output to. If you use this parameter, the count of returned noncompliant resources includes only resources in the specified Regions.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

[ResourceTypeFilters \(p. 10\)](#)

Specifies that you want the response to include information for only resources of the specified types. The format of each resource type is `service[:resourceType]`. For example, specifying a resource type of `ec2` returns all Amazon EC2 resources (which includes EC2 instances). Specifying a resource type of `ec2:instance` returns only EC2 instances.

The string for each service name and resource type is the same as that embedded in a resource's Amazon Resource Name (ARN). Consult the [Amazon General Reference](#) for the following:

- For a list of service name strings, see [Amazon Service Namespaces](#).
- For resource type strings, see [Example ARNs](#).
- For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#).

Note

For the list of services whose resources you can tag using the Resource Groups Tagging API, see [Services that support the Resource Groups Tagging API](#). If an Amazon service isn't listed on that page, you might still be able to tag that service's resources by using that service's native tagging operations instead of using Resource Groups Tagging API operations. All tagged resources, whether the tagging used the Resource Groups Tagging API or not, are returned by the `Get*` operation.

You can specify multiple resource types by using a comma separated array. The array can include up to 100 items. Note that the length constraint requirement applies to each resource type filter.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

[TagKeyFilters \(p. 10\)](#)

Specifies that you want the response to include information for only resources that have tags with the specified tag keys. If you use this parameter, the count of returned noncompliant resources includes only resources that have the specified tag keys.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: $^([\p{L}\p{Z}\p{N}_.\:/\+=\-\@]*)\$$

Required: No

[TargetIdFilters \(p. 10\)](#)

Specifies target identifiers (usually, specific account IDs) to limit the output by. If you use this parameter, the count of returned noncompliant resources includes only resources with the specified target IDs.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 6. Maximum length of 68.

Pattern: $[a-zA-Z0-9-]*$

Required: No

Response Syntax

```
{
  "PaginationToken": "string",
  "SummaryList": [
    {
      "LastUpdated": "string",
      "NonCompliantResources": number,
      "Region": "string",
      "ResourceType": "string",
      "TargetId": "string",
      "TargetIdType": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[PaginationToken \(p. 12\)](#)

A string that indicates that there is more data available than this response contains. To receive the next part of the response, specify this response value as the `PaginationToken` value in the request for the next page.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

[SummaryList \(p. 12\)](#)

A table that shows counts of noncompliant resources.

Type: Array of [Summary \(p. 47\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 53\)](#).

ConstraintViolationException

The request failed because performing the operation would violate a constraint.

Some of the reasons in the following list might not apply to this specific operation.

- You must meet the prerequisites for using tag policies. For information, see [Prerequisites and Permissions for Using Tag Policies](#) in the *Amazon Organizations User Guide*.
- You must enable the tag policies service principal (`tagpolicies.tag.amazonaws.com`) to integrate with Amazon Organizations For information, see [EnableAWSServiceAccess](#).
- You must have a tag policy attached to the organization root, an OU, or an account.

HTTP Status Code: 400

InternalServiceException

The request processing failed because of an unknown error, exception, or failure. You can retry the request.

HTTP Status Code: 500

InvalidParameterException

The request failed because of one of the following reasons:

- A required parameter is missing.
- A provided string parameter is malformed.
- An provided parameter value is out of range.
- The target ID is invalid, unsupported, or doesn't exist.
- You can't access the Amazon S3 bucket for report storage. For more information, see [Additional Requirements for Organization-wide Tag Compliance Reports](#) in the *Amazon Organizations User Guide*.
- The partition specified in an ARN parameter in the request doesn't match the partition where you invoked the operation. The partition is specified by the second field of the ARN.

HTTP Status Code: 400

ThrottledException

The request failed because it exceeded the allowed frequency of submitted requests.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetComplianceSummary.

Sample Request

```
HTTP/1.1
Host: tagging.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 663
X-Amz-Target: ResourceGroupsTaggingAPI_20170126.GetComplianceSummary
X-Amz-Date: 20191201T214524Z
User-Agent: aws-cli/1.11.79 Python/2.7.9 Windows/7 botocore/1.5.42
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "GroupBy": [
    "TARGET_ID",
    "REGION",
    "RESOURCE_TYPE"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestID: d3cf21f0-26db-11e7-a532-75e05382c8b1
Content-Type: application/x-amz-json-1.1
Date: Sun, 1 Dec 2019 21:45:25 GMT
{
  "SummaryList": [
    {
      "LastUpdated": "2019-10-28T21:53:16Z",
      "NonCompliantResources": 1,
      "Region": "us-east-1",
      "ResourceType": "ec2:instance",
      "TargetId": "333333333333",
      "TargetIdType": "ACCOUNT"
    },
    {
      "LastUpdated": "2019-10-28T21:53:17Z",
      "NonCompliantResources": 0,
      "Region": "us-east-1",
      "ResourceType": "ec2:snapshot",
      "TargetId": "222222222222",
      "TargetIdType": "ACCOUNT"
    },
    {
      "LastUpdated": "2019-10-28T21:53:16Z",
      "NonCompliantResources": 1,
      "Region": "us-east-1",
      "ResourceType": "ec2:volume",
      "TargetId": "111111111111",
      "TargetIdType": "ACCOUNT"
    }
  ]
}
```

```
} ]
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetResources

Returns all the tagged or previously tagged resources that are located in the specified Amazon Region for the account.

Depending on what information you want returned, you can also specify the following:

- *Filters* that specify what tags and resource types you want returned. The response includes all tags that are associated with the requested resources.
- Information about compliance with the account's effective tag policy. For more information on tag policies, see [Tag Policies](#) in the *Amazon Organizations User Guide*.

Note

This operation has a rate limit that specifies the maximum number of times you can call it per second. For the current value of this limit, see [Service Quotas for Resource Groups Tagging API](#) in the *Tag Editor Users Guide*.

This operation supports pagination, where the response can be sent in multiple pages. You should check the `PaginationToken` response parameter to determine if there are additional results available to return. Repeat the query, passing the `PaginationToken` response parameter value as an input to the next request until you receive a null value. A null value for `PaginationToken` indicates that there are no more results waiting to be returned.

Request Syntax

```
{
  "ExcludeCompliantResources": boolean,
  "IncludeComplianceDetails": boolean,
  "PaginationToken": "string",
  "ResourceARNList": [ "string" ],
  "ResourcesPerPage": number,
  "ResourceTypeFilters": [ "string" ],
  "TagFilters": [
    {
      "Key": "string",
      "Values": [ "string" ]
    }
  ],
  "TagsPerPage": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 51\)](#).

The request accepts the following data in JSON format.

[ExcludeCompliantResources \(p. 16\)](#)

Specifies whether to exclude resources that are compliant with the tag policy. Set this to `true` if you are interested in retrieving information on noncompliant resources only.

You can use this parameter only if the `IncludeComplianceDetails` parameter is also set to `true`.

Type: Boolean

Required: No

IncludeComplianceDetails (p. 16)

Specifies whether to include details regarding the compliance with the effective tag policy. Set this to `true` to determine whether resources are compliant with the tag policy and to get details.

Type: Boolean

Required: No

PaginationToken (p. 16)

Specifies a `PaginationToken` response value from a previous request to indicate that you want the next page of results. Leave this parameter empty in your initial request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Required: No

ResourceARNList (p. 16)

Specifies a list of ARNs of resources for which you want to retrieve tag data.

You can't specify both this parameter and the `ResourceTypeFilters` parameter in the same request. If you do, you get an `Invalid Parameter` exception.

You can't specify both this parameter and the `TagFilters` parameter in the same request. If you do, you get an `Invalid Parameter` exception.

You can't specify both this parameter and any of the pagination parameters (`ResourcesPerPage`, `TagsPerPage`, `PaginationToken`) in the same request. If you do, you get an `Invalid Parameter` exception.

If a resource specified by this parameter doesn't exist, it doesn't generate an error; it simply isn't included in the response.

An ARN (Amazon Resource Name) uniquely identifies a resource. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `[\s\S]*`

Required: No

ResourcesPerPage (p. 16)

Specifies the maximum number of results to be returned in each page. A query can return fewer than this maximum, even if there are more results still to return. You should always check the `PaginationToken` response value to see if there are more results. You can specify a minimum of 1 and a maximum value of 100.

Type: Integer

Required: No

[ResourceTypeFilters \(p. 16\)](#)

Specifies the resource types that you want included in the response. The format of each resource type is `service[:resourceType]`. For example, specifying a resource type of `ec2` returns all Amazon EC2 resources (which includes EC2 instances). Specifying a resource type of `ec2:instance` returns only EC2 instances.

You can't specify both this parameter and the `ResourceArnList` parameter in the same request. If you do, you get an `Invalid Parameter` exception.

The string for each service name and resource type is the same as that embedded in a resource's Amazon Resource Name (ARN).

Note

For the list of services whose resources you can tag using the Resource Groups Tagging API, see [Services that support the Resource Groups Tagging API](#). If an Amazon service isn't listed on that page, you might still be able to tag that service's resources by using that service's native tagging operations instead of using Resource Groups Tagging API operations. All tagged resources, whether the tagging used the Resource Groups Tagging API or not, are returned by the `Get*` operation.

You can specify multiple resource types by using an array. The array can include up to 100 items. Note that the length constraint requirement applies to each resource type filter. For example, the following string would limit the response to only Amazon EC2 instances, Amazon S3 buckets, or any Amazon Audit Manager resource:

```
ec2:instance,s3:bucket,auditmanager
```

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

[TagFilters \(p. 16\)](#)

Specifies a list of `TagFilters` (keys and values) to restrict the output to only those resources that have tags with the specified keys and, if included, the specified values. Each `TagFilter` must contain a key with values optional. A request can include up to 50 keys, and each key can include up to 20 values.

You can't specify both this parameter and the `ResourceArnList` parameter in the same request. If you do, you get an `Invalid Parameter` exception.

Note the following when deciding how to use `TagFilters`:

- If you *don't* specify a `TagFilter`, the response includes all resources that are currently tagged or ever had a tag. Resources that currently don't have tags are shown with an empty tag set, like this: `"Tags": []`.
- If you specify more than one filter in a single request, the response returns only those resources that satisfy all filters.
- If you specify a filter that contains more than one value for a key, the response returns resources that match *any* of the specified values for that key.
- If you don't specify a value for a key, the response returns all resources that are tagged with that key, with any or no value.

For example, for the following filters: `filter1= {keyA,{value1}}`, `filter2={keyB,{value2,value3,value4}}`, `filter3= {keyC}`:

- `GetResources({filter1})` returns resources tagged with `key1=value1`
- `GetResources({filter2})` returns resources tagged with `key2=value2` or `key2=value3` or `key2=value4`
- `GetResources({filter3})` returns resources tagged with any tag with the key `key3`, and with any or no value
- `GetResources({filter1, filter2, filter3})` returns resources tagged with (`key1=value1`) and (`key2=value2` or `key2=value3` or `key2=value4`) and (`key3`, any or no value)

Type: Array of [TagFilter \(p. 50\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

[TagsPerPage \(p. 16\)](#)

Amazon recommends using `ResourcesPerPage` instead of this parameter.

A limit that restricts the number of tags (key and value pairs) returned by `GetResources` in paginated output. A resource with no tags is counted as having one tag (one key and value pair).

`GetResources` does not split a resource and its associated tags across pages. If the specified `TagsPerPage` would cause such a break, a `PaginationToken` is returned in place of the affected resource and its tags. Use that token in another request to get the remaining data. For example, if you specify a `TagsPerPage` of 100 and the account has 22 resources with 10 tags each (meaning that each resource has 10 key and value pairs), the output will consist of three pages. The first page displays the first 10 resources, each with its 10 tags. The second page displays the next 10 resources, each with its 10 tags. The third page displays the remaining 2 resources, each with its 10 tags.

You can set `TagsPerPage` to a minimum of 100 items up to a maximum of 500 items.

Type: Integer

Required: No

Response Syntax

```
{
  "PaginationToken": "string",
  "ResourceTagMappingList": [
    {
      "ComplianceDetails": {
        "ComplianceStatus": boolean,
        "KeysWithNoncompliantValues": [ "string" ],
        "NoncompliantKeys": [ "string" ]
      },
      "ResourceARN": "string",
      "Tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[PaginationToken \(p. 19\)](#)

A string that indicates that there is more data available than this response contains. To receive the next part of the response, specify this response value as the `PaginationToken` value in the request for the next page.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

[ResourceTagMappingList \(p. 19\)](#)

A list of resource ARNs and the tags (keys and values) associated with each.

Type: Array of [ResourceTagMapping \(p. 46\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 53\)](#).

InternalServerErrorException

The request processing failed because of an unknown error, exception, or failure. You can retry the request.

HTTP Status Code: 500

InvalidParameterException

The request failed because of one of the following reasons:

- A required parameter is missing.
- A provided string parameter is malformed.
- An provided parameter value is out of range.
- The target ID is invalid, unsupported, or doesn't exist.
- You can't access the Amazon S3 bucket for report storage. For more information, see [Additional Requirements for Organization-wide Tag Compliance Reports](#) in the *Amazon Organizations User Guide*.
- The partition specified in an ARN parameter in the request doesn't match the partition where you invoked the operation. The partition is specified by the second field of the ARN.

HTTP Status Code: 400

PaginationTokenExpiredException

The request failed because the specified `PaginationToken` has expired. A `PaginationToken` is valid for a maximum of 15 minutes.

HTTP Status Code: 400

ThrottledException

The request failed because it exceeded the allowed frequency of submitted requests.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetResources.

Sample Request

```
POST / HTTP/1.1
Host: tagging.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 80
X-Amz-Target: ResourceGroupsTaggingAPI_20170126.GetResources
X-Amz-Date: 20191201T214524Z
User-Agent: aws-cli/1.11.79 Python/2.7.9 Windows/7 botocore/1.5.42
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "ExcludeCompliantResources": null,
  "IncludeComplianceDetails": true,
  "PaginationToken": " 1
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 14bc735b-26da-11e7-a933-67e2d2f3ef37
Content-Type: application/x-amz-json-1.1
Content-Length: 4060
Date: Sun, 1 Dec 2019 21:45:25 GMT

{
  "PaginationToken": "",
  "ResourceTagMappingList": [
    {
      "ComplianceDetails": {
        "ComplianceStatus": true,
        "KeysWithNoncompliantValues": [],
        "NoncompliantKeys": []
      },
      "ResourceARN": "arn:aws:inspector:us-west-2:123456789012:target/0-nvgVhaxX/
template/0-7sbz2Kz0",
      "Tags": []
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetTagKeys

Returns all tag keys currently in use in the specified Amazon Region for the calling account.

This operation supports pagination, where the response can be sent in multiple pages. You should check the `PaginationToken` response parameter to determine if there are additional results available to return. Repeat the query, passing the `PaginationToken` response parameter value as an input to the next request until you receive a null value. A null value for `PaginationToken` indicates that there are no more results waiting to be returned.

Request Syntax

```
{  
  "PaginationToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 51\)](#).

The request accepts the following data in JSON format.

[PaginationToken \(p. 23\)](#)

Specifies a `PaginationToken` response value from a previous request to indicate that you want the next page of results. Leave this parameter empty in your initial request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Required: No

Response Syntax

```
{  
  "PaginationToken": "string",  
  "TagKeys": [ "string" ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[PaginationToken \(p. 23\)](#)

A string that indicates that there is more data available than this response contains. To receive the next part of the response, specify this response value as the `PaginationToken` value in the request for the next page.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

[TagKeys \(p. 23\)](#)

A list of all tag keys in the Amazon account.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_.\:/=\+\-@]*)$`

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 53\)](#).

InternalServiceException

The request processing failed because of an unknown error, exception, or failure. You can retry the request.

HTTP Status Code: 500

InvalidParameterException

The request failed because of one of the following reasons:

- A required parameter is missing.
- A provided string parameter is malformed.
- An provided parameter value is out of range.
- The target ID is invalid, unsupported, or doesn't exist.
- You can't access the Amazon S3 bucket for report storage. For more information, see [Additional Requirements for Organization-wide Tag Compliance Reports](#) in the *Amazon Organizations User Guide*.
- The partition specified in an ARN parameter in the request doesn't match the partition where you invoked the operation. The partition is specified by the second field of the ARN.

HTTP Status Code: 400

PaginationTokenExpiredException

The request failed because the specified `PaginationToken` has expired. A `PaginationToken` is valid for a maximum of 15 minutes.

HTTP Status Code: 400

ThrottledException

The request failed because it exceeded the allowed frequency of submitted requests.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `GetTagKeys`.

Sample Request

```
POST / HTTP/1.1
Host: tagging.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: ResourceGroupsTaggingAPI_20170126.GetTagKeys
X-Amz-Date: 20170421T214126Z
User-Agent: aws-cli/1.11.79 Python/2.7.9 Windows/7 botocore/1.5.42
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 462f0799-26db-11e7-a88c-a74e0c5622c9
Content-Type: application/x-amz-json-1.1
Content-Length: 79
Date: Fri, 21 Apr 2017 21:41:27 GMT

{
  "PaginationToken": "",
  "TagKeys": [
    "Example",
    "Example1",
    "Example2"
  ]
}
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetTagValues

Returns all tag values for the specified key that are used in the specified Amazon Region for the calling account.

This operation supports pagination, where the response can be sent in multiple pages. You should check the `PaginationToken` response parameter to determine if there are additional results available to return. Repeat the query, passing the `PaginationToken` response parameter value as an input to the next request until you receive a null value. A null value for `PaginationToken` indicates that there are no more results waiting to be returned.

Request Syntax

```
{  
  "Key": "string",  
  "PaginationToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 51\)](#).

The request accepts the following data in JSON format.

[Key \(p. 26\)](#)

Specifies the tag key for which you want to list all existing values that are currently used in the specified Amazon Region for the calling account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\s\S]*`

Required: Yes

[PaginationToken \(p. 26\)](#)

Specifies a `PaginationToken` response value from a previous request to indicate that you want the next page of results. Leave this parameter empty in your initial request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

Required: No

Response Syntax

```
{  
  "PaginationToken": "string",  
}
```

```
}  "TagValues": [ "string" ]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[PaginationToken \(p. 26\)](#)

A string that indicates that there is more data available than this response contains. To receive the next part of the response, specify this response value as the `PaginationToken` value in the request for the next page.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[\s\S]*`

[TagValues \(p. 26\)](#)

A list of all tag values for the specified key currently used in the specified Amazon Region for the calling account.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.\:/+=\-\@]*)$`

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 53\)](#).

InternalServiceException

The request processing failed because of an unknown error, exception, or failure. You can retry the request.

HTTP Status Code: 500

InvalidParameterException

The request failed because of one of the following reasons:

- A required parameter is missing.
- A provided string parameter is malformed.
- An provided parameter value is out of range.
- The target ID is invalid, unsupported, or doesn't exist.
- You can't access the Amazon S3 bucket for report storage. For more information, see [Additional Requirements for Organization-wide Tag Compliance Reports](#) in the *Amazon Organizations User Guide*.
- The partition specified in an ARN parameter in the request doesn't match the partition where you invoked the operation. The partition is specified by the second field of the ARN.

HTTP Status Code: 400

PaginationTokenExpiredException

The request failed because the specified `PaginationToken` has expired. A `PaginationToken` is valid for a maximum of 15 minutes.

HTTP Status Code: 400

ThrottledException

The request failed because it exceeded the allowed frequency of submitted requests.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `GetTagValues`.

Sample Request

```
POST / HTTP/1.1
Host: tagging.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 18
X-Amz-Target: ResourceGroupsTaggingAPI_20170126.GetTagValues
X-Amz-Date: 20170421T214524Z
User-Agent: aws-cli/1.11.79 Python/2.7.9 Windows/7 botocore/1.5.42
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "Key": "Example_key"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: d3cf21f0-26db-11e7-a532-75e05382c8b1
Content-Type: application/x-amz-json-1.1
Content-Length: 42
Date: Fri, 21 Apr 2017 21:45:25 GMT

{
  "PaginationToken": "",
  "TagValues": [
    "Example_value"
  ]
}
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

StartReportCreation

Generates a report that lists all tagged resources in the accounts across your organization and tells whether each resource is compliant with the effective tag policy. Compliance data is refreshed daily. The report is generated asynchronously.

The generated report is saved to the following location:

```
s3://example-bucket/AwsTagPolicies/o-exampleorgid/YYYY-MM-ddTHH:mm:ssZ/  
report.csv
```

You can call this operation only from the organization's management account and from the us-east-1 Region.

Request Syntax

```
{  
  "S3Bucket": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 51\)](#).

The request accepts the following data in JSON format.

[S3Bucket \(p. 30\)](#)

The name of the Amazon S3 bucket where the report will be stored; for example:

```
awsexamplebucket
```

For more information on S3 bucket requirements, including an example bucket policy, see the [example S3 bucket policy](#) on this page.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: [a-z0-9.-]*

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 53\)](#).

ConcurrentModificationException

The request failed because the target of the operation is currently being modified by a different request. Try again later.

HTTP Status Code: 400

ConstraintViolationException

The request failed because performing the operation would violate a constraint.

Some of the reasons in the following list might not apply to this specific operation.

- You must meet the prerequisites for using tag policies. For information, see [Prerequisites and Permissions for Using Tag Policies](#) in the *Amazon Organizations User Guide*.
- You must enable the tag policies service principal (`tagpolicies.tag.amazonaws.com`) to integrate with Amazon Organizations For information, see [EnableAWSServiceAccess](#).
- You must have a tag policy attached to the organization root, an OU, or an account.

HTTP Status Code: 400

InternalServiceException

The request processing failed because of an unknown error, exception, or failure. You can retry the request.

HTTP Status Code: 500

InvalidParameterException

The request failed because of one of the following reasons:

- A required parameter is missing.
- A provided string parameter is malformed.
- An provided parameter value is out of range.
- The target ID is invalid, unsupported, or doesn't exist.
- You can't access the Amazon S3 bucket for report storage. For more information, see [Additional Requirements for Organization-wide Tag Compliance Reports](#) in the *Amazon Organizations User Guide*.
- The partition specified in an ARN parameter in the request doesn't match the partition where you invoked the operation. The partition is specified by the second field of the ARN.

HTTP Status Code: 400

ThrottledException

The request failed because it exceeded the allowed frequency of submitted requests.

HTTP Status Code: 400

Examples

Sample Amazon S3 policy

Before creating the report, you must grant access for the tag policies service principal to an Amazon S3 bucket for report storage. Attach the following bucket policy to the bucket. The statements in the `Condition` element ensure that the operations can be performed only by the management account of the specified organization. If you don't know your organization ID or your management account's ID, you can call [DescribeOrganization](#) to find it.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "TagPolicyACL",
```

```

        "Effect": "Allow",
        "Principal": {
            "Service": [
                "tagpolicies.tag.amazonaws.com"
            ]
        },
        "Action": "s3:GetBucketAcl",
        "Resource": "arn:aws:s3:::your-bucket-name",
        "Condition": {
            "StringEquals": {
                "aws:SourceAccount": "your-org-management-account-id",
                "aws:SourceArn": "arn:aws:tag:us-east-1:your-org-management-account-
id:*"
            }
        }
    },
    {
        "Sid": "TagPolicyBucketDelivery",
        "Effect": "Allow",
        "Principal": {
            "Service": [
                "tagpolicies.tag.amazonaws.com"
            ]
        },
        "Action": [
            "s3:PutObject",
            "s3:PutObjectAcl"
        ],
        "Resource": "arn:aws:s3:::<your-bucket-name>/AwsTagPolicies/<your-org-id>/*",
        "Condition": {
            "StringEquals": {
                "aws:SourceAccount": "<your-org-management-account-id>",
                "aws:SourceArn": "arn:aws:tag:us-east-1:<your-org-management-account-
id>:*"
            }
        }
    }
]
}

```

Sample KMS Key Policy

If you choose to use a customer managed KMS key, you must grant access for the tag policies service principal before creating the report. Add the following Statement to your current KMS key policy. The statements in the Condition element ensure that the operations can be performed only by the management account of the specified organization. If you don't know your organization ID or your organization admin account ID, you can call the [DescribeOrganization](#) operation to find it.

```

...
{
    "Sid": "AllowBucketAccessKMSPolicy",
    "Effect": "Allow",
    "Principal": {
        "Service": "tagpolicies.tag.amazonaws.com"
    },
    "Action": [
        "kms:Decrypt",
        "kms:GenerateDataKey*"
    ],
    "Resource": "arn:aws:kms:<region>:<your-kms-key-arn>",
    "Condition": {
        "StringEquals": {
            "aws:SourceAccount": "<org-admin-account-id>",

```

```
    "aws:SourceArn": "arn:aws:tag:us-east-1:<org-admin-account-id>:*"  
  }  
}  
}
```

Example

This example illustrates one usage of StartReportCreation.

Sample Request

```
POST / HTTP/1.1  
Host: tagging.us-east-1.amazonaws.com  
Accept-Encoding: identity  
Content-Length: 20  
X-Amz-Target: ResourceGroupsTaggingAPI_20170126.StartReportCreation  
X-Amz-Date: 20191201T214524Z  
User-Agent: aws-cli/1.11.79 Python/2.7.9 Windows/7 botocore/1.5.42  
Content-Type: application/x-amz-json-1.1  
Authorization: AUTHPARAMS  
  
{  
  "S3Bucket": "awsexamplebucket"  
}
```

Sample Response

```
HTTP/1.1 200 OK  
x-amzn-RequestID: d3cf21f0-26db-11e7-a532-75e05382c8b1  
Content-Type: application/x-amz-json-1.1  
Date: Sun, 1 Dec 2019 21:45:25 GMT  
  
{}
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

TagResources

Applies one or more tags to the specified resources. Note the following:

- Not all resources can have tags. For a list of services with resources that support tagging using this operation, see [Services that support the Resource Groups Tagging API](#). If the resource doesn't yet support this operation, the resource's service might support tagging using its own API operations. For more information, refer to the documentation for that service.
- Each resource can have up to 50 tags. For other limits, see [Tag Naming and Usage Conventions](#) in the *Amazon General Reference*.
- You can only tag resources that are located in the specified Amazon Region for the Amazon account.
- To add tags to a resource, you need the necessary permissions for the service that the resource belongs to as well as permissions for adding tags. For more information, see the documentation for each service.

Important

Do not store personally identifiable information (PII) or other confidential or sensitive information in tags. We use tags to provide you with billing and administration services. Tags are not intended to be used for private or sensitive data.

Minimum permissions

In addition to the `tag:TagResources` permission required by this operation, you must also have the tagging permission defined by the service that created the resource. For example, to tag an Amazon EC2 instance using the `TagResources` operation, you must have both of the following permissions:

- `tag:TagResources`
- `ec2:CreateTags`

Note

In addition, some services might have specific requirements for tagging some types of resources. For example, to tag an Amazon S3 bucket, you must also have the `s3:GetBucketTagging` permission. If the expected minimum permissions don't work, check the documentation for that service's tagging APIs for more information.

Request Syntax

```
{
  "ResourceARNList": [ "string" ],
  "Tags": {
    "string" : "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 51\)](#).

The request accepts the following data in JSON format.

[ResourceARNList \(p. 34\)](#)

Specifies the list of ARNs of the resources that you want to apply tags to.

An ARN (Amazon Resource Name) uniquely identifies a resource. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `[\s\S]*`

Required: Yes

[Tags \(p. 34\)](#)

Specifies a list of tags that you want to add to the specified resources. A tag consists of a key and a value that you define.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^([\p{L}\p{Z}\p{N}_.\:/=+\-@]*)$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^([\p{L}\p{Z}\p{N}_.\:/=+\-@]*)$`

Required: Yes

Response Syntax

```
{
  "FailedResourcesMap": {
    "string": {
      "ErrorCode": "string",
      "ErrorMessage": "string",
      "StatusCode": number
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[FailedResourcesMap \(p. 35\)](#)

A map containing a key-value pair for each failed item that couldn't be tagged. The key is the ARN of the failed resource. The value is a `FailureInfo` object that contains an error code, a status code, and an error message. If there are no errors, the `FailedResourcesMap` is empty.

Type: String to [FailureInfo \(p. 44\)](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 1011.

Key Pattern: [\s\S]*

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 53\)](#).

InternalServerErrorException

The request processing failed because of an unknown error, exception, or failure. You can retry the request.

HTTP Status Code: 500

InvalidParameterException

The request failed because of one of the following reasons:

- A required parameter is missing.
- A provided string parameter is malformed.
- An provided parameter value is out of range.
- The target ID is invalid, unsupported, or doesn't exist.
- You can't access the Amazon S3 bucket for report storage. For more information, see [Additional Requirements for Organization-wide Tag Compliance Reports](#) in the *Amazon Organizations User Guide*.
- The partition specified in an ARN parameter in the request doesn't match the partition where you invoked the operation. The partition is specified by the second field of the ARN.

HTTP Status Code: 400

ThrottledException

The request failed because it exceeded the allowed frequency of submitted requests.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of TagResources.

Sample Request

```
POST / HTTP/1.1
Host: tagging.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 82
X-Amz-Target: ResourceGroupsTaggingAPI_20170126.TagResources
X-Amz-Date: 20170421T214834Z
User-Agent: aws-cli/1.11.79 Python/2.7.9 Windows/7 botocore/1.5.42
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "ResourceARNList": [
    "arn:aws:s3:::example_bucket"
  ],
```



```
"Tags": {  
  "key": "Example_key"  
}
```

Sample Response

```
HTTP/1.1 200 OK  
x-amzn-RequestId: 45352206-26dc-11e7-8812-6fb02084e31d  
Content-Type: application/x-amz-json-1.1  
Content-Length: 0  
Date: Fri, 21 Apr 2017 21:48:35 GMT
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UntagResources

Removes the specified tags from the specified resources. When you specify a tag key, the action removes both that key and its associated value. The operation succeeds even if you attempt to remove tags from a resource that were already removed. Note the following:

- To remove tags from a resource, you need the necessary permissions for the service that the resource belongs to as well as permissions for removing tags. For more information, see the documentation for the service whose resource you want to untag.
- You can only tag resources that are located in the specified Amazon Region for the calling Amazon account.

Minimum permissions

In addition to the `tag:UntagResources` permission required by this operation, you must also have the remove tags permission defined by the service that created the resource. For example, to remove the tags from an Amazon EC2 instance using the `UntagResources` operation, you must have both of the following permissions:

- `tag:UntagResource`
- `ec2:DeleteTags`

Note

In addition, some services might have specific requirements for untagging some types of resources. For example, to untag Amazon Glue Connection, you must also have the `glue:GetConnection` permission. If the expected minimum permissions don't work, check the documentation for that service's tagging APIs for more information.

Request Syntax

```
{
  "ResourceARNList": [ "string" ],
  "TagKeys": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 51\)](#).

The request accepts the following data in JSON format.

[ResourceARNList \(p. 38\)](#)

Specifies a list of ARNs of the resources that you want to remove tags from.

An ARN (Amazon Resource Name) uniquely identifies a resource. For more information, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `[\s\S]*`

Required: Yes

[TagKeys \(p. 38\)](#)

Specifies a list of tag keys that you want to remove from the specified resources.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_.\:/=+\-@]*)$`

Required: Yes

Response Syntax

```
{
  "FailedResourcesMap": {
    "string": {
      "ErrorCode": "string",
      "ErrorMessage": "string",
      "StatusCode": number
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[FailedResourcesMap \(p. 39\)](#)

A map containing a key-value pair for each failed item that couldn't be untagged. The key is the ARN of the failed resource. The value is a [FailureInfo \(p. 44\)](#) object that contains an error code, a status code, and an error message. If there are no errors, the `FailedResourcesMap` is empty.

Type: String to [FailureInfo \(p. 44\)](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 1011.

Key Pattern: `[\s\S]*`

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 53\)](#).

InternalServiceException

The request processing failed because of an unknown error, exception, or failure. You can retry the request.

HTTP Status Code: 500

InvalidParameterException

The request failed because of one of the following reasons:

- A required parameter is missing.
- A provided string parameter is malformed.
- An provided parameter value is out of range.
- The target ID is invalid, unsupported, or doesn't exist.
- You can't access the Amazon S3 bucket for report storage. For more information, see [Additional Requirements for Organization-wide Tag Compliance Reports](#) in the *Amazon Organizations User Guide*.
- The partition specified in an ARN parameter in the request doesn't match the partition where you invoked the operation. The partition is specified by the second field of the ARN.

HTTP Status Code: 400

ThrottledException

The request failed because it exceeded the allowed frequency of submitted requests.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UntagResources.

Sample Request

```
POST / HTTP/1.1
Host: tagging.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 74
X-Amz-Target: ResourceGroupsTaggingAPI_20170126.UntagResources
X-Amz-Date: 20170421T215122Z
User-Agent: aws-cli/1.11.79 Python/2.7.9 Windows/7 botocore/1.5.42
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "TagKeys": [
    "key"
  ],
  "ResourceARNList": [
    "arn:aws:s3:::examplebucket"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: a923ddd9-26dc-11e7-bf86-49f2fe9ee8df
Content-Type: application/x-amz-json-1.1
Content-Length: 25
Date: Fri, 21 Apr 2017 21:51:23 GMT
```

```
{  
  "FailedResourcesMap": {}  
}
```

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

Data Types

The Resource Groups Tagging API API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [ComplianceDetails \(p. 43\)](#)
- [FailureInfo \(p. 44\)](#)
- [ResourceTagMapping \(p. 46\)](#)
- [Summary \(p. 47\)](#)
- [Tag \(p. 49\)](#)
- [TagFilter \(p. 50\)](#)

ComplianceDetails

Information that shows whether a resource is compliant with the effective tag policy, including details on any noncompliant tag keys.

Contents

ComplianceStatus

Whether a resource is compliant with the effective tag policy.

Type: Boolean

Required: No

KeysWithNoncompliantValues

These are keys defined in the effective policy that are on the resource with either incorrect case treatment or noncompliant values.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_.\:/=+\-@]*)$`

Required: No

NoncompliantKeys

These tag keys on the resource are noncompliant with the effective tag policy.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_.\:/=+\-@]*)$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

FailureInfo

Information about the errors that are returned for each failed resource. This information can include `InternalServerErrorException` and `InvalidParameterException` errors. It can also include any valid error code returned by the Amazon service that hosts the resource that the ARN key represents.

The following are common error codes that you might receive from other Amazon services:

- **InternalServerErrorException** – This can mean that the Resource Groups Tagging API didn't receive a response from another Amazon service. It can also mean that the resource type in the request is not supported by the Resource Groups Tagging API. In these cases, it's safe to retry the request and then call [GetResources](#) to verify the changes.
- **AccessDeniedException** – This can mean that you need permission to call the tagging operations in the Amazon service that contains the resource. For example, to use the Resource Groups Tagging API to tag a Amazon CloudWatch alarm resource, you need permission to call both [TagResources](#) and [TagResource](#) in the CloudWatch API.

For more information on errors that are generated from other Amazon services, see the documentation for that service.

Contents

ErrorCode

The code of the common error. Valid values include `InternalServerErrorException`, `InvalidParameterException`, and any valid error code returned by the Amazon service that hosts the resource that you want to tag.

Type: String

Valid Values: `InternalServerErrorException` | `InvalidParameterException`

Required: No

ErrorMessage

The message of the common error.

Type: String

Required: No

StatusCode

The HTTP status code of the common error.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ResourceTagMapping

A list of resource ARNs and the tags (keys and values) that are associated with each.

Contents

ComplianceDetails

Information that shows whether a resource is compliant with the effective tag policy, including details on any noncompliant tag keys.

Type: [ComplianceDetails \(p. 43\)](#) object

Required: No

ResourceARN

The ARN of the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `[\s\S]*`

Required: No

Tags

The tags that have been applied to one or more Amazon resources.

Type: Array of [Tag \(p. 49\)](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Summary

A count of noncompliant resources.

Contents

LastUpdated

The timestamp that shows when this summary was generated in this Region.

Type: String

Required: No

NonCompliantResources

The count of noncompliant resources.

Type: Long

Required: No

Region

The Amazon Region that the summary applies to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

ResourceType

The Amazon resource type.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\s\S]*`

Required: No

TargetId

The account identifier or the root identifier of the organization. If you don't know the root ID, you can call the Amazon Organizations [ListRoots](#) API.

Type: String

Length Constraints: Minimum length of 6. Maximum length of 68.

Pattern: `[a-zA-Z0-9-]*`

Required: No

TargetIdType

Whether the target is an account, an OU, or the organization root.

Type: String

Valid Values: ACCOUNT | OU | ROOT

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Tag

The metadata that you apply to Amazon resources to help you categorize and organize them. Each tag consists of a key and a value, both of which you define. For more information, see [Tagging Amazon Resources](#) in the *Amazon General Reference*.

Contents

Key

One part of a key-value pair that makes up a tag. A key is a general label that acts like a category for more specific tag values.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_.\:/=+\-@]*)$`

Required: Yes

Value

One part of a key-value pair that make up a tag. A value acts as a descriptor within a tag category (key). The value can be empty or null.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.\:/=+\-@]*)$`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

TagFilter

A list of tags (keys and values) that are used to specify the associated resources.

Contents

Key

One part of a key-value pair that makes up a tag. A key is a general label that acts like a category for more specific tag values.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_.\:/=+\-@]*)$`

Required: No

Values

One part of a key-value pair that make up a tag. A value acts as a descriptor within a tag category (key). The value can be empty or null.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 256 items.

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.\:/=+\-@]*)$`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing Amazon API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed Amazon API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an Amazon API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to Amazon Security Token Service (Amazon STS). For a list of services that support temporary security credentials from Amazon STS, see [Amazon Web Services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from Amazon STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed Amazon API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all Amazon services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to Amazon standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or Amazon access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The Amazon access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an Amazon service.

HTTP Status Code: 400

Making API requests

Query requests for the Amazon Resource Groups Tagging API are HTTP or HTTPS requests that use an HTTP verb such as GET or POST.

Amazon Resource Groups Tagging API endpoints

An *endpoint* is a URL that serves as an entry point for a web service. You can select an Amazon Web Services Region endpoint when you make your requests to reduce latency. For information about the endpoints used with Resource Groups Tagging API, see the [Tagging section of Amazon Resource Groups and Tagging endpoints and quotas](#) in the *Amazon Web Services General Reference*.

Query parameters

Each query request must include some common parameters to handle authentication and selection of an action. For more information, see [Common Parameters \(p. 51\)](#).

Some API operations take lists of parameters. These lists are specified using the following notation:

```
param.member.n
```

Values of *n* are integers starting from 1. All lists of parameters must follow this notation, including lists that contain only one parameter. A query parameter list looks like the following example.

```
&attribute.member.1=this  
&attribute.member.2=that
```

Request identifiers

In every response from an Amazon Query API, there is a `ResponseMetadata` element, which contains a `RequestId` element. This string is a unique identifier that Amazon assigns to provide tracking information. Although `RequestId` is included as part of every response, it isn't listed on the individual API documentation pages to improve readability and to reduce redundancy.

Query API authentication

You can send query requests over either HTTP or HTTPS. Regardless of which protocol you use, you must include a signature in every query request. For more information about creating and including a signature, see [Signing Amazon API Requests](#) in the *Amazon Web Services General Reference*.

Available libraries

Amazon provides libraries, sample code, tutorials, and other resources for software developers who prefer to build applications using language-specific APIs instead of the command-line tools and Query API. These libraries provide basic functions (not included in the APIs), such as request authentication, request retries, and error handling so that it's easier to get started. Libraries and resources are available for the following languages and platforms:

- [Amazon SDK for Go](#)
- [Amazon Amplify for mobile apps for Android and iOS](#)
- [Amazon SDK for Java 2.x](#)
- [Amazon SDK for Java 1.x](#)
- [Amazon SDK for JavaScript](#)
- [Amazon SDK for JavaScript in Node.js](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for PHP](#)
- [Amazon SDK for Python \(Boto\)](#)
- [Amazon SDK for Ruby](#)
- [Amazon SDK for Rust](#)
- [Amazon SDK for Swift](#)

For more information about libraries and sample code in all languages, see [Sample Code & Libraries](#).

Making API requests using the POST method

If you don't use one of the Amazon SDKs, you can make Resource Groups Tagging API requests over HTTP using the POST request method. The POST method requires that you specify the operation in the header of the request and provide the data for the operation in JSON format in the body of the request.

Header name	Header value
host	The Amazon Resource Groups Tagging API endpoint. For example: <code>tagging.us-east-1.amazonaws.com.cn</code>
x-amz-date	<p>You must provide the timestamp in either the HTTP Date header or the Amazon <i>x-amz-date</i> header. Some HTTP client libraries don't let you set the Date header. When an <i>x-amz-date</i> header is present, the system ignores any Date header during the request authentication.</p> <p>The <i>x-amz-date</i> header must be specified in ISO 8601 basic format. For example: <code>20130315T092054Z</code></p>
Authorization	The set of authorization parameters that Amazon uses to ensure the validity and authenticity of the request. For more information about constructing this header, see Signature Version 4 Signing Process in the <i>Amazon Web Services General Reference</i> .
x-amz-target	<p>Specifies the Resource Groups Tagging API namespace and version, and the operation that you want to perform.</p> <p><code>ResourceGroupsTaggingAPI_20170126.<i>API_Name</i></code></p> <p>Note For the Resource Groups Tagging API, always use the version 20170126.</p> <p>For example, to call the <code>GetTagValues</code> operation, use the following target value.</p> <p><code>ResourceGroupsTaggingAPI_20170126.GetTagValues</code></p>

Header name	Header value
Content-Type	Specifies the input format. Use the following value. application/json
Accept	Specifies the response format. Use the following value. application/json
Content-Length	Size of the payload in bytes.
Content-Encoding	Specifies the encoding format of the input and output. Use the following value. amz-1.0

The following is an example header for an HTTP request to return metric data in JSON format. In this example, the Authorization line is word-wrapped here for easier reading. Don't word wrap it in your actual request.

```
POST / HTTP/1.1
host: tagging.us-east-1.amazonaws.com.cn
x-amz-target: ResourceGroupsTaggingAPI_20170126.GetTagValues
x-amz-date: 20180112T092034Z
Authorization: AWS4-HMAC-SHA256 Credential=REDACTED/20180411/us-east-1/monitoring/
aws4_request,
    SignedHeaders=content-encoding;content-length;content-type;host;x-amz-date;x-amz-
target,
    Signature=EXAMPLE5cb91f88f1EXAMPLEa02d3af93dEXAMPLE91e5d03588EXAMPLE88ff1d
Content-Type: application/json
Accept: application/json
Content-Encoding: amz-1.0
Content-Length: 18
Connection: keep-alive

{
  "Key": "Example_key"
}
```