

Amazon Security Hub



Amazon Security Hub: API Reference

Table of Contents

Overview	1
Finding Regional endpoints	2
Throttling limits	2
Timestamps	3
Actions	4
AcceptAdministratorInvitation	7
Request Syntax	7
URI Request Parameters	7
Request Body	7
Response Syntax	8
Response Elements	8
Errors	8
See Also	9
AcceptInvitation	10
Request Syntax	10
URI Request Parameters	10
Request Body	10
Response Syntax	11
Response Elements	11
Errors	11
See Also	12
BatchDeleteAutomationRules	13
Request Syntax	13
URI Request Parameters	13
Request Body	13
Response Syntax	13
Response Elements	14
Errors	14
See Also	15
BatchDisableStandards	16
Request Syntax	16
URI Request Parameters	16
Request Body	16
Response Syntax	16

Response Elements	17
Errors	17
See Also	18
BatchEnableStandards	19
Request Syntax	19
URI Request Parameters	19
Request Body	19
Response Syntax	20
Response Elements	20
Errors	20
See Also	21
BatchGetAutomationRules	23
Request Syntax	23
URI Request Parameters	23
Request Body	23
Response Syntax	23
Response Elements	31
Errors	31
See Also	32
BatchGetConfigurationPolicyAssociations	33
Request Syntax	33
URI Request Parameters	33
Request Body	33
Response Syntax	33
Response Elements	34
Errors	35
See Also	35
BatchGetSecurityControls	37
Request Syntax	37
URI Request Parameters	37
Request Body	37
Response Syntax	37
Response Elements	38
Errors	39
See Also	39
BatchGetStandardsControlAssociations	41

Request Syntax	41
URI Request Parameters	41
Request Body	41
Response Syntax	42
Response Elements	42
Errors	43
See Also	43
BatchImportFindings	45
Request Syntax	46
URI Request Parameters	143
Request Body	143
Response Syntax	144
Response Elements	144
Errors	145
See Also	145
BatchUpdateAutomationRules	147
Request Syntax	147
URI Request Parameters	154
Request Body	154
Response Syntax	154
Response Elements	155
Errors	155
See Also	156
BatchUpdateFindings	157
Request Syntax	157
URI Request Parameters	158
Request Body	158
Response Syntax	161
Response Elements	162
Errors	162
See Also	163
BatchUpdateStandardsControlAssociations	164
Request Syntax	164
URI Request Parameters	164
Request Body	164
Response Syntax	165

Response Elements	165
Errors	165
See Also	166
CreateActionTarget	168
Request Syntax	168
URI Request Parameters	168
Request Body	168
Response Syntax	169
Response Elements	169
Errors	169
See Also	170
CreateAutomationRule	172
Request Syntax	172
URI Request Parameters	179
Request Body	179
Response Syntax	181
Response Elements	181
Errors	181
See Also	182
CreateConfigurationPolicy	184
Request Syntax	184
URI Request Parameters	184
Request Body	184
Response Syntax	185
Response Elements	186
Errors	187
See Also	188
CreateFindingAggregator	190
Request Syntax	190
URI Request Parameters	190
Request Body	190
Response Syntax	191
Response Elements	192
Errors	193
See Also	193
CreateInsight	195

Request Syntax	195
URI Request Parameters	211
Request Body	211
Response Syntax	212
Response Elements	212
Errors	212
See Also	213
CreateMembers	214
Request Syntax	215
URI Request Parameters	215
Request Body	215
Response Syntax	215
Response Elements	216
Errors	216
See Also	217
DeclineInvitations	218
Request Syntax	218
URI Request Parameters	218
Request Body	218
Response Syntax	219
Response Elements	219
Errors	219
See Also	220
DeleteActionTarget	221
Request Syntax	221
URI Request Parameters	221
Request Body	221
Response Syntax	221
Response Elements	221
Errors	222
See Also	222
DeleteConfigurationPolicy	224
Request Syntax	224
URI Request Parameters	224
Request Body	224
Response Syntax	224

Response Elements	224
Errors	224
See Also	225
DeleteFindingAggregator	227
Request Syntax	227
URI Request Parameters	227
Request Body	227
Response Syntax	227
Response Elements	228
Errors	228
See Also	229
DeleteInsight	230
Request Syntax	230
URI Request Parameters	230
Request Body	230
Response Syntax	230
Response Elements	230
Errors	231
See Also	232
DeleteInvitations	233
Request Syntax	233
URI Request Parameters	233
Request Body	233
Response Syntax	234
Response Elements	234
Errors	234
See Also	235
DeleteMembers	237
Request Syntax	237
URI Request Parameters	237
Request Body	237
Response Syntax	237
Response Elements	238
Errors	238
See Also	239
DescribeActionTargets	240

Request Syntax	240
URI Request Parameters	240
Request Body	240
Response Syntax	241
Response Elements	241
Errors	242
See Also	242
DescribeHub	244
Request Syntax	244
URI Request Parameters	244
Request Body	244
Response Syntax	244
Response Elements	244
Errors	246
See Also	247
DescribeOrganizationConfiguration	248
Request Syntax	248
URI Request Parameters	248
Request Body	248
Response Syntax	248
Response Elements	248
Errors	250
See Also	250
DescribeProducts	252
Request Syntax	252
URI Request Parameters	252
Request Body	252
Response Syntax	253
Response Elements	253
Errors	253
See Also	254
DescribeStandards	256
Request Syntax	256
URI Request Parameters	256
Request Body	256
Response Syntax	256

Response Elements	257
Errors	257
See Also	258
DescribeStandardsControls	259
Request Syntax	259
URI Request Parameters	259
Request Body	260
Response Syntax	260
Response Elements	260
Errors	261
See Also	261
DisableImportFindingsForProduct	263
Request Syntax	263
URI Request Parameters	263
Request Body	263
Response Syntax	263
Response Elements	263
Errors	263
See Also	264
DisableOrganizationAdminAccount	266
Request Syntax	266
URI Request Parameters	266
Request Body	266
Response Syntax	266
Response Elements	266
Errors	267
See Also	267
DisableSecurityHub	269
Request Syntax	269
URI Request Parameters	269
Request Body	269
Response Syntax	269
Response Elements	269
Errors	269
See Also	270
DisassociateFromAdministratorAccount	272

Request Syntax	272
URI Request Parameters	272
Request Body	272
Response Syntax	272
Response Elements	272
Errors	272
See Also	273
DisassociateFromMasterAccount	274
Request Syntax	274
URI Request Parameters	274
Request Body	274
Response Syntax	274
Response Elements	274
Errors	274
See Also	275
DisassociateMembers	277
Request Syntax	277
URI Request Parameters	277
Request Body	277
Response Syntax	277
Response Elements	277
Errors	278
See Also	278
EnableImportFindingsForProduct	280
Request Syntax	280
URI Request Parameters	280
Request Body	280
Response Syntax	280
Response Elements	281
Errors	281
See Also	282
EnableOrganizationAdminAccount	283
Request Syntax	283
URI Request Parameters	283
Request Body	283
Response Syntax	283

Response Elements	283
Errors	284
See Also	284
EnableSecurityHub	286
Request Syntax	286
URI Request Parameters	286
Request Body	287
Response Syntax	288
Response Elements	288
Errors	288
See Also	289
GetAdministratorAccount	290
Request Syntax	290
URI Request Parameters	290
Request Body	290
Response Syntax	290
Response Elements	290
Errors	291
See Also	291
GetConfigurationPolicy	293
Request Syntax	293
URI Request Parameters	293
Request Body	293
Response Syntax	293
Response Elements	294
Errors	295
See Also	296
GetConfigurationPolicyAssociation	297
Request Syntax	297
URI Request Parameters	297
Request Body	297
Response Syntax	297
Response Elements	298
Errors	299
See Also	300
GetEnabledStandards	301

Request Syntax	301
URI Request Parameters	301
Request Body	301
Response Syntax	302
Response Elements	302
Errors	303
See Also	304
GetFindingAggregator	305
Request Syntax	305
URI Request Parameters	305
Request Body	305
Response Syntax	305
Response Elements	306
Errors	307
See Also	307
GetFindingHistory	309
Request Syntax	309
URI Request Parameters	309
Request Body	309
Response Syntax	311
Response Elements	312
Errors	312
See Also	313
GetFindings	314
Request Syntax	314
URI Request Parameters	330
Request Body	330
Response Syntax	331
Response Elements	429
Errors	429
See Also	430
GetInsightResults	431
Request Syntax	431
URI Request Parameters	431
Request Body	431
Response Syntax	431

Response Elements	432
Errors	432
See Also	433
GetInsights	434
Request Syntax	434
URI Request Parameters	434
Request Body	434
Response Syntax	435
Response Elements	451
Errors	451
See Also	452
GetInvitationsCount	454
Request Syntax	454
URI Request Parameters	454
Request Body	454
Response Syntax	454
Response Elements	454
Errors	455
See Also	455
GetMasterAccount	457
Request Syntax	457
URI Request Parameters	457
Request Body	457
Response Syntax	457
Response Elements	458
Errors	458
See Also	459
GetMembers	460
Request Syntax	460
URI Request Parameters	460
Request Body	460
Response Syntax	460
Response Elements	461
Errors	461
See Also	462
GetSecurityControlDefinition	464

Request Syntax	464
URI Request Parameters	464
Request Body	464
Response Syntax	464
Response Elements	465
Errors	465
See Also	466
InviteMembers	467
Request Syntax	467
URI Request Parameters	467
Request Body	467
Response Syntax	468
Response Elements	468
Errors	468
See Also	469
ListAutomationRules	471
Request Syntax	471
URI Request Parameters	471
Request Body	471
Response Syntax	471
Response Elements	472
Errors	472
See Also	473
ListConfigurationPolicies	474
Request Syntax	474
URI Request Parameters	474
Request Body	474
Response Syntax	475
Response Elements	475
Errors	476
See Also	476
ListConfigurationPolicyAssociations	478
Request Syntax	478
URI Request Parameters	478
Request Body	478
Response Syntax	479

Response Elements	480
Errors	480
See Also	481
ListEnabledProductsForImport	482
Request Syntax	482
URI Request Parameters	482
Request Body	482
Response Syntax	482
Response Elements	483
Errors	483
See Also	484
ListFindingAggregators	485
Request Syntax	485
URI Request Parameters	485
Request Body	485
Response Syntax	485
Response Elements	486
Errors	486
See Also	487
ListInvitations	488
Request Syntax	488
URI Request Parameters	488
Request Body	488
Response Syntax	489
Response Elements	489
Errors	489
See Also	490
ListMembers	492
Request Syntax	492
URI Request Parameters	492
Request Body	492
Response Syntax	493
Response Elements	493
Errors	493
See Also	494
ListOrganizationAdminAccounts	496

Request Syntax	496
URI Request Parameters	496
Request Body	496
Response Syntax	496
Response Elements	497
Errors	497
See Also	498
ListSecurityControlDefinitions	499
Request Syntax	499
URI Request Parameters	499
Request Body	499
Response Syntax	499
Response Elements	500
Errors	500
See Also	501
ListStandardsControlAssociations	503
Request Syntax	503
URI Request Parameters	503
Request Body	504
Response Syntax	504
Response Elements	504
Errors	505
See Also	505
ListTagsForResource	507
Request Syntax	507
URI Request Parameters	507
Request Body	507
Response Syntax	507
Response Elements	507
Errors	508
See Also	508
StartConfigurationPolicyAssociation	510
Request Syntax	510
URI Request Parameters	510
Request Body	510
Response Syntax	511

Response Elements	511
Errors	512
See Also	513
StartConfigurationPolicyDisassociation	515
Request Syntax	515
URI Request Parameters	515
Request Body	515
Response Syntax	516
Response Elements	516
Errors	516
See Also	517
TagResource	518
Request Syntax	518
URI Request Parameters	518
Request Body	518
Response Syntax	519
Response Elements	519
Errors	519
See Also	519
UntagResource	521
Request Syntax	521
URI Request Parameters	521
Request Body	521
Response Syntax	521
Response Elements	522
Errors	522
See Also	522
UpdateActionTarget	524
Request Syntax	524
URI Request Parameters	524
Request Body	524
Response Syntax	525
Response Elements	525
Errors	525
See Also	526
UpdateConfigurationPolicy	527

Request Syntax	527
URI Request Parameters	527
Request Body	527
Response Syntax	529
Response Elements	529
Errors	530
See Also	531
UpdateFindingAggregator	533
Request Syntax	533
URI Request Parameters	533
Request Body	533
Response Syntax	535
Response Elements	535
Errors	536
See Also	537
UpdateFindings	538
Request Syntax	538
URI Request Parameters	554
Request Body	554
Response Syntax	555
Response Elements	555
Errors	555
See Also	556
UpdateInsight	557
Request Syntax	557
URI Request Parameters	573
Request Body	573
Response Syntax	574
Response Elements	574
Errors	574
See Also	575
UpdateOrganizationConfiguration	576
Request Syntax	576
URI Request Parameters	576
Request Body	576
Response Syntax	577

Response Elements	577
Errors	578
See Also	579
UpdateSecurityControl	580
Request Syntax	580
URI Request Parameters	580
Request Body	580
Response Syntax	581
Response Elements	581
Errors	581
See Also	582
UpdateSecurityHubConfiguration	584
Request Syntax	584
URI Request Parameters	584
Request Body	584
Response Syntax	585
Response Elements	585
Errors	585
See Also	586
UpdateStandardsControl	588
Request Syntax	588
URI Request Parameters	588
Request Body	588
Response Syntax	589
Response Elements	589
Errors	589
See Also	590
Data Types	591
Primary data types	617
AccountDetails	623
Action	624
ActionLocalIpDetails	626
ActionLocalPortDetails	627
ActionRemoteIpDetails	628
ActionRemotePortDetails	630
ActionTarget	631

Actor	633
ActorSession	635
ActorUser	637
Adjustment	639
AdminAccount	640
AssociatedStandard	641
AssociationFilters	642
AutomationRulesAction	644
AutomationRulesConfig	645
AutomationRulesFindingFieldsUpdate	648
AutomationRulesFindingFilters	651
AutomationRulesMetadata	661
AwsApiCallAction	664
AwsApiCallActionDomainDetails	667
AwsSecurityFinding	668
AwsSecurityFindingFilters	680
AwsSecurityFindingIdentifier	701
BatchUpdateFindingsUnprocessedFinding	702
BooleanConfigurationOptions	704
BooleanFilter	705
Cell	706
City	708
ClassificationResult	709
ClassificationStatus	711
CodeVulnerabilitiesFilePath	712
Compliance	714
ConfigurationOptions	717
ConfigurationPolicyAssociation	719
ConfigurationPolicyAssociationSummary	720
ConfigurationPolicySummary	722
Country	724
CustomDataIdentifiersDetections	725
CustomDataIdentifiersResult	727
Cvss	728
DataClassificationDetails	730
DateFilter	731

DateRange	733
Detection	734
DnsRequestAction	735
DoubleConfigurationOptions	737
EnumConfigurationOptions	738
EnumListConfigurationOptions	739
FilePaths	741
FindingAggregator	743
FindingHistoryRecord	744
FindingHistoryUpdate	746
FindingHistoryUpdateSource	748
FindingProviderFields	749
FindingProviderSeverity	752
GeneratorDetails	754
GeoLocation	756
IcmpTypeCode	757
ImportFindingsError	758
Indicator	760
Insight	762
InsightResults	764
InsightResultValue	766
IntegerConfigurationOptions	767
IntegerListConfigurationOptions	768
Invitation	770
IpFilter	772
IpOrganizationDetails	773
KeywordFilter	775
Malware	776
MapFilter	778
Member	781
Network	784
NetworkAutonomousSystem	787
NetworkConnection	788
NetworkConnectionAction	789
NetworkEndpoint	791
NetworkGeoLocation	793

NetworkPathComponent	795
NetworkPathComponentDetails	797
Note	798
NoteUpdate	800
NumberFilter	801
Occurrences	803
OrganizationConfiguration	805
Page	807
ParameterConfiguration	808
ParameterDefinition	810
ParameterValue	811
PatchSummary	814
Policy	818
PortProbeAction	819
PortProbeDetail	820
ProcessDetails	821
Product	823
Range	826
Recommendation	827
Record	828
RelatedFinding	829
Remediation	830
Resource	831
ResourceDetails	834
Result	853
SecurityControl	854
SecurityControlCustomParameter	857
SecurityControlDefinition	858
SecurityControlParameter	861
SecurityControlsConfiguration	862
SecurityHubPolicy	864
SensitiveDataDetections	866
SensitiveDataResult	867
Sequence	868
Severity	870
SeverityUpdate	873

Signal	875
SoftwarePackage	879
SortCriterion	882
Standard	883
StandardsControl	885
StandardsControlAssociationDetail	888
StandardsControlAssociationId	891
StandardsControlAssociationSummary	892
StandardsControlAssociationUpdate	895
StandardsManagedBy	897
StandardsStatusReason	898
StandardsSubscription	899
StandardsSubscriptionRequest	902
StatusReason	903
StringConfigurationOptions	904
StringFilter	906
StringListConfigurationOptions	909
Target	911
Threat	913
ThreatIntelIndicator	915
UnprocessedAutomationRule	917
UnprocessedConfigurationPolicyAssociation	919
UnprocessedSecurityControl	921
UnprocessedStandardsControlAssociation	923
UnprocessedStandardsControlAssociationUpdate	925
UpdateAutomationRulesRequestItem	927
UserAccount	930
Vulnerability	931
VulnerabilityCodeVulnerabilities	934
VulnerabilityVendor	936
Workflow	938
WorkflowUpdate	940
ASFF resource objects	941
Amazon MQ objects	962
Amazon API Gateway	977
Amazon AppSync objects	1004

Amazon Athena objects	1017
Amazon Backup	1022
ACM objects	1046
Amazon CloudFormation	1063
Amazon CloudFront	1070
Amazon CloudTrail	1092
Amazon CloudWatch	1096
Amazon CodeBuild	1103
Amazon DMS objects	1125
Amazon DynamoDB	1139
Amazon EC2	1164
Amazon EC2 Auto Scaling	1324
Amazon ECR objects	1351
Amazon ECS objects	1357
Amazon EFS objects	1454
Amazon EKS objects	1462
Amazon Elastic Beanstalk	1470
Amazon ElasticSearch objects	1479
Elastic Load Balancing objects	1496
Amazon EventBridge objects	1524
Amazon GuardDuty objects	1538
Amazon Identity and Access Management (IAM) objects	1552
Amazon Kinesis objects	1582
Amazon KMS objects	1585
Amazon Lambda objects	1589
Amazon MSK objects	1605
Amazon Network Firewall objects	1617
Amazon OpenSearch Service	1658
Amazon RDS objects	1680
Amazon Redshift objects	1749
Amazon Route 53	1784
Amazon S3 objects	1794
Amazon SageMaker AI	1844
Amazon Secrets Manager objects	1852
Amazon SNS objects	1855
Amazon SQS objects	1859

Amazon Systems Manager objects	1861
Amazon Step Functions objects	1868
Amazon WAF objects	1875
Amazon X-Ray objects	1938
Container objects	1940
Common Parameters	1944
Common Errors	1947

Amazon Security Hub API Reference

Amazon Security Hub provides you with a comprehensive view of your security state in Amazon and helps you assess your Amazon environment against security industry standards and best practices.

Security Hub collects security data across Amazon Web Services accounts, Amazon Web Services services, and supported third-party products and helps you analyze your security trends and identify the highest priority security issues.

To help you manage the security state of your organization, Security Hub supports multiple security standards. These include the Amazon Foundational Security Best Practices (FSBP) standard developed by Amazon, and external compliance frameworks such as the Center for Internet Security (CIS), the Payment Card Industry Data Security Standard (PCI DSS), and the National Institute of Standards and Technology (NIST). Each standard includes several security controls, each of which represents a security best practice. Security Hub runs checks against security controls and generates control findings to help you assess your compliance against security best practices.

In addition to generating control findings, Security Hub also receives findings from other Amazon Web Services services, such as Amazon GuardDuty and Amazon Inspector, and supported third-party products. This gives you visibility into a variety of security-related issues. You can also send Security Hub findings to other Amazon Web Services services and supported third-party products.

Security Hub offers automation features that help you triage and remediate security issues. For example, you can use automation rules to automatically update critical findings when a security check fails. You can also leverage the integration with Amazon EventBridge to trigger automatic responses to specific findings.

This guide, the *Amazon Security Hub API Reference*, provides information about the Security Hub API. This includes supported resources, HTTP methods, parameters, and schemas. If you're new to Security Hub, you might find it helpful to also review the [Amazon Security Hub User Guide](#). The user guide explains key concepts and provides procedures that demonstrate how to use Security Hub features. It also provides information about topics such as integrating Security Hub with other Amazon Web Services services. Additional information about the [Amazon Security Finding Format \(ASFF\)](#) is also included in the *Amazon Security Hub User Guide*.

In addition to interacting with Security Hub by making calls to the Security Hub API, you can use a current version of an Amazon command line tool or SDK. Amazon provides tools and SDKs that

consist of libraries and sample code for various languages and platforms, such as PowerShell, Java, Go, Python, C++, and .NET. These tools and SDKs provide convenient, programmatic access to Security Hub and other Amazon Web Services services. They also handle tasks such as signing requests, managing errors, and retrying requests automatically. For information about installing and using the Amazon tools and SDKs, see [Tools to Build on Amazon](#).

Finding Regional endpoints

The Amazon Security Hub API is available in most Amazon Web Services Regions, and it provides an endpoint for each of these Regions. For a list of Regions and endpoints where the API is currently available, see [Amazon Security Hub endpoints and quotas](#) in the *Amazon General Reference*. To learn about managing Amazon Web Services Regions for your Amazon Web Services account, see [Enable or disable Amazon Web Services Regions in your account](#) in the *Amazon Account Management Reference Guide*.

With the exception of operations that are related to central configuration, Security Hub API requests are executed only in the Amazon Web Services Region that's currently active in your Amazon Web Services account or specified in your request. Any changes submitted by a request apply only in that Region. To make the same changes in other Regions, send the request in each additional Region that you want to apply the changes to. When you use central configuration, API requests for configuring Security Hub, standards, and controls are executed in the home Region and all linked Regions. For more information, see [Central configuration](#) in the *Amazon Security Hub User Guide*.

Throttling limits

The following throttling limits apply to Security Hub API operations.

- `BatchEnableStandards` - RateLimit of 1 request per second. BurstLimit of 1 request per second.
- `GetFindings` - RateLimit of 3 requests per second. BurstLimit of 6 requests per second.
- `BatchImportFindings` - RateLimit of 10 requests per second. BurstLimit of 30 requests per second.
- `BatchUpdateFindings` - RateLimit of 10 requests per second. BurstLimit of 30 requests per second.
- `UpdateStandardsControl` - RateLimit of 1 request per second. BurstLimit of 5 requests per second.

- All other operations - RateLimit of 10 requests per second. BurstLimit of 30 requests per second.

Timestamps

In the Security Hub API, timestamp fields can end with Z or ("+" / "-") time-hour [":" time-minute]. The time-secfrac after seconds is limited to a maximum of 9 digits. The offset is bounded by +/-18:00. Here are valid timestamp formats that you can send to Security Hub:

- YYYY-MM-DDTHH:MM:SSZ (for example, 2019-01-31T23:00:00Z)
- YYYY-MM-DDTHH:MM:SS.mmmmmmmmmZ (for example, 2019-01-31T23:00:00.123456789Z)
- YYYY-MM-DDTHH:MM:SS+HH:MM (for example, 2024-01-04T15:25:10+17:59)
- YYYY-MM-DDTHH:MM:SS-HHMM (for example, 2024-01-04T15:25:10-1759)
- YYYY-MM-DDTHH:MM:SS.mmmmmmmmm+HH:MM (for example, 2024-01-04T15:25:10.123456789+17:59)

If a finding provider sends a finding to Security Hub that contains a timestamp in nanoseconds, we round it to milliseconds. For example, we round 2024-10-31T23:00:00.123456789Z to 2024-10-31T23:00:00.123Z.

Actions

The following actions are supported:

- [AcceptAdministratorInvitation](#)
- [AcceptInvitation](#)
- [BatchDeleteAutomationRules](#)
- [BatchDisableStandards](#)
- [BatchEnableStandards](#)
- [BatchGetAutomationRules](#)
- [BatchGetConfigurationPolicyAssociations](#)
- [BatchGetSecurityControls](#)
- [BatchGetStandardsControlAssociations](#)
- [BatchImportFindings](#)
- [BatchUpdateAutomationRules](#)
- [BatchUpdateFindings](#)
- [BatchUpdateStandardsControlAssociations](#)
- [CreateActionTarget](#)
- [CreateAutomationRule](#)
- [CreateConfigurationPolicy](#)
- [CreateFindingAggregator](#)
- [CreateInsight](#)
- [CreateMembers](#)
- [DeclineInvitations](#)
- [DeleteActionTarget](#)
- [DeleteConfigurationPolicy](#)
- [DeleteFindingAggregator](#)
- [DeleteInsight](#)
- [DeleteInvitations](#)
- [DeleteMembers](#)
- [DescribeActionTargets](#)

- [DescribeHub](#)
- [DescribeOrganizationConfiguration](#)
- [DescribeProducts](#)
- [DescribeStandards](#)
- [DescribeStandardsControls](#)
- [DisableImportFindingsForProduct](#)
- [DisableOrganizationAdminAccount](#)
- [DisableSecurityHub](#)
- [DisassociateFromAdministratorAccount](#)
- [DisassociateFromMasterAccount](#)
- [DisassociateMembers](#)
- [EnableImportFindingsForProduct](#)
- [EnableOrganizationAdminAccount](#)
- [EnableSecurityHub](#)
- [GetAdministratorAccount](#)
- [GetConfigurationPolicy](#)
- [GetConfigurationPolicyAssociation](#)
- [GetEnabledStandards](#)
- [GetFindingAggregator](#)
- [GetFindingHistory](#)
- [GetFindings](#)
- [GetInsightResults](#)
- [GetInsights](#)
- [GetInvitationsCount](#)
- [GetMasterAccount](#)
- [GetMembers](#)
- [GetSecurityControlDefinition](#)
- [InviteMembers](#)
- [ListAutomationRules](#)
- [ListConfigurationPolicies](#)

- [ListConfigurationPolicyAssociations](#)
- [ListEnabledProductsForImport](#)
- [ListFindingAggregators](#)
- [ListInvitations](#)
- [ListMembers](#)
- [ListOrganizationAdminAccounts](#)
- [ListSecurityControlDefinitions](#)
- [ListStandardsControlAssociations](#)
- [ListTagsForResource](#)
- [StartConfigurationPolicyAssociation](#)
- [StartConfigurationPolicyDisassociation](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateActionTarget](#)
- [UpdateConfigurationPolicy](#)
- [UpdateFindingAggregator](#)
- [UpdateFindings](#)
- [UpdateInsight](#)
- [UpdateOrganizationConfiguration](#)
- [UpdateSecurityControl](#)
- [UpdateSecurityHubConfiguration](#)
- [UpdateStandardsControl](#)

AcceptAdministratorInvitation

Note

We recommend using Amazon Organizations instead of Security Hub invitations to manage your member accounts. For information, see [Managing Security Hub administrator and member accounts with Organizations](#) in the *Amazon Security Hub User Guide*.

Accepts the invitation to be a member account and be monitored by the Security Hub administrator account that the invitation was sent from.

This operation is only used by member accounts that are not added through Organizations.

When the member account accepts the invitation, permission is granted to the administrator account to view findings generated in the member account.

Request Syntax

```
POST /administrator HTTP/1.1
Content-type: application/json

{
  "AdministratorId": "string",
  "InvitationId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AdministratorId

The account ID of the Security Hub administrator account that sent the invitation.

Type: String

Pattern: .*\\S.*

Required: Yes

InvitationId

The identifier of the invitation sent from the Security Hub administrator account.

Type: String

Pattern: .*\\S.*

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

AcceptInvitation

This method is deprecated. Instead, use `AcceptAdministratorInvitation`.

The Security Hub console continues to use `AcceptInvitation`. It will eventually change to use `AcceptAdministratorInvitation`. Any IAM policies that specifically control access to this function must continue to use `AcceptInvitation`. You should also add `AcceptAdministratorInvitation` to your policies to ensure that the correct permissions are in place after the console begins to use `AcceptAdministratorInvitation`.

Accepts the invitation to be a member account and be monitored by the Security Hub administrator account that the invitation was sent from.

This operation is only used by member accounts that are not added through Organizations.

When the member account accepts the invitation, permission is granted to the administrator account to view findings generated in the member account.

Request Syntax

```
POST /master HTTP/1.1
Content-type: application/json

{
  "InvitationId": "string",
  "MasterId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

InvitationId

The identifier of the invitation sent from the Security Hub administrator account.

Type: String

Pattern: `.*\S.*`

Required: Yes

MasterId

The account ID of the Security Hub administrator account that sent the invitation.

Type: String

Pattern: `.*\S.*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

BatchDeleteAutomationRules

Deletes one or more automation rules.

Request Syntax

```
POST /automationrules/delete HTTP/1.1
Content-type: application/json
```

```
{
  "AutomationRulesArns": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[AutomationRulesArns](#)

A list of Amazon Resource Names (ARNs) for the rules that are to be deleted.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Pattern: `.*\S.*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "ProcessedAutomationRules": [ "string" ],
  "UnprocessedAutomationRules": [
```

```
{
  "ErrorCode": number,
  "ErrorMessage": "string",
  "RuleArn": "string"
}
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ProcessedAutomationRules

A list of properly processed rule ARNs.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Pattern: `.*\S.*`

UnprocessedAutomationRules

A list of objects containing `RuleArn`, `ErrorCode`, and `ErrorMessage`. This parameter tells you which automation rules the request didn't delete and why.

Type: Array of [UnprocessedAutomationRule](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

BatchDisableStandards

Disables the standards specified by the provided StandardsSubscriptionArns.

For more information, see [Security Standards](#) section of the *Amazon Security Hub User Guide*.

Request Syntax

```
POST /standards/deregister HTTP/1.1
Content-type: application/json

{
  "StandardsSubscriptionArns": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[StandardsSubscriptionArns](#)

The ARNs of the standards subscriptions to disable.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Pattern: `.*\S.*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"StandardsSubscriptions": [  
  {  
    "StandardsArn": "string",  
    "StandardsControlsUpdatable": "string",  
    "StandardsInput": {  
      "string" : "string"  
    },  
    "StandardsStatus": "string",  
    "StandardsStatusReason": {  
      "StatusReasonCode": "string"  
    },  
    "StandardsSubscriptionArn": "string"  
  }  
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

StandardsSubscriptions

The details of the standards subscriptions that were disabled.

Type: Array of [StandardsSubscription](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

BatchEnableStandards

Enables the standards specified by the provided `StandardsArn`. To obtain the ARN for a standard, use the `DescribeStandards` operation.

For more information, see the [Security Standards](#) section of the *Amazon Security Hub User Guide*.

Request Syntax

```
POST /standards/register HTTP/1.1
Content-type: application/json

{
  "StandardsSubscriptionRequests": [
    {
      "StandardsArn": "string",
      "StandardsInput": {
        "string" : "string"
      }
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[StandardsSubscriptionRequests](#)

The list of standards checks to enable.

Type: Array of [StandardsSubscriptionRequest](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "StandardsSubscriptions": [
    {
      "StandardsArn": "string",
      "StandardsControlsUpdatable": "string",
      "StandardsInput": {
        "string" : "string"
      },
      "StandardsStatus": "string",
      "StandardsStatusReason": {
        "StatusReasonCode": "string"
      },
      "StandardsSubscriptionArn": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

StandardsSubscriptions

The details of the standards subscriptions that were enabled.

Type: Array of [StandardsSubscription](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)

- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

BatchGetAutomationRules

Retrieves a list of details for automation rules based on rule Amazon Resource Names (ARNs).

Request Syntax

```
POST /automationrules/get HTTP/1.1
Content-type: application/json

{
  "AutomationRulesArns": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AutomationRulesArns

A list of rule ARNs to get details for.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Pattern: `.*\S.*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Rules": [
    {
      "Actions": [
```

```
{
  "FindingFieldsUpdate": {
    "Confidence": number,
    "Criticality": number,
    "Note": {
      "Text": "string",
      "UpdatedBy": "string"
    },
    "RelatedFindings": [
      {
        "Id": "string",
        "ProductArn": "string"
      }
    ],
    "Severity": {
      "Label": "string",
      "Normalized": number,
      "Product": number
    },
    "Types": [ "string " ],
    "UserDefinedFields": {
      "string": "string"
    },
    "VerificationState": "string",
    "Workflow": {
      "Status": "string"
    }
  },
  "Type": "string"
}
],
"CreatedAt": "string",
"CreatedBy": "string",
"Criteria": {
  "AwsAccountId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "AwsAccountName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ]
}
```

```
    }
  ],
  "CompanyName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ComplianceAssociatedStandardsId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ComplianceSecurityControlId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ComplianceStatus": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Confidence": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "CreatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ]
}
```

```
],
  "Criticality": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "Description": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "FirstObservedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "GeneratorId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Id": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "LastObservedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
    },
  ],
```



```
        "End": "string",
        "Start": "string"
    }
],
"NoteText": [
    {
        "Comparison": "string",
        "Value": "string"
    }
],
"NoteUpdatedAt": [
    {
        "DateRange": {
            "Unit": "string",
            "Value": number
        },
        "End": "string",
        "Start": "string"
    }
],
"NoteUpdatedBy": [
    {
        "Comparison": "string",
        "Value": "string"
    }
],
"ProductArn": [
    {
        "Comparison": "string",
        "Value": "string"
    }
],
"ProductName": [
    {
        "Comparison": "string",
        "Value": "string"
    }
],
"RecordState": [
    {
        "Comparison": "string",
        "Value": "string"
    }
],
]
```



```
{
  "Comparison": "string",
  "Value": "string"
},
"ResourceTags": [
  {
    "Comparison": "string",
    "Key": "string",
    "Value": "string"
  }
],
"ResourceType": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"SeverityLabel": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"SourceUrl": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"Title": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"Type": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"UpdatedAt": [
  {
```

```
        "DateRange": {
            "Unit": "string",
            "Value": number
        },
        "End": "string",
        "Start": "string"
    }
],
"UserDefinedFields": [
    {
        "Comparison": "string",
        "Key": "string",
        "Value": "string"
    }
],
"VerificationState": [
    {
        "Comparison": "string",
        "Value": "string"
    }
],
"WorkflowStatus": [
    {
        "Comparison": "string",
        "Value": "string"
    }
]
],
"Description": "string",
"IsTerminal": boolean,
"RuleArn": "string",
"RuleName": "string",
"RuleOrder": number,
"RuleStatus": "string",
"UpdatedAt": "string"
}
],
"UnprocessedAutomationRules": [
    {
        "ErrorCode": number,
        "ErrorMessage": "string",
        "RuleArn": "string"
    }
]
]
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Rules

A list of rule details for the provided rule ARNs.

Type: Array of [AutomationRulesConfig](#) objects

UnprocessedAutomationRules

A list of objects containing `RuleArn`, `ErrorCode`, and `ErrorMessage`. This parameter tells you which automation rules the request didn't retrieve and why.

Type: Array of [UnprocessedAutomationRule](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

BatchGetConfigurationPolicyAssociations

Returns associations between an Amazon Security Hub configuration and a batch of target accounts, organizational units, or the root. Only the Security Hub delegated administrator can invoke this operation from the home Region. A configuration can refer to a configuration policy or to a self-managed configuration.

Request Syntax

```
POST /configurationPolicyAssociation/batchget HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "ConfigurationPolicyAssociationIdentifiers": [
    {
      "Target": { ... }
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[ConfigurationPolicyAssociationIdentifiers](#)

Specifies one or more target account IDs, organizational unit (OU) IDs, or the root ID to retrieve associations for.

Type: Array of [ConfigurationPolicyAssociation](#) objects

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "ConfigurationPolicyAssociations": [
    {
      "AssociationStatus": "string",
      "AssociationStatusMessage": "string",
      "AssociationType": "string",
      "ConfigurationPolicyId": "string",
      "TargetId": "string",
      "TargetType": "string",
      "UpdatedAt": "string"
    }
  ],
  "UnprocessedConfigurationPolicyAssociations": [
    {
      "ConfigurationPolicyAssociationIdentifiers": {
        "Target": { ... }
      },
      "ErrorCode": "string",
      "ErrorReason": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ConfigurationPolicyAssociations

Describes associations for the target accounts, OUs, or the root.

Type: Array of [ConfigurationPolicyAssociationSummary](#) objects

UnprocessedConfigurationPolicyAssociations

An array of configuration policy associations, one for each configuration policy association identifier, that was specified in the request but couldn't be processed due to an error.

Type: Array of [UnprocessedConfigurationPolicyAssociation](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

BatchGetSecurityControls

Provides details about a batch of security controls for the current Amazon Web Services account and Amazon Web Services Region.

Request Syntax

```
POST /securityControls/batchGet HTTP/1.1
Content-type: application/json

{
  "SecurityControlIds": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

SecurityControlIds

A list of security controls (identified with `SecurityControlId`, `SecurityControlArn`, or a mix of both parameters). The security control ID or Amazon Resource Name (ARN) is the same across standards.

Type: Array of strings

Pattern: `.*\S.*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "SecurityControls": [
    {
      "Description": "string",
      "LastUpdateReason": "string",
      "Parameters": {
        "string": {
          "Value": { ... },
          "ValueType": "string"
        }
      },
      "RemediationUrl": "string",
      "SecurityControlArn": "string",
      "SecurityControlId": "string",
      "SecurityControlStatus": "string",
      "SeverityRating": "string",
      "Title": "string",
      "UpdateStatus": "string"
    }
  ],
  "UnprocessedIds": [
    {
      "ErrorCode": "string",
      "ErrorReason": "string",
      "SecurityControlId": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

SecurityControls

An array that returns the identifier, Amazon Resource Name (ARN), and other details about a security control. The same information is returned whether the request includes `SecurityControlId` or `SecurityControlArn`.

Type: Array of [SecurityControl](#) objects

UnprocessedIds

A security control (identified with `SecurityControlId`, `SecurityControlArn`, or a mix of both parameters) for which details cannot be returned.

Type: Array of [UnprocessedSecurityControl](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

BatchGetStandardsControlAssociations

For a batch of security controls and standards, identifies whether each control is currently enabled or disabled in a standard.

Calls to this operation return a `RESOURCE_NOT_FOUND_EXCEPTION` error when the standard subscription for the association has a `NOT_READY_FOR_UPDATES` value for `StandardsControlsUpdatable`.

Request Syntax

```
POST /associations/batchGet HTTP/1.1
Content-type: application/json
```

```
{
  "StandardsControlAssociationIds": [
    {
      "SecurityControlId": "string",
      "StandardsArn": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

StandardsControlAssociationIds

An array with one or more objects that includes a security control (identified with `SecurityControlId`, `SecurityControlArn`, or a mix of both parameters) and the Amazon Resource Name (ARN) of a standard. This field is used to query the enablement status of a control in a specified standard. The security control ID or ARN is the same across standards.

Type: Array of [StandardsControlAssociationId](#) objects

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "StandardsControlAssociationDetails": [
    {
      "AssociationStatus": "string",
      "RelatedRequirements": [ "string" ],
      "SecurityControlArn": "string",
      "SecurityControlId": "string",
      "StandardsArn": "string",
      "StandardsControlArns": [ "string" ],
      "StandardsControlDescription": "string",
      "StandardsControlTitle": "string",
      "UpdatedAt": "string",
      "UpdatedReason": "string"
    }
  ],
  "UnprocessedAssociations": [
    {
      "ErrorCode": "string",
      "ErrorReason": "string",
      "StandardsControlAssociationId": {
        "SecurityControlId": "string",
        "StandardsArn": "string"
      }
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

StandardsControlAssociationDetails

Provides the enablement status of a security control in a specified standard and other details for the control in relation to the specified standard.

Type: Array of [StandardsControlAssociationDetail](#) objects

UnprocessedAssociations

A security control (identified with `SecurityControlId`, `SecurityControlArn`, or a mix of both parameters) whose enablement status in a specified standard cannot be returned.

Type: Array of [UnprocessedStandardsControlAssociation](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

BatchImportFindings

Imports security findings generated by a finding provider into Security Hub. This action is requested by the finding provider to import its findings into Security Hub.

BatchImportFindings must be called by one of the following:

- The Amazon Web Services account that is associated with a finding if you are using the [default product ARN](#) or are a partner sending findings from within a customer's Amazon Web Services account. In these cases, the identifier of the account that you are calling BatchImportFindings from needs to be the same as the `AwsAccountId` attribute for the finding.
- An Amazon Web Services account that Security Hub has allow-listed for an official partner integration. In this case, you can call BatchImportFindings from the allow-listed account and send findings from different customer accounts in the same batch.

The maximum allowed size for a finding is 240 Kb. An error is returned for any finding larger than 240 Kb.

After a finding is created, BatchImportFindings cannot be used to update the following finding fields and objects, which Security Hub customers use to manage their investigation workflow.

- Note
- UserDefinedFields
- VerificationState
- Workflow

Finding providers also should not use BatchImportFindings to update the following attributes.

- Confidence
- Criticality
- RelatedFindings
- Severity
- Types

Instead, finding providers use `FindingProviderFields` to provide values for these attributes.

Request Syntax

```
POST /findings/import HTTP/1.1
Content-type: application/json
```

```
{
  "Findings": [
    {
      "Action": {
        "ActionType": "string",
        "AwsApiCallAction": {
          "AffectedResources": {
            "string": "string"
          },
          "Api": "string",
          "CallerType": "string",
          "DomainDetails": {
            "Domain": "string"
          },
          "FirstSeen": "string",
          "LastSeen": "string",
          "RemoteIpDetails": {
            "City": {
              "CityName": "string"
            },
            "Country": {
              "CountryCode": "string",
              "CountryName": "string"
            },
            "GeoLocation": {
              "Lat": number,
              "Lon": number
            },
            "IpAddressV4": "string",
            "Organization": {
              "Asn": number,
              "AsnOrg": "string",
              "Isp": "string",
              "Org": "string"
            }
          },
          "ServiceName": "string"
        }
      }
    }
  ]
}
```

```
"DnsRequestAction": {
  "Blocked": boolean,
  "Domain": "string",
  "Protocol": "string"
},
"NetworkConnectionAction": {
  "Blocked": boolean,
  "ConnectionDirection": "string",
  "LocalPortDetails": {
    "Port": number,
    "PortName": "string"
  },
  "Protocol": "string",
  "RemoteIpDetails": {
    "City": {
      "CityName": "string"
    },
    "Country": {
      "CountryCode": "string",
      "CountryName": "string"
    },
    "GeoLocation": {
      "Lat": number,
      "Lon": number
    },
    "IpAddressV4": "string",
    "Organization": {
      "Asn": number,
      "AsnOrg": "string",
      "Isp": "string",
      "Org": "string"
    }
  },
  "RemotePortDetails": {
    "Port": number,
    "PortName": "string"
  }
},
"PortProbeAction": {
  "Blocked": boolean,
  "PortProbeDetails": [
    {
      "LocalIpDetails": {
        "IpAddressV4": "string"
      }
    }
  ]
}
```

```

    },
    "LocalPortDetails": {
      "Port": number,
      "PortName": "string"
    },
    "RemoteIpDetails": {
      "City": {
        "CityName": "string"
      },
      "Country": {
        "CountryCode": "string",
        "CountryName": "string"
      },
      "GeoLocation": {
        "Lat": number,
        "Lon": number
      },
      "IpAddressV4": "string",
      "Organization": {
        "Asn": number,
        "AsnOrg": "string",
        "Isp": "string",
        "Org": "string"
      }
    }
  }
]
}
},
"AwsAccountId": "string",
"AwsAccountName": "string",
"CompanyName": "string",
"Compliance": {
  "AssociatedStandards": [
    {
      "StandardsId": "string"
    }
  ],
  "RelatedRequirements": [ "string" ],
  "SecurityControlId": "string",
  "SecurityControlParameters": [
    {
      "Name": "string",
      "Value": [ "string" ]
    }
  ]
}

```

```
    }
  ],
  "Status": "string",
  "StatusReasons": [
    {
      "Description": "string",
      "ReasonCode": "string"
    }
  ]
},
"Confidence": number,
"CreatedAt": "string",
"Criticality": number,
"Description": "string",
"Detection": {
  "Sequence": {
    "Actors": [
      {
        "Id": "string",
        "Session": {
          "CreatedTime": number,
          "Issuer": "string",
          "MfaStatus": "string",
          "Uid": "string"
        },
        "User": {
          "Account": {
            "Name": "string",
            "Uid": "string"
          },
          "CredentialUid": "string",
          "Name": "string",
          "Type": "string",
          "Uid": "string"
        }
      }
    ]
  },
  "Endpoints": [
    {
      "AutonomousSystem": {
        "Name": "string",
        "Number": number
      },
      "Connection": {
```

```
        "Direction": "string"
    },
    "Domain": "string",
    "Id": "string",
    "Ip": "string",
    "Location": {
        "City": "string",
        "Country": "string",
        "Lat": number,
        "Lon": number
    },
    "Port": number
}
],
"SequenceIndicators": [
    {
        "Key": "string",
        "Title": "string",
        "Type": "string",
        "Values": [ "string" ]
    }
],
"Signals": [
    {
        "ActorIds": [ "string" ],
        "Count": number,
        "CreatedAt": number,
        "EndpointIds": [ "string" ],
        "FirstSeenAt": number,
        "Id": "string",
        "LastSeenAt": number,
        "Name": "string",
        "ProductArn": "string",
        "ResourceIds": [ "string" ],
        "Severity": number,
        "SignalIndicators": [
            {
                "Key": "string",
                "Title": "string",
                "Type": "string",
                "Values": [ "string" ]
            }
        ],
        "Title": "string",
```



```
        "Type": "string",
        "UpdatedAt": number
      }
    ],
    "Uid": "string"
  }
},
"FindingProviderFields": {
  "Confidence": number,
  "Criticality": number,
  "RelatedFindings": [
    {
      "Id": "string",
      "ProductArn": "string"
    }
  ],
  "Severity": {
    "Label": "string",
    "Original": "string"
  },
  "Types": [ "string" ]
},
"FirstObservedAt": "string",
"GeneratorDetails": {
  "Description": "string",
  "Labels": [ "string" ],
  "Name": "string"
},
"GeneratorId": "string",
"Id": "string",
"LastObservedAt": "string",
"Malware": [
  {
    "Name": "string",
    "Path": "string",
    "State": "string",
    "Type": "string"
  }
],
"Network": {
  "DestinationDomain": "string",
  "DestinationIPv4": "string",
  "DestinationIPv6": "string",
  "DestinationPort": number,

```

```
"Direction": "string",
"OpenPortRange": {
  "Begin": number,
  "End": number
},
"Protocol": "string",
"SourceDomain": "string",
"SourceIpV4": "string",
"SourceIpV6": "string",
"SourceMac": "string",
"SourcePort": number
},
"NetworkPath": [
  {
    "ComponentId": "string",
    "ComponentType": "string",
    "Egress": {
      "Destination": {
        "Address": [ "string" ],
        "PortRanges": [
          {
            "Begin": number,
            "End": number
          }
        ]
      },
      "Protocol": "string",
      "Source": {
        "Address": [ "string" ],
        "PortRanges": [
          {
            "Begin": number,
            "End": number
          }
        ]
      }
    }
  },
  {
    "Ingress": {
      "Destination": {
        "Address": [ "string" ],
        "PortRanges": [
          {
            "Begin": number,
            "End": number
          }
        ]
      }
    }
  }
]
```

```

    }
  ]
},
"Protocol": "string",
"Source": {
  "Address": [ "string" ],
  "PortRanges": [
    {
      "Begin": number,
      "End": number
    }
  ]
}
}
],
"Note": {
  "Text": "string",
  "UpdatedAt": "string",
  "UpdatedBy": "string"
},
"PatchSummary": {
  "FailedCount": number,
  "Id": "string",
  "InstalledCount": number,
  "InstalledOtherCount": number,
  "InstalledPendingReboot": number,
  "InstalledRejectedCount": number,
  "MissingCount": number,
  "Operation": "string",
  "OperationEndTime": "string",
  "OperationStartTime": "string",
  "RebootOption": "string"
},
"Process": {
  "LaunchedAt": "string",
  "Name": "string",
  "ParentPid": number,
  "Path": "string",
  "Pid": number,
  "TerminatedAt": "string"
},
"ProcessedAt": "string",
"ProductArn": "string",

```

```
"ProductFields": {
  "string" : "string"
},
"ProductName": "string",
"RecordState": "string",
"Region": "string",
"RelatedFindings": [
  {
    "Id": "string",
    "ProductArn": "string"
  }
],
"Remediation": {
  "Recommendation": {
    "Text": "string",
    "Url": "string"
  }
},
"Resources": [
  {
    "ApplicationArn": "string",
    "ApplicationName": "string",
    "DataClassification": {
      "DetailedResultsLocation": "string",
      "Result": {
        "AdditionalOccurrences": boolean,
        "CustomDataIdentifiers": {
          "Detections": [
            {
              "Arn": "string",
              "Count": number,
              "Name": "string",
              "Occurrences": {
                "Cells": [
                  {
                    "CellReference": "string",
                    "Column": number,
                    "ColumnName": "string",
                    "Row": number
                  }
                ]
              }
            }
          ],
          "LineRanges": [
            {
              "End": number,
```

```
        "Start": number,
        "StartColumn": number
    }
],
"OffsetRanges": [
    {
        "End": number,
        "Start": number,
        "StartColumn": number
    }
],
"Pages": [
    {
        "LineRange": {
            "End": number,
            "Start": number,
            "StartColumn": number
        },
        "OffsetRange": {
            "End": number,
            "Start": number,
            "StartColumn": number
        },
        "PageNumber": number
    }
],
"Records": [
    {
        "JsonPath": "string",
        "RecordIndex": number
    }
]
}
},
"TotalCount": number
},
"MimeType": "string",
"SensitiveData": [
    {
        "Category": "string",
        "Detections": [
            {
                "Count": number,
```

```
"Occurrences": {
  "Cells": [
    {
      "CellReference": "string",
      "Column": number,
      "ColumnName": "string",
      "Row": number
    }
  ],
  "LineRanges": [
    {
      "End": number,
      "Start": number,
      "StartColumn": number
    }
  ],
  "OffsetRanges": [
    {
      "End": number,
      "Start": number,
      "StartColumn": number
    }
  ],
  "Pages": [
    {
      "LineRange": {
        "End": number,
        "Start": number,
        "StartColumn": number
      },
      "OffsetRange": {
        "End": number,
        "Start": number,
        "StartColumn": number
      },
      "PageNumber": number
    }
  ],
  "Records": [
    {
      "JsonPath": "string",
      "RecordIndex": number
    }
  ]
}
```

```

        },
        "Type": "string"
    }
],
"TotalCount": number
}
],
"SizeClassified": number,
"Status": {
    "Code": "string",
    "Reason": "string"
}
}
},
"Details": {
    "AwsAmazonMqBroker": {
        "AuthenticationStrategy": "string",
        "AutoMinorVersionUpgrade": boolean,
        "BrokerArn": "string",
        "BrokerId": "string",
        "BrokerName": "string",
        "DeploymentMode": "string",
        "EncryptionOptions": {
            "KmsKeyId": "string",
            "UseAwsOwnedKey": boolean
        },
        "EngineType": "string",
        "EngineVersion": "string",
        "HostInstanceType": "string",
        "LdapServerMetadata": {
            "Hosts": [ "string" ],
            "RoleBase": "string",
            "RoleName": "string",
            "RoleSearchMatching": "string",
            "RoleSearchSubtree": boolean,
            "ServiceAccountUsername": "string",
            "UserBase": "string",
            "UserRoleName": "string",
            "UserSearchMatching": "string",
            "UserSearchSubtree": boolean
        },
        "Logs": {
            "Audit": boolean,
            "AuditLogGroup": "string",

```

```

    "General": boolean,
    "GeneralLogGroup": "string",
    "Pending": {
        "Audit": boolean,
        "General": boolean
    }
},
"MaintenanceWindowStartTime": {
    "DayOfWeek": "string",
    "TimeOfDay": "string",
    "TimeZone": "string"
},
"PubliclyAccessible": boolean,
"SecurityGroups": [ "string" ],
"StorageType": "string",
"SubnetIds": [ "string" ],
"Users": [
    {
        "PendingChange": "string",
        "Username": "string"
    }
]
},
"AwsApiGatewayRestApi": {
    "ApiKeySource": "string",
    "BinaryMediaTypes": [ "string" ],
    "CreateDate": "string",
    "Description": "string",
    "EndpointConfiguration": {
        "Types": [ "string" ]
    },
    "Id": "string",
    "MinimumCompressionSize": number,
    "Name": "string",
    "Version": "string"
},
"AwsApiGatewayStage": {
    "AccessLogSettings": {
        "DestinationArn": "string",
        "Format": "string"
    },
    "CacheClusterEnabled": boolean,
    "CacheClusterSize": "string",
    "CacheClusterStatus": "string",

```



```
"CanarySettings": {
  "DeploymentId": "string",
  "PercentTraffic": number,
  "StageVariableOverrides": {
    "string" : "string"
  },
  "UseStageCache": boolean
},
"ClientCertificateId": "string",
"CreatedDate": "string",
"DeploymentId": "string",
"Description": "string",
"DocumentationVersion": "string",
"LastUpdatedDate": "string",
"MethodSettings": [
  {
    "CacheDataEncrypted": boolean,
    "CacheTtlInSeconds": number,
    "CachingEnabled": boolean,
    "DataTraceEnabled": boolean,
    "HttpMethod": "string",
    "LoggingLevel": "string",
    "MetricsEnabled": boolean,
    "RequireAuthorizationForCacheControl": boolean,
    "ResourcePath": "string",
    "ThrottlingBurstLimit": number,
    "ThrottlingRateLimit": number,
    "UnauthorizedCacheControlHeaderStrategy": "string"
  }
],
"StageName": "string",
"TracingEnabled": boolean,
"Variables": {
  "string" : "string"
},
"WebAclArn": "string"
},
"AwsApiGatewayV2Api": {
  "ApiEndpoint": "string",
  "ApiId": "string",
  "ApiKeySelectionExpression": "string",
  "CorsConfiguration": {
    "AllowCredentials": boolean,
    "AllowHeaders": [ "string" ],
```

```
    "AllowMethods": [ "string" ],
    "AllowOrigins": [ "string" ],
    "ExposeHeaders": [ "string" ],
    "MaxAge": number
  },
  "CreateDate": "string",
  "Description": "string",
  "Name": "string",
  "ProtocolType": "string",
  "RouteSelectionExpression": "string",
  "Version": "string"
},
"AwsApiGatewayV2Stage": {
  "AccessLogSettings": {
    "DestinationArn": "string",
    "Format": "string"
  },
  "ApiGatewayManaged": boolean,
  "AutoDeploy": boolean,
  "ClientCertificateId": "string",
  "CreateDate": "string",
  "DefaultRouteSettings": {
    "DataTraceEnabled": boolean,
    "DetailedMetricsEnabled": boolean,
    "LoggingLevel": "string",
    "ThrottlingBurstLimit": number,
    "ThrottlingRateLimit": number
  },
  "DeploymentId": "string",
  "Description": "string",
  "LastDeploymentStatusMessage": "string",
  "LastUpdatedDate": "string",
  "RouteSettings": {
    "DataTraceEnabled": boolean,
    "DetailedMetricsEnabled": boolean,
    "LoggingLevel": "string",
    "ThrottlingBurstLimit": number,
    "ThrottlingRateLimit": number
  },
  "StageName": "string",
  "StageVariables": {
    "string" : "string"
  }
},
```

```

"AwsAppSyncGraphQLApi": {
  "AdditionalAuthenticationProviders": [
    {
      "AuthenticationType": "string",
      "LambdaAuthorizerConfig": {
        "AuthorizerResultTtlInSeconds": number,
        "AuthorizerUri": "string",
        "IdentityValidationExpression": "string"
      },
      "OpenIdConnectConfig": {
        "AuthTtl": number,
        "ClientId": "string",
        "IatTtl": number,
        "Issuer": "string"
      },
      "UserPoolConfig": {
        "AppIdClientRegex": "string",
        "AwsRegion": "string",
        "DefaultAction": "string",
        "UserPoolId": "string"
      }
    }
  ],
  "ApiId": "string",
  "Arn": "string",
  "AuthenticationType": "string",
  "Id": "string",
  "LambdaAuthorizerConfig": {
    "AuthorizerResultTtlInSeconds": number,
    "AuthorizerUri": "string",
    "IdentityValidationExpression": "string"
  },
  "LogConfig": {
    "CloudWatchLogsRoleArn": "string",
    "ExcludeVerboseContent": boolean,
    "FieldLogLevel": "string"
  },
  "Name": "string",
  "OpenIdConnectConfig": {
    "AuthTtl": number,
    "ClientId": "string",
    "IatTtl": number,
    "Issuer": "string"
  },
}

```

```
"UserPoolConfig": {
  "AppIdClientRegex": "string",
  "AwsRegion": "string",
  "DefaultAction": "string",
  "UserPoolId": "string"
},
"WafWebAclArn": "string",
"XrayEnabled": boolean
},
"AwsAthenaWorkGroup": {
  "Configuration": {
    "ResultConfiguration": {
      "EncryptionConfiguration": {
        "EncryptionOption": "string",
        "KmsKey": "string"
      }
    }
  },
  "Description": "string",
  "Name": "string",
  "State": "string"
},
"AwsAutoScalingAutoScalingGroup": {
  "AvailabilityZones": [
    {
      "Value": "string"
    }
  ],
  "CapacityRebalance": boolean,
  "CreatedTime": "string",
  "HealthCheckGracePeriod": number,
  "HealthCheckType": "string",
  "LaunchConfigurationName": "string",
  "LaunchTemplate": {
    "LaunchTemplateId": "string",
    "LaunchTemplateName": "string",
    "Version": "string"
  },
  "LoadBalancerNames": [ "string" ],
  "MixedInstancesPolicy": {
    "InstancesDistribution": {
      "OnDemandAllocationStrategy": "string",
      "OnDemandBaseCapacity": number,
      "OnDemandPercentageAboveBaseCapacity": number,
```

```
    "SpotAllocationStrategy": "string",
    "SpotInstancePools": number,
    "SpotMaxPrice": "string"
  },
  "LaunchTemplate": {
    "LaunchTemplateSpecification": {
      "LaunchTemplateId": "string",
      "LaunchTemplateName": "string",
      "Version": "string"
    },
    "Overrides": [
      {
        "InstanceType": "string",
        "WeightedCapacity": "string"
      }
    ]
  }
},
"AwsAutoScalingLaunchConfiguration": {
  "AssociatePublicIpAddress": boolean,
  "BlockDeviceMappings": [
    {
      "DeviceName": "string",
      "Ebs": {
        "DeleteOnTermination": boolean,
        "Encrypted": boolean,
        "Iops": number,
        "SnapshotId": "string",
        "VolumeSize": number,
        "VolumeType": "string"
      },
      "NoDevice": boolean,
      "VirtualName": "string"
    }
  ],
  "ClassicLinkVpcId": "string",
  "ClassicLinkVpcSecurityGroups": [ "string" ],
  "CreatedTime": "string",
  "EbsOptimized": boolean,
  "IamInstanceProfile": "string",
  "ImageId": "string",
  "InstanceMonitoring": {
    "Enabled": boolean
  }
}
```

```

    },
    "InstanceType": "string",
    "KernelId": "string",
    "KeyName": "string",
    "LaunchConfigurationName": "string",
    "MetadataOptions": {
      "HttpEndpoint": "string",
      "HttpPutResponseHopLimit": number,
      "HttpTokens": "string"
    },
    "PlacementTenancy": "string",
    "RamdiskId": "string",
    "SecurityGroups": [ "string" ],
    "SpotPrice": "string",
    "UserData": "string"
  },
  "AwsBackupBackupPlan": {
    "BackupPlan": {
      "AdvancedBackupSettings": [
        {
          "BackupOptions": {
            "string": "string"
          },
          "ResourceType": "string"
        }
      ],
      "BackupPlanName": "string",
      "BackupPlanRule": [
        {
          "CompletionWindowMinutes": number,
          "CopyActions": [
            {
              "DestinationBackupVaultArn": "string",
              "Lifecycle": {
                "DeleteAfterDays": number,
                "MoveToColdStorageAfterDays": number
              }
            }
          ]
        }
      ],
      "EnableContinuousBackup": boolean,
      "Lifecycle": {
        "DeleteAfterDays": number,
        "MoveToColdStorageAfterDays": number
      }
    },
  },

```

```

        "RuleId": "string",
        "RuleName": "string",
        "ScheduleExpression": "string",
        "StartWindowMinutes": number,
        "TargetBackupVault": "string"
    }
]
},
"BackupPlanArn": "string",
"BackupPlanId": "string",
"VersionId": "string"
},
"AwsBackupBackupVault": {
    "AccessPolicy": "string",
    "BackupVaultArn": "string",
    "BackupVaultName": "string",
    "EncryptionKeyArn": "string",
    "Notifications": {
        "BackupVaultEvents": [ "string" ],
        "SnsTopicArn": "string"
    }
},
"AwsBackupRecoveryPoint": {
    "BackupSizeInBytes": number,
    "BackupVaultArn": "string",
    "BackupVaultName": "string",
    "CalculatedLifecycle": {
        "DeleteAt": "string",
        "MoveToColdStorageAt": "string"
    },
    "CompletionDate": "string",
    "CreatedBy": {
        "BackupPlanArn": "string",
        "BackupPlanId": "string",
        "BackupPlanVersion": "string",
        "BackupRuleId": "string"
    },
    "CreationDate": "string",
    "EncryptionKeyArn": "string",
    "IamRoleArn": "string",
    "IsEncrypted": boolean,
    "LastRestoreTime": "string",
    "Lifecycle": {
        "DeleteAfterDays": number,

```

```
    "MoveToColdStorageAfterDays": number
  },
  "RecoveryPointArn": "string",
  "ResourceArn": "string",
  "ResourceType": "string",
  "SourceBackupVaultArn": "string",
  "Status": "string",
  "StatusMessage": "string",
  "StorageClass": "string"
},
"AwsCertificateManagerCertificate": {
  "CertificateAuthorityArn": "string",
  "CreatedAt": "string",
  "DomainName": "string",
  "DomainValidationOptions": [
    {
      "DomainName": "string",
      "ResourceRecord": {
        "Name": "string",
        "Type": "string",
        "Value": "string"
      },
      "ValidationDomain": "string",
      "ValidationEmails": [ "string" ],
      "ValidationMethod": "string",
      "ValidationStatus": "string"
    }
  ],
  "ExtendedKeyUsages": [
    {
      "Name": "string",
      "OId": "string"
    }
  ],
  "FailureReason": "string",
  "ImportedAt": "string",
  "InUseBy": [ "string" ],
  "IssuedAt": "string",
  "Issuer": "string",
  "KeyAlgorithm": "string",
  "KeyUsages": [
    {
      "Name": "string"
    }
  ]
}
```



```
    ],
    "NotAfter": "string",
    "NotBefore": "string",
    "Options": {
      "CertificateTransparencyLoggingPreference": "string"
    },
    "RenewalEligibility": "string",
    "RenewalSummary": {
      "DomainValidationOptions": [
        {
          "DomainName": "string",
          "ResourceRecord": {
            "Name": "string",
            "Type": "string",
            "Value": "string"
          },
          "ValidationDomain": "string",
          "ValidationEmails": [ "string" ],
          "ValidationMethod": "string",
          "ValidationStatus": "string"
        }
      ],
      "RenewalStatus": "string",
      "RenewalStatusReason": "string",
      "UpdatedAt": "string"
    },
    "Serial": "string",
    "SignatureAlgorithm": "string",
    "Status": "string",
    "Subject": "string",
    "SubjectAlternativeNames": [ "string" ],
    "Type": "string"
  },
  "AwsCloudFormationStack": {
    "Capabilities": [ "string" ],
    "CreationTime": "string",
    "Description": "string",
    "DisableRollback": boolean,
    "DriftInformation": {
      "StackDriftStatus": "string"
    },
    "EnableTerminationProtection": boolean,
    "LastUpdatedTime": "string",
    "NotificationArns": [ "string" ],
```

```
"Outputs": [
  {
    "Description": "string",
    "OutputKey": "string",
    "OutputValue": "string"
  }
],
"RoleArn": "string",
"StackId": "string",
"StackName": "string",
"StackStatus": "string",
"StackStatusReason": "string",
"TimeoutInMinutes": number
},
"AwsCloudFrontDistribution": {
  "CacheBehaviors": {
    "Items": [
      {
        "ViewerProtocolPolicy": "string"
      }
    ]
  },
  "DefaultCacheBehavior": {
    "ViewerProtocolPolicy": "string"
  },
  "DefaultRootObject": "string",
  "DomainName": "string",
  "ETag": "string",
  "LastModifiedTime": "string",
  "Logging": {
    "Bucket": "string",
    "Enabled": boolean,
    "IncludeCookies": boolean,
    "Prefix": "string"
  },
  "OriginGroups": {
    "Items": [
      {
        "FailoverCriteria": {
          "StatusCodes": {
            "Items": [ number ],
            "Quantity": number
          }
        }
      }
    ]
  }
}
```

```

    }
  ]
},
"Origins": {
  "Items": [
    {
      "CustomOriginConfig": {
        "HttpPort": number,
        "HttpsPort": number,
        "OriginKeepaliveTimeout": number,
        "OriginProtocolPolicy": "string",
        "OriginReadTimeout": number,
        "OriginSslProtocols": {
          "Items": [ "string" ],
          "Quantity": number
        }
      },
      "DomainName": "string",
      "Id": "string",
      "OriginPath": "string",
      "S3OriginConfig": {
        "OriginAccessIdentity": "string"
      }
    }
  ]
},
"Status": "string",
"ViewerCertificate": {
  "AcmCertificateArn": "string",
  "Certificate": "string",
  "CertificateSource": "string",
  "CloudFrontDefaultCertificate": boolean,
  "IamCertificateId": "string",
  "MinimumProtocolVersion": "string",
  "SslSupportMethod": "string"
},
"WebAclId": "string"
},
"AwsCloudTrailTrail": {
  "CloudWatchLogsLogGroupArn": "string",
  "CloudWatchLogsRoleArn": "string",
  "HasCustomEventSelectors": boolean,
  "HomeRegion": "string",
  "IncludeGlobalServiceEvents": boolean,

```

```
    "IsMultiRegionTrail": boolean,
    "IsOrganizationTrail": boolean,
    "KmsKeyId": "string",
    "LogFileValidationEnabled": boolean,
    "Name": "string",
    "S3BucketName": "string",
    "S3KeyPrefix": "string",
    "SnsTopicArn": "string",
    "SnsTopicName": "string",
    "TrailArn": "string"
  },
  "AwsCloudWatchAlarm": {
    "ActionsEnabled": boolean,
    "AlarmActions": [ "string" ],
    "AlarmArn": "string",
    "AlarmConfigurationUpdatedTimestamp": "string",
    "AlarmDescription": "string",
    "AlarmName": "string",
    "ComparisonOperator": "string",
    "DatapointsToAlarm": number,
    "Dimensions": [
      {
        "Name": "string",
        "Value": "string"
      }
    ],
    "EvaluateLowSampleCountPercentile": "string",
    "EvaluationPeriods": number,
    "ExtendedStatistic": "string",
    "InsufficientDataActions": [ "string" ],
    "MetricName": "string",
    "Namespace": "string",
    "OkActions": [ "string" ],
    "Period": number,
    "Statistic": "string",
    "Threshold": number,
    "ThresholdMetricId": "string",
    "TreatMissingData": "string",
    "Unit": "string"
  },
  "AwsCodeBuildProject": {
    "Artifacts": [
      {
        "ArtifactIdentifier": "string",
```

```
    "EncryptionDisabled": boolean,
    "Location": "string",
    "Name": "string",
    "NamespaceType": "string",
    "OverrideArtifactName": boolean,
    "Packaging": "string",
    "Path": "string",
    "Type": "string"
  }
],
"EncryptionKey": "string",
"Environment": {
  "Certificate": "string",
  "EnvironmentVariables": [
    {
      "Name": "string",
      "Type": "string",
      "Value": "string"
    }
  ],
  "ImagePullCredentialsType": "string",
  "PrivilegedMode": boolean,
  "RegistryCredential": {
    "Credential": "string",
    "CredentialProvider": "string"
  },
  "Type": "string"
},
"LogsConfig": {
  "CloudWatchLogs": {
    "GroupName": "string",
    "Status": "string",
    "StreamName": "string"
  },
  "S3Logs": {
    "EncryptionDisabled": boolean,
    "Location": "string",
    "Status": "string"
  }
},
"Name": "string",
"SecondaryArtifacts": [
  {
    "ArtifactIdentifier": "string",
```

```
        "EncryptionDisabled": boolean,
        "Location": "string",
        "Name": "string",
        "NamespaceType": "string",
        "OverrideArtifactName": boolean,
        "Packaging": "string",
        "Path": "string",
        "Type": "string"
    }
],
"ServiceRole": "string",
"Source": {
    "GitCloneDepth": number,
    "InsecureSsl": boolean,
    "Location": "string",
    "Type": "string"
},
"VpcConfig": {
    "SecurityGroupIds": [ "string" ],
    "Subnets": [ "string" ],
    "VpcId": "string"
}
},
"AwsDmsEndpoint": {
    "CertificateArn": "string",
    "DatabaseName": "string",
    "EndpointArn": "string",
    "EndpointIdentifier": "string",
    "EndpointType": "string",
    "EngineName": "string",
    "ExternalId": "string",
    "ExtraConnectionAttributes": "string",
    "KmsKeyId": "string",
    "Port": number,
    "ServerName": "string",
    "SslMode": "string",
    "Username": "string"
},
"AwsDmsReplicationInstance": {
    "AllocatedStorage": number,
    "AutoMinorVersionUpgrade": boolean,
    "AvailabilityZone": "string",
    "EngineVersion": "string",
    "KmsKeyId": "string",
```

```
"MultiAZ": boolean,
"PreferredMaintenanceWindow": "string",
"PubliclyAccessible": boolean,
"ReplicationInstanceClass": "string",
"ReplicationInstanceIdentifier": "string",
"ReplicationSubnetGroup": {
  "ReplicationSubnetGroupIdentifier": "string"
},
"VpcSecurityGroups": [
  {
    "VpcSecurityGroupId": "string"
  }
]
},
"AwsDmsReplicationTask": {
  "CdcStartPosition": "string",
  "CdcStartTime": "string",
  "CdcStopPosition": "string",
  "Id": "string",
  "MigrationType": "string",
  "ReplicationInstanceArn": "string",
  "ReplicationTaskIdentifier": "string",
  "ReplicationTaskSettings": "string",
  "ResourceIdentifier": "string",
  "SourceEndpointArn": "string",
  "TableMappings": "string",
  "TargetEndpointArn": "string",
  "TaskData": "string"
},
"AwsDynamoDbTable": {
  "AttributeDefinitions": [
    {
      "AttributeName": "string",
      "AttributeType": "string"
    }
  ],
  "BillingModeSummary": {
    "BillingMode": "string",
    "LastUpdateToPayPerRequestDateTime": "string"
  },
  "CreationDateTime": "string",
  "DeletionProtectionEnabled": boolean,
  "GlobalSecondaryIndexes": [
    {
```

```
"Backfilling": boolean,
"IndexArn": "string",
"IndexName": "string",
"IndexSizeBytes": number,
"IndexStatus": "string",
"ItemCount": number,
"KeySchema": [
  {
    "AttributeName": "string",
    "KeyType": "string"
  }
],
"Projection": {
  "NonKeyAttributes": [ "string" ],
  "ProjectionType": "string"
},
"ProvisionedThroughput": {
  "LastDecreaseDateTime": "string",
  "LastIncreaseDateTime": "string",
  "NumberOfDecreasesToday": number,
  "ReadCapacityUnits": number,
  "WriteCapacityUnits": number
}
],
"GlobalTableVersion": "string",
"ItemCount": number,
"KeySchema": [
  {
    "AttributeName": "string",
    "KeyType": "string"
  }
],
"LatestStreamArn": "string",
"LatestStreamLabel": "string",
"LocalSecondaryIndexes": [
  {
    "IndexArn": "string",
    "IndexName": "string",
    "KeySchema": [
      {
        "AttributeName": "string",
        "KeyType": "string"
      }
    ]
  }
]
```



```

    ],
    "Projection": {
      "NonKeyAttributes": [ "string" ],
      "ProjectionType": "string"
    }
  ],
  "ProvisionedThroughput": {
    "LastDecreaseDateTime": "string",
    "LastIncreaseDateTime": "string",
    "NumberOfDecreasesToday": number,
    "ReadCapacityUnits": number,
    "WriteCapacityUnits": number
  },
  "Replicas": [
    {
      "GlobalSecondaryIndexes": [
        {
          "IndexName": "string",
          "ProvisionedThroughputOverride": {
            "ReadCapacityUnits": number
          }
        }
      ],
      "KmsMasterKeyId": "string",
      "ProvisionedThroughputOverride": {
        "ReadCapacityUnits": number
      },
      "RegionName": "string",
      "ReplicaStatus": "string",
      "ReplicaStatusDescription": "string"
    }
  ],
  "RestoreSummary": {
    "RestoreDateTime": "string",
    "RestoreInProgress": boolean,
    "SourceBackupArn": "string",
    "SourceTableArn": "string"
  },
  "SseDescription": {
    "InaccessibleEncryptionDateTime": "string",
    "KmsMasterKeyArn": "string",
    "SseType": "string",
    "Status": "string"
  }
}

```

```
    },
    "StreamSpecification": {
      "StreamEnabled": boolean,
      "StreamViewType": "string"
    },
    "TableId": "string",
    "TableName": "string",
    "TableSizeBytes": number,
    "TableStatus": "string"
  },
  "AwsEc2ClientVpnEndpoint": {
    "AuthenticationOptions": [
      {
        "ActiveDirectory": {
          "DirectoryId": "string"
        },
        "FederatedAuthentication": {
          "SamlProviderArn": "string",
          "SelfServiceSamlProviderArn": "string"
        },
        "MutualAuthentication": {
          "ClientRootCertificateChain": "string"
        },
        "Type": "string"
      }
    ],
    "ClientCidrBlock": "string",
    "ClientConnectOptions": {
      "Enabled": boolean,
      "LambdaFunctionArn": "string",
      "Status": {
        "Code": "string",
        "Message": "string"
      }
    },
    "ClientLoginBannerOptions": {
      "BannerText": "string",
      "Enabled": boolean
    },
    "ClientVpnEndpointId": "string",
    "ConnectionLogOptions": {
      "CloudwatchLogGroup": "string",
      "CloudwatchLogStream": "string",
      "Enabled": boolean
    }
  }
}
```

```
    },
    "Description": "string",
    "DnsServer": [ "string" ],
    "SecurityGroupIdSet": [ "string" ],
    "SelfServicePortalUrl": "string",
    "ServerCertificateArn": "string",
    "SessionTimeoutHours": number,
    "SplitTunnel": boolean,
    "TransportProtocol": "string",
    "VpcId": "string",
    "VpnPort": number
  },
  "AwsEc2Eip": {
    "AllocationId": "string",
    "AssociationId": "string",
    "Domain": "string",
    "InstanceId": "string",
    "NetworkBorderGroup": "string",
    "NetworkInterfaceId": "string",
    "NetworkInterfaceOwnerId": "string",
    "PrivateIpAddress": "string",
    "PublicIp": "string",
    "PublicIpv4Pool": "string"
  },
  "AwsEc2Instance": {
    "IamInstanceProfileArn": "string",
    "ImageId": "string",
    "IPv4Addresses": [ "string" ],
    "IPv6Addresses": [ "string" ],
    "KeyName": "string",
    "LaunchedAt": "string",
    "MetadataOptions": {
      "HttpEndpoint": "string",
      "HttpProtocolIpv6": "string",
      "HttpPutResponseHopLimit": number,
      "HttpTokens": "string",
      "InstanceMetadataTags": "string"
    },
    "Monitoring": {
      "State": "string"
    },
    "NetworkInterfaces": [
      {
        "NetworkInterfaceId": "string"
      }
    ]
  }
}
```

```

    }
  ],
  "SubnetId": "string",
  "Type": "string",
  "VirtualizationType": "string",
  "VpcId": "string"
},
"AwsEc2LaunchTemplate": {
  "DefaultVersionNumber": number,
  "Id": "string",
  "LatestVersionNumber": number,
  "LaunchTemplateData": {
    "BlockDeviceMappingSet": [
      {
        "DeviceName": "string",
        "Ebs": {
          "DeleteOnTermination": boolean,
          "Encrypted": boolean,
          "Iops": number,
          "KmsKeyId": "string",
          "SnapshotId": "string",
          "Throughput": number,
          "VolumeSize": number,
          "VolumeType": "string"
        },
        "NoDevice": "string",
        "VirtualName": "string"
      }
    ],
    "CapacityReservationSpecification": {
      "CapacityReservationPreference": "string",
      "CapacityReservationTarget": {
        "CapacityReservationId": "string",
        "CapacityReservationResourceGroupArn": "string"
      }
    },
    "CpuOptions": {
      "CoreCount": number,
      "ThreadsPerCore": number
    },
    "CreditSpecification": {
      "CpuCredits": "string"
    },
    "DisableApiStop": boolean,

```

```
"DisableApiTermination": boolean,
"EbsOptimized": boolean,
"ElasticGpuSpecificationSet": [
  {
    "Type": "string"
  }
],
"ElasticInferenceAcceleratorSet": [
  {
    "Count": number,
    "Type": "string"
  }
],
"EnclaveOptions": {
  "Enabled": boolean
},
"HibernationOptions": {
  "Configured": boolean
},
"IamInstanceProfile": {
  "Arn": "string",
  "Name": "string"
},
"ImageId": "string",
"InstanceInitiatedShutdownBehavior": "string",
"InstanceMarketOptions": {
  "MarketType": "string",
  "SpotOptions": {
    "BlockDurationMinutes": number,
    "InstanceInterruptionBehavior": "string",
    "MaxPrice": "string",
    "SpotInstanceType": "string",
    "ValidUntil": "string"
  }
},
"InstanceRequirements": {
  "AcceleratorCount": {
    "Max": number,
    "Min": number
  },
  "AcceleratorManufacturers": [ "string" ],
  "AcceleratorNames": [ "string" ],
  "AcceleratorTotalMemoryMiB": {
    "Max": number,
```

```
    "Min": number
  },
  "AcceleratorTypes": [ string ],
  "BareMetal": string,
  "BaselineEbsBandwidthMbps": {
    "Max": number,
    "Min": number
  },
  "BurstablePerformance": string,
  "CpuManufacturers": [ string ],
  "ExcludedInstanceTypes": [ string ],
  "InstanceGenerations": [ string ],
  "LocalStorage": string,
  "LocalStorageTypes": [ string ],
  "MemoryGiBPerVCpu": {
    "Max": number,
    "Min": number
  },
  "MemoryMiB": {
    "Max": number,
    "Min": number
  },
  "NetworkInterfaceCount": {
    "Max": number,
    "Min": number
  },
  "OnDemandMaxPricePercentageOverLowestPrice": number,
  "RequireHibernateSupport": boolean,
  "SpotMaxPricePercentageOverLowestPrice": number,
  "TotalLocalStorageGB": {
    "Max": number,
    "Min": number
  },
  "VCpuCount": {
    "Max": number,
    "Min": number
  }
},
"InstanceType": string,
"KernelId": string,
"KeyName": string,
"LicenseSet": [
  {
    "LicenseConfigurationArn": string
  }
]
```

```
    }
  ],
  "MaintenanceOptions": {
    "AutoRecovery": "string"
  },
  "MetadataOptions": {
    "HttpEndpoint": "string",
    "HttpProtocolIpv6": "string",
    "HttpPutResponseHopLimit": number,
    "HttpTokens": "string",
    "InstanceMetadataTags": "string"
  },
  "Monitoring": {
    "Enabled": boolean
  },
  "NetworkInterfaceSet": [
    {
      "AssociateCarrierIpAddress": boolean,
      "AssociatePublicIpAddress": boolean,
      "DeleteOnTermination": boolean,
      "Description": "string",
      "DeviceIndex": number,
      "Groups": [ "string" ],
      "InterfaceType": "string",
      "Ipv4PrefixCount": number,
      "Ipv4Prefixes": [
        {
          "Ipv4Prefix": "string"
        }
      ],
      "Ipv6AddressCount": number,
      "Ipv6Addresses": [
        {
          "Ipv6Address": "string"
        }
      ],
      "Ipv6PrefixCount": number,
      "Ipv6Prefixes": [
        {
          "Ipv6Prefix": "string"
        }
      ],
      "NetworkCardIndex": number,
      "NetworkInterfaceId": "string",
```

```
    "PrivateIpAddress": "string",
    "PrivateIpAddresses": [
      {
        "Primary": boolean,
        "PrivateIpAddress": "string"
      }
    ],
    "SecondaryPrivateIpAddressCount": number,
    "SubnetId": "string"
  }
],
"Placement": {
  "Affinity": "string",
  "AvailabilityZone": "string",
  "GroupName": "string",
  "HostId": "string",
  "HostResourceGroupArn": "string",
  "PartitionNumber": number,
  "SpreadDomain": "string",
  "Tenancy": "string"
},
"PrivateDnsNameOptions": {
  "EnableResourceNameDnsAAAARecord": boolean,
  "EnableResourceNameDnsARecord": boolean,
  "HostnameType": "string"
},
"RamDiskId": "string",
"SecurityGroupIdSet": [ "string" ],
"SecurityGroupSet": [ "string" ],
"UserData": "string"
},
"LaunchTemplateName": "string"
},
"AwsEc2NetworkAcl": {
  "Associations": [
    {
      "NetworkAclAssociationId": "string",
      "NetworkAclId": "string",
      "SubnetId": "string"
    }
  ]
},
"Entries": [
  {
    "CidrBlock": "string",
```



```
    "Egress": boolean,
    "IcmpTypeCode": {
      "Code": number,
      "Type": number
    },
    "Ipv6CidrBlock": "string",
    "PortRange": {
      "From": number,
      "To": number
    },
    "Protocol": "string",
    "RuleAction": "string",
    "RuleNumber": number
  }
],
"IsDefault": boolean,
"NetworkAclId": "string",
"OwnerId": "string",
"VpcId": "string"
},
"AwsEc2NetworkInterface": {
  "Attachment": {
    "AttachmentId": "string",
    "AttachTime": "string",
    "DeleteOnTermination": boolean,
    "DeviceIndex": number,
    "InstanceId": "string",
    "InstanceOwnerId": "string",
    "Status": "string"
  },
  "IPv6Addresses": [
    {
      "IPv6Address": "string"
    }
  ],
  "NetworkInterfaceId": "string",
  "PrivateIpAddresses": [
    {
      "PrivateDnsName": "string",
      "PrivateIpAddress": "string"
    }
  ],
  "PublicDnsName": "string",
  "PublicIp": "string",
```

```
    "SecurityGroups": [
      {
        "GroupId": "string",
        "GroupName": "string"
      }
    ],
    "SourceDestCheck": boolean
  },
  "AwsEc2RouteTable": {
    "AssociationSet": [
      {
        "AssociationState": {
          "State": "string",
          "StatusMessage": "string"
        },
        "GatewayId": "string",
        "Main": boolean,
        "RouteTableAssociationId": "string",
        "RouteTableId": "string",
        "SubnetId": "string"
      }
    ],
    "OwnerId": "string",
    "PropagatingVgwSet": [
      {
        "GatewayId": "string"
      }
    ],
    "RouteSet": [
      {
        "CarrierGatewayId": "string",
        "CoreNetworkArn": "string",
        "DestinationCidrBlock": "string",
        "DestinationIpv6CidrBlock": "string",
        "DestinationPrefixListId": "string",
        "EgressOnlyInternetGatewayId": "string",
        "GatewayId": "string",
        "InstanceId": "string",
        "InstanceOwnerId": "string",
        "LocalGatewayId": "string",
        "NatGatewayId": "string",
        "NetworkInterfaceId": "string",
        "Origin": "string",
        "State": "string",
```

```
        "TransitGatewayId": "string",
        "VpcPeeringConnectionId": "string"
    }
],
"RouteTableId": "string",
"VpcId": "string"
},
"AwsEc2SecurityGroup": {
    "GroupId": "string",
    "GroupName": "string",
    "IpPermissions": [
        {
            "FromPort": number,
            "IpProtocol": "string",
            "IpRanges": [
                {
                    "CidrIp": "string"
                }
            ],
            "Ipv6Ranges": [
                {
                    "CidrIpv6": "string"
                }
            ],
            "PrefixListIds": [
                {
                    "PrefixListId": "string"
                }
            ],
            "ToPort": number,
            "UserIdGroupPairs": [
                {
                    "GroupId": "string",
                    "GroupName": "string",
                    "PeeringStatus": "string",
                    "UserId": "string",
                    "VpcId": "string",
                    "VpcPeeringConnectionId": "string"
                }
            ]
        }
    ]
},
"IpPermissionsEgress": [
    {
```

```
    "FromPort": number,
    "IpProtocol": "string",
    "IpRanges": [
      {
        "CidrIp": "string"
      }
    ],
    "Ipv6Ranges": [
      {
        "CidrIpv6": "string"
      }
    ],
    "PrefixListIds": [
      {
        "PrefixListId": "string"
      }
    ],
    "ToPort": number,
    "UserIdGroupPairs": [
      {
        "GroupId": "string",
        "GroupName": "string",
        "PeeringStatus": "string",
        "UserId": "string",
        "VpcId": "string",
        "VpcPeeringConnectionId": "string"
      }
    ]
  },
  "OwnerId": "string",
  "VpcId": "string"
},
"AwsEc2Subnet": {
  "AssignIpv6AddressOnCreation": boolean,
  "AvailabilityZone": "string",
  "AvailabilityZoneId": "string",
  "AvailableIpAddressCount": number,
  "CidrBlock": "string",
  "DefaultForAz": boolean,
  "Ipv6CidrBlockAssociationSet": [
    {
      "AssociationId": "string",
      "CidrBlockState": "string",
```

```

        "Ipv6CidrBlock": "string"
    }
],
"MapPublicIpOnLaunch": boolean,
"OwnerId": "string",
"State": "string",
"SubnetArn": "string",
"SubnetId": "string",
"VpcId": "string"
},
"AwsEc2TransitGateway": {
    "AmazonSideAsn": number,
    "AssociationDefaultRouteTableId": "string",
    "AutoAcceptSharedAttachments": "string",
    "DefaultRouteTableAssociation": "string",
    "DefaultRouteTablePropagation": "string",
    "Description": "string",
    "DnsSupport": "string",
    "Id": "string",
    "MulticastSupport": "string",
    "PropagationDefaultRouteTableId": "string",
    "TransitGatewayCidrBlocks": [ "string" ],
    "VpnEcmpSupport": "string"
},
"AwsEc2Volume": {
    "Attachments": [
        {
            "AttachTime": "string",
            "DeleteOnTermination": boolean,
            "InstanceId": "string",
            "Status": "string"
        }
    ],
    "CreateTime": "string",
    "DeviceName": "string",
    "Encrypted": boolean,
    "KmsKeyId": "string",
    "Size": number,
    "SnapshotId": "string",
    "Status": "string",
    "VolumeId": "string",
    "VolumeScanStatus": "string",
    "VolumeType": "string"
},

```

```
"AwsEc2Vpc": {
  "CidrBlockAssociationSet": [
    {
      "AssociationId": "string",
      "CidrBlock": "string",
      "CidrBlockState": "string"
    }
  ],
  "DhcpOptionsId": "string",
  "Ipv6CidrBlockAssociationSet": [
    {
      "AssociationId": "string",
      "CidrBlockState": "string",
      "Ipv6CidrBlock": "string"
    }
  ],
  "State": "string"
},
"AwsEc2VpcEndpointService": {
  "AcceptanceRequired": boolean,
  "AvailabilityZones": [ "string" ],
  "BaseEndpointDnsNames": [ "string" ],
  "GatewayLoadBalancerArns": [ "string" ],
  "ManagesVpcEndpoints": boolean,
  "NetworkLoadBalancerArns": [ "string" ],
  "PrivateDnsName": "string",
  "ServiceId": "string",
  "ServiceName": "string",
  "ServiceState": "string",
  "ServiceType": [
    {
      "ServiceType": "string"
    }
  ]
},
"AwsEc2VpcPeeringConnection": {
  "AcceptorVpcInfo": {
    "CidrBlock": "string",
    "CidrBlockSet": [
      {
        "CidrBlock": "string"
      }
    ],
  },
  "Ipv6CidrBlockSet": [
```

```
    {
      "Ipv6CidrBlock": "string"
    }
  ],
  "OwnerId": "string",
  "PeeringOptions": {
    "AllowDnsResolutionFromRemoteVpc": boolean,
    "AllowEgressFromLocalClassicLinkToRemoteVpc": boolean,
    "AllowEgressFromLocalVpcToRemoteClassicLink": boolean
  },
  "Region": "string",
  "VpcId": "string"
},
"ExpirationTime": "string",
"RequesterVpcInfo": {
  "CidrBlock": "string",
  "CidrBlockSet": [
    {
      "CidrBlock": "string"
    }
  ],
  "Ipv6CidrBlockSet": [
    {
      "Ipv6CidrBlock": "string"
    }
  ],
  "OwnerId": "string",
  "PeeringOptions": {
    "AllowDnsResolutionFromRemoteVpc": boolean,
    "AllowEgressFromLocalClassicLinkToRemoteVpc": boolean,
    "AllowEgressFromLocalVpcToRemoteClassicLink": boolean
  },
  "Region": "string",
  "VpcId": "string"
},
"Status": {
  "Code": "string",
  "Message": "string"
},
"VpcPeeringConnectionId": "string"
},
"AwsEc2VpnConnection": {
  "Category": "string",
  "CustomerGatewayConfiguration": "string",
```

```
"CustomerGatewayId": "string",
"Options": {
  "StaticRoutesOnly": boolean,
  "TunnelOptions": [
    {
      "DpdTimeoutSeconds": number,
      "IkeVersions": [ "string" ],
      "OutsideIpAddress": "string",
      "Phase1DhGroupNumbers": [ number ],
      "Phase1EncryptionAlgorithms": [ "string" ],
      "Phase1IntegrityAlgorithms": [ "string" ],
      "Phase1LifetimeSeconds": number,
      "Phase2DhGroupNumbers": [ number ],
      "Phase2EncryptionAlgorithms": [ "string" ],
      "Phase2IntegrityAlgorithms": [ "string" ],
      "Phase2LifetimeSeconds": number,
      "PreSharedKey": "string",
      "RekeyFuzzPercentage": number,
      "RekeyMarginTimeSeconds": number,
      "ReplayWindowSize": number,
      "TunnelInsideCidr": "string"
    }
  ]
},
"Routes": [
  {
    "DestinationCidrBlock": "string",
    "State": "string"
  }
],
"State": "string",
"TransitGatewayId": "string",
"Type": "string",
"VgwTelemetry": [
  {
    "AcceptedRouteCount": number,
    "CertificateArn": "string",
    "LastStatusChange": "string",
    "OutsideIpAddress": "string",
    "Status": "string",
    "StatusMessage": "string"
  }
],
"VpnConnectionId": "string",
```



```
    "VpnGatewayId": "string"
  },
  "AwsEcrContainerImage": {
    "Architecture": "string",
    "ImageDigest": "string",
    "ImagePublishedAt": "string",
    "ImageTags": [ "string" ],
    "RegistryId": "string",
    "RepositoryName": "string"
  },
  "AwsEcrRepository": {
    "Arn": "string",
    "ImageScanningConfiguration": {
      "ScanOnPush": boolean
    },
    "ImageTagMutability": "string",
    "LifecyclePolicy": {
      "LifecyclePolicyText": "string",
      "RegistryId": "string"
    },
    "RepositoryName": "string",
    "RepositoryPolicyText": "string"
  },
  "AwsEcsCluster": {
    "ActiveServicesCount": number,
    "CapacityProviders": [ "string" ],
    "ClusterArn": "string",
    "ClusterName": "string",
    "ClusterSettings": [
      {
        "Name": "string",
        "Value": "string"
      }
    ],
    "Configuration": {
      "ExecuteCommandConfiguration": {
        "KmsKeyId": "string",
        "LogConfiguration": {
          "CloudWatchEncryptionEnabled": boolean,
          "CloudWatchLogGroupName": "string",
          "S3BucketName": "string",
          "S3EncryptionEnabled": boolean,
          "S3KeyPrefix": "string"
        }
      }
    }
  }
}
```

```
        "Logging": "string"
      }
    },
    "DefaultCapacityProviderStrategy": [
      {
        "Base": number,
        "CapacityProvider": "string",
        "Weight": number
      }
    ],
    "RegisteredContainerInstancesCount": number,
    "RunningTasksCount": number,
    "Status": "string"
  },
  "AwsEcsContainer": {
    "Image": "string",
    "MountPoints": [
      {
        "ContainerPath": "string",
        "SourceVolume": "string"
      }
    ],
    "Name": "string",
    "Privileged": boolean
  },
  "AwsEcsService": {
    "CapacityProviderStrategy": [
      {
        "Base": number,
        "CapacityProvider": "string",
        "Weight": number
      }
    ],
    "Cluster": "string",
    "DeploymentConfiguration": {
      "DeploymentCircuitBreaker": {
        "Enable": boolean,
        "Rollback": boolean
      },
      "MaximumPercent": number,
      "MinimumHealthyPercent": number
    },
    "DeploymentController": {
      "Type": "string"
    }
  }
}
```

```
},
  "DesiredCount": number,
  "EnableEcsManagedTags": boolean,
  "EnableExecuteCommand": boolean,
  "HealthCheckGracePeriodSeconds": number,
  "LaunchType": "string",
  "LoadBalancers": [
    {
      "ContainerName": "string",
      "ContainerPort": number,
      "LoadBalancerName": "string",
      "TargetGroupArn": "string"
    }
  ],
  "Name": "string",
  "NetworkConfiguration": {
    "AwsVpcConfiguration": {
      "AssignPublicIp": "string",
      "SecurityGroups": [ "string" ],
      "Subnets": [ "string" ]
    }
  },
  "PlacementConstraints": [
    {
      "Expression": "string",
      "Type": "string"
    }
  ],
  "PlacementStrategies": [
    {
      "Field": "string",
      "Type": "string"
    }
  ],
  "PlatformVersion": "string",
  "PropagateTags": "string",
  "Role": "string",
  "SchedulingStrategy": "string",
  "ServiceArn": "string",
  "ServiceName": "string",
  "ServiceRegistries": [
    {
      "ContainerName": "string",
      "ContainerPort": number,
```

```

        "Port": number,
        "RegistryArn": "string"
    }
],
"TaskDefinition": "string"
},
"AwsEcsTask": {
    "ClusterArn": "string",
    "Containers": [
        {
            "Image": "string",
            "MountPoints": [
                {
                    "ContainerPath": "string",
                    "SourceVolume": "string"
                }
            ],
            "Name": "string",
            "Privileged": boolean
        }
    ],
    "CreatedAt": "string",
    "Group": "string",
    "StartedAt": "string",
    "StartedBy": "string",
    "TaskDefinitionArn": "string",
    "Version": "string",
    "Volumes": [
        {
            "Host": {
                "SourcePath": "string"
            },
            "Name": "string"
        }
    ]
},
"AwsEcsTaskDefinition": {
    "ContainerDefinitions": [
        {
            "Command": [ "string" ],
            "Cpu": number,
            "DependsOn": [
                {
                    "Condition": "string",

```

```
    "ContainerName": "string"
  }
],
"DisableNetworking": boolean,
"DnsSearchDomains": [ "string" ],
"DnsServers": [ "string" ],
"DockerLabels": {
  "string" : "string"
},
"DockerSecurityOptions": [ "string" ],
"EntryPoint": [ "string" ],
"Environment": [
  {
    "Name": "string",
    "Value": "string"
  }
],
"EnvironmentFiles": [
  {
    "Type": "string",
    "Value": "string"
  }
],
"Essential": boolean,
"ExtraHosts": [
  {
    "Hostname": "string",
    "IpAddress": "string"
  }
],
"FirelensConfiguration": {
  "Options": {
    "string" : "string"
  },
  "Type": "string"
},
"HealthCheck": {
  "Command": [ "string" ],
  "Interval": number,
  "Retries": number,
  "StartPeriod": number,
  "Timeout": number
},
"Hostname": "string",
```

```
"Image": "string",
"Interactive": boolean,
"Links": [ "string" ],
"LinuxParameters": {
  "Capabilities": {
    "Add": [ "string" ],
    "Drop": [ "string" ]
  },
  "Devices": [
    {
      "ContainerPath": "string",
      "HostPath": "string",
      "Permissions": [ "string" ]
    }
  ],
  "InitProcessEnabled": boolean,
  "MaxSwap": number,
  "SharedMemorySize": number,
  "Swappiness": number,
  "Tmpfs": [
    {
      "ContainerPath": "string",
      "MountOptions": [ "string" ],
      "Size": number
    }
  ]
},
"LogConfiguration": {
  "LogDriver": "string",
  "Options": {
    "string": "string"
  },
  "SecretOptions": [
    {
      "Name": "string",
      "ValueFrom": "string"
    }
  ]
},
"Memory": number,
"MemoryReservation": number,
"MountPoints": [
  {
    "ContainerPath": "string",
```

```
        "ReadOnly": boolean,
        "SourceVolume": "string"
    }
],
"Name": "string",
"PortMappings": [
    {
        "ContainerPort": number,
        "HostPort": number,
        "Protocol": "string"
    }
],
"Privileged": boolean,
"PseudoTerminal": boolean,
"ReadOnlyRootFilesystem": boolean,
"RepositoryCredentials": {
    "CredentialsParameter": "string"
},
"ResourceRequirements": [
    {
        "Type": "string",
        "Value": "string"
    }
],
"Secrets": [
    {
        "Name": "string",
        "ValueFrom": "string"
    }
],
"StartTimeout": number,
"StopTimeout": number,
"SystemControls": [
    {
        "Namespace": "string",
        "Value": "string"
    }
],
"Ulimits": [
    {
        "HardLimit": number,
        "Name": "string",
        "SoftLimit": number
    }
]
```

```
    ],
    "User": "string",
    "VolumesFrom": [
      {
        "ReadOnly": boolean,
        "SourceContainer": "string"
      }
    ],
    "WorkingDirectory": "string"
  }
],
"Cpu": "string",
"ExecutionRoleArn": "string",
"Family": "string",
"InferenceAccelerators": [
  {
    "DeviceName": "string",
    "DeviceType": "string"
  }
],
"IpcMode": "string",
"Memory": "string",
"NetworkMode": "string",
"PidMode": "string",
"PlacementConstraints": [
  {
    "Expression": "string",
    "Type": "string"
  }
],
"ProxyConfiguration": {
  "ContainerName": "string",
  "ProxyConfigurationProperties": [
    {
      "Name": "string",
      "Value": "string"
    }
  ],
  "Type": "string"
},
"RequiresCompatibilities": [ "string" ],
"Status": "string",
"TaskRoleArn": "string",
"Volumes": [
```



```

    {
      "DockerVolumeConfiguration": {
        "Autoprovision": boolean,
        "Driver": "string",
        "DriverOpts": {
          "string" : "string"
        },
        "Labels": {
          "string" : "string"
        },
        "Scope": "string"
      },
      "EfsVolumeConfiguration": {
        "AuthorizationConfig": {
          "AccessPointId": "string",
          "Iam": "string"
        },
        "FilesystemId": "string",
        "RootDirectory": "string",
        "TransitEncryption": "string",
        "TransitEncryptionPort": number
      },
      "Host": {
        "SourcePath": "string"
      },
      "Name": "string"
    }
  ]
},
"AwsEfsAccessPoint": {
  "AccessPointId": "string",
  "Arn": "string",
  "ClientToken": "string",
  "FileSystemId": "string",
  "PosixUser": {
    "Gid": "string",
    "SecondaryGids": [ "string" ],
    "Uid": "string"
  },
  "RootDirectory": {
    "CreationInfo": {
      "OwnerGid": "string",
      "OwnerUid": "string",
      "Permissions": "string"
    }
  }
}

```

```
    },
    "Path": "string"
  }
},
"AwsEksCluster": {
  "Arn": "string",
  "CertificateAuthorityData": "string",
  "ClusterStatus": "string",
  "Endpoint": "string",
  "Logging": {
    "ClusterLogging": [
      {
        "Enabled": boolean,
        "Types": [ "string" ]
      }
    ]
  },
  "Name": "string",
  "ResourcesVpcConfig": {
    "EndpointPublicAccess": boolean,
    "SecurityGroupIds": [ "string" ],
    "SubnetIds": [ "string" ]
  },
  "RoleArn": "string",
  "Version": "string"
},
"AwsElasticBeanstalkEnvironment": {
  "ApplicationName": "string",
  "Cname": "string",
  "DateCreated": "string",
  "DateUpdated": "string",
  "Description": "string",
  "EndpointUrl": "string",
  "EnvironmentArn": "string",
  "EnvironmentId": "string",
  "EnvironmentLinks": [
    {
      "EnvironmentName": "string",
      "LinkName": "string"
    }
  ],
  "EnvironmentName": "string",
  "OptionSettings": [
    {
```

```
        "Namespace": "string",
        "OptionName": "string",
        "ResourceName": "string",
        "Value": "string"
    }
],
"PlatformArn": "string",
"SolutionStackName": "string",
"Status": "string",
"Tier": {
    "Name": "string",
    "Type": "string",
    "Version": "string"
},
"VersionLabel": "string"
},
"AwsElasticsearchDomain": {
    "AccessPolicies": "string",
    "DomainEndpointOptions": {
        "EnforceHTTPS": boolean,
        "TLSSecurityPolicy": "string"
    },
    "DomainId": "string",
    "DomainName": "string",
    "ElasticsearchClusterConfig": {
        "DedicatedMasterCount": number,
        "DedicatedMasterEnabled": boolean,
        "DedicatedMasterType": "string",
        "InstanceCount": number,
        "InstanceType": "string",
        "ZoneAwarenessConfig": {
            "AvailabilityZoneCount": number
        },
        "ZoneAwarenessEnabled": boolean
    },
    "ElasticsearchVersion": "string",
    "EncryptionAtRestOptions": {
        "Enabled": boolean,
        "KmsKeyId": "string"
    },
    "Endpoint": "string",
    "Endpoints": {
        "string" : "string"
    },
}
```

```
"LogPublishingOptions": {
  "AuditLogs": {
    "CloudWatchLogsLogGroupArn": "string",
    "Enabled": boolean
  },
  "IndexSlowLogs": {
    "CloudWatchLogsLogGroupArn": "string",
    "Enabled": boolean
  },
  "SearchSlowLogs": {
    "CloudWatchLogsLogGroupArn": "string",
    "Enabled": boolean
  }
},
"NodeToNodeEncryptionOptions": {
  "Enabled": boolean
},
"ServiceSoftwareOptions": {
  "AutomatedUpdateDate": "string",
  "Cancellable": boolean,
  "CurrentVersion": "string",
  "Description": "string",
  "NewVersion": "string",
  "UpdateAvailable": boolean,
  "UpdateStatus": "string"
},
"VPCOptions": {
  "AvailabilityZones": [ "string" ],
  "SecurityGroupIds": [ "string" ],
  "SubnetIds": [ "string" ],
  "VPCId": "string"
},
"AwsElbLoadBalancer": {
  "AvailabilityZones": [ "string" ],
  "BackendServerDescriptions": [
    {
      "InstancePort": number,
      "PolicyNames": [ "string" ]
    }
  ],
  "CanonicalHostedZoneName": "string",
  "CanonicalHostedZoneNameID": "string",
  "CreatedTime": "string",
```

```
"DnsName": "string",
"HealthCheck": {
  "HealthyThreshold": number,
  "Interval": number,
  "Target": "string",
  "Timeout": number,
  "UnhealthyThreshold": number
},
"Instances": [
  {
    "InstanceId": "string"
  }
],
"ListenerDescriptions": [
  {
    "Listener": {
      "InstancePort": number,
      "InstanceProtocol": "string",
      "LoadBalancerPort": number,
      "Protocol": "string",
      "SslCertificateId": "string"
    },
    "PolicyNames": [ "string" ]
  }
],
"LoadBalancerAttributes": {
  "AccessLog": {
    "EmitInterval": number,
    "Enabled": boolean,
    "S3BucketName": "string",
    "S3BucketPrefix": "string"
  },
  "AdditionalAttributes": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "ConnectionDraining": {
    "Enabled": boolean,
    "Timeout": number
  },
  "ConnectionSettings": {
    "IdleTimeout": number
  }
}
```

```

    },
    "CrossZoneLoadBalancing": {
      "Enabled": boolean
    }
  },
  "LoadBalancerName": string,
  "Policies": {
    "AppCookieStickinessPolicies": [
      {
        "CookieName": string,
        "PolicyName": string
      }
    ],
    "LbCookieStickinessPolicies": [
      {
        "CookieExpirationPeriod": number,
        "PolicyName": string
      }
    ],
    "OtherPolicies": [ string ]
  },
  "Scheme": string,
  "SecurityGroups": [ string ],
  "SourceSecurityGroup": {
    "GroupName": string,
    "OwnerAlias": string
  },
  "Subnets": [ string ],
  "VpcId": string
},
"AwsElbv2LoadBalancer": {
  "AvailabilityZones": [
    {
      "SubnetId": string,
      "ZoneName": string
    }
  ],
  "CanonicalHostedZoneId": string,
  "CreatedTime": string,
  "DNSName": string,
  "IpAddressType": string,
  "LoadBalancerAttributes": [
    {
      "Key": string,

```

```
        "Value": "string"
      }
    ],
    "Scheme": "string",
    "SecurityGroups": [ "string" ],
    "State": {
      "Code": "string",
      "Reason": "string"
    },
    "Type": "string",
    "VpcId": "string"
  },
  "AwsEventSchemasRegistry": {
    "Description": "string",
    "RegistryArn": "string",
    "RegistryName": "string"
  },
  "AwsEventsEndpoint": {
    "Arn": "string",
    "Description": "string",
    "EndpointId": "string",
    "EndpointUrl": "string",
    "EventBuses": [
      {
        "EventBusArn": "string"
      }
    ],
    "Name": "string",
    "ReplicationConfig": {
      "State": "string"
    },
    "RoleArn": "string",
    "RoutingConfig": {
      "FailoverConfig": {
        "Primary": {
          "HealthCheck": "string"
        },
        "Secondary": {
          "Route": "string"
        }
      }
    }
  },
  "State": "string",
  "StateReason": "string"
```

```
    },
    "AwsEventsEventbus": {
      "Arn": "string",
      "Name": "string",
      "Policy": "string"
    },
    "AwsGuardDutyDetector": {
      "DataSources": {
        "CloudTrail": {
          "Status": "string"
        },
        "DnsLogs": {
          "Status": "string"
        },
        "FlowLogs": {
          "Status": "string"
        },
        "Kubernetes": {
          "AuditLogs": {
            "Status": "string"
          }
        }
      },
      "MalwareProtection": {
        "ScanEc2InstanceWithFindings": {
          "EbsVolumes": {
            "Reason": "string",
            "Status": "string"
          }
        },
        "ServiceRole": "string"
      },
      "S3Logs": {
        "Status": "string"
      }
    },
    "Features": [
      {
        "Name": "string",
        "Status": "string"
      }
    ],
    "FindingPublishingFrequency": "string",
    "ServiceRole": "string",
    "Status": "string"
  }
```



```
    },
    "AwsIamAccessKey": {
      "AccessKeyId": "string",
      "AccountId": "string",
      "CreatedAt": "string",
      "PrincipalId": "string",
      "PrincipalName": "string",
      "PrincipalType": "string",
      "SessionContext": {
        "Attributes": {
          "CreationDate": "string",
          "MfaAuthenticated": boolean
        },
        "SessionIssuer": {
          "AccountId": "string",
          "Arn": "string",
          "PrincipalId": "string",
          "Type": "string",
          "UserName": "string"
        }
      },
      "Status": "string",
      "UserName": "string"
    },
    "AwsIamGroup": {
      "AttachedManagedPolicies": [
        {
          "PolicyArn": "string",
          "PolicyName": "string"
        }
      ],
      "CreateDate": "string",
      "GroupId": "string",
      "GroupName": "string",
      "GroupPolicyList": [
        {
          "PolicyName": "string"
        }
      ],
      "Path": "string"
    },
    "AwsIamPolicy": {
      "AttachmentCount": number,
      "CreateDate": "string",
```

```
"DefaultVersionId": "string",
"Description": "string",
"IsAttachable": boolean,
"Path": "string",
"PermissionsBoundaryUsageCount": number,
"PolicyId": "string",
"PolicyName": "string",
"PolicyVersionList": [
  {
    "CreateDate": "string",
    "IsDefaultVersion": boolean,
    "VersionId": "string"
  }
],
"UpdateDate": "string"
},
"AwsIamRole": {
  "AssumeRolePolicyDocument": "string",
  "AttachedManagedPolicies": [
    {
      "PolicyArn": "string",
      "PolicyName": "string"
    }
  ],
  "CreateDate": "string",
  "InstanceProfileList": [
    {
      "Arn": "string",
      "CreateDate": "string",
      "InstanceProfileId": "string",
      "InstanceProfileName": "string",
      "Path": "string",
      "Roles": [
        {
          "Arn": "string",
          "AssumeRolePolicyDocument": "string",
          "CreateDate": "string",
          "Path": "string",
          "RoleId": "string",
          "RoleName": "string"
        }
      ]
    }
  ]
}
```

```
"MaxSessionDuration": number,
"Path": "string",
"PermissionsBoundary": {
  "PermissionsBoundaryArn": "string",
  "PermissionsBoundaryType": "string"
},
"RoleId": "string",
"RoleName": "string",
"RolePolicyList": [
  {
    "PolicyName": "string"
  }
]
},
"AwsIamUser": {
  "AttachedManagedPolicies": [
    {
      "PolicyArn": "string",
      "PolicyName": "string"
    }
  ],
  "CreateDate": "string",
  "GroupList": [ "string" ],
  "Path": "string",
  "PermissionsBoundary": {
    "PermissionsBoundaryArn": "string",
    "PermissionsBoundaryType": "string"
  },
  "UserId": "string",
  "UserName": "string",
  "UserPolicyList": [
    {
      "PolicyName": "string"
    }
  ]
},
"AwsKinesisStream": {
  "Arn": "string",
  "Name": "string",
  "RetentionPeriodHours": number,
  "ShardCount": number,
  "StreamEncryption": {
    "EncryptionType": "string",
    "KeyId": "string"
  }
}
```

```
    }
  },
  "AwsKmsKey": {
    "AWSAccountId": "string",
    "CreationDate": number,
    "Description": "string",
    "KeyId": "string",
    "KeyManager": "string",
    "KeyRotationStatus": boolean,
    "KeyState": "string",
    "Origin": "string"
  },
  "AwsLambdaFunction": {
    "Architectures": [ "string" ],
    "Code": {
      "S3Bucket": "string",
      "S3Key": "string",
      "S3ObjectVersion": "string",
      "ZipFile": "string"
    },
    "CodeSha256": "string",
    "DeadLetterConfig": {
      "TargetArn": "string"
    },
    "Environment": {
      "Error": {
        "ErrorCode": "string",
        "Message": "string"
      },
      "Variables": {
        "string": "string"
      }
    },
    "FunctionName": "string",
    "Handler": "string",
    "KmsKeyArn": "string",
    "LastModified": "string",
    "Layers": [
      {
        "Arn": "string",
        "CodeSize": number
      }
    ],
    "MasterArn": "string",
```

```
"MemorySize": number,
"PackageType": "string",
"RevisionId": "string",
"Role": "string",
"Runtime": "string",
"Timeout": number,
"TracingConfig": {
  "Mode": "string"
},
"Version": "string",
"VpcConfig": {
  "SecurityGroupIds": [ "string" ],
  "SubnetIds": [ "string" ],
  "VpcId": "string"
}
},
"AwsLambdaLayerVersion": {
  "CompatibleRuntimes": [ "string" ],
  "CreateDate": "string",
  "Version": number
},
"AwsMskCluster": {
  "ClusterInfo": {
    "ClientAuthentication": {
      "Sasl": {
        "Iam": {
          "Enabled": boolean
        },
        "Scram": {
          "Enabled": boolean
        }
      },
      "Tls": {
        "CertificateAuthorityArnList": [ "string" ],
        "Enabled": boolean
      },
      "Unauthenticated": {
        "Enabled": boolean
      }
    },
    "ClusterName": "string",
    "CurrentVersion": "string",
    "EncryptionInfo": {
      "EncryptionAtRest": {
```

```
        "DataVolumeKMSKeyId": "string"
      },
      "EncryptionInTransit": {
        "ClientBroker": "string",
        "InCluster": boolean
      }
    },
    "EnhancedMonitoring": "string",
    "NumberOfBrokerNodes": number
  }
},
"AwsNetworkFirewallFirewall": {
  "DeleteProtection": boolean,
  "Description": "string",
  "FirewallArn": "string",
  "FirewallId": "string",
  "FirewallName": "string",
  "FirewallPolicyArn": "string",
  "FirewallPolicyChangeProtection": boolean,
  "SubnetChangeProtection": boolean,
  "SubnetMappings": [
    {
      "SubnetId": "string"
    }
  ],
  "VpcId": "string"
},
"AwsNetworkFirewallFirewallPolicy": {
  "Description": "string",
  "FirewallPolicy": {
    "StatefulRuleGroupReferences": [
      {
        "ResourceArn": "string"
      }
    ],
    "StatelessCustomActions": [
      {
        "ActionDefinition": {
          "PublishMetricAction": {
            "Dimensions": [
              {
                "Value": "string"
              }
            ]
          }
        }
      }
    ]
  }
}
```

```

    }
    },
    "ActionName": "string"
  }
],
"StatelessDefaultActions": [ "string" ],
"StatelessFragmentDefaultActions": [ "string" ],
"StatelessRuleGroupReferences": [
  {
    "Priority": number,
    "ResourceArn": "string"
  }
],
},
"FirewallPolicyArn": "string",
"FirewallPolicyId": "string",
"FirewallPolicyName": "string"
},
"AwsNetworkFirewallRuleGroup": {
  "Capacity": number,
  "Description": "string",
  "RuleGroup": {
    "RulesSource": {
      "RulesSourceList": {
        "GeneratedRulesType": "string",
        "Targets": [ "string" ],
        "TargetTypes": [ "string" ]
      },
      "RulesString": "string",
      "StatefulRules": [
        {
          "Action": "string",
          "Header": {
            "Destination": "string",
            "DestinationPort": "string",
            "Direction": "string",
            "Protocol": "string",
            "Source": "string",
            "SourcePort": "string"
          },
          "RuleOptions": [
            {
              "Keyword": "string",
              "Settings": [ "string" ]
            }
          ]
        }
      ]
    }
  }
}

```

```
    }
  ]
}
],
"StatelessRulesAndCustomActions": {
  "CustomActions": [
    {
      "ActionDefinition": {
        "PublishMetricAction": {
          "Dimensions": [
            {
              "Value": "string"
            }
          ]
        }
      },
      "ActionName": "string"
    }
  ],
  "StatelessRules": [
    {
      "Priority": number,
      "RuleDefinition": {
        "Actions": [ "string" ],
        "MatchAttributes": {
          "DestinationPorts": [
            {
              "FromPort": number,
              "ToPort": number
            }
          ],
          "Destinations": [
            {
              "AddressDefinition": "string"
            }
          ],
          "Protocols": [ number ],
          "SourcePorts": [
            {
              "FromPort": number,
              "ToPort": number
            }
          ],
          "Sources": [
```



```

        {
            "AddressDefinition": "string"
        }
    ],
    "TcpFlags": [
        {
            "Flags": [ "string" ],
            "Masks": [ "string" ]
        }
    ]
}
}
}
}
},
"RuleVariables": {
    "IpSets": {
        "Definition": [ "string" ]
    },
    "PortSets": {
        "Definition": [ "string" ]
    }
}
},
"RuleGroupArn": "string",
"RuleGroupId": "string",
"RuleGroupName": "string",
"Type": "string"
},
"AwsOpenSearchServiceDomain": {
    "AccessPolicies": "string",
    "AdvancedSecurityOptions": {
        "Enabled": boolean,
        "InternalUserDatabaseEnabled": boolean,
        "MasterUserOptions": {
            "MasterUserArn": "string",
            "MasterUserName": "string",
            "MasterUserPassword": "string"
        }
    }
},
"Arn": "string",
"ClusterConfig": {
    "DedicatedMasterCount": number,

```

```
    "DedicatedMasterEnabled": boolean,
    "DedicatedMasterType": "string",
    "InstanceCount": number,
    "InstanceType": "string",
    "WarmCount": number,
    "WarmEnabled": boolean,
    "WarmType": "string",
    "ZoneAwarenessConfig": {
      "AvailabilityZoneCount": number
    },
    "ZoneAwarenessEnabled": boolean
  },
  "DomainEndpoint": "string",
  "DomainEndpointOptions": {
    "CustomEndpoint": "string",
    "CustomEndpointCertificateArn": "string",
    "CustomEndpointEnabled": boolean,
    "EnforceHTTPS": boolean,
    "TLSSecurityPolicy": "string"
  },
  "DomainEndpoints": {
    "string" : "string"
  },
  "DomainName": "string",
  "EncryptionAtRestOptions": {
    "Enabled": boolean,
    "KmsKeyId": "string"
  },
  "EngineVersion": "string",
  "Id": "string",
  "LogPublishingOptions": {
    "AuditLogs": {
      "CloudWatchLogsLogGroupArn": "string",
      "Enabled": boolean
    },
    "IndexSlowLogs": {
      "CloudWatchLogsLogGroupArn": "string",
      "Enabled": boolean
    },
    "SearchSlowLogs": {
      "CloudWatchLogsLogGroupArn": "string",
      "Enabled": boolean
    }
  }
},
```

```
"NodeToNodeEncryptionOptions": {
  "Enabled": boolean
},
"ServiceSoftwareOptions": {
  "AutomatedUpdateDate": "string",
  "Cancellable": boolean,
  "CurrentVersion": "string",
  "Description": "string",
  "NewVersion": "string",
  "OptionalDeployment": boolean,
  "UpdateAvailable": boolean,
  "UpdateStatus": "string"
},
"VpcOptions": {
  "SecurityGroupIds": [ "string" ],
  "SubnetIds": [ "string" ]
}
},
"AwsRdsDbCluster": {
  "ActivityStreamStatus": "string",
  "AllocatedStorage": number,
  "AssociatedRoles": [
    {
      "RoleArn": "string",
      "Status": "string"
    }
  ],
  "AutoMinorVersionUpgrade": boolean,
  "AvailabilityZones": [ "string" ],
  "BackupRetentionPeriod": number,
  "ClusterCreateTime": "string",
  "CopyTagsToSnapshot": boolean,
  "CrossAccountClone": boolean,
  "CustomEndpoints": [ "string" ],
  "DatabaseName": "string",
  "DbClusterIdentifier": "string",
  "DbClusterMembers": [
    {
      "DbClusterParameterGroupStatus": "string",
      "DbInstanceIdentifier": "string",
      "IsClusterWriter": boolean,
      "PromotionTier": number
    }
  ]
},
```

```
"DbClusterOptionGroupMemberships": [
  {
    "DbClusterOptionGroupName": "string",
    "Status": "string"
  }
],
"DbClusterParameterGroup": "string",
"DbClusterResourceId": "string",
"DbSubnetGroup": "string",
"DeletionProtection": boolean,
"DomainMemberships": [
  {
    "Domain": "string",
    "Fqdn": "string",
    "IamRoleName": "string",
    "Status": "string"
  }
],
"EnabledCloudWatchLogsExports": [ "string" ],
"Endpoint": "string",
"Engine": "string",
"EngineMode": "string",
"EngineVersion": "string",
"HostedZoneId": "string",
"HttpEndpointEnabled": boolean,
"IamDatabaseAuthenticationEnabled": boolean,
"KmsKeyId": "string",
"MasterUsername": "string",
"MultiAz": boolean,
"Port": number,
"PreferredBackupWindow": "string",
"PreferredMaintenanceWindow": "string",
"ReaderEndpoint": "string",
"ReadReplicaIdentifiers": [ "string" ],
"Status": "string",
"StorageEncrypted": boolean,
"VpcSecurityGroups": [
  {
    "Status": "string",
    "VpcSecurityGroupId": "string"
  }
]
},
"AwsRdsDbClusterSnapshot": {
```

```
"AllocatedStorage": number,
"AvailabilityZones": [ "string" ],
"ClusterCreateTime": "string",
"DbClusterIdentifier": "string",
"DbClusterSnapshotAttributes": [
  {
    "AttributeName": "string",
    "AttributeValues": [ "string" ]
  }
],
"DbClusterSnapshotIdentifier": "string",
"Engine": "string",
"EngineVersion": "string",
"IamDatabaseAuthenticationEnabled": boolean,
"KmsKeyId": "string",
"LicenseModel": "string",
"MasterUsername": "string",
"PercentProgress": number,
"Port": number,
"SnapshotCreateTime": "string",
"SnapshotType": "string",
"Status": "string",
"StorageEncrypted": boolean,
"VpcId": "string"
},
"AwsRdsDbInstance": {
  "AllocatedStorage": number,
  "AssociatedRoles": [
    {
      "FeatureName": "string",
      "RoleArn": "string",
      "Status": "string"
    }
  ],
  "AutoMinorVersionUpgrade": boolean,
  "AvailabilityZone": "string",
  "BackupRetentionPeriod": number,
  "CACertificateIdentifier": "string",
  "CharacterSetName": "string",
  "CopyTagsToSnapshot": boolean,
  "DBClusterIdentifier": "string",
  "DBInstanceClass": "string",
  "DBInstanceIdentifier": "string",
  "DbInstancePort": number,
```

```
"DbInstanceStatus": "string",
"DbiResourceId": "string",
"DBName": "string",
"DbParameterGroups": [
  {
    "DbParameterGroupName": "string",
    "ParameterApplyStatus": "string"
  }
],
"DbSecurityGroups": [ "string" ],
"DbSubnetGroup": {
  "DbSubnetGroupArn": "string",
  "DbSubnetGroupDescription": "string",
  "DbSubnetGroupName": "string",
  "SubnetGroupStatus": "string",
  "Subnets": [
    {
      "SubnetAvailabilityZone": {
        "Name": "string"
      },
      "SubnetIdentifier": "string",
      "SubnetStatus": "string"
    }
  ],
  "VpcId": "string"
},
"DeletionProtection": boolean,
"DomainMemberships": [
  {
    "Domain": "string",
    "Fqdn": "string",
    "IamRoleName": "string",
    "Status": "string"
  }
],
"EnabledCloudWatchLogsExports": [ "string" ],
"Endpoint": {
  "Address": "string",
  "HostedZoneId": "string",
  "Port": number
},
"Engine": "string",
"EngineVersion": "string",
"EnhancedMonitoringResourceArn": "string",
```

```
"IAMDatabaseAuthenticationEnabled": boolean,
"InstanceCreateTime": "string",
"Iops": number,
"KmsKeyId": "string",
"LatestRestorableTime": "string",
"LicenseModel": "string",
"ListenerEndpoint": {
  "Address": "string",
  "HostedZoneId": "string",
  "Port": number
},
"MasterUsername": "string",
"MaxAllocatedStorage": number,
"MonitoringInterval": number,
"MonitoringRoleArn": "string",
"MultiAz": boolean,
"OptionGroupMemberships": [
  {
    "OptionGroupName": "string",
    "Status": "string"
  }
],
"PendingModifiedValues": {
  "AllocatedStorage": number,
  "BackupRetentionPeriod": number,
  "CaCertificateIdentifier": "string",
  "DbInstanceClass": "string",
  "DbInstanceIdentifier": "string",
  "DbSubnetGroupName": "string",
  "EngineVersion": "string",
  "Iops": number,
  "LicenseModel": "string",
  "MasterUserPassword": "string",
  "MultiAZ": boolean,
  "PendingCloudWatchLogsExports": {
    "LogTypesToDisable": [ "string" ],
    "LogTypesToEnable": [ "string" ]
  },
  "Port": number,
  "ProcessorFeatures": [
    {
      "Name": "string",
      "Value": "string"
    }
  ]
}
```

```
    ],
    "StorageType": "string"
  },
  "PerformanceInsightsEnabled": boolean,
  "PerformanceInsightsKmsKeyId": "string",
  "PerformanceInsightsRetentionPeriod": number,
  "PreferredBackupWindow": "string",
  "PreferredMaintenanceWindow": "string",
  "ProcessorFeatures": [
    {
      "Name": "string",
      "Value": "string"
    }
  ],
  "PromotionTier": number,
  "PubliclyAccessible": boolean,
  "ReadReplicaDBClusterIdentifiers": [ "string" ],
  "ReadReplicaDBInstanceIdentifiers": [ "string" ],
  "ReadReplicaSourceDBInstanceIdentifier": "string",
  "SecondaryAvailabilityZone": "string",
  "StatusInfos": [
    {
      "Message": "string",
      "Normal": boolean,
      "Status": "string",
      "StatusType": "string"
    }
  ],
  "StorageEncrypted": boolean,
  "StorageType": "string",
  "TdeCredentialArn": "string",
  "Timezone": "string",
  "VpcSecurityGroups": [
    {
      "Status": "string",
      "VpcSecurityGroupId": "string"
    }
  ]
},
"AwsRdsDbSecurityGroup": {
  "DbSecurityGroupArn": "string",
  "DbSecurityGroupDescription": "string",
  "DbSecurityGroupName": "string",
  "Ec2SecurityGroups": [
```



```
    {
      "Ec2SecurityGroupId": "string",
      "Ec2SecurityGroupName": "string",
      "Ec2SecurityGroupOwnerId": "string",
      "Status": "string"
    }
  ],
  "IpRanges": [
    {
      "CidrIp": "string",
      "Status": "string"
    }
  ],
  "OwnerId": "string",
  "VpcId": "string"
},
"AwsRdsDbSnapshot": {
  "AllocatedStorage": number,
  "AvailabilityZone": "string",
  "DbInstanceIdentifier": "string",
  "DbiResourceId": "string",
  "DbSnapshotIdentifier": "string",
  "Encrypted": boolean,
  "Engine": "string",
  "EngineVersion": "string",
  "IamDatabaseAuthenticationEnabled": boolean,
  "InstanceCreateTime": "string",
  "Iops": number,
  "KmsKeyId": "string",
  "LicenseModel": "string",
  "MasterUsername": "string",
  "OptionGroupName": "string",
  "PercentProgress": number,
  "Port": number,
  "ProcessorFeatures": [
    {
      "Name": "string",
      "Value": "string"
    }
  ],
  "SnapshotCreateTime": "string",
  "SnapshotType": "string",
  "SourceDbSnapshotIdentifier": "string",
  "SourceRegion": "string",
```

```
    "Status": "string",
    "StorageType": "string",
    "TdeCredentialArn": "string",
    "Timezone": "string",
    "VpcId": "string"
  },
  "AwsRdsEventSubscription": {
    "CustomerAwsId": "string",
    "CustSubscriptionId": "string",
    "Enabled": boolean,
    "EventCategoriesList": [ "string" ],
    "EventSubscriptionArn": "string",
    "SnsTopicArn": "string",
    "SourceIdsList": [ "string" ],
    "SourceType": "string",
    "Status": "string",
    "SubscriptionCreationTime": "string"
  },
  "AwsRedshiftCluster": {
    "AllowVersionUpgrade": boolean,
    "AutomatedSnapshotRetentionPeriod": number,
    "AvailabilityZone": "string",
    "ClusterAvailabilityStatus": "string",
    "ClusterCreateTime": "string",
    "ClusterIdentifier": "string",
    "ClusterNodes": [
      {
        "NodeRole": "string",
        "PrivateIpAddress": "string",
        "PublicIpAddress": "string"
      }
    ],
    "ClusterParameterGroups": [
      {
        "ClusterParameterStatusList": [
          {
            "ParameterApplyErrorDescription": "string",
            "ParameterApplyStatus": "string",
            "ParameterName": "string"
          }
        ],
        "ParameterApplyStatus": "string",
        "ParameterGroupName": "string"
      }
    ]
  }
}
```

```
],
  "ClusterPublicKey": "string",
  "ClusterRevisionNumber": "string",
  "ClusterSecurityGroups": [
    {
      "ClusterSecurityGroupName": "string",
      "Status": "string"
    }
  ],
  "ClusterSnapshotCopyStatus": {
    "DestinationRegion": "string",
    "ManualSnapshotRetentionPeriod": number,
    "RetentionPeriod": number,
    "SnapshotCopyGrantName": "string"
  },
  "ClusterStatus": "string",
  "ClusterSubnetGroupName": "string",
  "ClusterVersion": "string",
  "DBName": "string",
  "DeferredMaintenanceWindows": [
    {
      "DeferMaintenanceEndTime": "string",
      "DeferMaintenanceIdentifier": "string",
      "DeferMaintenanceStartTime": "string"
    }
  ],
  "ElasticIpStatus": {
    "ElasticIp": "string",
    "Status": "string"
  },
  "ElasticResizeNumberOfNodeOptions": "string",
  "Encrypted": boolean,
  "Endpoint": {
    "Address": "string",
    "Port": number
  },
  "EnhancedVpcRouting": boolean,
  "ExpectedNextSnapshotScheduleTime": "string",
  "ExpectedNextSnapshotScheduleTimeStatus": "string",
  "HsmStatus": {
    "HsmClientCertificateIdentifier": "string",
    "HsmConfigurationIdentifier": "string",
    "Status": "string"
  },
}
```

```
"IamRoles": [
  {
    "ApplyStatus": "string",
    "IamRoleArn": "string"
  }
],
"KmsKeyId": "string",
"LoggingStatus": {
  "BucketName": "string",
  "LastFailureMessage": "string",
  "LastFailureTime": "string",
  "LastSuccessfulDeliveryTime": "string",
  "LoggingEnabled": boolean,
  "S3KeyPrefix": "string"
},
"MaintenanceTrackName": "string",
"ManualSnapshotRetentionPeriod": number,
"MasterUsername": "string",
"NextMaintenanceWindowStartTime": "string",
"NodeType": "string",
"NumberOfNodes": number,
"PendingActions": [ "string" ],
"PendingModifiedValues": {
  "AutomatedSnapshotRetentionPeriod": number,
  "ClusterIdentifier": "string",
  "ClusterType": "string",
  "ClusterVersion": "string",
  "EncryptionType": "string",
  "EnhancedVpcRouting": boolean,
  "MaintenanceTrackName": "string",
  "MasterUserPassword": "string",
  "NodeType": "string",
  "NumberOfNodes": number,
  "PubliclyAccessible": boolean
},
"PreferredMaintenanceWindow": "string",
"PubliclyAccessible": boolean,
"ResizeInfo": {
  "AllowCancelResize": boolean,
  "ResizeType": "string"
},
"RestoreStatus": {
  "CurrentRestoreRateInMegaBytesPerSecond": number,
  "ElapsedTimeInSeconds": number,
```

```
    "EstimatedTimeToCompletionInSeconds": number,
    "ProgressInMegaBytes": number,
    "SnapshotSizeInMegaBytes": number,
    "Status": "string"
  },
  "SnapshotScheduleIdentifier": "string",
  "SnapshotScheduleState": "string",
  "VpcId": "string",
  "VpcSecurityGroups": [
    {
      "Status": "string",
      "VpcSecurityGroupId": "string"
    }
  ]
},
"AwsRoute53HostedZone": {
  "HostedZone": {
    "Config": {
      "Comment": "string"
    },
    "Id": "string",
    "Name": "string"
  },
  "NameServers": [ "string" ],
  "QueryLoggingConfig": {
    "CloudWatchLogsLogGroupArn": {
      "CloudWatchLogsLogGroupArn": "string",
      "HostedZoneId": "string",
      "Id": "string"
    }
  },
  "Vpcs": [
    {
      "Id": "string",
      "Region": "string"
    }
  ]
},
"AwsS3AccessPoint": {
  "AccessPointArn": "string",
  "Alias": "string",
  "Bucket": "string",
  "BucketAccountId": "string",
  "Name": "string",
```

```
"NetworkOrigin": "string",
"PublicAccessBlockConfiguration": {
  "BlockPublicAcls": boolean,
  "BlockPublicPolicy": boolean,
  "IgnorePublicAcls": boolean,
  "RestrictPublicBuckets": boolean
},
"VpcConfiguration": {
  "VpcId": "string"
}
},
"AwsS3AccountPublicAccessBlock": {
  "BlockPublicAcls": boolean,
  "BlockPublicPolicy": boolean,
  "IgnorePublicAcls": boolean,
  "RestrictPublicBuckets": boolean
},
"AwsS3Bucket": {
  "AccessControlList": "string",
  "BucketLifecycleConfiguration": {
    "Rules": [
      {
        "AbortIncompleteMultipartUpload": {
          "DaysAfterInitiation": number
        },
        "ExpirationDate": "string",
        "ExpirationInDays": number,
        "ExpiredObjectDeleteMarker": boolean,
        "Filter": {
          "Predicate": {
            "Operands": [
              {
                "Prefix": "string",
                "Tag": {
                  "Key": "string",
                  "Value": "string"
                },
                "Type": "string"
              }
            ],
            "Prefix": "string",
            "Tag": {
              "Key": "string",
              "Value": "string"
            }
          }
        }
      }
    ]
  }
}
```

```

        },
        "Type": "string"
    }
},
"ID": "string",
"NoncurrentVersionExpirationInDays": number,
"NoncurrentVersionTransitions": [
    {
        "Days": number,
        "StorageClass": "string"
    }
],
"Prefix": "string",
"Status": "string",
"Transitions": [
    {
        "Date": "string",
        "Days": number,
        "StorageClass": "string"
    }
]
}
]
},
"BucketLoggingConfiguration": {
    "DestinationBucketName": "string",
    "LogFilePrefix": "string"
},
"BucketNotificationConfiguration": {
    "Configurations": [
        {
            "Destination": "string",
            "Events": [ "string" ],
            "Filter": {
                "S3KeyFilter": {
                    "FilterRules": [
                        {
                            "Name": "string",
                            "Value": "string"
                        }
                    ]
                }
            }
        }
    ]
},
"Type": "string"

```

```

    }
  ]
},
"BucketVersioningConfiguration": {
  "IsMfaDeleteEnabled": boolean,
  "Status": "string"
},
"BucketWebsiteConfiguration": {
  "ErrorDocument": "string",
  "IndexDocumentSuffix": "string",
  "RedirectAllRequestsTo": {
    "Hostname": "string",
    "Protocol": "string"
  },
  "RoutingRules": [
    {
      "Condition": {
        "HttpErrorCodeReturnedEquals": "string",
        "KeyPrefixEquals": "string"
      },
      "Redirect": {
        "Hostname": "string",
        "HttpRedirectCode": "string",
        "Protocol": "string",
        "ReplaceKeyPrefixWith": "string",
        "ReplaceKeyWith": "string"
      }
    }
  ]
},
"CreatedAt": "string",
"Name": "string",
"ObjectLockConfiguration": {
  "ObjectLockEnabled": "string",
  "Rule": {
    "DefaultRetention": {
      "Days": number,
      "Mode": "string",
      "Years": number
    }
  }
},
"OwnerAccountId": "string",
"OwnerId": "string",

```



```

"OwnerName": "string",
"PublicAccessBlockConfiguration": {
  "BlockPublicAcls": boolean,
  "BlockPublicPolicy": boolean,
  "IgnorePublicAcls": boolean,
  "RestrictPublicBuckets": boolean
},
"ServerSideEncryptionConfiguration": {
  "Rules": [
    {
      "ApplyServerSideEncryptionByDefault": {
        "KMSEncryptionKeyId": "string",
        "SSEAlgorithm": "string"
      }
    }
  ]
},
"AwsS3Object": {
  "ContentType": "string",
  "ETag": "string",
  "LastModified": "string",
  "ServerSideEncryption": "string",
  "SSEKMSKeyId": "string",
  "VersionId": "string"
},
"AwsSageMakerNotebookInstance": {
  "AcceleratorTypes": [ "string" ],
  "AdditionalCodeRepositories": [ "string" ],
  "DefaultCodeRepository": "string",
  "DirectInternetAccess": "string",
  "FailureReason": "string",
  "InstanceMetadataServiceConfiguration": {
    "MinimumInstanceMetadataServiceVersion": "string"
  },
  "InstanceType": "string",
  "KmsKeyId": "string",
  "NetworkInterfaceId": "string",
  "NotebookInstanceArn": "string",
  "NotebookInstanceLifecycleConfigName": "string",
  "NotebookInstanceName": "string",
  "NotebookInstanceStatus": "string",
  "PlatformIdentifier": "string",
  "RoleArn": "string",

```

```
    "RootAccess": "string",
    "SecurityGroups": [ "string" ],
    "SubnetId": "string",
    "Url": "string",
    "VolumeSizeInGB": number
  },
  "AwsSecretsManagerSecret": {
    "Deleted": boolean,
    "Description": "string",
    "KmsKeyId": "string",
    "Name": "string",
    "RotationEnabled": boolean,
    "RotationLambdaArn": "string",
    "RotationOccurredWithinFrequency": boolean,
    "RotationRules": {
      "AutomaticallyAfterDays": number
    }
  },
  "AwsSnsTopic": {
    "ApplicationSuccessFeedbackRoleArn": "string",
    "FirehoseFailureFeedbackRoleArn": "string",
    "FirehoseSuccessFeedbackRoleArn": "string",
    "HttpFailureFeedbackRoleArn": "string",
    "HttpSuccessFeedbackRoleArn": "string",
    "KmsMasterKeyId": "string",
    "Owner": "string",
    "SqsFailureFeedbackRoleArn": "string",
    "SqsSuccessFeedbackRoleArn": "string",
    "Subscription": [
      {
        "Endpoint": "string",
        "Protocol": "string"
      }
    ],
    "TopicName": "string"
  },
  "AwsSqsQueue": {
    "DeadLetterTargetArn": "string",
    "KmsDataKeyReusePeriodSeconds": number,
    "KmsMasterKeyId": "string",
    "QueueName": "string"
  },
  "AwsSsmPatchCompliance": {
    "Patch": {
```

```
    "ComplianceSummary": {
      "ComplianceType": "string",
      "CompliantCriticalCount": number,
      "CompliantHighCount": number,
      "CompliantInformationalCount": number,
      "CompliantLowCount": number,
      "CompliantMediumCount": number,
      "CompliantUnspecifiedCount": number,
      "ExecutionType": "string",
      "NonCompliantCriticalCount": number,
      "NonCompliantHighCount": number,
      "NonCompliantInformationalCount": number,
      "NonCompliantLowCount": number,
      "NonCompliantMediumCount": number,
      "NonCompliantUnspecifiedCount": number,
      "OverallSeverity": "string",
      "PatchBaselineId": "string",
      "PatchGroup": "string",
      "Status": "string"
    }
  },
  "AwsStepFunctionStateMachine": {
    "Label": "string",
    "LoggingConfiguration": {
      "Destinations": [
        {
          "CloudWatchLogsLogGroup": {
            "LogGroupArn": "string"
          }
        }
      ],
      "IncludeExecutionData": boolean,
      "Level": "string"
    },
    "Name": "string",
    "RoleArn": "string",
    "StateMachineArn": "string",
    "Status": "string",
    "TracingConfiguration": {
      "Enabled": boolean
    },
    "Type": "string"
  },
}
```

```
"AwsWafRateBasedRule": {
  "MatchPredicates": [
    {
      "DataId": "string",
      "Negated": boolean,
      "Type": "string"
    }
  ],
  "MetricName": "string",
  "Name": "string",
  "RateKey": "string",
  "RateLimit": number,
  "RuleId": "string"
},
"AwsWafRegionalRateBasedRule": {
  "MatchPredicates": [
    {
      "DataId": "string",
      "Negated": boolean,
      "Type": "string"
    }
  ],
  "MetricName": "string",
  "Name": "string",
  "RateKey": "string",
  "RateLimit": number,
  "RuleId": "string"
},
"AwsWafRegionalRule": {
  "MetricName": "string",
  "Name": "string",
  "PredicateList": [
    {
      "DataId": "string",
      "Negated": boolean,
      "Type": "string"
    }
  ],
  "RuleId": "string"
},
"AwsWafRegionalRuleGroup": {
  "MetricName": "string",
  "Name": "string",
  "RuleGroupId": "string",
```

```
"Rules": [  
  {  
    "Action": {  
      "Type": "string"  
    },  
    "Priority": number,  
    "RuleId": "string",  
    "Type": "string"  
  }  
],  
{  
  "AwsWafRegionalWebAcl": {  
    "DefaultAction": "string",  
    "MetricName": "string",  
    "Name": "string",  
    "RulesList": [  
      {  
        "Action": {  
          "Type": "string"  
        },  
        "OverrideAction": {  
          "Type": "string"  
        },  
        "Priority": number,  
        "RuleId": "string",  
        "Type": "string"  
      }  
    ],  
    "WebAclId": "string"  
  },  
  "AwsWafRule": {  
    "MetricName": "string",  
    "Name": "string",  
    "PredicateList": [  
      {  
        "DataId": "string",  
        "Negated": boolean,  
        "Type": "string"  
      }  
    ],  
    "RuleId": "string"  
  },  
  "AwsWafRuleGroup": {  
    "MetricName": "string",
```

```
"Name": "string",
"RuleGroupId": "string",
"Rules": [
  {
    "Action": {
      "Type": "string"
    },
    "Priority": number,
    "RuleId": "string",
    "Type": "string"
  }
],
},
"AwsWafv2RuleGroup": {
  "Arn": "string",
  "Capacity": number,
  "Description": "string",
  "Id": "string",
  "Name": "string",
  "Rules": [
    {
      "Action": {
        "Allow": {
          "CustomRequestHandling": {
            "InsertHeaders": [
              {
                "Name": "string",
                "Value": "string"
              }
            ]
          }
        },
        "Block": {
          "CustomResponse": {
            "CustomResponseBodyKey": "string",
            "ResponseCode": number,
            "ResponseHeaders": [
              {
                "Name": "string",
                "Value": "string"
              }
            ]
          }
        }
      }
    }
  ],
}
```

```

    "Captcha": {
      "CustomRequestHandling": {
        "InsertHeaders": [
          {
            "Name": "string",
            "Value": "string"
          }
        ]
      }
    },
    "Count": {
      "CustomRequestHandling": {
        "InsertHeaders": [
          {
            "Name": "string",
            "Value": "string"
          }
        ]
      }
    }
  },
  "Name": "string",
  "OverrideAction": "string",
  "Priority": number,
  "VisibilityConfig": {
    "CloudWatchMetricsEnabled": boolean,
    "MetricName": "string",
    "SampledRequestsEnabled": boolean
  }
}
],
"Scope": "string",
"VisibilityConfig": {
  "CloudWatchMetricsEnabled": boolean,
  "MetricName": "string",
  "SampledRequestsEnabled": boolean
}
},
"AwsWafv2WebAcl": {
  "Arn": "string",
  "Capacity": number,
  "CaptchaConfig": {
    "ImmunityTimeProperty": {
      "ImmunityTime": number
    }
  }
}

```

```
    }
  },
  "DefaultAction": {
    "Allow": {
      "CustomRequestHandling": {
        "InsertHeaders": [
          {
            "Name": "string",
            "Value": "string"
          }
        ]
      }
    },
    "Block": {
      "CustomResponse": {
        "CustomResponseBodyKey": "string",
        "ResponseCode": number,
        "ResponseHeaders": [
          {
            "Name": "string",
            "Value": "string"
          }
        ]
      }
    }
  },
  "Description": "string",
  "Id": "string",
  "ManagedbyFirewallManager": boolean,
  "Name": "string",
  "Rules": [
    {
      "Action": {
        "Allow": {
          "CustomRequestHandling": {
            "InsertHeaders": [
              {
                "Name": "string",
                "Value": "string"
              }
            ]
          }
        },
        "Block": {
```



```
    "CustomResponse": {
      "CustomResponseBodyKey": "string",
      "ResponseCode": number,
      "ResponseHeaders": [
        {
          "Name": "string",
          "Value": "string"
        }
      ]
    },
    "Captcha": {
      "CustomRequestHandling": {
        "InsertHeaders": [
          {
            "Name": "string",
            "Value": "string"
          }
        ]
      }
    },
    "Count": {
      "CustomRequestHandling": {
        "InsertHeaders": [
          {
            "Name": "string",
            "Value": "string"
          }
        ]
      }
    }
  ],
  "Name": "string",
  "OverrideAction": "string",
  "Priority": number,
  "VisibilityConfig": {
    "CloudWatchMetricsEnabled": boolean,
    "MetricName": "string",
    "SampledRequestsEnabled": boolean
  }
},
"VisibilityConfig": {
  "CloudWatchMetricsEnabled": boolean,
```

```
        "MetricName": "string",
        "SampledRequestsEnabled": boolean
    }
},
"AwsWafWebAcl": {
    "DefaultAction": "string",
    "Name": "string",
    "Rules": [
        {
            "Action": {
                "Type": "string"
            },
            "ExcludedRules": [
                {
                    "RuleId": "string"
                }
            ],
            "OverrideAction": {
                "Type": "string"
            },
            "Priority": number,
            "RuleId": "string",
            "Type": "string"
        }
    ],
    "WebAclId": "string"
},
"AwsXrayEncryptionConfig": {
    "KeyId": "string",
    "Status": "string",
    "Type": "string"
},
"Container": {
    "ContainerRuntime": "string",
    "ImageId": "string",
    "ImageName": "string",
    "LaunchedAt": "string",
    "Name": "string",
    "Privileged": boolean,
    "VolumeMounts": [
        {
            "MountPath": "string",
            "Name": "string"
        }
    ]
}
```

```
    ]
  },
  "Other": {
    "string" : "string"
  }
},
"Id": "string",
"Partition": "string",
"Region": "string",
"ResourceRole": "string",
"Tags": {
  "string" : "string"
},
"Type": "string"
}
],
"Sample": boolean,
"SchemaVersion": "string",
"Severity": {
  "Label": "string",
  "Normalized": number,
  "Original": "string",
  "Product": number
},
"SourceUrl": "string",
"ThreatIntelIndicators": [
  {
    "Category": "string",
    "LastObservedAt": "string",
    "Source": "string",
    "SourceUrl": "string",
    "Type": "string",
    "Value": "string"
  }
],
"Threats": [
  {
    "FilePaths": [
      {
        "FileName": "string",
        "FilePath": "string",
        "Hash": "string",
        "ResourceId": "string"
      }
    ]
  }
]
```

```
    ],
    "ItemCount": number,
    "Name": "string",
    "Severity": "string"
  }
],
"Title": "string",
"Types": [ "string" ],
"UpdatedAt": "string",
"UserDefinedFields": {
  "string" : "string"
},
"VerificationState": "string",
"Vulnerabilities": [
  {
    "CodeVulnerabilities": [
      {
        "Cwes": [ "string" ],
        "FilePath": {
          "EndLine": number,
          "FileName": "string",
          "FilePath": "string",
          "StartLine": number
        },
        "SourceArn": "string"
      }
    ],
    "Cvss": [
      {
        "Adjustments": [
          {
            "Metric": "string",
            "Reason": "string"
          }
        ],
        "BaseScore": number,
        "BaseVector": "string",
        "Source": "string",
        "Version": "string"
      }
    ],
    "EpssScore": number,
    "ExploitAvailable": "string",
    "FixAvailable": "string",
```

```

    "Id": "string",
    "LastKnownExploitAt": "string",
    "ReferenceUrls": [ "string" ],
    "RelatedVulnerabilities": [ "string" ],
    "Vendor": {
      "Name": "string",
      "Url": "string",
      "VendorCreatedAt": "string",
      "VendorSeverity": "string",
      "VendorUpdatedAt": "string"
    },
    "VulnerablePackages": [
      {
        "Architecture": "string",
        "Epoch": "string",
        "FilePath": "string",
        "FixedInVersion": "string",
        "Name": "string",
        "PackageManager": "string",
        "Release": "string",
        "Remediation": "string",
        "SourceLayerArn": "string",
        "SourceLayerHash": "string",
        "Version": "string"
      }
    ]
  },
  "Workflow": {
    "Status": "string"
  },
  "WorkflowState": "string"
}
]
}

```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Findings

A list of findings to import. To successfully import a finding, it must follow the [Amazon Security Finding Format](#). Maximum of 100 findings per request.

Type: Array of [AwsSecurityFinding](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "FailedCount": number,
  "FailedFindings": [
    {
      "ErrorCode": "string",
      "ErrorMessage": "string",
      "Id": "string"
    }
  ],
  "SuccessCount": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[FailedCount](#)

The number of findings that failed to import.

Type: Integer

[FailedFindings](#)

The list of findings that failed to import.

Type: Array of [ImportFindingsError](#) objects

SuccessCount

The number of findings that were successfully imported.

Type: Integer

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

BatchUpdateAutomationRules

Updates one or more automation rules based on rule Amazon Resource Names (ARNs) and input parameters.

Request Syntax

```
PATCH /automationrules/update HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "UpdateAutomationRulesRequestItems": [
    {
      "Actions": [
        {
          "FindingFieldsUpdate": {
            "Confidence": number,
            "Criticality": number,
            "Note": {
              "Text": "string",
              "UpdatedBy": "string"
            },
            "RelatedFindings": [
              {
                "Id": "string",
                "ProductArn": "string"
              }
            ],
            "Severity": {
              "Label": "string",
              "Normalized": number,
              "Product": number
            },
            "Types": [ "string" ],
            "UserDefinedFields": {
              "string": "string"
            },
            "VerificationState": "string",
            "Workflow": {
              "Status": "string"
            }
          },
          "Type": "string"
        }
      ]
    }
  ]
}
```

```
    }
  ],
  "Criteria": {
    "AwsAccountId": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "AwsAccountName": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "CompanyName": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "ComplianceAssociatedStandardsId": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "ComplianceSecurityControlId": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "ComplianceStatus": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "Confidence": [
      {
        "Eq": number,
        "Gt": number,
        "Gte": number,
```

```
        "Lt": number,  
        "Lte": number  
    }  
],  
"CreatedAt": [  
    {  
        "DateRange": {  
            "Unit": "string",  
            "Value": number  
        },  
        "End": "string",  
        "Start": "string"  
    }  
],  
"Criticality": [  
    {  
        "Eq": number,  
        "Gt": number,  
        "Gte": number,  
        "Lt": number,  
        "Lte": number  
    }  
],  
"Description": [  
    {  
        "Comparison": "string",  
        "Value": "string"  
    }  
],  
"FirstObservedAt": [  
    {  
        "DateRange": {  
            "Unit": "string",  
            "Value": number  
        },  
        "End": "string",  
        "Start": "string"  
    }  
],  
"GeneratorId": [  
    {  
        "Comparison": "string",  
        "Value": "string"  
    }  
]
```

```
],
  "Id": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "LastObservedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "NoteText": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "NoteUpdatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "NoteUpdatedBy": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ProductArn": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ]
}
```

```
],
  "ProductName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "RecordState": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "RelatedFindingsId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "RelatedFindingsProductArn": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceApplicationArn": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceApplicationName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceDetailsOther": [
    {
      "Comparison": "string",
      "Key": "string",
      "Value": "string"
    }
  ],
],
```

```
"ResourceId": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourcePartition": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceRegion": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceTags": [  
  {  
    "Comparison": "string",  
    "Key": "string",  
    "Value": "string"  
  }  
],  
"ResourceType": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"SeverityLabel": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"SourceUrl": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"Title": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],
```

```
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Type": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "UpdatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "UserDefinedFields": [
    {
      "Comparison": "string",
      "Key": "string",
      "Value": "string"
    }
  ],
  "VerificationState": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "WorkflowStatus": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ]
],
"Description": "string",
"IsTerminal": boolean,
"RuleArn": "string",
```

```
    "RuleName": "string",
    "RuleOrder": number,
    "RuleStatus": "string"
  }
]
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

UpdateAutomationRulesRequestItems

An array of ARNs for the rules that are to be updated. Optionally, you can also include `RuleStatus` and `RuleOrder`.

Type: Array of [UpdateAutomationRulesRequestItem](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ProcessedAutomationRules": [ "string" ],
  "UnprocessedAutomationRules": [
    {
      "ErrorCode": number,
      "ErrorMessage": "string",
      "RuleArn": "string"
    }
  ]
}
```


Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ProcessedAutomationRules

A list of properly processed rule ARNs.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Pattern: `.*\S.*`

UnprocessedAutomationRules

A list of objects containing `RuleArn`, `ErrorCode`, and `ErrorMessage`. This parameter tells you which automation rules the request didn't update and why.

Type: Array of [UnprocessedAutomationRule](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

BatchUpdateFindings

Used by Security Hub customers to update information about their investigation into a finding. Requested by administrator accounts or member accounts. Administrator accounts can update findings for their account and their member accounts. Member accounts can update findings for their account.

Updates from BatchUpdateFindings don't affect the value of UpdatedAt for a finding.

Administrator and member accounts can use BatchUpdateFindings to update the following finding fields and objects.

- Confidence
- Criticality
- Note
- RelatedFindings
- Severity
- Types
- UserDefinedFields
- VerificationState
- Workflow

You can configure IAM policies to restrict access to fields and field values. For example, you might not want member accounts to be able to suppress findings or change the finding severity. See [Configuring access to BatchUpdateFindings](#) in the *Amazon Security Hub User Guide*.

Request Syntax

```
PATCH /findings/batchupdate HTTP/1.1
Content-type: application/json
```

```
{
  "Confidence": number,
  "Criticality": number,
  "FindingIdentifiers": [
    {
      "Id": "string",
```

```
    "ProductArn": "string"
  }
],
"Note": {
  "Text": "string",
  "UpdatedBy": "string"
},
"RelatedFindings": [
  {
    "Id": "string",
    "ProductArn": "string"
  }
],
"Severity": {
  "Label": "string",
  "Normalized": number,
  "Product": number
},
"Types": [ "string" ],
"UserDefinedFields": {
  "string" : "string"
},
"VerificationState": "string",
"Workflow": {
  "Status": "string"
}
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Confidence

The updated value for the finding confidence. Confidence is defined as the likelihood that a finding accurately identifies the behavior or issue that it was intended to identify.

Confidence is scored on a 0-100 basis using a ratio scale, where 0 means zero percent confidence and 100 means 100 percent confidence.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

Criticality

The updated value for the level of importance assigned to the resources associated with the findings.

A score of 0 means that the underlying resources have no criticality, and a score of 100 is reserved for the most critical resources.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

FindingIdentifiers

The list of findings to update. `BatchUpdateFindings` can be used to update up to 100 findings at a time.

For each finding, the list provides the finding identifier and the ARN of the finding provider.

Type: Array of [AwsSecurityFindingIdentifier](#) objects

Required: Yes

Note

The updated note.

Type: [NoteUpdate](#) object

Required: No

RelatedFindings

A list of findings that are related to the updated findings.

Type: Array of [RelatedFinding](#) objects

Required: No

Severity

Used to update the finding severity.

Type: [SeverityUpdate](#) object

Required: No

Types

One or more finding types in the format of namespace/category/classifier that classify a finding.

Valid namespace values are as follows.

- Software and Configuration Checks
- TTPs
- Effects
- Unusual Behaviors
- Sensitive Data Identifications

Type: Array of strings

Pattern: `.*\S.*`

Required: No

UserDefinedFields

A list of name/value string pairs associated with the finding. These are custom, user-defined fields added to a finding.

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

VerificationState

Indicates the veracity of a finding.

The available values for `VerificationState` are as follows.

- UNKNOWN – The default disposition of a security finding
- TRUE_POSITIVE – The security finding is confirmed
- FALSE_POSITIVE – The security finding was determined to be a false alarm
- BENIGN_POSITIVE – A special case of TRUE_POSITIVE where the finding doesn't pose any threat, is expected, or both

Type: String

Valid Values: UNKNOWN | TRUE_POSITIVE | FALSE_POSITIVE | BENIGN_POSITIVE

Required: No

Workflow

Used to update the workflow status of a finding.

The workflow status indicates the progress of the investigation into the finding.

Type: [WorkflowUpdate](#) object

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ProcessedFindings": [
    {
      "Id": "string",
      "ProductArn": "string"
    }
  ],
  "UnprocessedFindings": [
    {
      "ErrorCode": "string",
      "ErrorMessage": "string",
      "FindingIdentifier": {
        "Id": "string",
```

```
        "ProductArn": "string"  
      }  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ProcessedFindings

The list of findings that were updated successfully.

Type: Array of [AwsSecurityFindingIdentifier](#) objects

UnprocessedFindings

The list of findings that were not updated.

Type: Array of [BatchUpdateFindingsUnprocessedFinding](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

BatchUpdateStandardsControlAssociations

For a batch of security controls and standards, this operation updates the enablement status of a control in a standard.

Request Syntax

```
PATCH /associations HTTP/1.1
Content-type: application/json

{
  "StandardsControlAssociationUpdates": [
    {
      "AssociationStatus": "string",
      "SecurityControlId": "string",
      "StandardsArn": "string",
      "UpdatedReason": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

StandardsControlAssociationUpdates

Updates the enablement status of a security control in a specified standard.

Calls to this operation return a RESOURCE_NOT_FOUND_EXCEPTION error when the standard subscription for the control has StandardsControlsUpdatable value NOT_READY_FOR_UPDATES.

Type: Array of [StandardsControlAssociationUpdate](#) objects

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "UnprocessedAssociationUpdates": [
    {
      "ErrorCode": "string",
      "ErrorReason": "string",
      "StandardsControlAssociationUpdate": {
        "AssociationStatus": "string",
        "SecurityControlId": "string",
        "StandardsArn": "string",
        "UpdatedReason": "string"
      }
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

UnprocessedAssociationUpdates

A security control (identified with `SecurityControlId`, `SecurityControlArn`, or a mix of both parameters) whose enablement status in a specified standard couldn't be updated.

Type: Array of [UnprocessedStandardsControlAssociationUpdate](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

CreateActionTarget

Creates a custom action target in Security Hub.

You can use custom actions on findings and insights in Security Hub to trigger target actions in Amazon CloudWatch Events.

Request Syntax

```
POST /actionTargets HTTP/1.1
Content-type: application/json
```

```
{
  "Description": "string",
  "Id": "string",
  "Name": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Description

The description for the custom action target.

Type: String

Pattern: `.*\S.*`

Required: Yes

Id

The ID for the custom action target. Can contain up to 20 alphanumeric characters.

Type: String

Pattern: `.*\S.*`

Required: Yes

Name

The name of the custom action target. Can contain up to 20 characters.

Type: String

Pattern: `.*\S.*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ActionTargetArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ActionTargetArn

The Amazon Resource Name (ARN) for the custom action target.

Type: String

Pattern: `.*\S.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceConflictException

The resource specified in the request conflicts with an existing resource.

HTTP Status Code: 409

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)

- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateAutomationRule

Creates an automation rule based on input parameters.

Request Syntax

```
POST /automationrules/create HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "Actions": [
    {
      "FindingFieldsUpdate": {
        "Confidence": number,
        "Criticality": number,
        "Note": {
          "Text": "string",
          "UpdatedBy": "string"
        },
        "RelatedFindings": [
          {
            "Id": "string",
            "ProductArn": "string"
          }
        ],
        "Severity": {
          "Label": "string",
          "Normalized": number,
          "Product": number
        },
        "Types": [ "string" ],
        "UserDefinedFields": {
          "string" : "string"
        },
        "VerificationState": "string",
        "Workflow": {
          "Status": "string"
        }
      },
      "Type": "string"
    }
  ],
  "Criteria": {
```

```
"AwsAccountId": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"AwsAccountName": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"CompanyName": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ComplianceAssociatedStandardsId": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ComplianceSecurityControlId": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ComplianceStatus": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"Confidence": [  
  {  
    "Eq": number,  
    "Gt": number,  
    "Gte": number,  
    "Lt": number,  
    "Lte": number  
  }  
]
```

```
],
  "CreatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "Criticality": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "Description": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "FirstObservedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "GeneratorId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Id": [
    {
```

```
    "Comparison": "string",
    "Value": "string"
  }
],
"LastObservedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    },
    "End": "string",
    "Start": "string"
  }
],
"NoteText": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"NoteUpdatedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    },
    "End": "string",
    "Start": "string"
  }
],
"NoteUpdatedBy": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ProductArn": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ProductName": [
  {
```

```
    "Comparison": "string",
    "Value": "string"
  }
],
"RecordState": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"RelatedFindingsId": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"RelatedFindingsProductArn": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceApplicationArn": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceApplicationName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceDetailsOther": [
  {
    "Comparison": "string",
    "Key": "string",
    "Value": "string"
  }
],
"ResourceId": [
  {
    "Comparison": "string",
```

```
    "Value": "string"
  }
],
"ResourcePartition": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceRegion": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceTags": [
  {
    "Comparison": "string",
    "Key": "string",
    "Value": "string"
  }
],
"ResourceType": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"SeverityLabel": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"SourceUrl": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"Title": [
  {
    "Comparison": "string",
    "Value": "string"
  }
]
```

```
    }
  ],
  "Type": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "UpdatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "UserDefinedFields": [
    {
      "Comparison": "string",
      "Key": "string",
      "Value": "string"
    }
  ],
  "VerificationState": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "WorkflowStatus": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ]
],
"Description": "string",
"IsTerminal": boolean,
"RuleName": "string",
"RuleOrder": number,
"RuleStatus": "string",
"Tags": {
```



```
    "string" : "string"  
  }  
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Actions

One or more actions to update finding fields if a finding matches the conditions specified in `Criteria`.

Type: Array of [AutomationRulesAction](#) objects

Array Members: Fixed number of 1 item.

Required: Yes

Criteria

A set of ASFF finding field attributes and corresponding expected values that Security Hub uses to filter findings. If a rule is enabled and a finding matches the conditions specified in this parameter, Security Hub applies the rule action to the finding.

Type: [AutomationRulesFindingFilters](#) object

Required: Yes

Description

A description of the rule.

Type: String

Pattern: `.*\S.*`

Required: Yes

IsTerminal

Specifies whether a rule is the last to be applied with respect to a finding that matches the rule criteria. This is useful when a finding matches the criteria for multiple rules, and each rule has different actions. If a rule is terminal, Security Hub applies the rule action to a finding that matches the rule criteria and doesn't evaluate other rules for the finding. By default, a rule isn't terminal.

Type: Boolean

Required: No

RuleName

The name of the rule.

Type: String

Pattern: `.*\S.*`

Required: Yes

RuleOrder

An integer ranging from 1 to 1000 that represents the order in which the rule action is applied to findings. Security Hub applies rules with lower values for this parameter first.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: Yes

RuleStatus

Whether the rule is active after it is created. If this parameter is equal to `ENABLED`, Security Hub starts applying the rule to findings and finding updates after the rule is created. To change the value of this parameter after creating a rule, use [BatchUpdateAutomationRules](#).

Type: String

Valid Values: `ENABLED` | `DISABLED`

Required: No

Tags

User-defined tags associated with an automation rule.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+ -=._:/]+$`

Value Length Constraints: Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "RuleArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[RuleArn](#)

The Amazon Resource Name (ARN) of the automation rule that you created.

Type: String

Pattern: `.*\S.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateConfigurationPolicy

Creates a configuration policy with the defined configuration. Only the Amazon Security Hub delegated administrator can invoke this operation from the home Region.

Request Syntax

```
POST /configurationPolicy/create HTTP/1.1
Content-type: application/json

{
  "ConfigurationPolicy": { ... },
  "Description": "string",
  "Name": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ConfigurationPolicy

An object that defines how Security Hub is configured. It includes whether Security Hub is enabled or disabled, a list of enabled security standards, a list of enabled or disabled security controls, and a list of custom parameter values for specified controls. If you provide a list of security controls that are enabled in the configuration policy, Security Hub disables all other controls (including newly released controls). If you provide a list of security controls that are disabled in the configuration policy, Security Hub enables all other controls (including newly released controls).

Type: [Policy](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Description

The description of the configuration policy.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the configuration policy. Alphanumeric characters and the following ASCII characters are permitted: `-`, `.`, `!`, `*`, `/`.

Type: String

Pattern: `.*\S.*`

Required: Yes

Tags

User-defined tags associated with a configuration policy. For more information, see [Tagging Amazon Security Hub resources](#) in the *Security Hub user guide*.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+-. _:/]+$`

Value Length Constraints: Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "Arn": "string",
  "ConfigurationPolicy": { ... },
  "CreatedAt": "string",
  "Description": "string",
  "Id": "string",
  "Name": "string",
  "UpdatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the configuration policy.

Type: String

Pattern: `.*\S.*`

ConfigurationPolicy

An object that defines how Security Hub is configured. It includes whether Security Hub is enabled or disabled, a list of enabled security standards, a list of enabled or disabled security controls, and a list of custom parameter values for specified controls. If the request included a list of security controls that are enabled in the configuration policy, Security Hub disables all other controls (including newly released controls). If the request included a list of security controls that are disabled in the configuration policy, Security Hub enables all other controls (including newly released controls).

Type: [Policy](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

CreatedAt

The date and time, in UTC and ISO 8601 format, that the configuration policy was created.

Type: Timestamp

Description

The description of the configuration policy.

Type: String

Pattern: .*\\S.*

Id

The universally unique identifier (UUID) of the configuration policy.

Type: String

Pattern: .*\\S.*

Name

The name of the configuration policy.

Type: String

Pattern: .*\\S.*

UpdatedAt

The date and time, in UTC and ISO 8601 format, that the configuration policy was last updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceConflictException

The resource specified in the request conflicts with an existing resource.

HTTP Status Code: 409

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)

- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateFindingAggregator

Note

The *aggregation Region* is now called the *home Region*.

Used to enable cross-Region aggregation. This operation can be invoked from the home Region only.

For information about how cross-Region aggregation works, see [Understanding cross-Region aggregation in Security Hub](#) in the *Amazon Security Hub User Guide*.

Request Syntax

```
POST /findingAggregator/create HTTP/1.1
Content-type: application/json
```

```
{
  "RegionLinkingMode": "string",
  "Regions": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

RegionLinkingMode

Indicates whether to aggregate findings from all of the available Regions in the current partition. Also determines whether to automatically aggregate findings from new Regions as Security Hub supports them and you opt into them.

The selected option also determines how to use the Regions provided in the Regions list.

The options are as follows:

- **ALL_REGIONS** - Aggregates findings from all of the Regions where Security Hub is enabled. When you choose this option, Security Hub also automatically aggregates findings from new Regions as Security Hub supports them and you opt into them.
- **ALL_REGIONS_EXCEPT_SPECIFIED** - Aggregates findings from all of the Regions where Security Hub is enabled, except for the Regions listed in the `Regions` parameter. When you choose this option, Security Hub also automatically aggregates findings from new Regions as Security Hub supports them and you opt into them.
- **SPECIFIED_REGIONS** - Aggregates findings only from the Regions listed in the `Regions` parameter. Security Hub does not automatically aggregate findings from new Regions.
- **NO_REGIONS** - Aggregates no data because no Regions are selected as linked Regions.

Type: String

Pattern: `.*\S.*`

Required: Yes

Regions

If `RegionLinkingMode` is `ALL_REGIONS_EXCEPT_SPECIFIED`, then this is a space-separated list of Regions that don't replicate and send findings to the home Region.

If `RegionLinkingMode` is `SPECIFIED_REGIONS`, then this is a space-separated list of Regions that do replicate and send findings to the home Region.

An `InvalidInputException` error results if you populate this field while `RegionLinkingMode` is `NO_REGIONS`.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"FindingAggregationRegion": "string",
"FindingAggregatorArn": "string",
"RegionLinkingMode": "string",
"Regions": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

FindingAggregationRegion

The home Region. Findings generated in linked Regions are replicated and sent to the home Region.

Type: String

Pattern: `.*\S.*`

FindingAggregatorArn

The ARN of the finding aggregator. You use the finding aggregator ARN to retrieve details for, update, and stop cross-Region aggregation.

Type: String

Pattern: `.*\S.*`

RegionLinkingMode

Indicates whether to link all Regions, all Regions except for a list of excluded Regions, or a list of included Regions.

Type: String

Pattern: `.*\S.*`

Regions

The list of excluded Regions or included Regions.

Type: Array of strings

Pattern: .*\\S.*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateInsight

Creates a custom insight in Security Hub. An insight is a consolidation of findings that relate to a security issue that requires attention or remediation.

To group the related findings in the insight, use the `GroupByAttribute`.

Request Syntax

```
POST /insights HTTP/1.1
Content-type: application/json

{
  "Filters": {
    "AwsAccountId": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "AwsAccountName": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "CompanyName": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "ComplianceAssociatedStandardsId": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "ComplianceSecurityControlId": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ]
  }
}
```

```
],
  "ComplianceSecurityControlParametersName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ComplianceSecurityControlParametersValue": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ComplianceStatus": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Confidence": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "CreatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "Criticality": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
```

```
    "Lte": number
  }
],
"Description": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"FindingProviderFieldsConfidence": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"FindingProviderFieldsCriticality": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"FindingProviderFieldsRelatedFindingsId": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"FindingProviderFieldsRelatedFindingsProductArn": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"FindingProviderFieldsSeverityLabel": [
  {
    "Comparison": "string",
    "Value": "string"
  }
]
```

```
],
"FindingProviderFieldsSeverityOriginal": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"FindingProviderFieldsTypes": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"FirstObservedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    },
    "End": "string",
    "Start": "string"
  }
],
"GeneratorId": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"Id": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"Keyword": [
  {
    "Value": "string"
  }
],
"LastObservedAt": [
  {
    "DateRange": {
      "Unit": "string",
```

```
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "MalwareName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "MalwarePath": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "MalwareState": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "MalwareType": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "NetworkDestinationDomain": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "NetworkDestinationIPv4": [
    {
      "Cidr": "string"
    }
  ],
  "NetworkDestinationIPv6": [
    {
      "Cidr": "string"
    }
  ]
}
```

```
    }
  ],
  "NetworkDestinationPort": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "NetworkDirection": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "NetworkProtocol": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "NetworkSourceDomain": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "NetworkSourceIPv4": [
    {
      "Cidr": "string"
    }
  ],
  "NetworkSourceIPv6": [
    {
      "Cidr": "string"
    }
  ],
  "NetworkSourceMac": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ]
}
```

```
],
  "NetworkSourcePort": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "NoteText": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "NoteUpdatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "NoteUpdatedBy": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ProcessLaunchedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "ProcessName": [
    {
```

```
    "Comparison": "string",
    "Value": "string"
  }
],
"ProcessParentPid": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"ProcessPath": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ProcessPid": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"ProcessTerminatedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    },
    "End": "string",
    "Start": "string"
  }
],
"ProductArn": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
```



```
"ProductFields": [  
  {  
    "Comparison": "string",  
    "Key": "string",  
    "Value": "string"  
  }  
],  
"ProductName": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"RecommendationText": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"RecordState": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"Region": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"RelatedFindingsId": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"RelatedFindingsProductArn": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceApplicationArn": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceApplicationArn": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],
```

```
{
  "Comparison": "string",
  "Value": "string"
},
"ResourceApplicationName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsEc2InstanceIamInstanceProfileArn": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsEc2InstanceImageId": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsEc2InstanceIpV4Addresses": [
  {
    "Cidr": "string"
  }
],
"ResourceAwsEc2InstanceIpV6Addresses": [
  {
    "Cidr": "string"
  }
],
"ResourceAwsEc2InstanceKeyName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsEc2InstanceLaunchedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    }
  }
]
```

```
    },
    "End": "string",
    "Start": "string"
  }
],
"ResourceAwsEc2InstanceSubnetId": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsEc2InstanceType": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsEc2InstanceVpcId": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsIamAccessKeyCreatedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    },
    "End": "string",
    "Start": "string"
  }
],
"ResourceAwsIamAccessKeyPrincipalName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsIamAccessKeyStatus": [
  {
    "Comparison": "string",
    "Value": "string"
  }
]
```

```
],
  "ResourceAwsIamAccessKeyUserName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsIamUserUserName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsS3BucketOwnerId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsS3BucketOwnerName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceContainerImageId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceContainerImageName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceContainerLaunchedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
    }
  ],

```

```
    "Start": "string"
  }
],
"ResourceContainerName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceDetailsOther": [
  {
    "Comparison": "string",
    "Key": "string",
    "Value": "string"
  }
],
"ResourceId": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourcePartition": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceRegion": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceTags": [
  {
    "Comparison": "string",
    "Key": "string",
    "Value": "string"
  }
],
"ResourceType": [
  {
    "Comparison": "string",
```

```
    "Value": "string"
  }
],
"Sample": [
  {
    "Value": boolean
  }
],
"SeverityLabel": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"SeverityNormalized": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"SeverityProduct": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"SourceUrl": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ThreatIntelIndicatorCategory": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
```

```
"ThreatIntelIndicatorLastObservedAt": [  
  {  
    "DateRange": {  
      "Unit": "string",  
      "Value": number  
    },  
    "End": "string",  
    "Start": "string"  
  }  
],  
"ThreatIntelIndicatorSource": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ThreatIntelIndicatorSourceUrl": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ThreatIntelIndicatorType": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ThreatIntelIndicatorValue": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"Title": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"Type": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
]
```

```
    }
  ],
  "UpdatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "UserDefinedFields": [
    {
      "Comparison": "string",
      "Key": "string",
      "Value": "string"
    }
  ],
  "VerificationState": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "VulnerabilitiesExploitAvailable": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "VulnerabilitiesFixAvailable": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "WorkflowState": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "WorkflowStatus": [
```



```
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "GroupByAttribute": "string",
  "Name": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Filters

One or more attributes used to filter the findings included in the insight. The insight only includes findings that match the criteria defined in the filters.

Type: [AwsSecurityFindingFilters](#) object

Required: Yes

GroupByAttribute

The attribute used to group the findings for the insight. The grouping attribute identifies the type of item that the insight applies to. For example, if an insight is grouped by resource identifier, then the insight produces a list of resource identifiers.

Type: String

Pattern: `.*\S.*`

Required: Yes

Name

The name of the custom insight to create.

Type: String

Pattern: `.*\S.*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "InsightArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[InsightArn](#)

The ARN of the insight created.

Type: String

Pattern: `.*\S.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceConflictException

The resource specified in the request conflicts with an existing resource.

HTTP Status Code: 409

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateMembers

Creates a member association in Security Hub between the specified accounts and the account used to make the request, which is the administrator account. If you are integrated with Organizations, then the administrator account is designated by the organization management account.

CreateMembers is always used to add accounts that are not organization members.

For accounts that are managed using Organizations, CreateMembers is only used in the following cases:

- Security Hub is not configured to automatically add new organization accounts.
- The account was disassociated or deleted in Security Hub.

This action can only be used by an account that has Security Hub enabled. To enable Security Hub, you can use the EnableSecurityHub operation.

For accounts that are not organization members, you create the account association and then send an invitation to the member account. To send the invitation, you use the InviteMembers operation. If the account owner accepts the invitation, the account becomes a member account in Security Hub.

Accounts that are managed using Organizations don't receive an invitation. They automatically become a member account in Security Hub.

- If the organization account does not have Security Hub enabled, then Security Hub and the default standards are automatically enabled. Note that Security Hub cannot be enabled automatically for the organization management account. The organization management account must enable Security Hub before the administrator account enables it as a member account.
- For organization accounts that already have Security Hub enabled, Security Hub does not make any other changes to those accounts. It does not change their enabled standards or controls.

A permissions policy is added that permits the administrator account to view the findings generated in the member account.

To remove the association between the administrator and member accounts, use the DisassociateFromMasterAccount or DisassociateMembers operation.

Request Syntax

```
POST /members HTTP/1.1
Content-type: application/json
```

```
{
  "AccountDetails": [
    {
      "AccountId": "string",
      "Email": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[AccountDetails](#)

The list of accounts to associate with the Security Hub administrator account. For each account, the list includes the account ID and optionally the email address.

Type: Array of [AccountDetails](#) objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "UnprocessedAccounts": [
    {
```

```
    "AccountId": "string",  
    "ProcessingResult": "string"  
  }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

UnprocessedAccounts

The list of Amazon Web Services accounts that were not processed. For each account, the list includes the account ID and the email address.

Type: Array of [Result](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceConflictException

The resource specified in the request conflicts with an existing resource.

HTTP Status Code: 409

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeclineInvitations

Note

We recommend using Amazon Organizations instead of Security Hub invitations to manage your member accounts. For information, see [Managing Security Hub administrator and member accounts with Organizations](#) in the *Amazon Security Hub User Guide*.

Declines invitations to become a Security Hub member account.

A prospective member account uses this operation to decline an invitation to become a member.

Only member accounts that aren't part of an Amazon organization should use this operation. Organization accounts don't receive invitations.

Request Syntax

```
POST /invitations/decline HTTP/1.1
Content-type: application/json

{
  "AccountIds": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AccountIds

The list of prospective member account IDs for which to decline an invitation.

Type: Array of strings

Pattern: `.*\S.*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "UnprocessedAccounts": [
    {
      "AccountId": "string",
      "ProcessingResult": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

UnprocessedAccounts

The list of Amazon Web Services accounts that were not processed. For each account, the list includes the account ID and the email address.

Type: Array of [Result](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteActionTarget

Deletes a custom action target from Security Hub.

Deleting a custom action target does not affect any findings or insights that were already sent to Amazon CloudWatch Events using the custom action.

Request Syntax

```
DELETE /actionTargets/ActionTargetArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ActionTargetArn

The Amazon Resource Name (ARN) of the custom action target to delete.

Pattern: `.*\S.*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ActionTargetArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ActionTargetArn

The ARN of the custom action target that was deleted.

Type: String

Pattern: .*\\S.*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteConfigurationPolicy

Deletes a configuration policy. Only the Amazon Security Hub delegated administrator can invoke this operation from the home Region. For the deletion to succeed, you must first disassociate a configuration policy from target accounts, organizational units, or the root by invoking the `StartConfigurationPolicyDisassociation` operation.

Request Syntax

```
DELETE /configurationPolicy/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The Amazon Resource Name (ARN) or universally unique identifier (UUID) of the configuration policy.

Pattern: `.*\S.*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceConflictException

The resource specified in the request conflicts with an existing resource.

HTTP Status Code: 409

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteFindingAggregator

Note

The *aggregation Region* is now called the *home Region*.

Deletes a finding aggregator. When you delete the finding aggregator, you stop cross-Region aggregation. Finding replication stops occurring from the linked Regions to the home Region.

When you stop cross-Region aggregation, findings that were already replicated and sent to the home Region are still visible from the home Region. However, new findings and finding updates are no longer replicated and sent to the home Region.

Request Syntax

```
DELETE /findingAggregator/delete/FindingAggregatorArn+ HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

FindingAggregatorArn

The ARN of the finding aggregator to delete. To obtain the ARN, use `ListFindingAggregators`.

Pattern: `.*\S.*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteInsight

Deletes the insight specified by the InsightArn.

Request Syntax

```
DELETE /insights/InsightArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

InsightArn

The ARN of the insight to delete.

Pattern: `.*\S.*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "InsightArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InsightArn

The ARN of the insight that was deleted.

Type: String

Pattern: `.*\S.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteInvitations

Note

We recommend using Amazon Organizations instead of Security Hub invitations to manage your member accounts. For information, see [Managing Security Hub administrator and member accounts with Organizations](#) in the *Amazon Security Hub User Guide*.

Deletes invitations to become a Security Hub member account.

A Security Hub administrator account can use this operation to delete invitations sent to one or more prospective member accounts.

This operation is only used to delete invitations that are sent to prospective member accounts that aren't part of an Amazon organization. Organization accounts don't receive invitations.

Request Syntax

```
POST /invitations/delete HTTP/1.1
Content-type: application/json

{
  "AccountIds": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[AccountIds](#)

The list of member account IDs that received the invitations you want to delete.

Type: Array of strings

Pattern: .*\\S.*

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "UnprocessedAccounts": [
    {
      "AccountId": "string",
      "ProcessingResult": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

UnprocessedAccounts

The list of Amazon Web Services accounts for which the invitations were not deleted. For each account, the list includes the account ID and the email address.

Type: Array of [Result](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

DeleteMembers

Deletes the specified member accounts from Security Hub.

You can invoke this API only to delete accounts that became members through invitation. You can't invoke this API to delete accounts that belong to an Amazon Organizations organization.

Request Syntax

```
POST /members/delete HTTP/1.1
Content-type: application/json

{
  "AccountIds": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AccountIds

The list of account IDs for the member accounts to delete.

Type: Array of strings

Pattern: .*\\S.*

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"UnprocessedAccounts": [  
  {  
    "AccountId": "string",  
    "ProcessingResult": "string"  
  }  
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

UnprocessedAccounts

The list of Amazon Web Services accounts that were not deleted. For each account, the list includes the account ID and the email address.

Type: Array of [Result](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeActionTargets

Returns a list of the custom action targets in Security Hub in your account.

Request Syntax

```
POST /actionTargets/get HTTP/1.1
Content-type: application/json

{
  "ActionTargetArns": [ "string" ],
  "MaxResults": number,
  "NextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ActionTargetArns

A list of custom action target ARNs for the custom action targets to retrieve.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

MaxResults

The maximum number of results to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token that is required for pagination. On your first call to the `DescribeActionTargets` operation, set the value of this parameter to `NULL`.

For subsequent calls to the operation, to continue listing data, set the value of this parameter to the value returned from the previous response.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ActionTargets": [
    {
      "ActionTargetArn": "string",
      "Description": "string",
      "Name": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ActionTargets

A list of `ActionTarget` objects. Each object includes the `ActionTargetArn`, `Description`, and `Name` of a custom action target available in Security Hub.

Type: Array of [ActionTarget](#) objects

NextToken

The pagination token to use to request the next page of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)

- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeHub

Returns details about the Hub resource in your account, including the `HubArn` and the time when you enabled Security Hub.

Request Syntax

```
GET /accounts?HubArn=HubArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

HubArn

The ARN of the Hub resource to retrieve.

Pattern: `.*\S.*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AutoEnableControls": boolean,
  "ControlFindingGenerator": "string",
  "HubArn": "string",
  "SubscribedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AutoEnableControls

Whether to automatically enable new controls when they are added to standards that are enabled.

If set to `true`, then new controls for enabled standards are enabled automatically. If set to `false`, then new controls are not enabled.

When you automatically enable new controls, you can interact with the controls in the console and programmatically immediately after release. However, automatically enabled controls have a temporary default status of `DISABLED`. It can take up to several days for Security Hub to process the control release and designate the control as `ENABLED` in your account. During the processing period, you can manually enable or disable a control, and Security Hub will maintain that designation regardless of whether you have `AutoEnableControls` set to `true`.

Type: Boolean

ControlFindingGenerator

Specifies whether the calling account has consolidated control findings turned on. If the value for this field is set to `SECURITY_CONTROL`, Security Hub generates a single finding for a control check even when the check applies to multiple enabled standards.

If the value for this field is set to `STANDARD_CONTROL`, Security Hub generates separate findings for a control check when the check applies to multiple enabled standards.

The value for this field in a member account matches the value in the administrator account. For accounts that aren't part of an organization, the default value of this field is `SECURITY_CONTROL` if you enabled Security Hub on or after February 23, 2023.

Type: String

Valid Values: `STANDARD_CONTROL` | `SECURITY_CONTROL`

HubArn

The ARN of the Hub resource that was retrieved.

Type: String

Pattern: `.*\S.*`

SubscribedAt

The date and time when Security Hub was enabled in the account.

Type: String

Pattern: .*\\S.*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeOrganizationConfiguration

Returns information about the way your organization is configured in Amazon Security Hub. Only the Security Hub administrator account can invoke this operation.

Request Syntax

```
GET /organization/configuration HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AutoEnable": boolean,
  "AutoEnableStandards": "string",
  "MemberAccountLimitReached": boolean,
  "OrganizationConfiguration": {
    "ConfigurationType": "string",
    "Status": "string",
    "StatusMessage": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AutoEnable

Whether to automatically enable Security Hub in new member accounts when they join the organization.

If set to `true`, then Security Hub is automatically enabled in new accounts. If set to `false`, then Security Hub isn't enabled in new accounts automatically. The default value is `false`.

If the `ConfigurationType` of your organization is set to `CENTRAL`, then this field is set to `false` and can't be changed in the home Region and linked Regions. However, in that case, the delegated administrator can create a configuration policy in which Security Hub is enabled and associate the policy with new organization accounts.

Type: Boolean

AutoEnableStandards

Whether to automatically enable Security Hub [default standards](#) in new member accounts when they join the organization.

If equal to `DEFAULT`, then Security Hub default standards are automatically enabled for new member accounts. If equal to `NONE`, then default standards are not automatically enabled for new member accounts. The default value of this parameter is equal to `DEFAULT`.

If the `ConfigurationType` of your organization is set to `CENTRAL`, then this field is set to `NONE` and can't be changed in the home Region and linked Regions. However, in that case, the delegated administrator can create a configuration policy in which specific security standards are enabled and associate the policy with new organization accounts.

Type: String

Valid Values: `NONE` | `DEFAULT`

MemberAccountLimitReached

Whether the maximum number of allowed member accounts are already associated with the Security Hub administrator account.

Type: Boolean

OrganizationConfiguration

Provides information about the way an organization is configured in Amazon Security Hub.

Type: [OrganizationConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeProducts

Returns information about product integrations in Security Hub.

You can optionally provide an integration ARN. If you provide an integration ARN, then the results only include that integration.

If you don't provide an integration ARN, then the results include all of the available product integrations.

Request Syntax

```
GET /products?MaxResults=MaxResults&NextToken=NextToken&ProductArn=ProductArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 100.

NextToken

The token that is required for pagination. On your first call to the `DescribeProducts` operation, set the value of this parameter to `NULL`.

For subsequent calls to the operation, to continue listing data, set the value of this parameter to the value returned from the previous response.

ProductArn

The ARN of the integration to return.

Pattern: `.*\S.*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Products": [
    {
      "ActivationUrl": "string",
      "Categories": [ "string" ],
      "CompanyName": "string",
      "Description": "string",
      "IntegrationTypes": [ "string" ],
      "MarketplaceUrl": "string",
      "ProductArn": "string",
      "ProductName": "string",
      "ProductSubscriptionResourcePolicy": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken](#)

The pagination token to use to request the next page of results.

Type: String

[Products](#)

A list of products, including details for each product.

Type: Array of [Product](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

DescribeStandards

Returns a list of the available standards in Security Hub.

For each standard, the results include the standard ARN, the name, and a description.

Request Syntax

```
GET /standards?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of standards to return.

Valid Range: Minimum value of 1. Maximum value of 100.

NextToken

The token that is required for pagination. On your first call to the DescribeStandards operation, set the value of this parameter to NULL.

For subsequent calls to the operation, to continue listing data, set the value of this parameter to the value returned from the previous response.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Standards": [
    {
```

```
    "Description": "string",
    "EnabledByDefault": boolean,
    "Name": "string",
    "StandardsArn": "string",
    "StandardsManagedBy": {
      "Company": "string",
      "Product": "string"
    }
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token to use to request the next page of results.

Type: String

Standards

A list of available standards.

Type: Array of [Standard](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeStandardsControls

Returns a list of security standards controls.

For each control, the results include information about whether it is currently enabled, the severity, and a link to remediation information.

This operation returns an empty list for standard subscriptions where `StandardsControlsUpdatable` has value `NOT_READY_FOR_UPDATES`.

Request Syntax

```
GET /standards/controls/StandardsSubscriptionArn?  
MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of security standard controls to return.

Valid Range: Minimum value of 1. Maximum value of 100.

NextToken

The token that is required for pagination. On your first call to the `DescribeStandardsControls` operation, set the value of this parameter to `NULL`.

For subsequent calls to the operation, to continue listing data, set the value of this parameter to the value returned from the previous response.

StandardsSubscriptionArn

The ARN of a resource that represents your subscription to a supported standard. To get the subscription ARNs of the standards you have enabled, use the `GetEnabledStandards` operation.

Pattern: `.*\S.*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Controls": [
    {
      "ControlId": "string",
      "ControlStatus": "string",
      "ControlStatusUpdatedAt": "string",
      "Description": "string",
      "DisabledReason": "string",
      "RelatedRequirements": [ "string" ],
      "RemediationUrl": "string",
      "SeverityRating": "string",
      "StandardsControlArn": "string",
      "Title": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Controls

A list of security standards controls.

Type: Array of [StandardsControl](#) objects

NextToken

The pagination token to use to request the next page of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DisableImportFindingsForProduct

Disables the integration of the specified product with Security Hub. After the integration is disabled, findings from that product are no longer sent to Security Hub.

Request Syntax

```
DELETE /productSubscriptions/ProductSubscriptionArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ProductSubscriptionArn

The ARN of the integrated product to disable the integration for.

Pattern: `.*\S.*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)

- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DisableOrganizationAdminAccount

Disables a Security Hub administrator account. Can only be called by the organization management account.

Request Syntax

```
POST /organization/admin/disable HTTP/1.1
Content-type: application/json

{
  "AdminAccountId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AdminAccountId

The Amazon Web Services account identifier of the Security Hub administrator account.

Type: String

Pattern: `.*\S.*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)

- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DisableSecurityHub

Disables Security Hub in your account only in the current Amazon Web Services Region. To disable Security Hub in all Regions, you must submit one request per Region where you have enabled Security Hub.

You can't disable Security Hub in an account that is currently the Security Hub administrator.

When you disable Security Hub, your existing findings and insights and any Security Hub configuration settings are deleted after 90 days and cannot be recovered. Any standards that were enabled are disabled, and your administrator and member account associations are removed.

If you want to save your existing findings, you must export them before you disable Security Hub.

Request Syntax

```
DELETE /accounts HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DisassociateFromAdministratorAccount

Disassociates the current Security Hub member account from the associated administrator account.

This operation is only used by accounts that are not part of an organization. For organization accounts, only the administrator account can disassociate a member account.

Request Syntax

```
POST /administrator/disassociate HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DisassociateFromMasterAccount

This method is deprecated. Instead, use `DisassociateFromAdministratorAccount`.

The Security Hub console continues to use `DisassociateFromMasterAccount`. It will eventually change to use `DisassociateFromAdministratorAccount`. Any IAM policies that specifically control access to this function must continue to use `DisassociateFromMasterAccount`. You should also add `DisassociateFromAdministratorAccount` to your policies to ensure that the correct permissions are in place after the console begins to use `DisassociateFromAdministratorAccount`.

Disassociates the current Security Hub member account from the associated administrator account.

This operation is only used by accounts that are not part of an organization. For organization accounts, only the administrator account can disassociate a member account.

Request Syntax

```
POST /master/disassociate HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DisassociateMembers

Disassociates the specified member accounts from the associated administrator account.

Can be used to disassociate both accounts that are managed using Organizations and accounts that were invited manually.

Request Syntax

```
POST /members/disassociate HTTP/1.1
Content-type: application/json

{
  "AccountIds": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AccountIds

The account IDs of the member accounts to disassociate from the administrator account.

Type: Array of strings

Pattern: `.*\S.*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

EnableImportFindingsForProduct

Enables the integration of a partner product with Security Hub. Integrated products send findings to Security Hub.

When you enable a product integration, a permissions policy that grants permission for the product to send findings to Security Hub is applied.

Request Syntax

```
POST /productSubscriptions HTTP/1.1
Content-type: application/json

{
  "ProductArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[ProductArn](#)

The ARN of the product to enable the integration for.

Type: String

Pattern: `.*\S.*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"ProductSubscriptionArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ProductSubscriptionArn

The ARN of your subscription to the product to enable integrations for.

Type: String

Pattern: `.*\S.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceConflictException

The resource specified in the request conflicts with an existing resource.

HTTP Status Code: 409

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

EnableOrganizationAdminAccount

Designates the Security Hub administrator account for an organization. Can only be called by the organization management account.

Request Syntax

```
POST /organization/admin/enable HTTP/1.1
Content-type: application/json

{
  "AdminAccountId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[AdminAccountId](#)

The Amazon Web Services account identifier of the account to designate as the Security Hub administrator account.

Type: String

Pattern: `.*\S.*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)

- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

EnableSecurityHub

Enables Security Hub for your account in the current Region or the Region you specify in the request.

When you enable Security Hub, you grant to Security Hub the permissions necessary to gather findings from other services that are integrated with Security Hub.

When you use the EnableSecurityHub operation to enable Security Hub, you also automatically enable the following standards:

- Center for Internet Security (CIS) Amazon Foundations Benchmark v1.2.0
- Amazon Foundational Security Best Practices

Other standards are not automatically enabled.

To opt out of automatically enabled standards, set EnableDefaultStandards to false.

After you enable Security Hub, to enable a standard, use the BatchEnableStandards operation. To disable a standard, use the BatchDisableStandards operation.

To learn more, see the [setup information](#) in the *Amazon Security Hub User Guide*.

Request Syntax

```
POST /accounts HTTP/1.1
Content-type: application/json

{
  "ControlFindingGenerator": "string",
  "EnableDefaultStandards": boolean,
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ControlFindingGenerator

This field, used when enabling Security Hub, specifies whether the calling account has consolidated control findings turned on. If the value for this field is set to `SECURITY_CONTROL`, Security Hub generates a single finding for a control check even when the check applies to multiple enabled standards.

If the value for this field is set to `STANDARD_CONTROL`, Security Hub generates separate findings for a control check when the check applies to multiple enabled standards.

The value for this field in a member account matches the value in the administrator account. For accounts that aren't part of an organization, the default value of this field is `SECURITY_CONTROL` if you enabled Security Hub on or after February 23, 2023.

Type: String

Valid Values: `STANDARD_CONTROL` | `SECURITY_CONTROL`

Required: No

EnableDefaultStandards

Whether to enable the security standards that Security Hub has designated as automatically enabled. If you don't provide a value for `EnableDefaultStandards`, it is set to `true`. To not enable the automatically enabled standards, set `EnableDefaultStandards` to `false`.

Type: Boolean

Required: No

Tags

The tags to add to the hub resource when you enable Security Hub.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+-._: /]+$`

Value Length Constraints: Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceConflictException

The resource specified in the request conflicts with an existing resource.

HTTP Status Code: 409

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetAdministratorAccount

Provides the details for the Security Hub administrator account for the current member account.

Can be used by both member accounts that are managed using Organizations and accounts that were invited manually.

Request Syntax

```
GET /administrator HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Administrator": {
    "AccountId": "string",
    "InvitationId": "string",
    "InvitedAt": "string",
    "MemberStatus": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Administrator](#)

Details about an invitation.

Type: [Invitation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetConfigurationPolicy

Provides information about a configuration policy. Only the Amazon Security Hub delegated administrator can invoke this operation from the home Region.

Request Syntax

```
GET /configurationPolicy/get/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The Amazon Resource Name (ARN) or universally unique identifier (UUID) of the configuration policy.

Pattern: `.*\S.*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "ConfigurationPolicy": { ... },
  "CreatedAt": "string",
  "Description": "string",
  "Id": "string",
  "Name": "string",
  "UpdatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The ARN of the configuration policy.

Type: String

Pattern: `.*\S.*`

ConfigurationPolicy

An object that defines how Security Hub is configured. It includes whether Security Hub is enabled or disabled, a list of enabled security standards, a list of enabled or disabled security controls, and a list of custom parameter values for specified controls. If the policy includes a list of security controls that are enabled, Security Hub disables all other controls (including newly released controls). If the policy includes a list of security controls that are disabled, Security Hub enables all other controls (including newly released controls).

Type: [Policy](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

CreatedAt

The date and time, in UTC and ISO 8601 format, that the configuration policy was created.

Type: Timestamp

Description

The description of the configuration policy.

Type: String

Pattern: `.*\S.*`

Id

The UUID of the configuration policy.

Type: String

Pattern: `.*\S.*`

Name

The name of the configuration policy.

Type: String

Pattern: `.*\S.*`

UpdatedAt

The date and time, in UTC and ISO 8601 format, that the configuration policy was last updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetConfigurationPolicyAssociation

Returns the association between a configuration and a target account, organizational unit, or the root. The configuration can be a configuration policy or self-managed behavior. Only the Amazon Security Hub delegated administrator can invoke this operation from the home Region.

Request Syntax

```
POST /configurationPolicyAssociation/get HTTP/1.1
Content-type: application/json
```

```
{
  "Target": { ... }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Target

The target account ID, organizational unit ID, or the root ID to retrieve the association for.

Type: [Target](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "AssociationStatus": "string",
```

```
"AssociationStatusMessage": "string",  
"AssociationType": "string",  
"ConfigurationPolicyId": "string",  
"TargetId": "string",  
"TargetType": "string",  
"UpdatedAt": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AssociationStatus

The current status of the association between the specified target and the configuration.

Type: String

Valid Values: PENDING | SUCCESS | FAILED

AssociationStatusMessage

The explanation for a FAILED value for AssociationStatus.

Type: String

Pattern: .*\\S.*

AssociationType

Indicates whether the association between the specified target and the configuration was directly applied by the Security Hub delegated administrator or inherited from a parent.

Type: String

Valid Values: INHERITED | APPLIED

ConfigurationPolicyId

The universally unique identifier (UUID) of a configuration policy. For self-managed behavior, the value is SELF_MANAGED_SECURITY_HUB.

Type: String

Pattern: .*\\S.*

TargetId

The target account ID, organizational unit ID, or the root ID for which the association is retrieved.

Type: String

Pattern: .*\\S.*

TargetType

Specifies whether the target is an Amazon Web Services account, organizational unit, or the organization root.

Type: String

Valid Values: ACCOUNT | ORGANIZATIONAL_UNIT | ROOT

UpdatedAt

The date and time, in UTC and ISO 8601 format, that the configuration policy association was last updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetEnabledStandards

Returns a list of the standards that are currently enabled.

Request Syntax

```
POST /standards/get HTTP/1.1
Content-type: application/json

{
  "MaxResults": number,
  "NextToken": "string",
  "StandardsSubscriptionArns": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to return in the response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token that is required for pagination. On your first call to the GetEnabledStandards operation, set the value of this parameter to NULL.

For subsequent calls to the operation, to continue listing data, set the value of this parameter to the value returned from the previous response.

Type: String

Required: No

StandardsSubscriptionArns

The list of the standards subscription ARNs for the standards to retrieve.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Pattern: .*\\S.*

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "StandardsSubscriptions": [
    {
      "StandardsArn": "string",
      "StandardsControlsUpdatable": "string",
      "StandardsInput": {
        "string": "string"
      },
      "StandardsStatus": "string",
      "StandardsStatusReason": {
        "StatusReasonCode": "string"
      },
      "StandardsSubscriptionArn": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token to use to request the next page of results.

Type: String

StandardsSubscriptions

The list of StandardsSubscriptions objects that include information about the enabled standards.

Type: Array of [StandardsSubscription](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetFindingAggregator

Note

The *aggregation Region* is now called the *home Region*.

Returns the current configuration in the calling account for cross-Region aggregation. A finding aggregator is a resource that establishes the home Region and any linked Regions.

Request Syntax

```
GET /findingAggregator/get/FindingAggregatorArn+ HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

FindingAggregatorArn

The ARN of the finding aggregator to return details for. To obtain the ARN, use `ListFindingAggregators`.

Pattern: `.*\S.*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "FindingAggregationRegion": "string",
```

```
"FindingAggregatorArn": "string",  
"RegionLinkingMode": "string",  
"Regions": [ "string" ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

FindingAggregationRegion

The home Region. Findings generated in linked Regions are replicated and sent to the home Region.

Type: String

Pattern: `.*\S.*`

FindingAggregatorArn

The ARN of the finding aggregator.

Type: String

Pattern: `.*\S.*`

RegionLinkingMode

Indicates whether to link all Regions, all Regions except for a list of excluded Regions, or a list of included Regions.

Type: String

Pattern: `.*\S.*`

Regions

The list of excluded Regions or included Regions.

Type: Array of strings

Pattern: `.*\S.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetFindingHistory

Returns the history of a Security Hub finding for the past 90 days. The history includes changes made to any fields in the Amazon Security Finding Format (ASFF) except top-level timestamp fields, such as the `CreatedAt` and `UpdatedAt` fields.

This operation might return fewer results than the maximum number of results (`MaxResults`) specified in a request, even when more results are available. If this occurs, the response includes a `NextToken` value, which you should use to retrieve the next set of results in the response. The presence of a `NextToken` value in a response doesn't necessarily indicate that the results are incomplete. However, you should continue to specify a `NextToken` value until you receive a response that doesn't include this value.

Request Syntax

```
POST /findingHistory/get HTTP/1.1
Content-type: application/json
```

```
{
  "EndTime": "string",
  "FindingIdentifier": {
    "Id": "string",
    "ProductArn": "string"
  },
  "MaxResults": number,
  "NextToken": "string",
  "StartTime": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

EndTime

An ISO 8601-formatted timestamp that indicates the end time of the requested finding history.

If you provide values for both `StartTime` and `EndTime`, Security Hub returns finding history for the specified time period. If you provide a value for `StartTime` but not for `EndTime`, Security Hub returns finding history from the `StartTime` to the time at which the API is called. If you provide a value for `EndTime` but not for `StartTime`, Security Hub returns finding history from the [CreatedAt](#) timestamp of the finding to the `EndTime`. If you provide neither `StartTime` nor `EndTime`, Security Hub returns finding history from the `CreatedAt` timestamp of the finding to the time at which the API is called. In all of these scenarios, the response is limited to 100 results, and the maximum time period is limited to 90 days.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: Timestamp

Required: No

[FindingIdentifier](#)

Identifies which finding to get the finding history for.

Type: [AwsSecurityFindingIdentifier](#) object

Required: Yes

[MaxResults](#)

The maximum number of results to be returned. If you don't provide it, Security Hub returns up to 100 results of finding history.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[NextToken](#)

A token for pagination purposes. Provide NULL as the initial value. In subsequent requests, provide the token included in the response to get up to an additional 100 results of finding history. If you don't provide `NextToken`, Security Hub returns up to 100 results of finding history for each request.

Type: String

Required: No

StartTime

A timestamp that indicates the start time of the requested finding history.

If you provide values for both `StartTime` and `EndTime`, Amazon Security Hub returns finding history for the specified time period. If you provide a value for `StartTime` but not for `EndTime`, Security Hub returns finding history from the `StartTime` to the time at which the API is called. If you provide a value for `EndTime` but not for `StartTime`, Security Hub returns finding history from the [CreatedAt](#) timestamp of the finding to the `EndTime`. If you provide neither `StartTime` nor `EndTime`, Security Hub returns finding history from the `CreatedAt` timestamp of the finding to the time at which the API is called. In all of these scenarios, the response is limited to 100 results, and the maximum time period is limited to 90 days.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: Timestamp

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Records": [
    {
      "FindingCreated": boolean,
      "FindingIdentifier": {
        "Id": "string",
        "ProductArn": "string"
      },
      "NextToken": "string",
      "Updates": [
        {
          "NewValue": "string",
          "OldValue": "string",
          "UpdatedField": "string"
        }
      ]
    }
  ]
}
```

```
    }
  ],
  "UpdateSource": {
    "Identity": "string",
    "Type": "string"
  },
  "UpdateTime": "string"
}
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A token for pagination purposes. Provide this token in the subsequent request to `GetFindingsHistory` to get up to an additional 100 results of history for the same finding that you specified in your initial request.

Type: String

Records

A list of events that altered the specified finding during the specified time period.

Type: Array of [FindingHistoryRecord](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetFindings

Returns a list of findings that match the specified criteria.

If cross-Region aggregation is enabled, then when you call `GetFindings` from the home Region, the results include all of the matching findings from both the home Region and linked Regions.

Request Syntax

```
POST /findings HTTP/1.1
Content-type: application/json

{
  "Filters": {
    "AwsAccountId": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "AwsAccountName": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "CompanyName": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "ComplianceAssociatedStandardsId": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "ComplianceSecurityControlId": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ]
  }
}
```



```
],
  "ComplianceSecurityControlParametersName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ComplianceSecurityControlParametersValue": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ComplianceStatus": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Confidence": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "CreatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "Criticality": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
```

```
    "Lte": number
  }
],
"Description": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"FindingProviderFieldsConfidence": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"FindingProviderFieldsCriticality": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"FindingProviderFieldsRelatedFindingsId": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"FindingProviderFieldsRelatedFindingsProductArn": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"FindingProviderFieldsSeverityLabel": [
  {
    "Comparison": "string",
    "Value": "string"
  }
]
```

```
],
  "FindingProviderFieldsSeverityOriginal": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "FindingProviderFieldsTypes": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "FirstObservedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "GeneratorId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Id": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Keyword": [
    {
      "Value": "string"
    }
  ],
  "LastObservedAt": [
    {
      "DateRange": {
        "Unit": "string",
```

```
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "MalwareName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "MalwarePath": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "MalwareState": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "MalwareType": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "NetworkDestinationDomain": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "NetworkDestinationIPv4": [
    {
      "Cidr": "string"
    }
  ],
  "NetworkDestinationIPv6": [
    {
      "Cidr": "string"
    }
  ]
}
```

```
    }
  ],
  "NetworkDestinationPort": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "NetworkDirection": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "NetworkProtocol": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "NetworkSourceDomain": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "NetworkSourceIPv4": [
    {
      "Cidr": "string"
    }
  ],
  "NetworkSourceIPv6": [
    {
      "Cidr": "string"
    }
  ],
  "NetworkSourceMac": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ]
}
```

```
],
  "NetworkSourcePort": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "NoteText": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "NoteUpdatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "NoteUpdatedBy": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ProcessLaunchedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "ProcessName": [
    {
```

```
    "Comparison": "string",
    "Value": "string"
  }
],
"ProcessParentPid": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"ProcessPath": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ProcessPid": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"ProcessTerminatedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    },
    "End": "string",
    "Start": "string"
  }
],
"ProductArn": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
```

```
"ProductFields": [  
  {  
    "Comparison": "string",  
    "Key": "string",  
    "Value": "string"  
  }  
],  
"ProductName": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"RecommendationText": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"RecordState": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"Region": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"RelatedFindingsId": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"RelatedFindingsProductArn": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceApplicationArn": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceApplicationArn": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],
```



```
{
  "Comparison": "string",
  "Value": "string"
},
"ResourceApplicationName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsEc2InstanceIamInstanceProfileArn": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsEc2InstanceImageId": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsEc2InstanceIpV4Addresses": [
  {
    "Cidr": "string"
  }
],
"ResourceAwsEc2InstanceIpV6Addresses": [
  {
    "Cidr": "string"
  }
],
"ResourceAwsEc2InstanceKeyName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsEc2InstanceLaunchedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    }
  }
]
```

```
    },
    "End": "string",
    "Start": "string"
  }
],
"ResourceAwsEc2InstanceSubnetId": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsEc2InstanceType": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsEc2InstanceVpcId": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsIamAccessKeyCreatedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    },
    "End": "string",
    "Start": "string"
  }
],
"ResourceAwsIamAccessKeyPrincipalName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsIamAccessKeyStatus": [
  {
    "Comparison": "string",
    "Value": "string"
  }
]
```

```
],
  "ResourceAwsIamAccessKeyUserName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsIamUserUserName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsS3BucketOwnerId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsS3BucketOwnerName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceContainerImageId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceContainerImageName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceContainerLaunchedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
    }
  ],

```

```
    "Start": "string"
  }
],
"ResourceContainerName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceDetailsOther": [
  {
    "Comparison": "string",
    "Key": "string",
    "Value": "string"
  }
],
"ResourceId": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourcePartition": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceRegion": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceTags": [
  {
    "Comparison": "string",
    "Key": "string",
    "Value": "string"
  }
],
"ResourceType": [
  {
    "Comparison": "string",
```

```
    "Value": "string"
  }
],
"Sample": [
  {
    "Value": boolean
  }
],
"SeverityLabel": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"SeverityNormalized": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"SeverityProduct": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"SourceUrl": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ThreatIntelIndicatorCategory": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
```

```
"ThreatIntelIndicatorLastObservedAt": [  
  {  
    "DateRange": {  
      "Unit": "string",  
      "Value": number  
    },  
    "End": "string",  
    "Start": "string"  
  }  
],  
"ThreatIntelIndicatorSource": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ThreatIntelIndicatorSourceUrl": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ThreatIntelIndicatorType": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ThreatIntelIndicatorValue": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"Title": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"Type": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
]
```

```
    }
  ],
  "UpdatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "UserDefinedFields": [
    {
      "Comparison": "string",
      "Key": "string",
      "Value": "string"
    }
  ],
  "VerificationState": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "VulnerabilitiesExploitAvailable": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "VulnerabilitiesFixAvailable": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "WorkflowState": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "WorkflowStatus": [
```

```
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "MaxResults": number,
  "NextToken": "string",
  "SortCriteria": [
    {
      "Field": "string",
      "SortOrder": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Filters

The finding attributes used to define a condition to filter the returned findings.

You can filter by up to 10 finding attributes. For each attribute, you can provide up to 20 filter values.

Note that in the available filter fields, `WorkflowState` is deprecated. To search for a finding based on its workflow status, use `WorkflowStatus`.

Type: [AwsSecurityFindingFilters](#) object

Required: No

MaxResults

The maximum number of findings to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token that is required for pagination. On your first call to the `GetFindings` operation, set the value of this parameter to `NULL`.

For subsequent calls to the operation, to continue listing data, set the value of this parameter to the value returned from the previous response.

Type: String

Required: No

SortCriteria

The finding attributes used to sort the list of returned findings.

Type: Array of [SortCriterion](#) objects

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Findings": [
    {
      "Action": {
        "ActionType": "string",
        "AwsApiCallAction": {
          "AffectedResources": {
            "string" : "string"
          },
          "Api": "string",
          "CallerType": "string",
          "DomainDetails": {
            "Domain": "string"
          },
          "FirstSeen": "string",
          "LastSeen": "string",
          "RemoteIpDetails": {
```

```
    "City": {
      "CityName": "string"
    },
    "Country": {
      "CountryCode": "string",
      "CountryName": "string"
    },
    "GeoLocation": {
      "Lat": number,
      "Lon": number
    },
    "IpAddressV4": "string",
    "Organization": {
      "Asn": number,
      "AsnOrg": "string",
      "Isp": "string",
      "Org": "string"
    }
  },
  "ServiceName": "string"
},
"DnsRequestAction": {
  "Blocked": boolean,
  "Domain": "string",
  "Protocol": "string"
},
"NetworkConnectionAction": {
  "Blocked": boolean,
  "ConnectionDirection": "string",
  "LocalPortDetails": {
    "Port": number,
    "PortName": "string"
  },
  "Protocol": "string",
  "RemoteIpDetails": {
    "City": {
      "CityName": "string"
    },
    "Country": {
      "CountryCode": "string",
      "CountryName": "string"
    },
    "GeoLocation": {
      "Lat": number,
```

```
        "Lon": number
    },
    "IpAddressV4": "string",
    "Organization": {
        "Asn": number,
        "AsnOrg": "string",
        "Isp": "string",
        "Org": "string"
    }
},
"RemotePortDetails": {
    "Port": number,
    "PortName": "string"
}
},
"PortProbeAction": {
    "Blocked": boolean,
    "PortProbeDetails": [
        {
            "LocalIpDetails": {
                "IpAddressV4": "string"
            },
            "LocalPortDetails": {
                "Port": number,
                "PortName": "string"
            },
            "RemoteIpDetails": {
                "City": {
                    "CityName": "string"
                },
                "Country": {
                    "CountryCode": "string",
                    "CountryName": "string"
                },
                "GeoLocation": {
                    "Lat": number,
                    "Lon": number
                },
                "IpAddressV4": "string",
                "Organization": {
                    "Asn": number,
                    "AsnOrg": "string",
                    "Isp": "string",
                    "Org": "string"
                }
            }
        }
    ]
}
```

```
    }
  }
}
],
},
  "AwsAccountId": "string",
  "AwsAccountName": "string",
  "CompanyName": "string",
  "Compliance": {
    "AssociatedStandards": [
      {
        "StandardsId": "string"
      }
    ],
    "RelatedRequirements": [ "string" ],
    "SecurityControlId": "string",
    "SecurityControlParameters": [
      {
        "Name": "string",
        "Value": [ "string" ]
      }
    ],
    "Status": "string",
    "StatusReasons": [
      {
        "Description": "string",
        "ReasonCode": "string"
      }
    ]
  },
  "Confidence": number,
  "CreatedAt": "string",
  "Criticality": number,
  "Description": "string",
  "Detection": {
    "Sequence": {
      "Actors": [
        {
          "Id": "string",
          "Session": {
            "CreatedTime": number,
            "Issuer": "string",
            "MfaStatus": "string",
```

```
        "Uid": "string"
    },
    "User": {
        "Account": {
            "Name": "string",
            "Uid": "string"
        },
        "CredentialUid": "string",
        "Name": "string",
        "Type": "string",
        "Uid": "string"
    }
},
"Endpoints": [
    {
        "AutonomousSystem": {
            "Name": "string",
            "Number": number
        },
        "Connection": {
            "Direction": "string"
        },
        "Domain": "string",
        "Id": "string",
        "Ip": "string",
        "Location": {
            "City": "string",
            "Country": "string",
            "Lat": number,
            "Lon": number
        },
        "Port": number
    }
],
"SequenceIndicators": [
    {
        "Key": "string",
        "Title": "string",
        "Type": "string",
        "Values": [ "string" ]
    }
],
"Signals": [
```

```
    {
      "ActorIds": [ "string" ],
      "Count": number,
      "CreatedAt": number,
      "EndpointIds": [ "string" ],
      "FirstSeenAt": number,
      "Id": "string",
      "LastSeenAt": number,
      "Name": "string",
      "ProductArn": "string",
      "ResourceIds": [ "string" ],
      "Severity": number,
      "SignalIndicators": [
        {
          "Key": "string",
          "Title": "string",
          "Type": "string",
          "Values": [ "string" ]
        }
      ],
      "Title": "string",
      "Type": "string",
      "UpdatedAt": number
    }
  ],
  "Uid": "string"
}
},
"FindingProviderFields": {
  "Confidence": number,
  "Criticality": number,
  "RelatedFindings": [
    {
      "Id": "string",
      "ProductArn": "string"
    }
  ],
  "Severity": {
    "Label": "string",
    "Original": "string"
  },
  "Types": [ "string" ]
},
"FirstObservedAt": "string",
```

```
"GeneratorDetails": {
  "Description": "string",
  "Labels": [ "string" ],
  "Name": "string"
},
"GeneratorId": "string",
"Id": "string",
"LastObservedAt": "string",
"Malware": [
  {
    "Name": "string",
    "Path": "string",
    "State": "string",
    "Type": "string"
  }
],
"Network": {
  "DestinationDomain": "string",
  "DestinationIPv4": "string",
  "DestinationIPv6": "string",
  "DestinationPort": number,
  "Direction": "string",
  "OpenPortRange": {
    "Begin": number,
    "End": number
  },
  "Protocol": "string",
  "SourceDomain": "string",
  "SourceIPv4": "string",
  "SourceIPv6": "string",
  "SourceMac": "string",
  "SourcePort": number
},
"NetworkPath": [
  {
    "ComponentId": "string",
    "ComponentType": "string",
    "Egress": {
      "Destination": {
        "Address": [ "string" ],
        "PortRanges": [
          {
            "Begin": number,
            "End": number
          }
        ]
      }
    }
  }
]
```

```
    }
  ]
},
"Protocol": "string",
"Source": {
  "Address": [ "string" ],
  "PortRanges": [
    {
      "Begin": number,
      "End": number
    }
  ]
}
},
"Ingress": {
  "Destination": {
    "Address": [ "string" ],
    "PortRanges": [
      {
        "Begin": number,
        "End": number
      }
    ]
  },
  "Protocol": "string",
  "Source": {
    "Address": [ "string" ],
    "PortRanges": [
      {
        "Begin": number,
        "End": number
      }
    ]
  }
}
}
],
"Note": {
  "Text": "string",
  "UpdatedAt": "string",
  "UpdatedBy": "string"
},
"PatchSummary": {
  "FailedCount": number,
```



```
    "Id": "string",
    "InstalledCount": number,
    "InstalledOtherCount": number,
    "InstalledPendingReboot": number,
    "InstalledRejectedCount": number,
    "MissingCount": number,
    "Operation": "string",
    "OperationEndTime": "string",
    "OperationStartTime": "string",
    "RebootOption": "string"
  },
  "Process": {
    "LaunchedAt": "string",
    "Name": "string",
    "ParentPid": number,
    "Path": "string",
    "Pid": number,
    "TerminatedAt": "string"
  },
  "ProcessedAt": "string",
  "ProductArn": "string",
  "ProductFields": {
    "string" : "string"
  },
  "ProductName": "string",
  "RecordState": "string",
  "Region": "string",
  "RelatedFindings": [
    {
      "Id": "string",
      "ProductArn": "string"
    }
  ],
  "Remediation": {
    "Recommendation": {
      "Text": "string",
      "Url": "string"
    }
  },
  "Resources": [
    {
      "ApplicationArn": "string",
      "ApplicationName": "string",
      "DataClassification": {
```

```
"DetailedResultsLocation": "string",
"Result": {
  "AdditionalOccurrences": boolean,
  "CustomDataIdentifiers": {
    "Detections": [
      {
        "Arn": "string",
        "Count": number,
        "Name": "string",
        "Occurrences": {
          "Cells": [
            {
              "CellReference": "string",
              "Column": number,
              "ColumnName": "string",
              "Row": number
            }
          ],
          "LineRanges": [
            {
              "End": number,
              "Start": number,
              "StartColumn": number
            }
          ],
          "OffsetRanges": [
            {
              "End": number,
              "Start": number,
              "StartColumn": number
            }
          ],
          "Pages": [
            {
              "LineRange": {
                "End": number,
                "Start": number,
                "StartColumn": number
              },
              "OffsetRange": {
                "End": number,
                "Start": number,
                "StartColumn": number
              }
            }
          ]
        }
      }
    ]
  }
}
```

```
        "PageNumber": number
      }
    ],
    "Records": [
      {
        "JsonPath": "string",
        "RecordIndex": number
      }
    ]
  }
},
"TotalCount": number
},
"MimeType": "string",
"SensitiveData": [
  {
    "Category": "string",
    "Detections": [
      {
        "Count": number,
        "Occurrences": {
          "Cells": [
            {
              "CellReference": "string",
              "Column": number,
              "ColumnName": "string",
              "Row": number
            }
          ],
          "LineRanges": [
            {
              "End": number,
              "Start": number,
              "StartColumn": number
            }
          ],
          "OffsetRanges": [
            {
              "End": number,
              "Start": number,
              "StartColumn": number
            }
          ]
        }
      }
    ]
  }
]
```

```

        "Pages": [
            {
                "LineRange": {
                    "End": number,
                    "Start": number,
                    "StartColumn": number
                },
                "OffsetRange": {
                    "End": number,
                    "Start": number,
                    "StartColumn": number
                },
                "PageNumber": number
            }
        ],
        "Records": [
            {
                "JsonPath": "string",
                "RecordIndex": number
            }
        ],
        "Type": "string"
    }
},
"TotalCount": number
}
],
"SizeClassified": number,
"Status": {
    "Code": "string",
    "Reason": "string"
}
}
},
"Details": {
    "AwsAmazonMqBroker": {
        "AuthenticationStrategy": "string",
        "AutoMinorVersionUpgrade": boolean,
        "BrokerArn": "string",
        "BrokerId": "string",
        "BrokerName": "string",
        "DeploymentMode": "string",
        "EncryptionOptions": {

```

```

        "KmsKeyId": "string",
        "UseAwsOwnedKey": boolean
    },
    "EngineType": "string",
    "EngineVersion": "string",
    "HostInstanceType": "string",
    "LdapServerMetadata": {
        "Hosts": [ "string" ],
        "RoleBase": "string",
        "RoleName": "string",
        "RoleSearchMatching": "string",
        "RoleSearchSubtree": boolean,
        "ServiceAccountUsername": "string",
        "UserBase": "string",
        "UserRoleName": "string",
        "UserSearchMatching": "string",
        "UserSearchSubtree": boolean
    },
    "Logs": {
        "Audit": boolean,
        "AuditLogGroup": "string",
        "General": boolean,
        "GeneralLogGroup": "string",
        "Pending": {
            "Audit": boolean,
            "General": boolean
        }
    },
    "MaintenanceWindowStartTime": {
        "DayOfWeek": "string",
        "TimeOfDay": "string",
        "TimeZone": "string"
    },
    "PubliclyAccessible": boolean,
    "SecurityGroups": [ "string" ],
    "StorageType": "string",
    "SubnetIds": [ "string" ],
    "Users": [
        {
            "PendingChange": "string",
            "Username": "string"
        }
    ]
},

```

```
"AwsApiGatewayRestApi": {
  "ApiKeySource": "string",
  "BinaryMediaTypes": [ "string" ],
  "CreatedDate": "string",
  "Description": "string",
  "EndpointConfiguration": {
    "Types": [ "string" ]
  },
  "Id": "string",
  "MinimumCompressionSize": number,
  "Name": "string",
  "Version": "string"
},
"AwsApiGatewayStage": {
  "AccessLogSettings": {
    "DestinationArn": "string",
    "Format": "string"
  },
  "CacheClusterEnabled": boolean,
  "CacheClusterSize": "string",
  "CacheClusterStatus": "string",
  "CanarySettings": {
    "DeploymentId": "string",
    "PercentTraffic": number,
    "StageVariableOverrides": {
      "string" : "string"
    },
    "UseStageCache": boolean
  },
  "ClientCertificateId": "string",
  "CreatedDate": "string",
  "DeploymentId": "string",
  "Description": "string",
  "DocumentationVersion": "string",
  "LastUpdatedDate": "string",
  "MethodSettings": [
    {
      "CacheDataEncrypted": boolean,
      "CacheTtlInSeconds": number,
      "CachingEnabled": boolean,
      "DataTraceEnabled": boolean,
      "HttpMethod": "string",
      "LoggingLevel": "string",
      "MetricsEnabled": boolean,
```

```

        "RequireAuthorizationForCacheControl": boolean,
        "ResourcePath": "string",
        "ThrottlingBurstLimit": number,
        "ThrottlingRateLimit": number,
        "UnauthorizedCacheControlHeaderStrategy": "string"
    }
],
"StageName": "string",
"TracingEnabled": boolean,
"Variables": {
    "string" : "string"
},
"WebAclArn": "string"
},
"AwsApiGatewayV2Api": {
    "ApiEndpoint": "string",
    "ApiId": "string",
    "ApiKeySelectionExpression": "string",
    "CorsConfiguration": {
        "AllowCredentials": boolean,
        "AllowHeaders": [ "string" ],
        "AllowMethods": [ "string" ],
        "AllowOrigins": [ "string" ],
        "ExposeHeaders": [ "string" ],
        "MaxAge": number
    },
    "CreateDate": "string",
    "Description": "string",
    "Name": "string",
    "ProtocolType": "string",
    "RouteSelectionExpression": "string",
    "Version": "string"
},
"AwsApiGatewayV2Stage": {
    "AccessLogSettings": {
        "DestinationArn": "string",
        "Format": "string"
    },
    "ApiGatewayManaged": boolean,
    "AutoDeploy": boolean,
    "ClientCertificateId": "string",
    "CreateDate": "string",
    "DefaultRouteSettings": {
        "DataTraceEnabled": boolean,

```

```

        "DetailedMetricsEnabled": boolean,
        "LoggingLevel": "string",
        "ThrottlingBurstLimit": number,
        "ThrottlingRateLimit": number
    },
    "DeploymentId": "string",
    "Description": "string",
    "LastDeploymentStatusMessage": "string",
    "LastUpdatedDate": "string",
    "RouteSettings": {
        "DataTraceEnabled": boolean,
        "DetailedMetricsEnabled": boolean,
        "LoggingLevel": "string",
        "ThrottlingBurstLimit": number,
        "ThrottlingRateLimit": number
    },
    "StageName": "string",
    "StageVariables": {
        "string" : "string"
    }
},
"AwsAppSyncGraphQLApi": {
    "AdditionalAuthenticationProviders": [
        {
            "AuthenticationType": "string",
            "LambdaAuthorizerConfig": {
                "AuthorizerResultTtlInSeconds": number,
                "AuthorizerUri": "string",
                "IdentityValidationExpression": "string"
            },
            "OpenIdConnectConfig": {
                "AuthTtl": number,
                "ClientId": "string",
                "IatTtl": number,
                "Issuer": "string"
            },
            "UserPoolConfig": {
                "AppIdClientRegex": "string",
                "AwsRegion": "string",
                "DefaultAction": "string",
                "UserPoolId": "string"
            }
        }
    ]
},

```



```
"ApiId": "string",
"Arn": "string",
"AuthenticationType": "string",
"Id": "string",
"LambdaAuthorizerConfig": {
  "AuthorizerResultTtlInSeconds": number,
  "AuthorizerUri": "string",
  "IdentityValidationExpression": "string"
},
"LogConfig": {
  "CloudWatchLogsRoleArn": "string",
  "ExcludeVerboseContent": boolean,
  "FieldLogLevel": "string"
},
"Name": "string",
"OpenIdConnectConfig": {
  "AuthTtl": number,
  "ClientId": "string",
  "IatTtl": number,
  "Issuer": "string"
},
"UserPoolConfig": {
  "AppIdClientRegex": "string",
  "AwsRegion": "string",
  "DefaultAction": "string",
  "UserPoolId": "string"
},
"WafWebAclArn": "string",
"XrayEnabled": boolean
},
"AwsAthenaWorkGroup": {
  "Configuration": {
    "ResultConfiguration": {
      "EncryptionConfiguration": {
        "EncryptionOption": "string",
        "KmsKey": "string"
      }
    }
  }
},
"Description": "string",
"Name": "string",
"State": "string"
},
"AwsAutoScalingAutoScalingGroup": {
```

```
"AvailabilityZones": [
  {
    "Value": "string"
  }
],
"CapacityRebalance": boolean,
"CreatedTime": "string",
"HealthCheckGracePeriod": number,
"HealthCheckType": "string",
"LaunchConfigurationName": "string",
"LaunchTemplate": {
  "LaunchTemplateId": "string",
  "LaunchTemplateName": "string",
  "Version": "string"
},
"LoadBalancerNames": [ "string" ],
"MixedInstancesPolicy": {
  "InstancesDistribution": {
    "OnDemandAllocationStrategy": "string",
    "OnDemandBaseCapacity": number,
    "OnDemandPercentageAboveBaseCapacity": number,
    "SpotAllocationStrategy": "string",
    "SpotInstancePools": number,
    "SpotMaxPrice": "string"
  },
  "LaunchTemplate": {
    "LaunchTemplateSpecification": {
      "LaunchTemplateId": "string",
      "LaunchTemplateName": "string",
      "Version": "string"
    },
    "Overrides": [
      {
        "InstanceType": "string",
        "WeightedCapacity": "string"
      }
    ]
  }
}
},
"AwsAutoScalingLaunchConfiguration": {
  "AssociatePublicIpAddress": boolean,
  "BlockDeviceMappings": [
    {
```

```
    "DeviceName": "string",
    "Ebs": {
      "DeleteOnTermination": boolean,
      "Encrypted": boolean,
      "Iops": number,
      "SnapshotId": "string",
      "VolumeSize": number,
      "VolumeType": "string"
    },
    "NoDevice": boolean,
    "VirtualName": "string"
  }
],
"ClassicLinkVpcId": "string",
"ClassicLinkVpcSecurityGroups": [ "string" ],
"CreatedTime": "string",
"EbsOptimized": boolean,
"IamInstanceProfile": "string",
"ImageId": "string",
"InstanceMonitoring": {
  "Enabled": boolean
},
"InstanceType": "string",
"KernelId": "string",
"KeyName": "string",
"LaunchConfigurationName": "string",
"MetadataOptions": {
  "HttpEndpoint": "string",
  "HttpPutResponseHopLimit": number,
  "HttpTokens": "string"
},
"PlacementTenancy": "string",
"RamdiskId": "string",
"SecurityGroups": [ "string" ],
"SpotPrice": "string",
"UserData": "string"
},
"AwsBackupBackupPlan": {
  "BackupPlan": {
    "AdvancedBackupSettings": [
      {
        "BackupOptions": {
          "string": "string"
        }
      }
    ]
  }
},
```

```

        "ResourceType": "string"
    }
],
"BackupPlanName": "string",
"BackupPlanRule": [
    {
        "CompletionWindowMinutes": number,
        "CopyActions": [
            {
                "DestinationBackupVaultArn": "string",
                "Lifecycle": {
                    "DeleteAfterDays": number,
                    "MoveToColdStorageAfterDays": number
                }
            }
        ],
        "EnableContinuousBackup": boolean,
        "Lifecycle": {
            "DeleteAfterDays": number,
            "MoveToColdStorageAfterDays": number
        },
        "RuleId": "string",
        "RuleName": "string",
        "ScheduleExpression": "string",
        "StartWindowMinutes": number,
        "TargetBackupVault": "string"
    }
]
},
"BackupPlanArn": "string",
"BackupPlanId": "string",
"VersionId": "string"
},
"AwsBackupBackupVault": {
    "AccessPolicy": "string",
    "BackupVaultArn": "string",
    "BackupVaultName": "string",
    "EncryptionKeyArn": "string",
    "Notifications": {
        "BackupVaultEvents": [ "string" ],
        "SnsTopicArn": "string"
    }
},
"AwsBackupRecoveryPoint": {

```

```
"BackupSizeInBytes": number,
"BackupVaultArn": "string",
"BackupVaultName": "string",
"CalculatedLifecycle": {
  "DeleteAt": "string",
  "MoveToColdStorageAt": "string"
},
"CompletionDate": "string",
"CreatedBy": {
  "BackupPlanArn": "string",
  "BackupPlanId": "string",
  "BackupPlanVersion": "string",
  "BackupRuleId": "string"
},
"CreationDate": "string",
"EncryptionKeyArn": "string",
"IamRoleArn": "string",
"IsEncrypted": boolean,
"LastRestoreTime": "string",
"Lifecycle": {
  "DeleteAfterDays": number,
  "MoveToColdStorageAfterDays": number
},
"RecoveryPointArn": "string",
"ResourceArn": "string",
"ResourceType": "string",
"SourceBackupVaultArn": "string",
"Status": "string",
"StatusMessage": "string",
"StorageClass": "string"
},
"AwsCertificateManagerCertificate": {
  "CertificateAuthorityArn": "string",
  "CreatedAt": "string",
  "DomainName": "string",
  "DomainValidationOptions": [
    {
      "DomainName": "string",
      "ResourceRecord": {
        "Name": "string",
        "Type": "string",
        "Value": "string"
      }
    }
  ],
  "ValidationDomain": "string",
```

```
        "ValidationEmails": [ "string" ],
        "ValidationMethod": "string",
        "ValidationStatus": "string"
    }
],
"ExtendedKeyUsages": [
    {
        "Name": "string",
        "Oid": "string"
    }
],
"FailureReason": "string",
"ImportedAt": "string",
"InUseBy": [ "string" ],
"IssuedAt": "string",
"Issuer": "string",
"KeyAlgorithm": "string",
"KeyUsages": [
    {
        "Name": "string"
    }
],
"NotAfter": "string",
"NotBefore": "string",
"Options": {
    "CertificateTransparencyLoggingPreference": "string"
},
"RenewalEligibility": "string",
"RenewalSummary": {
    "DomainValidationOptions": [
        {
            "DomainName": "string",
            "ResourceRecord": {
                "Name": "string",
                "Type": "string",
                "Value": "string"
            },
            "ValidationDomain": "string",
            "ValidationEmails": [ "string" ],
            "ValidationMethod": "string",
            "ValidationStatus": "string"
        }
    ],
    "RenewalStatus": "string",
```

```
        "RenewalStatusReason": "string",
        "UpdatedAt": "string"
    },
    "Serial": "string",
    "SignatureAlgorithm": "string",
    "Status": "string",
    "Subject": "string",
    "SubjectAlternativeNames": [ "string" ],
    "Type": "string"
},
"AwsCloudFormationStack": {
    "Capabilities": [ "string" ],
    "CreationTime": "string",
    "Description": "string",
    "DisableRollback": boolean,
    "DriftInformation": {
        "StackDriftStatus": "string"
    },
    "EnableTerminationProtection": boolean,
    "LastUpdatedTime": "string",
    "NotificationArns": [ "string" ],
    "Outputs": [
        {
            "Description": "string",
            "OutputKey": "string",
            "OutputValue": "string"
        }
    ],
    "RoleArn": "string",
    "StackId": "string",
    "StackName": "string",
    "StackStatus": "string",
    "StackStatusReason": "string",
    "TimeoutInMinutes": number
},
"AwsCloudFrontDistribution": {
    "CacheBehaviors": {
        "Items": [
            {
                "ViewerProtocolPolicy": "string"
            }
        ]
    },
    "DefaultCacheBehavior": {
```

```

    "ViewerProtocolPolicy": "string"
  },
  "DefaultRootObject": "string",
  "DomainName": "string",
  "ETag": "string",
  "LastModifiedTime": "string",
  "Logging": {
    "Bucket": "string",
    "Enabled": boolean,
    "IncludeCookies": boolean,
    "Prefix": "string"
  },
  "OriginGroups": {
    "Items": [
      {
        "FailoverCriteria": {
          "StatusCodes": {
            "Items": [ number ],
            "Quantity": number
          }
        }
      }
    ]
  },
  "Origins": {
    "Items": [
      {
        "CustomOriginConfig": {
          "HttpPort": number,
          "HttpsPort": number,
          "OriginKeepaliveTimeout": number,
          "OriginProtocolPolicy": "string",
          "OriginReadTimeout": number,
          "OriginSslProtocols": {
            "Items": [ "string" ],
            "Quantity": number
          }
        },
        "DomainName": "string",
        "Id": "string",
        "OriginPath": "string",
        "S3OriginConfig": {
          "OriginAccessIdentity": "string"
        }
      }
    ]
  }
}

```



```

    }
  ]
},
"Status": "string",
"ViewerCertificate": {
  "AcmCertificateArn": "string",
  "Certificate": "string",
  "CertificateSource": "string",
  "CloudFrontDefaultCertificate": boolean,
  "IamCertificateId": "string",
  "MinimumProtocolVersion": "string",
  "SslSupportMethod": "string"
},
"WebAclId": "string"
},
"AwsCloudTrailTrail": {
  "CloudWatchLogsLogGroupArn": "string",
  "CloudWatchLogsRoleArn": "string",
  "HasCustomEventSelectors": boolean,
  "HomeRegion": "string",
  "IncludeGlobalServiceEvents": boolean,
  "IsMultiRegionTrail": boolean,
  "IsOrganizationTrail": boolean,
  "KmsKeyId": "string",
  "LogFileValidationEnabled": boolean,
  "Name": "string",
  "S3BucketName": "string",
  "S3KeyPrefix": "string",
  "SnsTopicArn": "string",
  "SnsTopicName": "string",
  "TrailArn": "string"
},
"AwsCloudWatchAlarm": {
  "ActionsEnabled": boolean,
  "AlarmActions": [ "string" ],
  "AlarmArn": "string",
  "AlarmConfigurationUpdatedTimestamp": "string",
  "AlarmDescription": "string",
  "AlarmName": "string",
  "ComparisonOperator": "string",
  "DatapointsToAlarm": number,
  "Dimensions": [
    {
      "Name": "string",

```

```
        "Value": "string"
      }
    ],
    "EvaluateLowSampleCountPercentile": "string",
    "EvaluationPeriods": number,
    "ExtendedStatistic": "string",
    "InsufficientDataActions": [ "string" ],
    "MetricName": "string",
    "Namespace": "string",
    "OkActions": [ "string" ],
    "Period": number,
    "Statistic": "string",
    "Threshold": number,
    "ThresholdMetricId": "string",
    "TreatMissingData": "string",
    "Unit": "string"
  },
  "AwsCodeBuildProject": {
    "Artifacts": [
      {
        "ArtifactIdentifier": "string",
        "EncryptionDisabled": boolean,
        "Location": "string",
        "Name": "string",
        "NamespaceType": "string",
        "OverrideArtifactName": boolean,
        "Packaging": "string",
        "Path": "string",
        "Type": "string"
      }
    ],
    "EncryptionKey": "string",
    "Environment": {
      "Certificate": "string",
      "EnvironmentVariables": [
        {
          "Name": "string",
          "Type": "string",
          "Value": "string"
        }
      ]
    },
    "ImagePullCredentialsType": "string",
    "PrivilegedMode": boolean,
    "RegistryCredential": {
```

```
        "Credential": "string",
        "CredentialProvider": "string"
    },
    "Type": "string"
},
"LogsConfig": {
    "CloudWatchLogs": {
        "GroupName": "string",
        "Status": "string",
        "StreamName": "string"
    },
    "S3Logs": {
        "EncryptionDisabled": boolean,
        "Location": "string",
        "Status": "string"
    }
},
"Name": "string",
"SecondaryArtifacts": [
    {
        "ArtifactIdentifier": "string",
        "EncryptionDisabled": boolean,
        "Location": "string",
        "Name": "string",
        "NamespaceType": "string",
        "OverrideArtifactName": boolean,
        "Packaging": "string",
        "Path": "string",
        "Type": "string"
    }
],
"ServiceRole": "string",
"Source": {
    "GitCloneDepth": number,
    "InsecureSsl": boolean,
    "Location": "string",
    "Type": "string"
},
"VpcConfig": {
    "SecurityGroupIds": [ "string" ],
    "Subnets": [ "string" ],
    "VpcId": "string"
}
},
```

```
"AwsDmsEndpoint": {
  "CertificateArn": "string",
  "DatabaseName": "string",
  "EndpointArn": "string",
  "EndpointIdentifier": "string",
  "EndpointType": "string",
  "EngineName": "string",
  "ExternalId": "string",
  "ExtraConnectionAttributes": "string",
  "KmsKeyId": "string",
  "Port": number,
  "ServerName": "string",
  "SslMode": "string",
  "Username": "string"
},
"AwsDmsReplicationInstance": {
  "AllocatedStorage": number,
  "AutoMinorVersionUpgrade": boolean,
  "AvailabilityZone": "string",
  "EngineVersion": "string",
  "KmsKeyId": "string",
  "MultiAZ": boolean,
  "PreferredMaintenanceWindow": "string",
  "PubliclyAccessible": boolean,
  "ReplicationInstanceClass": "string",
  "ReplicationInstanceIdentifier": "string",
  "ReplicationSubnetGroup": {
    "ReplicationSubnetGroupIdentifier": "string"
  },
  "VpcSecurityGroups": [
    {
      "VpcSecurityGroupId": "string"
    }
  ]
},
"AwsDmsReplicationTask": {
  "CdcStartPosition": "string",
  "CdcStartTime": "string",
  "CdcStopPosition": "string",
  "Id": "string",
  "MigrationType": "string",
  "ReplicationInstanceArn": "string",
  "ReplicationTaskIdentifier": "string",
  "ReplicationTaskSettings": "string",
```

```
    "ResourceIdentifier": "string",
    "SourceEndpointArn": "string",
    "TableMappings": "string",
    "TargetEndpointArn": "string",
    "TaskData": "string"
  },
  "AwsDynamoDbTable": {
    "AttributeDefinitions": [
      {
        "AttributeName": "string",
        "AttributeType": "string"
      }
    ],
    "BillingModeSummary": {
      "BillingMode": "string",
      "LastUpdateToPayPerRequestDateTime": "string"
    },
    "CreationDateTime": "string",
    "DeletionProtectionEnabled": boolean,
    "GlobalSecondaryIndexes": [
      {
        "Backfilling": boolean,
        "IndexArn": "string",
        "IndexName": "string",
        "IndexSizeBytes": number,
        "IndexStatus": "string",
        "ItemCount": number,
        "KeySchema": [
          {
            "AttributeName": "string",
            "KeyType": "string"
          }
        ],
        "Projection": {
          "NonKeyAttributes": [ "string" ],
          "ProjectionType": "string"
        },
        "ProvisionedThroughput": {
          "LastDecreaseDateTime": "string",
          "LastIncreaseDateTime": "string",
          "NumberOfDecreasesToday": number,
          "ReadCapacityUnits": number,
          "WriteCapacityUnits": number
        }
      }
    ]
  }
}
```

```
    }
  ],
  "GlobalTableVersion": "string",
  "ItemCount": number,
  "KeySchema": [
    {
      "AttributeName": "string",
      "KeyType": "string"
    }
  ],
  "LatestStreamArn": "string",
  "LatestStreamLabel": "string",
  "LocalSecondaryIndexes": [
    {
      "IndexArn": "string",
      "IndexName": "string",
      "KeySchema": [
        {
          "AttributeName": "string",
          "KeyType": "string"
        }
      ],
      "Projection": {
        "NonKeyAttributes": [ "string" ],
        "ProjectionType": "string"
      }
    }
  ],
  "ProvisionedThroughput": {
    "LastDecreaseDateTime": "string",
    "LastIncreaseDateTime": "string",
    "NumberOfDecreasesToday": number,
    "ReadCapacityUnits": number,
    "WriteCapacityUnits": number
  },
  "Replicas": [
    {
      "GlobalSecondaryIndexes": [
        {
          "IndexName": "string",
          "ProvisionedThroughputOverride": {
            "ReadCapacityUnits": number
          }
        }
      ]
    }
  ]
}
```

```

    ],
    "KmsMasterKeyId": "string",
    "ProvisionedThroughputOverride": {
      "ReadCapacityUnits": number
    },
    "RegionName": "string",
    "ReplicaStatus": "string",
    "ReplicaStatusDescription": "string"
  }
],
"RestoreSummary": {
  "RestoreDateTime": "string",
  "RestoreInProgress": boolean,
  "SourceBackupArn": "string",
  "SourceTableArn": "string"
},
"SseDescription": {
  "InaccessibleEncryptionDateTime": "string",
  "KmsMasterKeyArn": "string",
  "SseType": "string",
  "Status": "string"
},
"StreamSpecification": {
  "StreamEnabled": boolean,
  "StreamViewType": "string"
},
"TableId": "string",
"TableName": "string",
"TableSizeBytes": number,
"TableStatus": "string"
},
"AwsEc2ClientVpnEndpoint": {
  "AuthenticationOptions": [
    {
      "ActiveDirectory": {
        "DirectoryId": "string"
      },
      "FederatedAuthentication": {
        "SamlProviderArn": "string",
        "SelfServiceSamlProviderArn": "string"
      },
      "MutualAuthentication": {
        "ClientRootCertificateChain": "string"
      }
    }
  ]
}

```

```
        "Type": "string"
      }
    ],
    "ClientCidrBlock": "string",
    "ClientConnectOptions": {
      "Enabled": boolean,
      "LambdaFunctionArn": "string",
      "Status": {
        "Code": "string",
        "Message": "string"
      }
    },
    "ClientLoginBannerOptions": {
      "BannerText": "string",
      "Enabled": boolean
    },
    "ClientVpnEndpointId": "string",
    "ConnectionLogOptions": {
      "CloudwatchLogGroup": "string",
      "CloudwatchLogStream": "string",
      "Enabled": boolean
    },
    "Description": "string",
    "DnsServer": [ "string" ],
    "SecurityGroupIdSet": [ "string" ],
    "SelfServicePortalUrl": "string",
    "ServerCertificateArn": "string",
    "SessionTimeoutHours": number,
    "SplitTunnel": boolean,
    "TransportProtocol": "string",
    "VpcId": "string",
    "VpnPort": number
  },
  "AwsEc2Eip": {
    "AllocationId": "string",
    "AssociationId": "string",
    "Domain": "string",
    "InstanceId": "string",
    "NetworkBorderGroup": "string",
    "NetworkInterfaceId": "string",
    "NetworkInterfaceOwnerId": "string",
    "PrivateIpAddress": "string",
    "PublicIp": "string",
    "PublicIpv4Pool": "string"
  }
}
```



```
    },
    "AwsEc2Instance": {
      "IamInstanceProfileArn": "string",
      "ImageId": "string",
      "IPv4Addresses": [ "string" ],
      "IPv6Addresses": [ "string" ],
      "KeyName": "string",
      "LaunchedAt": "string",
      "MetadataOptions": {
        "HttpEndpoint": "string",
        "HttpProtocolIpv6": "string",
        "HttpPutResponseHopLimit": number,
        "HttpTokens": "string",
        "InstanceMetadataTags": "string"
      },
      "Monitoring": {
        "State": "string"
      },
      "NetworkInterfaces": [
        {
          "NetworkInterfaceId": "string"
        }
      ],
      "SubnetId": "string",
      "Type": "string",
      "VirtualizationType": "string",
      "VpcId": "string"
    },
    "AwsEc2LaunchTemplate": {
      "DefaultVersionNumber": number,
      "Id": "string",
      "LatestVersionNumber": number,
      "LaunchTemplateData": {
        "BlockDeviceMappingSet": [
          {
            "DeviceName": "string",
            "Ebs": {
              "DeleteOnTermination": boolean,
              "Encrypted": boolean,
              "Iops": number,
              "KmsKeyId": "string",
              "SnapshotId": "string",
              "Throughput": number,
              "VolumeSize": number,
            }
          }
        ]
      }
    }
  }
}
```

```
        "VolumeType": "string"
      },
      "NoDevice": "string",
      "VirtualName": "string"
    }
  ],
  "CapacityReservationSpecification": {
    "CapacityReservationPreference": "string",
    "CapacityReservationTarget": {
      "CapacityReservationId": "string",
      "CapacityReservationResourceGroupArn": "string"
    }
  },
  "CpuOptions": {
    "CoreCount": number,
    "ThreadsPerCore": number
  },
  "CreditSpecification": {
    "CpuCredits": "string"
  },
  "DisableApiStop": boolean,
  "DisableApiTermination": boolean,
  "EbsOptimized": boolean,
  "ElasticGpuSpecificationSet": [
    {
      "Type": "string"
    }
  ],
  "ElasticInferenceAcceleratorSet": [
    {
      "Count": number,
      "Type": "string"
    }
  ],
  "EnclaveOptions": {
    "Enabled": boolean
  },
  "HibernationOptions": {
    "Configured": boolean
  },
  "IamInstanceProfile": {
    "Arn": "string",
    "Name": "string"
  },
}
```

```
"ImageId": "string",
"InstanceInitiatedShutdownBehavior": "string",
"InstanceMarketOptions": {
  "MarketType": "string",
  "SpotOptions": {
    "BlockDurationMinutes": number,
    "InstanceInterruptionBehavior": "string",
    "MaxPrice": "string",
    "SpotInstanceType": "string",
    "ValidUntil": "string"
  }
},
"InstanceRequirements": {
  "AcceleratorCount": {
    "Max": number,
    "Min": number
  },
  "AcceleratorManufacturers": [ "string" ],
  "AcceleratorNames": [ "string" ],
  "AcceleratorTotalMemoryMiB": {
    "Max": number,
    "Min": number
  },
  "AcceleratorTypes": [ "string" ],
  "BareMetal": "string",
  "BaselineEbsBandwidthMbps": {
    "Max": number,
    "Min": number
  },
  "BurstablePerformance": "string",
  "CpuManufacturers": [ "string" ],
  "ExcludedInstanceTypes": [ "string" ],
  "InstanceGenerations": [ "string" ],
  "LocalStorage": "string",
  "LocalStorageTypes": [ "string" ],
  "MemoryGiBPerVCpu": {
    "Max": number,
    "Min": number
  },
  "MemoryMiB": {
    "Max": number,
    "Min": number
  },
  "NetworkInterfaceCount": {
```

```
        "Max": number,
        "Min": number
    },
    "OnDemandMaxPricePercentageOverLowestPrice": number,
    "RequireHibernateSupport": boolean,
    "SpotMaxPricePercentageOverLowestPrice": number,
    "TotalLocalStorageGB": {
        "Max": number,
        "Min": number
    },
    "VCpuCount": {
        "Max": number,
        "Min": number
    }
},
"InstanceType": "string",
"KernelId": "string",
"KeyName": "string",
"LicenseSet": [
    {
        "LicenseConfigurationArn": "string"
    }
],
"MaintenanceOptions": {
    "AutoRecovery": "string"
},
"MetadataOptions": {
    "HttpEndpoint": "string",
    "HttpProtocolIpv6": "string",
    "HttpPutResponseHopLimit": number,
    "HttpTokens": "string",
    "InstanceMetadataTags": "string"
},
"Monitoring": {
    "Enabled": boolean
},
"NetworkInterfaceSet": [
    {
        "AssociateCarrierIpAddress": boolean,
        "AssociatePublicIpAddress": boolean,
        "DeleteOnTermination": boolean,
        "Description": "string",
        "DeviceIndex": number,
        "Groups": [ "string " ],
    }
]
```

```
    "InterfaceType": "string",
    "Ipv4PrefixCount": number,
    "Ipv4Prefixes": [
      {
        "Ipv4Prefix": "string"
      }
    ],
    "Ipv6AddressCount": number,
    "Ipv6Addresses": [
      {
        "Ipv6Address": "string"
      }
    ],
    "Ipv6PrefixCount": number,
    "Ipv6Prefixes": [
      {
        "Ipv6Prefix": "string"
      }
    ],
    "NetworkCardIndex": number,
    "NetworkInterfaceId": "string",
    "PrivateIpAddress": "string",
    "PrivateIpAddresses": [
      {
        "Primary": boolean,
        "PrivateIpAddress": "string"
      }
    ],
    "SecondaryPrivateIpAddressCount": number,
    "SubnetId": "string"
  }
],
"Placement": {
  "Affinity": "string",
  "AvailabilityZone": "string",
  "GroupName": "string",
  "HostId": "string",
  "HostResourceGroupArn": "string",
  "PartitionNumber": number,
  "SpreadDomain": "string",
  "Tenancy": "string"
},
"PrivateDnsNameOptions": {
  "EnableResourceNameDnsAAAARecord": boolean,
```

```

        "EnableResourceNameDnsARecord": boolean,
        "HostnameType": "string"
    },
    "RamDiskId": "string",
    "SecurityGroupIdSet": [ "string" ],
    "SecurityGroupSet": [ "string" ],
    "UserData": "string"
},
"LaunchTemplateName": "string"
},
"AwsEc2NetworkAcl": {
    "Associations": [
        {
            "NetworkAclAssociationId": "string",
            "NetworkAclId": "string",
            "SubnetId": "string"
        }
    ],
    "Entries": [
        {
            "CidrBlock": "string",
            "Egress": boolean,
            "IcmpTypeCode": {
                "Code": number,
                "Type": number
            },
            "Ipv6CidrBlock": "string",
            "PortRange": {
                "From": number,
                "To": number
            },
            "Protocol": "string",
            "RuleAction": "string",
            "RuleNumber": number
        }
    ],
    "IsDefault": boolean,
    "NetworkAclId": "string",
    "OwnerId": "string",
    "VpcId": "string"
},
"AwsEc2NetworkInterface": {
    "Attachment": {
        "AttachmentId": "string",

```

```
    "AttachTime": "string",
    "DeleteOnTermination": boolean,
    "DeviceIndex": number,
    "InstanceId": "string",
    "InstanceOwnerId": "string",
    "Status": "string"
  },
  "IPv6Addresses": [
    {
      "IPv6Address": "string"
    }
  ],
  "NetworkInterfaceId": "string",
  "PrivateIpAddresses": [
    {
      "PrivateDnsName": "string",
      "PrivateIpAddress": "string"
    }
  ],
  "PublicDnsName": "string",
  "PublicIp": "string",
  "SecurityGroups": [
    {
      "GroupId": "string",
      "GroupName": "string"
    }
  ],
  "SourceDestCheck": boolean
},
"AwsEc2RouteTable": {
  "AssociationSet": [
    {
      "AssociationState": {
        "State": "string",
        "StatusMessage": "string"
      },
      "GatewayId": "string",
      "Main": boolean,
      "RouteTableAssociationId": "string",
      "RouteTableId": "string",
      "SubnetId": "string"
    }
  ],
  "OwnerId": "string",
```

```
"PropagatingVgwSet": [  
  {  
    "GatewayId": "string"  
  }  
],  
"RouteSet": [  
  {  
    "CarrierGatewayId": "string",  
    "CoreNetworkArn": "string",  
    "DestinationCidrBlock": "string",  
    "DestinationIpv6CidrBlock": "string",  
    "DestinationPrefixListId": "string",  
    "EgressOnlyInternetGatewayId": "string",  
    "GatewayId": "string",  
    "InstanceId": "string",  
    "InstanceOwnerId": "string",  
    "LocalGatewayId": "string",  
    "NatGatewayId": "string",  
    "NetworkInterfaceId": "string",  
    "Origin": "string",  
    "State": "string",  
    "TransitGatewayId": "string",  
    "VpcPeeringConnectionId": "string"  
  }  
],  
"RouteTableId": "string",  
"VpcId": "string"  
},  
"AwsEc2SecurityGroup": {  
  "GroupId": "string",  
  "GroupName": "string",  
  "IpPermissions": [  
    {  
      "FromPort": number,  
      "IpProtocol": "string",  
      "IpRanges": [  
        {  
          "CidrIp": "string"  
        }  
      ],  
      "Ipv6Ranges": [  
        {  
          "CidrIpv6": "string"  
        }  
      ]  
    }  
  ]  
}
```



```
    ],
    "PrefixListIds": [
      {
        "PrefixListId": "string"
      }
    ],
    "ToPort": number,
    "UserIdGroupPairs": [
      {
        "GroupId": "string",
        "GroupName": "string",
        "PeeringStatus": "string",
        "UserId": "string",
        "VpcId": "string",
        "VpcPeeringConnectionId": "string"
      }
    ]
  }
],
"IpPermissionsEgress": [
  {
    "FromPort": number,
    "IpProtocol": "string",
    "IpRanges": [
      {
        "CidrIp": "string"
      }
    ],
    "Ipv6Ranges": [
      {
        "CidrIpv6": "string"
      }
    ],
    "PrefixListIds": [
      {
        "PrefixListId": "string"
      }
    ],
    "ToPort": number,
    "UserIdGroupPairs": [
      {
        "GroupId": "string",
        "GroupName": "string",
        "PeeringStatus": "string",
```

```

        "UserId": "string",
        "VpcId": "string",
        "VpcPeeringConnectionId": "string"
    }
]
}
],
"OwnerId": "string",
"VpcId": "string"
},
"AwsEc2Subnet": {
    "AssignIpv6AddressOnCreation": boolean,
    "AvailabilityZone": "string",
    "AvailabilityZoneId": "string",
    "AvailableIpAddressCount": number,
    "CidrBlock": "string",
    "DefaultForAz": boolean,
    "Ipv6CidrBlockAssociationSet": [
        {
            "AssociationId": "string",
            "CidrBlockState": "string",
            "Ipv6CidrBlock": "string"
        }
    ],
    "MapPublicIpOnLaunch": boolean,
    "OwnerId": "string",
    "State": "string",
    "SubnetArn": "string",
    "SubnetId": "string",
    "VpcId": "string"
},
"AwsEc2TransitGateway": {
    "AmazonSideAsn": number,
    "AssociationDefaultRouteTableId": "string",
    "AutoAcceptSharedAttachments": "string",
    "DefaultRouteTableAssociation": "string",
    "DefaultRouteTablePropagation": "string",
    "Description": "string",
    "DnsSupport": "string",
    "Id": "string",
    "MulticastSupport": "string",
    "PropagationDefaultRouteTableId": "string",
    "TransitGatewayCidrBlocks": [ "string" ],
    "VpnEcmpSupport": "string"
}

```

```
    },
    "AwsEc2Volume": {
      "Attachments": [
        {
          "AttachTime": "string",
          "DeleteOnTermination": boolean,
          "InstanceId": "string",
          "Status": "string"
        }
      ],
      "CreateTime": "string",
      "DeviceName": "string",
      "Encrypted": boolean,
      "KmsKeyId": "string",
      "Size": number,
      "SnapshotId": "string",
      "Status": "string",
      "VolumeId": "string",
      "VolumeScanStatus": "string",
      "VolumeType": "string"
    },
    "AwsEc2Vpc": {
      "CidrBlockAssociationSet": [
        {
          "AssociationId": "string",
          "CidrBlock": "string",
          "CidrBlockState": "string"
        }
      ],
      "DhcpOptionsId": "string",
      "Ipv6CidrBlockAssociationSet": [
        {
          "AssociationId": "string",
          "CidrBlockState": "string",
          "Ipv6CidrBlock": "string"
        }
      ],
      "State": "string"
    },
    "AwsEc2VpcEndpointService": {
      "AcceptanceRequired": boolean,
      "AvailabilityZones": [ "string" ],
      "BaseEndpointDnsNames": [ "string" ],
      "GatewayLoadBalancerArns": [ "string" ],
```

```
"ManagesVpcEndpoints": boolean,
"NetworkLoadBalancerArns": [ "string" ],
"PrivateDnsName": "string",
"ServiceId": "string",
"ServiceName": "string",
"ServiceState": "string",
"ServiceType": [
  {
    "ServiceType": "string"
  }
]
},
"AwsEc2VpcPeeringConnection": {
  "AcceptorVpcInfo": {
    "CidrBlock": "string",
    "CidrBlockSet": [
      {
        "CidrBlock": "string"
      }
    ],
    "Ipv6CidrBlockSet": [
      {
        "Ipv6CidrBlock": "string"
      }
    ],
  },
  "OwnerId": "string",
  "PeeringOptions": {
    "AllowDnsResolutionFromRemoteVpc": boolean,
    "AllowEgressFromLocalClassicLinkToRemoteVpc": boolean,
    "AllowEgressFromLocalVpcToRemoteClassicLink": boolean
  },
  "Region": "string",
  "VpcId": "string"
},
"ExpirationTime": "string",
"RequesterVpcInfo": {
  "CidrBlock": "string",
  "CidrBlockSet": [
    {
      "CidrBlock": "string"
    }
  ],
  "Ipv6CidrBlockSet": [
    {
```

```

        "Ipv6CidrBlock": "string"
    }
],
"OwnerId": "string",
"PeeringOptions": {
    "AllowDnsResolutionFromRemoteVpc": boolean,
    "AllowEgressFromLocalClassicLinkToRemoteVpc": boolean,
    "AllowEgressFromLocalVpcToRemoteClassicLink": boolean
},
"Region": "string",
"VpcId": "string"
},
"Status": {
    "Code": "string",
    "Message": "string"
},
"VpcPeeringConnectionId": "string"
},
"AwsEc2VpnConnection": {
    "Category": "string",
    "CustomerGatewayConfiguration": "string",
    "CustomerGatewayId": "string",
    "Options": {
        "StaticRoutesOnly": boolean,
        "TunnelOptions": [
            {
                "DpdTimeoutSeconds": number,
                "IkeVersions": [ "string" ],
                "OutsideIpAddress": "string",
                "Phase1DhGroupNumbers": [ number ],
                "Phase1EncryptionAlgorithms": [ "string" ],
                "Phase1IntegrityAlgorithms": [ "string" ],
                "Phase1LifetimeSeconds": number,
                "Phase2DhGroupNumbers": [ number ],
                "Phase2EncryptionAlgorithms": [ "string" ],
                "Phase2IntegrityAlgorithms": [ "string" ],
                "Phase2LifetimeSeconds": number,
                "PreSharedKey": "string",
                "RekeyFuzzPercentage": number,
                "RekeyMarginTimeSeconds": number,
                "ReplayWindowSize": number,
                "TunnelInsideCidr": "string"
            }
        ]
    }
}
]

```

```
    },
    "Routes": [
      {
        "DestinationCidrBlock": "string",
        "State": "string"
      }
    ],
    "State": "string",
    "TransitGatewayId": "string",
    "Type": "string",
    "VgwTelemetry": [
      {
        "AcceptedRouteCount": number,
        "CertificateArn": "string",
        "LastStatusChange": "string",
        "OutsideIpAddress": "string",
        "Status": "string",
        "StatusMessage": "string"
      }
    ],
    "VpnConnectionId": "string",
    "VpnGatewayId": "string"
  },
  "AwsEcrContainerImage": {
    "Architecture": "string",
    "ImageDigest": "string",
    "ImagePublishedAt": "string",
    "ImageTags": [ "string" ],
    "RegistryId": "string",
    "RepositoryName": "string"
  },
  "AwsEcrRepository": {
    "Arn": "string",
    "ImageScanningConfiguration": {
      "ScanOnPush": boolean
    },
    "ImageTagMutability": "string",
    "LifecyclePolicy": {
      "LifecyclePolicyText": "string",
      "RegistryId": "string"
    },
    "RepositoryName": "string",
    "RepositoryPolicyText": "string"
  },
}
```

```
"AwsEcsCluster": {
  "ActiveServicesCount": number,
  "CapacityProviders": [ "string" ],
  "ClusterArn": "string",
  "ClusterName": "string",
  "ClusterSettings": [
    {
      "Name": "string",
      "Value": "string"
    }
  ],
  "Configuration": {
    "ExecuteCommandConfiguration": {
      "KmsKeyId": "string",
      "LogConfiguration": {
        "CloudWatchEncryptionEnabled": boolean,
        "CloudWatchLogGroupName": "string",
        "S3BucketName": "string",
        "S3EncryptionEnabled": boolean,
        "S3KeyPrefix": "string"
      },
      "Logging": "string"
    }
  },
  "DefaultCapacityProviderStrategy": [
    {
      "Base": number,
      "CapacityProvider": "string",
      "Weight": number
    }
  ],
  "RegisteredContainerInstancesCount": number,
  "RunningTasksCount": number,
  "Status": "string"
},
"AwsEcsContainer": {
  "Image": "string",
  "MountPoints": [
    {
      "ContainerPath": "string",
      "SourceVolume": "string"
    }
  ],
  "Name": "string",
```

```
    "Privileged": boolean
  },
  "AwsEcsService": {
    "CapacityProviderStrategy": [
      {
        "Base": number,
        "CapacityProvider": "string",
        "Weight": number
      }
    ],
    "Cluster": "string",
    "DeploymentConfiguration": {
      "DeploymentCircuitBreaker": {
        "Enable": boolean,
        "Rollback": boolean
      },
      "MaximumPercent": number,
      "MinimumHealthyPercent": number
    },
    "DeploymentController": {
      "Type": "string"
    },
    "DesiredCount": number,
    "EnableEcsManagedTags": boolean,
    "EnableExecuteCommand": boolean,
    "HealthCheckGracePeriodSeconds": number,
    "LaunchType": "string",
    "LoadBalancers": [
      {
        "ContainerName": "string",
        "ContainerPort": number,
        "LoadBalancerName": "string",
        "TargetGroupArn": "string"
      }
    ],
    "Name": "string",
    "NetworkConfiguration": {
      "AwsVpcConfiguration": {
        "AssignPublicIp": "string",
        "SecurityGroups": [ "string ],
        "Subnets": [ "string ]
      }
    },
    "PlacementConstraints": [
```



```
    {
      "Expression": "string",
      "Type": "string"
    }
  ],
  "PlacementStrategies": [
    {
      "Field": "string",
      "Type": "string"
    }
  ],
  "PlatformVersion": "string",
  "PropagateTags": "string",
  "Role": "string",
  "SchedulingStrategy": "string",
  "ServiceArn": "string",
  "ServiceName": "string",
  "ServiceRegistries": [
    {
      "ContainerName": "string",
      "ContainerPort": number,
      "Port": number,
      "RegistryArn": "string"
    }
  ],
  "TaskDefinition": "string"
},
"AwsEcsTask": {
  "ClusterArn": "string",
  "Containers": [
    {
      "Image": "string",
      "MountPoints": [
        {
          "ContainerPath": "string",
          "SourceVolume": "string"
        }
      ],
      "Name": "string",
      "Privileged": boolean
    }
  ],
  "CreatedAt": "string",
  "Group": "string",
```

```
"StartedAt": "string",
"StartedBy": "string",
"TaskDefinitionArn": "string",
"Version": "string",
"Volumes": [
  {
    "Host": {
      "SourcePath": "string"
    },
    "Name": "string"
  }
],
"AwsEcsTaskDefinition": {
  "ContainerDefinitions": [
    {
      "Command": [ "string" ],
      "Cpu": number,
      "DependsOn": [
        {
          "Condition": "string",
          "ContainerName": "string"
        }
      ],
      "DisableNetworking": boolean,
      "DnsSearchDomains": [ "string" ],
      "DnsServers": [ "string" ],
      "DockerLabels": {
        "string" : "string"
      },
      "DockerSecurityOptions": [ "string" ],
      "EntryPoint": [ "string" ],
      "Environment": [
        {
          "Name": "string",
          "Value": "string"
        }
      ],
      "EnvironmentFiles": [
        {
          "Type": "string",
          "Value": "string"
        }
      ]
    }
  ]
}
```

```
"Essential": boolean,
"ExtraHosts": [
  {
    "Hostname": "string",
    "IpAddress": "string"
  }
],
"FirelensConfiguration": {
  "Options": {
    "string": "string"
  },
  "Type": "string"
},
"HealthCheck": {
  "Command": [ "string " ],
  "Interval": number,
  "Retries": number,
  "StartPeriod": number,
  "Timeout": number
},
"Hostname": "string",
"Image": "string",
"Interactive": boolean,
"Links": [ "string " ],
"LinuxParameters": {
  "Capabilities": {
    "Add": [ "string " ],
    "Drop": [ "string " ]
  },
  "Devices": [
    {
      "ContainerPath": "string",
      "HostPath": "string",
      "Permissions": [ "string " ]
    }
  ],
  "InitProcessEnabled": boolean,
  "MaxSwap": number,
  "SharedMemorySize": number,
  "Swappiness": number,
  "Tmpfs": [
    {
      "ContainerPath": "string",
      "MountOptions": [ "string " ],
```

```
        "Size": number
      }
    ]
  },
  "LogConfiguration": {
    "LogDriver": "string",
    "Options": {
      "string" : "string"
    },
    "SecretOptions": [
      {
        "Name": "string",
        "ValueFrom": "string"
      }
    ]
  },
  "Memory": number,
  "MemoryReservation": number,
  "MountPoints": [
    {
      "ContainerPath": "string",
      "ReadOnly": boolean,
      "SourceVolume": "string"
    }
  ],
  "Name": "string",
  "PortMappings": [
    {
      "ContainerPort": number,
      "HostPort": number,
      "Protocol": "string"
    }
  ],
  "Privileged": boolean,
  "PseudoTerminal": boolean,
  "ReadOnlyRootFilesystem": boolean,
  "RepositoryCredentials": {
    "CredentialsParameter": "string"
  },
  "ResourceRequirements": [
    {
      "Type": "string",
      "Value": "string"
    }
  ]
}
```

```
    ],
    "Secrets": [
      {
        "Name": "string",
        "ValueFrom": "string"
      }
    ],
    "StartTimeout": number,
    "StopTimeout": number,
    "SystemControls": [
      {
        "Namespace": "string",
        "Value": "string"
      }
    ],
    "ULimits": [
      {
        "HardLimit": number,
        "Name": "string",
        "SoftLimit": number
      }
    ],
    "User": "string",
    "VolumesFrom": [
      {
        "ReadOnly": boolean,
        "SourceContainer": "string"
      }
    ],
    "WorkingDirectory": "string"
  }
],
"Cpu": "string",
"ExecutionRoleArn": "string",
"Family": "string",
"InferenceAccelerators": [
  {
    "DeviceName": "string",
    "DeviceType": "string"
  }
],
"IpcMode": "string",
"Memory": "string",
"NetworkMode": "string",
```

```

"PidMode": "string",
"PlacementConstraints": [
  {
    "Expression": "string",
    "Type": "string"
  }
],
"ProxyConfiguration": {
  "ContainerName": "string",
  "ProxyConfigurationProperties": [
    {
      "Name": "string",
      "Value": "string"
    }
  ],
  "Type": "string"
},
"RequiresCompatibilities": [ "string" ],
"Status": "string",
"TaskRoleArn": "string",
"Volumes": [
  {
    "DockerVolumeConfiguration": {
      "Autoprovision": boolean,
      "Driver": "string",
      "DriverOpts": {
        "string": "string"
      },
      "Labels": {
        "string": "string"
      },
      "Scope": "string"
    },
    "EfsVolumeConfiguration": {
      "AuthorizationConfig": {
        "AccessPointId": "string",
        "Iam": "string"
      },
      "FilesystemId": "string",
      "RootDirectory": "string",
      "TransitEncryption": "string",
      "TransitEncryptionPort": number
    },
    "Host": {

```

```
        "SourcePath": "string"
      },
      "Name": "string"
    }
  ]
},
"AwsEfsAccessPoint": {
  "AccessPointId": "string",
  "Arn": "string",
  "ClientToken": "string",
  "FileSystemId": "string",
  "PosixUser": {
    "Gid": "string",
    "SecondaryGids": [ "string" ],
    "Uid": "string"
  },
  "RootDirectory": {
    "CreationInfo": {
      "OwnerGid": "string",
      "OwnerUid": "string",
      "Permissions": "string"
    },
    "Path": "string"
  }
},
"AwsEksCluster": {
  "Arn": "string",
  "CertificateAuthorityData": "string",
  "ClusterStatus": "string",
  "Endpoint": "string",
  "Logging": {
    "ClusterLogging": [
      {
        "Enabled": boolean,
        "Types": [ "string" ]
      }
    ]
  },
  "Name": "string",
  "ResourcesVpcConfig": {
    "EndpointPublicAccess": boolean,
    "SecurityGroupIds": [ "string" ],
    "SubnetIds": [ "string" ]
  }
},
```

```
    "RoleArn": "string",
    "Version": "string"
  },
  "AwsElasticBeanstalkEnvironment": {
    "ApplicationName": "string",
    "Cname": "string",
    "DateCreated": "string",
    "DateUpdated": "string",
    "Description": "string",
    "EndpointUrl": "string",
    "EnvironmentArn": "string",
    "EnvironmentId": "string",
    "EnvironmentLinks": [
      {
        "EnvironmentName": "string",
        "LinkName": "string"
      }
    ],
    "EnvironmentName": "string",
    "OptionSettings": [
      {
        "Namespace": "string",
        "OptionName": "string",
        "ResourceName": "string",
        "Value": "string"
      }
    ],
    "PlatformArn": "string",
    "SolutionStackName": "string",
    "Status": "string",
    "Tier": {
      "Name": "string",
      "Type": "string",
      "Version": "string"
    },
    "VersionLabel": "string"
  },
  "AwsElasticsearchDomain": {
    "AccessPolicies": "string",
    "DomainEndpointOptions": {
      "EnforceHTTPS": boolean,
      "TLSSecurityPolicy": "string"
    },
    "DomainId": "string",
```



```
"DomainName": "string",
"ElasticsearchClusterConfig": {
  "DedicatedMasterCount": number,
  "DedicatedMasterEnabled": boolean,
  "DedicatedMasterType": "string",
  "InstanceCount": number,
  "InstanceType": "string",
  "ZoneAwarenessConfig": {
    "AvailabilityZoneCount": number
  },
  "ZoneAwarenessEnabled": boolean
},
"ElasticsearchVersion": "string",
"EncryptionAtRestOptions": {
  "Enabled": boolean,
  "KmsKeyId": "string"
},
"Endpoint": "string",
"Endpoints": {
  "string" : "string"
},
"LogPublishingOptions": {
  "AuditLogs": {
    "CloudWatchLogsLogGroupArn": "string",
    "Enabled": boolean
  },
  "IndexSlowLogs": {
    "CloudWatchLogsLogGroupArn": "string",
    "Enabled": boolean
  },
  "SearchSlowLogs": {
    "CloudWatchLogsLogGroupArn": "string",
    "Enabled": boolean
  }
},
"NodeToNodeEncryptionOptions": {
  "Enabled": boolean
},
"ServiceSoftwareOptions": {
  "AutomatedUpdateDate": "string",
  "Cancellable": boolean,
  "CurrentVersion": "string",
  "Description": "string",
  "NewVersion": "string",
```

```
    "UpdateAvailable": boolean,
    "UpdateStatus": "string"
  },
  "VPCOptions": {
    "AvailabilityZones": [ "string " ],
    "SecurityGroupIds": [ "string " ],
    "SubnetIds": [ "string " ],
    "VPCId": "string"
  }
},
"AwsElbLoadBalancer": {
  "AvailabilityZones": [ "string " ],
  "BackendServerDescriptions": [
    {
      "InstancePort": number,
      "PolicyNames": [ "string " ]
    }
  ],
  "CanonicalHostedZoneName": "string",
  "CanonicalHostedZoneNameID": "string",
  "CreatedTime": "string",
  "DnsName": "string",
  "HealthCheck": {
    "HealthyThreshold": number,
    "Interval": number,
    "Target": "string",
    "Timeout": number,
    "UnhealthyThreshold": number
  },
  "Instances": [
    {
      "InstanceId": "string"
    }
  ],
  "ListenerDescriptions": [
    {
      "Listener": {
        "InstancePort": number,
        "InstanceProtocol": "string",
        "LoadBalancerPort": number,
        "Protocol": "string",
        "SslCertificateId": "string"
      },
      "PolicyNames": [ "string " ]
    }
  ]
}
```

```
    }
  ],
  "LoadBalancerAttributes": {
    "AccessLog": {
      "EmitInterval": number,
      "Enabled": boolean,
      "S3BucketName": "string",
      "S3BucketPrefix": "string"
    },
    "AdditionalAttributes": [
      {
        "Key": "string",
        "Value": "string"
      }
    ],
    "ConnectionDraining": {
      "Enabled": boolean,
      "Timeout": number
    },
    "ConnectionSettings": {
      "IdleTimeout": number
    },
    "CrossZoneLoadBalancing": {
      "Enabled": boolean
    }
  },
  "LoadBalancerName": "string",
  "Policies": {
    "AppCookieStickinessPolicies": [
      {
        "CookieName": "string",
        "PolicyName": "string"
      }
    ],
    "LbCookieStickinessPolicies": [
      {
        "CookieExpirationPeriod": number,
        "PolicyName": "string"
      }
    ],
    "OtherPolicies": [ "string" ]
  },
  "Scheme": "string",
  "SecurityGroups": [ "string" ],
```

```
    "SourceSecurityGroup": {
      "GroupName": "string",
      "OwnerAlias": "string"
    },
    "Subnets": [ "string" ],
    "VpcId": "string"
  },
  "AwsElbv2LoadBalancer": {
    "AvailabilityZones": [
      {
        "SubnetId": "string",
        "ZoneName": "string"
      }
    ],
    "CanonicalHostedZoneId": "string",
    "CreatedTime": "string",
    "DNSName": "string",
    "IpAddressType": "string",
    "LoadBalancerAttributes": [
      {
        "Key": "string",
        "Value": "string"
      }
    ],
    "Scheme": "string",
    "SecurityGroups": [ "string" ],
    "State": {
      "Code": "string",
      "Reason": "string"
    },
    "Type": "string",
    "VpcId": "string"
  },
  "AwsEventSchemasRegistry": {
    "Description": "string",
    "RegistryArn": "string",
    "RegistryName": "string"
  },
  "AwsEventsEndpoint": {
    "Arn": "string",
    "Description": "string",
    "EndpointId": "string",
    "EndpointUrl": "string",
    "EventBuses": [
```

```
    {
      "EventBusArn": "string"
    }
  ],
  "Name": "string",
  "ReplicationConfig": {
    "State": "string"
  },
  "RoleArn": "string",
  "RoutingConfig": {
    "FailoverConfig": {
      "Primary": {
        "HealthCheck": "string"
      },
      "Secondary": {
        "Route": "string"
      }
    }
  },
  "State": "string",
  "StateReason": "string"
},
"AwsEventsEventbus": {
  "Arn": "string",
  "Name": "string",
  "Policy": "string"
},
"AwsGuardDutyDetector": {
  "DataSources": {
    "CloudTrail": {
      "Status": "string"
    },
    "DnsLogs": {
      "Status": "string"
    },
    "FlowLogs": {
      "Status": "string"
    },
    "Kubernetes": {
      "AuditLogs": {
        "Status": "string"
      }
    }
  },
  "MalwareProtection": {
```

```
    "ScanEc2InstanceWithFindings": {
      "EbsVolumes": {
        "Reason": "string",
        "Status": "string"
      }
    },
    "ServiceRole": "string"
  },
  "S3Logs": {
    "Status": "string"
  }
},
"Features": [
  {
    "Name": "string",
    "Status": "string"
  }
],
"FindingPublishingFrequency": "string",
"ServiceRole": "string",
"Status": "string"
},
"AwsIamAccessKey": {
  "AccessKeyId": "string",
  "AccountId": "string",
  "CreatedAt": "string",
  "PrincipalId": "string",
  "PrincipalName": "string",
  "PrincipalType": "string",
  "SessionContext": {
    "Attributes": {
      "CreationDate": "string",
      "MfaAuthenticated": boolean
    }
  },
  "SessionIssuer": {
    "AccountId": "string",
    "Arn": "string",
    "PrincipalId": "string",
    "Type": "string",
    "UserName": "string"
  }
},
"Status": "string",
"UserName": "string"
```

```
    },
    "AwsIamGroup": {
      "AttachedManagedPolicies": [
        {
          "PolicyArn": "string",
          "PolicyName": "string"
        }
      ],
      "CreateDate": "string",
      "GroupId": "string",
      "GroupName": "string",
      "GroupPolicyList": [
        {
          "PolicyName": "string"
        }
      ],
      "Path": "string"
    },
    "AwsIamPolicy": {
      "AttachmentCount": number,
      "CreateDate": "string",
      "DefaultVersionId": "string",
      "Description": "string",
      "IsAttachable": boolean,
      "Path": "string",
      "PermissionsBoundaryUsageCount": number,
      "PolicyId": "string",
      "PolicyName": "string",
      "PolicyVersionList": [
        {
          "CreateDate": "string",
          "IsDefaultVersion": boolean,
          "VersionId": "string"
        }
      ],
      "UpdateDate": "string"
    },
    "AwsIamRole": {
      "AssumeRolePolicyDocument": "string",
      "AttachedManagedPolicies": [
        {
          "PolicyArn": "string",
          "PolicyName": "string"
        }
      ]
    }
  }
}
```

```
],
  "CreateDate": "string",
  "InstanceProfileList": [
    {
      "Arn": "string",
      "CreateDate": "string",
      "InstanceProfileId": "string",
      "InstanceProfileName": "string",
      "Path": "string",
      "Roles": [
        {
          "Arn": "string",
          "AssumeRolePolicyDocument": "string",
          "CreateDate": "string",
          "Path": "string",
          "RoleId": "string",
          "RoleName": "string"
        }
      ]
    }
  ],
  "MaxSessionDuration": number,
  "Path": "string",
  "PermissionsBoundary": {
    "PermissionsBoundaryArn": "string",
    "PermissionsBoundaryType": "string"
  },
  "RoleId": "string",
  "RoleName": "string",
  "RolePolicyList": [
    {
      "PolicyName": "string"
    }
  ]
},
"AwsIamUser": {
  "AttachedManagedPolicies": [
    {
      "PolicyArn": "string",
      "PolicyName": "string"
    }
  ],
  "CreateDate": "string",
  "GroupList": [ "string" ],
```



```
"Path": "string",
"PermissionsBoundary": {
  "PermissionsBoundaryArn": "string",
  "PermissionsBoundaryType": "string"
},
"UserId": "string",
"UserName": "string",
"UserPolicyList": [
  {
    "PolicyName": "string"
  }
]
},
"AwsKinesisStream": {
  "Arn": "string",
  "Name": "string",
  "RetentionPeriodHours": number,
  "ShardCount": number,
  "StreamEncryption": {
    "EncryptionType": "string",
    "KeyId": "string"
  }
},
"AwsKmsKey": {
  "AWSAccountId": "string",
  "CreationDate": number,
  "Description": "string",
  "KeyId": "string",
  "KeyManager": "string",
  "KeyRotationStatus": boolean,
  "KeyState": "string",
  "Origin": "string"
},
"AwsLambdaFunction": {
  "Architectures": [ "string" ],
  "Code": {
    "S3Bucket": "string",
    "S3Key": "string",
    "S3ObjectVersion": "string",
    "ZipFile": "string"
  },
  "CodeSha256": "string",
  "DeadLetterConfig": {
    "TargetArn": "string"
```

```
    },
    "Environment": {
      "Error": {
        "ErrorCode": "string",
        "Message": "string"
      },
      "Variables": {
        "string": "string"
      }
    },
    "FunctionName": "string",
    "Handler": "string",
    "KmsKeyArn": "string",
    "LastModified": "string",
    "Layers": [
      {
        "Arn": "string",
        "CodeSize": number
      }
    ],
    "MasterArn": "string",
    "MemorySize": number,
    "PackageType": "string",
    "RevisionId": "string",
    "Role": "string",
    "Runtime": "string",
    "Timeout": number,
    "TracingConfig": {
      "Mode": "string"
    },
    "Version": "string",
    "VpcConfig": {
      "SecurityGroupIds": [ "string" ],
      "SubnetIds": [ "string" ],
      "VpcId": "string"
    }
  },
  "AwsLambdaLayerVersion": {
    "CompatibleRuntimes": [ "string" ],
    "CreateDate": "string",
    "Version": number
  },
  "AwsMskCluster": {
    "ClusterInfo": {
```

```

    "ClientAuthentication": {
      "Sasl": {
        "Iam": {
          "Enabled": boolean
        },
        "Scram": {
          "Enabled": boolean
        }
      },
      "Tls": {
        "CertificateAuthorityArnList": [ "string ],
        "Enabled": boolean
      },
      "Unauthenticated": {
        "Enabled": boolean
      }
    },
    "ClusterName": "string",
    "CurrentVersion": "string",
    "EncryptionInfo": {
      "EncryptionAtRest": {
        "DataVolumeKMSKeyId": "string"
      },
      "EncryptionInTransit": {
        "ClientBroker": "string",
        "InCluster": boolean
      }
    },
    "EnhancedMonitoring": "string",
    "NumberOfBrokerNodes": number
  }
},
"AwsNetworkFirewallFirewall": {
  "DeleteProtection": boolean,
  "Description": "string",
  "FirewallArn": "string",
  "FirewallId": "string",
  "FirewallName": "string",
  "FirewallPolicyArn": "string",
  "FirewallPolicyChangeProtection": boolean,
  "SubnetChangeProtection": boolean,
  "SubnetMappings": [
    {
      "SubnetId": "string"
    }
  ]
}

```

```

    }
  ],
  "VpcId": "string"
},
"AwsNetworkFirewallFirewallPolicy": {
  "Description": "string",
  "FirewallPolicy": {
    "StatefulRuleGroupReferences": [
      {
        "ResourceArn": "string"
      }
    ],
    "StatelessCustomActions": [
      {
        "ActionDefinition": {
          "PublishMetricAction": {
            "Dimensions": [
              {
                "Value": "string"
              }
            ]
          }
        },
        "ActionName": "string"
      }
    ],
    "StatelessDefaultActions": [ "string" ],
    "StatelessFragmentDefaultActions": [ "string" ],
    "StatelessRuleGroupReferences": [
      {
        "Priority": number,
        "ResourceArn": "string"
      }
    ]
  },
  "FirewallPolicyArn": "string",
  "FirewallPolicyId": "string",
  "FirewallPolicyName": "string"
},
"AwsNetworkFirewallRuleGroup": {
  "Capacity": number,
  "Description": "string",
  "RuleGroup": {
    "RulesSource": {

```

```

"RulesSourceList": {
  "GeneratedRulesType": "string",
  "Targets": [ "string" ],
  "TargetTypes": [ "string" ]
},
"RulesString": "string",
"StatefulRules": [
  {
    "Action": "string",
    "Header": {
      "Destination": "string",
      "DestinationPort": "string",
      "Direction": "string",
      "Protocol": "string",
      "Source": "string",
      "SourcePort": "string"
    },
    "RuleOptions": [
      {
        "Keyword": "string",
        "Settings": [ "string" ]
      }
    ]
  }
],
"StatelessRulesAndCustomActions": {
  "CustomActions": [
    {
      "ActionDefinition": {
        "PublishMetricAction": {
          "Dimensions": [
            {
              "Value": "string"
            }
          ]
        }
      },
      "ActionName": "string"
    }
  ],
  "StatelessRules": [
    {
      "Priority": number,
      "RuleDefinition": {

```

```

    "Actions": [ "string" ],
    "MatchAttributes": {
      "DestinationPorts": [
        {
          "FromPort": number,
          "ToPort": number
        }
      ],
      "Destinations": [
        {
          "AddressDefinition": "string"
        }
      ],
      "Protocols": [ number ],
      "SourcePorts": [
        {
          "FromPort": number,
          "ToPort": number
        }
      ],
      "Sources": [
        {
          "AddressDefinition": "string"
        }
      ],
      "TcpFlags": [
        {
          "Flags": [ "string" ],
          "Masks": [ "string" ]
        }
      ]
    }
  ],
}
},
"RuleVariables": {
  "IpSets": {
    "Definition": [ "string" ]
  },
  "PortSets": {
    "Definition": [ "string" ]
  }
}

```

```

    }
  },
  "RuleGroupArn": "string",
  "RuleGroupId": "string",
  "RuleGroupName": "string",
  "Type": "string"
},
"AwsOpenSearchServiceDomain": {
  "AccessPolicies": "string",
  "AdvancedSecurityOptions": {
    "Enabled": boolean,
    "InternalUserDatabaseEnabled": boolean,
    "MasterUserOptions": {
      "MasterUserArn": "string",
      "MasterUserName": "string",
      "MasterUserPassword": "string"
    }
  }
},
"Arn": "string",
"ClusterConfig": {
  "DedicatedMasterCount": number,
  "DedicatedMasterEnabled": boolean,
  "DedicatedMasterType": "string",
  "InstanceCount": number,
  "InstanceType": "string",
  "WarmCount": number,
  "WarmEnabled": boolean,
  "WarmType": "string",
  "ZoneAwarenessConfig": {
    "AvailabilityZoneCount": number
  },
  "ZoneAwarenessEnabled": boolean
},
"DomainEndpoint": "string",
"DomainEndpointOptions": {
  "CustomEndpoint": "string",
  "CustomEndpointCertificateArn": "string",
  "CustomEndpointEnabled": boolean,
  "EnforceHTTPS": boolean,
  "TLSSecurityPolicy": "string"
},
"DomainEndpoints": {
  "string" : "string"
},

```

```
"DomainName": "string",
"EncryptionAtRestOptions": {
  "Enabled": boolean,
  "KmsKeyId": "string"
},
"EngineVersion": "string",
"Id": "string",
"LogPublishingOptions": {
  "AuditLogs": {
    "CloudWatchLogsLogGroupArn": "string",
    "Enabled": boolean
  },
  "IndexSlowLogs": {
    "CloudWatchLogsLogGroupArn": "string",
    "Enabled": boolean
  },
  "SearchSlowLogs": {
    "CloudWatchLogsLogGroupArn": "string",
    "Enabled": boolean
  }
},
"NodeToNodeEncryptionOptions": {
  "Enabled": boolean
},
"ServiceSoftwareOptions": {
  "AutomatedUpdateDate": "string",
  "Cancellable": boolean,
  "CurrentVersion": "string",
  "Description": "string",
  "NewVersion": "string",
  "OptionalDeployment": boolean,
  "UpdateAvailable": boolean,
  "UpdateStatus": "string"
},
"VpcOptions": {
  "SecurityGroupIds": [ "string" ],
  "SubnetIds": [ "string" ]
}
},
"AwsRdsDbCluster": {
  "ActivityStreamStatus": "string",
  "AllocatedStorage": number,
  "AssociatedRoles": [
    {
```



```
        "RoleArn": "string",
        "Status": "string"
    }
],
"AutoMinorVersionUpgrade": boolean,
"AvailabilityZones": [ "string" ],
"BackupRetentionPeriod": number,
"ClusterCreateTime": "string",
"CopyTagsToSnapshot": boolean,
"CrossAccountClone": boolean,
"CustomEndpoints": [ "string" ],
"DatabaseName": "string",
"DbClusterIdentifier": "string",
"DbClusterMembers": [
    {
        "DbClusterParameterGroupStatus": "string",
        "DbInstanceIdentifier": "string",
        "IsClusterWriter": boolean,
        "PromotionTier": number
    }
],
"DbClusterOptionGroupMemberships": [
    {
        "DbClusterOptionGroupName": "string",
        "Status": "string"
    }
],
"DbClusterParameterGroup": "string",
"DbClusterResourceId": "string",
"DbSubnetGroup": "string",
"DeletionProtection": boolean,
"DomainMemberships": [
    {
        "Domain": "string",
        "Fqdn": "string",
        "IamRoleName": "string",
        "Status": "string"
    }
],
"EnabledCloudWatchLogsExports": [ "string" ],
"Endpoint": "string",
"Engine": "string",
"EngineMode": "string",
"EngineVersion": "string",
```

```
"HostedZoneId": "string",
"HttpEndpointEnabled": boolean,
"IamDatabaseAuthenticationEnabled": boolean,
"KmsKeyId": "string",
"MasterUsername": "string",
"MultiAz": boolean,
"Port": number,
"PreferredBackupWindow": "string",
"PreferredMaintenanceWindow": "string",
"ReaderEndpoint": "string",
"ReadReplicaIdentifiers": [ "string" ],
"Status": "string",
"StorageEncrypted": boolean,
"VpcSecurityGroups": [
  {
    "Status": "string",
    "VpcSecurityGroupId": "string"
  }
],
},
"AwsRdsDbClusterSnapshot": {
  "AllocatedStorage": number,
  "AvailabilityZones": [ "string" ],
  "ClusterCreateTime": "string",
  "DbClusterIdentifier": "string",
  "DbClusterSnapshotAttributes": [
    {
      "AttributeName": "string",
      "AttributeValues": [ "string" ]
    }
  ],
  "DbClusterSnapshotIdentifier": "string",
  "Engine": "string",
  "EngineVersion": "string",
  "IamDatabaseAuthenticationEnabled": boolean,
  "KmsKeyId": "string",
  "LicenseModel": "string",
  "MasterUsername": "string",
  "PercentProgress": number,
  "Port": number,
  "SnapshotCreateTime": "string",
  "SnapshotType": "string",
  "Status": "string",
  "StorageEncrypted": boolean,
```

```
    "VpcId": "string"
  },
  "AwsRdsDbInstance": {
    "AllocatedStorage": number,
    "AssociatedRoles": [
      {
        "FeatureName": "string",
        "RoleArn": "string",
        "Status": "string"
      }
    ],
    "AutoMinorVersionUpgrade": boolean,
    "AvailabilityZone": "string",
    "BackupRetentionPeriod": number,
    "CACertificateIdentifier": "string",
    "CharacterSetName": "string",
    "CopyTagsToSnapshot": boolean,
    "DBClusterIdentifier": "string",
    "DBInstanceClass": "string",
    "DBInstanceIdentifier": "string",
    "DbInstancePort": number,
    "DbInstanceStatus": "string",
    "DbiResourceId": "string",
    "DBName": "string",
    "DbParameterGroups": [
      {
        "DbParameterGroupName": "string",
        "ParameterApplyStatus": "string"
      }
    ],
    "DbSecurityGroups": [ "string" ],
    "DbSubnetGroup": {
      "DbSubnetGroupArn": "string",
      "DbSubnetGroupDescription": "string",
      "DbSubnetGroupName": "string",
      "SubnetGroupStatus": "string",
      "Subnets": [
        {
          "SubnetAvailabilityZone": {
            "Name": "string"
          },
          "SubnetIdentifier": "string",
          "SubnetStatus": "string"
        }
      ]
    }
  }
}
```

```
    ],
    "VpcId": "string"
  },
  "DeletionProtection": boolean,
  "DomainMemberships": [
    {
      "Domain": "string",
      "Fqdn": "string",
      "IamRoleName": "string",
      "Status": "string"
    }
  ],
  "EnabledCloudWatchLogsExports": [ "string" ],
  "Endpoint": {
    "Address": "string",
    "HostedZoneId": "string",
    "Port": number
  },
  "Engine": "string",
  "EngineVersion": "string",
  "EnhancedMonitoringResourceArn": "string",
  "IAMDatabaseAuthenticationEnabled": boolean,
  "InstanceCreateTime": "string",
  "Iops": number,
  "KmsKeyId": "string",
  "LatestRestorableTime": "string",
  "LicenseModel": "string",
  "ListenerEndpoint": {
    "Address": "string",
    "HostedZoneId": "string",
    "Port": number
  },
  "MasterUsername": "string",
  "MaxAllocatedStorage": number,
  "MonitoringInterval": number,
  "MonitoringRoleArn": "string",
  "MultiAz": boolean,
  "OptionGroupMemberships": [
    {
      "OptionGroupName": "string",
      "Status": "string"
    }
  ],
  "PendingModifiedValues": {
```

```
"AllocatedStorage": number,
"BackupRetentionPeriod": number,
"CaCertificateIdentifier": "string",
"DbInstanceClass": "string",
"DbInstanceIdentifier": "string",
"DbSubnetGroupName": "string",
"EngineVersion": "string",
"Iops": number,
"LicenseModel": "string",
"MasterUserPassword": "string",
"MultiAZ": boolean,
"PendingCloudWatchLogsExports": {
  "LogTypesToDisable": [ "string" ],
  "LogTypesToEnable": [ "string" ]
},
"Port": number,
"ProcessorFeatures": [
  {
    "Name": "string",
    "Value": "string"
  }
],
"StorageType": "string"
},
"PerformanceInsightsEnabled": boolean,
"PerformanceInsightsKmsKeyId": "string",
"PerformanceInsightsRetentionPeriod": number,
"PreferredBackupWindow": "string",
"PreferredMaintenanceWindow": "string",
"ProcessorFeatures": [
  {
    "Name": "string",
    "Value": "string"
  }
],
"PromotionTier": number,
"PubliclyAccessible": boolean,
"ReadReplicaDBClusterIdentifiers": [ "string" ],
"ReadReplicaDBInstanceIdentifiers": [ "string" ],
"ReadReplicaSourceDBInstanceIdentifier": "string",
"SecondaryAvailabilityZone": "string",
"StatusInfos": [
  {
    "Message": "string",
```

```

        "Normal": boolean,
        "Status": "string",
        "StatusType": "string"
    }
],
"StorageEncrypted": boolean,
"StorageType": "string",
"TdeCredentialArn": "string",
"Timezone": "string",
"VpcSecurityGroups": [
    {
        "Status": "string",
        "VpcSecurityGroupId": "string"
    }
]
},
"AwsRdsDbSecurityGroup": {
    "DbSecurityGroupArn": "string",
    "DbSecurityGroupDescription": "string",
    "DbSecurityGroupName": "string",
    "Ec2SecurityGroups": [
        {
            "Ec2SecurityGroupId": "string",
            "Ec2SecurityGroupName": "string",
            "Ec2SecurityGroupOwnerId": "string",
            "Status": "string"
        }
    ],
    "IpRanges": [
        {
            "CidrIp": "string",
            "Status": "string"
        }
    ],
    "OwnerId": "string",
    "VpcId": "string"
},
"AwsRdsDbSnapshot": {
    "AllocatedStorage": number,
    "AvailabilityZone": "string",
    "DbInstanceIdentifier": "string",
    "DbiResourceId": "string",
    "DbSnapshotIdentifier": "string",
    "Encrypted": boolean,

```

```
"Engine": "string",
"EngineVersion": "string",
"IamDatabaseAuthenticationEnabled": boolean,
"InstanceCreateTime": "string",
"Iops": number,
"KmsKeyId": "string",
"LicenseModel": "string",
"MasterUsername": "string",
"OptionGroupName": "string",
"PercentProgress": number,
"Port": number,
"ProcessorFeatures": [
  {
    "Name": "string",
    "Value": "string"
  }
],
"SnapshotCreateTime": "string",
"SnapshotType": "string",
"SourceDbSnapshotIdentifier": "string",
"SourceRegion": "string",
"Status": "string",
"StorageType": "string",
"TdeCredentialArn": "string",
"Timezone": "string",
"VpcId": "string"
},
"AwsRdsEventSubscription": {
  "CustomerAwsId": "string",
  "CustSubscriptionId": "string",
  "Enabled": boolean,
  "EventCategoriesList": [ "string" ],
  "EventSubscriptionArn": "string",
  "SnsTopicArn": "string",
  "SourceIdsList": [ "string" ],
  "SourceType": "string",
  "Status": "string",
  "SubscriptionCreationTime": "string"
},
"AwsRedshiftCluster": {
  "AllowVersionUpgrade": boolean,
  "AutomatedSnapshotRetentionPeriod": number,
  "AvailabilityZone": "string",
  "ClusterAvailabilityStatus": "string",
```

```
"ClusterCreateTime": "string",
"ClusterIdentifier": "string",
"ClusterNodes": [
  {
    "NodeRole": "string",
    "PrivateIpAddress": "string",
    "PublicIpAddress": "string"
  }
],
"ClusterParameterGroups": [
  {
    "ClusterParameterStatusList": [
      {
        "ParameterApplyErrorDescription": "string",
        "ParameterApplyStatus": "string",
        "ParameterName": "string"
      }
    ],
    "ParameterApplyStatus": "string",
    "ParameterGroupName": "string"
  }
],
"ClusterPublicKey": "string",
"ClusterRevisionNumber": "string",
"ClusterSecurityGroups": [
  {
    "ClusterSecurityGroupName": "string",
    "Status": "string"
  }
],
"ClusterSnapshotCopyStatus": {
  "DestinationRegion": "string",
  "ManualSnapshotRetentionPeriod": number,
  "RetentionPeriod": number,
  "SnapshotCopyGrantName": "string"
},
"ClusterStatus": "string",
"ClusterSubnetGroupName": "string",
"ClusterVersion": "string",
"DBName": "string",
"DeferredMaintenanceWindows": [
  {
    "DeferMaintenanceEndTime": "string",
    "DeferMaintenanceIdentifier": "string",
```



```
    "DeferMaintenanceStartTime": "string"
  }
],
"ElasticIpStatus": {
  "ElasticIp": "string",
  "Status": "string"
},
"ElasticResizeNumberOfNodeOptions": "string",
"Encrypted": boolean,
"Endpoint": {
  "Address": "string",
  "Port": number
},
"EnhancedVpcRouting": boolean,
"ExpectedNextSnapshotScheduleTime": "string",
"ExpectedNextSnapshotScheduleTimeStatus": "string",
"HsmStatus": {
  "HsmClientCertificateIdentifier": "string",
  "HsmConfigurationIdentifier": "string",
  "Status": "string"
},
"IamRoles": [
  {
    "ApplyStatus": "string",
    "IamRoleArn": "string"
  }
],
"KmsKeyId": "string",
"LoggingStatus": {
  "BucketName": "string",
  "LastFailureMessage": "string",
  "LastFailureTime": "string",
  "LastSuccessfulDeliveryTime": "string",
  "LoggingEnabled": boolean,
  "S3KeyPrefix": "string"
},
"MaintenanceTrackName": "string",
"ManualSnapshotRetentionPeriod": number,
"MasterUsername": "string",
"NextMaintenanceWindowStartTime": "string",
"NodeType": "string",
"NumberOfNodes": number,
"PendingActions": [ "string" ],
"PendingModifiedValues": {
```

```
    "AutomatedSnapshotRetentionPeriod": number,
    "ClusterIdentifier": "string",
    "ClusterType": "string",
    "ClusterVersion": "string",
    "EncryptionType": "string",
    "EnhancedVpcRouting": boolean,
    "MaintenanceTrackName": "string",
    "MasterUserPassword": "string",
    "NodeType": "string",
    "NumberOfNodes": number,
    "PubliclyAccessible": boolean
  },
  "PreferredMaintenanceWindow": "string",
  "PubliclyAccessible": boolean,
  "ResizeInfo": {
    "AllowCancelResize": boolean,
    "ResizeType": "string"
  },
  "RestoreStatus": {
    "CurrentRestoreRateInMegaBytesPerSecond": number,
    "ElapsedTimeInSeconds": number,
    "EstimatedTimeToCompletionInSeconds": number,
    "ProgressInMegaBytes": number,
    "SnapshotSizeInMegaBytes": number,
    "Status": "string"
  },
  "SnapshotScheduleIdentifier": "string",
  "SnapshotScheduleState": "string",
  "VpcId": "string",
  "VpcSecurityGroups": [
    {
      "Status": "string",
      "VpcSecurityGroupId": "string"
    }
  ]
},
"AwsRoute53HostedZone": {
  "HostedZone": {
    "Config": {
      "Comment": "string"
    },
  },
  "Id": "string",
  "Name": "string"
},
```

```

    "NameServers": [ "string" ],
    "QueryLoggingConfig": {
      "CloudWatchLogsLogGroupArn": {
        "CloudWatchLogsLogGroupArn": "string",
        "HostedZoneId": "string",
        "Id": "string"
      }
    },
    "Vpcs": [
      {
        "Id": "string",
        "Region": "string"
      }
    ]
  },
  "AwsS3AccessPoint": {
    "AccessPointArn": "string",
    "Alias": "string",
    "Bucket": "string",
    "BucketAccountId": "string",
    "Name": "string",
    "NetworkOrigin": "string",
    "PublicAccessBlockConfiguration": {
      "BlockPublicAcls": boolean,
      "BlockPublicPolicy": boolean,
      "IgnorePublicAcls": boolean,
      "RestrictPublicBuckets": boolean
    },
    "VpcConfiguration": {
      "VpcId": "string"
    }
  },
  "AwsS3AccountPublicAccessBlock": {
    "BlockPublicAcls": boolean,
    "BlockPublicPolicy": boolean,
    "IgnorePublicAcls": boolean,
    "RestrictPublicBuckets": boolean
  },
  "AwsS3Bucket": {
    "AccessControlList": "string",
    "BucketLifecycleConfiguration": {
      "Rules": [
        {
          "AbortIncompleteMultipartUpload": {

```

```

    "DaysAfterInitiation": number
  },
  "ExpirationDate": "string",
  "ExpirationInDays": number,
  "ExpiredObjectDeleteMarker": boolean,
  "Filter": {
    "Predicate": {
      "Operands": [
        {
          "Prefix": "string",
          "Tag": {
            "Key": "string",
            "Value": "string"
          },
          "Type": "string"
        }
      ],
      "Prefix": "string",
      "Tag": {
        "Key": "string",
        "Value": "string"
      },
      "Type": "string"
    }
  },
  "ID": "string",
  "NoncurrentVersionExpirationInDays": number,
  "NoncurrentVersionTransitions": [
    {
      "Days": number,
      "StorageClass": "string"
    }
  ],
  "Prefix": "string",
  "Status": "string",
  "Transitions": [
    {
      "Date": "string",
      "Days": number,
      "StorageClass": "string"
    }
  ]
}
]

```

```
},
  "BucketLoggingConfiguration": {
    "DestinationBucketName": "string",
    "LogFilePrefix": "string"
  },
  "BucketNotificationConfiguration": {
    "Configurations": [
      {
        "Destination": "string",
        "Events": [ "string" ],
        "Filter": {
          "S3KeyFilter": {
            "FilterRules": [
              {
                "Name": "string",
                "Value": "string"
              }
            ]
          }
        },
        "Type": "string"
      }
    ]
  },
  "BucketVersioningConfiguration": {
    "IsMfaDeleteEnabled": boolean,
    "Status": "string"
  },
  "BucketWebsiteConfiguration": {
    "ErrorDocument": "string",
    "IndexDocumentSuffix": "string",
    "RedirectAllRequestsTo": {
      "Hostname": "string",
      "Protocol": "string"
    },
    "RoutingRules": [
      {
        "Condition": {
          "HttpErrorCodeReturnedEquals": "string",
          "KeyPrefixEquals": "string"
        },
        "Redirect": {
          "Hostname": "string",
          "HttpRedirectCode": "string",
```

```

        "Protocol": "string",
        "ReplaceKeyPrefixWith": "string",
        "ReplaceKeyWith": "string"
    }
}
]
},
"CreatedAt": "string",
"Name": "string",
"ObjectLockConfiguration": {
    "ObjectLockEnabled": "string",
    "Rule": {
        "DefaultRetention": {
            "Days": number,
            "Mode": "string",
            "Years": number
        }
    }
},
"OwnerAccountId": "string",
"OwnerId": "string",
"OwnerName": "string",
"PublicAccessBlockConfiguration": {
    "BlockPublicAcls": boolean,
    "BlockPublicPolicy": boolean,
    "IgnorePublicAcls": boolean,
    "RestrictPublicBuckets": boolean
},
"ServerSideEncryptionConfiguration": {
    "Rules": [
        {
            "ApplyServerSideEncryptionByDefault": {
                "KMSEMasterKeyID": "string",
                "SSEAlgorithm": "string"
            }
        }
    ]
}
},
"AwsS3Object": {
    "ContentType": "string",
    "ETag": "string",
    "LastModified": "string",
    "ServerSideEncryption": "string",

```

```
"SSEKMSKeyId": "string",
"VersionId": "string"
},
"AwsSageMakerNotebookInstance": {
  "AcceleratorTypes": [ "string" ],
  "AdditionalCodeRepositories": [ "string" ],
  "DefaultCodeRepository": "string",
  "DirectInternetAccess": "string",
  "FailureReason": "string",
  "InstanceMetadataServiceConfiguration": {
    "MinimumInstanceMetadataServiceVersion": "string"
  },
  "InstanceType": "string",
  "KmsKeyId": "string",
  "NetworkInterfaceId": "string",
  "NotebookInstanceArn": "string",
  "NotebookInstanceLifecycleConfigName": "string",
  "NotebookInstanceName": "string",
  "NotebookInstanceStatus": "string",
  "PlatformIdentifier": "string",
  "RoleArn": "string",
  "RootAccess": "string",
  "SecurityGroups": [ "string" ],
  "SubnetId": "string",
  "Url": "string",
  "VolumeSizeInGB": number
},
"AwsSecretsManagerSecret": {
  "Deleted": boolean,
  "Description": "string",
  "KmsKeyId": "string",
  "Name": "string",
  "RotationEnabled": boolean,
  "RotationLambdaArn": "string",
  "RotationOccurredWithinFrequency": boolean,
  "RotationRules": {
    "AutomaticallyAfterDays": number
  }
},
"AwsSnsTopic": {
  "ApplicationSuccessFeedbackRoleArn": "string",
  "FirehoseFailureFeedbackRoleArn": "string",
  "FirehoseSuccessFeedbackRoleArn": "string",
  "HttpFailureFeedbackRoleArn": "string",
```

```
"HttpSuccessFeedbackRoleArn": "string",
"KmsMasterKeyId": "string",
"Owner": "string",
"SqsFailureFeedbackRoleArn": "string",
"SqsSuccessFeedbackRoleArn": "string",
"Subscription": [
  {
    "Endpoint": "string",
    "Protocol": "string"
  }
],
"TopicName": "string"
},
"AwsSqsQueue": {
  "DeadLetterTargetArn": "string",
  "KmsDataKeyReusePeriodSeconds": number,
  "KmsMasterKeyId": "string",
  "QueueName": "string"
},
"AwsSsmPatchCompliance": {
  "Patch": {
    "ComplianceSummary": {
      "ComplianceType": "string",
      "CompliantCriticalCount": number,
      "CompliantHighCount": number,
      "CompliantInformationalCount": number,
      "CompliantLowCount": number,
      "CompliantMediumCount": number,
      "CompliantUnspecifiedCount": number,
      "ExecutionType": "string",
      "NonCompliantCriticalCount": number,
      "NonCompliantHighCount": number,
      "NonCompliantInformationalCount": number,
      "NonCompliantLowCount": number,
      "NonCompliantMediumCount": number,
      "NonCompliantUnspecifiedCount": number,
      "OverallSeverity": "string",
      "PatchBaselineId": "string",
      "PatchGroup": "string",
      "Status": "string"
    }
  }
},
"AwsStepFunctionStateMachine": {
```



```
"Label": "string",
"LoggingConfiguration": {
  "Destinations": [
    {
      "CloudWatchLogsLogGroup": {
        "LogGroupArn": "string"
      }
    }
  ],
  "IncludeExecutionData": boolean,
  "Level": "string"
},
"Name": "string",
"RoleArn": "string",
"StateMachineArn": "string",
"Status": "string",
"TracingConfiguration": {
  "Enabled": boolean
},
"Type": "string"
},
"AwsWafRateBasedRule": {
  "MatchPredicates": [
    {
      "DataId": "string",
      "Negated": boolean,
      "Type": "string"
    }
  ],
  "MetricName": "string",
  "Name": "string",
  "RateKey": "string",
  "RateLimit": number,
  "RuleId": "string"
},
"AwsWafRegionalRateBasedRule": {
  "MatchPredicates": [
    {
      "DataId": "string",
      "Negated": boolean,
      "Type": "string"
    }
  ],
  "MetricName": "string",
```

```
    "Name": "string",
    "RateKey": "string",
    "RateLimit": number,
    "RuleId": "string"
  },
  "AwsWafRegionalRule": {
    "MetricName": "string",
    "Name": "string",
    "PredicateList": [
      {
        "DataId": "string",
        "Negated": boolean,
        "Type": "string"
      }
    ],
    "RuleId": "string"
  },
  "AwsWafRegionalRuleGroup": {
    "MetricName": "string",
    "Name": "string",
    "RuleGroupId": "string",
    "Rules": [
      {
        "Action": {
          "Type": "string"
        },
        "Priority": number,
        "RuleId": "string",
        "Type": "string"
      }
    ]
  },
  "AwsWafRegionalWebAcl": {
    "DefaultAction": "string",
    "MetricName": "string",
    "Name": "string",
    "RulesList": [
      {
        "Action": {
          "Type": "string"
        },
        "OverrideAction": {
          "Type": "string"
        }
      }
    ]
  }
}
```

```
        "Priority": number,
        "RuleId": "string",
        "Type": "string"
    }
],
"WebAclId": "string"
},
"AwsWafRule": {
    "MetricName": "string",
    "Name": "string",
    "PredicateList": [
        {
            "DataId": "string",
            "Negated": boolean,
            "Type": "string"
        }
    ],
    "RuleId": "string"
},
"AwsWafRuleGroup": {
    "MetricName": "string",
    "Name": "string",
    "RuleGroupId": "string",
    "Rules": [
        {
            "Action": {
                "Type": "string"
            },
            "Priority": number,
            "RuleId": "string",
            "Type": "string"
        }
    ]
},
"AwsWafv2RuleGroup": {
    "Arn": "string",
    "Capacity": number,
    "Description": "string",
    "Id": "string",
    "Name": "string",
    "Rules": [
        {
            "Action": {
                "Allow": {
```

```
    "CustomRequestHandling": {
      "InsertHeaders": [
        {
          "Name": "string",
          "Value": "string"
        }
      ]
    },
    "Block": {
      "CustomResponse": {
        "CustomResponseBodyKey": "string",
        "ResponseCode": number,
        "ResponseHeaders": [
          {
            "Name": "string",
            "Value": "string"
          }
        ]
      }
    },
    "Captcha": {
      "CustomRequestHandling": {
        "InsertHeaders": [
          {
            "Name": "string",
            "Value": "string"
          }
        ]
      }
    },
    "Count": {
      "CustomRequestHandling": {
        "InsertHeaders": [
          {
            "Name": "string",
            "Value": "string"
          }
        ]
      }
    },
    "Name": "string",
    "OverrideAction": "string",
```

```
    "Priority": number,
    "VisibilityConfig": {
      "CloudWatchMetricsEnabled": boolean,
      "MetricName": "string",
      "SampledRequestsEnabled": boolean
    }
  ],
  "Scope": "string",
  "VisibilityConfig": {
    "CloudWatchMetricsEnabled": boolean,
    "MetricName": "string",
    "SampledRequestsEnabled": boolean
  }
},
"AwsWafv2WebAcl": {
  "Arn": "string",
  "Capacity": number,
  "CaptchaConfig": {
    "ImmunityTimeProperty": {
      "ImmunityTime": number
    }
  },
  "DefaultAction": {
    "Allow": {
      "CustomRequestHandling": {
        "InsertHeaders": [
          {
            "Name": "string",
            "Value": "string"
          }
        ]
      }
    }
  },
  "Block": {
    "CustomResponse": {
      "CustomResponseBodyKey": "string",
      "ResponseCode": number,
      "ResponseHeaders": [
        {
          "Name": "string",
          "Value": "string"
        }
      ]
    }
  }
}
```

```
    }
  }
},
"Description": "string",
"Id": "string",
"ManagedbyFirewallManager": boolean,
"Name": "string",
"Rules": [
  {
    "Action": {
      "Allow": {
        "CustomRequestHandling": {
          "InsertHeaders": [
            {
              "Name": "string",
              "Value": "string"
            }
          ]
        }
      },
      "Block": {
        "CustomResponse": {
          "CustomResponseBodyKey": "string",
          "ResponseCode": number,
          "ResponseHeaders": [
            {
              "Name": "string",
              "Value": "string"
            }
          ]
        }
      }
    },
    "Captcha": {
      "CustomRequestHandling": {
        "InsertHeaders": [
          {
            "Name": "string",
            "Value": "string"
          }
        ]
      }
    },
    "Count": {
      "CustomRequestHandling": {
```

```
        "InsertHeaders": [
            {
                "Name": "string",
                "Value": "string"
            }
        ]
    },
    "Name": "string",
    "OverrideAction": "string",
    "Priority": number,
    "VisibilityConfig": {
        "CloudWatchMetricsEnabled": boolean,
        "MetricName": "string",
        "SampledRequestsEnabled": boolean
    }
},
"VisibilityConfig": {
    "CloudWatchMetricsEnabled": boolean,
    "MetricName": "string",
    "SampledRequestsEnabled": boolean
}
},
"AwsWafWebAcl": {
    "DefaultAction": "string",
    "Name": "string",
    "Rules": [
        {
            "Action": {
                "Type": "string"
            },
            "ExcludedRules": [
                {
                    "RuleId": "string"
                }
            ],
            "OverrideAction": {
                "Type": "string"
            },
            "Priority": number,
            "RuleId": "string",
            "Type": "string"
        }
    ]
}
```

```
    }
  ],
  "WebAclId": "string"
},
"AwsXrayEncryptionConfig": {
  "KeyId": "string",
  "Status": "string",
  "Type": "string"
},
"Container": {
  "ContainerRuntime": "string",
  "ImageId": "string",
  "ImageName": "string",
  "LaunchedAt": "string",
  "Name": "string",
  "Privileged": boolean,
  "VolumeMounts": [
    {
      "MountPath": "string",
      "Name": "string"
    }
  ]
},
"Other": {
  "string" : "string"
}
},
"Id": "string",
"Partition": "string",
"Region": "string",
"ResourceRole": "string",
"Tags": {
  "string" : "string"
},
"Type": "string"
}
],
"Sample": boolean,
"SchemaVersion": "string",
"Severity": {
  "Label": "string",
  "Normalized": number,
  "Original": "string",
  "Product": number
}
```



```
},
  "SourceUrl": "string",
  "ThreatIntelIndicators": [
    {
      "Category": "string",
      "LastObservedAt": "string",
      "Source": "string",
      "SourceUrl": "string",
      "Type": "string",
      "Value": "string"
    }
  ],
  "Threats": [
    {
      "FilePaths": [
        {
          "FileName": "string",
          "FilePath": "string",
          "Hash": "string",
          "ResourceId": "string"
        }
      ],
      "ItemCount": number,
      "Name": "string",
      "Severity": "string"
    }
  ],
  "Title": "string",
  "Types": [ "string" ],
  "UpdatedAt": "string",
  "UserDefinedFields": {
    "string" : "string"
  },
  "VerificationState": "string",
  "Vulnerabilities": [
    {
      "CodeVulnerabilities": [
        {
          "Cwes": [ "string" ],
          "FilePath": {
            "EndLine": number,
            "FileName": "string",
            "FilePath": "string",
            "StartLine": number
          }
        }
      ]
    }
  ]
}
```

```
    },
    "SourceArn": "string"
  }
],
"Cvss": [
  {
    "Adjustments": [
      {
        "Metric": "string",
        "Reason": "string"
      }
    ],
    "BaseScore": number,
    "BaseVector": "string",
    "Source": "string",
    "Version": "string"
  }
],
"EpssScore": number,
"ExploitAvailable": "string",
"FixAvailable": "string",
"Id": "string",
"LastKnownExploitAt": "string",
"ReferenceUrls": [ "string" ],
"RelatedVulnerabilities": [ "string" ],
"Vendor": {
  "Name": "string",
  "Url": "string",
  "VendorCreatedAt": "string",
  "VendorSeverity": "string",
  "VendorUpdatedAt": "string"
},
"VulnerablePackages": [
  {
    "Architecture": "string",
    "Epoch": "string",
    "FilePath": "string",
    "FixedInVersion": "string",
    "Name": "string",
    "PackageManager": "string",
    "Release": "string",
    "Remediation": "string",
    "SourceLayerArn": "string",
    "SourceLayerHash": "string",
```

```
        "Version": "string"
      }
    ]
  },
  "Workflow": {
    "Status": "string"
  },
  "WorkflowState": "string"
}
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Findings

The findings that matched the filters specified in the request.

Type: Array of [AwsSecurityFinding](#) objects

NextToken

The pagination token to use to request the next page of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetInsightResults

Lists the results of the Security Hub insight specified by the insight ARN.

Request Syntax

```
GET /insights/results/InsightArn+ HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

InsightArn

The ARN of the insight for which to return results.

Pattern: `.*\S.*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "InsightResults": {
    "GroupByAttribute": "string",
    "InsightArn": "string",
    "ResultValues": [
      {
        "Count": number,
        "GroupByAttributeValue": "string"
      }
    ]
  }
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InsightResults

The insight results returned by the operation.

Type: [InsightResults](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetInsights

Lists and describes insights for the specified insight ARNs.

Request Syntax

```
POST /insights/get HTTP/1.1
Content-type: application/json

{
  "InsightArns": [ "string" ],
  "MaxResults": number,
  "NextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

InsightArns

The ARNs of the insights to describe. If you don't provide any insight ARNs, then `GetInsights` returns all of your custom insights. It does not return any managed insights.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

MaxResults

The maximum number of items to return in the response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The token that is required for pagination. On your first call to the GetInsights operation, set the value of this parameter to NULL.

For subsequent calls to the operation, to continue listing data, set the value of this parameter to the value returned from the previous response.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Insights": [
    {
      "Filters": {
        "AwsAccountId": [
          {
            "Comparison": "string",
            "Value": "string"
          }
        ],
        "AwsAccountName": [
          {
            "Comparison": "string",
            "Value": "string"
          }
        ],
        "CompanyName": [
          {
            "Comparison": "string",
            "Value": "string"
          }
        ],
        "ComplianceAssociatedStandardsId": [
          {
            "Comparison": "string",
            "Value": "string"
          }
        ]
      }
    }
  ]
}
```

```
    }
  ],
  "ComplianceSecurityControlId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ComplianceSecurityControlParametersName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ComplianceSecurityControlParametersValue": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ComplianceStatus": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Confidence": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "CreatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ]
}
```

```
],
  "Criticality": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "Description": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "FindingProviderFieldsConfidence": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "FindingProviderFieldsCriticality": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "FindingProviderFieldsRelatedFindingsId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "FindingProviderFieldsRelatedFindingsProductArn": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ]
}
```

```
    }
  ],
  "FindingProviderFieldsSeverityLabel": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "FindingProviderFieldsSeverityOriginal": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "FindingProviderFieldsTypes": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "FirstObservedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "GeneratorId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Id": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Keyword": [
    {
```

```
        "Value": "string"
      }
    ],
    "LastObservedAt": [
      {
        "DateRange": {
          "Unit": "string",
          "Value": number
        },
        "End": "string",
        "Start": "string"
      }
    ],
    "MalwareName": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "MalwarePath": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "MalwareState": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "MalwareType": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "NetworkDestinationDomain": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "NetworkDestinationIPv4": [
```

```
{
  "Cidr": "string"
},
"NetworkDestinationIpV6": [
  {
    "Cidr": "string"
  }
],
"NetworkDestinationPort": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"NetworkDirection": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"NetworkProtocol": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"NetworkSourceDomain": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"NetworkSourceIpV4": [
  {
    "Cidr": "string"
  }
],
"NetworkSourceIpV6": [
  {
    "Cidr": "string"
  }
]
```

```
    }
  ],
  "NetworkSourceMac": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "NetworkSourcePort": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "NoteText": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "NoteUpdatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "NoteUpdatedBy": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ProcessLaunchedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      }
    }
  ]
}
```

```
    },
    "End": "string",
    "Start": "string"
  }
],
"ProcessName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ProcessParentPid": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"ProcessPath": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ProcessPid": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"ProcessTerminatedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    },
    "End": "string",
    "Start": "string"
  }
]
```



```
],
  "ProductArn": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ProductFields": [
    {
      "Comparison": "string",
      "Key": "string",
      "Value": "string"
    }
  ],
  "ProductName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "RecommendationText": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "RecordState": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Region": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "RelatedFindingsId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
],
```

```
"RelatedFindingsProductArn": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceApplicationArn": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceApplicationName": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceAwsEc2InstanceIamInstanceProfileArn": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceAwsEc2InstanceImageId": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceAwsEc2InstanceIPv4Addresses": [  
  {  
    "Cidr": "string"  
  }  
],  
"ResourceAwsEc2InstanceIPv6Addresses": [  
  {  
    "Cidr": "string"  
  }  
],  
"ResourceAwsEc2InstanceKeyName": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
]
```

```
    }
  ],
  "ResourceAwsEc2InstanceLaunchedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "ResourceAwsEc2InstanceSubnetId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsEc2InstanceType": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsEc2InstanceVpcId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsIamAccessKeyCreatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "ResourceAwsIamAccessKeyPrincipalName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ]
}
```

```
    }
  ],
  "ResourceAwsIamAccessKeyStatus": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsIamAccessKeyUserName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsIamUserUserName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsS3BucketOwnerId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsS3BucketOwnerName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceContainerImageId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceContainerImageName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
],
```

```
"ResourceContainerLaunchedAt": [  
  {  
    "DateRange": {  
      "Unit": "string",  
      "Value": number  
    },  
    "End": "string",  
    "Start": "string"  
  }  
],  
"ResourceContainerName": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceDetailsOther": [  
  {  
    "Comparison": "string",  
    "Key": "string",  
    "Value": "string"  
  }  
],  
"ResourceId": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourcePartition": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceRegion": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceTags": [  
  {  
    "Comparison": "string",
```

```
        "Key": "string",
        "Value": "string"
    }
],
"ResourceType": [
    {
        "Comparison": "string",
        "Value": "string"
    }
],
"Sample": [
    {
        "Value": boolean
    }
],
"SeverityLabel": [
    {
        "Comparison": "string",
        "Value": "string"
    }
],
"SeverityNormalized": [
    {
        "Eq": number,
        "Gt": number,
        "Gte": number,
        "Lt": number,
        "Lte": number
    }
],
"SeverityProduct": [
    {
        "Eq": number,
        "Gt": number,
        "Gte": number,
        "Lt": number,
        "Lte": number
    }
],
"SourceUrl": [
    {
        "Comparison": "string",
        "Value": "string"
    }
]
```

```
],
  "ThreatIntelIndicatorCategory": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ThreatIntelIndicatorLastObservedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "ThreatIntelIndicatorSource": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ThreatIntelIndicatorSourceUrl": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ThreatIntelIndicatorType": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ThreatIntelIndicatorValue": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Title": [
    {
      "Comparison": "string",
```

```
        "Value": "string"
      }
    ],
    "Type": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "UpdatedAt": [
      {
        "DateRange": {
          "Unit": "string",
          "Value": number
        },
        "End": "string",
        "Start": "string"
      }
    ],
    "UserDefinedFields": [
      {
        "Comparison": "string",
        "Key": "string",
        "Value": "string"
      }
    ],
    "VerificationState": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "VulnerabilitiesExploitAvailable": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "VulnerabilitiesFixAvailable": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ]
  ],
```



```
    "WorkflowState": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "WorkflowStatus": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ]
  },
  "GroupByAttribute": "string",
  "InsightArn": "string",
  "Name": "string"
}
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Insights

The insights returned by the operation.

Type: Array of [Insight](#) objects

NextToken

The pagination token to use to request the next page of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetInvitationsCount

Note

We recommend using Amazon Organizations instead of Security Hub invitations to manage your member accounts. For information, see [Managing Security Hub administrator and member accounts with Organizations](#) in the *Amazon Security Hub User Guide*.

Returns the count of all Security Hub membership invitations that were sent to the calling member account, not including the currently accepted invitation.

Request Syntax

```
GET /invitations/count HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "InvitationsCount": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InvitationsCount

The number of all membership invitations sent to this Security Hub member account, not including the currently accepted invitation.

Type: Integer

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetMasterAccount

This method is deprecated. Instead, use `GetAdministratorAccount`.

The Security Hub console continues to use `GetMasterAccount`. It will eventually change to use `GetAdministratorAccount`. Any IAM policies that specifically control access to this function must continue to use `GetMasterAccount`. You should also add `GetAdministratorAccount` to your policies to ensure that the correct permissions are in place after the console begins to use `GetAdministratorAccount`.

Provides the details for the Security Hub administrator account for the current member account.

Can be used by both member accounts that are managed using Organizations and accounts that were invited manually.

Request Syntax

```
GET /master HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Master": {
    "AccountId": "string",
    "InvitationId": "string",
    "InvitedAt": "string",
    "MemberStatus": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Master

A list of details about the Security Hub administrator account for the current member account.

Type: [Invitation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetMembers

Returns the details for the Security Hub member accounts for the specified account IDs.

An administrator account can be either the delegated Security Hub administrator account for an organization or an administrator account that enabled Security Hub manually.

The results include both member accounts that are managed using Organizations and accounts that were invited manually.

Request Syntax

```
POST /members/get HTTP/1.1
Content-type: application/json

{
  "AccountIds": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AccountIds

The list of account IDs for the Security Hub member accounts to return the details for.

Type: Array of strings

Pattern: `.*\S.*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Members": [
    {
      "AccountId": "string",
      "AdministratorId": "string",
      "Email": "string",
      "InvitedAt": "string",
      "MasterId": "string",
      "MemberStatus": "string",
      "UpdatedAt": "string"
    }
  ],
  "UnprocessedAccounts": [
    {
      "AccountId": "string",
      "ProcessingResult": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Members

The list of details about the Security Hub member accounts.

Type: Array of [Member](#) objects

UnprocessedAccounts

The list of Amazon Web Services accounts that could not be processed. For each account, the list includes the account ID and the email address.

Type: Array of [Result](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetSecurityControlDefinition

Retrieves the definition of a security control. The definition includes the control title, description, Region availability, parameter definitions, and other details.

Request Syntax

```
GET /securityControl/definition?SecurityControlId=SecurityControlId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

SecurityControlId

The ID of the security control to retrieve the definition for. This field doesn't accept an Amazon Resource Name (ARN).

Pattern: `.*\S.*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "SecurityControlDefinition": {
    "CurrentRegionAvailability": "string",
    "CustomizableProperties": [ "string" ],
    "Description": "string",
    "ParameterDefinitions": {
      "string": {
        "ConfigurationOptions": { ... },
        "Description": "string"
      }
    }
  }
}
```

```
    }  
  },  
  "RemediationUrl": "string",  
  "SecurityControlId": "string",  
  "SeverityRating": "string",  
  "Title": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

SecurityControlDefinition

Provides metadata for a security control, including its unique standard-agnostic identifier, title, description, severity, availability in Amazon Web Services Regions, and a link to remediation steps.

Type: [SecurityControlDefinition](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

InviteMembers

Note

We recommend using Amazon Organizations instead of Security Hub invitations to manage your member accounts. For information, see [Managing Security Hub administrator and member accounts with Organizations](#) in the *Amazon Security Hub User Guide*.

Invites other Amazon Web Services accounts to become member accounts for the Security Hub administrator account that the invitation is sent from.

This operation is only used to invite accounts that don't belong to an Amazon organization. Organization accounts don't receive invitations.

Before you can use this action to invite a member, you must first use the `CreateMembers` action to create the member account in Security Hub.

When the account owner enables Security Hub and accepts the invitation to become a member account, the administrator account can view the findings generated in the member account.

Request Syntax

```
POST /members/invite HTTP/1.1
Content-type: application/json

{
  "AccountIds": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AccountIds

The list of account IDs of the Amazon Web Services accounts to invite to Security Hub as members.

Type: Array of strings

Pattern: `.*\S.*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "UnprocessedAccounts": [
    {
      "AccountId": "string",
      "ProcessingResult": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

UnprocessedAccounts

The list of Amazon Web Services accounts that could not be processed. For each account, the list includes the account ID and the email address.

Type: Array of [Result](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListAutomationRules

A list of automation rules and their metadata for the calling account.

Request Syntax

```
GET /automationrules/list?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of rules to return in the response. This currently ranges from 1 to 100.

Valid Range: Minimum value of 1. Maximum value of 100.

NextToken

A token to specify where to start paginating the response. This is the NextToken from a previously truncated response. On your first call to the ListAutomationRules API, set the value of this parameter to NULL.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AutomationRulesMetadata": [
    {
      "CreatedAt": "string",
      "CreatedBy": "string",
      "Description": "string",
      "IsTerminal": boolean,
      "RuleArn": "string",
```

```
    "RuleName": "string",
    "RuleOrder": number,
    "RuleStatus": "string",
    "UpdatedAt": "string"
  }
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AutomationRulesMetadata

Metadata for rules in the calling account. The response includes rules with a `RuleStatus` of `ENABLED` and `DISABLED`.

Type: Array of [AutomationRulesMetadata](#) objects

NextToken

A pagination token for the response.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListConfigurationPolicies

Lists the configuration policies that the Amazon Security Hub delegated administrator has created for your organization. Only the delegated administrator can invoke this operation from the home Region.

Request Syntax

```
GET /configurationPolicy/list?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results that's returned by `ListConfigurationPolicies` in each page of the response. When this parameter is used, `ListConfigurationPolicies` returns the specified number of results in a single page and a `NextToken` response element. You can see the remaining results of the initial request by sending another `ListConfigurationPolicies` request with the returned `NextToken` value. A valid range for `MaxResults` is between 1 and 100.

Valid Range: Minimum value of 1. Maximum value of 100.

NextToken

The `NextToken` value that's returned from a previous paginated `ListConfigurationPolicies` request where `MaxResults` was used but the results exceeded the value of that parameter. Pagination continues from the `MaxResults` was used but the results exceeded the value of that parameter. Pagination continues from the end of the previous response that returned the `NextToken` value. This value is `null` when there are no more results to return.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ConfigurationPolicySummaries": [
    {
      "Arn": "string",
      "Description": "string",
      "Id": "string",
      "Name": "string",
      "ServiceEnabled": boolean,
      "UpdatedAt": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ConfigurationPolicySummaries](#)

Provides metadata for each of your configuration policies.

Type: Array of [ConfigurationPolicySummary](#) objects

[NextToken](#)

The NextToken value to include in the next ListConfigurationPolicies request. When the results of a ListConfigurationPolicies request exceed MaxResults, this value can be used to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListConfigurationPolicyAssociations

Provides information about the associations for your configuration policies and self-managed behavior. Only the Amazon Security Hub delegated administrator can invoke this operation from the home Region.

Request Syntax

```
POST /configurationPolicyAssociation/list HTTP/1.1
Content-type: application/json

{
  "Filters": {
    "AssociationStatus": "string",
    "AssociationType": "string",
    "ConfigurationPolicyId": "string"
  },
  "MaxResults": number,
  "NextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Filters

Options for filtering the ListConfigurationPolicyAssociations response. You can filter by the Amazon Resource Name (ARN) or universally unique identifier (UUID) of a configuration, AssociationType, or AssociationStatus.

Type: [AssociationFilters](#) object

Required: No

MaxResults

The maximum number of results that's returned by `ListConfigurationPolicies` in each page of the response. When this parameter is used, `ListConfigurationPolicyAssociations` returns the specified number of results in a single page and a `NextToken` response element. You can see the remaining results of the initial request by sending another `ListConfigurationPolicyAssociations` request with the returned `NextToken` value. A valid range for `MaxResults` is between 1 and 100.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The `NextToken` value that's returned from a previous paginated `ListConfigurationPolicyAssociations` request where `MaxResults` was used but the results exceeded the value of that parameter. Pagination continues from the end of the previous response that returned the `NextToken` value. This value is `null` when there are no more results to return.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ConfigurationPolicyAssociationSummaries": [
    {
      "AssociationStatus": "string",
      "AssociationStatusMessage": "string",
      "AssociationType": "string",
      "ConfigurationPolicyId": "string",
      "TargetId": "string",
      "TargetType": "string",
```

```
    "UpdatedAt": "string"  
  }  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ConfigurationPolicyAssociationSummaries

An object that contains the details of each configuration policy association that's returned in a `ListConfigurationPolicyAssociations` request.

Type: Array of [ConfigurationPolicyAssociationSummary](#) objects

NextToken

The `NextToken` value to include in the next `ListConfigurationPolicyAssociations` request. When the results of a `ListConfigurationPolicyAssociations` request exceed `MaxResults`, this value can be used to retrieve the next page of results. This value is `null` when there are no more results to return.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListEnabledProductsForImport

Lists all findings-generating solutions (products) that you are subscribed to receive findings from in Security Hub.

Request Syntax

```
GET /productSubscriptions?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of items to return in the response.

Valid Range: Minimum value of 1. Maximum value of 100.

NextToken

The token that is required for pagination. On your first call to the `ListEnabledProductsForImport` operation, set the value of this parameter to NULL.

For subsequent calls to the operation, to continue listing data, set the value of this parameter to the value returned from the previous response.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "ProductSubscriptions": [ "string" ]
}
```



```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token to use to request the next page of results.

Type: String

ProductSubscriptions

The list of ARNs for the resources that represent your subscriptions to products.

Type: Array of strings

Pattern: .*\\S.*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListFindingAggregators

If cross-Region aggregation is enabled, then `ListFindingAggregators` returns the Amazon Resource Name (ARN) of the finding aggregator. You can run this operation from any Amazon Web Services Region.

Request Syntax

```
GET /findingAggregator/list?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return. This operation currently only returns a single result.

Valid Range: Minimum value of 1. Maximum value of 100.

NextToken

The token returned with the previous set of results. Identifies the next set of results to return.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "FindingAggregators": [
    {
      "FindingAggregatorArn": "string"
    }
  ],
  "NextToken": "string"
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

FindingAggregators

The list of finding aggregators. This operation currently only returns a single result.

Type: Array of [FindingAggregator](#) objects

NextToken

If there are more results, this is the token to provide in the next call to `ListFindingAggregators`.

This operation currently only returns a single result.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListInvitations

Note

We recommend using Amazon Organizations instead of Security Hub invitations to manage your member accounts. For information, see [Managing Security Hub administrator and member accounts with Organizations](#) in the *Amazon Security Hub User Guide*.

Lists all Security Hub membership invitations that were sent to the calling account.

Only accounts that are managed by invitation can use this operation. Accounts that are managed using the integration with Organizations don't receive invitations.

Request Syntax

```
GET /invitations?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of items to return in the response.

Valid Range: Minimum value of 1. Maximum value of 50.

NextToken

The token that is required for pagination. On your first call to the `ListInvitations` operation, set the value of this parameter to `NULL`.

For subsequent calls to the operation, to continue listing data, set the value of this parameter to the value returned from the previous response.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Invitations": [
    {
      "AccountId": "string",
      "InvitationId": "string",
      "InvitedAt": "string",
      "MemberStatus": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Invitations

The details of the invitations returned by the operation.

Type: Array of [Invitation](#) objects

NextToken

The pagination token to use to request the next page of results.

Type: String

Pattern: `.*\S.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

ListMembers

Lists details about all member accounts for the current Security Hub administrator account.

The results include both member accounts that belong to an organization and member accounts that were invited manually.

Request Syntax

```
GET /members?MaxResults=MaxResults&NextToken=NextToken&OnlyAssociated=OnlyAssociated  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of items to return in the response.

Valid Range: Minimum value of 1. Maximum value of 50.

NextToken

The token that is required for pagination. On your first call to the ListMembers operation, set the value of this parameter to NULL.

For subsequent calls to the operation, to continue listing data, set the value of this parameter to the value returned from the previous response.

OnlyAssociated

Specifies which member accounts to include in the response based on their relationship status with the administrator account. The default value is TRUE.

If OnlyAssociated is set to TRUE, the response includes member accounts whose relationship status with the administrator account is set to ENABLED.

If OnlyAssociated is set to FALSE, the response includes all existing member accounts.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Members": [
    {
      "AccountId": "string",
      "AdministratorId": "string",
      "Email": "string",
      "InvitedAt": "string",
      "MasterId": "string",
      "MemberStatus": "string",
      "UpdatedAt": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Members

Member details returned by the operation.

Type: Array of [Member](#) objects

NextToken

The pagination token to use to request the next page of results.

Type: String

Pattern: `.*\S.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

ListOrganizationAdminAccounts

Lists the Security Hub administrator accounts. Can only be called by the organization management account.

Request Syntax

```
GET /organization/admin?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of items to return in the response.

Valid Range: Minimum value of 1. Maximum value of 10.

NextToken

The token that is required for pagination. On your first call to the `ListOrganizationAdminAccounts` operation, set the value of this parameter to `NULL`. For subsequent calls to the operation, to continue listing data, set the value of this parameter to the value returned from the previous response.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AdminAccounts": [
    {
      "AccountId": "string",
      "Status": "string"
    }
  ]
}
```

```
    }  
  ],  
  "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AdminAccounts

The list of Security Hub administrator accounts.

Type: Array of [AdminAccount](#) objects

NextToken

The pagination token to use to request the next page of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListSecurityControlDefinitions

Lists all of the security controls that apply to a specified standard.

Request Syntax

```
GET /securityControls/definitions?  
MaxResults=MaxResults&NextToken=NextToken&StandardsArn=StandardsArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

An optional parameter that limits the total results of the API response to the specified number. If this parameter isn't provided in the request, the results include the first 25 security controls that apply to the specified standard. The results also include a `NextToken` parameter that you can use in a subsequent API call to get the next 25 controls. This repeats until all controls for the standard are returned.

Valid Range: Minimum value of 1. Maximum value of 100.

NextToken

Optional pagination parameter.

StandardsArn

The Amazon Resource Name (ARN) of the standard that you want to view controls for.

Pattern: `.*\S.*`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "NextToken": "string",
  "SecurityControlDefinitions": [
    {
      "CurrentRegionAvailability": "string",
      "CustomizableProperties": [ "string" ],
      "Description": "string",
      "ParameterDefinitions": {
        "string" : {
          "ConfigurationOptions": { ... },
          "Description": "string"
        }
      },
      "RemediationUrl": "string",
      "SecurityControlId": "string",
      "SeverityRating": "string",
      "Title": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A pagination parameter that's included in the response only if it was included in the request.

Type: String

SecurityControlDefinitions

An array of controls that apply to the specified standard.

Type: Array of [SecurityControlDefinition](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

ListStandardsControlAssociations

Specifies whether a control is currently enabled or disabled in each enabled standard in the calling account.

This operation omits standards control associations for standard subscriptions where `StandardsControlsUpdatable` has value `NOT_READY_FOR_UPDATES`.

Request Syntax

```
GET /associations?  
MaxResults=MaxResults&NextToken=NextToken&SecurityControlId=SecurityControlId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

An optional parameter that limits the total results of the API response to the specified number. If this parameter isn't provided in the request, the results include the first 25 standard and control associations. The results also include a `NextToken` parameter that you can use in a subsequent API call to get the next 25 associations. This repeats until all associations for the specified control are returned. The number of results is limited by the number of supported Security Hub standards that you've enabled in the calling account.

Valid Range: Minimum value of 1. Maximum value of 100.

NextToken

Optional pagination parameter.

SecurityControlId

The identifier of the control (identified with `SecurityControlId`, `SecurityControlArn`, or a mix of both parameters) that you want to determine the enablement status of in each enabled standard.

Pattern: `.*\S.*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "StandardsControlAssociationSummaries": [
    {
      "AssociationStatus": "string",
      "RelatedRequirements": [ "string" ],
      "SecurityControlArn": "string",
      "SecurityControlId": "string",
      "StandardsArn": "string",
      "StandardsControlDescription": "string",
      "StandardsControlTitle": "string",
      "UpdatedAt": "string",
      "UpdatedReason": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A pagination parameter that's included in the response only if it was included in the request.

Type: String

StandardsControlAssociationSummaries

An array that provides the enablement status and other details for each security control that applies to each enabled standard.

Type: Array of [StandardsControlAssociationSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListTagsForResource

Returns a list of tags associated with a resource.

Request Syntax

```
GET /tags/ResourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The ARN of the resource to retrieve tags for.

Pattern: `^arn:aws:securityhub:.*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tags

The tags associated with a resource.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+ -=._:/]+$`

Value Length Constraints: Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

StartConfigurationPolicyAssociation

Associates a target account, organizational unit, or the root with a specified configuration. The target can be associated with a configuration policy or self-managed behavior. Only the Amazon Security Hub delegated administrator can invoke this operation from the home Region.

Request Syntax

```
POST /configurationPolicyAssociation/associate HTTP/1.1
Content-type: application/json

{
  "ConfigurationPolicyIdentifier": "string",
  "Target": { ... }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ConfigurationPolicyIdentifier

The Amazon Resource Name (ARN) of a configuration policy, the universally unique identifier (UUID) of a configuration policy, or a value of SELF_MANAGED_SECURITY_HUB for a self-managed configuration.

Type: String

Pattern: `.*\S.*`

Required: Yes

Target

The identifier of the target account, organizational unit, or the root to associate with the specified configuration.

Type: [Target](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AssociationStatus": "string",
  "AssociationStatusMessage": "string",
  "AssociationType": "string",
  "ConfigurationPolicyId": "string",
  "TargetId": "string",
  "TargetType": "string",
  "UpdatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AssociationStatus](#)

The current status of the association between the specified target and the configuration.

Type: String

Valid Values: PENDING | SUCCESS | FAILED

[AssociationStatusMessage](#)

An explanation for a FAILED value for AssociationStatus.

Type: String

Pattern: .*S.*

AssociationType

Indicates whether the association between the specified target and the configuration was directly applied by the Security Hub delegated administrator or inherited from a parent.

Type: String

Valid Values: INHERITED | APPLIED

ConfigurationPolicyId

The UUID of the configuration policy.

Type: String

Pattern: .*\\S.*

TargetId

The identifier of the target account, organizational unit, or the organization root with which the configuration is associated.

Type: String

Pattern: .*\\S.*

TargetType

Indicates whether the target is an Amazon Web Services account, organizational unit, or the organization root.

Type: String

Valid Values: ACCOUNT | ORGANIZATIONAL_UNIT | ROOT

UpdatedAt

The date and time, in UTC and ISO 8601 format, that the configuration policy association was last updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)

- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

StartConfigurationPolicyDisassociation

Disassociates a target account, organizational unit, or the root from a specified configuration. When you disassociate a configuration from its target, the target inherits the configuration of the closest parent. If there's no configuration to inherit, the target retains its settings but becomes a self-managed account. A target can be disassociated from a configuration policy or self-managed behavior. Only the Amazon Security Hub delegated administrator can invoke this operation from the home Region.

Request Syntax

```
POST /configurationPolicyAssociation/disassociate HTTP/1.1
Content-type: application/json

{
  "ConfigurationPolicyIdentifier": "string",
  "Target": { ... }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ConfigurationPolicyIdentifier

The Amazon Resource Name (ARN) of a configuration policy, the universally unique identifier (UUID) of a configuration policy, or a value of SELF_MANAGED_SECURITY_HUB for a self-managed configuration.

Type: String

Pattern: `.*\S.*`

Required: Yes

Target

The identifier of the target account, organizational unit, or the root to disassociate from the specified configuration.

Type: [Target](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

TagResource

Adds one or more tags to a resource.

Request Syntax

```
POST /tags/ResourceArn HTTP/1.1
Content-type: application/json
```

```
{
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The ARN of the resource to apply the tags to.

Pattern: `^arn:aws:securityhub:.*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Tags

The tags to add to the resource. You can add up to 50 tags at a time. The tag keys can be no longer than 128 characters. The tag values can be no longer than 256 characters.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z+-._: /]+$`

Value Length Constraints: Maximum length of 256.

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UntagResource

Removes one or more tags from a resource.

Request Syntax

```
DELETE /tags/ResourceArn?tagKeys=TagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The ARN of the resource to remove the tags from.

Pattern: `^arn:aws:securityhub:.*`

Required: Yes

TagKeys

The tag keys associated with the tags to remove from the resource. You can remove up to 50 tags at a time.

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!aws:)[a-zA-Z+-. _:/]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)

- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateActionTarget

Updates the name and description of a custom action target in Security Hub.

Request Syntax

```
PATCH /actionTargets/ActionTargetArn HTTP/1.1
Content-type: application/json

{
  "Description": "string",
  "Name": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

ActionTargetArn

The ARN of the custom action target to update.

Pattern: `.*\S.*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Description

The updated description for the custom action target.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The updated name of the custom action target.

Type: String

Pattern: .*\\S.*

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateConfigurationPolicy

Updates a configuration policy. Only the Amazon Security Hub delegated administrator can invoke this operation from the home Region.

Request Syntax

```
PATCH /configurationPolicy/Identifier HTTP/1.1
Content-type: application/json

{
  "ConfigurationPolicy": { ... },
  "Description": "string",
  "Name": "string",
  "UpdatedReason": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The Amazon Resource Name (ARN) or universally unique identifier (UUID) of the configuration policy.

Pattern: `.*\S.*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

ConfigurationPolicy

An object that defines how Security Hub is configured. It includes whether Security Hub is enabled or disabled, a list of enabled security standards, a list of enabled or disabled security controls, and a list of custom parameter values for specified controls. If you provide a list of security controls that are enabled in the configuration policy, Security Hub disables all other

controls (including newly released controls). If you provide a list of security controls that are disabled in the configuration policy, Security Hub enables all other controls (including newly released controls).

When updating a configuration policy, provide a complete list of standards that you want to enable and a complete list of controls that you want to enable or disable. The updated configuration replaces the current configuration.

Type: [Policy](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

Description

The description of the configuration policy.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the configuration policy. Alphanumeric characters and the following ASCII characters are permitted: `-`, `.`, `!`, `*`, `/`.

Type: String

Pattern: `.*\S.*`

Required: No

UpdatedReason

The reason for updating the configuration policy.

Type: String

Pattern: `.*\S.*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "ConfigurationPolicy": { ... },
  "CreatedAt": "string",
  "Description": "string",
  "Id": "string",
  "Name": "string",
  "UpdatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The ARN of the configuration policy.

Type: String

Pattern: `.*\S.*`

ConfigurationPolicy

An object that defines how Security Hub is configured. It includes whether Security Hub is enabled or disabled, a list of enabled security standards, a list of enabled or disabled security controls, and a list of custom parameter values for specified controls. If the request included a list of security controls that are enabled in the configuration policy, Security Hub disables all other controls (including newly released controls). If the request included a list of security controls that are disabled in the configuration policy, Security Hub enables all other controls (including newly released controls).

Type: [Policy](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

CreatedAt

The date and time, in UTC and ISO 8601 format, that the configuration policy was created.

Type: Timestamp

Description

The description of the configuration policy.

Type: String

Pattern: `.*\S.*`

Id

The UUID of the configuration policy.

Type: String

Pattern: `.*\S.*`

Name

The name of the configuration policy.

Type: String

Pattern: `.*\S.*`

UpdatedAt

The date and time, in UTC and ISO 8601 format, that the configuration policy was last updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceConflictException

The resource specified in the request conflicts with an existing resource.

HTTP Status Code: 409

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)

- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateFindingAggregator

Note

The *aggregation Region* is now called the *home Region*.

Updates cross-Region aggregation settings. You can use this operation to update the Region linking mode and the list of included or excluded Amazon Web Services Regions. However, you can't use this operation to change the home Region.

You can invoke this operation from the current home Region only.

Request Syntax

```
PATCH /findingAggregator/update HTTP/1.1
Content-type: application/json
```

```
{
  "FindingAggregatorArn": "string",
  "RegionLinkingMode": "string",
  "Regions": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

FindingAggregatorArn

The ARN of the finding aggregator. To obtain the ARN, use `ListFindingAggregators`.

Type: String

Pattern: `.*\S.*`

Required: Yes

RegionLinkingMode

Indicates whether to aggregate findings from all of the available Regions in the current partition. Also determines whether to automatically aggregate findings from new Regions as Security Hub supports them and you opt into them.

The selected option also determines how to use the Regions provided in the Regions list.

The options are as follows:

- **ALL_REGIONS** - Aggregates findings from all of the Regions where Security Hub is enabled. When you choose this option, Security Hub also automatically aggregates findings from new Regions as Security Hub supports them and you opt into them.
- **ALL_REGIONS_EXCEPT_SPECIFIED** - Aggregates findings from all of the Regions where Security Hub is enabled, except for the Regions listed in the Regions parameter. When you choose this option, Security Hub also automatically aggregates findings from new Regions as Security Hub supports them and you opt into them.
- **SPECIFIED_REGIONS** - Aggregates findings only from the Regions listed in the Regions parameter. Security Hub does not automatically aggregate findings from new Regions.
- **NO_REGIONS** - Aggregates no data because no Regions are selected as linked Regions.

Type: String

Pattern: `.*\S.*`

Required: Yes

Regions

If `RegionLinkingMode` is `ALL_REGIONS_EXCEPT_SPECIFIED`, then this is a space-separated list of Regions that don't replicate and send findings to the home Region.

If `RegionLinkingMode` is `SPECIFIED_REGIONS`, then this is a space-separated list of Regions that do replicate and send findings to the home Region.

An `InvalidInputException` error results if you populate this field while `RegionLinkingMode` is `NO_REGIONS`.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "FindingAggregationRegion": "string",
  "FindingAggregatorArn": "string",
  "RegionLinkingMode": "string",
  "Regions": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

FindingAggregationRegion

The home Region. Findings generated in linked Regions are replicated and sent to the home Region.

Type: String

Pattern: `.*\S.*`

FindingAggregatorArn

The ARN of the finding aggregator.

Type: String

Pattern: `.*\S.*`

RegionLinkingMode

Indicates whether to link all Regions, all Regions except for a list of excluded Regions, or a list of included Regions.

Type: String

Pattern: .*\\S.*

Regions

The list of excluded Regions or included Regions.

Type: Array of strings

Pattern: .*\\S.*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateFindings

UpdateFindings is a deprecated operation. Instead of UpdateFindings, use the BatchUpdateFindings operation.

The UpdateFindings operation updates the Note and RecordState of the Amazon Security Hub aggregated findings that the filter attributes specify. Any member account that can view the finding can also see the update to the finding.

Finding updates made with UpdateFindings aren't persisted if the same finding is later updated by the finding provider through the BatchImportFindings operation. In addition, Security Hub doesn't record updates made with UpdateFindings in the finding history.

Request Syntax

```
PATCH /findings HTTP/1.1
Content-type: application/json

{
  "Filters": {
    "AwsAccountId": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "AwsAccountName": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "CompanyName": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "ComplianceAssociatedStandardsId": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ]
  }
}
```



```
    }
  ],
  "ComplianceSecurityControlId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ComplianceSecurityControlParametersName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ComplianceSecurityControlParametersValue": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ComplianceStatus": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Confidence": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "CreatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ]
}
```

```
],
  "Criticality": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "Description": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "FindingProviderFieldsConfidence": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "FindingProviderFieldsCriticality": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "FindingProviderFieldsRelatedFindingsId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "FindingProviderFieldsRelatedFindingsProductArn": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ]
}
```

```
    }
  ],
  "FindingProviderFieldsSeverityLabel": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "FindingProviderFieldsSeverityOriginal": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "FindingProviderFieldsTypes": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "FirstObservedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "GeneratorId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Id": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Keyword": [
    {
```

```
    "Value": "string"
  }
],
"LastObservedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    },
    "End": "string",
    "Start": "string"
  }
],
"MalwareName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"MalwarePath": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"MalwareState": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"MalwareType": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"NetworkDestinationDomain": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"NetworkDestinationIPv4": [
```

```
{
  "Cidr": "string"
},
"NetworkDestinationIpV6": [
  {
    "Cidr": "string"
  }
],
"NetworkDestinationPort": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"NetworkDirection": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"NetworkProtocol": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"NetworkSourceDomain": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"NetworkSourceIpV4": [
  {
    "Cidr": "string"
  }
],
"NetworkSourceIpV6": [
  {
    "Cidr": "string"
  }
]
```

```
    }
  ],
  "NetworkSourceMac": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "NetworkSourcePort": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "NoteText": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "NoteUpdatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "NoteUpdatedBy": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ProcessLaunchedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      }
    }
  ]
}
```

```
    },
    "End": "string",
    "Start": "string"
  }
],
"ProcessName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ProcessParentPid": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"ProcessPath": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ProcessPid": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"ProcessTerminatedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    },
    "End": "string",
    "Start": "string"
  }
]
```

```
],
  "ProductArn": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ProductFields": [
    {
      "Comparison": "string",
      "Key": "string",
      "Value": "string"
    }
  ],
  "ProductName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "RecommendationText": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "RecordState": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Region": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "RelatedFindingsId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
],
```



```
"RelatedFindingsProductArn": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceApplicationArn": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceApplicationName": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceAwsEc2InstanceIamInstanceProfileArn": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceAwsEc2InstanceImageId": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceAwsEc2InstanceIPv4Addresses": [  
  {  
    "Cidr": "string"  
  }  
],  
"ResourceAwsEc2InstanceIPv6Addresses": [  
  {  
    "Cidr": "string"  
  }  
],  
"ResourceAwsEc2InstanceKeyName": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
]
```

```
    }
  ],
  "ResourceAwsEc2InstanceLaunchedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "ResourceAwsEc2InstanceSubnetId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsEc2InstanceType": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsEc2InstanceVpcId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsIamAccessKeyCreatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "ResourceAwsIamAccessKeyPrincipalName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ]
}
```

```
    }
  ],
  "ResourceAwsIamAccessKeyStatus": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsIamAccessKeyUserName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsIamUserUserName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsS3BucketOwnerId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsS3BucketOwnerName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceContainerImageId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceContainerImageName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
],
```

```
"ResourceContainerLaunchedAt": [  
  {  
    "DateRange": {  
      "Unit": "string",  
      "Value": number  
    },  
    "End": "string",  
    "Start": "string"  
  }  
],  
"ResourceContainerName": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceDetailsOther": [  
  {  
    "Comparison": "string",  
    "Key": "string",  
    "Value": "string"  
  }  
],  
"ResourceId": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourcePartition": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceRegion": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceTags": [  
  {  
    "Comparison": "string",
```

```
    "Key": "string",
    "Value": "string"
  }
],
"ResourceType": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"Sample": [
  {
    "Value": boolean
  }
],
"SeverityLabel": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"SeverityNormalized": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"SeverityProduct": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"SourceUrl": [
  {
    "Comparison": "string",
    "Value": "string"
  }
]
```

```
],
  "ThreatIntelIndicatorCategory": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ThreatIntelIndicatorLastObservedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "ThreatIntelIndicatorSource": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ThreatIntelIndicatorSourceUrl": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ThreatIntelIndicatorType": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ThreatIntelIndicatorValue": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "Title": [
    {
      "Comparison": "string",
```

```
    "Value": "string"
  }
],
"Type": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"UpdatedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    },
    "End": "string",
    "Start": "string"
  }
],
"UserDefinedFields": [
  {
    "Comparison": "string",
    "Key": "string",
    "Value": "string"
  }
],
"VerificationState": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"VulnerabilitiesExploitAvailable": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"VulnerabilitiesFixAvailable": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
],
```

```
    "WorkflowState": [  
      {  
        "Comparison": "string",  
        "Value": "string"  
      }  
    ],  
    "WorkflowStatus": [  
      {  
        "Comparison": "string",  
        "Value": "string"  
      }  
    ]  
  },  
  "Note": {  
    "Text": "string",  
    "UpdatedBy": "string"  
  },  
  "RecordState": "string"  
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Filters

A collection of attributes that specify which findings you want to update.

Type: [AwsSecurityFindingFilters](#) object

Required: Yes

Note

The updated note for the finding.

Type: [NoteUpdate](#) object

Required: No

RecordState

The updated record state for the finding.

Type: String

Valid Values: ACTIVE | ARCHIVED

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateInsight

Updates the Security Hub insight identified by the specified insight ARN.

Request Syntax

```
PATCH /insights/InsightArn+ HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "Filters": {
    "AwsAccountId": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "AwsAccountName": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "CompanyName": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "ComplianceAssociatedStandardsId": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "ComplianceSecurityControlId": [
      {
        "Comparison": "string",
        "Value": "string"
      }
    ],
    "ComplianceSecurityControlParametersName": [
      {
```

```
    "Comparison": "string",
    "Value": "string"
  }
],
"ComplianceSecurityControlParametersValue": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ComplianceStatus": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"Confidence": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"CreatedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    },
    "End": "string",
    "Start": "string"
  }
],
"Criticality": [
  {
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
```

```
"Description": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"FindingProviderFieldsConfidence": [  
  {  
    "Eq": number,  
    "Gt": number,  
    "Gte": number,  
    "Lt": number,  
    "Lte": number  
  }  
],  
"FindingProviderFieldsCriticality": [  
  {  
    "Eq": number,  
    "Gt": number,  
    "Gte": number,  
    "Lt": number,  
    "Lte": number  
  }  
],  
"FindingProviderFieldsRelatedFindingsId": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"FindingProviderFieldsRelatedFindingsProductArn": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"FindingProviderFieldsSeverityLabel": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"FindingProviderFieldsSeverityOriginal": [  
  {
```

```
    "Comparison": "string",
    "Value": "string"
  }
],
"FindingProviderFieldsTypes": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"FirstObservedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    },
    "End": "string",
    "Start": "string"
  }
],
"GeneratorId": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"Id": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"Keyword": [
  {
    "Value": "string"
  }
],
"LastObservedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    },
    "End": "string",
```

```
    "Start": "string"
  }
],
"MalwareName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"MalwarePath": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"MalwareState": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"MalwareType": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"NetworkDestinationDomain": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"NetworkDestinationIPv4": [
  {
    "Cidr": "string"
  }
],
"NetworkDestinationIPv6": [
  {
    "Cidr": "string"
  }
],
"NetworkDestinationPort": [
```

```
{
  "Eq": number,
  "Gt": number,
  "Gte": number,
  "Lt": number,
  "Lte": number
}
],
"NetworkDirection": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"NetworkProtocol": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"NetworkSourceDomain": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"NetworkSourceIPv4": [
  {
    "Cidr": "string"
  }
],
"NetworkSourceIPv6": [
  {
    "Cidr": "string"
  }
],
"NetworkSourceMac": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"NetworkSourcePort": [
  {
```



```
    "Eq": number,
    "Gt": number,
    "Gte": number,
    "Lt": number,
    "Lte": number
  }
],
"NoteText": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"NoteUpdatedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    },
    "End": "string",
    "Start": "string"
  }
],
"NoteUpdatedBy": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ProcessLaunchedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    },
    "End": "string",
    "Start": "string"
  }
],
"ProcessName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
]
```

```
],
  "ProcessParentPid": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "ProcessPath": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ProcessPid": [
    {
      "Eq": number,
      "Gt": number,
      "Gte": number,
      "Lt": number,
      "Lte": number
    }
  ],
  "ProcessTerminatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "ProductArn": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ProductFields": [
    {
      "Comparison": "string",
```

```
    "Key": "string",
    "Value": "string"
  }
],
"ProductName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"RecommendationText": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"RecordState": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"Region": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"RelatedFindingsId": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"RelatedFindingsProductArn": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceApplicationArn": [
  {
    "Comparison": "string",
    "Value": "string"
  }
]
```

```
    }
  ],
  "ResourceApplicationName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsEc2InstanceIamInstanceProfileArn": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsEc2InstanceImageId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsEc2InstanceIpV4Addresses": [
    {
      "Cidr": "string"
    }
  ],
  "ResourceAwsEc2InstanceIpV6Addresses": [
    {
      "Cidr": "string"
    }
  ],
  "ResourceAwsEc2InstanceKeyName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsEc2InstanceLaunchedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ]
}
```

```
    }
  ],
  "ResourceAwsEc2InstanceSubnetId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsEc2InstanceType": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsEc2InstanceVpcId": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsIamAccessKeyCreatedAt": [
    {
      "DateRange": {
        "Unit": "string",
        "Value": number
      },
      "End": "string",
      "Start": "string"
    }
  ],
  "ResourceAwsIamAccessKeyPrincipalName": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsIamAccessKeyStatus": [
    {
      "Comparison": "string",
      "Value": "string"
    }
  ],
  "ResourceAwsIamAccessKeyUserName": [
    {
```

```
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsIamUserUserName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsS3BucketOwnerId": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceAwsS3BucketOwnerName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceContainerImageId": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceContainerImageName": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"ResourceContainerLaunchedAt": [
  {
    "DateRange": {
      "Unit": "string",
      "Value": number
    },
    "End": "string",
    "Start": "string"
  }
],
```

```
"ResourceContainerName": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceDetailsOther": [  
  {  
    "Comparison": "string",  
    "Key": "string",  
    "Value": "string"  
  }  
],  
"ResourceId": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourcePartition": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceRegion": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ResourceTags": [  
  {  
    "Comparison": "string",  
    "Key": "string",  
    "Value": "string"  
  }  
],  
"ResourceType": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],
```

```
"Sample": [  
  {  
    "Value": boolean  
  }  
],  
"SeverityLabel": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"SeverityNormalized": [  
  {  
    "Eq": number,  
    "Gt": number,  
    "Gte": number,  
    "Lt": number,  
    "Lte": number  
  }  
],  
"SeverityProduct": [  
  {  
    "Eq": number,  
    "Gt": number,  
    "Gte": number,  
    "Lt": number,  
    "Lte": number  
  }  
],  
"SourceUrl": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ThreatIntelIndicatorCategory": [  
  {  
    "Comparison": "string",  
    "Value": "string"  
  }  
],  
"ThreatIntelIndicatorLastObservedAt": [  
  {  
    "DateRange": {
```



```
        "Unit": "string",
        "Value": number
    },
    "End": "string",
    "Start": "string"
}
],
"ThreatIntelIndicatorSource": [
{
    "Comparison": "string",
    "Value": "string"
}
],
"ThreatIntelIndicatorSourceUrl": [
{
    "Comparison": "string",
    "Value": "string"
}
],
"ThreatIntelIndicatorType": [
{
    "Comparison": "string",
    "Value": "string"
}
],
"ThreatIntelIndicatorValue": [
{
    "Comparison": "string",
    "Value": "string"
}
],
"Title": [
{
    "Comparison": "string",
    "Value": "string"
}
],
"Type": [
{
    "Comparison": "string",
    "Value": "string"
}
],
"UpdatedAt": [
```

```
{
  "DateRange": {
    "Unit": "string",
    "Value": number
  },
  "End": "string",
  "Start": "string"
},
"UserDefinedFields": [
  {
    "Comparison": "string",
    "Key": "string",
    "Value": "string"
  }
],
"VerificationState": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"VulnerabilitiesExploitAvailable": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"VulnerabilitiesFixAvailable": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"WorkflowState": [
  {
    "Comparison": "string",
    "Value": "string"
  }
],
"WorkflowStatus": [
  {
    "Comparison": "string",
    "Value": "string"
  }
]
```

```
    }  
  ]  
},  
"GroupByAttribute": "string",  
"Name": "string"  
}
```

URI Request Parameters

The request uses the following URI parameters.

InsightArn

The ARN of the insight that you want to update.

Pattern: `.*\S.*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Filters

The updated filters that define this insight.

Type: [AwsSecurityFindingFilters](#) object

Required: No

GroupByAttribute

The updated GroupBy attribute that defines this insight.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The updated name for the insight.

Type: String

Pattern: .*\\S.*

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateOrganizationConfiguration

Updates the configuration of your organization in Amazon Security Hub. Only the Security Hub administrator account can invoke this operation.

Request Syntax

```
POST /organization/configuration HTTP/1.1
Content-type: application/json
```

```
{
  "AutoEnable": boolean,
  "AutoEnableStandards": "string",
  "OrganizationConfiguration": {
    "ConfigurationType": "string",
    "Status": "string",
    "StatusMessage": "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AutoEnable

Whether to automatically enable Security Hub in new member accounts when they join the organization.

If set to `true`, then Security Hub is automatically enabled in new accounts. If set to `false`, then Security Hub isn't enabled in new accounts automatically. The default value is `false`.

If the `ConfigurationType` of your organization is set to `CENTRAL`, then this field is set to `false` and can't be changed in the home Region and linked Regions. However, in that case, the delegated administrator can create a configuration policy in which Security Hub is enabled and associate the policy with new organization accounts.

Type: Boolean

Required: Yes

AutoEnableStandards

Whether to automatically enable Security Hub [default standards](#) in new member accounts when they join the organization.

The default value of this parameter is equal to DEFAULT.

If equal to DEFAULT, then Security Hub default standards are automatically enabled for new member accounts. If equal to NONE, then default standards are not automatically enabled for new member accounts.

If the `ConfigurationType` of your organization is set to CENTRAL, then this field is set to NONE and can't be changed in the home Region and linked Regions. However, in that case, the delegated administrator can create a configuration policy in which specific security standards are enabled and associate the policy with new organization accounts.

Type: String

Valid Values: NONE | DEFAULT

Required: No

OrganizationConfiguration

Provides information about the way an organization is configured in Amazon Security Hub.

Type: [OrganizationConfiguration](#) object

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceConflictException

The resource specified in the request conflicts with an existing resource.

HTTP Status Code: 409

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateSecurityControl

Updates the properties of a security control.

Request Syntax

```
PATCH /securityControl/update HTTP/1.1
Content-type: application/json
```

```
{
  "LastUpdateReason": "string",
  "Parameters": {
    "string" : {
      "Value": { ... },
      "ValueType": "string"
    }
  },
  "SecurityControlId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

LastUpdateReason

The most recent reason for updating the properties of the security control. This field accepts alphanumeric characters in addition to white spaces, dashes, and underscores.

Type: String

Pattern: `^[^\u0000-\u007F]|[-_ a-zA-Z0-9])+$`

Required: No

Parameters

An object that specifies which security control parameters to update.

Type: String to [ParameterConfiguration](#) object map

Key Pattern: .*\\S.*

Required: Yes

SecurityControlId

The Amazon Resource Name (ARN) or ID of the control to update.

Type: String

Pattern: .*\\S.*

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceInUseException

The request was rejected because it conflicts with the resource's availability. For example, you tried to update a security control that's currently in the UPDATING state.

HTTP Status Code: 400

ResourceInUseException

The request was rejected because it conflicts with the resource's availability. For example, you tried to update a security control that's currently in the UPDATING state.

HTTP Status Code: 400

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateSecurityHubConfiguration

Updates configuration options for Security Hub.

Request Syntax

```
PATCH /accounts HTTP/1.1
Content-type: application/json

{
  "AutoEnableControls": boolean,
  "ControlFindingGenerator": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AutoEnableControls

Whether to automatically enable new controls when they are added to standards that are enabled.

By default, this is set to `true`, and new controls are enabled automatically. To not automatically enable new controls, set this to `false`.

When you automatically enable new controls, you can interact with the controls in the console and programmatically immediately after release. However, automatically enabled controls have a temporary default status of `DISABLED`. It can take up to several days for Security Hub to process the control release and designate the control as `ENABLED` in your account. During the processing period, you can manually enable or disable a control, and Security Hub will maintain that designation regardless of whether you have `AutoEnableControls` set to `true`.

Type: Boolean

Required: No

ControlFindingGenerator

Updates whether the calling account has consolidated control findings turned on. If the value for this field is set to `SECURITY_CONTROL`, Security Hub generates a single finding for a control check even when the check applies to multiple enabled standards.

If the value for this field is set to `STANDARD_CONTROL`, Security Hub generates separate findings for a control check when the check applies to multiple enabled standards.

For accounts that are part of an organization, this value can only be updated in the administrator account.

Type: String

Valid Values: `STANDARD_CONTROL` | `SECURITY_CONTROL`

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current Amazon account or throttling limits. The error code describes the limit exceeded.

HTTP Status Code: 429

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

UpdateStandardsControl

Used to control whether an individual security standard control is enabled or disabled.

Calls to this operation return a `RESOURCE_NOT_FOUND_EXCEPTION` error when the standard subscription for the control has `StandardsControlsUpdatable` value `NOT_READY_FOR_UPDATES`.

Request Syntax

```
PATCH /standards/control/StandardsControlArn+ HTTP/1.1
Content-type: application/json

{
  "ControlStatus": "string",
  "DisabledReason": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

StandardsControlArn

The ARN of the security standard control to enable or disable.

Pattern: `.*\S.*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

ControlStatus

The updated status of the security standard control.

Type: String

Valid Values: `ENABLED` | `DISABLED`

Required: No

DisabledReason

A description of the reason why you are disabling a security standard control. If you are disabling a control, then this is required.

Type: String

Pattern: .*\\S.*

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action specified in the request.

HTTP Status Code: 403

InternalException

Internal server error.

HTTP Status Code: 500

InvalidAccessException

The account doesn't have permission to perform this action.

HTTP Status Code: 401

InvalidInputException

The request was rejected because you supplied an invalid or out-of-range value for an input parameter.

HTTP Status Code: 400

ResourceNotFoundException

The request was rejected because we can't find the specified resource.

HTTP Status Code: 404

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

Data Types

The Amazon Security Hub API contains several data types that the various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

Security Hub supports the following primary data types:

- [AccountDetails](#)
- [Action](#)
- [ActionLocalIpDetails](#)
- [ActionLocalPortDetails](#)
- [ActionRemoteIpDetails](#)
- [ActionRemotePortDetails](#)
- [ActionTarget](#)
- [Actor](#)
- [ActorSession](#)
- [ActorUser](#)
- [Adjustment](#)
- [AdminAccount](#)
- [AssociatedStandard](#)
- [AssociationFilters](#)
- [AutomationRulesAction](#)
- [AutomationRulesConfig](#)
- [AutomationRulesFindingFieldsUpdate](#)
- [AutomationRulesFindingFilters](#)
- [AutomationRulesMetadata](#)

- [AwsApiCallAction](#)
- [AwsApiCallActionDomainDetails](#)
- [BatchUpdateFindingsUnprocessedFinding](#)
- [BooleanConfigurationOptions](#)
- [BooleanFilter](#)
- [Cell](#)
- [City](#)
- [ClassificationResult](#)
- [ClassificationStatus](#)
- [CodeVulnerabilitiesFilePath](#)
- [Compliance](#)
- [ConfigurationOptions](#)
- [ConfigurationPolicyAssociation](#)
- [ConfigurationPolicyAssociationSummary](#)
- [ConfigurationPolicySummary](#)
- [Country](#)
- [CustomDataIdentifiersDetections](#)
- [CustomDataIdentifiersResult](#)
- [Cvss](#)
- [DataClassificationDetails](#)
- [DateFilter](#)
- [DateRange](#)
- [Detection](#)
- [DnsRequestAction](#)
- [DoubleConfigurationOptions](#)
- [EnumConfigurationOptions](#)
- [EnumListConfigurationOptions](#)
- [FilePaths](#)
- [FindingAggregator](#)
- [FindingHistoryRecord](#)

- [FindingHistoryUpdate](#)
- [FindingHistoryUpdateSource](#)
- [FindingProviderFields](#)
- [FindingProviderSeverity](#)
- [GeneratorDetails](#)
- [GeoLocation](#)
- [IcmpTypeCode](#)
- [ImportFindingsError](#)
- [Indicator](#)
- [Insight](#)
- [InsightResults](#)
- [InsightResultValue](#)
- [IntegerConfigurationOptions](#)
- [IntegerListConfigurationOptions](#)
- [Invitation](#)
- [IpFilter](#)
- [IpOrganizationDetails](#)
- [KeywordFilter](#)
- [Malware](#)
- [MapFilter](#)
- [Member](#)
- [Network](#)
- [NetworkAutonomousSystem](#)
- [NetworkConnection](#)
- [NetworkConnectionAction](#)
- [NetworkEndpoint](#)
- [NetworkGeoLocation](#)
- [NetworkPathComponent](#)
- [NetworkPathComponentDetails](#)
- [Note](#)

- [NoteUpdate](#)
- [NumberFilter](#)
- [Occurrences](#)
- [OrganizationConfiguration](#)
- [Page](#)
- [ParameterConfiguration](#)
- [ParameterDefinition](#)
- [ParameterValue](#)
- [PatchSummary](#)
- [Policy](#)
- [PortProbeAction](#)
- [PortProbeDetail](#)
- [ProcessDetails](#)
- [Product](#)
- [Range](#)
- [Recommendation](#)
- [Record](#)
- [RelatedFinding](#)
- [Remediation](#)
- [Resource](#)
- [ResourceDetails](#)
- [Result](#)
- [SecurityControl](#)
- [SecurityControlCustomParameter](#)
- [SecurityControlDefinition](#)
- [SecurityControlParameter](#)
- [SecurityControlsConfiguration](#)
- [SecurityHubPolicy](#)
- [SensitiveDataDetections](#)
- [SensitiveDataResult](#)

- [Sequence](#)
- [Severity](#)
- [SeverityUpdate](#)
- [Signal](#)
- [SoftwarePackage](#)
- [SortCriterion](#)
- [Standard](#)
- [StandardsControl](#)
- [StandardsControlAssociationDetail](#)
- [StandardsControlAssociationId](#)
- [StandardsControlAssociationSummary](#)
- [StandardsControlAssociationUpdate](#)
- [StandardsManagedBy](#)
- [StandardsStatusReason](#)
- [StandardsSubscription](#)
- [StandardsSubscriptionRequest](#)
- [StatusReason](#)
- [StringConfigurationOptions](#)
- [StringFilter](#)
- [StringListConfigurationOptions](#)
- [Target](#)
- [Threat](#)
- [ThreatIntelIndicator](#)
- [UnprocessedAutomationRule](#)
- [UnprocessedConfigurationPolicyAssociation](#)
- [UnprocessedSecurityControl](#)
- [UnprocessedStandardsControlAssociation](#)
- [UnprocessedStandardsControlAssociationUpdate](#)
- [UpdateAutomationRulesRequestItem](#)
- [UserAccount](#)

- [Vulnerability](#)
- [VulnerabilityCodeVulnerabilities](#)
- [VulnerabilityVendor](#)
- [Workflow](#)
- [WorkflowUpdate](#)

Security Hub supports the following objects as part of the `ResourceDetails` data type. These objects apply to Security Hub findings in the Amazon Security Finding Format (ASFF).

Amazon MQ objects

- [AwsAmazonMqBrokerDetails](#)
- [AwsAmazonMqBrokerEncryptionOptionsDetails](#)
- [AwsAmazonMqBrokerLdapServerMetadataDetails](#)
- [AwsAmazonMqBrokerLogsDetails](#)
- [AwsAmazonMqBrokerLogsPendingDetails](#)
- [AwsAmazonMqBrokerMaintenanceWindowStartTimeDetails](#)
- [AwsAmazonMqBrokerUsersDetails](#)

Amazon API Gateway objects

- [AwsApiGatewayAccessLogSettings](#)
- [AwsApiGatewayCanarySettings](#)
- [AwsApiGatewayEndpointConfiguration](#)
- [AwsApiGatewayMethodSettings](#)
- [AwsApiGatewayRestApiDetails](#)
- [AwsApiGatewayStageDetails](#)
- [AwsApiGatewayV2ApiDetails](#)
- [AwsApiGatewayV2RouteSettings](#)
- [AwsApiGatewayV2StageDetails](#)
- [AwsCorsConfiguration](#)

Amazon AppSync objects

- [AwsAppSyncGraphQLApiDetails](#)
- [AwsAppSyncGraphQLApiAdditionalAuthenticationProvidersDetails](#)
- [AwsAppSyncGraphQLApiLambdaAuthorizerConfigDetails](#)
- [AwsAppSyncGraphQLApiLogConfigDetails](#)
- [AwsAppSyncGraphQLApiOpenIdConnectConfigDetails](#)
- [AwsAppSyncGraphQLApiUserPoolConfigDetails](#)

Amazon Athena objects

- [AwsAthenaWorkGroupConfigurationDetails](#)
- [AwsAthenaWorkGroupConfigurationResultConfigurationDetails](#)
- [AwsAthenaWorkGroupConfigurationResultConfigurationEncryptionConfigurationDetails](#)

Amazon Backup objects

- [AwsBackupBackupPlanAdvancedBackupSettingsDetails](#)
- [AwsBackupBackupPlanBackupPlanDetails](#)
- [AwsBackupBackupPlanDetails](#)
- [AwsBackupBackupPlanLifecycleDetails](#)
- [AwsBackupBackupPlanRuleCopyActionsDetails](#)
- [AwsBackupBackupPlanRuleDetails](#)
- [AwsBackupBackupVaultDetails](#)
- [AwsBackupBackupVaultNotificationsDetails](#)
- [AwsBackupRecoveryPointCalculatedLifecycleDetails](#)
- [AwsBackupRecoveryPointCreatedByDetails](#)
- [AwsBackupRecoveryPointDetails](#)
- [AwsBackupRecoveryPointLifecycleDetails](#)

Amazon Certificate Manager objects

- [AwsCertificateManagerCertificateDetails](#)
- [AwsCertificateManagerCertificateDomainValidationOption](#)

- [AwsCertificateManagerCertificateExtendedKeyUsage](#)
- [AwsCertificateManagerCertificateKeyUsage](#)
- [AwsCertificateManagerCertificateOptions](#)
- [AwsCertificateManagerCertificateRenewalSummary](#)
- [AwsCertificateManagerCertificateResourceRecord](#)

Amazon CloudFormation objects

- [AwsCloudFormationStackDetails](#)
- [AwsCloudFormationStackDriftInformationDetails](#)
- [AwsCloudFormationStackOutputsDetails](#)

Amazon CloudFront objects

- [AwsCloudFrontDistributionCacheBehavior](#)
- [AwsCloudFrontDistributionCacheBehaviors](#)
- [AwsCloudFrontDistributionDefaultCacheBehavior](#)
- [AwsCloudFrontDistributionDetails](#)
- [AwsCloudFrontDistributionLogging](#)
- [AwsCloudFrontDistributionOriginCustomOriginConfig](#)
- [AwsCloudFrontDistributionOriginGroup](#)
- [AwsCloudFrontDistributionOriginGroupFailover](#)
- [AwsCloudFrontDistributionOriginGroupFailoverStatusCodes](#)
- [AwsCloudFrontDistributionOriginGroups](#)
- [AwsCloudFrontDistributionOriginItem](#)
- [AwsCloudFrontDistributionOrigins](#)
- [AwsCloudFrontDistributionOriginS3OriginConfig](#)
- [AwsCloudFrontDistributionOriginSslProtocols](#)
- [AwsCloudFrontDistributionViewerCertificate](#)

Amazon CloudTrail objects

- [AwsCloudTrailTrailDetails](#)

Amazon CloudWatch objects

- [AwsCloudWatchAlarmDetails](#)
- [AwsCloudWatchAlarmDimensionsDetails](#)

Amazon CodeBuild objects

- [AwsCodeBuildProjectArtifactsDetails](#)
- [AwsCodeBuildProjectDetails](#)
- [AwsCodeBuildProjectEnvironment](#)
- [AwsCodeBuildProjectEnvironmentEnvironmentVariablesDetails](#)
- [AwsCodeBuildProjectEnvironmentRegistryCredential](#)
- [AwsCodeBuildProjectLogsConfigCloudWatchLogsDetails](#)
- [AwsCodeBuildProjectLogsConfigDetails](#)
- [AwsCodeBuildProjectLogsConfigS3LogsDetails](#)
- [AwsCodeBuildProjectSource](#)
- [AwsCodeBuildProjectVpcConfig](#)

Amazon Database Migration Service objects (Amazon DMS)

- [AwsDmsEndpointDetails](#)
- [AwsDmsReplicationInstanceDetails](#)
- [AwsDmsReplicationInstanceReplicationSubnetGroupDetails](#)
- [AwsDmsReplicationInstanceVpcSecurityGroupsDetails](#)
- [AwsDmsReplicationTaskDetails](#)

Amazon DynamoDB objects

- [AwsDynamoDbTableAttributeDefinition](#)
- [AwsDynamoDbTableBillingModeSummary](#)
- [AwsDynamoDbTableDetails](#)

- [AwsDynamoDbTableGlobalSecondaryIndex](#)
- [AwsDynamoDbTableKeySchema](#)
- [AwsDynamoDbTableLocalSecondaryIndex](#)
- [AwsDynamoDbTableProjection](#)
- [AwsDynamoDbTableProvisionedThroughput](#)
- [AwsDynamoDbTableProvisionedThroughputOverride](#)
- [AwsDynamoDbTableReplica](#)
- [AwsDynamoDbTableReplicaGlobalSecondaryIndex](#)
- [AwsDynamoDbTableRestoreSummary](#)
- [AwsDynamoDbTableSseDescription](#)
- [AwsDynamoDbTableStreamSpecification](#)

Amazon Elastic Compute Cloud (EC2) objects

- [AwsEc2ClientVpnEndpointAuthenticationOptionsActiveDirectoryDetails](#)
- [AwsEc2ClientVpnEndpointAuthenticationOptionsDetails](#)
- [AwsEc2ClientVpnEndpointAuthenticationOptionsFederatedAuthenticationDetails](#)
- [AwsEc2ClientVpnEndpointAuthenticationOptionsMutualAuthenticationDetails](#)
- [AwsEc2ClientVpnEndpointClientConnectOptionsDetails](#)
- [AwsEc2ClientVpnEndpointClientConnectOptionsStatusDetails](#)
- [AwsEc2ClientVpnEndpointClientLoginBannerOptionsDetails](#)
- [AwsEc2ClientVpnEndpointConnectionLogOptionsDetails](#)
- [AwsEc2ClientVpnEndpointDetails](#)
- [AwsEc2EipDetails](#)
- [AwsEc2InstanceDetails](#)
- [AwsEc2InstanceMetadataOptions](#)
- [AwsEc2InstanceMonitoringDetails](#)
- [AwsEc2InstanceNetworkInterfacesDetails](#)
- [AwsEc2LaunchTemplateDataBlockDeviceMappingSetDetails](#)
- [AwsEc2LaunchTemplateDataBlockDeviceMappingSetEbsDetails](#)
- [AwsEc2LaunchTemplateDataCapacityReservationSpecificationCapacityReservationTargetDetails](#)

- [AwsEc2LaunchTemplateDataCapacityReservationSpecificationDetails](#)
- [AwsEc2LaunchTemplateDataCpuOptionsDetails](#)
- [AwsEc2LaunchTemplateDataCreditSpecificationDetails](#)
- [AwsEc2LaunchTemplateDataDetails](#)
- [AwsEc2LaunchTemplateDataElasticGpuSpecificationSetDetails](#)
- [AwsEc2LaunchTemplateDataElasticInferenceAcceleratorSetDetails](#)
- [AwsEc2LaunchTemplateDataEnclaveOptionsDetails](#)
- [AwsEc2LaunchTemplateDataHibernationOptionsDetails](#)
- [AwsEc2LaunchTemplateDataIamInstanceProfileDetails](#)
- [AwsEc2LaunchTemplateDataInstanceMarketOptionsDetails](#)
- [AwsEc2LaunchTemplateDataInstanceMarketOptionsSpotOptionsDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsAcceleratorCountDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsAcceleratorTotalMemoryMiBDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsBaselineEbsBandwidthMbpsDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsMemoryGiBPerVCpuDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsMemoryMiBDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsNetworkInterfaceCountDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsTotalLocalStorageGBDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsVCpuCountDetails](#)
- [AwsEc2LaunchTemplateDataLicenseSetDetails](#)
- [AwsEc2LaunchTemplateDataMaintenanceOptionsDetails](#)
- [AwsEc2LaunchTemplateDataMetadataOptionsDetails](#)
- [AwsEc2LaunchTemplateDataMonitoringDetails](#)
- [AwsEc2LaunchTemplateDataNetworkInterfaceSetDetails](#)
- [AwsEc2LaunchTemplateDataNetworkInterfaceSetIpv4PrefixesDetails](#)
- [AwsEc2LaunchTemplateDataNetworkInterfaceSetIpv6AddressesDetails](#)
- [AwsEc2LaunchTemplateDataNetworkInterfaceSetIpv6PrefixesDetails](#)
- [AwsEc2LaunchTemplateDataNetworkInterfaceSetPrivateIpAddressesDetails](#)
- [AwsEc2LaunchTemplateDataPlacementDetails](#)

- [AwsEc2LaunchTemplateDataPrivateDnsNameOptionsDetails](#)
- [AwsEc2LaunchTemplateDetails](#)
- [AwsEc2NetworkAclAssociation](#)
- [AwsEc2NetworkAclDetails](#)
- [AwsEc2NetworkAclEntry](#)
- [PortRange](#)
- [PortRangeFromTo](#)
- [AwsEc2NetworkInterfaceAttachment](#)
- [AwsEc2NetworkInterfaceDetails](#)
- [AwsEc2NetworkInterfaceIpv6AddressDetail](#)
- [AwsEc2NetworkInterfacePrivateIpvAddressDetail](#)
- [AwsEc2NetworkInterfaceSecurityGroup](#)
- [AwsEc2RouteTableDetails](#)
- [RouteSetDetails](#)
- [AssociationSetDetails](#)
- [AssociationStateDetails](#)
- [PropagatingVgwSetDetails](#)
- [AwsEc2SecurityGroupDetails](#)
- [AwsEc2SecurityGroupIpPermission](#)
- [AwsEc2SecurityGroupIpRange](#)
- [AwsEc2SecurityGroupIpv6Range](#)
- [AwsEc2SecurityGroupPrefixListId](#)
- [AwsEc2SecurityGroupUserIdGroupPair](#)
- [AwsEc2SubnetDetails](#)
- [Ipv6CidrBlockAssociation](#)
- [AvailabilityZone](#)
- [AwsEc2TransitGatewayDetails](#)
- [AwsEc2VolumeAttachment](#)
- [AwsEc2VolumeDetails](#)
- [AwsEc2VpcDetails](#)

- [CidrBlockAssociation](#)
- [AwsEc2VpcEndpointServiceDetails](#)
- [AwsEc2VpcEndpointServiceServiceTypeDetails](#)
- [AwsEc2VpcPeeringConnectionDetails](#)
- [VpcInfoCidrBlockSetDetails](#)
- [VpcInfoIpv6CidrBlockSetDetails](#)
- [VpcInfoPeeringOptionsDetails](#)
- [AwsEc2VpcPeeringConnectionStatusDetails](#)
- [AwsEc2VpcPeeringConnectionVpcInfoDetails](#)
- [AwsEc2VpnConnectionDetails](#)
- [AwsEc2VpnConnectionOptionsDetails](#)
- [AwsEc2VpnConnectionOptionsTunnelOptionsDetails](#)
- [AwsEc2VpnConnectionRoutesDetails](#)
- [AwsEc2VpnConnectionVgwTelemetryDetails](#)

Amazon EC2 Auto Scaling objects

- [AwsAutoScalingAutoScalingGroupAvailabilityZonesListDetails](#)
- [AwsAutoScalingAutoScalingGroupDetails](#)
- [AwsAutoScalingAutoScalingGroupLaunchTemplateLaunchTemplateSpecification](#)
- [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyDetails](#)
- [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyInstancesDistributionDetails](#)
- [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyLaunchTemplateDetails](#)
- [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyLaunchTemplateLaunchTemplateSpecification](#)
- [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyLaunchTemplateOverridesListDetails](#)
- [AwsAutoScalingLaunchConfigurationBlockDeviceMappingsDetails](#)
- [AwsAutoScalingLaunchConfigurationBlockDeviceMappingsEbsDetails](#)
- [AwsAutoScalingLaunchConfigurationDetails](#)
- [AwsAutoScalingLaunchConfigurationInstanceMonitoringDetails](#)
- [AwsAutoScalingLaunchConfigurationMetadataOptions](#)

Amazon Elastic Container Registry (ECR) objects

- [AwsEcrContainerImageDetails](#)
- [AwsEcrRepositoryDetails](#)
- [AwsEcrRepositoryImageScanningConfigurationDetails](#)
- [AwsEcrRepositoryLifecyclePolicyDetails](#)

Amazon Elastic Container Service (ECS) objects

- [AwsEcsClusterClusterSettingsDetails](#)
- [AwsEcsClusterConfigurationDetails](#)
- [AwsEcsClusterConfigurationExecuteCommandConfigurationDetails](#)
- [AwsEcsClusterConfigurationExecuteCommandConfigurationLogConfigurationDetails](#)
- [AwsEcsClusterDefaultCapacityProviderStrategyDetails](#)
- [AwsEcsClusterDetails](#)
- [AwsEcsContainerDetails](#)
- [AwsEcsServiceCapacityProviderStrategyDetails](#)
- [AwsEcsServiceDeploymentConfigurationDeploymentCircuitBreakerDetails](#)
- [AwsEcsServiceDeploymentConfigurationDetails](#)
- [AwsEcsServiceDeploymentControllerDetails](#)
- [AwsEcsServiceDetails](#)
- [AwsEcsServiceLoadBalancersDetails](#)
- [AwsEcsServiceNetworkConfigurationAwsVpcConfigurationDetails](#)
- [AwsEcsServiceNetworkConfigurationDetails](#)
- [AwsEcsServicePlacementConstraintsDetails](#)
- [AwsEcsServicePlacementStrategiesDetails](#)
- [AwsEcsServiceServiceRegistriesDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsDependsOnDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsEnvironmentDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsEnvironmentFilesDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsExtraHostsDetails](#)

- [AwsEcsTaskDefinitionContainerDefinitionsFirelensConfigurationDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsHealthCheckDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersCapabilitiesDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersDevicesDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersTmpfsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLogConfigurationDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLogConfigurationSecretOptionsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsMountPointsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsPortMappingsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsRepositoryCredentialsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsResourceRequirementsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsSecretsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsSystemControlsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsUlimitsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsVolumesFromDetails](#)
- [AwsEcsTaskDefinitionDetails](#)
- [AwsEcsTaskDefinitionInferenceAcceleratorsDetails](#)
- [AwsEcsTaskDefinitionPlacementConstraintsDetails](#)
- [AwsEcsTaskDefinitionProxyConfigurationDetails](#)
- [AwsEcsTaskDefinitionProxyConfigurationProxyConfigurationPropertiesDetails](#)
- [AwsEcsTaskDefinitionVolumesDetails](#)
- [AwsEcsTaskDefinitionVolumesDockerVolumeConfigurationDetails](#)
- [AwsEcsTaskDefinitionVolumesEfsVolumeConfigurationAuthorizationConfigDetails](#)
- [AwsEcsTaskDefinitionVolumesEfsVolumeConfigurationDetails](#)
- [AwsEcsTaskDefinitionVolumesHostDetails](#)
- [AwsEcsTaskDetails](#)
- [AwsEcsTaskVolumeDetails](#)
- [AwsEcsTaskVolumeHostDetails](#)
- [AwsMountPoint](#)

Amazon Elastic File System (EFS) objects

- [AwsEfsAccessPointDetails](#)
- [AwsEfsAccessPointPosixUserDetails](#)
- [AwsEfsAccessPointRootDirectoryCreationInfoDetails](#)
- [AwsEfsAccessPointRootDirectoryDetails](#)

Amazon Elastic Kubernetes Service (EKS) objects

- [AwsEksClusterDetails](#)
- [AwsEksClusterLoggingClusterLoggingDetails](#)
- [AwsEksClusterLoggingDetails](#)
- [AwsEksClusterResourcesVpcConfigDetails](#)

Amazon Elastic Beanstalk objects

- [AwsElasticBeanstalkEnvironmentDetails](#)
- [AwsElasticBeanstalkEnvironmentEnvironmentLink](#)
- [AwsElasticBeanstalkEnvironmentOptionSetting](#)
- [AwsElasticBeanstalkEnvironmentTier](#)

Elasticsearch objects

- [AwsElasticsearchDomainDetails](#)
- [AwsElasticsearchDomainDomainEndpointOptions](#)
- [AwsElasticsearchDomainElasticsearchClusterConfigDetails](#)
- [AwsElasticsearchDomainElasticsearchClusterConfigZoneAwarenessConfigDetails](#)
- [AwsElasticsearchDomainEncryptionAtRestOptions](#)
- [AwsElasticsearchDomainLogPublishingOptions](#)
- [AwsElasticsearchDomainLogPublishingOptionsLogConfig](#)
- [AwsElasticsearchDomainNodeToNodeEncryptionOptions](#)
- [AwsElasticsearchDomainServiceSoftwareOptions](#)
- [AwsElasticsearchDomainVPCOptions](#)

Elastic Load Balancing objects

- [AwsElbAppCookieStickinessPolicy](#)
- [AwsElbLbCookieStickinessPolicy](#)
- [AwsElbLoadBalancerAccessLog](#)
- [AwsElbLoadBalancerAdditionalAttribute](#)
- [AwsElbLoadBalancerAttributes](#)
- [AwsElbLoadBalancerBackendServerDescription](#)
- [AwsElbLoadBalancerConnectionDraining](#)
- [AwsElbLoadBalancerConnectionSettings](#)
- [AwsElbLoadBalancerCrossZoneLoadBalancing](#)
- [AwsElbLoadBalancerDetails](#)
- [AwsElbLoadBalancerHealthCheck](#)
- [AwsElbLoadBalancerInstance](#)
- [AwsElbLoadBalancerListener](#)
- [AwsElbLoadBalancerListenerDescription](#)
- [AwsElbLoadBalancerPolicies](#)
- [AwsElbLoadBalancerSourceSecurityGroup](#)
- [AwsElbv2LoadBalancerAttribute](#)
- [AwsElbv2LoadBalancerDetails](#)
- [LoadBalancerState](#)

Amazon EventBridge objects

- [AwsEventSchemasRegistryDetails](#)
- [AwsEventsEndpointDetails](#)
- [AwsEventsEndpointEventBusesDetails](#)
- [AwsEventsEndpointReplicationConfigDetails](#)
- [AwsEventsEndpointRoutingConfigDetails](#)
- [AwsEventsEndpointRoutingConfigFailoverConfigDetails](#)
- [AwsEventsEndpointRoutingConfigFailoverConfigPrimaryDetails](#)
- [AwsEventsEndpointRoutingConfigFailoverConfigSecondaryDetails](#)

- [AwsEventsEventbusDetails](#)

Amazon GuardDuty objects

- [AwsGuardDutyDetectorDataSourcesCloudTrailDetails](#)
- [AwsGuardDutyDetectorDataSourcesDetails](#)
- [AwsGuardDutyDetectorDataSourcesDnsLogsDetails](#)
- [AwsGuardDutyDetectorDataSourcesFlowLogsDetails](#)
- [AwsGuardDutyDetectorDataSourcesKubernetesAuditLogsDetails](#)
- [AwsGuardDutyDetectorDataSourcesKubernetesDetails](#)
- [AwsGuardDutyDetectorDataSourcesMalwareProtectionDetails](#)
- [AwsGuardDutyDetectorDataSourcesMalwareProtectionScanEc2InstanceWithFindingsDetails](#)
- [AwsGuardDutyDetectorDataSourcesMalwareProtectionScanEc2InstanceWithFindingsEbsVolumesDetails](#)
- [AwsGuardDutyDetectorDataSourcesS3LogsDetails](#)
- [AwsGuardDutyDetectorDetails](#)
- [AwsGuardDutyDetectorFeaturesDetails](#)

Amazon Identity and Access Management (IAM) objects

- [AwsIamAccessKeyDetails](#)
- [AwsIamAccessKeySessionContext](#)
- [AwsIamAccessKeySessionContextAttributes](#)
- [AwsIamAccessKeySessionContextSessionIssuer](#)
- [AwsIamAttachedManagedPolicy](#)
- [AwsIamGroupDetails](#)
- [AwsIamGroupPolicy](#)
- [AwsIamInstanceProfile](#)
- [AwsIamInstanceProfileRole](#)
- [AwsIamPermissionsBoundary](#)
- [AwsIamPolicyDetails](#)
- [AwsIamPolicyVersion](#)
- [AwsIamRoleDetails](#)

- [AwsIamRolePolicy](#)
- [AwsIamUserDetails](#)
- [AwsIamUserPolicy](#)

Amazon Kinesis objects

- [AwsKinesisStreamDetails](#)
- [AwsKinesisStreamStreamEncryptionDetails](#)

Amazon Key Management Service (Amazon KMS) objects

- [AwsKmsKeyDetails](#)

Amazon Lambda objects

- [AwsLambdaFunctionCode](#)
- [AwsLambdaFunctionDeadLetterConfig](#)
- [AwsLambdaFunctionDetails](#)
- [AwsLambdaFunctionEnvironment](#)
- [AwsLambdaFunctionEnvironmentError](#)
- [AwsLambdaFunctionLayer](#)
- [AwsLambdaFunctionTracingConfig](#)
- [AwsLambdaFunctionVpcConfig](#)
- [AwsLambdaLayerVersionDetails](#)

Amazon Managed Streaming for Apache Kafka (Amazon MSK) objects

- [AwsMskClusterDetails](#)
- [AwsMskClusterClusterInfoClientAuthenticationDetails](#)
- [AwsMskClusterClusterInfoClientAuthenticationSaslDetails](#)
- [AwsMskClusterClusterInfoClientAuthenticationSaslIamDetails](#)
- [AwsMskClusterClusterInfoClientAuthenticationSaslScramDetails](#)
- [AwsMskClusterClusterInfoClientAuthenticationTlsDetails](#)

- [AwsMskClusterClusterInfoClientAuthenticationUnauthenticatedDetails](#)
- [AwsMskClusterClusterInfoDetails](#)
- [AwsMskClusterClusterInfoEncryptionInfoDetails](#)
- [AwsMskClusterClusterInfoEncryptionInfoEncryptionAtRestDetails](#)
- [AwsMskClusterClusterInfoEncryptionInfoEncryptionInTransitDetails](#)

Amazon Network Firewall objects

- [AwsNetworkFirewallFirewallDetails](#)
- [AwsNetworkFirewallFirewallPolicyDetails](#)
- [FirewallPolicyDetails](#)
- [FirewallPolicyStatelessCustomActionsDetails](#)
- [StatelessCustomActionDefinition](#)
- [StatelessCustomPublishMetricAction](#)
- [StatelessCustomPublishMetricActionDimension](#)
- [AwsNetworkFirewallFirewallSubnetMappingsDetails](#)
- [AwsNetworkFirewallRuleGroupDetails](#)
- [RuleGroupDetails](#)
- [RuleGroupSource](#)
- [RuleGroupSourceCustomActionsDetails](#)
- [RuleGroupSourceListDetails](#)
- [RuleGroupSourceStatefulRulesDetails](#)
- [RuleGroupSourceStatefulRulesHeaderDetails](#)
- [RuleGroupSourceStatefulRulesOptionsDetails](#)
- [RuleGroupSourceStatelessRuleDefinition](#)
- [RuleGroupSourceStatelessRuleMatchAttributes](#)
- [RuleGroupSourceStatelessRuleMatchAttributesDestinationPorts](#)
- [RuleGroupSourceStatelessRuleMatchAttributesDestinations](#)
- [RuleGroupSourceStatelessRuleMatchAttributesSourcePorts](#)
- [RuleGroupSourceStatelessRuleMatchAttributesSources](#)
- [RuleGroupSourceStatelessRuleMatchAttributesTcpFlags](#)

- [RuleGroupSourceStatelessRulesAndCustomActionsDetails](#)
- [RuleGroupSourceStatelessRulesDetails](#)
- [RuleGroupVariables](#)
- [RuleGroupVariablesIpSetsDetails](#)
- [RuleGroupVariablesPortSetsDetails](#)
- [NetworkHeader](#)
- [FirewallPolicyStatefulRuleGroupReferencesDetails](#)
- [FirewallPolicyStatelessRuleGroupReferencesDetails](#)

Amazon OpenSearch Service objects

- [AwsOpenSearchServiceDomainAdvancedSecurityOptionsDetails](#)
- [AwsOpenSearchServiceDomainClusterConfigDetails](#)
- [AwsOpenSearchServiceDomainClusterConfigZoneAwarenessConfigDetails](#)
- [AwsOpenSearchServiceDomainDetails](#)
- [AwsOpenSearchServiceDomainDomainEndpointOptionsDetails](#)
- [AwsOpenSearchServiceDomainEncryptionAtRestOptionsDetails](#)
- [AwsOpenSearchServiceDomainLogPublishingOption](#)
- [AwsOpenSearchServiceDomainLogPublishingOptionsDetails](#)
- [AwsOpenSearchServiceDomainMasterUserOptionsDetails](#)
- [AwsOpenSearchServiceDomainNodeToNodeEncryptionOptionsDetails](#)
- [AwsOpenSearchServiceDomainServiceSoftwareOptionsDetails](#)
- [AwsOpenSearchServiceDomainVpcOptionsDetails](#)

Amazon Relational Database Service (RDS) objects

- [AwsRdsDbClusterAssociatedRole](#)
- [AwsRdsDbClusterDetails](#)
- [AwsRdsDbClusterMember](#)
- [AwsRdsDbClusterOptionGroupMembership](#)
- [AwsRdsDbClusterSnapshotDbClusterSnapshotAttribute](#)
- [AwsRdsDbClusterSnapshotDetails](#)

- [AwsRdsDbDomainMembership](#)
- [AwsRdsDbInstanceAssociatedRole](#)
- [AwsRdsDbInstanceDetails](#)
- [AwsRdsDbInstanceEndpoint](#)
- [AwsRdsDbInstanceVpcSecurityGroup](#)
- [AwsRdsDbOptionGroupMembership](#)
- [AwsRdsDbParameterGroup](#)
- [AwsRdsDbPendingModifiedValues](#)
- [AwsRdsDbProcessorFeature](#)
- [AwsRdsDbSecurityGroupDetails](#)
- [AwsRdsDbSecurityGroupEc2SecurityGroup](#)
- [AwsRdsDbSecurityGroupIpRange](#)
- [AwsRdsDbSnapshotDetails](#)
- [AwsRdsDbStatusInfo](#)
- [AwsRdsDbSubnetGroup](#)
- [AwsRdsDbSubnetGroupSubnet](#)
- [AwsRdsDbSubnetGroupSubnetAvailabilityZone](#)
- [AwsRdsEventSubscriptionDetails](#)
- [AwsRdsPendingCloudWatchLogsExports](#)

Amazon Redshift objects

- [AwsRedshiftClusterClusterNode](#)
- [AwsRedshiftClusterClusterParameterGroup](#)
- [AwsRedshiftClusterClusterParameterStatus](#)
- [AwsRedshiftClusterClusterSecurityGroup](#)
- [AwsRedshiftClusterClusterSnapshotCopyStatus](#)
- [AwsRedshiftClusterDeferredMaintenanceWindow](#)
- [AwsRedshiftClusterDetails](#)
- [AwsRedshiftClusterElasticIpStatus](#)
- [AwsRedshiftClusterEndpoint](#)

- [AwsRedshiftClusterHsmStatus](#)
- [AwsRedshiftClusterIamRole](#)
- [AwsRedshiftClusterLoggingStatus](#)
- [AwsRedshiftClusterPendingModifiedValues](#)
- [AwsRedshiftClusterResizeInfo](#)
- [AwsRedshiftClusterRestoreStatus](#)
- [AwsRedshiftClusterVpcSecurityGroup](#)

Amazon Route 53 objects

- [AwsRoute53HostedZoneConfigDetails](#)
- [AwsRoute53HostedZoneDetails](#)
- [AwsRoute53HostedZoneObjectDetails](#)
- [AwsRoute53HostedZoneVpcDetails](#)
- [AwsRoute53QueryLoggingConfigDetails](#)
- [CloudWatchLogsLogGroupArnConfigDetails](#)

Amazon Simple Storage Service (S3) objects

- [AwsS3AccessPointDetails](#)
- [AwsS3AccessPointVpcConfigurationDetails](#)
- [AwsS3AccountPublicAccessBlockDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesAbortIncompleteMultipartUploadDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesFilterDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateOperandsDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateOperandsTagDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateTagDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesNoncurrentVersionTransitionsDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesTransitionsDetails](#)

- [AwsS3BucketBucketVersioningConfiguration](#)
- [AwsS3BucketDetails](#)
- [AwsS3BucketLoggingConfiguration](#)
- [AwsS3BucketNotificationConfiguration](#)
- [AwsS3BucketNotificationConfigurationDetail](#)
- [AwsS3BucketNotificationConfigurationFilter](#)
- [AwsS3BucketNotificationConfigurationS3KeyFilter](#)
- [AwsS3BucketNotificationConfigurationS3KeyFilterRule](#)
- [AwsS3BucketObjectLockConfiguration](#)
- [AwsS3BucketObjectLockConfigurationRuleDefaultRetentionDetails](#)
- [AwsS3BucketObjectLockConfigurationRuleDetails](#)
- [AwsS3BucketServerSideEncryptionByDefault](#)
- [AwsS3BucketServerSideEncryptionConfiguration](#)
- [AwsS3BucketServerSideEncryptionRule](#)
- [AwsS3BucketWebsiteConfiguration](#)
- [AwsS3BucketWebsiteConfigurationRedirectTo](#)
- [AwsS3BucketWebsiteConfigurationRoutingRule](#)
- [AwsS3BucketWebsiteConfigurationRoutingRuleCondition](#)
- [AwsS3BucketWebsiteConfigurationRoutingRuleRedirect](#)
- [AwsS3ObjectDetails](#)

Amazon SageMaker AI objects

- [AwsSageMakerNotebookInstanceDetails](#)
- [AwsSageMakerNotebookInstanceMetadataServiceConfigurationDetails](#)

Amazon Secrets Manager objects

- [AwsSecretsManagerSecretDetails](#)
- [AwsSecretsManagerSecretRotationRules](#)

Amazon Simple Notification Service (SNS) objects

- [AwsSnsTopicDetails](#)
- [AwsSnsTopicSubscription](#)

Amazon Simple Queue Service (SQS) objects

- [AwsSqsQueueDetails](#)

Amazon Systems Manager objects

- [AwsSsmComplianceSummary](#)
- [AwsSsmPatch](#)
- [AwsSsmPatchComplianceDetails](#)

Amazon Step Functions objects

- [AwsStepFunctionStateMachineDetails](#)
- [AwsStepFunctionStateMachineLoggingConfigurationDestinationsCloudWatchLogsLogGroupDetails](#)
- [AwsStepFunctionStateMachineLoggingConfigurationDestinationsDetails](#)
- [AwsStepFunctionStateMachineLoggingConfigurationDetails](#)
- [AwsStepFunctionStateMachineTracingConfigurationDetails](#)

Amazon WAF objects

- [AwsWafRateBasedRuleDetails](#)
- [AwsWafRateBasedRuleMatchPredicate](#)
- [AwsWafRegionalRateBasedRuleDetails](#)
- [AwsWafRegionalRateBasedRuleMatchPredicate](#)
- [AwsWafRegionalRuleDetails](#)
- [AwsWafRegionalRuleGroupDetails](#)
- [AwsWafRegionalRuleGroupRulesActionDetails](#)
- [AwsWafRegionalRuleGroupRulesDetails](#)
- [AwsWafRegionalRulePredicateListDetails](#)
- [AwsWafRegionalWebAclDetails](#)

- [AwsWafRegionalWebAclRulesListActionDetails](#)
- [AwsWafRegionalWebAclRulesListDetails](#)
- [AwsWafRegionalWebAclRulesListOverrideActionDetails](#)
- [AwsWafRuleDetails](#)
- [AwsWafRuleGroupDetails](#)
- [AwsWafRuleGroupRulesActionDetails](#)
- [AwsWafRuleGroupRulesDetails](#)
- [AwsWafRulePredicateListDetails](#)
- [AwsWafv2ActionAllowDetails](#)
- [AwsWafv2ActionBlockDetails](#)
- [AwsWafv2CustomHttpHeader](#)
- [AwsWafv2CustomRequestHandlingDetails](#)
- [AwsWafv2CustomResponseDetails](#)
- [AwsWafv2RuleGroupDetails](#)
- [AwsWafv2RulesActionCaptchaDetails](#)
- [AwsWafv2RulesActionCountDetails](#)
- [AwsWafv2RulesActionDetails](#)
- [AwsWafv2RulesDetails](#)
- [AwsWafv2VisibilityConfigDetails](#)
- [AwsWafv2WebAclActionDetails](#)
- [AwsWafv2WebAclCaptchaConfigDetails](#)
- [AwsWafv2WebAclCaptchaConfigImmunityTimePropertyDetails](#)
- [AwsWafv2WebAclDetails](#)
- [AwsWafWebAclDetails](#)
- [WafAction](#)
- [WafExcludedRule](#)
- [WafOverrideAction](#)
- [AwsWafWebAclRule](#)

Amazon X-Ray objects

- [AwsXrayEncryptionConfigDetails](#)

Container objects

- [ContainerDetails](#)
- [VolumeMount](#)

Primary data types

Amazon Security Hub supports the following primary data types:

- [AccountDetails](#)
- [Action](#)
- [ActionLocalIpDetails](#)
- [ActionLocalPortDetails](#)
- [ActionRemoteIpDetails](#)
- [ActionRemotePortDetails](#)
- [ActionTarget](#)
- [Actor](#)
- [ActorSession](#)
- [ActorUser](#)
- [Adjustment](#)
- [AdminAccount](#)
- [AssociatedStandard](#)
- [AssociationFilters](#)
- [AutomationRulesAction](#)
- [AutomationRulesConfig](#)
- [AutomationRulesFindingFieldsUpdate](#)
- [AutomationRulesFindingFilters](#)
- [AutomationRulesMetadata](#)
- [AwsApiCallAction](#)
- [AwsApiCallActionDomainDetails](#)

- [AwsSecurityFinding](#)
- [AwsSecurityFindingFilters](#)
- [AwsSecurityFindingIdentifier](#)
- [BatchUpdateFindingsUnprocessedFinding](#)
- [BooleanConfigurationOptions](#)
- [BooleanFilter](#)
- [Cell](#)
- [City](#)
- [ClassificationResult](#)
- [ClassificationStatus](#)
- [CodeVulnerabilitiesFilePath](#)
- [Compliance](#)
- [ConfigurationOptions](#)
- [ConfigurationPolicyAssociation](#)
- [ConfigurationPolicyAssociationSummary](#)
- [ConfigurationPolicySummary](#)
- [Country](#)
- [CustomDataIdentifiersDetections](#)
- [CustomDataIdentifiersResult](#)
- [Cvss](#)
- [DataClassificationDetails](#)
- [DateFilter](#)
- [DateRange](#)
- [Detection](#)
- [DnsRequestAction](#)
- [DoubleConfigurationOptions](#)
- [EnumConfigurationOptions](#)
- [EnumListConfigurationOptions](#)
- [FilePaths](#)
- [FindingAggregator](#)

- [FindingHistoryRecord](#)
- [FindingHistoryUpdate](#)
- [FindingHistoryUpdateSource](#)
- [FindingProviderFields](#)
- [FindingProviderSeverity](#)
- [GeneratorDetails](#)
- [GeoLocation](#)
- [IcmpTypeCode](#)
- [ImportFindingsError](#)
- [Indicator](#)
- [Insight](#)
- [InsightResults](#)
- [InsightResultValue](#)
- [IntegerConfigurationOptions](#)
- [IntegerListConfigurationOptions](#)
- [Invitation](#)
- [IpFilter](#)
- [IpOrganizationDetails](#)
- [KeywordFilter](#)
- [Malware](#)
- [MapFilter](#)
- [Member](#)
- [Network](#)
- [NetworkAutonomousSystem](#)
- [NetworkConnection](#)
- [NetworkConnectionAction](#)
- [NetworkEndpoint](#)
- [NetworkGeoLocation](#)
- [NetworkPathComponent](#)
- [NetworkPathComponentDetails](#)

- [Note](#)
- [NoteUpdate](#)
- [NumberFilter](#)
- [Occurrences](#)
- [OrganizationConfiguration](#)
- [Page](#)
- [ParameterConfiguration](#)
- [ParameterDefinition](#)
- [ParameterValue](#)
- [PatchSummary](#)
- [Policy](#)
- [PortProbeAction](#)
- [PortProbeDetail](#)
- [ProcessDetails](#)
- [Product](#)
- [Range](#)
- [Recommendation](#)
- [Record](#)
- [RelatedFinding](#)
- [Remediation](#)
- [Resource](#)
- [ResourceDetails](#)
- [Result](#)
- [SecurityControl](#)
- [SecurityControlCustomParameter](#)
- [SecurityControlDefinition](#)
- [SecurityControlParameter](#)
- [SecurityControlsConfiguration](#)
- [SecurityHubPolicy](#)
- [SensitiveDataDetections](#)

- [SensitiveDataResult](#)
- [Sequence](#)
- [Severity](#)
- [SeverityUpdate](#)
- [Signal](#)
- [SoftwarePackage](#)
- [SortCriterion](#)
- [Standard](#)
- [StandardsControl](#)
- [StandardsControlAssociationDetail](#)
- [StandardsControlAssociationId](#)
- [StandardsControlAssociationSummary](#)
- [StandardsControlAssociationUpdate](#)
- [StandardsManagedBy](#)
- [StandardsStatusReason](#)
- [StandardsSubscription](#)
- [StandardsSubscriptionRequest](#)
- [StatusReason](#)
- [StringConfigurationOptions](#)
- [StringFilter](#)
- [StringListConfigurationOptions](#)
- [Target](#)
- [Threat](#)
- [ThreatIntelIndicator](#)
- [UnprocessedAutomationRule](#)
- [UnprocessedConfigurationPolicyAssociation](#)
- [UnprocessedSecurityControl](#)
- [UnprocessedStandardsControlAssociation](#)
- [UnprocessedStandardsControlAssociationUpdate](#)
- [UpdateAutomationRulesRequestItem](#)

- [UserAccount](#)
- [Vulnerability](#)
- [VulnerabilityCodeVulnerabilities](#)
- [VulnerabilityVendor](#)
- [Workflow](#)
- [WorkflowUpdate](#)

AccountDetails

The details of an Amazon Web Services account.

Contents

AccountId

The ID of an Amazon Web Services account.

Type: String

Required: Yes

Email

The email of an Amazon Web Services account.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Action

Provides details about one of the following actions that affects or that was taken on a resource:

- A remote IP address issued an Amazon API call
- A DNS request was received
- A remote IP address attempted to connect to an EC2 instance
- A remote IP address attempted a port probe on an EC2 instance

Contents

ActionType

The type of action that was detected. The possible action types are:

- NETWORK_CONNECTION
- AWS_API_CALL
- DNS_REQUEST
- PORT_PROBE

Type: String

Pattern: .*\\S.*

Required: No

AwsApiCallAction

Included if `ActionType` is `AWS_API_CALL`. Provides details about the API call that was detected.

Type: [AwsApiCallAction](#) object

Required: No

DnsRequestAction

Included if `ActionType` is `DNS_REQUEST`. Provides details about the DNS request that was detected.

Type: [DnsRequestAction](#) object

Required: No

NetworkConnectionAction

Included if `ActionType` is `NETWORK_CONNECTION`. Provides details about the network connection that was detected.

Type: [NetworkConnectionAction](#) object

Required: No

PortProbeAction

Included if `ActionType` is `PORT_PROBE`. Provides details about the port probe that was detected.

Type: [PortProbeAction](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ActionLocalIpDetails

Provides information about the IP address where the scanned port is located.

Contents

IpAddressV4

The IP address.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ActionLocalPortDetails

For `NetworkConnectionAction` and `PortProbeDetails`, `LocalPortDetails` provides information about the local port that was involved in the action.

Contents

Port

The number of the port.

Type: Integer

Required: No

PortName

The port name of the local connection.

Length Constraints: 128.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ActionRemoteIpDetails

For `AwsApiAction`, `NetworkConnectionAction`, and `PortProbeAction`, `RemoteIpDetails` provides information about the remote IP address that was involved in the action.

Contents

City

The city where the remote IP address is located.

Type: [City](#) object

Required: No

Country

The country where the remote IP address is located.

Type: [Country](#) object

Required: No

GeoLocation

The coordinates of the location of the remote IP address.

Type: [GeoLocation](#) object

Required: No

IpAddressV4

The IP address.

Type: String

Pattern: `.*\S.*`

Required: No

Organization

The internet service provider (ISP) organization associated with the remote IP address.

Type: [IpOrganizationDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ActionRemotePortDetails

Provides information about the remote port that was involved in an attempted network connection.

Contents

Port

The number of the port.

Type: Integer

Required: No

PortName

The port name of the remote connection.

Length Constraints: 128.

Type: String

Pattern: .*S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ActionTarget

An ActionTarget object.

Contents

ActionTargetArn

The ARN for the target action.

Type: String

Pattern: `.*\S.*`

Required: Yes

Description

The description of the target action.

Type: String

Pattern: `.*\S.*`

Required: Yes

Name

The name of the action target.

Type: String

Pattern: `.*\S.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

Actor

Information about the threat actor identified in an Amazon GuardDuty Extended Threat Detection attack sequence. GuardDuty generates an attack sequence finding when multiple events align to a potentially suspicious activity. To receive GuardDuty attack sequence findings in Amazon Security Hub, you must have GuardDuty enabled. For more information, see [GuardDuty Extended Threat Detection](#) in the *Amazon GuardDuty User Guide*.

Contents

Id

The ID of the threat actor.

Type: String

Pattern: `.*\S.*`

Required: No

Session

Contains information about the user session where the activity initiated.

Type: [ActorSession](#) object

Required: No

User

Contains information about the user credentials used by the threat actor.

Type: [ActorUser](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ActorSession

Contains information about the authenticated session used by the threat actor identified in an Amazon GuardDuty Extended Threat Detection attack sequence. GuardDuty generates an attack sequence finding when multiple events align to a potentially suspicious activity. To receive GuardDuty attack sequence findings in Amazon Security Hub, you must have GuardDuty enabled. For more information, see [GuardDuty Extended Threat Detection](#) in the *Amazon GuardDuty User Guide*.

Contents

CreatedTime

The timestamp for when the session was created.

In Amazon CloudTrail, you can find this value as `userIdentity.sessionContext.attributes.creationDate`.

Type: Long

Required: No

Issuer

The issuer of the session.

In Amazon CloudTrail, you can find this value as `userIdentity.sessionContext.sessionIssuer.arn`.

Type: String

Pattern: `.*\S.*`

Required: No

MfaStatus

Indicates whether multi-factor authentication (MFA) was used for authentication during the session.

In Amazon CloudTrail, you can find this value as `userIdentity.sessionContext.attributes.mfaAuthenticated`.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

Uid

Unique identifier of the session.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ActorUser

Contains information about the credentials used by the threat actor identified in an Amazon GuardDuty Extended Threat Detection attack sequence. GuardDuty generates an attack sequence finding when multiple events align to a potentially suspicious activity. To receive GuardDuty attack sequence findings in Amazon Security Hub, you must have GuardDuty enabled. For more information, see [GuardDuty Extended Threat Detection](#) in the *Amazon GuardDuty User Guide*.

Contents

Account

The account of the threat actor.

Type: [UserAccount](#) object

Required: No

CredentialUid

Unique identifier of the threat actor's user credentials.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the threat actor.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The type of user.

Type: String

Pattern: `.*\S.*`

Required: No

Uid

The unique identifier of the threat actor.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Adjustment

An adjustment to the CVSS metric.

Contents

Metric

The metric to adjust.

Type: String

Pattern: `.*\S.*`

Required: No

Reason

The reason for the adjustment.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AdminAccount

Represents a Security Hub administrator account designated by an organization management account.

Contents

AccountId

The Amazon Web Services account identifier of the Security Hub administrator account.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The current status of the Security Hub administrator account. Indicates whether the account is currently enabled as a Security Hub administrator.

Type: String

Valid Values: `ENABLED` | `DISABLE_IN_PROGRESS`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssociatedStandard

Information about an enabled security standard in which a security control is enabled.

Contents

StandardsId

The unique identifier of a standard in which a control is enabled. This field consists of the resource portion of the Amazon Resource Name (ARN) returned for a standard in the [DescribeStandards](#) API response.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssociationFilters

Options for filtering the `ListConfigurationPolicyAssociations` response. You can filter by the Amazon Resource Name (ARN) or universally unique identifier (UUID) of a configuration policy, `AssociationType`, or `AssociationStatus`.

Contents

AssociationStatus

The current status of the association between a target and a configuration policy.

Type: String

Valid Values: PENDING | SUCCESS | FAILED

Required: No

AssociationType

Indicates whether the association between a target and a configuration was directly applied by the Amazon Security Hub delegated administrator or inherited from a parent.

Type: String

Valid Values: INHERITED | APPLIED

Required: No

ConfigurationPolicyId

The ARN or UUID of the configuration policy.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AutomationRulesAction

One or more actions that Amazon Security Hub takes when a finding matches the defined criteria of a rule.

Contents

FindingFieldsUpdate

Specifies that the automation rule action is an update to a finding field.

Type: [AutomationRulesFindingFieldsUpdate](#) object

Required: No

Type

Specifies the type of action that Security Hub takes when a finding matches the defined criteria of a rule.

Type: String

Valid Values: FINDING_FIELDS_UPDATE

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AutomationRulesConfig

Defines the configuration of an automation rule.

Contents

Actions

One or more actions to update finding fields if a finding matches the defined criteria of the rule.

Type: Array of [AutomationRulesAction](#) objects

Array Members: Fixed number of 1 item.

Required: No

CreatedAt

A timestamp that indicates when the rule was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: Timestamp

Required: No

CreatedBy

The principal that created a rule.

Type: String

Pattern: `.*\S.*`

Required: No

Criteria

A set of [Amazon Security Finding Format](#) finding field attributes and corresponding expected values that Security Hub uses to filter findings. If a rule is enabled and a finding matches the conditions specified in this parameter, Security Hub applies the rule action to the finding.

Type: [AutomationRulesFindingFilters](#) object

Required: No

Description

A description of the rule.

Type: String

Pattern: `.*\S.*`

Required: No

IsTerminal

Specifies whether a rule is the last to be applied with respect to a finding that matches the rule criteria. This is useful when a finding matches the criteria for multiple rules, and each rule has different actions. If a rule is terminal, Security Hub applies the rule action to a finding that matches the rule criteria and doesn't evaluate other rules for the finding. By default, a rule isn't terminal.

Type: Boolean

Required: No

RuleArn

The Amazon Resource Name (ARN) of a rule.

Type: String

Pattern: `.*\S.*`

Required: No

RuleName

The name of the rule.

Type: String

Pattern: `.*\S.*`

Required: No

RuleOrder

An integer ranging from 1 to 1000 that represents the order in which the rule action is applied to findings. Security Hub applies rules with lower values for this parameter first.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

RuleStatus

Whether the rule is active after it is created. If this parameter is equal to ENABLED, Security Hub starts applying the rule to findings and finding updates after the rule is created.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

UpdatedAt

A timestamp that indicates when the rule was most recently updated.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AutomationRulesFindingFieldsUpdate

Identifies the finding fields that the automation rule action updates when a finding matches the defined criteria.

Contents

Confidence

The rule action updates the Confidence field of a finding.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

Criticality

The rule action updates the Criticality field of a finding.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

Note

The updated note.

Type: [NoteUpdate](#) object

Required: No

RelatedFindings

The rule action updates the RelatedFindings field of a finding.

Type: Array of [RelatedFinding](#) objects

Required: No

Severity

Updates to the severity information for a finding.

Type: [SeverityUpdate](#) object

Required: No

Types

The rule action updates the `Types` field of a finding.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

UserDefinedFields

The rule action updates the `UserDefinedFields` field of a finding.

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

VerificationState

The rule action updates the `VerificationState` field of a finding.

Type: String

Valid Values: UNKNOWN | TRUE_POSITIVE | FALSE_POSITIVE | BENIGN_POSITIVE

Required: No

Workflow

Used to update information about the investigation into the finding.

Type: [WorkflowUpdate](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AutomationRulesFindingFilters

The criteria that determine which findings a rule applies to.

Contents

AwsAccountId

The Amazon Web Services account ID in which a finding was generated.

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Type: Array of [StringFilter](#) objects

Required: No

AwsAccountName

The name of the Amazon Web Services account in which a finding was generated.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

CompanyName

The name of the company for the product that generated the finding. For control-based findings, the company is Amazon.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

ComplianceAssociatedStandardsId

The unique identifier of a standard in which a control is enabled. This field consists of the resource portion of the Amazon Resource Name (ARN) returned for a standard in the [DescribeStandards](#) API response.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

ComplianceSecurityControlId

The security control ID for which a finding was generated. Security control IDs are the same across standards.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

ComplianceStatus

The result of a security check. This field is only used for findings generated from controls.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

Confidence

The likelihood that a finding accurately identifies the behavior or issue that it was intended to identify. Confidence is scored on a 0–100 basis using a ratio scale. A value of 0 means 0 percent confidence, and a value of 100 means 100 percent confidence. For example, a data exfiltration detection based on a statistical deviation of network traffic has low confidence because an actual exfiltration hasn't been verified. For more information, see [Confidence](#) in the *Amazon Security Hub User Guide*.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [NumberFilter](#) objects

Required: No

CreatedAt

A timestamp that indicates when this finding record was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [DateFilter](#) objects

Required: No

Criticality

The level of importance that is assigned to the resources that are associated with a finding. **Criticality** is scored on a 0–100 basis, using a ratio scale that supports only full integers. A score of 0 means that the underlying resources have no criticality, and a score of 100 is reserved for the most critical resources. For more information, see [Criticality](#) in the *Amazon Security Hub User Guide*.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [NumberFilter](#) objects

Required: No

Description

A finding's description.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

FirstObservedAt

A timestamp that indicates when the potential security issue captured by a finding was first observed by the security findings product.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [DateFilter](#) objects

Required: No

GeneratorId

The identifier for the solution-specific component that generated a finding.

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Type: Array of [StringFilter](#) objects

Required: No

Id

The product-specific identifier for a finding.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

LastObservedAt

A timestamp that indicates when the security findings provider most recently observed a change in the resource that is involved in the finding.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [DateFilter](#) objects

Required: No

NoteText

The text of a user-defined note that's added to a finding.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

NoteUpdatedAt

The timestamp of when the note was updated.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [DateFilter](#) objects

Required: No

NoteUpdatedBy

The principal that created a note.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

ProductArn

The Amazon Resource Name (ARN) for a third-party product that generated a finding in Security Hub.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

ProductName

Provides the name of the product that generated the finding. For control-based findings, the product name is Security Hub.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

RecordState

Provides the current state of a finding.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

RelatedFindingsId

The product-generated identifier for a related finding.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

RelatedFindingsProductArn

The ARN for the product that generated a related finding.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

ResourceApplicationArn

The Amazon Resource Name (ARN) of the application that is related to a finding.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

ResourceApplicationName

The name of the application that is related to a finding.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

ResourceDetailsOther

Custom fields and values about the resource that a finding pertains to.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [MapFilter](#) objects

Required: No

ResourceId

The identifier for the given resource type. For Amazon resources that are identified by Amazon Resource Names (ARNs), this is the ARN. For Amazon resources that lack ARNs, this is the identifier as defined by the Amazon Web Services service that created the resource. For non-Amazon resources, this is a unique identifier that is associated with the resource.

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Type: Array of [StringFilter](#) objects

Required: No

ResourcePartition

The partition in which the resource that the finding pertains to is located. A partition is a group of Amazon Web Services Regions. Each Amazon Web Services account is scoped to one partition.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

ResourceRegion

The Amazon Web Services Region where the resource that a finding pertains to is located.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

ResourceTags

A list of Amazon tags associated with a resource at the time the finding was processed.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [MapFilter](#) objects

Required: No

ResourceType

The type of resource that the finding pertains to.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

SeverityLabel

The severity value of the finding.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

SourceUrl

Provides a URL that links to a page about the current finding in the finding product.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

Title

A finding's title.

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Type: Array of [StringFilter](#) objects

Required: No

Type

One or more finding types in the format of namespace/category/classifier that classify a finding. For a list of namespaces, classifiers, and categories, see [Types taxonomy for ASFF](#) in the *Amazon Security Hub User Guide*.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

UpdatedAt

A timestamp that indicates when the finding record was most recently updated.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [DateFilter](#) objects

Required: No

UserDefinedFields

A list of user-defined name and value string pairs added to a finding.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [MapFilter](#) objects

Required: No

VerificationState

Provides the veracity of a finding.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

WorkflowStatus

Provides information about the status of the investigation into a finding.

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Type: Array of [StringFilter](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AutomationRulesMetadata

Metadata for automation rules in the calling account. The response includes rules with a `RuleStatus` of `ENABLED` and `DISABLED`.

Contents

CreatedAt

A timestamp that indicates when the rule was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: Timestamp

Required: No

CreatedBy

The principal that created a rule.

Type: String

Pattern: `.*\S.*`

Required: No

Description

A description of the rule.

Type: String

Pattern: `.*\S.*`

Required: No

IsTerminal

Specifies whether a rule is the last to be applied with respect to a finding that matches the rule criteria. This is useful when a finding matches the criteria for multiple rules, and each rule has different actions. If a rule is terminal, Security Hub applies the rule action to a finding that matches the rule criteria and doesn't evaluate other rules for the finding. By default, a rule isn't terminal.

Type: Boolean

Required: No

RuleArn

The Amazon Resource Name (ARN) for the rule.

Type: String

Pattern: `.*\S.*`

Required: No

RuleName

The name of the rule.

Type: String

Pattern: `.*\S.*`

Required: No

RuleOrder

An integer ranging from 1 to 1000 that represents the order in which the rule action is applied to findings. Security Hub applies rules with lower values for this parameter first.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

RuleStatus

Whether the rule is active after it is created. If this parameter is equal to `ENABLED`, Security Hub starts applying the rule to findings and finding updates after the rule is created. To change the value of this parameter after creating a rule, use [BatchUpdateAutomationRules](#).

Type: String

Valid Values: `ENABLED` | `DISABLED`

Required: No

UpdatedAt

A timestamp that indicates when the rule was most recently updated.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsApiCallAction

Provided if `ActionType` is `AWS_API_CALL`. It provides details about the API call that was detected.

Contents

AffectedResources

Identifies the resources that were affected by the API call.

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

Api

The name of the API method that was issued.

Length Constraints: 128.

Type: String

Pattern: `.*\S.*`

Required: No

CallerType

Indicates whether the API call originated from a remote IP address (`remoteip`) or from a DNS domain (`domain`).

Type: String

Pattern: `.*\S.*`

Required: No

DomainDetails

Provided if `CallerType` is `domain`. Provides information about the DNS domain that the API call originated from.

Type: [AwsApiCallActionDomainDetails](#) object

Required: No

FirstSeen

A timestamp that indicates when the API call was first observed.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

LastSeen

A timestamp that indicates when the API call was most recently observed.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

RemotelpDetails

Provided if `CallerType` is `remoteip`. Provides information about the remote IP address that the API call originated from.

Type: [ActionRemotelpDetails](#) object

Required: No

ServiceName

The name of the Amazon service that the API method belongs to.

Length Constraints: 128.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsApiCallActionDomainDetails

Provided if `CallerType` is `domain`. It provides information about the DNS domain that issued the API call.

Contents

Domain

The name of the DNS domain that issued the API call.

Length Constraints: 128.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsSecurityFinding

Provides a consistent format for Security Hub findings. `AwsSecurityFinding` format allows you to share findings between Amazon security services and third-party solutions.

Note

A finding is a potential security issue generated either by Amazon services or by the integrated third-party solutions and standards checks.

Contents

AwsAccountId

The Amazon Web Services account ID that a finding is generated in.

Length Constraints: 12.

Type: String

Pattern: `.*\S.*`

Required: Yes

CreatedAt

Indicates when the security findings provider created the potential security issue that a finding captured.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: Yes

Description

A finding's description. `Description` is a required property.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Type: String

Pattern: `.*\S.*`

Required: Yes

GeneratorId

The identifier for the solution-specific component (a discrete unit of logic) that generated a finding. In various security findings providers' solutions, this generator can be called a rule, a check, a detector, a plugin, or something else.

Length Constraints: Minimum length of 1. Maximum length of 512.

Type: String

Pattern: `.*\S.*`

Required: Yes

Id

The security findings provider-specific identifier for a finding.

Length Constraints: Minimum length of 1. Maximum length of 512.

Type: String

Pattern: `.*\S.*`

Required: Yes

ProductArn

The ARN generated by Security Hub that uniquely identifies a product that generates findings. This can be the ARN for a third-party product that is integrated with Security Hub, or the ARN for a custom integration.

Length Constraints: Minimum length of 12. Maximum length of 2048.

Type: String

Pattern: `.*\S.*`

Required: Yes

Resources

A set of resource data types that describe the resources that the finding refers to.

Array Members: Minimum number of 1 item. Maximum number of 32 items.

Type: Array of [Resource](#) objects

Required: Yes

SchemaVersion

The schema version that a finding is formatted for. The value is 2018-10-08.

Type: String

Pattern: `.*\S.*`

Required: Yes

Title

A finding's title. Title is a required property.

Length Constraints: Minimum length of 1. Maximum length of 256.

Type: String

Pattern: `.*\S.*`

Required: Yes

UpdatedAt

Indicates when the security findings provider last updated the finding record.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: Yes

Action

Provides details about an action that affects or that was taken on a resource.

Type: [Action](#) object

Required: No

AwsAccountName

The name of the Amazon Web Services account from which a finding was generated.

Length Constraints: Minimum length of 1. Maximum length of 50.

Type: String

Pattern: `.*\S.*`

Required: No

CompanyName

The name of the company for the product that generated the finding.

Security Hub populates this attribute automatically for each finding. You cannot update this attribute with `BatchImportFindings` or `BatchUpdateFindings`. The exception to this is a custom integration.

When you use the Security Hub console or API to filter findings by company name, you use this attribute.

Length Constraints: Minimum length of 1. Maximum length of 128.

Type: String

Pattern: `.*\S.*`

Required: No

Compliance

This data type is exclusive to findings that are generated as the result of a check run against a specific rule in a supported security standard, such as CIS Amazon Foundations. Contains security standard-related finding details.

Type: [Compliance](#) object

Required: No

Confidence

A finding's confidence. Confidence is defined as the likelihood that a finding accurately identifies the behavior or issue that it was intended to identify.

Confidence is scored on a 0-100 basis using a ratio scale, where 0 means zero percent confidence and 100 means 100 percent confidence.

Type: Integer

Required: No

Criticality

The level of importance assigned to the resources associated with the finding.

A score of 0 means that the underlying resources have no criticality, and a score of 100 is reserved for the most critical resources.

Type: Integer

Required: No

Detection

Provides details about an Amazon GuardDuty Extended Threat Detection attack sequence. GuardDuty generates an attack sequence finding when multiple events align to a potentially suspicious activity. To receive GuardDuty attack sequence findings in Amazon Security Hub, you must have GuardDuty enabled. For more information, see [GuardDuty Extended Threat Detection](#) in the *Amazon GuardDuty User Guide*.

Type: [Detection](#) object

Required: No

FindingProviderFields

In a BatchImportFindings request, finding providers use FindingProviderFields to provide and update their own values for confidence, criticality, related findings, severity, and types.

Type: [FindingProviderFields](#) object

Required: No

FirstObservedAt

Indicates when the security findings provider first observed the potential security issue that a finding captured.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

GeneratorDetails

Provides metadata for the Amazon CodeGuru detector associated with a finding. This field pertains to findings that relate to Amazon Lambda functions. Amazon Inspector identifies policy violations and vulnerabilities in Lambda function code based on internal detectors developed in collaboration with Amazon CodeGuru. Amazon Security Hub receives those findings.

Type: [GeneratorDetails](#) object

Required: No

LastObservedAt

Indicates when the security findings provider most recently observed a change in the resource that is involved in the finding.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

Malware

A list of malware related to a finding.

Array Members: Maximum number of 5 items.

Type: Array of [Malware](#) objects

Required: No

Network

The details of network-related information about a finding.

Type: [Network](#) object

Required: No

NetworkPath

Provides information about a network path that is relevant to a finding. Each entry under `NetworkPath` represents a component of that path.

Type: Array of [NetworkPathComponent](#) objects

Required: No

Note

A user-defined note added to a finding.

Type: [Note](#) object

Required: No

PatchSummary

Provides an overview of the patch compliance status for an instance against a selected compliance standard.

Type: [PatchSummary](#) object

Required: No

Process

The details of process-related information about a finding.

Type: [ProcessDetails](#) object

Required: No

ProcessedAt

A timestamp that indicates when Amazon Security Hub received a finding and begins to process it.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

ProductFields

A data type where security findings providers can include additional solution-specific details that aren't part of the defined `AwsSecurityFinding` format.

Can contain up to 50 key-value pairs. For each key-value pair, the key can contain up to 128 characters, and the value can contain up to 2048 characters.

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

ProductName

The name of the product that generated the finding.

Security Hub populates this attribute automatically for each finding. You cannot update this attribute with `BatchImportFindings` or `BatchUpdateFindings`. The exception to this is a custom integration.

When you use the Security Hub console or API to filter findings by product name, you use this attribute.

Length Constraints: Minimum length of 1. Maximum length of 128.

Type: String

Pattern: .*\\S.*

Required: No

RecordState

The record state of a finding.

Type: String

Valid Values: ACTIVE | ARCHIVED

Required: No

Region

The Region from which the finding was generated.

Security Hub populates this attribute automatically for each finding. You cannot update it using `BatchImportFindings` or `BatchUpdateFindings`.

Length Constraints: Minimum length of 1. Maximum length of 16.

Type: String

Pattern: .*\\S.*

Required: No

RelatedFindings

A list of related findings.

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Type: Array of [RelatedFinding](#) objects

Required: No

Remediation

A data type that describes the remediation options for a finding.

Type: [Remediation](#) object

Required: No

Sample

Indicates whether the finding is a sample finding.

Type: Boolean

Required: No

Severity

A finding's severity.

Type: [Severity](#) object

Required: No

SourceUrl

A URL that links to a page about the current finding in the security findings provider's solution.

Type: String

Pattern: `.*\S.*`

Required: No

ThreatIntelIndicators

Threat intelligence details related to a finding.

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Type: Array of [ThreatIntelIndicator](#) objects

Required: No

Threats

Details about the threat detected in a security finding and the file paths that were affected by the threat.

Array Members: Minimum number of 1 item. Maximum number of 32 items.

Type: Array of [Threat](#) objects

Required: No

Types

One or more finding types in the format of `namespace/category/classifier` that classify a finding.

Valid namespace values are: Software and Configuration Checks | TTPs | Effects | Unusual Behaviors | Sensitive Data Identifications

Array Members: Maximum number of 50 items.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

UserDefinedFields

A list of name/value string pairs associated with the finding. These are custom, user-defined fields added to a finding.

Can contain up to 50 key-value pairs. For each key-value pair, the key can contain up to 128 characters, and the value can contain up to 1024 characters.

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

VerificationState

Indicates the veracity of a finding.

Type: String

Valid Values: UNKNOWN | TRUE_POSITIVE | FALSE_POSITIVE | BENIGN_POSITIVE

Required: No

Vulnerabilities

Provides a list of vulnerabilities associated with the findings.

Type: Array of [Vulnerability](#) objects

Required: No

Workflow

Provides information about the status of the investigation into a finding.

Type: [Workflow](#) object

Required: No

WorkflowState

This member has been deprecated.

The workflow state of a finding.

Type: String

Valid Values: NEW | ASSIGNED | IN_PROGRESS | DEFERRED | RESOLVED

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsSecurityFindingFilters

A collection of filters that are applied to all active findings aggregated by Amazon Security Hub.

You can filter by up to ten finding attributes. For each attribute, you can provide up to 20 filter values.

Contents

AwsAccountId

The Amazon Web Services account ID in which a finding is generated.

Type: Array of [StringFilter](#) objects

Required: No

AwsAccountName

The name of the Amazon Web Services account in which a finding is generated.

Type: Array of [StringFilter](#) objects

Required: No

CompanyName

The name of the findings provider (company) that owns the solution (product) that generates findings.

Type: Array of [StringFilter](#) objects

Required: No

ComplianceAssociatedStandardsId

The unique identifier of a standard in which a control is enabled. This field consists of the resource portion of the Amazon Resource Name (ARN) returned for a standard in the [DescribeStandards](#) API response.

Type: Array of [StringFilter](#) objects

Required: No

ComplianceSecurityControlId

The unique identifier of a control across standards. Values for this field typically consist of an Amazon Web Services service and a number, such as APIGateway.5.

Type: Array of [StringFilter](#) objects

Required: No

ComplianceSecurityControlParametersName

The name of a security control parameter.

Type: Array of [StringFilter](#) objects

Required: No

ComplianceSecurityControlParametersValue

The current value of a security control parameter.

Type: Array of [StringFilter](#) objects

Required: No

ComplianceStatus

Exclusive to findings that are generated as the result of a check run against a specific rule in a supported standard, such as CIS Amazon Foundations. Contains security standard-related finding details.

Type: Array of [StringFilter](#) objects

Required: No

Confidence

A finding's confidence. Confidence is defined as the likelihood that a finding accurately identifies the behavior or issue that it was intended to identify.

Confidence is scored on a 0-100 basis using a ratio scale, where 0 means zero percent confidence and 100 means 100 percent confidence.

Type: Array of [NumberFilter](#) objects

Required: No

CreatedAt

A timestamp that indicates when the security findings provider created the potential security issue that a finding reflects.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: Array of [DateFilter](#) objects

Required: No

Criticality

The level of importance assigned to the resources associated with the finding.

A score of 0 means that the underlying resources have no criticality, and a score of 100 is reserved for the most critical resources.

Type: Array of [NumberFilter](#) objects

Required: No

Description

A finding's description.

Type: Array of [StringFilter](#) objects

Required: No

FindingProviderFieldsConfidence

The finding provider value for the finding confidence. Confidence is defined as the likelihood that a finding accurately identifies the behavior or issue that it was intended to identify.

Confidence is scored on a 0-100 basis using a ratio scale, where 0 means zero percent confidence and 100 means 100 percent confidence.

Type: Array of [NumberFilter](#) objects

Required: No

FindingProviderFieldsCriticality

The finding provider value for the level of importance assigned to the resources associated with the findings.

A score of 0 means that the underlying resources have no criticality, and a score of 100 is reserved for the most critical resources.

Type: Array of [NumberFilter](#) objects

Required: No

FindingProviderFieldsRelatedFindingsId

The finding identifier of a related finding that is identified by the finding provider.

Type: Array of [StringFilter](#) objects

Required: No

FindingProviderFieldsRelatedFindingsProductArn

The ARN of the solution that generated a related finding that is identified by the finding provider.

Type: Array of [StringFilter](#) objects

Required: No

FindingProviderFieldsSeverityLabel

The finding provider value for the severity label.

Type: Array of [StringFilter](#) objects

Required: No

FindingProviderFieldsSeverityOriginal

The finding provider's original value for the severity.

Type: Array of [StringFilter](#) objects

Required: No

FindingProviderFieldsTypes

One or more finding types that the finding provider assigned to the finding. Uses the format of `namespace/category/classifier` that classify a finding.

Valid namespace values are: Software and Configuration Checks | TTPs | Effects | Unusual Behaviors | Sensitive Data Identifications

Type: Array of [StringFilter](#) objects

Required: No

FirstObservedAt

A timestamp that indicates when the security findings provider first observed the potential security issue that a finding captured.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: Array of [DateFilter](#) objects

Required: No

GeneratorId

The identifier for the solution-specific component (a discrete unit of logic) that generated a finding. In various security findings providers' solutions, this generator can be called a rule, a check, a detector, a plugin, etc.

Type: Array of [StringFilter](#) objects

Required: No

Id

The security findings provider-specific identifier for a finding.

Type: Array of [StringFilter](#) objects

Required: No

Keyword

This member has been deprecated.

A keyword for a finding.

Type: Array of [KeywordFilter](#) objects

Required: No

LastObservedAt

A timestamp that indicates when the security findings provider most recently observed a change in the resource that is involved in the finding.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: Array of [DateFilter](#) objects

Required: No

MalwareName

The name of the malware that was observed.

Type: Array of [StringFilter](#) objects

Required: No

MalwarePath

The filesystem path of the malware that was observed.

Type: Array of [StringFilter](#) objects

Required: No

MalwareState

The state of the malware that was observed.

Type: Array of [StringFilter](#) objects

Required: No

MalwareType

The type of the malware that was observed.

Type: Array of [StringFilter](#) objects

Required: No

NetworkDestinationDomain

The destination domain of network-related information about a finding.

Type: Array of [StringFilter](#) objects

Required: No

NetworkDestinationIPv4

The destination IPv4 address of network-related information about a finding.

Type: Array of [IpFilter](#) objects

Required: No

NetworkDestinationIPv6

The destination IPv6 address of network-related information about a finding.

Type: Array of [IpFilter](#) objects

Required: No

NetworkDestinationPort

The destination port of network-related information about a finding.

Type: Array of [NumberFilter](#) objects

Required: No

NetworkDirection

Indicates the direction of network traffic associated with a finding.

Type: Array of [StringFilter](#) objects

Required: No

NetworkProtocol

The protocol of network-related information about a finding.

Type: Array of [StringFilter](#) objects

Required: No

NetworkSourceDomain

The source domain of network-related information about a finding.

Type: Array of [StringFilter](#) objects

Required: No

NetworkSourceIpV4

The source IPv4 address of network-related information about a finding.

Type: Array of [IpFilter](#) objects

Required: No

NetworkSourceIpV6

The source IPv6 address of network-related information about a finding.

Type: Array of [IpFilter](#) objects

Required: No

NetworkSourceMac

The source media access control (MAC) address of network-related information about a finding.

Type: Array of [StringFilter](#) objects

Required: No

NetworkSourcePort

The source port of network-related information about a finding.

Type: Array of [NumberFilter](#) objects

Required: No

NoteText

The text of a note.

Type: Array of [StringFilter](#) objects

Required: No

NoteUpdatedAt

The timestamp of when the note was updated.

Type: Array of [DateFilter](#) objects

Required: No

NoteUpdatedBy

The principal that created a note.

Type: Array of [StringFilter](#) objects

Required: No

ProcessLaunchedAt

A timestamp that identifies when the process was launched.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: Array of [DateFilter](#) objects

Required: No

ProcessName

The name of the process.

Type: Array of [StringFilter](#) objects

Required: No

ProcessParentPid

The parent process ID. This field accepts positive integers between 0 and 2147483647.

Type: Array of [NumberFilter](#) objects

Required: No

ProcessPath

The path to the process executable.

Type: Array of [StringFilter](#) objects

Required: No

ProcessPid

The process ID.

Type: Array of [NumberFilter](#) objects

Required: No

ProcessTerminatedAt

A timestamp that identifies when the process was terminated.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: Array of [DateFilter](#) objects

Required: No

ProductArn

The ARN generated by Security Hub that uniquely identifies a third-party company (security findings provider) after this provider's product (solution that generates findings) is registered with Security Hub.

Type: Array of [StringFilter](#) objects

Required: No

ProductFields

A data type where security findings providers can include additional solution-specific details that aren't part of the defined `AwsSecurityFinding` format.

Type: Array of [MapFilter](#) objects

Required: No

ProductName

The name of the solution (product) that generates findings.

Type: Array of [StringFilter](#) objects

Required: No

RecommendationText

The recommendation of what to do about the issue described in a finding.

Type: Array of [StringFilter](#) objects

Required: No

RecordState

The updated record state for the finding.

Type: Array of [StringFilter](#) objects

Required: No

Region

The Region from which the finding was generated.

Type: Array of [StringFilter](#) objects

Required: No

RelatedFindingsId

The solution-generated identifier for a related finding.

Type: Array of [StringFilter](#) objects

Required: No

RelatedFindingsProductArn

The ARN of the solution that generated a related finding.

Type: Array of [StringFilter](#) objects

Required: No

ResourceApplicationArn

The ARN of the application that is related to a finding.

Type: Array of [StringFilter](#) objects

Required: No

ResourceApplicationName

The name of the application that is related to a finding.

Type: Array of [StringFilter](#) objects

Required: No

ResourceAwsEc2InstancelamInstanceProfileArn

The IAM profile ARN of the instance.

Type: Array of [StringFilter](#) objects

Required: No

ResourceAwsEc2InstanceImageId

The Amazon Machine Image (AMI) ID of the instance.

Type: Array of [StringFilter](#) objects

Required: No

ResourceAwsEc2InstanceIpV4Addresses

The IPv4 addresses associated with the instance.

Type: Array of [IpFilter](#) objects

Required: No

ResourceAwsEc2InstanceIpV6Addresses

The IPv6 addresses associated with the instance.

Type: Array of [IpFilter](#) objects

Required: No

ResourceAwsEc2InstanceKeyName

The key name associated with the instance.

Type: Array of [StringFilter](#) objects

Required: No

ResourceAwsEc2InstanceLaunchedAt

The date and time the instance was launched.

Type: Array of [DateFilter](#) objects

Required: No

ResourceAwsEc2InstanceSubnetId

The identifier of the subnet that the instance was launched in.

Type: Array of [StringFilter](#) objects

Required: No

ResourceAwsEc2InstanceType

The instance type of the instance.

Type: Array of [StringFilter](#) objects

Required: No

ResourceAwsEc2InstanceVpcId

The identifier of the VPC that the instance was launched in.

Type: Array of [StringFilter](#) objects

Required: No

ResourceAwsIamAccessKeyCreatedAt

The creation date/time of the IAM access key related to a finding.

Type: Array of [DateFilter](#) objects

Required: No

ResourceAwsIamAccessKeyPrincipalName

The name of the principal that is associated with an IAM access key.

Type: Array of [StringFilter](#) objects

Required: No

ResourceAwsIamAccessKeyStatus

The status of the IAM access key related to a finding.

Type: Array of [StringFilter](#) objects

Required: No

ResourceAwsIamAccessKeyUserName

This member has been deprecated.

The user associated with the IAM access key related to a finding.

Type: Array of [StringFilter](#) objects

Required: No

ResourceAwsIamUserUserName

The name of an IAM user.

Type: Array of [StringFilter](#) objects

Required: No

ResourceAwsS3BucketOwnerId

The canonical user ID of the owner of the S3 bucket.

Type: Array of [StringFilter](#) objects

Required: No

ResourceAwsS3BucketOwnerName

The display name of the owner of the S3 bucket.

Type: Array of [StringFilter](#) objects

Required: No

ResourceContainerImageId

The identifier of the image related to a finding.

Type: Array of [StringFilter](#) objects

Required: No

ResourceContainerImageName

The name of the image related to a finding.

Type: Array of [StringFilter](#) objects

Required: No

ResourceContainerLaunchedAt

A timestamp that identifies when the container was started.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: Array of [DateFilter](#) objects

Required: No

ResourceContainerName

The name of the container related to a finding.

Type: Array of [StringFilter](#) objects

Required: No

ResourceDetailsOther

The details of a resource that doesn't have a specific subfield for the resource type defined.

Type: Array of [MapFilter](#) objects

Required: No

ResourceId

The canonical identifier for the given resource type.

Type: Array of [StringFilter](#) objects

Required: No

ResourcePartition

The canonical Amazon partition name that the Region is assigned to.

Type: Array of [StringFilter](#) objects

Required: No

ResourceRegion

The canonical Amazon external Region name where this resource is located.

Type: Array of [StringFilter](#) objects

Required: No

ResourceTags

A list of Amazon tags associated with a resource at the time the finding was processed.

Type: Array of [MapFilter](#) objects

Required: No

ResourceType

Specifies the type of the resource that details are provided for.

Type: Array of [StringFilter](#) objects

Required: No

Sample

Indicates whether or not sample findings are included in the filter results.

Type: Array of [BooleanFilter](#) objects

Required: No

SeverityLabel

The label of a finding's severity.

Type: Array of [StringFilter](#) objects

Required: No

SeverityNormalized

This member has been deprecated.

The normalized severity of a finding.

Type: Array of [NumberFilter](#) objects

Required: No

SeverityProduct

This member has been deprecated.

The native severity as defined by the security findings provider's solution that generated the finding.

Type: Array of [NumberFilter](#) objects

Required: No

SourceUrl

A URL that links to a page about the current finding in the security findings provider's solution.

Type: Array of [StringFilter](#) objects

Required: No

ThreatIntelIndicatorCategory

The category of a threat intelligence indicator.

Type: Array of [StringFilter](#) objects

Required: No

ThreatIntelIndicatorLastObservedAt

A timestamp that identifies the last observation of a threat intelligence indicator.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: Array of [DateFilter](#) objects

Required: No

ThreatIntelIndicatorSource

The source of the threat intelligence.

Type: Array of [StringFilter](#) objects

Required: No

ThreatIntelIndicatorSourceUrl

The URL for more details from the source of the threat intelligence.

Type: Array of [StringFilter](#) objects

Required: No

ThreatIntelIndicatorType

The type of a threat intelligence indicator.

Type: Array of [StringFilter](#) objects

Required: No

ThreatIntelIndicatorValue

The value of a threat intelligence indicator.

Type: Array of [StringFilter](#) objects

Required: No

Title

A finding's title.

Type: Array of [StringFilter](#) objects

Required: No

Type

A finding type in the format of namespace/category/classifier that classifies a finding.

Type: Array of [StringFilter](#) objects

Required: No

UpdatedAt

A timestamp that indicates when the security findings provider last updated the finding record.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: Array of [DateFilter](#) objects

Required: No

UserDefinedFields

A list of name/value string pairs associated with the finding. These are custom, user-defined fields added to a finding.

Type: Array of [MapFilter](#) objects

Required: No

VerificationState

The veracity of a finding.

Type: Array of [StringFilter](#) objects

Required: No

VulnerabilitiesExploitAvailable

Indicates whether a software vulnerability in your environment has a known exploit. You can filter findings by this field only if you use Security Hub and Amazon Inspector.

Type: Array of [StringFilter](#) objects

Required: No

VulnerabilitiesFixAvailable

Indicates whether a vulnerability is fixed in a newer version of the affected software packages. You can filter findings by this field only if you use Security Hub and Amazon Inspector.

Type: Array of [StringFilter](#) objects

Required: No

WorkflowState

The workflow state of a finding.

Note that this field is deprecated. To search for a finding based on its workflow status, use `WorkflowStatus`.

Type: Array of [StringFilter](#) objects

Required: No

WorkflowStatus

The status of the investigation into a finding. Allowed values are the following.

- NEW - The initial state of a finding, before it is reviewed.

Security Hub also resets the workflow status from NOTIFIED or RESOLVED to NEW in the following cases:

- `RecordState` changes from ARCHIVED to ACTIVE.
- `Compliance.Status` changes from PASSED to either WARNING, FAILED, or NOT_AVAILABLE.
- NOTIFIED - Indicates that the resource owner has been notified about the security issue. Used when the initial reviewer is not the resource owner, and needs intervention from the resource owner.

If one of the following occurs, the workflow status is changed automatically from NOTIFIED to NEW:

- `RecordState` changes from ARCHIVED to ACTIVE.
- `Compliance.Status` changes from PASSED to FAILED, WARNING, or NOT_AVAILABLE.
- SUPPRESSED - Indicates that you reviewed the finding and don't believe that any action is needed.

The workflow status of a SUPPRESSED finding does not change if `RecordState` changes from ARCHIVED to ACTIVE.

- RESOLVED - The finding was reviewed and remediated and is now considered resolved.

The finding remains RESOLVED unless one of the following occurs:

- `RecordState` changes from `ARCHIVED` to `ACTIVE`.
- `Compliance.Status` changes from `PASSED` to `FAILED`, `WARNING`, or `NOT_AVAILABLE`.

In those cases, the workflow status is automatically reset to `NEW`.

For findings from controls, if `Compliance.Status` is `PASSED`, then Security Hub automatically sets the workflow status to `RESOLVED`.

Type: Array of [StringFilter](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsSecurityFindingIdentifier

Identifies which finding to get the finding history for.

Contents

Id

The identifier of the finding that was specified by the finding provider.

Type: String

Pattern: `.*\S.*`

Required: Yes

ProductArn

The ARN generated by Security Hub that uniquely identifies a product that generates findings. This can be the ARN for a third-party product that is integrated with Security Hub, or the ARN for a custom integration.

Type: String

Pattern: `.*\S.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BatchUpdateFindingsUnprocessedFinding

A finding from a BatchUpdateFindings request that Security Hub was unable to update.

Contents

ErrorCode

The code associated with the error. Possible values are:

- `ConcurrentUpdateError` - Another request attempted to update the finding while this request was being processed. This error may also occur if you call [BatchUpdateFindings](#) and [BatchImportFindings](#) at the same time.
- `DuplicatedFindingIdentifier` - The request included two or more findings with the same `FindingIdentifier`.
- `FindingNotFound` - The `FindingIdentifier` included in the request did not match an existing finding.
- `FindingSizeExceeded` - The finding size was greater than the permissible value of 240 KB.
- `InternalFailure` - An internal service failure occurred when updating the finding.
- `InvalidInput` - The finding update contained an invalid value that did not satisfy the [Amazon Security Finding Format](#) syntax.

Type: String

Pattern: `.*\S.*`

Required: Yes

ErrorMessage

The message associated with the error. Possible values are:

- Concurrent finding updates detected
- Finding Identifier is duplicated
- Finding Not Found
- Finding size exceeded 240 KB
- Internal service failure
- Invalid Input

Type: String

Pattern: `.*\S.*`

Required: Yes

FindingIdentifier

The identifier of the finding that was not updated.

Type: [AwsSecurityFindingIdentifier](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BooleanConfigurationOptions

The options for customizing a security control parameter with a boolean. For a boolean parameter, the options are `true` and `false`.

Contents

DefaultValue

The Security Hub default value for a boolean parameter.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BooleanFilter

Boolean filter for querying findings.

Contents

Value

The value of the boolean.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Cell

An occurrence of sensitive data detected in a Microsoft Excel workbook, comma-separated value (CSV) file, or tab-separated value (TSV) file.

Contents

CellReference

For a Microsoft Excel workbook, provides the location of the cell, as an absolute cell reference, that contains the data. For example, Sheet2!C5 for cell C5 on Sheet2.

Type: String

Pattern: .*\\S.*

Required: No

Column

The column number of the column that contains the data. For a Microsoft Excel workbook, the column number corresponds to the alphabetical column identifiers. For example, a value of 1 for Column corresponds to the A column in the workbook.

Type: Long

Required: No

ColumnName

The name of the column that contains the data.

Type: String

Pattern: .*\\S.*

Required: No

Row

The row number of the row that contains the data.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

City

Information about a city.

Contents

CityName

The name of the city.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ClassificationResult

Details about the sensitive data that was detected on the resource.

Contents

AdditionalOccurrences

Indicates whether there are additional occurrences of sensitive data that are not included in the finding. This occurs when the number of occurrences exceeds the maximum that can be included.

Type: Boolean

Required: No

CustomDataIdentifiers

Provides details about sensitive data that was identified based on customer-defined configuration.

Type: [CustomDataIdentifiersResult](#) object

Required: No

MimeType

The type of content that the finding applies to.

Type: String

Pattern: .*\\S.*

Required: No

SensitiveData

Provides details about sensitive data that was identified based on built-in configuration.

Type: Array of [SensitiveDataResult](#) objects

Required: No

SizeClassified

The total size in bytes of the affected data.

Type: Long

Required: No

Status

The current status of the sensitive data detection.

Type: [ClassificationStatus](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ClassificationStatus

Provides details about the current status of the sensitive data detection.

Contents

Code

The code that represents the status of the sensitive data detection.

Type: String

Pattern: `.*\S.*`

Required: No

Reason

A longer description of the current status of the sensitive data detection.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

CodeVulnerabilitiesFilePath

Provides details about where a code vulnerability is located in your Amazon Lambda function.

Contents

EndLine

The line number of the last line of code in which the vulnerability is located.

Type: Integer

Required: No

FileName

The name of the file in which the code vulnerability is located.

Type: String

Pattern: `.*\S.*`

Required: No

FilePath

The file path to the code in which the vulnerability is located.

Type: String

Pattern: `.*\S.*`

Required: No

StartLine

The line number of the first line of code in which the vulnerability is located.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Compliance

This object typically provides details about a control finding, such as applicable standards and the status of control checks. While finding providers can add custom content in Compliance object fields, they are typically used to review details of Security Hub control findings.

Contents

AssociatedStandards

Typically provides an array of enabled security standards in which a security control is currently enabled.

Type: Array of [AssociatedStandard](#) objects

Required: No

RelatedRequirements

Typically provides the industry or regulatory framework requirements that are related to a control. The check for that control is aligned with these requirements.

Array Members: Maximum number of 32 items.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

SecurityControlId

Typically provides the unique identifier of a control across standards. For Security Hub controls, this field consists of an Amazon Web Services service and a unique number, such as `APIGateway.5`.

Type: String

Pattern: `.*\S.*`

Required: No

SecurityControlParameters

Typically an object that includes security control parameter names and values.

Type: Array of [SecurityControlParameter](#) objects

Required: No

Status

Typically summarizes the result of a control check.

For Security Hub controls, valid values for Status are as follows.

- PASSED - Standards check passed for all evaluated resources.
- WARNING - Some information is missing or this check is not supported for your configuration.
- FAILED - Standards check failed for at least one evaluated resource.
- NOT_AVAILABLE - Check could not be performed due to a service outage, API error, or because the result of the Amazon Config evaluation was NOT_APPLICABLE. If the Amazon Config evaluation result was NOT_APPLICABLE for a Security Hub control, Security Hub automatically archives the finding after 3 days.

Type: String

Valid Values: PASSED | WARNING | FAILED | NOT_AVAILABLE

Required: No

StatusReasons

Typically used to provide a list of reasons for the value of Status.

Type: Array of [StatusReason](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ConfigurationOptions

The options for customizing a security control parameter.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

Boolean

The options for customizing a security control parameter that is a boolean. For a boolean parameter, the options are `true` and `false`.

Type: [BooleanConfigurationOptions](#) object

Required: No

Double

The options for customizing a security control parameter that is a double.

Type: [DoubleConfigurationOptions](#) object

Required: No

Enum

The options for customizing a security control parameter that is an enum.

Type: [EnumConfigurationOptions](#) object

Required: No

EnumList

The options for customizing a security control parameter that is a list of enums.

Type: [EnumListConfigurationOptions](#) object

Required: No

Integer

The options for customizing a security control parameter that is an integer.

Type: [IntegerConfigurationOptions](#) object

Required: No

IntegerList

The options for customizing a security control parameter that is a list of integers.

Type: [IntegerListConfigurationOptions](#) object

Required: No

String

The options for customizing a security control parameter that is a string data type.

Type: [StringConfigurationOptions](#) object

Required: No

StringList

The options for customizing a security control parameter that is a list of strings.

Type: [StringListConfigurationOptions](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ConfigurationPolicyAssociation

Provides details about the association between an Amazon Security Hub configuration and a target account, organizational unit, or the root. An association can exist between a target and a configuration policy, or between a target and self-managed behavior.

Contents

Target

The target account, organizational unit, or the root.

Type: [Target](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ConfigurationPolicyAssociationSummary

An object that contains the details of a configuration policy association that's returned in a `ListConfigurationPolicyAssociations` request.

Contents

AssociationStatus

The current status of the association between the specified target and the configuration.

Type: String

Valid Values: PENDING | SUCCESS | FAILED

Required: No

AssociationStatusMessage

The explanation for a FAILED value for `AssociationStatus`.

Type: String

Pattern: `.*\S.*`

Required: No

AssociationType

Indicates whether the association between the specified target and the configuration was directly applied by the Amazon Security Hub delegated administrator or inherited from a parent.

Type: String

Valid Values: INHERITED | APPLIED

Required: No

ConfigurationPolicyId

The universally unique identifier (UUID) of the configuration policy.

Type: String

Pattern: `.*\S.*`

Required: No

TargetId

The identifier of the target account, organizational unit, or the root.

Type: String

Pattern: `.*\S.*`

Required: No

TargetType

Specifies whether the target is an Amazon Web Services account, organizational unit, or the root.

Type: String

Valid Values: ACCOUNT | ORGANIZATIONAL_UNIT | ROOT

Required: No

UpdatedAt

The date and time, in UTC and ISO 8601 format, that the configuration policy association was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ConfigurationPolicySummary

An object that contains the details of an Amazon Security Hub configuration policy that's returned in a `ListConfigurationPolicies` request.

Contents

Arn

The Amazon Resource Name (ARN) of the configuration policy.

Type: String

Pattern: `.*\S.*`

Required: No

Description

The description of the configuration policy.

Type: String

Pattern: `.*\S.*`

Required: No

Id

The universally unique identifier (UUID) of the configuration policy.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the configuration policy. Alphanumeric characters and the following ASCII characters are permitted: `-`, `.`, `!`, `*`, `/`.

Type: String

Pattern: `.*\S.*`

Required: No

ServiceEnabled

Indicates whether the service that the configuration policy applies to is enabled in the policy.

Type: Boolean

Required: No

UpdatedAt

The date and time, in UTC and ISO 8601 format, that the configuration policy was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Country

Information about a country.

Contents

CountryCode

The 2-letter ISO 3166 country code for the country.

Type: String

Pattern: `.*\S.*`

Required: No

CountryName

The name of the country.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

CustomDataIdentifiersDetections

The list of detected instances of sensitive data.

Contents

Arn

The ARN of the custom identifier that was used to detect the sensitive data.

Type: String

Pattern: `.*\S.*`

Required: No

Count

The total number of occurrences of sensitive data that were detected.

Type: Long

Required: No

Name

The name of the custom identifier that detected the sensitive data.

Type: String

Pattern: `.*\S.*`

Required: No

Occurrences

Details about the sensitive data that was detected.

Type: [Occurrences](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

CustomDataIdentifiersResult

Contains an instance of sensitive data that was detected by a customer-defined identifier.

Contents

Detections

The list of detected instances of sensitive data.

Type: Array of [CustomDataIdentifiersDetections](#) objects

Required: No

TotalCount

The total number of occurrences of sensitive data.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Cvss

CVSS scores from the advisory related to the vulnerability.

Contents

Adjustments

Adjustments to the CVSS metrics.

Type: Array of [Adjustment](#) objects

Required: No

BaseScore

The base CVSS score.

Type: Double

Required: No

BaseVector

The base scoring vector for the CVSS score.

Type: String

Pattern: `.*\S.*`

Required: No

Source

The origin of the original CVSS score and vector.

Type: String

Pattern: `.*\S.*`

Required: No

Version

The version of CVSS for the CVSS score.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DataClassificationDetails

Provides details about sensitive data that was detected on a resource.

Contents

DetailedResultsLocation

The path to the folder or file that contains the sensitive data.

Type: String

Pattern: .*\\S.*

Required: No

Result

The details about the sensitive data that was detected on the resource.

Type: [ClassificationResult](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DateFilter

A date filter for querying findings.

Contents

DateRange

A date range for the date filter.

Type: [DateRange](#) object

Required: No

End

A timestamp that provides the end date for the date filter.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

Start

A timestamp that provides the start date for the date filter.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DateRange

A date range for the date filter.

Contents

Unit

A date range unit for the date filter.

Type: String

Valid Values: DAYS

Required: No

Value

A date range value for the date filter.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Detection

A top-level object field that provides details about an Amazon GuardDuty Extended Threat Detection attack sequence. GuardDuty generates an attack sequence finding when multiple events align to a potentially suspicious activity. To receive GuardDuty attack sequence findings in Amazon Security Hub, you must have GuardDuty enabled. For more information, see [GuardDuty Extended Threat Detection](#) in the *Amazon GuardDuty User Guide*.

Contents

Sequence

Provides details about an attack sequence.

Type: [Sequence](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DnsRequestAction

Provided if `ActionType` is `DNS_REQUEST`. It provides details about the DNS request that was detected.

Contents

Blocked

Indicates whether the DNS request was blocked.

Type: Boolean

Required: No

Domain

The DNS domain that is associated with the DNS request.

Length Constraints: 128.

Type: String

Pattern: `.*\S.*`

Required: No

Protocol

The protocol that was used for the DNS request.

Length Constraints: Minimum length of 1. Maximum length of 64.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DoubleConfigurationOptions

The options for customizing a security control parameter that is a double.

Contents

DefaultValue

The Security Hub default value for a control parameter that is a double.

Type: Double

Required: No

Max

The maximum valid value for a control parameter that is a double.

Type: Double

Required: No

Min

The minimum valid value for a control parameter that is a double.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

EnumConfigurationOptions

The options for customizing a security control parameter that is an enum.

Contents

AllowedValues

The valid values for a control parameter that is an enum.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

DefaultValue

The Security Hub default value for a control parameter that is an enum.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

EnumListConfigurationOptions

The options for customizing a security control parameter that is a list of enums.

Contents

AllowedValues

The valid values for a control parameter that is a list of enums.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

DefaultValue

The Security Hub default value for a control parameter that is a list of enums.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

MaxItems

The maximum number of list items that an enum list control parameter can accept.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

FilePaths

Provides information about the file paths that were affected by the threat.

Contents

FileName

The name of the infected or suspicious file corresponding to the hash.

Length Constraints: Minimum of 1 length. Maximum of 128 length.

Type: String

Pattern: .*\\S.*

Required: No

FilePath

Path to the infected or suspicious file on the resource it was detected on.

Length Constraints: Minimum of 1 length. Maximum of 128 length.

Type: String

Pattern: .*\\S.*

Required: No

Hash

The hash value for the infected or suspicious file.

Length Constraints: Minimum of 1 length. Maximum of 128 length.

Type: String

Pattern: .*\\S.*

Required: No

ResourceId

The Amazon Resource Name (ARN) of the resource on which the threat was detected.

Length Constraints: Minimum of 1 length. Maximum of 128 length.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

FindingAggregator

A finding aggregator is a Security Hub resource that specifies cross-Region aggregation settings, including the home Region and any linked Regions.

Contents

FindingAggregatorArn

The ARN of the finding aggregator. You use the finding aggregator ARN to retrieve details for, update, and delete the finding aggregator.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

FindingHistoryRecord

A list of events that changed the specified finding during the specified time period. Each record represents a single finding change event.

Contents

FindingCreated

Identifies whether the event marks the creation of a new finding. A value of `True` means that the finding is newly created. A value of `False` means that the finding isn't newly created.

Type: Boolean

Required: No

FindingIdentifier

Identifies which finding to get the finding history for.

Type: [AwsSecurityFindingIdentifier](#) object

Required: No

NextToken

A token for pagination purposes. Provide this token in the subsequent request to [GetFindingsHistory](#) to get up to an additional 100 results of history for the same finding that you specified in your initial request.

Type: String

Required: No

Updates

An array of objects that provides details about the finding change event, including the Amazon Security Finding Format (ASFF) field that changed, the value of the field before the change, and the value of the field after the change.

Type: Array of [FindingHistoryUpdate](#) objects

Required: No

UpdateSource

Identifies the source of the event that changed the finding. For example, an integrated Amazon Web Services service or third-party partner integration may call [BatchImportFindings](#), or an Amazon Security Hub customer may call [BatchUpdateFindings](#).

Type: [FindingHistoryUpdateSource](#) object

Required: No

UpdateTime

A timestamp that indicates when Security Hub processed the updated finding record.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

FindingHistoryUpdate

An array of objects that provides details about a change to a finding, including the Amazon Security Finding Format (ASFF) field that changed, the value of the field before the change, and the value of the field after the change.

Contents

NewValue

The value of the ASFF field after the finding change event. To preserve storage and readability, Security Hub omits this value if [FindingHistoryRecord](#) exceeds database limits.

Type: String

Pattern: `.*\S.*`

Required: No

OldValue

The value of the ASFF field before the finding change event.

Type: String

Pattern: `.*\S.*`

Required: No

UpdatedField

The ASFF field that changed during the finding change event.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

FindingHistoryUpdateSource

Identifies the source of the finding change event.

Contents

Identity

The identity of the source that initiated the finding change event. For example, the Amazon Resource Name (ARN) of a partner that calls `BatchImportFindings` or of a customer that calls `BatchUpdateFindings`.

Type: String

Pattern: `.*\S.*`

Required: No

Type

Describes the type of finding change event, such as a call to [BatchImportFindings](#) (by an integrated Amazon Web Services service or third party partner integration) or [BatchUpdateFindings](#) (by a Security Hub customer).

Type: String

Valid Values: `BATCH_UPDATE_FINDINGS` | `BATCH_IMPORT_FINDINGS`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

FindingProviderFields

In a [BatchImportFindings](#) request, finding providers use `FindingProviderFields` to provide and update values for the following fields:

- Confidence
- Criticality
- RelatedFindings
- Severity
- Types

The preceding fields are nested under the `FindingProviderFields` object, but also have analogues of the same name as top-level ASFF fields. When a new finding is sent to Amazon Security Hub by a finding provider, Security Hub populates the `FindingProviderFields` object automatically, if it is empty, based on the corresponding top-level fields.

Finding providers can update `FindingProviderFields` only by using the `BatchImportFindings` operation. Finding providers can't update this object with the [BatchUpdateFindings](#) operation. Customers can update the top-level fields by using the `BatchUpdateFindings` operation. Customers can't update `FindingProviderFields`.

For information about how Security Hub handles updates from `BatchImportFindings` to `FindingProviderFields` and to the corresponding top-level attributes, see [Using FindingProviderFields](#) in the *Amazon Security Hub User Guide*.

Contents

Confidence

A finding's confidence. Confidence is defined as the likelihood that a finding accurately identifies the behavior or issue that it was intended to identify.

Confidence is scored on a 0-100 basis using a ratio scale, where 0 means zero percent confidence and 100 means 100 percent confidence.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

Criticality

The level of importance assigned to the resources associated with the finding.

A score of 0 means that the underlying resources have no criticality, and a score of 100 is reserved for the most critical resources.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

RelatedFindings

A list of findings that are related to the current finding.

Type: Array of [RelatedFinding](#) objects

Required: No

Severity

The severity of a finding.

Type: [FindingProviderSeverity](#) object

Required: No

Types

One or more finding types in the format of `namespace/category/classifier` that classify a finding.

Valid namespace values are: Software and Configuration Checks | TTPs | Effects | Unusual Behaviors | Sensitive Data Identifications

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

FindingProviderSeverity

The severity assigned to a finding by the finding provider. This object may include one or more of the following attributes:

- Label
- Normalized
- Original
- Product

If a [BatchImportFindings](#) request for a new finding only provides Label or only provides Normalized, Amazon Security Hub automatically populates the value of the other field.

The Normalized and Product attributes are included in the FindingProviderSeverity structure to preserve the historical information associated with the finding, even if the top-level Severity object is later modified using the [BatchUpdateFindings](#) operation.

If the top-level Finding.Severity object is present, but Finding.FindingProviderFields isn't present, Security Hub creates the FindingProviderFields.Severity object and copies the entire Finding.Severity object into it. This ensures that the original, provider-supplied details are retained within the FindingProviderFields.Severity object, even if the top-level Severity object is overwritten.

Contents

Label

The severity label assigned to the finding by the finding provider.

Type: String

Valid Values: INFORMATIONAL | LOW | MEDIUM | HIGH | CRITICAL

Required: No

Original

The finding provider's original value for the severity.

Length Constraints: Minimum length of 1. Maximum length of 64.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

GeneratorDetails

Provides metadata for the Amazon CodeGuru detector associated with a finding. This field pertains to findings that relate to Amazon Lambda functions. Amazon Inspector identifies policy violations and vulnerabilities in Lambda function code based on internal detectors developed in collaboration with Amazon CodeGuru. Amazon Security Hub receives those findings.

Contents

Description

The description of the detector used to identify the code vulnerability.

Type: String

Pattern: `.*\S.*`

Required: No

Labels

An array of tags used to identify the detector associated with the finding.

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Name

The name of the detector used to identify the code vulnerability.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

GeoLocation

Provides the latitude and longitude coordinates of a location.

Contents

Lat

The latitude of the location.

Type: Double

Required: No

Lon

The longitude of the location.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

IcmpTypeCode

An Internet Control Message Protocol (ICMP) type and code.

Contents

Code

The ICMP code for which to deny or allow access. To deny or allow all codes, use the value -1.

Type: Integer

Required: No

Type

The ICMP type for which to deny or allow access. To deny or allow all types, use the value -1.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ImportFindingsError

The list of the findings that cannot be imported. For each finding, the list provides the error.

Contents

ErrorCode

The code of the error returned by the BatchImportFindings operation.

Type: String

Pattern: `.*\S.*`

Required: Yes

ErrorMessage

The message of the error returned by the BatchImportFindings operation.

Type: String

Pattern: `.*\S.*`

Required: Yes

Id

The identifier of the finding that could not be updated.

Type: String

Pattern: `.*\S.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

Indicator

Contains information about the indicators observed in an Amazon GuardDuty Extended Threat Detection attack sequence. Indicators include a set of signals, which can be API activities or findings that GuardDuty uses to detect an attack sequence finding. GuardDuty generates an attack sequence finding when multiple signals align to a potentially suspicious activity. To receive GuardDuty attack sequence findings in Amazon Security Hub, you must have GuardDuty and GuardDuty S3 Protection enabled. For more information, see [GuardDuty Extended Threat Detection](#) in the *Amazon GuardDuty User Guide*.

Contents

Key

The name of the indicator that's present in the attack sequence finding.

Type: String

Pattern: `.*\S.*`

Required: No

Title

The title describing the indicator.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The type of indicator.

Type: String

Pattern: `.*\S.*`

Required: No

Values

Values associated with each indicator key. For example, if the indicator key is `SUSPICIOUS_NETWORK`, then the value will be the name of the network. If the indicator key is `ATTACK_TACTIC`, then the value will be one of the MITRE tactics.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Insight

Contains information about a Security Hub insight.

Contents

Filters

One or more attributes used to filter the findings included in the insight. You can filter by up to ten finding attributes. For each attribute, you can provide up to 20 filter values. The insight only includes findings that match the criteria defined in the filters.

Type: [AwsSecurityFindingFilters](#) object

Required: Yes

GroupByAttribute

The grouping attribute for the insight's findings. Indicates how to group the matching findings, and identifies the type of item that the insight applies to. For example, if an insight is grouped by resource identifier, then the insight produces a list of resource identifiers.

Type: String

Pattern: `.*\S.*`

Required: Yes

InsightArn

The ARN of a Security Hub insight.

Type: String

Pattern: `.*\S.*`

Required: Yes

Name

The name of a Security Hub insight.

Type: String

Pattern: `.*\S.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

InsightResults

The insight results returned by the `GetInsightResults` operation.

Contents

GroupByAttribute

The attribute that the findings are grouped by for the insight whose results are returned by the `GetInsightResults` operation.

Type: String

Pattern: `.*\S.*`

Required: Yes

InsightArn

The ARN of the insight whose results are returned by the `GetInsightResults` operation.

Type: String

Pattern: `.*\S.*`

Required: Yes

ResultValues

The list of insight result values returned by the `GetInsightResults` operation.

Type: Array of [InsightResultValue](#) objects

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

InsightResultValue

The insight result values returned by the `GetInsightResults` operation.

Contents

Count

The number of findings returned for each `GroupByAttributeValue`.

Type: Integer

Required: Yes

GroupByAttributeValue

The value of the attribute that the findings are grouped by for the insight whose results are returned by the `GetInsightResults` operation.

Type: String

Pattern: `.*\S.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

IntegerConfigurationOptions

The options for customizing a security control parameter that is an integer.

Contents

DefaultValue

The Security Hub default value for a control parameter that is an integer.

Type: Integer

Required: No

Max

The maximum valid value for a control parameter that is an integer.

Type: Integer

Required: No

Min

The minimum valid value for a control parameter that is an integer.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

IntegerListConfigurationOptions

The options for customizing a security control parameter that is a list of integers.

Contents

DefaultValue

The Security Hub default value for a control parameter that is a list of integers.

Type: Array of integers

Required: No

Max

The maximum valid value for a control parameter that is a list of integers.

Type: Integer

Required: No

MaxItems

The maximum number of list items that an interger list control parameter can accept.

Type: Integer

Required: No

Min

The minimum valid value for a control parameter that is a list of integers.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Invitation

Details about an invitation.

Contents

AccountId

The account ID of the Security Hub administrator account that the invitation was sent from.

Type: String

Required: No

InvitationId

The ID of the invitation sent to the member account.

Type: String

Pattern: `.*\S.*`

Required: No

InvitedAt

The timestamp of when the invitation was sent.

Type: Timestamp

Required: No

MemberStatus

The current status of the association between the member and administrator accounts.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

IpFilter

The IP filter for querying findings.

Contents

Cidr

A finding's CIDR value.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

IpOrganizationDetails

Provides information about an internet provider.

Contents

Asn

The Autonomous System Number (ASN) of the internet provider

Type: Integer

Required: No

AsnOrg

The name of the organization that registered the ASN.

Type: String

Pattern: .*\\S.*

Required: No

Isp

The ISP information for the internet provider.

Type: String

Pattern: .*\\S.*

Required: No

Org

The name of the internet provider.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

KeywordFilter

A keyword filter for querying findings.

Contents

Value

A value for the keyword.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Malware

A list of malware related to a finding.

Contents

Name

The name of the malware that was observed.

Length Constraints: Minimum of 1. Maximum of 64.

Type: String

Pattern: `.*\S.*`

Required: Yes

Path

The file system path of the malware that was observed.

Length Constraints: Minimum of 1. Maximum of 512.

Type: String

Pattern: `.*\S.*`

Required: No

State

The state of the malware that was observed.

Type: String

Valid Values: OBSERVED | REMOVAL_FAILED | REMOVED

Required: No

Type

The type of the malware that was observed.

Type: String

Valid Values: ADWARE | BLENDED_THREAT | BOTNET_AGENT | COIN_MINER | EXPLOIT_KIT | KEYLOGGER | MACRO | POTENTIALLY_UNWANTED | SPYWARE | RANSOMWARE | REMOTE_ACCESS | ROOTKIT | TROJAN | VIRUS | WORM

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

MapFilter

A map filter for filtering Amazon Security Hub findings. Each map filter provides the field to check for, the value to check for, and the comparison operator.

Contents

Comparison

The condition to apply to the key value when filtering Security Hub findings with a map filter.

To search for values that have the filter value, use one of the following comparison operators:

- To search for values that include the filter value, use `CONTAINS`. For example, for the `ResourceTags` field, the filter `Department CONTAINS Security` matches findings that include the value `Security` for the `Department` tag. In the same example, a finding with a value of `Security team` for the `Department` tag is a match.
- To search for values that exactly match the filter value, use `EQUALS`. For example, for the `ResourceTags` field, the filter `Department EQUALS Security` matches findings that have the value `Security` for the `Department` tag.

`CONTAINS` and `EQUALS` filters on the same field are joined by `OR`. A finding matches if it matches any one of those filters. For example, the filters `Department CONTAINS Security` `OR` `Department CONTAINS Finance` match a finding that includes either `Security`, `Finance`, or both values.

To search for values that don't have the filter value, use one of the following comparison operators:

- To search for values that exclude the filter value, use `NOT_CONTAINS`. For example, for the `ResourceTags` field, the filter `Department NOT_CONTAINS Finance` matches findings that exclude the value `Finance` for the `Department` tag.
- To search for values other than the filter value, use `NOT_EQUALS`. For example, for the `ResourceTags` field, the filter `Department NOT_EQUALS Finance` matches findings that don't have the value `Finance` for the `Department` tag.

`NOT_CONTAINS` and `NOT_EQUALS` filters on the same field are joined by `AND`. A finding matches only if it matches all of those filters. For example, the filters `Department NOT_CONTAINS Security` `AND` `Department NOT_CONTAINS Finance` match a finding that excludes both the `Security` and `Finance` values.

CONTAINS filters can only be used with other CONTAINS filters. NOT_CONTAINS filters can only be used with other NOT_CONTAINS filters.

You can't have both a CONTAINS filter and a NOT_CONTAINS filter on the same field. Similarly, you can't have both an EQUALS filter and a NOT_EQUALS filter on the same field. Combining filters in this way returns an error.

CONTAINS and NOT_CONTAINS operators can be used only with automation rules. For more information, see [Automation rules](#) in the *Amazon Security Hub User Guide*.

Type: String

Valid Values: EQUALS | NOT_EQUALS | CONTAINS | NOT_CONTAINS

Required: No

Key

The key of the map filter. For example, for ResourceTags, Key identifies the name of the tag. For UserDefinedFields, Key is the name of the field.

Type: String

Pattern: `.*\S.*`

Required: No

Value

The value for the key in the map filter. Filter values are case sensitive. For example, one of the values for a tag called Department might be Security. If you provide security as the filter value, then there's no match.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Member

The details about a member account.

Contents

AccountId

The Amazon Web Services account ID of the member account.

Type: String

Required: No

AdministratorId

The Amazon Web Services account ID of the Security Hub administrator account associated with this member account.

Type: String

Pattern: `.*\S.*`

Required: No

Email

The email address of the member account.

Type: String

Pattern: `.*\S.*`

Required: No

InvitedAt

A timestamp for the date and time when the invitation was sent to the member account.

Type: Timestamp

Required: No

MasterId

This member has been deprecated.

This is replaced by `AdministratorID`.

The Amazon Web Services account ID of the Security Hub administrator account associated with this member account.

Type: String

Pattern: `.*\S.*`

Required: No

MemberStatus

The status of the relationship between the member account and its administrator account.

The status can have one of the following values:

- `Created` - Indicates that the administrator account added the member account, but has not yet invited the member account.
- `Invited` - Indicates that the administrator account invited the member account. The member account has not yet responded to the invitation.
- `Enabled` - Indicates that the member account is currently active. For manually invited member accounts, indicates that the member account accepted the invitation.
- `Removed` - Indicates that the administrator account disassociated the member account.
- `Resigned` - Indicates that the member account disassociated themselves from the administrator account.
- `Deleted` - Indicates that the administrator account deleted the member account.
- `AccountSuspended` - Indicates that an organization account was suspended from Amazon at the same time that the administrator account tried to enable the organization account as a member account.

Type: String

Pattern: `.*\S.*`

Required: No

UpdatedAt

The timestamp for the date and time when the member account was updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Network

The details of network-related information about a finding.

Contents

DestinationDomain

The destination domain of network-related information about a finding.

Length Constraints: Minimum of 1. Maximum of 128.

Type: String

Pattern: `.*\S.*`

Required: No

DestinationIPv4

The destination IPv4 address of network-related information about a finding.

Type: String

Pattern: `.*\S.*`

Required: No

DestinationIPv6

The destination IPv6 address of network-related information about a finding.

Type: String

Pattern: `.*\S.*`

Required: No

DestinationPort

The destination port of network-related information about a finding.

Type: Integer

Required: No

Direction

The direction of network traffic associated with a finding.

Type: String

Valid Values: IN | OUT

Required: No

OpenPortRange

The range of open ports that is present on the network.

Type: [PortRange](#) object

Required: No

Protocol

The protocol of network-related information about a finding.

Length Constraints: Minimum of 1. Maximum of 16.

Type: String

Pattern: .*\\S.*

Required: No

SourceDomain

The source domain of network-related information about a finding.

Length Constraints: Minimum of 1. Maximum of 128.

Type: String

Pattern: .*\\S.*

Required: No

SourceIpV4

The source IPv4 address of network-related information about a finding.

Type: String

Pattern: `.*\S.*`

Required: No

SourceIpV6

The source IPv6 address of network-related information about a finding.

Type: String

Pattern: `.*\S.*`

Required: No

SourceMac

The source media access control (MAC) address of network-related information about a finding.

Type: String

Pattern: `.*\S.*`

Required: No

SourcePort

The source port of network-related information about a finding.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

NetworkAutonomousSystem

Contains information about the Autonomous System (AS) of the network endpoints involved in an Amazon GuardDuty Extended Threat Detection attack sequence. GuardDuty generates an attack sequence finding when multiple events align to a potentially suspicious activity. To receive GuardDuty attack sequence findings in Amazon Security Hub, you must have GuardDuty enabled. For more information, see [GuardDuty Extended Threat Detection](#) in the *Amazon GuardDuty User Guide*.

Contents

Name

The name associated with the AS.

Type: String

Pattern: `.*\S.*`

Required: No

Number

The unique number that identifies the AS.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

NetworkConnection

Contains information about the network connection involved in an Amazon GuardDuty Extended Threat Detection attack sequence. GuardDuty generates an attack sequence finding when multiple events align to a potentially suspicious activity. To receive GuardDuty attack sequence findings in Amazon Security Hub, you must have GuardDuty enabled. For more information, see [GuardDuty Extended Threat Detection](#) in the *Amazon GuardDuty User Guide*.

Contents

Direction

The direction in which the network traffic is flowing.

Type: String

Valid Values: INBOUND | OUTBOUND

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

NetworkConnectionAction

Provided if `ActionType` is `NETWORK_CONNECTION`. It provides details about the attempted network connection that was detected.

Contents

Blocked

Indicates whether the network connection attempt was blocked.

Type: Boolean

Required: No

ConnectionDirection

The direction of the network connection request (IN or OUT).

Type: String

Pattern: `.*\S.*`

Required: No

LocalPortDetails

Information about the port on the EC2 instance.

Type: [ActionLocalPortDetails](#) object

Required: No

Protocol

The protocol used to make the network connection request.

Length Constraints: Minimum length of 1. Maximum length of 64.

Type: String

Pattern: `.*\S.*`

Required: No

RemoteIpDetails

Information about the remote IP address that issued the network connection request.

Type: [ActionRemoteIpDetails](#) object

Required: No

RemotePortDetails

Information about the port on the remote IP address.

Type: [ActionRemotePortDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

NetworkEndpoint

Contains information about network endpoints involved in an Amazon GuardDuty Extended Threat Detection attack sequence. GuardDuty generates an attack sequence finding when multiple events align to a potentially suspicious activity. To receive GuardDuty attack sequence findings in Amazon Security Hub, you must have GuardDuty enabled. For more information, see [GuardDuty Extended Threat Detection](#) in the *Amazon GuardDuty User Guide*.

This field can provide information about the network endpoints associated with the resource in the attack sequence finding, or about a specific network endpoint used for the attack.

Contents

AutonomousSystem

The Autonomous System Number (ASN) of the network endpoint.

Type: [NetworkAutonomousSystem](#) object

Required: No

Connection

Information about the network connection.

Type: [NetworkConnection](#) object

Required: No

Domain

The domain information for the network endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

Id

The identifier of the network endpoint involved in the attack sequence.

Type: String

Pattern: .*\\S.*

Required: No

Ip

The IP address used in the network endpoint.

Type: String

Pattern: .*\\S.*

Required: No

Location

Information about the location of the network endpoint.

Type: [NetworkGeoLocation](#) object

Required: No

Port

The port number associated with the network endpoint.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

NetworkGeoLocation

Contains information about the location of a network endpoint involved in an Amazon GuardDuty Extended Threat Detection attack sequence. GuardDuty generates an attack sequence finding when multiple events align to a potentially suspicious activity. To receive GuardDuty attack sequence findings in Amazon Security Hub, you must have GuardDuty enabled. For more information, see [GuardDuty Extended Threat Detection](#) in the *Amazon GuardDuty User Guide*.

Contents

City

The name of the city.

Type: String

Pattern: `.*\S.*`

Required: No

Country

The name of the country.

Type: String

Pattern: `.*\S.*`

Required: No

Lat

The latitude information of the endpoint location.

Type: Double

Required: No

Lon

The longitude information of the endpoint location.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

NetworkPathComponent

Information about a network path component.

Contents

ComponentId

The identifier of a component in the network path.

Length Constraints: Minimum of 1. Maximum of 32.

Type: String

Pattern: `.*\S.*`

Required: No

ComponentType

The type of component.

Length Constraints: Minimum of 1. Maximum of 32.

Type: String

Pattern: `.*\S.*`

Required: No

Egress

Information about the component that comes after the current component in the network path.

Type: [NetworkHeader](#) object

Required: No

Ingress

Information about the component that comes before the current node in the network path.

Type: [NetworkHeader](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

NetworkPathComponentDetails

Information about the destination of the next component in the network path.

Contents

Address

The IP addresses of the destination.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

PortRanges

A list of port ranges for the destination.

Type: Array of [PortRange](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Note

A user-defined note added to a finding.

Contents

Text

The text of a note.

Length Constraints: Minimum of 1. Maximum of 512.

Type: String

Pattern: `.*\S.*`

Required: Yes

UpdatedAt

A timestamp that indicates when the note was updated.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: Yes

UpdatedBy

The principal that created a note.

Type: String

Pattern: `.*\S.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

NoteUpdate

The updated note.

Contents

Text

The updated note text.

Type: String

Pattern: `.*\S.*`

Required: Yes

UpdatedBy

The principal that updated the note.

Type: String

Pattern: `.*\S.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

NumberFilter

A number filter for querying findings.

Contents

Eq

The equal-to condition to be applied to a single field when querying for findings.

Type: Double

Required: No

Gt

The greater-than condition to be applied to a single field when querying for findings.

Type: Double

Required: No

Gte

The greater-than-equal condition to be applied to a single field when querying for findings.

Type: Double

Required: No

Lt

The less-than condition to be applied to a single field when querying for findings.

Type: Double

Required: No

Lte

The less-than-equal condition to be applied to a single field when querying for findings.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Occurrences

The detected occurrences of sensitive data.

Contents

Cells

Occurrences of sensitive data detected in Microsoft Excel workbooks, comma-separated value (CSV) files, or tab-separated value (TSV) files.

Type: Array of [Cell](#) objects

Required: No

LineRanges

Occurrences of sensitive data detected in a non-binary text file or a Microsoft Word file. Non-binary text files include files such as HTML, XML, JSON, and TXT files.

Type: Array of [Range](#) objects

Required: No

OffsetRanges

Occurrences of sensitive data detected in a binary text file.

Type: Array of [Range](#) objects

Required: No

Pages

Occurrences of sensitive data in an Adobe Portable Document Format (PDF) file.

Type: Array of [Page](#) objects

Required: No

Records

Occurrences of sensitive data in an Apache Avro object container or an Apache Parquet file.

Type: Array of [Record](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

OrganizationConfiguration

Provides information about the way an organization is configured in Amazon Security Hub.

Contents

ConfigurationType

Indicates whether the organization uses local or central configuration.

If you use local configuration, the Security Hub delegated administrator can set `AutoEnable` to `true` and `AutoEnableStandards` to `DEFAULT`. This automatically enables Security Hub and default security standards in new organization accounts. These new account settings must be set separately in each Amazon Web Services Region, and settings may be different in each Region.

If you use central configuration, the delegated administrator can create configuration policies. Configuration policies can be used to configure Security Hub, security standards, and security controls in multiple accounts and Regions. If you want new organization accounts to use a specific configuration, you can create a configuration policy and associate it with the root or specific organizational units (OUs). New accounts will inherit the policy from the root or their assigned OU.

Type: String

Valid Values: CENTRAL | LOCAL

Required: No

Status

Describes whether central configuration could be enabled as the `ConfigurationType` for the organization. If your `ConfigurationType` is local configuration, then the value of `Status` is always `ENABLED`.

Type: String

Valid Values: PENDING | ENABLED | FAILED

Required: No

StatusMessage

Provides an explanation if the value of Status is equal to FAILED when ConfigurationType is equal to CENTRAL.

Type: String

Pattern: .*S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Page

An occurrence of sensitive data in an Adobe Portable Document Format (PDF) file.

Contents

LineRange

An occurrence of sensitive data detected in a non-binary text file or a Microsoft Word file. Non-binary text files include files such as HTML, XML, JSON, and TXT files.

Type: [Range](#) object

Required: No

OffsetRange

An occurrence of sensitive data detected in a binary text file.

Type: [Range](#) object

Required: No

PageNumber

The page number of the page that contains the sensitive data.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ParameterConfiguration

An object that provides the current value of a security control parameter and identifies whether it has been customized.

Contents

ValueType

Identifies whether a control parameter uses a custom user-defined value or subscribes to the default Amazon Security Hub behavior.

When `ValueType` is set equal to `DEFAULT`, the default behavior can be a specific Security Hub default value, or the default behavior can be to ignore a specific parameter. When `ValueType` is set equal to `DEFAULT`, Security Hub ignores user-provided input for the `Value` field.

When `ValueType` is set equal to `CUSTOM`, the `Value` field can't be empty.

Type: String

Valid Values: `DEFAULT` | `CUSTOM`

Required: Yes

Value

The current value of a control parameter.

Type: [ParameterValue](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

ParameterDefinition

An object that describes a security control parameter and the options for customizing it.

Contents

ConfigurationOptions

The options for customizing a control parameter. Customization options vary based on the data type of the parameter.

Type: [ConfigurationOptions](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Description

Description of a control parameter.

Type: String

Pattern: `.*\S.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ParameterValue

An object that includes the data type of a security control parameter and its current value.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

Boolean

A control parameter that is a boolean.

Type: Boolean

Required: No

Double

A control parameter that is a double.

Type: Double

Required: No

Enum

A control parameter that is an enum.

Type: String

Pattern: `.*\S.*`

Required: No

EnumList

A control parameter that is a list of enums.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Integer

A control parameter that is an integer.

Type: Integer

Required: No

IntegerList

A control parameter that is a list of integers.

Type: Array of integers

Required: No

String

A control parameter that is a string.

Type: String

Pattern: `.*\S.*`

Required: No

StringList

A control parameter that is a list of strings.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

PatchSummary

Provides an overview of the patch compliance status for an instance against a selected compliance standard.

Contents

Id

The identifier of the compliance standard that was used to determine the patch compliance status.

Length Constraints: Minimum length of 1. Maximum length of 256.

Type: String

Pattern: `.*\S.*`

Required: Yes

FailedCount

The number of patches from the compliance standard that failed to install.

The value can be an integer from 0 to 100000.

Type: Integer

Required: No

InstalledCount

The number of patches from the compliance standard that were installed successfully.

The value can be an integer from 0 to 100000.

Type: Integer

Required: No

InstalledOtherCount

The number of installed patches that are not part of the compliance standard.

The value can be an integer from 0 to 100000.

Type: Integer

Required: No

InstalledPendingReboot

The number of patches that were applied, but that require the instance to be rebooted in order to be marked as installed.

The value can be an integer from 0 to 100000.

Type: Integer

Required: No

InstalledRejectedCount

The number of patches that are installed but are also on a list of patches that the customer rejected.

The value can be an integer from 0 to 100000.

Type: Integer

Required: No

MissingCount

The number of patches that are part of the compliance standard but are not installed. The count includes patches that failed to install.

The value can be an integer from 0 to 100000.

Type: Integer

Required: No

Operation

The type of patch operation performed. For Patch Manager, the values are SCAN and INSTALL.

Length Constraints: Minimum length of 1. Maximum length of 256.

Type: String

Pattern: .*\\S.*

Required: No

OperationEndTime

Indicates when the operation completed.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

OperationStartTime

Indicates when the operation started.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

RebootOption

The reboot option specified for the instance.

Length Constraints: Minimum length of 1. Maximum length of 256.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Policy

An object that defines how Amazon Security Hub is configured. It includes whether Security Hub is enabled or disabled, a list of enabled security standards, a list of enabled or disabled security controls, and a list of custom parameter values for specified controls. If you provide a list of security controls that are enabled in the configuration policy, Security Hub disables all other controls (including newly released controls). If you provide a list of security controls that are disabled in the configuration policy, Security Hub enables all other controls (including newly released controls).

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

SecurityHub

The Amazon Web Services service that the configuration policy applies to.

Type: [SecurityHubPolicy](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PortProbeAction

Provided if `ActionType` is `PORT_PROBE`. It provides details about the attempted port probe that was detected.

Contents

Blocked

Indicates whether the port probe was blocked.

Type: Boolean

Required: No

PortProbeDetails

Information about the ports affected by the port probe.

Type: Array of [PortProbeDetail](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PortProbeDetail

A port scan that was part of the port probe. For each scan, PortProbeDetails provides information about the local IP address and port that were scanned, and the remote IP address that the scan originated from.

Contents

LocalIpDetails

Provides information about the IP address where the scanned port is located.

Type: [ActionLocalIpDetails](#) object

Required: No

LocalPortDetails

Provides information about the port that was scanned.

Type: [ActionLocalPortDetails](#) object

Required: No

RemoteIpDetails

Provides information about the remote IP address that performed the scan.

Type: [ActionRemoteIpDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ProcessDetails

The details of process-related information about a finding.

Contents

LaunchedAt

Indicates when the process was launched.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

Name

The name of the process.

Length Constraints: Minimum of 1. Maximum of 64.

Type: String

Pattern: .*\\S.*

Required: No

ParentPid

The parent process ID. This field accepts positive integers between 0 and 2147483647.

Type: Integer

Required: No

Path

The path to the process executable.

Length Constraints: Minimum of 1. Maximum of 512.

Type: String

Pattern: `.*\S.*`

Required: No

Pid

The process ID.

Type: Integer

Required: No

TerminatedAt

Indicates when the process was terminated.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Product

Contains details about a product.

Contents

ProductArn

The ARN assigned to the product.

Type: String

Pattern: `.*\S.*`

Required: Yes

ActivationUrl

The URL to the service or product documentation about the integration with Security Hub, including how to activate the integration.

Type: String

Pattern: `.*\S.*`

Required: No

Categories

The categories assigned to the product.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

CompanyName

The name of the company that provides the product.

Type: String

Pattern: `.*\S.*`

Required: No

Description

A description of the product.

Type: String

Pattern: `.*\S.*`

Required: No

IntegrationTypes

The types of integration that the product supports. Available values are the following.

- `SEND_FINDINGS_TO_SECURITY_HUB` - The integration sends findings to Security Hub.
- `RECEIVE_FINDINGS_FROM_SECURITY_HUB` - The integration receives findings from Security Hub.
- `UPDATE_FINDINGS_IN_SECURITY_HUB` - The integration does not send new findings to Security Hub, but does make updates to the findings that it receives from Security Hub.

Type: Array of strings

Valid Values: `SEND_FINDINGS_TO_SECURITY_HUB` | `RECEIVE_FINDINGS_FROM_SECURITY_HUB` | `UPDATE_FINDINGS_IN_SECURITY_HUB`

Required: No

MarketplaceUrl

For integrations with Amazon services, the Amazon Console URL from which to activate the service.

For integrations with third-party products, the Amazon Web Services Marketplace URL from which to subscribe to or purchase the product.

Type: String

Pattern: `.*\S.*`

Required: No

ProductName

The name of the product.

Type: String

Pattern: .*\\S.*

Required: No

ProductSubscriptionResourcePolicy

The resource policy associated with the product.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Range

Identifies where the sensitive data begins and ends.

Contents

End

The number of lines (for a line range) or characters (for an offset range) from the beginning of the file to the end of the sensitive data.

Type: Long

Required: No

Start

The number of lines (for a line range) or characters (for an offset range) from the beginning of the file to the end of the sensitive data.

Type: Long

Required: No

StartColumn

In the line where the sensitive data starts, the column within the line where the sensitive data starts.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Recommendation

A recommendation on how to remediate the issue identified in a finding.

Contents

Text

Describes the recommended steps to take to remediate an issue identified in a finding.

Length Constraints: Minimum of 1 length. Maximum of 512 length.

Type: String

Pattern: `.*\S.*`

Required: No

Url

A URL to a page or site that contains information about how to remediate a finding.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Record

An occurrence of sensitive data in an Apache Avro object container or an Apache Parquet file.

Contents

JsonPath

The path, as a JSONPath expression, to the field in the record that contains the data. If the field name is longer than 20 characters, it is truncated. If the path is longer than 250 characters, it is truncated.

Type: String

Pattern: `.*\S.*`

Required: No

RecordIndex

The record index, starting from 0, for the record that contains the data.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RelatedFinding

Details about a related finding.

Contents

Id

The product-generated identifier for a related finding.

Type: String

Pattern: `.*\S.*`

Required: Yes

ProductArn

The ARN of the product that generated a related finding.

Type: String

Pattern: `.*\S.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Remediation

Details about the remediation steps for a finding.

Contents

Recommendation

A recommendation on the steps to take to remediate the issue identified by a finding.

Type: [Recommendation](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Resource

A resource related to a finding.

Contents

Id

The canonical identifier for the given resource type.

Type: String

Pattern: `.*\S.*`

Required: Yes

Type

The type of the resource that details are provided for. If possible, set Type to one of the supported resource types. For example, if the resource is an EC2 instance, then set Type to `AwsEc2Instance`.

If the resource does not match any of the provided types, then set Type to `Other`.

Length Constraints: Minimum length of 1. Maximum length of 256.

Type: String

Pattern: `.*\S.*`

Required: Yes

ApplicationArn

The Amazon Resource Name (ARN) of the application that is related to a finding.

Type: String

Pattern: `.*\S.*`

Required: No

ApplicationName

The name of the application that is related to a finding.

Type: String

Pattern: `.*\S.*`

Required: No

DataClassification

Contains information about sensitive data that was detected on the resource.

Type: [DataClassificationDetails](#) object

Required: No

Details

Additional details about the resource related to a finding.

Type: [ResourceDetails](#) object

Required: No

Partition

The canonical Amazon partition name that the Region is assigned to.

Type: String

Valid Values: `aws` | `aws-cn` | `aws-us-gov`

Required: No

Region

The canonical Amazon external Region name where this resource is located.

Length Constraints: Minimum length of 1. Maximum length of 16.

Type: String

Pattern: `.*\S.*`

Required: No

ResourceRole

Identifies the role of the resource in the finding. A resource is either the actor or target of the finding activity,

Type: String

Pattern: `.*\S.*`

Required: No

Tags

A list of Amazon tags associated with a resource at the time the finding was processed. Tags must follow [Amazon tag naming limits and requirements](#).

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ResourceDetails

Additional details about a resource related to a finding.

To provide the details, use the object that corresponds to the resource type. For example, if the resource type is `AwsEc2Instance`, then you use the `AwsEc2Instance` object to provide the details.

If the type-specific object does not contain all of the fields you want to populate, then you use the `Other` object to populate those additional fields.

You also use the `Other` object to populate the details when the selected type does not have a corresponding object.

Contents

AwsAmazonMqBroker

Provides details about Amazon AppSync message broker. A message broker allows software applications and components to communicate using various programming languages, operating systems, and formal messaging protocols.

Type: [AwsAmazonMqBrokerDetails](#) object

Required: No

AwsApiGatewayRestApi

Provides information about a REST API in version 1 of Amazon API Gateway.

Type: [AwsApiGatewayRestApiDetails](#) object

Required: No

AwsApiGatewayStage

Provides information about a version 1 Amazon API Gateway stage.

Type: [AwsApiGatewayStageDetails](#) object

Required: No

AwsApiGatewayV2Api

Provides information about a version 2 API in Amazon API Gateway.

Type: [AwsApiGatewayV2ApiDetails](#) object

Required: No

AwsApiGatewayV2Stage

Provides information about a version 2 stage for Amazon API Gateway.

Type: [AwsApiGatewayV2StageDetails](#) object

Required: No

AwsAppSyncGraphQLApi

Provides details about an Amazon AppSync GraphQL API, which lets you query multiple databases, microservices, and APIs from a single GraphQL endpoint.

Type: [AwsAppSyncGraphQLApiDetails](#) object

Required: No

AwsAthenaWorkGroup

Provides information about an Amazon Athena workgroup. A workgroup helps you separate users, teams, applications, or workloads. It also helps you set limits on data processing and track costs.

Type: [AwsAthenaWorkGroupDetails](#) object

Required: No

AwsAutoScalingAutoScalingGroup

Details for an autoscaling group.

Type: [AwsAutoScalingAutoScalingGroupDetails](#) object

Required: No

AwsAutoScalingLaunchConfiguration

Provides details about a launch configuration.

Type: [AwsAutoScalingLaunchConfigurationDetails](#) object

Required: No

AwsBackupBackupPlan

Provides details about an Amazon Backup backup plan.

Type: [AwsBackupBackupPlanDetails](#) object

Required: No

AwsBackupBackupVault

Provides details about an Amazon Backup backup vault.

Type: [AwsBackupBackupVaultDetails](#) object

Required: No

AwsBackupRecoveryPoint

Provides details about an Amazon Backup backup, or recovery point.

Type: [AwsBackupRecoveryPointDetails](#) object

Required: No

AwsCertificateManagerCertificate

Provides details about an Amazon Certificate Manager certificate.

Type: [AwsCertificateManagerCertificateDetails](#) object

Required: No

AwsCloudFormationStack

Details about an Amazon CloudFormation stack. A stack is a collection of Amazon resources that you can manage as a single unit.

Type: [AwsCloudFormationStackDetails](#) object

Required: No

AwsCloudFrontDistribution

Details about a CloudFront distribution.

Type: [AwsCloudFrontDistributionDetails](#) object

Required: No

AwsCloudTrailTrail

Provides details about a CloudTrail trail.

Type: [AwsCloudTrailTrailDetails](#) object

Required: No

AwsCloudWatchAlarm

Details about an Amazon CloudWatch alarm. An alarm allows you to monitor and receive alerts about your Amazon resources and applications across multiple Regions.

Type: [AwsCloudWatchAlarmDetails](#) object

Required: No

AwsCodeBuildProject

Details for an Amazon CodeBuild project.

Type: [AwsCodeBuildProjectDetails](#) object

Required: No

AwsDmsEndpoint

Provides details about an Amazon Database Migration Service (Amazon DMS) endpoint. An endpoint provides connection, data store type, and location information about your data store.

Type: [AwsDmsEndpointDetails](#) object

Required: No

AwsDmsReplicationInstance

Provides details about an Amazon DMS replication instance. DMS uses a replication instance to connect to your source data store, read the source data, and format the data for consumption by the target data store.

Type: [AwsDmsReplicationInstanceDetails](#) object

Required: No

AwsDmsReplicationTask

Provides details about an Amazon DMS replication task. A replication task moves a set of data from the source endpoint to the target endpoint.

Type: [AwsDmsReplicationTaskDetails](#) object

Required: No

AwsDynamoDbTable

Details about a DynamoDB table.

Type: [AwsDynamoDbTableDetails](#) object

Required: No

AwsEc2ClientVpnEndpoint

Provides details about an Amazon Client VPN endpoint. A Client VPN endpoint is the resource that you create and configure to enable and manage client VPN sessions. It's the termination point for all client VPN sessions.

Type: [AwsEc2ClientVpnEndpointDetails](#) object

Required: No

AwsEc2Eip

Details about an Elastic IP address.

Type: [AwsEc2EipDetails](#) object

Required: No

AwsEc2Instance

Details about an EC2 instance related to a finding.

Type: [AwsEc2InstanceDetails](#) object

Required: No

AwsEc2LaunchTemplate

Specifies the properties for creating an Amazon Elastic Compute Cloud (Amazon EC2) launch template.

Type: [AwsEc2LaunchTemplateDetails](#) object

Required: No

AwsEc2NetworkAcl

Details about an EC2 network access control list (ACL).

Type: [AwsEc2NetworkAclDetails](#) object

Required: No

AwsEc2NetworkInterface

Details for an EC2 network interface.

Type: [AwsEc2NetworkInterfaceDetails](#) object

Required: No

AwsEc2RouteTable

Provides details about a route table. A route table contains a set of rules, called routes, that determine where to direct network traffic from your subnet or gateway.

Type: [AwsEc2RouteTableDetails](#) object

Required: No

AwsEc2SecurityGroup

Details for an EC2 security group.

Type: [AwsEc2SecurityGroupDetails](#) object

Required: No

AwsEc2Subnet

Details about a subnet in Amazon EC2.

Type: [AwsEc2SubnetDetails](#) object

Required: No

AwsEc2TransitGateway

Details about an Amazon EC2 transit gateway that interconnects your virtual private clouds (VPC) and on-premises networks.

Type: [AwsEc2TransitGatewayDetails](#) object

Required: No

AwsEc2Volume

Details for an Amazon EC2 volume.

Type: [AwsEc2VolumeDetails](#) object

Required: No

AwsEc2Vpc

Details for an Amazon EC2 VPC.

Type: [AwsEc2VpcDetails](#) object

Required: No

AwsEc2VpcEndpointService

Details about the service configuration for a VPC endpoint service.

Type: [AwsEc2VpcEndpointServiceDetails](#) object

Required: No

AwsEc2VpcPeeringConnection

Details about an Amazon EC2 VPC peering connection. A VPC peering connection is a networking connection between two VPCs that enables you to route traffic between them privately.

Type: [AwsEc2VpcPeeringConnectionDetails](#) object

Required: No

AwsEc2VpnConnection

Details about an Amazon EC2 VPN connection.

Type: [AwsEc2VpnConnectionDetails](#) object

Required: No

AwsEcrContainerImage

Information about an Amazon ECR image.

Type: [AwsEcrContainerImageDetails](#) object

Required: No

AwsEcrRepository

Information about an Amazon Elastic Container Registry repository.

Type: [AwsEcrRepositoryDetails](#) object

Required: No

AwsEcsCluster

Details about an Amazon ECS cluster.

Type: [AwsEcsClusterDetails](#) object

Required: No

AwsEcsContainer

Provides information about a Docker container that's part of a task.

Type: [AwsEcsContainerDetails](#) object

Required: No

AwsEcsService

Details about a service within an ECS cluster.

Type: [AwsEcsServiceDetails](#) object

Required: No

AwsEcsTask

Details about a task in a cluster.

Type: [AwsEcsTaskDetails](#) object

Required: No

AwsEcsTaskDefinition

Details about a task definition. A task definition describes the container and volume definitions of an Amazon Elastic Container Service task.

Type: [AwsEcsTaskDefinitionDetails](#) object

Required: No

AwsEfsAccessPoint

Details about an Amazon EFS access point. An access point is an application-specific view into an EFS file system that applies an operating system user and group, and a file system path, to any file system request made through the access point.

Type: [AwsEfsAccessPointDetails](#) object

Required: No

AwsEksCluster

Details about an Amazon EKS cluster.

Type: [AwsEksClusterDetails](#) object

Required: No

AwsElasticBeanstalkEnvironment

Details about an Elastic Beanstalk environment.

Type: [AwsElasticBeanstalkEnvironmentDetails](#) object

Required: No

AwsElasticsearchDomain

Details for an Elasticsearch domain.

Type: [AwsElasticsearchDomainDetails](#) object

Required: No

AwsElbLoadBalancer

Contains details about a Classic Load Balancer.

Type: [AwsElbLoadBalancerDetails](#) object

Required: No

AwsElbv2LoadBalancer

Details about a load balancer.

Type: [AwsElbv2LoadBalancerDetails](#) object

Required: No

AwsEventSchemasRegistry

A schema defines the structure of events that are sent to Amazon EventBridge. Schema registries are containers for schemas. They collect and organize schemas so that your schemas are in logical groups.

Type: [AwsEventSchemasRegistryDetails](#) object

Required: No

AwsEventsEndpoint

Provides details about an Amazon EventBridge global endpoint. The endpoint can improve your application's availability by making it Regional-fault tolerant.

Type: [AwsEventsEndpointDetails](#) object

Required: No

AwsEventsEventbus

Provides details about Amazon EventBridge event bus for an endpoint. An event bus is a router that receives events and delivers them to zero or more destinations, or targets.

Type: [AwsEventsEventbusDetails](#) object

Required: No

AwsGuardDutyDetector

Provides details about an Amazon GuardDuty detector. A detector is an object that represents the GuardDuty service. A detector is required for GuardDuty to become operational.

Type: [AwsGuardDutyDetectorDetails](#) object

Required: No

AwsIamAccessKey

Details about an IAM access key related to a finding.

Type: [AwsIamAccessKeyDetails](#) object

Required: No

AwsIamGroup

Contains details about an IAM group.

Type: [AwsIamGroupDetails](#) object

Required: No

AwsIamPolicy

Details about an IAM permissions policy.

Type: [AwsIamPolicyDetails](#) object

Required: No

AwsIamRole

Details about an IAM role.

Type: [AwsIamRoleDetails](#) object

Required: No

AwsIamUser

Details about an IAM user.

Type: [AwsIamUserDetails](#) object

Required: No

AwsKinesisStream

Details about an Amazon Kinesis data stream.

Type: [AwsKinesisStreamDetails](#) object

Required: No

AwsKmsKey

Details about an Amazon KMS key.

Type: [AwsKmsKeyDetails](#) object

Required: No

AwsLambdaFunction

Details about a Lambda function.

Type: [AwsLambdaFunctionDetails](#) object

Required: No

AwsLambdaLayerVersion

Details for a Lambda layer version.

Type: [AwsLambdaLayerVersionDetails](#) object

Required: No

AwsMskCluster

Provides details about an Amazon Managed Streaming for Apache Kafka (Amazon MSK) cluster.

Type: [AwsMskClusterDetails](#) object

Required: No

AwsNetworkFirewallFirewall

Details about an Amazon Network Firewall firewall.

Type: [AwsNetworkFirewallFirewallDetails](#) object

Required: No

AwsNetworkFirewallFirewallPolicy

Details about an Amazon Network Firewall firewall policy.

Type: [AwsNetworkFirewallFirewallPolicyDetails](#) object

Required: No

AwsNetworkFirewallRuleGroup

Details about an Amazon Network Firewall rule group.

Type: [AwsNetworkFirewallRuleGroupDetails](#) object

Required: No

AwsOpenSearchServiceDomain

Details about an Amazon OpenSearch Service domain.

Type: [AwsOpenSearchServiceDomainDetails](#) object

Required: No

AwsRdsDbCluster

Details about an Amazon RDS database cluster.

Type: [AwsRdsDbClusterDetails](#) object

Required: No

AwsRdsDbClusterSnapshot

Details about an Amazon RDS database cluster snapshot.

Type: [AwsRdsDbClusterSnapshotDetails](#) object

Required: No

AwsRdsDbInstance

Details about an Amazon RDS database instance.

Type: [AwsRdsDbInstanceDetails](#) object

Required: No

AwsRdsDbSecurityGroup

Details about an Amazon RDS DB security group.

Type: [AwsRdsDbSecurityGroupDetails](#) object

Required: No

AwsRdsDbSnapshot

Details about an Amazon RDS database snapshot.

Type: [AwsRdsDbSnapshotDetails](#) object

Required: No

AwsRdsEventSubscription

Details about an RDS event notification subscription.

Type: [AwsRdsEventSubscriptionDetails](#) object

Required: No

AwsRedshiftCluster

Contains details about an Amazon Redshift cluster.

Type: [AwsRedshiftClusterDetails](#) object

Required: No

AwsRoute53HostedZone

Provides details about an Amazon Route 53 hosted zone, including the four name servers assigned to the hosted zone. A hosted zone represents a collection of records that can be managed together, belonging to a single parent domain name.

Type: [AwsRoute53HostedZoneDetails](#) object

Required: No

AwsS3AccessPoint

Provides details about an Amazon Simple Storage Service (Amazon S3) access point. S3 access points are named network endpoints that are attached to S3 buckets that you can use to perform S3 object operations.

Type: [AwsS3AccessPointDetails](#) object

Required: No

AwsS3AccountPublicAccessBlock

Details about the Amazon S3 Public Access Block configuration for an account.

Type: [AwsS3AccountPublicAccessBlockDetails](#) object

Required: No

AwsS3Bucket

Details about an S3 bucket related to a finding.

Type: [AwsS3BucketDetails](#) object

Required: No

AwsS3Object

Details about an S3 object related to a finding.

Type: [AwsS3ObjectDetails](#) object

Required: No

AwsSageMakerNotebookInstance

Provides details about an Amazon SageMaker AI notebook instance.

Type: [AwsSageMakerNotebookInstanceDetails](#) object

Required: No

AwsSecretsManagerSecret

Details about a Secrets Manager secret.

Type: [AwsSecretsManagerSecretDetails](#) object

Required: No

AwsSnsTopic

Details about an SNS topic.

Type: [AwsSnsTopicDetails](#) object

Required: No

AwsSqsQueue

Details about an SQS queue.

Type: [AwsSqsQueueDetails](#) object

Required: No

AwsSsmPatchCompliance

Provides information about the state of a patch on an instance based on the patch baseline that was used to patch the instance.

Type: [AwsSsmPatchComplianceDetails](#) object

Required: No

AwsStepFunctionStateMachine

Provides details about an Amazon Step Functions state machine, which is a workflow consisting of a series of event-driven steps.

Type: [AwsStepFunctionStateMachineDetails](#) object

Required: No

AwsWafRateBasedRule

Details about a rate-based rule for global resources.

Type: [AwsWafRateBasedRuleDetails](#) object

Required: No

AwsWafRegionalRateBasedRule

Details about a rate-based rule for Regional resources.

Type: [AwsWafRegionalRateBasedRuleDetails](#) object

Required: No

AwsWafRegionalRule

Details about an Amazon WAF rule for Regional resources.

Type: [AwsWafRegionalRuleDetails](#) object

Required: No

AwsWafRegionalRuleGroup

Details about an Amazon WAF rule group for Regional resources.

Type: [AwsWafRegionalRuleGroupDetails](#) object

Required: No

AwsWafRegionalWebAcl

Details about an Amazon WAF web access control list (web ACL) for Regional resources.

Type: [AwsWafRegionalWebAclDetails](#) object

Required: No

AwsWafRule

Details about an Amazon WAF rule for global resources.

Type: [AwsWafRuleDetails](#) object

Required: No

AwsWafRuleGroup

Details about an Amazon WAF rule group for global resources.

Type: [AwsWafRuleGroupDetails](#) object

Required: No

AwsWafv2RuleGroup

Details about an Amazon WAFv2 rule group.

Type: [AwsWafv2RuleGroupDetails](#) object

Required: No

AwsWafv2WebAcl

Details about an Amazon WAFv2 web Access Control List (ACL).

Type: [AwsWafv2WebAclDetails](#) object

Required: No

AwsWafWebAcl

Details for an Amazon WAF web ACL.

Type: [AwsWafWebAclDetails](#) object

Required: No

AwsXrayEncryptionConfig

Information about the encryption configuration for Amazon X-Ray.

Type: [AwsXrayEncryptionConfigDetails](#) object

Required: No

Container

Details about a container resource related to a finding.

Type: [ContainerDetails](#) object

Required: No

Other

Details about a resource that are not available in a type-specific details object. Use the `Other` object in the following cases.

- The type-specific object does not contain all of the fields that you want to populate. In this case, first use the type-specific object to populate those fields. Use the `Other` object to populate the fields that are missing from the type-specific object.
- The resource type does not have a corresponding object. This includes resources for which the type is `Other`.

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Result

Details about the account that was not processed.

Contents

AccountId

An Amazon Web Services account ID of the account that was not processed.

Type: String

Required: No

ProcessingResult

The reason that the account was not processed.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SecurityControl

A security control in Security Hub describes a security best practice related to a specific resource.

Contents

Description

The description of a security control across standards. This typically summarizes how Security Hub evaluates the control and the conditions under which it produces a failed finding. This parameter doesn't reference a specific standard.

Type: String

Pattern: `.*\S.*`

Required: Yes

RemediationUrl

A link to Security Hub documentation that explains how to remediate a failed finding for a security control.

Type: String

Pattern: `.*\S.*`

Required: Yes

SecurityControlArn

The Amazon Resource Name (ARN) for a security control across standards, such as `arn:aws:securityhub:eu-central-1:123456789012:security-control/S3.1`. This parameter doesn't mention a specific standard.

Type: String

Pattern: `.*\S.*`

Required: Yes

SecurityControlId

The unique identifier of a security control across standards. Values for this field typically consist of an Amazon Web Services service name and a number, such as `APIGateway.3`.

Type: String

Pattern: `.*\S.*`

Required: Yes

SecurityControlStatus

The enablement status of a security control in a specific standard.

Type: String

Valid Values: ENABLED | DISABLED

Required: Yes

SeverityRating

The severity of a security control. For more information about how Security Hub determines control severity, see [Assigning severity to control findings](#) in the *Security Hub User Guide*.

Type: String

Valid Values: LOW | MEDIUM | HIGH | CRITICAL

Required: Yes

Title

The title of a security control.

Type: String

Pattern: `.*\S.*`

Required: Yes

LastUpdateReason

The most recent reason for updating the customizable properties of a security control. This differs from the UpdateReason field of the [BatchUpdateStandardsControlAssociations](#) API, which tracks the reason for updating the enablement status of a control. This field accepts alphanumeric characters in addition to white spaces, dashes, and underscores.

Type: String

Pattern: `^[^\u0000-\u007F]|[-_ a-zA-Z0-9])+$`

Required: No

Parameters

An object that identifies the name of a control parameter, its current value, and whether it has been customized.

Type: String to [ParameterConfiguration](#) object map

Key Pattern: `.*\S.*`

Required: No

UpdateStatus

Identifies whether customizable properties of a security control are reflected in Security Hub findings. A status of READY indicates that Security Hub uses the current control parameter values when running security checks of the control. A status of UPDATING indicates that all security checks might not use the current parameter values.

Type: String

Valid Values: READY | UPDATING

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SecurityControlCustomParameter

A list of security controls and control parameter values that are included in a configuration policy.

Contents

Parameters

An object that specifies parameter values for a control in a configuration policy.

Type: String to [ParameterConfiguration](#) object map

Key Pattern: `.*\S.*`

Required: No

SecurityControlId

The ID of the security control.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SecurityControlDefinition

Provides metadata for a security control, including its unique standard-agnostic identifier, title, description, severity, availability in Amazon Web Services Regions, and a link to remediation steps.

Contents

CurrentRegionAvailability

Specifies whether a security control is available in the current Amazon Web Services Region.

Type: String

Valid Values: AVAILABLE | UNAVAILABLE

Required: Yes

Description

The description of a security control across standards. This typically summarizes how Security Hub evaluates the control and the conditions under which it produces a failed finding. This parameter doesn't reference a specific standard.

Type: String

Pattern: `.*\S.*`

Required: Yes

RemediationUrl

A link to Security Hub documentation that explains how to remediate a failed finding for a security control.

Type: String

Pattern: `.*\S.*`

Required: Yes

SecurityControlId

The unique identifier of a security control across standards. Values for this field typically consist of an Amazon Web Services service name and a number (for example, `APIGateway.3`). This parameter differs from `SecurityControlArn`, which is a unique Amazon Resource

Name (ARN) assigned to a control. The ARN references the security control ID (for example, `arn:aws:securityhub:eu-central-1:123456789012:security-control/APIGateway.3`).

Type: String

Pattern: `.*\S.*`

Required: Yes

SeverityRating

The severity of a security control. For more information about how Security Hub determines control severity, see [Assigning severity to control findings](#) in the *Security Hub User Guide*.

Type: String

Valid Values: LOW | MEDIUM | HIGH | CRITICAL

Required: Yes

Title

The title of a security control.

Type: String

Pattern: `.*\S.*`

Required: Yes

CustomizableProperties

Security control properties that you can customize. Currently, only parameter customization is supported for select controls. An empty array is returned for controls that don't support custom properties.

Type: Array of strings

Valid Values: Parameters

Required: No

ParameterDefinitions

An object that provides a security control parameter name, description, and the options for customizing it. This object is excluded for a control that doesn't support custom parameters.

Type: String to [ParameterDefinition](#) object map

Key Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SecurityControlParameter

A parameter that a security control accepts.

Contents

Name

The name of a

Type: String

Pattern: `.*\S.*`

Required: No

Value

The current value of a control parameter.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SecurityControlsConfiguration

An object that defines which security controls are enabled in an Amazon Security Hub configuration policy. The enablement status of a control is aligned across all of the enabled standards in an account.

Contents

DisabledSecurityControlIdentifiers

A list of security controls that are disabled in the configuration policy. Security Hub enables all other controls (including newly released controls) other than the listed controls.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

EnabledSecurityControlIdentifiers

A list of security controls that are enabled in the configuration policy. Security Hub disables all other controls (including newly released controls) other than the listed controls.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

SecurityControlCustomParameters

A list of security controls and control parameter values that are included in a configuration policy.

Type: Array of [SecurityControlCustomParameter](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SecurityHubPolicy

An object that defines how Amazon Security Hub is configured. The configuration policy includes whether Security Hub is enabled or disabled, a list of enabled security standards, a list of enabled or disabled security controls, and a list of custom parameter values for specified controls. If you provide a list of security controls that are enabled in the configuration policy, Security Hub disables all other controls (including newly released controls). If you provide a list of security controls that are disabled in the configuration policy, Security Hub enables all other controls (including newly released controls).

Contents

EnabledStandardIdentifiers

A list that defines which security standards are enabled in the configuration policy.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

SecurityControlsConfiguration

An object that defines which security controls are enabled in the configuration policy. The enablement status of a control is aligned across all of the enabled standards in an account.

Type: [SecurityControlsConfiguration](#) object

Required: No

ServiceEnabled

Indicates whether Security Hub is enabled in the policy.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SensitiveDataDetections

The list of detected instances of sensitive data.

Contents

Count

The total number of occurrences of sensitive data that were detected.

Type: Long

Required: No

Occurrences

Details about the sensitive data that was detected.

Type: [Occurrences](#) object

Required: No

Type

The type of sensitive data that was detected. For example, the type might indicate that the data is an email address.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SensitiveDataResult

Contains a detected instance of sensitive data that are based on built-in identifiers.

Contents

Category

The category of sensitive data that was detected. For example, the category can indicate that the sensitive data involved credentials, financial information, or personal information.

Type: String

Pattern: `.*\S.*`

Required: No

Detections

The list of detected instances of sensitive data.

Type: Array of [SensitiveDataDetections](#) objects

Required: No

TotalCount

The total number of occurrences of sensitive data.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Sequence

Contains information about an Amazon GuardDuty Extended Threat Detection attack sequence finding. GuardDuty generates an attack sequence finding when multiple events align to a potentially suspicious activity. To receive GuardDuty attack sequence findings in Amazon Security Hub, you must have GuardDuty enabled. For more information, see [GuardDuty Extended Threat Detection](#) in the *Amazon GuardDuty User Guide*.

Contents

Actors

Provides information about the actors involved in the attack sequence.

Type: Array of [Actor](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

Endpoints

Contains information about the network endpoints that were used in the attack sequence.

Type: Array of [NetworkEndpoint](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

SequenceIndicators

Contains information about the indicators observed in the attack sequence. The values for [SignalIndicators](#) are a subset of the values for SequenceIndicators, but the values for these fields don't always match 1:1.

Type: Array of [Indicator](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Required: No

Signals

Contains information about the signals involved in the attack sequence.

Type: Array of [Signal](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

Uid

Unique identifier of the attack sequence.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Severity

The severity of the finding.

The finding provider can provide the initial severity. The finding provider can only update the severity if it hasn't been updated using `BatchUpdateFindings`.

The finding must have either `Label` or `Normalized` populated. If only one of these attributes is populated, then Security Hub automatically populates the other one. If neither attribute is populated, then the finding is invalid. `Label` is the preferred attribute.

Contents

Label

The severity value of the finding. The allowed values are the following.

- `INFORMATIONAL` - No issue was found.
- `LOW` - The issue does not require action on its own.
- `MEDIUM` - The issue must be addressed but not urgently.
- `HIGH` - The issue must be addressed as a priority.
- `CRITICAL` - The issue must be remediated immediately to avoid it escalating.

If you provide `Normalized` and don't provide `Label`, then `Label` is set automatically as follows.

- `0` - `INFORMATIONAL`
- `1–39` - `LOW`
- `40–69` - `MEDIUM`
- `70–89` - `HIGH`
- `90–100` - `CRITICAL`

Type: String

Valid Values: `INFORMATIONAL` | `LOW` | `MEDIUM` | `HIGH` | `CRITICAL`

Required: No

Normalized

Deprecated. The normalized severity of a finding. Instead of providing `Normalized`, provide `Label`.

The value of `Normalized` can be an integer between 0 and 100.

If you provide `Label` and don't provide `Normalized`, then `Normalized` is set automatically as follows.

- INFORMATIONAL - 0
- LOW - 1
- MEDIUM - 40
- HIGH - 70
- CRITICAL - 90

Type: Integer

Required: No

Original

The native severity from the finding product that generated the finding.

Length Constraints: Minimum length of 1. Maximum length of 64.

Type: String

Pattern: `.*\S.*`

Required: No

Product

Deprecated. This attribute isn't included in findings. Instead of providing `Product`, provide `Original`.

The native severity as defined by the Amazon service or integrated partner product that generated the finding.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SeverityUpdate

Updates to the severity information for a finding.

Contents

Label

The severity value of the finding. The allowed values are the following.

- INFORMATIONAL - No issue was found.
- LOW - The issue does not require action on its own.
- MEDIUM - The issue must be addressed but not urgently.
- HIGH - The issue must be addressed as a priority.
- CRITICAL - The issue must be remediated immediately to avoid it escalating.

Type: String

Valid Values: INFORMATIONAL | LOW | MEDIUM | HIGH | CRITICAL

Required: No

Normalized

The normalized severity for the finding. This attribute is to be deprecated in favor of Label.

If you provide Normalized and don't provide Label, Label is set automatically as follows.

- 0 - INFORMATIONAL
- 1–39 - LOW
- 40–69 - MEDIUM
- 70–89 - HIGH
- 90–100 - CRITICAL

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

Product

The native severity as defined by the Amazon service or integrated partner product that generated the finding.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Signal

Contains information about the signals involved in an Amazon GuardDuty Extended Threat Detection attack sequence. An attack sequence is a type of threat detected by GuardDuty. GuardDuty generates an attack sequence finding when multiple events, or signals, align to a potentially suspicious activity. When GuardDuty and Amazon Security Hub are integrated, GuardDuty sends attack sequence findings to Security Hub.

A signal can be an API activity or a finding that GuardDuty uses to detect an attack sequence finding.

Contents

ActorIds

The IDs of the threat actors involved in the signal.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Count

The number of times this signal was observed.

Type: Integer

Required: No

CreatedAt

The timestamp when the first finding or activity related to this signal was observed.

Type: Long

Required: No

EndpointIds

Information about the endpoint IDs associated with this signal.

Type: Array of strings

Pattern: .*\\S.*

Required: No

FirstSeenAt

The timestamp when the first finding or activity related to this signal was observed.

Type: Long

Required: No

Id

The identifier of the signal.

Type: String

Pattern: .*\\S.*

Required: No

LastSeenAt

The timestamp when the last finding or activity related to this signal was observed.

Type: Long

Required: No

Name

The name of the GuardDuty signal. For example, when signal type is FINDING, the signal name is the name of the finding.

Type: String

Pattern: .*\\S.*

Required: No

ProductArn

The Amazon Resource Name (ARN) of the product that generated the signal.

Type: String

Pattern: .*\\S.*

Required: No

ResourceIds

The ARN or ID of the Amazon resource associated with the signal.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Severity

The severity associated with the signal. For more information about severity, see [Severity levels for GuardDuty findings](#) in the *Amazon GuardDuty User Guide*.

Type: Double

Required: No

SignalIndicators

Contains information about the indicators associated with the signals in this attack sequence finding. The values for `SignalIndicators` are a subset of the values for [SequenceIndicators](#), but the values for these fields don't always match 1:1.

Type: Array of [Indicator](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Required: No

Title

The description of the GuardDuty finding.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The type of the signal used to identify an attack sequence.

Signals can be GuardDuty findings or activities observed in data sources that GuardDuty monitors. For more information, see [GuardDuty foundational data sources](#) in the *Amazon GuardDuty User Guide*.

A signal type can be one of the following values. Here are the related descriptions:

- FINDING - Individually generated GuardDuty finding.
- CLOUD_TRAIL - Activity observed from Amazon CloudTrail logs
- S3_DATA_EVENTS - Activity observed from CloudTrail data events for Amazon Simple Storage Service (S3). Activities associated with this type will show up only when you have enabled GuardDuty S3 Protection feature in your account. For more information about S3 Protection and the steps to enable it, see [S3 Protection](#) in the *Amazon GuardDuty User Guide*.

Type: String

Pattern: .*\\S.*

Required: No

UpdatedAt

The timestamp when this signal was last observed.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SoftwarePackage

Information about a software package.

Contents

Architecture

The architecture used for the software package.

Type: String

Pattern: `.*\S.*`

Required: No

Epoch

The epoch of the software package.

Type: String

Pattern: `.*\S.*`

Required: No

FilePath

The file system path to the package manager inventory file.

Type: String

Pattern: `.*\S.*`

Required: No

FixedInVersion

The version of the software package in which the vulnerability has been resolved.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the software package.

Type: String

Pattern: `.*\S.*`

Required: No

PackageManager

The source of the package.

Type: String

Pattern: `.*\S.*`

Required: No

Release

The release of the software package.

Type: String

Pattern: `.*\S.*`

Required: No

Remediation

Describes the actions a customer can take to resolve the vulnerability in the software package.

Type: String

Pattern: `.*\S.*`

Required: No

SourceLayerArn

The Amazon Resource Name (ARN) of the source layer.

Type: String

Pattern: `.*\S.*`

Required: No

SourceLayerHash

The source layer hash of the vulnerable package.

Type: String

Pattern: `.*\S.*`

Required: No

Version

The version of the software package.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SortCriterion

A collection of finding attributes used to sort findings.

Contents

Field

The finding attribute used to sort findings.

Type: String

Pattern: `.*\S.*`

Required: No

SortOrder

The order used to sort findings.

Type: String

Valid Values: `asc` | `desc`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Standard

Provides information about a specific security standard.

Contents

Description

A description of the standard.

Type: String

Pattern: `.*\S.*`

Required: No

EnabledByDefault

Whether the standard is enabled by default. When Security Hub is enabled from the console, if a standard is enabled by default, the check box for that standard is selected by default.

When Security Hub is enabled using the `EnableSecurityHub` API operation, the standard is enabled by default unless `EnableDefaultStandards` is set to `false`.

Type: Boolean

Required: No

Name

The name of the standard.

Type: String

Pattern: `.*\S.*`

Required: No

StandardsArn

The ARN of the standard.

Type: String

Pattern: `.*\S.*`

Required: No

StandardsManagedBy

Provides details about the management of a standard.

Type: [StandardsManagedBy](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StandardsControl

Details for an individual security standard control.

Contents

ControlId

The identifier of the security standard control.

Type: String

Pattern: `.*\S.*`

Required: No

ControlStatus

The current status of the security standard control. Indicates whether the control is enabled or disabled. Security Hub does not check against disabled controls.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

ControlStatusUpdatedAt

The date and time that the status of the security standard control was most recently updated.

Type: Timestamp

Required: No

Description

The longer description of the security standard control. Provides information about what the control is checking for.

Type: String

Pattern: `.*\S.*`

Required: No

DisabledReason

The reason provided for the most recent change in status for the control.

Type: String

Pattern: `.*\S.*`

Required: No

RelatedRequirements

The list of requirements that are related to this control.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

RemediationUrl

A link to remediation information for the control in the Security Hub user documentation.

Type: String

Pattern: `.*\S.*`

Required: No

SeverityRating

The severity of findings generated from this security standard control.

The finding severity is based on an assessment of how easy it would be to compromise Amazon resources if the issue is detected.

Type: String

Valid Values: LOW | MEDIUM | HIGH | CRITICAL

Required: No

StandardsControlArn

The ARN of the security standard control.

Type: String

Pattern: .*\\S.*

Required: No

Title

The title of the security standard control.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StandardsControlAssociationDetail

Provides details about a control's enablement status in a specified standard.

Contents

AssociationStatus

Specifies whether a control is enabled or disabled in a specified standard.

Type: String

Valid Values: ENABLED | DISABLED

Required: Yes

SecurityControlArn

The ARN of a security control across standards, such as `arn:aws:securityhub:eu-central-1:123456789012:security-control/S3.1`. This parameter doesn't mention a specific standard.

Type: String

Pattern: `.*\S.*`

Required: Yes

SecurityControlId

The unique identifier of a security control across standards. Values for this field typically consist of an Amazon Web Services service name and a number, such as `APIGateway.3`.

Type: String

Pattern: `.*\S.*`

Required: Yes

StandardsArn

The Amazon Resource Name (ARN) of a security standard.

Type: String

Pattern: `.*\S.*`

Required: Yes

RelatedRequirements

The requirement that underlies a control in the compliance framework related to the standard.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

StandardsControlArns

Provides the input parameter that Security Hub uses to call the [UpdateStandardsControl](#) API. This API can be used to enable or disable a control in a specified standard.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

StandardsControlDescription

The description of a control. This typically summarizes how Security Hub evaluates the control and the conditions under which it produces a failed finding. This parameter may reference a specific standard.

Type: String

Pattern: `.*\S.*`

Required: No

StandardsControlTitle

The title of a control. This field may reference a specific standard.

Type: String

Pattern: `.*\S.*`

Required: No

UpdatedAt

The time at which the enablement status of the control in the specified standard was last updated.

Type: Timestamp

Required: No

UpdatedReason

The reason for updating the enablement status of a control in a specified standard.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StandardsControlAssociationId

An array with one or more objects that includes a security control (identified with `SecurityControlId`, `SecurityControlArn`, or a mix of both parameters) and the Amazon Resource Name (ARN) of a standard. The security control ID or ARN is the same across standards.

Contents

SecurityControlId

The unique identifier (identified with `SecurityControlId`, `SecurityControlArn`, or a mix of both parameters) of a security control across standards.

Type: String

Pattern: `.*\S.*`

Required: Yes

StandardsArn

The ARN of a standard.

Type: String

Pattern: `.*\S.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StandardsControlAssociationSummary

An array that provides the enablement status and other details for each control that applies to each enabled standard.

Contents

AssociationStatus

The enablement status of a control in a specific standard.

Type: String

Valid Values: ENABLED | DISABLED

Required: Yes

SecurityControlArn

The ARN of a control, such as `arn:aws:securityhub:eu-central-1:123456789012:security-control/S3.1`. This parameter doesn't mention a specific standard.

Type: String

Pattern: `.*\S.*`

Required: Yes

SecurityControlId

A unique standard-agnostic identifier for a control. Values for this field typically consist of an Amazon Web Services service and a number, such as `APIGateway.5`. This field doesn't reference a specific standard.

Type: String

Pattern: `.*\S.*`

Required: Yes

StandardsArn

The Amazon Resource Name (ARN) of a standard.

Type: String

Pattern: `.*\S.*`

Required: Yes

RelatedRequirements

The requirement that underlies this control in the compliance framework related to the standard.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

StandardsControlDescription

The description of a control. This typically summarizes how Security Hub evaluates the control and the conditions under which it produces a failed finding. The parameter may reference a specific standard.

Type: String

Pattern: `.*\S.*`

Required: No

StandardsControlTitle

The title of a control.

Type: String

Pattern: `.*\S.*`

Required: No

UpdatedAt

The last time that a control's enablement status in a specified standard was updated.

Type: Timestamp

Required: No

UpdatedReason

The reason for updating a control's enablement status in a specified standard.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StandardsControlAssociationUpdate

An array of requested updates to the enablement status of controls in specified standards. The objects in the array include a security control ID, the Amazon Resource Name (ARN) of the standard, the requested enablement status, and the reason for updating the enablement status.

Contents

AssociationStatus

The desired enablement status of the control in the standard.

Type: String

Valid Values: ENABLED | DISABLED

Required: Yes

SecurityControlId

The unique identifier for the security control whose enablement status you want to update.

Type: String

Pattern: `.*\S.*`

Required: Yes

StandardsArn

The Amazon Resource Name (ARN) of the standard in which you want to update the control's enablement status.

Type: String

Pattern: `.*\S.*`

Required: Yes

UpdatedReason

The reason for updating the control's enablement status in the standard.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StandardsManagedBy

Provides details about the management of a security standard.

Contents

Company

An identifier for the company that manages a specific security standard. For existing standards, the value is equal to `Amazon`.

Type: String

Pattern: `.*\S.*`

Required: No

Product

An identifier for the product that manages a specific security standard. For existing standards, the value is equal to the Amazon service that manages the standard.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StandardsStatusReason

The reason for the current status of your subscription to the standard.

Contents

StatusReasonCode

The reason code that represents the reason for the current status of a standard subscription.

Type: String

Valid Values: NO_AVAILABLE_CONFIGURATION_RECORDER |
MAXIMUM_NUMBER_OF_CONFIG_RULES_EXCEEDED | INTERNAL_ERROR

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StandardsSubscription

A resource that represents your subscription to a supported standard.

Contents

StandardsArn

The ARN of the standard.

Type: String

Pattern: `.*\S.*`

Required: Yes

StandardsInput

A key-value pair of input for the standard.

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: Yes

StandardsStatus

The status of your subscription to the standard. Possible values are:

- **PENDING** - The standard is in the process of being enabled. Or the standard is already enabled and Amazon Security Hub is adding new controls to the standard.
- **READY** - The standard is enabled.
- **INCOMPLETE** - The standard could not be enabled completely. One or more errors (`StandardsStatusReason`) occurred when Amazon Security Hub attempted to enable the standard.
- **DELETING** - The standard is in the process of being disabled.
- **FAILED** - The standard could not be disabled. One or more errors (`StandardsStatusReason`) occurred when Amazon Security Hub attempted to disable the standard.

Type: String

Valid Values: PENDING | READY | FAILED | DELETING | INCOMPLETE

Required: Yes

StandardsSubscriptionArn

The ARN of the resource that represents your subscription to the standard.

Type: String

Pattern: .*\\S.*

Required: Yes

StandardsControlsUpdatable

Specifies whether you can retrieve information about and configure individual controls that apply to the standard. Possible values are:

- `READY_FOR_UPDATES` - Controls in the standard can be retrieved and configured.
- `NOT_READY_FOR_UPDATES` - Controls in the standard cannot be retrieved or configured.

Type: String

Valid Values: `READY_FOR_UPDATES` | `NOT_READY_FOR_UPDATES`

Required: No

StandardsStatusReason

The reason for the current status.

Type: [StandardsStatusReason](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StandardsSubscriptionRequest

The standard that you want to enable.

Contents

StandardsArn

The ARN of the standard that you want to enable. To view the list of available standards and their ARNs, use the `DescribeStandards` operation.

Type: String

Pattern: `.*\S.*`

Required: Yes

StandardsInput

A key-value pair of input for the standard.

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StatusReason

Provides additional context for the value of `Compliance.Status`.

Contents

ReasonCode

A code that represents a reason for the control status. For the list of status reason codes and their meanings, see [Compliance details for control findings](#) in the *Amazon Security Hub User Guide*.

Type: String

Pattern: `.*\S.*`

Required: Yes

Description

The corresponding description for the status reason code.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StringConfigurationOptions

The options for customizing a security control parameter that is a string.

Contents

DefaultValue

The Security Hub default value for a control parameter that is a string.

Type: String

Pattern: `.*\S.*`

Required: No

ExpressionDescription

The description of the RE2 regular expression.

Type: String

Pattern: `.*\S.*`

Required: No

Re2Expression

An RE2 regular expression that Security Hub uses to validate a user-provided control parameter string.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StringFilter

A string filter for filtering Amazon Security Hub findings.

Contents

Comparison

The condition to apply to a string value when filtering Security Hub findings.

To search for values that have the filter value, use one of the following comparison operators:

- To search for values that include the filter value, use `CONTAINS`. For example, the filter `Title CONTAINS CloudFront` matches findings that have a `Title` that includes the string `CloudFront`.
- To search for values that exactly match the filter value, use `EQUALS`. For example, the filter `AwsAccountId EQUALS 123456789012` only matches findings that have an account ID of `123456789012`.
- To search for values that start with the filter value, use `PREFIX`. For example, the filter `ResourceRegion PREFIX us` matches findings that have a `ResourceRegion` that starts with `us`. A `ResourceRegion` that starts with a different value, such as `af`, `ap`, or `ca`, doesn't match.

`CONTAINS`, `EQUALS`, and `PREFIX` filters on the same field are joined by `OR`. A finding matches if it matches any one of those filters. For example, the filters `Title CONTAINS CloudFront` `OR` `Title CONTAINS CloudWatch` match a finding that includes either `CloudFront`, `CloudWatch`, or both strings in the title.

To search for values that don't have the filter value, use one of the following comparison operators:

- To search for values that exclude the filter value, use `NOT_CONTAINS`. For example, the filter `Title NOT_CONTAINS CloudFront` matches findings that have a `Title` that excludes the string `CloudFront`.
- To search for values other than the filter value, use `NOT_EQUALS`. For example, the filter `AwsAccountId NOT_EQUALS 123456789012` only matches findings that have an account ID other than `123456789012`.
- To search for values that don't start with the filter value, use `PREFIX_NOT_EQUALS`. For example, the filter `ResourceRegion PREFIX_NOT_EQUALS us` matches findings with a `ResourceRegion` that starts with a value other than `us`.

NOT_CONTAINS, NOT_EQUALS, and PREFIX_NOT_EQUALS filters on the same field are joined by AND. A finding matches only if it matches all of those filters. For example, the filters `Title NOT_CONTAINS CloudFront AND Title NOT_CONTAINS CloudWatch` match a finding that excludes both `CloudFront` and `CloudWatch` in the title.

You can't have both a CONTAINS filter and a NOT_CONTAINS filter on the same field. Similarly, you can't provide both an EQUALS filter and a NOT_EQUALS or PREFIX_NOT_EQUALS filter on the same field. Combining filters in this way returns an error. CONTAINS filters can only be used with other CONTAINS filters. NOT_CONTAINS filters can only be used with other NOT_CONTAINS filters.

You can combine PREFIX filters with NOT_EQUALS or PREFIX_NOT_EQUALS filters for the same field. Security Hub first processes the PREFIX filters, and then the NOT_EQUALS or PREFIX_NOT_EQUALS filters.

For example, for the following filters, Security Hub first identifies findings that have resource types that start with either `AwsIam` or `AwsEc2`. It then excludes findings that have a resource type of `AwsIamPolicy` and findings that have a resource type of `AwsEc2NetworkInterface`.

- `ResourceType PREFIX AwsIam`
- `ResourceType PREFIX AwsEc2`
- `ResourceType NOT_EQUALS AwsIamPolicy`
- `ResourceType NOT_EQUALS AwsEc2NetworkInterface`

CONTAINS and NOT_CONTAINS operators can be used only with automation rules. For more information, see [Automation rules](#) in the *Amazon Security Hub User Guide*.

Type: String

Valid Values: EQUALS | PREFIX | NOT_EQUALS | PREFIX_NOT_EQUALS | CONTAINS | NOT_CONTAINS

Required: No

Value

The string filter value. Filter values are case sensitive. For example, the product name for control-based findings is `Security Hub`. If you provide `security hub` as the filter value, there's no match.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StringListConfigurationOptions

The options for customizing a security control parameter that is a list of strings.

Contents

DefaultValue

The Security Hub default value for a control parameter that is a list of strings.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

ExpressionDescription

The description of the RE2 regular expression.

Type: String

Pattern: `.*\S.*`

Required: No

MaxItems

The maximum number of list items that a string list control parameter can accept.

Type: Integer

Required: No

Re2Expression

An RE2 regular expression that Security Hub uses to validate a user-provided list of strings for a control parameter.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Target

The target account, organizational unit, or the root that is associated with an Amazon Security Hub configuration. The configuration can be a configuration policy or self-managed behavior.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

AccountId

The Amazon Web Services account ID of the target account.

Type: String

Pattern: `.*\S.*`

Required: No

OrganizationalUnitId

The organizational unit ID of the target organizational unit.

Type: String

Pattern: `.*\S.*`

Required: No

RootId

The ID of the organization root.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Threat

Provides information about the threat detected in a security finding and the file paths that were affected by the threat.

Contents

FilePaths

Provides information about the file paths that were affected by the threat.

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Type: Array of [FilePaths](#) objects

Required: No

ItemCount

This total number of items in which the threat has been detected.

Type: Integer

Required: No

Name

The name of the threat.

Length Constraints: Minimum of 1 length. Maximum of 128 length.

Type: String

Pattern: .*\\S.*

Required: No

Severity

The severity of the threat.

Length Constraints: Minimum of 1 length. Maximum of 128 length.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ThreatIntelIndicator

Details about the threat intelligence related to a finding.

Contents

Category

The category of a threat intelligence indicator.

Type: String

Valid Values: BACKDOOR | CARD_STEALER | COMMAND_AND_CONTROL | DROP_SITE | EXPLOIT_SITE | KEYLOGGER

Required: No

LastObservedAt

Indicates when the most recent instance of a threat intelligence indicator was observed.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

Source

The source of the threat intelligence indicator.

Length Constraints: Minimum of 1 length. Maximum of 64 length.

Type: String

Pattern: .*\\S.*

Required: No

SourceUrl

The URL to the page or site where you can get more information about the threat intelligence indicator.

Type: String

Pattern: .*\\S.*

Required: No

Type

The type of threat intelligence indicator.

Type: String

Valid Values: DOMAIN | EMAIL_ADDRESS | HASH_MD5 | HASH_SHA1 | HASH_SHA256 | HASH_SHA512 | IPV4_ADDRESS | IPV6_ADDRESS | MUTEX | PROCESS | URL

Required: No

Value

The value of a threat intelligence indicator.

Length Constraints: Minimum of 1 length. Maximum of 512 length.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

UnprocessedAutomationRule

A list of objects containing `RuleArn`, `ErrorCode`, and `ErrorMessage`. This parameter tells you which automation rules the request didn't process and why.

Contents

ErrorCode

The error code associated with the unprocessed automation rule.

Type: Integer

Required: No

ErrorMessage

An error message describing why a request didn't process a specific rule.

Type: String

Pattern: `.*\S.*`

Required: No

RuleArn

The Amazon Resource Name (ARN) for the unprocessed automation rule.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

UnprocessedConfigurationPolicyAssociation

An array of configuration policy associations, one for each configuration policy association identifier, that was specified in a `BatchGetConfigurationPolicyAssociations` request but couldn't be processed due to an error.

Contents

ConfigurationPolicyAssociationIdentifiers

Configuration policy association identifiers that were specified in a `BatchGetConfigurationPolicyAssociations` request but couldn't be processed due to an error.

Type: [ConfigurationPolicyAssociation](#) object

Required: No

ErrorCode

An HTTP status code that identifies why the configuration policy association failed.

Type: String

Pattern: `.*\S.*`

Required: No

ErrorReason

A string that identifies why the configuration policy association failed.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

UnprocessedSecurityControl

Provides details about a security control for which a response couldn't be returned.

Contents

ErrorCode

The error code for the unprocessed security control.

Type: String

Valid Values: INVALID_INPUT | ACCESS_DENIED | NOT_FOUND | LIMIT_EXCEEDED

Required: Yes

SecurityControlId

The control (identified with SecurityControlId, SecurityControlArn, or a mix of both parameters) for which a response couldn't be returned.

Type: String

Pattern: .*\\S.*

Required: Yes

ErrorReason

The reason why the security control was unprocessed.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

UnprocessedStandardsControlAssociation

Provides details about which control's enablement status couldn't be retrieved in a specified standard when calling [BatchUpdateStandardsControlAssociations](#). This parameter also provides details about why the request was unprocessed.

Contents

ErrorCode

The error code for the unprocessed standard and control association.

Type: String

Valid Values: INVALID_INPUT | ACCESS_DENIED | NOT_FOUND | LIMIT_EXCEEDED

Required: Yes

StandardsControlAssociationId

An array with one or more objects that includes a security control (identified with `SecurityControlId`, `SecurityControlArn`, or a mix of both parameters) and the Amazon Resource Name (ARN) of a standard. This parameter shows the specific controls for which the enablement status couldn't be retrieved in specified standards when calling [BatchUpdateStandardsControlAssociations](#).

Type: [StandardsControlAssociationId](#) object

Required: Yes

ErrorReason

The reason why the standard and control association was unprocessed.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

UnprocessedStandardsControlAssociationUpdate

Provides details about which control's enablement status could not be updated in a specified standard when calling the [BatchUpdateStandardsControlAssociations](#) API. This parameter also provides details about why the request was unprocessed.

Contents

ErrorCode

The error code for the unprocessed update of the control's enablement status in the specified standard.

Type: String

Valid Values: INVALID_INPUT | ACCESS_DENIED | NOT_FOUND | LIMIT_EXCEEDED

Required: Yes

StandardsControlAssociationUpdate

An array of control and standard associations for which an update failed when calling [BatchUpdateStandardsControlAssociations](#).

Type: [StandardsControlAssociationUpdate](#) object

Required: Yes

ErrorReason

The reason why a control's enablement status in the specified standard couldn't be updated.

Type: String

Pattern: .*S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

UpdateAutomationRulesRequestItem

Specifies the parameters to update in an existing automation rule.

Contents

RuleArn

The Amazon Resource Name (ARN) for the rule.

Type: String

Pattern: `.*\S.*`

Required: Yes

Actions

One or more actions to update finding fields if a finding matches the conditions specified in `Criteria`.

Type: Array of [AutomationRulesAction](#) objects

Array Members: Fixed number of 1 item.

Required: No

Criteria

A set of ASFF finding field attributes and corresponding expected values that Security Hub uses to filter findings. If a rule is enabled and a finding matches the conditions specified in this parameter, Security Hub applies the rule action to the finding.

Type: [AutomationRulesFindingFilters](#) object

Required: No

Description

A description of the rule.

Type: String

Pattern: `.*\S.*`

Required: No

IsTerminal

Specifies whether a rule is the last to be applied with respect to a finding that matches the rule criteria. This is useful when a finding matches the criteria for multiple rules, and each rule has different actions. If a rule is terminal, Security Hub applies the rule action to a finding that matches the rule criteria and doesn't evaluate other rules for the finding. By default, a rule isn't terminal.

Type: Boolean

Required: No

RuleName

The name of the rule.

Type: String

Pattern: `.*\S.*`

Required: No

RuleOrder

An integer ranging from 1 to 1000 that represents the order in which the rule action is applied to findings. Security Hub applies rules with lower values for this parameter first.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

RuleStatus

Whether the rule is active after it is created. If this parameter is equal to `ENABLED`, Security Hub starts applying the rule to findings and finding updates after the rule is created. To change the value of this parameter after creating a rule, use [BatchUpdateAutomationRules](#).

Type: String

Valid Values: `ENABLED` | `DISABLED`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

UserAccount

Provides Amazon Web Services account information of the user involved in an Amazon GuardDuty Extended Threat Detection attack sequence. GuardDuty generates an attack sequence finding when multiple events align to a potentially suspicious activity. To receive GuardDuty attack sequence findings in Amazon Security Hub, you must have GuardDuty enabled. For more information, see [GuardDuty Extended Threat Detection](#) in the *Amazon GuardDuty User Guide*.

Contents

Name

The name of the user account involved in the attack sequence.

Type: String

Pattern: `.*\S.*`

Required: No

Uid

The unique identifier of the user account involved in the attack sequence.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Vulnerability

A vulnerability associated with a finding.

Contents

Id

The identifier of the vulnerability.

Type: String

Pattern: `.*\S.*`

Required: Yes

CodeVulnerabilities

The vulnerabilities found in your Amazon Lambda function code. This field pertains to findings that Amazon Security Hub receives from Amazon Inspector.

Type: Array of [VulnerabilityCodeVulnerabilities](#) objects

Required: No

Cvss

CVSS scores from the advisory related to the vulnerability.

Type: Array of [Cvss](#) objects

Required: No

EpssScore

The Exploit Prediction Scoring System (EPSS) score for a finding.

Type: Double

Required: No

ExploitAvailable

Whether an exploit is available for a finding.

Type: String

Valid Values: YES | NO

Required: No

FixAvailable

Specifies if all vulnerable packages in a finding have a value for `FixedInVersion` and `Remediation`. This field is evaluated for each vulnerability `Id` based on the number of vulnerable packages that have a value for both `FixedInVersion` and `Remediation`. Valid values are as follows:

- YES if all vulnerable packages have a value for both `FixedInVersion` and `Remediation`
- NO if no vulnerable packages have a value for `FixedInVersion` and `Remediation`
- PARTIAL otherwise

Type: String

Valid Values: YES | NO | PARTIAL

Required: No

LastKnownExploitAt

The date and time of the last exploit associated with a finding discovered in your environment.

Type: String

Pattern: `.*\S.*`

Required: No

ReferenceUrls

A list of URLs that provide additional information about the vulnerability.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

RelatedVulnerabilities

List of vulnerabilities that are related to this vulnerability.

Type: Array of strings

Pattern: .*\\S.*

Required: No

Vendor

Information about the vendor that generates the vulnerability report.

Type: [VulnerabilityVendor](#) object

Required: No

VulnerablePackages

List of software packages that have the vulnerability.

Type: Array of [SoftwarePackage](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

VulnerabilityCodeVulnerabilities

Provides details about the vulnerabilities found in your Amazon Lambda function code. This field pertains to findings that Amazon Security Hub receives from Amazon Inspector.

Contents

Cwes

The Common Weakness Enumeration (CWE) item associated with the detected code vulnerability.

Type: Array of strings

Pattern: .*\\S.*

Required: No

FilePath

Provides details about where a code vulnerability is located in your Amazon Lambda function.

Type: [CodeVulnerabilitiesFilePath](#) object

Required: No

SourceArn

The Amazon Resource Name (ARN) of the Lambda layer in which the code vulnerability is located.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

VulnerabilityVendor

A vendor that generates a vulnerability report.

Contents

Name

The name of the vendor.

Type: String

Pattern: `.*\S.*`

Required: Yes

Url

The URL of the vulnerability advisory.

Type: String

Pattern: `.*\S.*`

Required: No

VendorCreatedAt

Indicates when the vulnerability advisory was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

VendorSeverity

The severity that the vendor assigned to the vulnerability.

Type: String

Pattern: .*\\S.*

Required: No

VendorUpdatedAt

Indicates when the vulnerability advisory was last updated.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Workflow

Provides details about the status of the investigation into a finding.

Contents

Status

The status of the investigation into the finding. The workflow status is specific to an individual finding. It does not affect the generation of new findings. For example, setting the workflow status to SUPPRESSED or RESOLVED does not prevent a new finding for the same issue.

The allowed values are the following.

- NEW - The initial state of a finding, before it is reviewed.

Security Hub also resets the workflow status from NOTIFIED or RESOLVED to NEW in the following cases:

- RecordState changes from ARCHIVED to ACTIVE.
- ComplianceStatus changes from PASSED to either WARNING, FAILED, or NOT_AVAILABLE.
- NOTIFIED - Indicates that you notified the resource owner about the security issue. Used when the initial reviewer is not the resource owner, and needs intervention from the resource owner.
- SUPPRESSED - Indicates that you reviewed the finding and don't believe that any action is needed. The finding is no longer updated.
- RESOLVED - The finding was reviewed and remediated and is now considered resolved.

Type: String

Valid Values: NEW | NOTIFIED | RESOLVED | SUPPRESSED

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

WorkflowUpdate

Used to update information about the investigation into the finding.

Contents

Status

The status of the investigation into the finding. The workflow status is specific to an individual finding. It does not affect the generation of new findings. For example, setting the workflow status to SUPPRESSED or RESOLVED does not prevent a new finding for the same issue.

The allowed values are the following.

- NEW - The initial state of a finding, before it is reviewed.

Security Hub also resets `WorkFlowStatus` from NOTIFIED or RESOLVED to NEW in the following cases:

- The record state changes from ARCHIVED to ACTIVE.
- The compliance status changes from PASSED to either WARNING, FAILED, or NOT_AVAILABLE.
- NOTIFIED - Indicates that you notified the resource owner about the security issue. Used when the initial reviewer is not the resource owner, and needs intervention from the resource owner.
- RESOLVED - The finding was reviewed and remediated and is now considered resolved.
- SUPPRESSED - Indicates that you reviewed the finding and don't believe that any action is needed. The finding is no longer updated.

Type: String

Valid Values: NEW | NOTIFIED | RESOLVED | SUPPRESSED

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ASFF resource objects

Amazon Security Hub supports the following objects as part of the `ResourceDetails` data type. These objects apply to Security Hub findings in the Amazon Security Finding Format (ASFF).

Amazon MQ objects

- [AwsAmazonMqBrokerDetails](#)
- [AwsAmazonMqBrokerEncryptionOptionsDetails](#)
- [AwsAmazonMqBrokerLdapServerMetadataDetails](#)
- [AwsAmazonMqBrokerLogsDetails](#)
- [AwsAmazonMqBrokerLogsPendingDetails](#)
- [AwsAmazonMqBrokerMaintenanceWindowStartTimeDetails](#)
- [AwsAmazonMqBrokerUsersDetails](#)

Amazon API Gateway objects

- [AwsApiGatewayAccessLogSettings](#)
- [AwsApiGatewayCanarySettings](#)
- [AwsApiGatewayEndpointConfiguration](#)
- [AwsApiGatewayMethodSettings](#)
- [AwsApiGatewayRestApiDetails](#)
- [AwsApiGatewayStageDetails](#)
- [AwsApiGatewayV2ApiDetails](#)
- [AwsApiGatewayV2RouteSettings](#)
- [AwsApiGatewayV2StageDetails](#)
- [AwsCorsConfiguration](#)

Amazon AppSync objects

- [AwsAppSyncGraphQLApiDetails](#)
- [AwsAppSyncGraphQLApiAdditionalAuthenticationProvidersDetails](#)
- [AwsAppSyncGraphQLApiLambdaAuthorizerConfigDetails](#)
- [AwsAppSyncGraphQLApiLogConfigDetails](#)
- [AwsAppSyncGraphQLApiOpenIdConnectConfigDetails](#)
- [AwsAppSyncGraphQLApiUserPoolConfigDetails](#)

Amazon Athena objects

- [AwsAthenaWorkGroupConfigurationDetails](#)
- [AwsAthenaWorkGroupConfigurationResultConfigurationDetails](#)
- [AwsAthenaWorkGroupConfigurationResultConfigurationEncryptionConfigurationDetails](#)

Amazon Backup objects

- [AwsBackupBackupPlanAdvancedBackupSettingsDetails](#)
- [AwsBackupBackupPlanBackupPlanDetails](#)
- [AwsBackupBackupPlanDetails](#)
- [AwsBackupBackupPlanLifecycleDetails](#)
- [AwsBackupBackupPlanRuleCopyActionsDetails](#)
- [AwsBackupBackupPlanRuleDetails](#)
- [AwsBackupBackupVaultDetails](#)
- [AwsBackupBackupVaultNotificationsDetails](#)
- [AwsBackupRecoveryPointCalculatedLifecycleDetails](#)
- [AwsBackupRecoveryPointCreatedByDetails](#)
- [AwsBackupRecoveryPointDetails](#)
- [AwsBackupRecoveryPointLifecycleDetails](#)

Amazon Certificate Manager objects

- [AwsCertificateManagerCertificateDetails](#)

- [AwsCertificateManagerCertificateDomainValidationOption](#)
- [AwsCertificateManagerCertificateExtendedKeyUsage](#)
- [AwsCertificateManagerCertificateKeyUsage](#)
- [AwsCertificateManagerCertificateOptions](#)
- [AwsCertificateManagerCertificateRenewalSummary](#)
- [AwsCertificateManagerCertificateResourceRecord](#)

Amazon CloudFormation objects

- [AwsCloudFormationStackDetails](#)
- [AwsCloudFormationStackDriftInformationDetails](#)
- [AwsCloudFormationStackOutputsDetails](#)

Amazon CloudFront objects

- [AwsCloudFrontDistributionCacheBehavior](#)
- [AwsCloudFrontDistributionCacheBehaviors](#)
- [AwsCloudFrontDistributionDefaultCacheBehavior](#)
- [AwsCloudFrontDistributionDetails](#)
- [AwsCloudFrontDistributionLogging](#)
- [AwsCloudFrontDistributionOriginCustomOriginConfig](#)
- [AwsCloudFrontDistributionOriginGroup](#)
- [AwsCloudFrontDistributionOriginGroupFailover](#)
- [AwsCloudFrontDistributionOriginGroupFailoverStatusCodes](#)
- [AwsCloudFrontDistributionOriginGroups](#)
- [AwsCloudFrontDistributionOriginItem](#)
- [AwsCloudFrontDistributionOrigins](#)
- [AwsCloudFrontDistributionOriginS3OriginConfig](#)
- [AwsCloudFrontDistributionOriginSslProtocols](#)
- [AwsCloudFrontDistributionViewerCertificate](#)

Amazon CloudTrail objects

- [AwsCloudTrailTrailDetails](#)

Amazon CloudWatch objects

- [AwsCloudWatchAlarmDetails](#)
- [AwsCloudWatchAlarmDimensionsDetails](#)

Amazon CodeBuild objects

- [AwsCodeBuildProjectArtifactsDetails](#)
- [AwsCodeBuildProjectDetails](#)
- [AwsCodeBuildProjectEnvironment](#)
- [AwsCodeBuildProjectEnvironmentEnvironmentVariablesDetails](#)
- [AwsCodeBuildProjectEnvironmentRegistryCredential](#)
- [AwsCodeBuildProjectLogsConfigCloudWatchLogsDetails](#)
- [AwsCodeBuildProjectLogsConfigDetails](#)
- [AwsCodeBuildProjectLogsConfigS3LogsDetails](#)
- [AwsCodeBuildProjectSource](#)
- [AwsCodeBuildProjectVpcConfig](#)

Amazon Database Migration Service objects (Amazon DMS)

- [AwsDmsEndpointDetails](#)
- [AwsDmsReplicationInstanceDetails](#)
- [AwsDmsReplicationInstanceReplicationSubnetGroupDetails](#)
- [AwsDmsReplicationInstanceVpcSecurityGroupsDetails](#)
- [AwsDmsReplicationTaskDetails](#)

Amazon DynamoDB objects

- [AwsDynamoDbTableAttributeDefinition](#)
- [AwsDynamoDbTableBillingModeSummary](#)
- [AwsDynamoDbTableDetails](#)

- [AwsDynamoDbTableGlobalSecondaryIndex](#)
- [AwsDynamoDbTableKeySchema](#)
- [AwsDynamoDbTableLocalSecondaryIndex](#)
- [AwsDynamoDbTableProjection](#)
- [AwsDynamoDbTableProvisionedThroughput](#)
- [AwsDynamoDbTableProvisionedThroughputOverride](#)
- [AwsDynamoDbTableReplica](#)
- [AwsDynamoDbTableReplicaGlobalSecondaryIndex](#)
- [AwsDynamoDbTableRestoreSummary](#)
- [AwsDynamoDbTableSseDescription](#)
- [AwsDynamoDbTableStreamSpecification](#)

Amazon Elastic Compute Cloud (EC2) objects

- [AwsEc2ClientVpnEndpointAuthenticationOptionsActiveDirectoryDetails](#)
- [AwsEc2ClientVpnEndpointAuthenticationOptionsDetails](#)
- [AwsEc2ClientVpnEndpointAuthenticationOptionsFederatedAuthenticationDetails](#)
- [AwsEc2ClientVpnEndpointAuthenticationOptionsMutualAuthenticationDetails](#)
- [AwsEc2ClientVpnEndpointClientConnectOptionsDetails](#)
- [AwsEc2ClientVpnEndpointClientConnectOptionsStatusDetails](#)
- [AwsEc2ClientVpnEndpointClientLoginBannerOptionsDetails](#)
- [AwsEc2ClientVpnEndpointConnectionLogOptionsDetails](#)
- [AwsEc2ClientVpnEndpointDetails](#)
- [AwsEc2EipDetails](#)
- [AwsEc2InstanceDetails](#)
- [AwsEc2InstanceMetadataOptions](#)
- [AwsEc2InstanceMonitoringDetails](#)
- [AwsEc2InstanceNetworkInterfacesDetails](#)
- [AwsEc2LaunchTemplateDataBlockDeviceMappingSetDetails](#)
- [AwsEc2LaunchTemplateDataBlockDeviceMappingSetEbsDetails](#)

- [AwsEc2LaunchTemplateDataCapacityReservationSpecificationCapacityReservationTargetDetails](#)
- [AwsEc2LaunchTemplateDataCapacityReservationSpecificationDetails](#)
- [AwsEc2LaunchTemplateDataCpuOptionsDetails](#)
- [AwsEc2LaunchTemplateDataCreditSpecificationDetails](#)
- [AwsEc2LaunchTemplateDataDetails](#)
- [AwsEc2LaunchTemplateDataElasticGpuSpecificationSetDetails](#)
- [AwsEc2LaunchTemplateDataElasticInferenceAcceleratorSetDetails](#)
- [AwsEc2LaunchTemplateDataEnclaveOptionsDetails](#)
- [AwsEc2LaunchTemplateDataHibernationOptionsDetails](#)
- [AwsEc2LaunchTemplateDataIamInstanceProfileDetails](#)
- [AwsEc2LaunchTemplateDataInstanceMarketOptionsDetails](#)
- [AwsEc2LaunchTemplateDataInstanceMarketOptionsSpotOptionsDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsAcceleratorCountDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsAcceleratorTotalMemoryMiBDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsBaselineEbsBandwidthMbpsDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsMemoryGiBPerVCpuDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsMemoryMiBDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsNetworkInterfaceCountDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsTotalLocalStorageGBDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsVCpuCountDetails](#)
- [AwsEc2LaunchTemplateDataLicenseSetDetails](#)
- [AwsEc2LaunchTemplateDataMaintenanceOptionsDetails](#)
- [AwsEc2LaunchTemplateDataMetadataOptionsDetails](#)
- [AwsEc2LaunchTemplateDataMonitoringDetails](#)
- [AwsEc2LaunchTemplateDataNetworkInterfaceSetDetails](#)
- [AwsEc2LaunchTemplateDataNetworkInterfaceSetIpv4PrefixesDetails](#)
- [AwsEc2LaunchTemplateDataNetworkInterfaceSetIpv6AddressesDetails](#)
- [AwsEc2LaunchTemplateDataNetworkInterfaceSetIpv6PrefixesDetails](#)
- [AwsEc2LaunchTemplateDataNetworkInterfaceSetPrivateIpAddressesDetails](#)

- [AwsEc2LaunchTemplateDataPlacementDetails](#)
- [AwsEc2LaunchTemplateDataPrivateDnsNameOptionsDetails](#)
- [AwsEc2LaunchTemplateDetails](#)
- [AwsEc2NetworkAclAssociation](#)
- [AwsEc2NetworkAclDetails](#)
- [AwsEc2NetworkAclEntry](#)
- [PortRange](#)
- [PortRangeFromTo](#)
- [AwsEc2NetworkInterfaceAttachment](#)
- [AwsEc2NetworkInterfaceDetails](#)
- [AwsEc2NetworkInterfaceIpv6AddressDetail](#)
- [AwsEc2NetworkInterfacePrivateIpAddressDetail](#)
- [AwsEc2NetworkInterfaceSecurityGroup](#)
- [AwsEc2RouteTableDetails](#)
- [RouteSetDetails](#)
- [AssociationSetDetails](#)
- [AssociationStateDetails](#)
- [PropagatingVgwSetDetails](#)
- [AwsEc2SecurityGroupDetails](#)
- [AwsEc2SecurityGroupIpPermission](#)
- [AwsEc2SecurityGroupIpRange](#)
- [AwsEc2SecurityGroupIpv6Range](#)
- [AwsEc2SecurityGroupPrefixListId](#)
- [AwsEc2SecurityGroupUserIdGroupPair](#)
- [AwsEc2SubnetDetails](#)
- [Ipv6CidrBlockAssociation](#)
- [AvailabilityZone](#)
- [AwsEc2TransitGatewayDetails](#)
- [AwsEc2VolumeAttachment](#)
- [AwsEc2VolumeDetails](#)

- [AwsEc2VpcDetails](#)
- [CidrBlockAssociation](#)
- [AwsEc2VpcEndpointServiceDetails](#)
- [AwsEc2VpcEndpointServiceServiceTypeDetails](#)
- [AwsEc2VpcPeeringConnectionDetails](#)
- [VpcInfoCidrBlockSetDetails](#)
- [VpcInfoIpv6CidrBlockSetDetails](#)
- [VpcInfoPeeringOptionsDetails](#)
- [AwsEc2VpcPeeringConnectionStatusDetails](#)
- [AwsEc2VpcPeeringConnectionVpcInfoDetails](#)
- [AwsEc2VpnConnectionDetails](#)
- [AwsEc2VpnConnectionOptionsDetails](#)
- [AwsEc2VpnConnectionOptionsTunnelOptionsDetails](#)
- [AwsEc2VpnConnectionRoutesDetails](#)
- [AwsEc2VpnConnectionVgwTelemetryDetails](#)

Amazon EC2 Auto Scaling objects

- [AwsAutoScalingAutoScalingGroupAvailabilityZonesListDetails](#)
- [AwsAutoScalingAutoScalingGroupDetails](#)
- [AwsAutoScalingAutoScalingGroupLaunchTemplateLaunchTemplateSpecification](#)
- [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyDetails](#)
- [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyInstancesDistributionDetails](#)
- [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyLaunchTemplateDetails](#)
- [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyLaunchTemplateLaunchTemplateSpecification](#)
- [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyLaunchTemplateOverridesListDetails](#)
- [AwsAutoScalingLaunchConfigurationBlockDeviceMappingsDetails](#)
- [AwsAutoScalingLaunchConfigurationBlockDeviceMappingsEbsDetails](#)
- [AwsAutoScalingLaunchConfigurationDetails](#)
- [AwsAutoScalingLaunchConfigurationInstanceMonitoringDetails](#)
- [AwsAutoScalingLaunchConfigurationMetadataOptions](#)

Amazon Elastic Container Registry (ECR) objects

- [AwsEcrContainerImageDetails](#)
- [AwsEcrRepositoryDetails](#)
- [AwsEcrRepositoryImageScanningConfigurationDetails](#)
- [AwsEcrRepositoryLifecyclePolicyDetails](#)

Amazon Elastic Container Service (ECS) objects

- [AwsEcsClusterClusterSettingsDetails](#)
- [AwsEcsClusterConfigurationDetails](#)
- [AwsEcsClusterConfigurationExecuteCommandConfigurationDetails](#)
- [AwsEcsClusterConfigurationExecuteCommandConfigurationLogConfigurationDetails](#)
- [AwsEcsClusterDefaultCapacityProviderStrategyDetails](#)
- [AwsEcsClusterDetails](#)
- [AwsEcsContainerDetails](#)
- [AwsEcsServiceCapacityProviderStrategyDetails](#)
- [AwsEcsServiceDeploymentConfigurationDeploymentCircuitBreakerDetails](#)
- [AwsEcsServiceDeploymentConfigurationDetails](#)
- [AwsEcsServiceDeploymentControllerDetails](#)
- [AwsEcsServiceDetails](#)
- [AwsEcsServiceLoadBalancersDetails](#)
- [AwsEcsServiceNetworkConfigurationAwsVpcConfigurationDetails](#)
- [AwsEcsServiceNetworkConfigurationDetails](#)
- [AwsEcsServicePlacementConstraintsDetails](#)
- [AwsEcsServicePlacementStrategiesDetails](#)
- [AwsEcsServiceServiceRegistriesDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsDependsOnDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsEnvironmentDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsEnvironmentFilesDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsExtraHostsDetails](#)

- [AwsEcsTaskDefinitionContainerDefinitionsFirelensConfigurationDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsHealthCheckDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersCapabilitiesDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersDevicesDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersTmpfsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLogConfigurationDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLogConfigurationSecretOptionsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsMountPointsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsPortMappingsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsRepositoryCredentialsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsResourceRequirementsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsSecretsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsSystemControlsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsUlimitsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsVolumesFromDetails](#)
- [AwsEcsTaskDefinitionDetails](#)
- [AwsEcsTaskDefinitionInferenceAcceleratorsDetails](#)
- [AwsEcsTaskDefinitionPlacementConstraintsDetails](#)
- [AwsEcsTaskDefinitionProxyConfigurationDetails](#)
- [AwsEcsTaskDefinitionProxyConfigurationProxyConfigurationPropertiesDetails](#)
- [AwsEcsTaskDefinitionVolumesDetails](#)
- [AwsEcsTaskDefinitionVolumesDockerVolumeConfigurationDetails](#)
- [AwsEcsTaskDefinitionVolumesEfsVolumeConfigurationAuthorizationConfigDetails](#)
- [AwsEcsTaskDefinitionVolumesEfsVolumeConfigurationDetails](#)
- [AwsEcsTaskDefinitionVolumesHostDetails](#)
- [AwsEcsTaskDetails](#)
- [AwsEcsTaskVolumeDetails](#)
- [AwsEcsTaskVolumeHostDetails](#)
- [AwsMountPoint](#)

Amazon Elastic File System (EFS) objects

- [AwsEfsAccessPointDetails](#)
- [AwsEfsAccessPointPosixUserDetails](#)
- [AwsEfsAccessPointRootDirectoryCreationInfoDetails](#)
- [AwsEfsAccessPointRootDirectoryDetails](#)

Amazon Elastic Kubernetes Service (EKS) objects

- [AwsEksClusterDetails](#)
- [AwsEksClusterLoggingClusterLoggingDetails](#)
- [AwsEksClusterLoggingDetails](#)
- [AwsEksClusterResourcesVpcConfigDetails](#)

Amazon Elastic Beanstalk objects

- [AwsElasticBeanstalkEnvironmentDetails](#)
- [AwsElasticBeanstalkEnvironmentEnvironmentLink](#)
- [AwsElasticBeanstalkEnvironmentOptionSetting](#)
- [AwsElasticBeanstalkEnvironmentTier](#)

Elasticsearch objects

- [AwsElasticsearchDomainDetails](#)
- [AwsElasticsearchDomainDomainEndpointOptions](#)
- [AwsElasticsearchDomainElasticsearchClusterConfigDetails](#)
- [AwsElasticsearchDomainElasticsearchClusterConfigZoneAwarenessConfigDetails](#)
- [AwsElasticsearchDomainEncryptionAtRestOptions](#)
- [AwsElasticsearchDomainLogPublishingOptions](#)
- [AwsElasticsearchDomainLogPublishingOptionsLogConfig](#)
- [AwsElasticsearchDomainNodeToNodeEncryptionOptions](#)
- [AwsElasticsearchDomainServiceSoftwareOptions](#)
- [AwsElasticsearchDomainVPCOptions](#)

Elastic Load Balancing objects

- [AwsElbAppCookieStickinessPolicy](#)
- [AwsElbLbCookieStickinessPolicy](#)
- [AwsElbLoadBalancerAccessLog](#)
- [AwsElbLoadBalancerAdditionalAttribute](#)
- [AwsElbLoadBalancerAttributes](#)
- [AwsElbLoadBalancerBackendServerDescription](#)
- [AwsElbLoadBalancerConnectionDraining](#)
- [AwsElbLoadBalancerConnectionSettings](#)
- [AwsElbLoadBalancerCrossZoneLoadBalancing](#)
- [AwsElbLoadBalancerDetails](#)
- [AwsElbLoadBalancerHealthCheck](#)
- [AwsElbLoadBalancerInstance](#)
- [AwsElbLoadBalancerListener](#)
- [AwsElbLoadBalancerListenerDescription](#)
- [AwsElbLoadBalancerPolicies](#)
- [AwsElbLoadBalancerSourceSecurityGroup](#)
- [AwsElbv2LoadBalancerAttribute](#)
- [AwsElbv2LoadBalancerDetails](#)
- [LoadBalancerState](#)

Amazon EventBridge objects

- [AwsEventSchemasRegistryDetails](#)
- [AwsEventsEndpointDetails](#)
- [AwsEventsEndpointEventBusesDetails](#)
- [AwsEventsEndpointReplicationConfigDetails](#)
- [AwsEventsEndpointRoutingConfigDetails](#)
- [AwsEventsEndpointRoutingConfigFailoverConfigDetails](#)
- [AwsEventsEndpointRoutingConfigFailoverConfigPrimaryDetails](#)
- [AwsEventsEndpointRoutingConfigFailoverConfigSecondaryDetails](#)

- [AwsEventsEventbusDetails](#)

Amazon GuardDuty objects

- [AwsGuardDutyDetectorDataSourcesCloudTrailDetails](#)
- [AwsGuardDutyDetectorDataSourcesDetails](#)
- [AwsGuardDutyDetectorDataSourcesDnsLogsDetails](#)
- [AwsGuardDutyDetectorDataSourcesFlowLogsDetails](#)
- [AwsGuardDutyDetectorDataSourcesKubernetesAuditLogsDetails](#)
- [AwsGuardDutyDetectorDataSourcesKubernetesDetails](#)
- [AwsGuardDutyDetectorDataSourcesMalwareProtectionDetails](#)
- [AwsGuardDutyDetectorDataSourcesMalwareProtectionScanEc2InstanceWithFindingsDetails](#)
- [AwsGuardDutyDetectorDataSourcesMalwareProtectionScanEc2InstanceWithFindingsEbsVolumesDetails](#)
- [AwsGuardDutyDetectorDataSourcesS3LogsDetails](#)
- [AwsGuardDutyDetectorDetails](#)
- [AwsGuardDutyDetectorFeaturesDetails](#)

Amazon Identity and Access Management (IAM) objects

- [AwsIamAccessKeyDetails](#)
- [AwsIamAccessKeySessionContext](#)
- [AwsIamAccessKeySessionContextAttributes](#)
- [AwsIamAccessKeySessionContextSessionIssuer](#)
- [AwsIamAttachedManagedPolicy](#)
- [AwsIamGroupDetails](#)
- [AwsIamGroupPolicy](#)
- [AwsIamInstanceProfile](#)
- [AwsIamInstanceProfileRole](#)
- [AwsIamPermissionsBoundary](#)
- [AwsIamPolicyDetails](#)
- [AwsIamPolicyVersion](#)
- [AwsIamRoleDetails](#)

- [AwsIamRolePolicy](#)
- [AwsIamUserDetails](#)
- [AwsIamUserPolicy](#)

Amazon Kinesis objects

- [AwsKinesisStreamDetails](#)
- [AwsKinesisStreamStreamEncryptionDetails](#)

Amazon Key Management Service (Amazon KMS) objects

- [AwsKmsKeyDetails](#)

Amazon Lambda objects

- [AwsLambdaFunctionCode](#)
- [AwsLambdaFunctionDeadLetterConfig](#)
- [AwsLambdaFunctionDetails](#)
- [AwsLambdaFunctionEnvironment](#)
- [AwsLambdaFunctionEnvironmentError](#)
- [AwsLambdaFunctionLayer](#)
- [AwsLambdaFunctionTracingConfig](#)
- [AwsLambdaFunctionVpcConfig](#)
- [AwsLambdaLayerVersionDetails](#)

Amazon Managed Streaming for Apache Kafka (Amazon MSK) objects

- [AwsMskClusterDetails](#)
- [AwsMskClusterClusterInfoClientAuthenticationDetails](#)
- [AwsMskClusterClusterInfoClientAuthenticationSaslDetails](#)
- [AwsMskClusterClusterInfoClientAuthenticationSaslIamDetails](#)
- [AwsMskClusterClusterInfoClientAuthenticationSaslScramDetails](#)
- [AwsMskClusterClusterInfoClientAuthenticationTlsDetails](#)

- [AwsMskClusterClusterInfoClientAuthenticationUnauthenticatedDetails](#)
- [AwsMskClusterClusterInfoDetails](#)
- [AwsMskClusterClusterInfoEncryptionInfoDetails](#)
- [AwsMskClusterClusterInfoEncryptionInfoEncryptionAtRestDetails](#)
- [AwsMskClusterClusterInfoEncryptionInfoEncryptionInTransitDetails](#)

Amazon Network Firewall objects

- [AwsNetworkFirewallFirewallDetails](#)
- [AwsNetworkFirewallFirewallPolicyDetails](#)
- [FirewallPolicyDetails](#)
- [FirewallPolicyStatelessCustomActionsDetails](#)
- [StatelessCustomActionDefinition](#)
- [StatelessCustomPublishMetricAction](#)
- [StatelessCustomPublishMetricActionDimension](#)
- [AwsNetworkFirewallFirewallSubnetMappingsDetails](#)
- [AwsNetworkFirewallRuleGroupDetails](#)
- [RuleGroupDetails](#)
- [RuleGroupSource](#)
- [RuleGroupSourceCustomActionsDetails](#)
- [RuleGroupSourceListDetails](#)
- [RuleGroupSourceStatefulRulesDetails](#)
- [RuleGroupSourceStatefulRulesHeaderDetails](#)
- [RuleGroupSourceStatefulRulesOptionsDetails](#)
- [RuleGroupSourceStatelessRuleDefinition](#)
- [RuleGroupSourceStatelessRuleMatchAttributes](#)
- [RuleGroupSourceStatelessRuleMatchAttributesDestinationPorts](#)
- [RuleGroupSourceStatelessRuleMatchAttributesDestinations](#)
- [RuleGroupSourceStatelessRuleMatchAttributesSourcePorts](#)
- [RuleGroupSourceStatelessRuleMatchAttributesSources](#)
- [RuleGroupSourceStatelessRuleMatchAttributesTcpFlags](#)

- [RuleGroupSourceStatelessRulesAndCustomActionsDetails](#)
- [RuleGroupSourceStatelessRulesDetails](#)
- [RuleGroupVariables](#)
- [RuleGroupVariablesIpSetsDetails](#)
- [RuleGroupVariablesPortSetsDetails](#)
- [NetworkHeader](#)
- [FirewallPolicyStatefulRuleGroupReferencesDetails](#)
- [FirewallPolicyStatelessRuleGroupReferencesDetails](#)

Amazon OpenSearch Service objects

- [AwsOpenSearchServiceDomainAdvancedSecurityOptionsDetails](#)
- [AwsOpenSearchServiceDomainClusterConfigDetails](#)
- [AwsOpenSearchServiceDomainClusterConfigZoneAwarenessConfigDetails](#)
- [AwsOpenSearchServiceDomainDetails](#)
- [AwsOpenSearchServiceDomainDomainEndpointOptionsDetails](#)
- [AwsOpenSearchServiceDomainEncryptionAtRestOptionsDetails](#)
- [AwsOpenSearchServiceDomainLogPublishingOption](#)
- [AwsOpenSearchServiceDomainLogPublishingOptionsDetails](#)
- [AwsOpenSearchServiceDomainMasterUserOptionsDetails](#)
- [AwsOpenSearchServiceDomainNodeToNodeEncryptionOptionsDetails](#)
- [AwsOpenSearchServiceDomainServiceSoftwareOptionsDetails](#)
- [AwsOpenSearchServiceDomainVpcOptionsDetails](#)

Amazon Relational Database Service (RDS) objects

- [AwsRdsDbClusterAssociatedRole](#)
- [AwsRdsDbClusterDetails](#)
- [AwsRdsDbClusterMember](#)
- [AwsRdsDbClusterOptionGroupMembership](#)
- [AwsRdsDbClusterSnapshotDbClusterSnapshotAttribute](#)
- [AwsRdsDbClusterSnapshotDetails](#)

- [AwsRdsDbDomainMembership](#)
- [AwsRdsDbInstanceAssociatedRole](#)
- [AwsRdsDbInstanceDetails](#)
- [AwsRdsDbInstanceEndpoint](#)
- [AwsRdsDbInstanceVpcSecurityGroup](#)
- [AwsRdsDbOptionGroupMembership](#)
- [AwsRdsDbParameterGroup](#)
- [AwsRdsDbPendingModifiedValues](#)
- [AwsRdsDbProcessorFeature](#)
- [AwsRdsDbSecurityGroupDetails](#)
- [AwsRdsDbSecurityGroupEc2SecurityGroup](#)
- [AwsRdsDbSecurityGroupIpRange](#)
- [AwsRdsDbSnapshotDetails](#)
- [AwsRdsDbStatusInfo](#)
- [AwsRdsDbSubnetGroup](#)
- [AwsRdsDbSubnetGroupSubnet](#)
- [AwsRdsDbSubnetGroupSubnetAvailabilityZone](#)
- [AwsRdsEventSubscriptionDetails](#)
- [AwsRdsPendingCloudWatchLogsExports](#)

Amazon Redshift objects

- [AwsRedshiftClusterClusterNode](#)
- [AwsRedshiftClusterClusterParameterGroup](#)
- [AwsRedshiftClusterClusterParameterStatus](#)
- [AwsRedshiftClusterClusterSecurityGroup](#)
- [AwsRedshiftClusterClusterSnapshotCopyStatus](#)
- [AwsRedshiftClusterDeferredMaintenanceWindow](#)
- [AwsRedshiftClusterDetails](#)
- [AwsRedshiftClusterElasticIpStatus](#)
- [AwsRedshiftClusterEndpoint](#)

- [AwsRedshiftClusterHsmStatus](#)
- [AwsRedshiftClusterIamRole](#)
- [AwsRedshiftClusterLoggingStatus](#)
- [AwsRedshiftClusterPendingModifiedValues](#)
- [AwsRedshiftClusterResizeInfo](#)
- [AwsRedshiftClusterRestoreStatus](#)
- [AwsRedshiftClusterVpcSecurityGroup](#)

Amazon Route 53 objects

- [AwsRoute53HostedZoneConfigDetails](#)
- [AwsRoute53HostedZoneDetails](#)
- [AwsRoute53HostedZoneObjectDetails](#)
- [AwsRoute53HostedZoneVpcDetails](#)
- [AwsRoute53QueryLoggingConfigDetails](#)
- [CloudWatchLogsLogGroupArnConfigDetails](#)

Amazon Simple Storage Service (S3) objects

- [AwsS3AccessPointDetails](#)
- [AwsS3AccessPointVpcConfigurationDetails](#)
- [AwsS3AccountPublicAccessBlockDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesAbortIncompleteMultipartUploadDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesFilterDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateOperandsDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateOperandsTagDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateTagDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesNoncurrentVersionTransitionsDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesTransitionsDetails](#)

- [AwsS3BucketBucketVersioningConfiguration](#)
- [AwsS3BucketDetails](#)
- [AwsS3BucketLoggingConfiguration](#)
- [AwsS3BucketNotificationConfiguration](#)
- [AwsS3BucketNotificationConfigurationDetail](#)
- [AwsS3BucketNotificationConfigurationFilter](#)
- [AwsS3BucketNotificationConfigurationS3KeyFilter](#)
- [AwsS3BucketNotificationConfigurationS3KeyFilterRule](#)
- [AwsS3BucketObjectLockConfiguration](#)
- [AwsS3BucketObjectLockConfigurationRuleDefaultRetentionDetails](#)
- [AwsS3BucketObjectLockConfigurationRuleDetails](#)
- [AwsS3BucketServerSideEncryptionByDefault](#)
- [AwsS3BucketServerSideEncryptionConfiguration](#)
- [AwsS3BucketServerSideEncryptionRule](#)
- [AwsS3BucketWebsiteConfiguration](#)
- [AwsS3BucketWebsiteConfigurationRedirectTo](#)
- [AwsS3BucketWebsiteConfigurationRoutingRule](#)
- [AwsS3BucketWebsiteConfigurationRoutingRuleCondition](#)
- [AwsS3BucketWebsiteConfigurationRoutingRuleRedirect](#)
- [AwsS3ObjectDetails](#)

Amazon SageMaker AI objects

- [AwsSageMakerNotebookInstanceDetails](#)
- [AwsSageMakerNotebookInstanceMetadataServiceConfigurationDetails](#)

Amazon Secrets Manager objects

- [AwsSecretsManagerSecretDetails](#)
- [AwsSecretsManagerSecretRotationRules](#)

Amazon Simple Notification Service (SNS) objects

- [AwsSnsTopicDetails](#)
- [AwsSnsTopicSubscription](#)

Amazon Simple Queue Service (SQS) objects

- [AwsSqsQueueDetails](#)

Amazon Systems Manager objects

- [AwsSsmComplianceSummary](#)
- [AwsSsmPatch](#)
- [AwsSsmPatchComplianceDetails](#)

Amazon Step Functions objects

- [AwsStepFunctionStateMachineDetails](#)
- [AwsStepFunctionStateMachineLoggingConfigurationDestinationsCloudWatchLogsLogGroupDetails](#)
- [AwsStepFunctionStateMachineLoggingConfigurationDestinationsDetails](#)
- [AwsStepFunctionStateMachineLoggingConfigurationDetails](#)
- [AwsStepFunctionStateMachineTracingConfigurationDetails](#)

Amazon WAF objects

- [AwsWafRateBasedRuleDetails](#)
- [AwsWafRateBasedRuleMatchPredicate](#)
- [AwsWafRegionalRateBasedRuleDetails](#)
- [AwsWafRegionalRateBasedRuleMatchPredicate](#)
- [AwsWafRegionalRuleDetails](#)
- [AwsWafRegionalRuleGroupDetails](#)
- [AwsWafRegionalRuleGroupRulesActionDetails](#)
- [AwsWafRegionalRuleGroupRulesDetails](#)
- [AwsWafRegionalRulePredicateListDetails](#)
- [AwsWafRegionalWebAclDetails](#)

- [AwsWafRegionalWebAclRulesListActionDetails](#)
- [AwsWafRegionalWebAclRulesListDetails](#)
- [AwsWafRegionalWebAclRulesListOverrideActionDetails](#)
- [AwsWafRuleDetails](#)
- [AwsWafRuleGroupDetails](#)
- [AwsWafRuleGroupRulesActionDetails](#)
- [AwsWafRuleGroupRulesDetails](#)
- [AwsWafRulePredicateListDetails](#)
- [AwsWafv2ActionAllowDetails](#)
- [AwsWafv2ActionBlockDetails](#)
- [AwsWafv2CustomHttpHeader](#)
- [AwsWafv2CustomRequestHandlingDetails](#)
- [AwsWafv2CustomResponseDetails](#)
- [AwsWafv2RuleGroupDetails](#)
- [AwsWafv2RulesActionCaptchaDetails](#)
- [AwsWafv2RulesActionCountDetails](#)
- [AwsWafv2RulesActionDetails](#)
- [AwsWafv2RulesDetails](#)
- [AwsWafv2VisibilityConfigDetails](#)
- [AwsWafv2WebAclActionDetails](#)
- [AwsWafv2WebAclCaptchaConfigDetails](#)
- [AwsWafv2WebAclCaptchaConfigImmunityTimePropertyDetails](#)
- [AwsWafv2WebAclDetails](#)
- [AwsWafWebAclDetails](#)
- [WafAction](#)
- [WafExcludedRule](#)
- [WafOverrideAction](#)
- [AwsWafWebAclRule](#)

Amazon X-Ray objects

- [AwsXrayEncryptionConfigDetails](#)

Container objects

- [ContainerDetails](#)
- [VolumeMount](#)

Amazon MQ objects

Amazon MQ objects

- [AwsAmazonMqBrokerDetails](#)
- [AwsAmazonMqBrokerEncryptionOptionsDetails](#)
- [AwsAmazonMqBrokerLdapServerMetadataDetails](#)
- [AwsAmazonMqBrokerLogsDetails](#)
- [AwsAmazonMqBrokerLogsPendingDetails](#)
- [AwsAmazonMqBrokerMaintenanceWindowStartTimeDetails](#)
- [AwsAmazonMqBrokerUsersDetails](#)

AwsAmazonMqBrokerDetails

Provides details about an Amazon MQ message broker. A message broker allows software applications and components to communicate using various programming languages, operating systems, and formal messaging protocols.

Contents

AuthenticationStrategy

The authentication strategy used to secure the broker. The default is SIMPLE.

Type: String

Pattern: `.*\S.*`

Required: No

AutoMinorVersionUpgrade

Whether automatically upgrade new minor versions for brokers, as new versions are released and supported by Amazon MQ. Automatic upgrades occur during the scheduled maintenance window of the broker or after a manual broker reboot.

Type: Boolean

Required: No

BrokerArn

The Amazon Resource Name (ARN) of the broker.

Type: String

Pattern: `.*\S.*`

Required: No

BrokerId

The unique ID that Amazon MQ generates for the broker.

Type: String

Pattern: `.*\S.*`

Required: No

BrokerName

The broker's name.

Type: String

Pattern: `.*\S.*`

Required: No

DeploymentMode

The broker's deployment mode.

Type: String

Pattern: `.*\S.*`

Required: No

EncryptionOptions

Encryption options for the broker. Doesn't apply to RabbitMQ brokers.

Type: [AwsAmazonMqBrokerEncryptionOptionsDetails](#) object

Required: No

EngineType

The type of broker engine.

Type: String

Pattern: `.*\S.*`

Required: No

EngineVersion

The version of the broker engine.

Type: String

Pattern: `.*\S.*`

Required: No

HostInstanceType

The broker's instance type.

Type: String

Pattern: `.*\S.*`

Required: No

LdapServerMetadata

The metadata of the Lightweight Directory Access Protocol (LDAP) server used to authenticate and authorize connections to the broker. This is an optional failover server.

Type: [AwsAmazonMqBrokerLdapServerMetadataDetails](#) object

Required: No

Logs

Turns on Amazon CloudWatch logging for brokers.

Type: [AwsAmazonMqBrokerLogsDetails](#) object

Required: No

MaintenanceWindowStartTime

The scheduled time period (UTC) during which Amazon MQ begins to apply pending updates or patches to the broker.

Type: [AwsAmazonMqBrokerMaintenanceWindowStartTimeDetails](#) object

Required: No

PubliclyAccessible

Permits connections from applications outside of the VPC that hosts the broker's subnets.

Type: Boolean

Required: No

SecurityGroups

The list of rules (one minimum, 125 maximum) that authorize connections to brokers.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

StorageType

The broker's storage type.

Type: String

Pattern: `.*\S.*`

Required: No

SubnetIds

The list of groups that define which subnets and IP ranges the broker can use from different Availability Zones.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Users

The list of all broker usernames for the specified broker. Doesn't apply to RabbitMQ brokers.

Type: Array of [AwsAmazonMqBrokerUsersDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAmazonMqBrokerEncryptionOptionsDetails

Provides details about broker encryption options.

Contents

KmsKeyId

The Amazon KMS key that's used to encrypt your data at rest. If not provided, Amazon MQ will use a default KMS key to encrypt your data.

Type: String

Pattern: `.*\S.*`

Required: No

UseAwsOwnedKey

Specifies that an Amazon KMS key should be used for at-rest encryption. Set to `true` by default if no value is provided (for example, for RabbitMQ brokers).

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAmazonMqBrokerLdapServerMetadataDetails

The metadata of the Lightweight Directory Access Protocol (LDAP) server used to authenticate and authorize connections to the broker. This is an optional failover server.

Contents

Hosts

Specifies the location of the LDAP server, such as Amazon Directory Service for Microsoft Active Directory.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

RoleBase

The distinguished name of the node in the directory information tree (DIT) to search for roles or groups.

Type: String

Pattern: `.*\S.*`

Required: No

RoleName

The group name attribute in a role entry whose value is the name of that role.

Type: String

Pattern: `.*\S.*`

Required: No

RoleSearchMatching

The LDAP search filter used to find roles within the `roleBase`.

Type: String

Pattern: .*\\S.*

Required: No

RoleSearchSubtree

The directory search scope for the role. If set to `true`, the scope is to search the entire subtree.

Type: Boolean

Required: No

ServiceAccountUsername

A username for the service account, which is an account in your LDAP server that has access to initiate a connection.

Type: String

Pattern: .*\\S.*

Required: No

UserBase

Selects a particular subtree of the directory information tree (DIT) to search for user entries.

Type: String

Pattern: .*\\S.*

Required: No

UserRoleName

The name of the LDAP attribute in the user's directory entry for the user's group membership.

Type: String

Pattern: .*\\S.*

Required: No

UserSearchMatching

The LDAP search filter used to find users within the `userBase`.

Type: String

Pattern: .*\\S.*

Required: No

UserSearchSubtree

The directory search scope for the user. If set to true, the scope is to search the entire subtree.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAmazonMqBrokerLogsDetails

Provides information about logs to be activated for the specified broker.

Contents

Audit

Activates audit logging. Every user management action made using JMX or the ActiveMQ Web Console is logged. Doesn't apply to RabbitMQ brokers.

Type: Boolean

Required: No

AuditLogGroup

The location of the CloudWatch Logs log group where audit logs are sent.

Type: String

Pattern: `.*\S.*`

Required: No

General

Activates general logging.

Type: Boolean

Required: No

GeneralLogGroup

The location of the CloudWatch Logs log group where general logs are sent.

Type: String

Pattern: `.*\S.*`

Required: No

Pending

The list of information about logs that are to be turned on for the specified broker.

Type: [AwsAmazonMqBrokerLogsPendingDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAmazonMqBrokerLogsPendingDetails

Provides information about logs to be activated for the specified broker.

Contents

Audit

Activates audit logging. Every user management action made using JMX or the ActiveMQ Web Console is logged. Doesn't apply to RabbitMQ brokers.

Type: Boolean

Required: No

General

Activates general logging.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAmazonMqBrokerMaintenanceWindowStartTimeDetails

The scheduled time period (UTC) during which Amazon MQ begins to apply pending updates or patches to the broker.

Contents

DayOfWeek

The day of the week on which the maintenance window falls.

Type: String

Pattern: .*\\S.*

Required: No

TimeOfDay

The time, in 24-hour format, on which the maintenance window falls.

Type: String

Pattern: .*\\S.*

Required: No

TimeZone

The time zone in either the Country/City format or the UTC offset format. UTC is the default format.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAmazonMqBrokerUsersDetails

Provides details about the broker usernames for the specified broker. Doesn't apply to RabbitMQ brokers.

Contents

PendingChange

The type of change pending for the broker user.

Type: String

Pattern: `.*\S.*`

Required: No

Username

The username of the broker user.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon API Gateway

Amazon API Gateway objects

- [AwsApiGatewayAccessLogSettings](#)

- [AwsApiGatewayCanarySettings](#)
- [AwsApiGatewayEndpointConfiguration](#)
- [AwsApiGatewayMethodSettings](#)
- [AwsApiGatewayRestApiDetails](#)
- [AwsApiGatewayStageDetails](#)
- [AwsApiGatewayV2ApiDetails](#)
- [AwsApiGatewayV2RouteSettings](#)
- [AwsApiGatewayV2StageDetails](#)
- [AwsCorsConfiguration](#)

AwsApiGatewayAccessLogSettings

Contains information about settings for logging access for the stage.

Contents

DestinationArn

The ARN of the CloudWatch Logs log group that receives the access logs.

Type: String

Pattern: `.*\S.*`

Required: No

Format

A single-line format of the access logs of data, as specified by selected `$context` variables. The format must include at least `$context.requestId`.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsApiGatewayCanarySettings

Contains information about settings for canary deployment in the stage.

Contents

DeploymentId

The deployment identifier for the canary deployment.

Type: String

Pattern: `.*\S.*`

Required: No

PercentTraffic

The percentage of traffic that is diverted to a canary deployment.

Type: Double

Required: No

StageVariableOverrides

Stage variables that are overridden in the canary release deployment. The variables include new stage variables that are introduced in the canary.

Each variable is represented as a string-to-string map between the stage variable name and the variable value.

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

UseStageCache

Indicates whether the canary deployment uses the stage cache.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsApiGatewayEndpointConfiguration

Contains information about the endpoints for the API.

Contents

Types

A list of endpoint types for the REST API.

For an edge-optimized API, the endpoint type is EDGE. For a Regional API, the endpoint type is REGIONAL. For a private API, the endpoint type is PRIVATE.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsApiGatewayMethodSettings

Defines settings for a method for the stage.

Contents

CacheDataEncrypted

Indicates whether the cached responses are encrypted.

Type: Boolean

Required: No

CacheTtlInSeconds

Specifies the time to live (TTL), in seconds, for cached responses. The higher the TTL, the longer the response is cached.

Type: Integer

Required: No

CachingEnabled

Indicates whether responses are cached and returned for requests. For responses to be cached, a cache cluster must be enabled on the stage.

Type: Boolean

Required: No

DataTraceEnabled

Indicates whether data trace logging is enabled for the method. Data trace logging affects the log entries that are pushed to CloudWatch Logs.

Type: Boolean

Required: No

HttpMethod

The HTTP method. You can use an asterisk (*) as a wildcard to apply method settings to multiple methods.

Type: String

Pattern: `.*\S.*`

Required: No

LoggingLevel

The logging level for this method. The logging level affects the log entries that are pushed to CloudWatch Logs.

If the logging level is `ERROR`, then the logs only include error-level entries.

If the logging level is `INFO`, then the logs include both `ERROR` events and extra informational events.

Valid values: `OFF` | `ERROR` | `INFO`

Type: String

Pattern: `.*\S.*`

Required: No

MetricsEnabled

Indicates whether CloudWatch metrics are enabled for the method.

Type: Boolean

Required: No

RequireAuthorizationForCacheControl

Indicates whether authorization is required for a cache invalidation request.

Type: Boolean

Required: No

ResourcePath

The resource path for this method. Forward slashes (/) are encoded as `~1`. The initial slash must include a forward slash.

For example, the path value `/resource/subresource` must be encoded as `~1resource~1subresource`.

To specify the root path, use only a slash (`/`). You can use an asterisk (`*`) as a wildcard to apply method settings to multiple methods.

Type: String

Pattern: `.*\S.*`

Required: No

ThrottlingBurstLimit

The throttling burst limit for the method.

Type: Integer

Required: No

ThrottlingRateLimit

The throttling rate limit for the method.

Type: Double

Required: No

UnauthorizedCacheControlHeaderStrategy

Indicates how to handle unauthorized requests for cache invalidation.

Valid values: `FAIL_WITH_403` | `SUCCEED_WITH_RESPONSE_HEADER` | `SUCCEED_WITHOUT_RESPONSE_HEADER`

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsApiGatewayRestApiDetails

Contains information about a REST API in version 1 of Amazon API Gateway.

Contents

ApiKeySource

The source of the API key for metering requests according to a usage plan.

HEADER indicates whether to read the API key from the X-API-Key header of a request.

AUTHORIZER indicates whether to read the API key from the UsageIdentifierKey from a custom authorizer.

Type: String

Pattern: `.*\S.*`

Required: No

BinaryMediaTypes

The list of binary media types supported by the REST API.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

CreatedDate

Indicates when the API was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

Description

A description of the REST API.

Type: String

Pattern: `.*\S.*`

Required: No

EndpointConfiguration

The endpoint configuration of the REST API.

Type: [AwsApiGatewayEndpointConfiguration](#) object

Required: No

Id

The identifier of the REST API.

Type: String

Pattern: `.*\S.*`

Required: No

MinimumCompressionSize

The minimum size in bytes of a payload before compression is enabled.

If `null`, then compression is disabled.

If 0, then all payloads are compressed.

Type: Integer

Required: No

Name

The name of the REST API.

Type: String

Pattern: `.*\S.*`

Required: No

Version

The version identifier for the REST API.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsApiGatewayStageDetails

Provides information about a version 1 Amazon API Gateway stage.

Contents

AccessLogSettings

Settings for logging access for the stage.

Type: [AwsApiGatewayAccessLogSettings](#) object

Required: No

CacheClusterEnabled

Indicates whether a cache cluster is enabled for the stage.

Type: Boolean

Required: No

CacheClusterSize

If a cache cluster is enabled, the size of the cache cluster.

Type: String

Pattern: `.*\S.*`

Required: No

CacheClusterStatus

If a cache cluster is enabled, the status of the cache cluster.

Type: String

Pattern: `.*\S.*`

Required: No

CanarySettings

Information about settings for canary deployment in the stage.

Type: [AwsApiGatewayCanarySettings](#) object

Required: No

ClientCertificateId

The identifier of the client certificate for the stage.

Type: String

Pattern: `.*\S.*`

Required: No

CreatedDate

Indicates when the stage was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

DeploymentId

The identifier of the deployment that the stage points to.

Type: String

Pattern: `.*\S.*`

Required: No

Description

A description of the stage.

Type: String

Pattern: `.*\S.*`

Required: No

DocumentationVersion

The version of the API documentation that is associated with the stage.

Type: String

Pattern: `.*\S.*`

Required: No

LastUpdatedDate

Indicates when the stage was most recently updated.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

MethodSettings

Defines the method settings for the stage.

Type: Array of [AwsApiGatewayMethodSettings](#) objects

Required: No

StageName

The name of the stage.

Type: String

Pattern: `.*\S.*`

Required: No

TracingEnabled

Indicates whether active tracing with Amazon X-Ray is enabled for the stage.

Type: Boolean

Required: No

Variables

A map that defines the stage variables for the stage.

Variable names can have alphanumeric and underscore characters.

Variable values can contain the following characters:

- Uppercase and lowercase letters
- Numbers
- Special characters `-.~:/?#&=,`

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

WebAclArn

The ARN of the web ACL associated with the stage.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsApiGatewayV2ApiDetails

Contains information about a version 2 API in Amazon API Gateway.

Contents

ApiEndpoint

The URI of the API.

Uses the format `<api-id>.execute-api.<region>.amazonaws.com`

The stage name is typically appended to the URI to form a complete path to a deployed API stage.

Type: String

Pattern: `.*\S.*`

Required: No

ApiId

The identifier of the API.

Type: String

Pattern: `.*\S.*`

Required: No

ApiKeySelectionExpression

An API key selection expression. Supported only for WebSocket APIs.

Type: String

Pattern: `.*\S.*`

Required: No

CorsConfiguration

A cross-origin resource sharing (CORS) configuration. Supported only for HTTP APIs.

Type: [AwsCorsConfiguration](#) object

Required: No

CreatedDate

Indicates when the API was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

Description

A description of the API.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the API.

Type: String

Pattern: `.*\S.*`

Required: No

ProtocolType

The API protocol for the API.

Valid values: WEBSOCKET | HTTP

Type: String

Pattern: `.*\S.*`

Required: No

RouteSelectionExpression

The route selection expression for the API.

For HTTP APIs, must be `${request.method} ${request.path}`. This is the default value for HTTP APIs.

For WebSocket APIs, there is no default value.

Type: String

Pattern: `.*\S.*`

Required: No

Version

The version identifier for the API.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsApiGatewayV2RouteSettings

Contains route settings for a stage.

Contents

DataTraceEnabled

Indicates whether data trace logging is enabled. Data trace logging affects the log entries that are pushed to CloudWatch Logs. Supported only for WebSocket APIs.

Type: Boolean

Required: No

DetailedMetricsEnabled

Indicates whether detailed metrics are enabled.

Type: Boolean

Required: No

LoggingLevel

The logging level. The logging level affects the log entries that are pushed to CloudWatch Logs. Supported only for WebSocket APIs.

If the logging level is ERROR, then the logs only include error-level entries.

If the logging level is INFO, then the logs include both ERROR events and extra informational events.

Valid values: OFF | ERROR | INFO

Type: String

Pattern: .*S.*

Required: No

ThrottlingBurstLimit

The throttling burst limit.

Type: Integer

Required: No

ThrottlingRateLimit

The throttling rate limit.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsApiGatewayV2StageDetails

Contains information about a version 2 stage for Amazon API Gateway.

Contents

AccessLogSettings

Information about settings for logging access for the stage.

Type: [AwsApiGatewayAccessLogSettings](#) object

Required: No

ApiGatewayManaged

Indicates whether the stage is managed by API Gateway.

Type: Boolean

Required: No

AutoDeploy

Indicates whether updates to an API automatically trigger a new deployment.

Type: Boolean

Required: No

ClientCertificateId

The identifier of a client certificate for a stage. Supported only for WebSocket API calls.

Type: String

Pattern: `.*\S.*`

Required: No

CreatedDate

Indicates when the stage was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

DefaultRouteSettings

Default route settings for the stage.

Type: [AwsApiGatewayV2RouteSettings](#) object

Required: No

DeploymentId

The identifier of the deployment that the stage is associated with.

Type: String

Pattern: `.*\S.*`

Required: No

Description

The description of the stage.

Type: String

Pattern: `.*\S.*`

Required: No

LastDeploymentStatusMessage

The status of the last deployment of a stage. Supported only if the stage has automatic deployment enabled.

Type: String

Pattern: `.*\S.*`

Required: No

LastUpdatedDate

Indicates when the stage was most recently updated.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

RouteSettings

The route settings for the stage.

Type: [AwsApiGatewayV2RouteSettings](#) object

Required: No

StageName

The name of the stage.

Type: String

Pattern: `.*\S.*`

Required: No

StageVariables

A map that defines the stage variables for the stage.

Variable names can have alphanumeric and underscore characters.

Variable values can contain the following characters:

- Uppercase and lowercase letters
- Numbers
- Special characters `-.~:/?#&=,`

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCorsConfiguration

Contains the cross-origin resource sharing (CORS) configuration for the API. CORS is only supported for HTTP APIs.

Contents

AllowCredentials

Indicates whether the CORS request includes credentials.

Type: Boolean

Required: No

AllowHeaders

The allowed headers for CORS requests.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

AllowMethods

The allowed methods for CORS requests.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

AllowOrigins

The allowed origins for CORS requests.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

ExposeHeaders

The exposed headers for CORS requests.

Type: Array of strings

Pattern: .*\\S.*

Required: No

MaxAge

The number of seconds for which the browser caches preflight request results.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon AppSync objects

Amazon AppSync objects

- [AwsAppSyncGraphQLApiDetails](#)
- [AwsAppSyncGraphQLApiAdditionalAuthenticationProvidersDetails](#)
- [AwsAppSyncGraphQLApiLambdaAuthorizerConfigDetails](#)
- [AwsAppSyncGraphQLApiLogConfigDetails](#)
- [AwsAppSyncGraphQLApiOpenIdConnectConfigDetails](#)
- [AwsAppSyncGraphQLApiUserPoolConfigDetails](#)

AwsAppSyncGraphQLApiDetails

Provides details about an Amazon AppSync GraphQL API, which lets you query multiple databases, microservices, and APIs from a single GraphQL endpoint.

Contents

AdditionalAuthenticationProviders

A list of additional authentication providers for the GraphQL API.

Type: Array of [AwsAppSyncGraphQLApiAdditionalAuthenticationProvidersDetails](#) objects

Required: No

ApiId

The unique identifier for the API.

Type: String

Pattern: `.*\S.*`

Required: No

Arn

The Amazon Resource Name (ARN) of the API.

Type: String

Pattern: `.*\S.*`

Required: No

AuthenticationType

The type of security configuration for your GraphQL API: API key, Amazon Identity and Access Management (IAM), OpenID Connect (OIDC), Amazon Cognito user pools, or Amazon Lambda.

Type: String

Pattern: `.*\S.*`

Required: No

Id

The unique identifier for the API.

Type: String

Pattern: `.*\S.*`

Required: No

LambdaAuthorizerConfig

Specifies the configuration for Amazon Lambda function authorization.

Type: [AwsAppSyncGraphQLApiLambdaAuthorizerConfigDetails](#) object

Required: No

LogConfig

The Amazon CloudWatch Logs configuration.

Type: [AwsAppSyncGraphQLApiLogConfigDetails](#) object

Required: No

Name

The API name.

Type: String

Pattern: `.*\S.*`

Required: No

OpenIdConnectConfig

Specifies the authorization configuration for using an OpenID Connect compliant service with an Amazon AppSync GraphQL API endpoint.

Type: [AwsAppSyncGraphQLApiOpenIdConnectConfigDetails](#) object

Required: No

UserPoolConfig

The Amazon Cognito user pools configuration.

Type: [AwsAppSyncGraphQLApiUserPoolConfigDetails](#) object

Required: No

WafWebAclArn

The Amazon Resource Name (ARN) of the Amazon WAF web access control list (web ACL) associated with this GraphQL API, if one exists.

Type: String

Pattern: `.*\S.*`

Required: No

XrayEnabled

Indicates whether to use Amazon X-Ray tracing for the GraphQL API.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAppSyncGraphQLApiAdditionalAuthenticationProvidersDetails

A list of additional authentication providers for the GraphQL API.

Contents

AuthenticationType

The type of security configuration for your GraphQL API: API key, Amazon Identity and Access Management (IAM), OpenID Connect (OIDC), Amazon Cognito user pools, or Amazon Lambda.

Type: String

Pattern: `.*\S.*`

Required: No

LambdaAuthorizerConfig

The configuration for Lambda function authorization.

Type: [AwsAppSyncGraphQLApiLambdaAuthorizerConfigDetails](#) object

Required: No

OpenIdConnectConfig

The OpenID Connect configuration.

Type: [AwsAppSyncGraphQLApiOpenIdConnectConfigDetails](#) object

Required: No

UserPoolConfig

The Amazon Cognito user pools configuration.

Type: [AwsAppSyncGraphQLApiUserPoolConfigDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAppSyncGraphQLApiLambdaAuthorizerConfigDetails

Specifies the authorization configuration for using an Lambda function with your Amazon AppSync GraphQL API endpoint.

Contents

AuthorizerResultTtlInSeconds

The number of seconds a response should be cached for. The default is 5 minutes (300 seconds).

Type: Integer

Required: No

AuthorizerUri

The Amazon Resource Name (ARN) of the Lambda function to be called for authorization. This can be a standard Lambda ARN, a version ARN (.../v3), or an alias ARN.

Type: String

Pattern: .*\\S.*

Required: No

IdentityValidationExpression

A regular expression for validation of tokens before the Lambda function is called.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAppSyncGraphQLApiLogConfigDetails

Specifies the logging configuration when writing GraphQL operations and tracing to Amazon CloudWatch for an Amazon AppSync GraphQL API.

Contents

CloudWatchLogsRoleArn

The Amazon Resource Name (ARN) of the service role that Amazon AppSync assumes to publish to CloudWatch Logs in your account.

Type: String

Pattern: `.*\S.*`

Required: No

ExcludeVerboseContent

Set to TRUE to exclude sections that contain information such as headers, context, and evaluated mapping templates, regardless of logging level.

Type: Boolean

Required: No

FieldLogLevel

The field logging level.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAppSyncGraphQLApiOpenIdConnectConfigDetails

Specifies the authorization configuration for using an OpenID Connect compliant service with your Amazon AppSync GraphQL API endpoint.

Contents

AuthTtl

The number of milliseconds that a token is valid after being authenticated.

Type: Long

Required: No

ClientId

The client identifier of the relying party at the OpenID identity provider. This identifier is typically obtained when the relying party is registered with the OpenID identity provider. You can specify a regular expression so that Amazon AppSync can validate against multiple client identifiers at a time.

Type: String

Pattern: `.*\S.*`

Required: No

IatTtl

The number of milliseconds that a token is valid after it's issued to a user.

Type: Long

Required: No

Issuer

The issuer for the OIDC configuration. The issuer returned by discovery must exactly match the value of `iss` in the ID token.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAppSyncGraphQLApiUserPoolConfigDetails

Specifies the authorization configuration for using Amazon Cognito user pools with your Amazon AppSync GraphQL API endpoint.

Contents

AppIdClientRegex

A regular expression for validating the incoming Amazon Cognito user pools app client ID. If this value isn't set, no filtering is applied.

Type: String

Pattern: `.*\S.*`

Required: No

AwsRegion

The Amazon Web Services Region in which the user pool was created.

Type: String

Pattern: `.*\S.*`

Required: No

DefaultAction

The action that you want your GraphQL API to take when a request that uses Amazon Cognito user pools authentication doesn't match the Amazon Cognito user pools configuration.

Type: String

Pattern: `.*\S.*`

Required: No

UserPoolId

The user pool ID.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Athena objects

Amazon Athena objects

- [AwsAthenaWorkGroupConfigurationDetails](#)
- [AwsAthenaWorkGroupConfigurationResultConfigurationDetails](#)
- [AwsAthenaWorkGroupConfigurationResultConfigurationEncryptionConfigurationDetails](#)
- [AwsAthenaWorkGroupDetails](#)

AwsAthenaWorkGroupConfigurationDetails

The configuration of the workgroup, which includes the location in Amazon Simple Storage Service (Amazon S3) where query results are stored, the encryption option, if any, used for query results, whether Amazon CloudWatch metrics are enabled for the workgroup, and the limit for the amount of bytes scanned (cutoff) per query, if it is specified.

Contents

ResultConfiguration

The location in Amazon S3 where query and calculation results are stored and the encryption option, if any, used for query and calculation results. These are known as client-side settings. If workgroup settings override client-side settings, then the query uses the workgroup settings.

Type: [AwsAthenaWorkGroupConfigurationResultConfigurationDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAthenaWorkGroupConfigurationResultConfigurationDetails

The location in Amazon Simple Storage Service (Amazon S3) where query and calculation results are stored and the encryption option, if any, used for query and calculation results. These are known as client-side settings. If workgroup settings override client-side settings, then the query uses the workgroup settings.

Contents

EncryptionConfiguration

Specifies the method used to encrypt the user's data stores in the Athena workgroup.

Type: [AwsAthenaWorkGroupConfigurationResultConfigurationEncryptionConfigurationDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAthenaWorkGroupConfigurationResultConfigurationEncryptionConfigurationDetail

Specifies the method used to encrypt the user's data stores in the Athena workgroup.

Contents

EncryptionOption

Indicates whether Amazon Simple Storage Service (Amazon S3) server-side encryption with Amazon S3 managed keys (SSE_S3), server-side encryption with Amazon KMS keys (SSE_KMS), or client-side encryption with Amazon KMS customer managed keys (CSE_KMS) is used.

Type: String

Pattern: `.*\S.*`

Required: No

KmsKey

For SSE_KMS and CSE_KMS, this is the KMS key Amazon Resource Name (ARN) or ID.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAthenaWorkGroupDetails

Provides information about an Amazon Athena workgroup.

Contents

Configuration

The configuration of the workgroup, which includes the location in Amazon Simple Storage Service (Amazon S3) where query results are stored, the encryption option, if any, used for query results, whether Amazon CloudWatch metrics are enabled for the workgroup, and the limit for the amount of bytes scanned (cutoff) per query, if it is specified.

Type: [AwsAthenaWorkGroupConfigurationDetails](#) object

Required: No

Description

The workgroup description.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The workgroup name.

Type: String

Pattern: `.*\S.*`

Required: No

State

Whether the workgroup is enabled or disabled.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Backup

Amazon Backup objects

- [AwsBackupBackupPlanAdvancedBackupSettingsDetails](#)
- [AwsBackupBackupPlanBackupPlanDetails](#)
- [AwsBackupBackupPlanDetails](#)
- [AwsBackupBackupPlanLifecycleDetails](#)
- [AwsBackupBackupPlanRuleCopyActionsDetails](#)
- [AwsBackupBackupPlanRuleDetails](#)
- [AwsBackupBackupVaultDetails](#)
- [AwsBackupBackupVaultNotificationsDetails](#)
- [AwsBackupRecoveryPointCalculatedLifecycleDetails](#)
- [AwsBackupRecoveryPointCreatedByDetails](#)
- [AwsBackupRecoveryPointDetails](#)
- [AwsBackupRecoveryPointLifecycleDetails](#)

AwsBackupBackupPlanAdvancedBackupSettingsDetails

Provides a list of backup options for each resource type.

Contents

BackupOptions

Specifies the backup option for a selected resource. This option is only available for Windows Volume Shadow Copy Service (VSS) backup jobs. Valid values are as follows:

- Set to `WindowsVSS: enabled` to enable the WindowsVSS backup option and create a Windows VSS backup.
- Set to `WindowsVSS: disabled` to create a regular backup. The WindowsVSS option is not enabled by default.

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

ResourceType

The name of a resource type. The only supported resource type is Amazon EC2 instances with Windows VSS.

The only valid value is `EC2`.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsBackupBackupPlanBackupPlanDetails

Provides details about an Amazon Backup backup plan and an array of BackupRule objects, each of which specifies a backup rule.

Contents

AdvancedBackupSettings

A list of backup options for each resource type.

Type: Array of [AwsBackupBackupPlanAdvancedBackupSettingsDetails](#) objects

Required: No

BackupPlanName

The display name of a backup plan.

Type: String

Pattern: `.*\S.*`

Required: No

BackupPlanRule

An array of BackupRule objects, each of which specifies a scheduled task that is used to back up a selection of resources.

Type: Array of [AwsBackupBackupPlanRuleDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsBackupBackupPlanDetails

Provides details about an Amazon Backup backup plan and an array of BackupRule objects, each of which specifies a backup rule.

Contents

BackupPlan

Uniquely identifies the backup plan to be associated with the selection of resources.

Type: [AwsBackupBackupPlanBackupPlanDetails](#) object

Required: No

BackupPlanArn

An Amazon Resource Name (ARN) that uniquely identifies the backup plan.

Type: String

Pattern: `.*\S.*`

Required: No

BackupPlanId

A unique ID for the backup plan.

Type: String

Pattern: `.*\S.*`

Required: No

VersionId

Unique, randomly generated, Unicode, UTF-8 encoded strings. Version IDs cannot be edited.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsBackupBackupPlanLifecycleDetails

Provides lifecycle details for the backup plan. A lifecycle defines when a backup is transitioned to cold storage and when it expires.

Contents

DeleteAfterDays

Specifies the number of days after creation that a recovery point is deleted. Must be greater than 90 days plus MoveToColdStorageAfterDays.

Type: Long

Required: No

MoveToColdStorageAfterDays

Specifies the number of days after creation that a recovery point is moved to cold storage.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsBackupBackupPlanRuleCopyActionsDetails

An array of CopyAction objects, each of which contains details of the copy operation.

Contents

DestinationBackupVaultArn

An Amazon Resource Name (ARN) that uniquely identifies the destination backup vault for the copied backup.

Type: String

Pattern: .*\\S.*

Required: No

Lifecycle

Defines when a protected resource is transitioned to cold storage and when it expires. Amazon Backup transitions and expires backups automatically according to the lifecycle that you define. If you don't specify a lifecycle, Amazon Backup applies the lifecycle policy of the source backup to the destination backup.

Backups transitioned to cold storage must be stored in cold storage for a minimum of 90 days.

Type: [AwsBackupBackupPlanLifecycleDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsBackupBackupPlanRuleDetails

Provides details about an array of BackupRule objects, each of which specifies a scheduled task that is used to back up a selection of resources.

Contents

CompletionWindowMinutes

A value in minutes after a backup job is successfully started before it must be completed, or it is canceled by Amazon Backup.

Type: Long

Required: No

CopyActions

An array of CopyAction objects, each of which contains details of the copy operation.

Type: Array of [AwsBackupBackupPlanRuleCopyActionsDetails](#) objects

Required: No

EnableContinuousBackup

Specifies whether Amazon Backup creates continuous backups capable of point-in-time restore (PITR).

Type: Boolean

Required: No

Lifecycle

Defines when a protected resource is transitioned to cold storage and when it expires. Amazon Backup transitions and expires backups automatically according to the lifecycle that you define. If you don't specify a lifecycle, Amazon Backup applies the lifecycle policy of the source backup to the destination backup.

Backups transitioned to cold storage must be stored in cold storage for a minimum of 90 days.

Type: [AwsBackupBackupPlanLifecycleDetails](#) object

Required: No

RuleId

Uniquely identifies a rule that is used to schedule the backup of a selection of resources.

Type: String

Pattern: `.*\S.*`

Required: No

RuleName

A display name for a backup rule. Must contain 1 to 50 alphanumeric or '-' '_' characters.

Type: String

Pattern: `.*\S.*`

Required: No

ScheduleExpression

A cron expression in UTC specifying when Amazon Backup initiates a backup job.

Type: String

Pattern: `.*\S.*`

Required: No

StartWindowMinutes

A value in minutes after a backup is scheduled before a job will be canceled if it doesn't start successfully.

Type: Long

Required: No

TargetBackupVault

The name of a logical container where backups are stored. Backup vaults are identified by names that are unique to the Amazon Web Services account used to create them and the Amazon Web Services Region where they are created. They consist of letters, numbers, and hyphens.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsBackupBackupVaultDetails

Provides details about an Amazon Backup backup vault. In Amazon Backup, a backup vault is a container that stores and organizes your backups.

Contents

AccessPolicy

A resource-based policy that is used to manage access permissions on the target backup vault.

Type: String

Pattern: `.*\S.*`

Required: No

BackupVaultArn

An Amazon Resource Name (ARN) that uniquely identifies a backup vault.

Type: String

Pattern: `.*\S.*`

Required: No

BackupVaultName

The name of a logical container where backups are stored. Backup vaults are identified by names that are unique to the Amazon Web Services account used to create them and the Amazon Web Services Region where they are created. They consist of lowercase letters, numbers, and hyphens.

Type: String

Pattern: `.*\S.*`

Required: No

EncryptionKeyArn

The unique ARN associated with the server-side encryption key. You can specify a key to encrypt your backups from services that support full Amazon Backup management. If you don't specify a key, Amazon Backup creates an Amazon KMS key for you by default.

Type: String

Pattern: .*\\S.*

Required: No

Notifications

The Amazon SNS event notifications for the specified backup vault.

Type: [AwsBackupBackupVaultNotificationsDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsBackupBackupVaultNotificationsDetails

Provides details about the Amazon SNS event notifications for the specified backup vault.

Contents

BackupVaultEvents

An array of events that indicate the status of jobs to back up resources to the backup vault. The following events are supported:

- BACKUP_JOB_STARTED | BACKUP_JOB_COMPLETED
- COPY_JOB_STARTED | COPY_JOB_SUCCESSFUL | COPY_JOB_FAILED
- RESTORE_JOB_STARTED | RESTORE_JOB_COMPLETED | RECOVERY_POINT_MODIFIED
- S3_BACKUP_OBJECT_FAILED | S3_RESTORE_OBJECT_FAILED

Type: Array of strings

Pattern: `.*\S.*`

Required: No

SnsTopicArn

The Amazon Resource Name (ARN) that uniquely identifies the Amazon SNS topic for a backup vault's events.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsBackupRecoveryPointCalculatedLifecycleDetails

Specifies how long in days before a recovery point transitions to cold storage or is deleted.

Contents

DeleteAt

Specifies the number of days after creation that a recovery point is deleted. Must be greater than 90 days plus `MoveToColdStorageAfterDays`.

Type: String

Pattern: `.*\S.*`

Required: No

MoveToColdStorageAt

Specifies the number of days after creation that a recovery point is moved to cold storage.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsBackupRecoveryPointCreatedByDetails

Contains information about the backup plan and rule that Amazon Backup used to initiate the recovery point backup.

Contents

BackupPlanArn

An Amazon Resource Name (ARN) that uniquely identifies a backup plan.

Type: String

Pattern: `.*\S.*`

Required: No

BackupPlanId

Uniquely identifies a backup plan.

Type: String

Pattern: `.*\S.*`

Required: No

BackupPlanVersion

Unique, randomly generated, Unicode, UTF-8 encoded strings that are at most 1,024 bytes long. Version IDs cannot be edited.

Type: String

Pattern: `.*\S.*`

Required: No

BackupRuleId

Uniquely identifies a rule used to schedule the backup of a selection of resources.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsBackupRecoveryPointDetails

Contains detailed information about the recovery points stored in an Amazon Backup backup vault. A backup, or recovery point, represents the content of a resource at a specified time.

Contents

BackupSizeInBytes

The size, in bytes, of a backup.

Type: Long

Required: No

BackupVaultArn

An Amazon Resource Name (ARN) that uniquely identifies a backup vault.

Type: String

Pattern: `.*\S.*`

Required: No

BackupVaultName

The name of a logical container where backups are stored. Backup vaults are identified by names that are unique to the Amazon Web Services account used to create them and the Amazon Web Services Region where they are created. They consist of lowercase letters, numbers, and hyphens.

Type: String

Pattern: `.*\S.*`

Required: No

CalculatedLifecycle

A `CalculatedLifecycle` object containing `DeleteAt` and `MoveToColdStorageAt` timestamps.

Type: [AwsBackupRecoveryPointCalculatedLifecycleDetails](#) object

Required: No

CompletionDate

The date and time that a job to create a recovery point is completed, in Unix format and UTC. The value of `CompletionDate` is accurate to milliseconds. For example, the value 1516925490.087 represents Friday, January 26, 2018 12:11:30.087 AM.

Type: String

Pattern: `.*\S.*`

Required: No

CreatedBy

Contains identifying information about the creation of a recovery point, including the `BackupPlanArn`, `BackupPlanId`, `BackupPlanVersion`, and `BackupRuleId` of the backup plan that is used to create it.

Type: [AwsBackupRecoveryPointCreatedByDetails](#) object

Required: No

CreationDate

The date and time a recovery point is created, in Unix format and UTC. The value of `CreationDate` is accurate to milliseconds. For example, the value 1516925490.087 represents Friday, January 26, 2018 12:11:30.087 AM.

Type: String

Pattern: `.*\S.*`

Required: No

EncryptionKeyArn

The ARN for the server-side encryption key that is used to protect your backups.

Type: String

Pattern: `.*\S.*`

Required: No

IamRoleArn

Specifies the IAM role ARN used to create the target recovery point

Type: String

Pattern: `.*\S.*`

Required: No

IsEncrypted

A Boolean value that is returned as TRUE if the specified recovery point is encrypted, or FALSE if the recovery point is not encrypted.

Type: Boolean

Required: No

LastRestoreTime

The date and time that a recovery point was last restored, in Unix format and UTC. The value of LastRestoreTime is accurate to milliseconds. For example, the value 1516925490.087 represents Friday, January 26, 2018 12:11:30.087 AM.

Type: String

Pattern: `.*\S.*`

Required: No

Lifecycle

The lifecycle defines when a protected resource is transitioned to cold storage and when it expires. Amazon Backup transitions and expires backups automatically according to the lifecycle that you define

Type: [AwsBackupRecoveryPointLifecycleDetails](#) object

Required: No

RecoveryPointArn

An ARN that uniquely identifies a recovery point.

Type: String

Pattern: .*\\S.*

Required: No

ResourceArn

An ARN that uniquely identifies a resource. The format of the ARN depends on the resource type.

Type: String

Pattern: .*\\S.*

Required: No

ResourceType

The type of Amazon resource saved as a recovery point, such as an Amazon EBS volume or an Amazon RDS database.

Type: String

Pattern: .*\\S.*

Required: No

SourceBackupVaultArn

The ARN for the backup vault where the recovery point was originally copied from. If the recovery point is restored to the same account, this value will be null.

Type: String

Pattern: .*\\S.*

Required: No

Status

A status code specifying the state of the recovery point. Valid values are as follows:

- COMPLETED
- DELETING
- EXPIRED
- PARTIAL

Type: String

Pattern: .*\\S.*

Required: No

StatusMessage

A message explaining the reason of the recovery point deletion failure.

Type: String

Pattern: .*\\S.*

Required: No

StorageClass

Specifies the storage class of the recovery point. Valid values are as follows:

- COLD
- DELETED
- WARM

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsBackupRecoveryPointLifecycleDetails

Contains an array of Transition objects specifying how long in days before a recovery point transitions to cold storage or is deleted.

Contents

DeleteAfterDays

Specifies the number of days after creation that a recovery point is deleted. Must be greater than 90 days plus MoveToColdStorageAfterDays.

Type: Long

Required: No

MoveToColdStorageAfterDays

Specifies the number of days after creation that a recovery point is moved to cold storage.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ACM objects

Amazon Certificate Manager (ACM) objects

- [AwsCertificateManagerCertificateDetails](#)
- [AwsCertificateManagerCertificateDomainValidationOption](#)
- [AwsCertificateManagerCertificateExtendedKeyUsage](#)

- [AwsCertificateManagerCertificateKeyUsage](#)
- [AwsCertificateManagerCertificateOptions](#)
- [AwsCertificateManagerCertificateRenewalSummary](#)
- [AwsCertificateManagerCertificateResourceRecord](#)

AwsCertificateManagerCertificateDetails

Provides details about an Amazon Certificate Manager certificate.

Contents

CertificateAuthorityArn

The ARN of the private certificate authority (CA) that will be used to issue the certificate.

Type: String

Pattern: `.*\S.*`

Required: No

CreatedAt

Indicates when the certificate was requested.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

DomainName

The fully qualified domain name (FQDN), such as `www.example.com`, that is secured by the certificate.

Type: String

Pattern: `.*\S.*`

Required: No

DomainValidationOptions

Contains information about the initial validation of each domain name that occurs as a result of the `RequestCertificate` request.

Only provided if the certificate type is AMAZON_ISSUED.

Type: Array of [AwsCertificateManagerCertificateDomainValidationOption](#) objects

Required: No

ExtendedKeyUsages

Contains a list of Extended Key Usage X.509 v3 extension objects. Each object specifies a purpose for which the certificate public key can be used and consists of a name and an object identifier (OID).

Type: Array of [AwsCertificateManagerCertificateExtendedKeyUsage](#) objects

Required: No

FailureReason

For a failed certificate request, the reason for the failure.

Valid values: NO_AVAILABLE_CONTACTS | ADDITIONAL_VERIFICATION_REQUIRED | DOMAIN_NOT_ALLOWED | INVALID_PUBLIC_DOMAIN | DOMAIN_VALIDATION_DENIED | CAA_ERROR | PCA_LIMIT_EXCEEDED | PCA_INVALID_ARN | PCA_INVALID_STATE | PCA_REQUEST_FAILED | PCA_NAME_CONSTRAINTS_VALIDATION | PCA_RESOURCE_NOT_FOUND | PCA_INVALID_ARGS | PCA_INVALID_DURATION | PCA_ACCESS_DENIED | SLR_NOT_FOUND | OTHER

Type: String

Pattern: .*S.*

Required: No

ImportedAt

Indicates when the certificate was imported. Provided if the certificate type is IMPORTED.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*S.*

Required: No

InUseBy

The list of ARNs for the Amazon resources that use the certificate.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

IssuedAt

Indicates when the certificate was issued. Provided if the certificate type is `AMAZON_ISSUED`.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

Issuer

The name of the certificate authority that issued and signed the certificate.

Type: String

Pattern: `.*\S.*`

Required: No

KeyAlgorithm

The algorithm that was used to generate the public-private key pair.

Valid values: `RSA_2048` | `RSA_1024` | `RSA_4096` | `EC_prime256v1` | `EC_secp384r1` | `EC_secp521r1`

Type: String

Pattern: `.*\S.*`

Required: No

KeyUsages

A list of key usage X.509 v3 extension objects.

Type: Array of [AwsCertificateManagerCertificateKeyUsage](#) objects

Required: No

NotAfter

The time after which the certificate becomes invalid.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

NotBefore

The time before which the certificate is not valid.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

Options

Provides a value that specifies whether to add the certificate to a transparency log.

Type: [AwsCertificateManagerCertificateOptions](#) object

Required: No

RenewalEligibility

Whether the certificate is eligible for renewal.

Valid values: ELIGIBLE | INELIGIBLE

Type: String

Pattern: `.*\S.*`

Required: No

RenewalSummary

Information about the status of the Amazon Certificate Manager managed renewal for the certificate. Provided only when the certificate type is AMAZON_ISSUED.

Type: [AwsCertificateManagerCertificateRenewalSummary](#) object

Required: No

Serial

The serial number of the certificate.

Type: String

Pattern: `.*\S.*`

Required: No

SignatureAlgorithm

The algorithm that was used to sign the certificate.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The status of the certificate.

Valid values: PENDING_VALIDATION | ISSUED | INACTIVE | EXPIRED | VALIDATION_TIMED_OUT | REVOKED | FAILED

Type: String

Pattern: `.*\S.*`

Required: No

Subject

The name of the entity that is associated with the public key contained in the certificate.

Type: String

Pattern: `.*\S.*`

Required: No

SubjectAlternativeNames

One or more domain names (subject alternative names) included in the certificate. This list contains the domain names that are bound to the public key that is contained in the certificate.

The subject alternative names include the canonical domain name (CN) of the certificate and additional domain names that can be used to connect to the website.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Type

The source of the certificate. For certificates that Amazon Certificate Manager provides, Type is `AMAZON_ISSUED`. For certificates that are imported with `ImportCertificate`, Type is `IMPORTED`.

Valid values: `IMPORTED` | `AMAZON_ISSUED` | `PRIVATE`

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCertificateManagerCertificateDomainValidationOption

Contains information about one of the following:

- The initial validation of each domain name that occurs as a result of the `RequestCertificate` request
- The validation of each domain name in the certificate, as it pertains to Amazon Certificate Manager managed renewal

Contents

DomainName

A fully qualified domain name (FQDN) in the certificate.

Type: String

Pattern: `.*\S.*`

Required: No

ResourceRecord

The CNAME record that is added to the DNS database for domain validation.

Type: [AwsCertificateManagerCertificateResourceRecord](#) object

Required: No

ValidationDomain

The domain name that Amazon Certificate Manager uses to send domain validation emails.

Type: String

Pattern: `.*\S.*`

Required: No

ValidationEmails

A list of email addresses that Amazon Certificate Manager uses to send domain validation emails.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

ValidationMethod

The method used to validate the domain name.

Type: String

Pattern: `.*\S.*`

Required: No

ValidationStatus

The validation status of the domain name.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCertificateManagerCertificateExtendedKeyUsage

Contains information about an extended key usage X.509 v3 extension object.

Contents

Name

The name of an extension value. Indicates the purpose for which the certificate public key can be used.

Type: String

Pattern: `.*\S.*`

Required: No

Old

An object identifier (OID) for the extension value.

The format is numbers separated by periods.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCertificateManagerCertificateKeyUsage

Contains information about a key usage X.509 v3 extension object.

Contents

Name

The key usage extension name.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCertificateManagerCertificateOptions

Contains other options for the certificate.

Contents

CertificateTransparencyLoggingPreference

Whether to add the certificate to a transparency log.

Valid values: DISABLED | ENABLED

Type: String

Pattern: .*S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCertificateManagerCertificateRenewalSummary

Contains information about the Amazon Certificate Manager managed renewal for an AMAZON_ISSUED certificate.

Contents

DomainValidationOptions

Information about the validation of each domain name in the certificate, as it pertains to Amazon Certificate Manager managed renewal. Provided only when the certificate type is AMAZON_ISSUED.

Type: Array of [AwsCertificateManagerCertificateDomainValidationOption](#) objects

Required: No

RenewalStatus

The status of the Amazon Certificate Manager managed renewal of the certificate.

Valid values: PENDING_AUTO_RENEWAL | PENDING_VALIDATION | SUCCESS | FAILED

Type: String

Pattern: .*\.S.*

Required: No

RenewalStatusReason

The reason that a renewal request was unsuccessful. This attribute is used only when RenewalStatus is FAILED.

Valid values: NO_AVAILABLE_CONTACTS | ADDITIONAL_VERIFICATION_REQUIRED | DOMAIN_NOT_ALLOWED | INVALID_PUBLIC_DOMAIN | DOMAIN_VALIDATION_DENIED | CAA_ERROR | PCA_LIMIT_EXCEEDED | PCA_INVALID_ARN | PCA_INVALID_STATE | PCA_REQUEST_FAILED | PCA_NAME_CONSTRAINTS_VALIDATION | PCA_RESOURCE_NOT_FOUND | PCA_INVALID_ARGS | PCA_INVALID_DURATION | PCA_ACCESS_DENIED | SLR_NOT_FOUND | OTHER

Type: String

Pattern: .*\.S.*

Required: No

UpdatedAt

Indicates when the renewal summary was last updated.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCertificateManagerCertificateResourceRecord

Provides details about the CNAME record that is added to the DNS database for domain validation.

Contents

Name

The name of the resource.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The type of resource.

Type: String

Pattern: `.*\S.*`

Required: No

Value

The value of the resource.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

Amazon CloudFormation

Amazon CloudFormation objects

- [AwsCloudFormationStackDetails](#)
- [AwsCloudFormationStackDriftInformationDetails](#)
- [AwsCloudFormationStackOutputsDetails](#)

AwsCloudFormationStackDetails

Nests a stack as a resource in a top-level template. Nested stacks are stacks created as resources for another stack.

Contents

Capabilities

The capabilities allowed in the stack.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

CreationTime

The time at which the stack was created.

Type: String

Pattern: `.*\S.*`

Required: No

Description

A user-defined description associated with the stack.

Type: String

Pattern: `.*\S.*`

Required: No

DisableRollback

Boolean to enable or disable rollback on stack creation failures.

Type: Boolean

Required: No

DriftInformation

Information about whether a stack's actual configuration differs, or has drifted, from its expected configuration, as defined in the stack template and any values specified as template parameters.

Type: [AwsCloudFormationStackDriftInformationDetails](#) object

Required: No

EnableTerminationProtection

Whether termination protection is enabled for the stack.

Type: Boolean

Required: No

LastUpdatedTime

The time the nested stack was last updated. This field will only be returned if the stack has been updated at least once.

Type: String

Pattern: `.*\S.*`

Required: No

NotificationArns

The Amazon Resource Names (ARNs) of the Amazon SNS topic to which stack-related events are published.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Outputs

A list of output structures.

Type: Array of [AwsCloudFormationStackOutputsDetails](#) objects

Required: No

RoleArn

The ARN of an IAM role that's associated with the stack.

Type: String

Pattern: `.*\S.*`

Required: No

StackId

Unique identifier of the stack.

Type: String

Pattern: `.*\S.*`

Required: No

StackName

The name associated with the stack.

Type: String

Pattern: `.*\S.*`

Required: No

StackStatus

Current status of the stack.

Type: String

Pattern: `.*\S.*`

Required: No

StackStatusReason

Success or failure message associated with the stack status.

Type: String

Pattern: `.*\S.*`

Required: No

TimeoutInMinutes

The length of time, in minutes, that CloudFormation waits for the nested stack to reach the `CREATE_COMPLETE` state.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCloudFormationStackDriftInformationDetails

Provides information about the stack's conformity to its expected template configuration.

Contents

StackDriftStatus

Status of the stack's actual configuration compared to its expected template configuration.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCloudFormationStackOutputsDetails

Provides information about the Amazon CloudFormation stack output.

Contents

Description

A user-defined description associated with the output.

Type: String

Pattern: `.*\S.*`

Required: No

OutputKey

The key associated with the output.

Type: String

Pattern: `.*\S.*`

Required: No

OutputValue

The value associated with the output.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

Amazon CloudFront

Amazon CloudFront objects

- [AwsCloudFrontDistributionCacheBehavior](#)
- [AwsCloudFrontDistributionCacheBehaviors](#)
- [AwsCloudFrontDistributionDefaultCacheBehavior](#)
- [AwsCloudFrontDistributionDetails](#)
- [AwsCloudFrontDistributionLogging](#)
- [AwsCloudFrontDistributionOriginCustomOriginConfig](#)
- [AwsCloudFrontDistributionOriginGroup](#)
- [AwsCloudFrontDistributionOriginGroupFailover](#)
- [AwsCloudFrontDistributionOriginGroupFailoverStatusCodes](#)
- [AwsCloudFrontDistributionOriginGroups](#)
- [AwsCloudFrontDistributionOriginItem](#)
- [AwsCloudFrontDistributionOrigins](#)
- [AwsCloudFrontDistributionOriginS3OriginConfig](#)
- [AwsCloudFrontDistributionOriginSslProtocols](#)
- [AwsCloudFrontDistributionViewerCertificate](#)

AwsCloudFrontDistributionCacheBehavior

Information about a cache behavior for the distribution.

Contents

ViewerProtocolPolicy

The protocol that viewers can use to access the files in an origin. You can specify the following options:

- `allow-all` - Viewers can use HTTP or HTTPS.
- `redirect-to-https` - CloudFront responds to HTTP requests with an HTTP status code of 301 (Moved Permanently) and the HTTPS URL. The viewer then uses the new URL to resubmit.
- `https-only` - CloudFront responds to HTTP request with an HTTP status code of 403 (Forbidden).

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCloudFrontDistributionCacheBehaviors

Provides information about caching for the CloudFront distribution.

Contents

Items

The cache behaviors for the distribution.

Type: Array of [AwsCloudFrontDistributionCacheBehavior](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCloudFrontDistributionDefaultCacheBehavior

Contains information about the default cache configuration for the CloudFront distribution.

Contents

ViewerProtocolPolicy

The protocol that viewers can use to access the files in an origin. You can specify the following options:

- `allow-all` - Viewers can use HTTP or HTTPS.
- `redirect-to-https` - CloudFront responds to HTTP requests with an HTTP status code of 301 (Moved Permanently) and the HTTPS URL. The viewer then uses the new URL to resubmit.
- `https-only` - CloudFront responds to HTTP request with an HTTP status code of 403 (Forbidden).

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCloudFrontDistributionDetails

A CloudFront distribution configuration.

Contents

CacheBehaviors

Provides information about the cache configuration for the distribution.

Type: [AwsCloudFrontDistributionCacheBehaviors](#) object

Required: No

DefaultCacheBehavior

The default cache behavior for the configuration.

Type: [AwsCloudFrontDistributionDefaultCacheBehavior](#) object

Required: No

DefaultRootObject

The object that CloudFront sends in response to requests from the origin (for example, index.html) when a viewer requests the root URL for the distribution (http://www.example.com) instead of an object in your distribution (http://www.example.com/product-description.html).

Type: String

Pattern: `.*\S.*`

Required: No

DomainName

The domain name corresponding to the distribution.

Type: String

Pattern: `.*\S.*`

Required: No

ETag

The entity tag is a hash of the object.

Type: String

Pattern: .*\\S.*

Required: No

LastModifiedTime

Indicates when that the distribution was last modified.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

Logging

A complex type that controls whether access logs are written for the distribution.

Type: [AwsCloudFrontDistributionLogging](#) object

Required: No

OriginGroups

Provides information about the origin groups in the distribution.

Type: [AwsCloudFrontDistributionOriginGroups](#) object

Required: No

Origins

A complex type that contains information about origins for this distribution.

Type: [AwsCloudFrontDistributionOrigins](#) object

Required: No

Status

Indicates the current status of the distribution.

Type: String

Pattern: .*\\S.*

Required: No

ViewerCertificate

Provides information about the TLS/SSL configuration that the distribution uses to communicate with viewers.

Type: [AwsCloudFrontDistributionViewerCertificate](#) object

Required: No

WebAclId

A unique identifier that specifies the Amazon WAF web ACL, if any, to associate with this distribution.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCloudFrontDistributionLogging

A complex type that controls whether access logs are written for the CloudFront distribution.

Contents

Bucket

The S3 bucket to store the access logs in.

Type: String

Pattern: `.*\S.*`

Required: No

Enabled

With this field, you can enable or disable the selected distribution.

Type: Boolean

Required: No

IncludeCookies

Specifies whether you want CloudFront to include cookies in access logs.

Type: Boolean

Required: No

Prefix

An optional string that you want CloudFront to use as a prefix to the access log filenames for this distribution.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCloudFrontDistributionOriginCustomOriginConfig

A custom origin. A custom origin is any origin that is not an Amazon S3 bucket, with one exception. An Amazon S3 bucket that is [configured with static website hosting](#) is a custom origin.

Contents

HttpPort

The HTTP port that CloudFront uses to connect to the origin.

Type: Integer

Required: No

HttpsPort

The HTTPS port that CloudFront uses to connect to the origin.

Type: Integer

Required: No

OriginKeepaliveTimeout

Specifies how long, in seconds, CloudFront persists its connection to the origin.

Type: Integer

Required: No

OriginProtocolPolicy

Specifies the protocol (HTTP or HTTPS) that CloudFront uses to connect to the origin.

Type: String

Pattern: `.*\S.*`

Required: No

OriginReadTimeout

Specifies how long, in seconds, CloudFront waits for a response from the origin.

Type: Integer

Required: No

OriginSslProtocols

Specifies the minimum SSL/TLS protocol that CloudFront uses when connecting to your origin over HTTPS.

Type: [AwsCloudFrontDistributionOriginSslProtocols](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCloudFrontDistributionOriginGroup

Information about an origin group for the CloudFront distribution.

Contents

FailoverCriteria

Provides the criteria for an origin group to fail over.

Type: [AwsCloudFrontDistributionOriginGroupFailover](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCloudFrontDistributionOriginGroupFailover

Provides information about when an origin group fails over.

Contents

StatusCodes

Information about the status codes that cause an origin group to fail over.

Type: [AwsCloudFrontDistributionOriginGroupFailoverStatusCodes](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCloudFrontDistributionOriginGroupFailoverStatusCodes

The status codes that cause an origin group to fail over.

Contents

Items

The list of status code values that can cause a failover to the next origin.

Type: Array of integers

Required: No

Quantity

The number of status codes that can cause a failover.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCloudFrontDistributionOriginGroups

Provides information about origin groups that are associated with the CloudFront distribution.

Contents

Items

The list of origin groups.

Type: Array of [AwsCloudFrontDistributionOriginGroup](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCloudFrontDistributionOriginItem

A complex type that describes the Amazon S3 bucket, HTTP server (for example, a web server), AWS Elemental MediaStore, or other server from which CloudFront gets your files.

Contents

CustomOriginConfig

An origin that is not an Amazon S3 bucket, with one exception. If the Amazon S3 bucket is configured with static website hosting, use this attribute. If the Amazon S3 bucket is not configured with static website hosting, use the `S3OriginConfig` type instead.

Type: [AwsCloudFrontDistributionOriginCustomOriginConfig](#) object

Required: No

DomainName

Amazon S3 origins: The DNS name of the S3 bucket from which you want CloudFront to get objects for this origin.

Type: String

Pattern: `.*\S.*`

Required: No

Id

A unique identifier for the origin or origin group.

Type: String

Pattern: `.*\S.*`

Required: No

OriginPath

An optional element that causes CloudFront to request your content from a directory in your Amazon S3 bucket or your custom origin.

Type: String

Pattern: `.*\S.*`

Required: No

S3OriginConfig

An origin that is an S3 bucket that is not configured with static website hosting.

Type: [AwsCloudFrontDistributionOriginS3OriginConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCloudFrontDistributionOrigins

A complex type that contains information about origins and origin groups for this CloudFront distribution.

Contents

Items

A complex type that contains origins or origin groups for this distribution.

Type: Array of [AwsCloudFrontDistributionOriginItem](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCloudFrontDistributionOriginS3OriginConfig

Information about an origin that is an Amazon S3 bucket that is not configured with static website hosting.

Contents

OriginAccessIdentity

The CloudFront origin access identity to associate with the origin.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCloudFrontDistributionOriginSslProtocols

A complex type that contains information about the SSL/TLS protocols that CloudFront can use when establishing an HTTPS connection with your origin.

Contents

Items

A list that contains allowed SSL/TLS protocols for this distribution.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Quantity

The number of SSL/TLS protocols that you want to allow CloudFront to use when establishing an HTTPS connection with this origin.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCloudFrontDistributionViewerCertificate

Provides information about the TLS/SSL configuration that the CloudFront distribution uses to communicate with viewers.

Contents

AcmCertificateArn

The ARN of the ACM certificate. Used if the certificate is stored in ACM. If you provide an ACM certificate ARN, you must also provide `MinimumCertificateVersion` and `SslSupportMethod`.

Type: String

Pattern: `.*\S.*`

Required: No

Certificate

The identifier of the certificate. Note that in CloudFront, this attribute is deprecated.

Type: String

Pattern: `.*\S.*`

Required: No

CertificateSource

The source of the certificate identified by `Certificate`. Note that in CloudFront, this attribute is deprecated.

Type: String

Pattern: `.*\S.*`

Required: No

CloudFrontDefaultCertificate

Whether the distribution uses the CloudFront domain name. If set to `false`, then you provide either `AcmCertificateArn` or `IamCertificateId`.

Type: Boolean

Required: No

IamCertificateId

The identifier of the IAM certificate. Used if the certificate is stored in IAM. If you provide `IamCertificateId`, then you also must provide `MinimumProtocolVersion` and `SslSupportMethod`.

Type: String

Pattern: `.*\S.*`

Required: No

MinimumProtocolVersion

The security policy that CloudFront uses for HTTPS connections with viewers. If `SslSupportMethod` is `sni-only`, then `MinimumProtocolVersion` must be `TLSv1` or higher.

Type: String

Pattern: `.*\S.*`

Required: No

SslSupportMethod

The viewers that the distribution accepts HTTPS connections from.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

Amazon CloudTrail

Amazon CloudTrail objects

- [AwsCloudTrailTrailDetails](#)

AwsCloudTrailTrailDetails

Provides details about a CloudTrail trail.

Contents

CloudWatchLogsLogGroupArn

The ARN of the log group that CloudTrail logs are delivered to.

Type: String

Pattern: `.*\S.*`

Required: No

CloudWatchLogsRoleArn

The ARN of the role that the CloudWatch Events endpoint assumes when it writes to the log group.

Type: String

Pattern: `.*\S.*`

Required: No

HasCustomEventSelectors

Indicates whether the trail has custom event selectors.

Type: Boolean

Required: No

HomeRegion

The Region where the trail was created.

Type: String

Pattern: `.*\S.*`

Required: No

IncludeGlobalServiceEvents

Indicates whether the trail publishes events from global services such as IAM to the log files.

Type: Boolean

Required: No

IsMultiRegionTrail

Indicates whether the trail applies only to the current Region or to all Regions.

Type: Boolean

Required: No

IsOrganizationTrail

Whether the trail is created for all accounts in an organization in Amazon Organizations, or only for the current Amazon Web Services account.

Type: Boolean

Required: No

KmsKeyId

The Amazon KMS key ID to use to encrypt the logs.

Type: String

Pattern: `.*\S.*`

Required: No

LogFileValidationEnabled

Indicates whether CloudTrail log file validation is enabled.

Type: Boolean

Required: No

Name

The name of the trail.

Type: String

Pattern: `.*\S.*`

Required: No

S3BucketName

The name of the S3 bucket where the log files are published.

Type: String

Pattern: `.*\S.*`

Required: No

S3KeyPrefix

The S3 key prefix. The key prefix is added after the name of the S3 bucket where the log files are published.

Type: String

Pattern: `.*\S.*`

Required: No

SnsTopicArn

The ARN of the SNS topic that is used for notifications of log file delivery.

Type: String

Pattern: `.*\S.*`

Required: No

SnsTopicName

The name of the SNS topic that is used for notifications of log file delivery.

Type: String

Pattern: `.*\S.*`

Required: No

TrailArn

The ARN of the trail.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon CloudWatch

Amazon CloudWatch objects

- [AwsCloudWatchAlarmDetails](#)
- [AwsCloudWatchAlarmDimensionsDetails](#)

AwsCloudWatchAlarmDetails

Specifies an alarm and associates it with the specified metric or metric math expression.

Contents

ActionsEnabled

Indicates whether actions should be executed during any changes to the alarm state.

Type: Boolean

Required: No

AlarmActions

The list of actions, specified as Amazon Resource Names (ARNs) to execute when this alarm transitions into an ALARM state from any other state.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

AlarmArn

The ARN of the alarm.

Type: String

Pattern: `.*\S.*`

Required: No

AlarmConfigurationUpdatedTimestamp

The time stamp of the last update to the alarm configuration.

Type: String

Pattern: `.*\S.*`

Required: No

AlarmDescription

The description of the alarm.

Type: String

Pattern: `.*\S.*`

Required: No

AlarmName

The name of the alarm. If you don't specify a name, CloudFront generates a unique physical ID and uses that ID for the alarm name.

Type: String

Pattern: `.*\S.*`

Required: No

ComparisonOperator

The arithmetic operation to use when comparing the specified statistic and threshold. The specified statistic value is used as the first operand.

Type: String

Pattern: `.*\S.*`

Required: No

DatapointsToAlarm

The number of datapoints that must be breaching to trigger the alarm.

Type: Integer

Required: No

Dimensions

The dimensions for the metric associated with the alarm.

Type: Array of [AwsCloudWatchAlarmDimensionsDetails](#) objects

Required: No

EvaluateLowSampleCountPercentile

Used only for alarms based on percentiles. If `ignore`, the alarm state does not change during periods with too few data points to be statistically significant. If `evaluate` or this parameter is not used, the alarm is always evaluated and possibly changes state no matter how many data points are available.

Type: String

Pattern: `.*\S.*`

Required: No

EvaluationPeriods

The number of periods over which data is compared to the specified threshold.

Type: Integer

Required: No

ExtendedStatistic

The percentile statistic for the metric associated with the alarm.

Type: String

Pattern: `.*\S.*`

Required: No

InsufficientDataActions

The actions to execute when this alarm transitions to the `INSUFFICIENT_DATA` state from any other state. Each action is specified as an ARN.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

MetricName

The name of the metric associated with the alarm. This is required for an alarm based on a metric. For an alarm based on a math expression, you use `Metrics` instead and you can't specify `MetricName`.

Type: String

Pattern: `.*\S.*`

Required: No

Namespace

The namespace of the metric associated with the alarm. This is required for an alarm based on a metric. For an alarm based on a math expression, you can't specify `Namespace` and you use `Metrics` instead.

Type: String

Pattern: `.*\S.*`

Required: No

OkActions

The actions to execute when this alarm transitions to the OK state from any other state. Each action is specified as an ARN.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Period

The period, in seconds, over which the statistic is applied. This is required for an alarm based on a metric.

Type: Integer

Required: No

Statistic

The statistic for the metric associated with the alarm, other than percentile. For percentile statistics, use `ExtendedStatistic`.

For an alarm based on a metric, you must specify either `Statistic` or `ExtendedStatistic` but not both.

For an alarm based on a math expression, you can't specify `Statistic`. Instead, you use `Metrics`.

Type: String

Pattern: `.*\S.*`

Required: No

Threshold

The value to compare with the specified statistic.

Type: Double

Required: No

ThresholdMetricId

In an alarm based on an anomaly detection model, this is the ID of the `ANOMALY_DETECTION_BAND` function used as the threshold for the alarm.

Type: String

Pattern: `.*\S.*`

Required: No

TreatMissingData

Sets how this alarm is to handle missing data points.

Type: String

Pattern: `.*\S.*`

Required: No

Unit

The unit of the metric associated with the alarm.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCloudWatchAlarmDimensionsDetails

Details about the dimensions for the metric associated with the alarm.

Contents

Name

The name of a dimension.

Type: String

Pattern: `.*\S.*`

Required: No

Value

The value of a dimension.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon CodeBuild

Amazon CodeBuild objects

- [AwsCodeBuildProjectArtifactsDetails](#)
- [AwsCodeBuildProjectDetails](#)

- [AwsCodeBuildProjectEnvironment](#)
- [AwsCodeBuildProjectEnvironmentEnvironmentVariablesDetails](#)
- [AwsCodeBuildProjectEnvironmentRegistryCredential](#)
- [AwsCodeBuildProjectLogsConfigCloudWatchLogsDetails](#)
- [AwsCodeBuildProjectLogsConfigDetails](#)
- [AwsCodeBuildProjectLogsConfigS3LogsDetails](#)
- [AwsCodeBuildProjectSource](#)
- [AwsCodeBuildProjectVpcConfig](#)

AwsCodeBuildProjectArtifactsDetails

Information about the build artifacts for the CodeBuild project.

Contents

ArtifactIdentifier

An identifier for the artifact definition.

Type: String

Pattern: `.*\S.*`

Required: No

EncryptionDisabled

Indicates whether to disable encryption on the artifact. Only valid when Type is S3.

Type: Boolean

Required: No

Location

Only used when Type is S3. The name of the S3 bucket where the artifact is located.

Type: String

Pattern: `.*\S.*`

Required: No

Name

Only used when Type is S3. The name of the artifact. Used with NamespaceType and Path to determine the pattern for storing the artifact.

Type: String

Pattern: `.*\S.*`

Required: No

NamespaceType

Only used when Type is S3. The value to use for the namespace. Used with Name and Path to determine the pattern for storing the artifact.

Type: String

Pattern: `.*\S.*`

Required: No

OverrideArtifactName

Whether the name specified in the buildspec file overrides the artifact name.

Type: Boolean

Required: No

Packaging

Only used when Type is S3. The type of output artifact to create.

Type: String

Pattern: `.*\S.*`

Required: No

Path

Only used when Type is S3. The path to the artifact. Used with Name and NamespaceType to determine the pattern for storing the artifact.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The type of build artifact.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCodeBuildProjectDetails

Information about an Amazon CodeBuild project.

Contents

Artifacts

Information about the build artifacts for the CodeBuild project.

Type: Array of [AwsCodeBuildProjectArtifactsDetails](#) objects

Required: No

EncryptionKey

The Amazon KMS key used to encrypt the build output artifacts.

You can specify either the ARN of the KMS key or, if available, the KMS key alias (using the format alias/alias-name).

Type: String

Pattern: `.*\S.*`

Required: No

Environment

Information about the build environment for this build project.

Type: [AwsCodeBuildProjectEnvironment](#) object

Required: No

LogsConfig

Information about logs for the build project.

Type: [AwsCodeBuildProjectLogsConfigDetails](#) object

Required: No

Name

The name of the build project.

Type: String

Pattern: .*\\S.*

Required: No

SecondaryArtifacts

Information about the secondary artifacts for the CodeBuild project.

Type: Array of [AwsCodeBuildProjectArtifactsDetails](#) objects

Required: No

ServiceRole

The ARN of the IAM role that enables Amazon CodeBuild to interact with dependent Amazon services on behalf of the Amazon Web Services account.

Type: String

Pattern: .*\\S.*

Required: No

Source

Information about the build input source code for this build project.

Type: [AwsCodeBuildProjectSource](#) object

Required: No

VpcConfig

Information about the VPC configuration that Amazon CodeBuild accesses.

Type: [AwsCodeBuildProjectVpcConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCodeBuildProjectEnvironment

Information about the build environment for this build project.

Contents

Certificate

The certificate to use with this build project.

Type: String

Pattern: `.*\S.*`

Required: No

EnvironmentVariables

A set of environment variables to make available to builds for the build project.

Type: Array of [AwsCodeBuildProjectEnvironmentEnvironmentVariablesDetails](#) objects

Required: No

ImagePullCredentialsType

The type of credentials Amazon CodeBuild uses to pull images in your build.

Valid values:

- `CODEBUILD` specifies that Amazon CodeBuild uses its own credentials. This requires that you modify your ECR repository policy to trust the Amazon CodeBuild service principal.
- `SERVICE_ROLE` specifies that Amazon CodeBuild uses your build project's service role.

When you use a cross-account or private registry image, you must use `SERVICE_ROLE` credentials. When you use an Amazon CodeBuild curated image, you must use `CODEBUILD` credentials.

Type: String

Pattern: `.*\S.*`

Required: No

PrivilegedMode

Whether to allow the Docker daemon to run inside a Docker container. Set to `true` if the build project is used to build Docker images.

Type: Boolean

Required: No

RegistryCredential

The credentials for access to a private registry.

Type: [AwsCodeBuildProjectEnvironmentRegistryCredential](#) object

Required: No

Type

The type of build environment to use for related builds.

The environment type `ARM_CONTAINER` is available only in Regions US East (N. Virginia), US East (Ohio), US West (Oregon), Europe (Ireland), Asia Pacific (Mumbai), Asia Pacific (Tokyo), Asia Pacific (Sydney), and Europe (Frankfurt).

The environment type `LINUX_CONTAINER` with compute type `build.general1.2xlarge` is available only in Regions US East (N. Virginia), US East (N. Virginia), US West (Oregon), Canada (Central), Europe (Ireland), Europe (London), Europe (Frankfurt), Asia Pacific (Tokyo), Asia Pacific (Seoul), Asia Pacific (Singapore), Asia Pacific (Sydney), China (Beijing), and China (Ningxia).

The environment type `LINUX_GPU_CONTAINER` is available only in Regions US East (N. Virginia), US East (N. Virginia), US West (Oregon), Canada (Central), Europe (Ireland), Europe (London), Europe (Frankfurt), Asia Pacific (Tokyo), Asia Pacific (Seoul), Asia Pacific (Singapore), Asia Pacific (Sydney), China (Beijing), and China (Ningxia).

Valid values: `WINDOWS_CONTAINER` | `LINUX_CONTAINER` | `LINUX_GPU_CONTAINER` | `ARM_CONTAINER`

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCodeBuildProjectEnvironmentEnvironmentVariablesDetails

Information about an environment variable that is available to builds for the build project.

Contents

Name

The name of the environment variable.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The type of environment variable.

Type: String

Pattern: `.*\S.*`

Required: No

Value

The value of the environment variable.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsCodeBuildProjectEnvironmentRegistryCredential

The credentials for access to a private registry.

Contents

Credential

The ARN or name of credentials created using Amazon Secrets Manager.

Note

The credential can use the name of the credentials only if they exist in your current Amazon Web Services Region.

Type: String

Pattern: `.*\S.*`

Required: No

CredentialProvider

The service that created the credentials to access a private Docker registry.

The valid value, `SECRETS_MANAGER`, is for Amazon Secrets Manager.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCodeBuildProjectLogsConfigCloudWatchLogsDetails

Information about CloudWatch Logs for the build project.

Contents

GroupName

The group name of the logs in CloudWatch Logs.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The current status of the logs in CloudWatch Logs for a build project.

Type: String

Pattern: `.*\S.*`

Required: No

StreamName

The prefix of the stream name of the CloudWatch Logs.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsCodeBuildProjectLogsConfigDetails

Information about logs for the build project.

Contents

CloudWatchLogs

Information about CloudWatch Logs for the build project.

Type: [AwsCodeBuildProjectLogsConfigCloudWatchLogsDetails](#) object

Required: No

S3Logs

Information about logs built to an S3 bucket for a build project.

Type: [AwsCodeBuildProjectLogsConfigS3LogsDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCodeBuildProjectLogsConfigS3LogsDetails

Information about logs built to an S3 bucket for a build project.

Contents

EncryptionDisabled

Whether to disable encryption of the S3 build log output.

Type: Boolean

Required: No

Location

The ARN of the S3 bucket and the path prefix for S3 logs.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The current status of the S3 build logs.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCodeBuildProjectSource

Information about the build input source code for this build project.

Contents

GitCloneDepth

Information about the Git clone depth for the build project.

Type: Integer

Required: No

InsecureSsl

Whether to ignore SSL warnings while connecting to the project source code.

Type: Boolean

Required: No

Location

Information about the location of the source code to be built.

Valid values include:

- For source code settings that are specified in the source action of a pipeline in Amazon CodePipeline, location should not be specified. If it is specified, Amazon CodePipeline ignores it. This is because Amazon CodePipeline uses the settings in a pipeline's source action instead of this value.
- For source code in an Amazon CodeCommit repository, the HTTPS clone URL to the repository that contains the source code and the build spec file (for example, `https://git-codecommit.region-ID.amazonaws.com/v1/repos/repo-name`).
- For source code in an S3 input bucket, one of the following.
 - The path to the ZIP file that contains the source code (for example, `bucket-name/path/to/object-name.zip`).
 - The path to the folder that contains the source code (for example, `bucket-name/path/to/source-code/folder/`).
- For source code in a GitHub repository, the HTTPS clone URL to the repository that contains the source and the build spec file.

- For source code in a Bitbucket repository, the HTTPS clone URL to the repository that contains the source and the build spec file.

Type: String

Pattern: .*\\S.*

Required: No

Type

The type of repository that contains the source code to be built. Valid values are:

- BITBUCKET - The source code is in a Bitbucket repository.
- CODECOMMIT - The source code is in an Amazon CodeCommit repository.
- CODEPIPELINE - The source code settings are specified in the source action of a pipeline in Amazon CodePipeline.
- GITHUB - The source code is in a GitHub repository.
- GITHUB_ENTERPRISE - The source code is in a GitHub Enterprise repository.
- NO_SOURCE - The project does not have input source code.
- S3 - The source code is in an S3 input bucket.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsCodeBuildProjectVpcConfig

Information about the VPC configuration that Amazon CodeBuild accesses.

Contents

SecurityGroupIds

A list of one or more security group IDs in your VPC.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Subnets

A list of one or more subnet IDs in your VPC.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

VpcId

The ID of the VPC.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

Amazon DMS objects

Amazon Database Migration Service (Amazon DMS) objects

- [AwsDmsEndpointDetails](#)
- [AwsDmsReplicationInstanceDetails](#)
- [AwsDmsReplicationInstanceReplicationSubnetGroupDetails](#)
- [AwsDmsReplicationInstanceVpcSecurityGroupsDetails](#)
- [AwsDmsReplicationTaskDetails](#)

AwsDmsEndpointDetails

Provides details about an Amazon Database Migration Service (Amazon DMS) endpoint. An endpoint provides connection, data store type, and location information about your data store.

Contents

CertificateArn

The Amazon Resource Name (ARN) for the SSL certificate that encrypts connections between the DMS endpoint and the replication instance.

Type: String

Pattern: `.*\S.*`

Required: No

DatabaseName

The name of the endpoint database.

Type: String

Pattern: `.*\S.*`

Required: No

EndpointArn

The Amazon Resource Name (ARN) of the endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

EndpointIdentifier

The database endpoint identifier.

Type: String

Pattern: `.*\S.*`

Required: No

EndpointType

The type of endpoint. Valid values are source and target.

Type: String

Pattern: `.*\S.*`

Required: No

EngineName

The type of engine for the endpoint, depending on the EndpointType value.

Type: String

Pattern: `.*\S.*`

Required: No

ExternalId

A value that can be used for cross-account validation.

Type: String

Pattern: `.*\S.*`

Required: No

ExtraConnectionAttributes

Additional attributes associated with the connection.

Type: String

Pattern: `.*\S.*`

Required: No

KmsKeyId

An Amazon DMS key identifier that is used to encrypt the connection parameters for the endpoint. If you don't specify a value for the KmsKeyId parameter, then Amazon DMS uses your default encryption key. Amazon KMS creates the default encryption key for your Amazon Web

Services account. Your Amazon Web Services account has a different default encryption key for each Amazon Web Services Region.

Type: String

Pattern: `.*\S.*`

Required: No

Port

The port used to access the endpoint.

Type: Integer

Required: No

ServerName

The name of the server where the endpoint database resides.

Type: String

Pattern: `.*\S.*`

Required: No

SslMode

The SSL mode used to connect to the endpoint. The default is none.

Type: String

Pattern: `.*\S.*`

Required: No

Username

The user name to be used to log in to the endpoint database.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsDmsReplicationInstanceDetails

Provides details about an Amazon Database Migration Service (Amazon DMS) replication instance. DMS uses a replication instance to connect to your source data store, read the source data, and format the data for consumption by the target data store.

Contents

AllocatedStorage

The amount of storage (in gigabytes) that is allocated for the replication instance.

Type: Integer

Required: No

AutoMinorVersionUpgrade

Indicates whether minor engine upgrades are applied automatically to the replication instance during the maintenance window.

Type: Boolean

Required: No

AvailabilityZone

The Availability Zone that the replication instance is created in. The default value is a random, system-chosen Availability Zone in the endpoint's Amazon Web Services Region, such as us-east-1d.

Type: String

Pattern: `.*\S.*`

Required: No

EngineVersion

The engine version number of the replication instance. If an engine version number is not specified when a replication instance is created, the default is the latest engine version available.

Type: String

Pattern: `.*\S.*`

Required: No

KmsKeyId

An Amazon KMS key identifier that is used to encrypt the data on the replication instance. If you don't specify a value for the `KmsKeyId` parameter, Amazon DMS uses your default encryption key. Amazon KMS creates the default encryption key for your Amazon Web Services account. Your Amazon Web Services account has a different default encryption key for each Amazon Web Services Region.

Type: String

Pattern: `.*\S.*`

Required: No

MultiAZ

Specifies whether the replication instance is deployed across multiple Availability Zones (AZs). You can't set the `AvailabilityZone` parameter if the `MultiAZ` parameter is set to `true`.

Type: Boolean

Required: No

PreferredMaintenanceWindow

The maintenance window times for the replication instance. Upgrades to the replication instance are performed during this time.

Type: String

Pattern: `.*\S.*`

Required: No

PubliclyAccessible

Specifies the accessibility options for the replication instance. A value of `true` represents an instance with a public IP address. A value of `false` represents an instance with a private IP address. The default value is `true`.

Type: Boolean

Required: No

ReplicationInstanceClass

The compute and memory capacity of the replication instance as defined for the specified replication instance class.

Type: String

Pattern: `.*\S.*`

Required: No

ReplicationInstanceIdentifier

The replication instance identifier.

Type: String

Pattern: `.*\S.*`

Required: No

ReplicationSubnetGroup

The subnet group for the replication instance.

Type: [AwsDmsReplicationInstanceReplicationSubnetGroupDetails](#) object

Required: No

VpcSecurityGroups

The virtual private cloud (VPC) security group for the replication instance.

Type: Array of [AwsDmsReplicationInstanceVpcSecurityGroupsDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsDmsReplicationInstanceReplicationSubnetGroupDetails

Provides details about the replication subnet group.

Contents

ReplicationSubnetGroupIdentifier

The identifier of the replication subnet group.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsDmsReplicationInstanceVpcSecurityGroupsDetails

Provides details about the virtual private cloud (VPC) security group that's associated with the replication instance.

Contents

VpcSecurityGroupId

The identifier of the VPC security group that's associated with the replication instance.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsDmsReplicationTaskDetails

Provides details about an Amazon Database Migration Service (Amazon DMS) replication task. A replication task moves a set of data from the source endpoint to the target endpoint.

Contents

CdcStartPosition

Indicates when you want a change data capture (CDC) operation to start. `CCdcStartPosition` or `CCdcStartTime` specifies when you want a CDC operation to start. Only a value for one of these fields is included.

Type: String

Pattern: `.*\S.*`

Required: No

CdcStartTime

Indicates the start time for a CDC operation. `CdcStartPosition` or `CCdcStartTime` specifies when you want a CDC operation to start. Only a value for one of these fields is included.

Type: String

Pattern: `.*\S.*`

Required: No

CdcStopPosition

Indicates when you want a CDC operation to stop. The value can be either server time or commit time.

Type: String

Pattern: `.*\S.*`

Required: No

Id

The identifier of the replication task.

Type: String

Pattern: `.*\S.*`

Required: No

MigrationType

The migration type.

Type: String

Pattern: `.*\S.*`

Required: No

ReplicationInstanceArn

The Amazon Resource Name (ARN) of a replication instance.

Type: String

Pattern: `.*\S.*`

Required: No

ReplicationTaskIdentifier

The user-defined replication task identifier or name.

Type: String

Pattern: `.*\S.*`

Required: No

ReplicationTaskSettings

The settings for the replication task.

Type: String

Pattern: `.*\S.*`

Required: No

ResourceIdentifier

A display name for the resource identifier at the end of the EndpointArn response parameter. If you don't specify a ResourceIdentifier value, DMS generates a default identifier value for the end of EndpointArn.

Type: String

Pattern: `.*\S.*`

Required: No

SourceEndpointArn

The ARN of the source endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

TableMappings

The table mappings for the replication task, in JSON format.

Type: String

Pattern: `.*\S.*`

Required: No

TargetEndpointArn

The ARN of the target endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

TaskData

Supplemental information that the task requires to migrate the data for certain source and target endpoints.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon DynamoDB

Amazon DynamoDB objects

- [AwsDynamoDbTableAttributeDefinition](#)
- [AwsDynamoDbTableBillingModeSummary](#)
- [AwsDynamoDbTableDetails](#)
- [AwsDynamoDbTableGlobalSecondaryIndex](#)
- [AwsDynamoDbTableKeySchema](#)
- [AwsDynamoDbTableLocalSecondaryIndex](#)
- [AwsDynamoDbTableProjection](#)
- [AwsDynamoDbTableProvisionedThroughput](#)
- [AwsDynamoDbTableProvisionedThroughputOverride](#)
- [AwsDynamoDbTableReplica](#)
- [AwsDynamoDbTableReplicaGlobalSecondaryIndex](#)
- [AwsDynamoDbTableRestoreSummary](#)
- [AwsDynamoDbTableSseDescription](#)
- [AwsDynamoDbTableStreamSpecification](#)

AwsDynamoDbTableAttributeDefinition

Contains a definition of an attribute for the table.

Contents

AttributeName

The name of the attribute.

Type: String

Pattern: `.*\S.*`

Required: No

AttributeType

The type of the attribute.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsDynamoDbTableBillingModeSummary

Provides information about the billing for read/write capacity on the table.

Contents

BillingMode

The method used to charge for read and write throughput and to manage capacity.

Type: String

Pattern: `.*\S.*`

Required: No

LastUpdateToPayPerRequestDateTime

If the billing mode is `PAY_PER_REQUEST`, indicates when the billing mode was set to that value.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsDynamoDbTableDetails

Provides details about a DynamoDB table.

Contents

AttributeDefinitions

A list of attribute definitions for the table.

Type: Array of [AwsDynamoDbTableAttributeDefinition](#) objects

Required: No

BillingModeSummary

Information about the billing for read/write capacity on the table.

Type: [AwsDynamoDbTableBillingModeSummary](#) object

Required: No

CreationDateTime

Indicates when the table was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

DeletionProtectionEnabled

Indicates whether deletion protection is to be enabled (true) or disabled (false) on the table.

Type: Boolean

Required: No

GlobalSecondaryIndexes

List of global secondary indexes for the table.

Type: Array of [AwsDynamoDbTableGlobalSecondaryIndex](#) objects

Required: No

GlobalTableVersion

The version of global tables being used.

Type: String

Pattern: `.*\S.*`

Required: No

ItemCount

The number of items in the table.

Type: Integer

Required: No

KeySchema

The primary key structure for the table.

Type: Array of [AwsDynamoDbTableKeySchema](#) objects

Required: No

LatestStreamArn

The ARN of the latest stream for the table.

Type: String

Pattern: `.*\S.*`

Required: No

LatestStreamLabel

The label of the latest stream. The label is not a unique identifier.

Type: String

Pattern: `.*\S.*`

Required: No

LocalSecondaryIndexes

The list of local secondary indexes for the table.

Type: Array of [AwsDynamoDbTableLocalSecondaryIndex](#) objects

Required: No

ProvisionedThroughput

Information about the provisioned throughput for the table.

Type: [AwsDynamoDbTableProvisionedThroughput](#) object

Required: No

Replicas

The list of replicas of this table.

Type: Array of [AwsDynamoDbTableReplica](#) objects

Required: No

RestoreSummary

Information about the restore for the table.

Type: [AwsDynamoDbTableRestoreSummary](#) object

Required: No

SseDescription

Information about the server-side encryption for the table.

Type: [AwsDynamoDbTableSseDescription](#) object

Required: No

StreamSpecification

The current DynamoDB Streams configuration for the table.

Type: [AwsDynamoDbTableStreamSpecification](#) object

Required: No

TableId

The identifier of the table.

Type: String

Pattern: `.*\S.*`

Required: No

TableName

The name of the table.

Type: String

Pattern: `.*\S.*`

Required: No

TableSizeBytes

The total size of the table in bytes.

Type: Long

Required: No

TableStatus

The current status of the table. Valid values are as follows:

- ACTIVE
- ARCHIVED
- ARCHIVING
- CREATING
- DELETING
- INACCESSIBLE_ENCRYPTION_CREDENTIALS
- UPDATING

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsDynamoDbTableGlobalSecondaryIndex

Information about a global secondary index for the table.

Contents

Backfilling

Whether the index is currently backfilling.

Type: Boolean

Required: No

IndexArn

The ARN of the index.

Type: String

Pattern: `.*\S.*`

Required: No

IndexName

The name of the index.

Type: String

Pattern: `.*\S.*`

Required: No

IndexSizeBytes

The total size in bytes of the index.

Type: Long

Required: No

IndexStatus

The current status of the index.

- ACTIVE

- CREATING
- DELETING
- UPDATING

Type: String

Pattern: .*\\S.*

Required: No

ItemCount

The number of items in the index.

Type: Integer

Required: No

KeySchema

The key schema for the index.

Type: Array of [AwsDynamoDbTableKeySchema](#) objects

Required: No

Projection

Attributes that are copied from the table into an index.

Type: [AwsDynamoDbTableProjection](#) object

Required: No

ProvisionedThroughput

Information about the provisioned throughput settings for the indexes.

Type: [AwsDynamoDbTableProvisionedThroughput](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsDynamoDbTableKeySchema

A component of the key schema for the DynamoDB table, a global secondary index, or a local secondary index.

Contents

AttributeName

The name of the key schema attribute.

Type: String

Pattern: `.*\S.*`

Required: No

KeyType

The type of key used for the key schema attribute. Valid values are HASH or RANGE.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsDynamoDbTableLocalSecondaryIndex

Information about a local secondary index for a DynamoDB table.

Contents

IndexArn

The ARN of the index.

Type: String

Pattern: `.*\S.*`

Required: No

IndexName

The name of the index.

Type: String

Pattern: `.*\S.*`

Required: No

KeySchema

The complete key schema for the index.

Type: Array of [AwsDynamoDbTableKeySchema](#) objects

Required: No

Projection

Attributes that are copied from the table into the index. These are in addition to the primary key attributes and index key attributes, which are automatically projected.

Type: [AwsDynamoDbTableProjection](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsDynamoDbTableProjection

For global and local secondary indexes, identifies the attributes that are copied from the table into the index.

Contents

NonKeyAttributes

The nonkey attributes that are projected into the index. For each attribute, provide the attribute name.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

ProjectionType

The types of attributes that are projected into the index. Valid values are as follows:

- ALL
- INCLUDE
- KEYS_ONLY

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsDynamoDbTableProvisionedThroughput

Information about the provisioned throughput for the table or for a global secondary index.

Contents

LastDecreaseDateTime

Indicates when the provisioned throughput was last decreased.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

LastIncreaseDateTime

Indicates when the provisioned throughput was last increased.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

NumberOfDecreasesToday

The number of times during the current UTC calendar day that the provisioned throughput was decreased.

Type: Integer

Required: No

ReadCapacityUnits

The maximum number of strongly consistent reads consumed per second before DynamoDB returns a `ThrottlingException`.

Type: Integer

Required: No

WriteCapacityUnits

The maximum number of writes consumed per second before DynamoDB returns a `ThrottlingException`.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsDynamoDbTableProvisionedThroughputOverride

Replica-specific configuration for the provisioned throughput.

Contents

ReadCapacityUnits

The read capacity units for the replica.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsDynamoDbTableReplica

Information about a replica of a DynamoDB table.

Contents

GlobalSecondaryIndexes

List of global secondary indexes for the replica.

Type: Array of [AwsDynamoDbTableReplicaGlobalSecondaryIndex](#) objects

Required: No

KmsMasterKeyId

The identifier of the Amazon KMS key that will be used for Amazon KMS encryption for the replica.

Type: String

Pattern: `.*\S.*`

Required: No

ProvisionedThroughputOverride

Replica-specific configuration for the provisioned throughput.

Type: [AwsDynamoDbTableProvisionedThroughputOverride](#) object

Required: No

RegionName

The name of the Region where the replica is located.

Type: String

Pattern: `.*\S.*`

Required: No

ReplicaStatus

The current status of the replica. Valid values are as follows:

- ACTIVE
- CREATING
- CREATION_FAILED
- DELETING
- UPDATING

Type: String

Pattern: .*\\S.*

Required: No

ReplicaStatusDescription

Detailed information about the replica status.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsDynamoDbTableReplicaGlobalSecondaryIndex

Information about a global secondary index for a DynamoDB table replica.

Contents

IndexName

The name of the index.

Type: String

Pattern: `.*\S.*`

Required: No

ProvisionedThroughputOverride

Replica-specific configuration for the provisioned throughput for the index.

Type: [AwsDynamoDbTableProvisionedThroughputOverride](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsDynamoDbTableRestoreSummary

Information about the restore for the table.

Contents

RestoreDateTime

Indicates the point in time that the table was restored to.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

RestoreInProgress

Whether a restore is currently in progress.

Type: Boolean

Required: No

SourceBackupArn

The ARN of the source backup from which the table was restored.

Type: String

Pattern: .*\\S.*

Required: No

SourceTableArn

The ARN of the source table for the backup.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsDynamoDbTableSseDescription

Information about the server-side encryption for the table.

Contents

InaccessibleEncryptionDateTime

If the key is inaccessible, the date and time when DynamoDB detected that the key was inaccessible.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

KmsMasterKeyArn

The ARN of the Amazon KMS key that is used for the Amazon KMS encryption.

Type: String

Pattern: .*\\S.*

Required: No

SseType

The type of server-side encryption.

Type: String

Pattern: .*\\S.*

Required: No

Status

The status of the server-side encryption.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsDynamoDbTableStreamSpecification

The current DynamoDB Streams configuration for the table.

Contents

StreamEnabled

Indicates whether DynamoDB Streams is enabled on the table.

Type: Boolean

Required: No

StreamViewType

Determines the information that is written to the table.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon EC2

Amazon EC2 objects

- [AwsEc2ClientVpnEndpointAuthenticationOptionsActiveDirectoryDetails](#)
- [AwsEc2ClientVpnEndpointAuthenticationOptionsDetails](#)
- [AwsEc2ClientVpnEndpointAuthenticationOptionsFederatedAuthenticationDetails](#)
- [AwsEc2ClientVpnEndpointAuthenticationOptionsMutualAuthenticationDetails](#)

- [AwsEc2ClientVpnEndpointClientConnectOptionsDetails](#)
- [AwsEc2ClientVpnEndpointClientConnectOptionsStatusDetails](#)
- [AwsEc2ClientVpnEndpointClientLoginBannerOptionsDetails](#)
- [AwsEc2ClientVpnEndpointConnectionLogOptionsDetails](#)
- [AwsEc2ClientVpnEndpointDetails](#)
- [AwsEc2EipDetails](#)
- [AwsEc2InstanceDetails](#)
- [AwsEc2InstanceMetadataOptions](#)
- [AwsEc2InstanceMonitoringDetails](#)
- [AwsEc2InstanceNetworkInterfacesDetails](#)
- [AwsEc2LaunchTemplateDataBlockDeviceMappingSetDetails](#)
- [AwsEc2LaunchTemplateDataBlockDeviceMappingSetEbsDetails](#)
- [AwsEc2LaunchTemplateDataCapacityReservationSpecificationCapacityReservationTargetDetails](#)
- [AwsEc2LaunchTemplateDataCapacityReservationSpecificationDetails](#)
- [AwsEc2LaunchTemplateDataCpuOptionsDetails](#)
- [AwsEc2LaunchTemplateDataCreditSpecificationDetails](#)
- [AwsEc2LaunchTemplateDataDetails](#)
- [AwsEc2LaunchTemplateDataElasticGpuSpecificationSetDetails](#)
- [AwsEc2LaunchTemplateDataElasticInferenceAcceleratorSetDetails](#)
- [AwsEc2LaunchTemplateDataEnclaveOptionsDetails](#)
- [AwsEc2LaunchTemplateDataHibernationOptionsDetails](#)
- [AwsEc2LaunchTemplateDataIamInstanceProfileDetails](#)
- [AwsEc2LaunchTemplateDataInstanceMarketOptionsDetails](#)
- [AwsEc2LaunchTemplateDataInstanceMarketOptionsSpotOptionsDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsAcceleratorCountDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsAcceleratorTotalMemoryMiBDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsBaselineEbsBandwidthMbpsDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsMemoryGiBPerVCpuDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsMemoryMiBDetails](#)

- [AwsEc2LaunchTemplateDataInstanceRequirementsNetworkInterfaceCountDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsTotalLocalStorageGBDetails](#)
- [AwsEc2LaunchTemplateDataInstanceRequirementsVCpuCountDetails](#)
- [AwsEc2LaunchTemplateDataLicenseSetDetails](#)
- [AwsEc2LaunchTemplateDataMaintenanceOptionsDetails](#)
- [AwsEc2LaunchTemplateDataMetadataOptionsDetails](#)
- [AwsEc2LaunchTemplateDataMonitoringDetails](#)
- [AwsEc2LaunchTemplateDataNetworkInterfaceSetDetails](#)
- [AwsEc2LaunchTemplateDataNetworkInterfaceSetIpv4PrefixesDetails](#)
- [AwsEc2LaunchTemplateDataNetworkInterfaceSetIpv6AddressesDetails](#)
- [AwsEc2LaunchTemplateDataNetworkInterfaceSetIpv6PrefixesDetails](#)
- [AwsEc2LaunchTemplateDataNetworkInterfaceSetPrivateIpAddressesDetails](#)
- [AwsEc2LaunchTemplateDataPlacementDetails](#)
- [AwsEc2LaunchTemplateDataPrivateDnsNameOptionsDetails](#)
- [AwsEc2LaunchTemplateDetails](#)
- [AwsEc2NetworkAclAssociation](#)
- [AwsEc2NetworkAclDetails](#)
- [AwsEc2NetworkAclEntry](#)
- [PortRange](#)
- [PortRangeFromTo](#)
- [AwsEc2NetworkInterfaceAttachment](#)
- [AwsEc2NetworkInterfaceDetails](#)
- [AwsEc2NetworkInterfaceIpV6AddressDetail](#)
- [AwsEc2NetworkInterfacePrivateIpAddressDetail](#)
- [AwsEc2NetworkInterfaceSecurityGroup](#)
- [AwsEc2RouteTableDetails](#)
- [RouteSetDetails](#)
- [AssociationSetDetails](#)
- [AssociationStateDetails](#)
- [PropagatingVgwSetDetails](#)

- [AwsEc2SecurityGroupDetails](#)
- [AwsEc2SecurityGroupIpPermission](#)
- [AwsEc2SecurityGroupIpRange](#)
- [AwsEc2SecurityGroupIpv6Range](#)
- [AwsEc2SecurityGroupPrefixListId](#)
- [AwsEc2SecurityGroupUserIdGroupPair](#)
- [AwsEc2SubnetDetails](#)
- [Ipv6CidrBlockAssociation](#)
- [AvailabilityZone](#)
- [AwsEc2TransitGatewayDetails](#)
- [AwsEc2VolumeAttachment](#)
- [AwsEc2VolumeDetails](#)
- [AwsEc2VpcDetails](#)
- [CidrBlockAssociation](#)
- [AwsEc2VpcEndpointServiceDetails](#)
- [AwsEc2VpcEndpointServiceServiceTypeDetails](#)
- [AwsEc2VpcPeeringConnectionDetails](#)
- [VpcInfoCidrBlockSetDetails](#)
- [VpcInfoIpv6CidrBlockSetDetails](#)
- [VpcInfoPeeringOptionsDetails](#)
- [AwsEc2VpcPeeringConnectionStatusDetails](#)
- [AwsEc2VpcPeeringConnectionVpcInfoDetails](#)
- [AwsEc2VpnConnectionDetails](#)
- [AwsEc2VpnConnectionOptionsDetails](#)
- [AwsEc2VpnConnectionOptionsTunnelOptionsDetails](#)
- [AwsEc2VpnConnectionRoutesDetails](#)
- [AwsEc2VpnConnectionVgwTelemetryDetails](#)

AwsEc2ClientVpnEndpointAuthenticationOptionsActiveDirectoryDetails

Provides details about an Active Directory that's used to authenticate an Amazon Client VPN endpoint.

Contents

DirectoryId

The ID of the Active Directory used for authentication.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2ClientVpnEndpointAuthenticationOptionsDetails

Information about the authentication method used by the Client VPN endpoint.

Contents

ActiveDirectory

Information about the Active Directory, if applicable. With Active Directory authentication, clients are authenticated against existing Active Directory groups.

Type: [AwsEc2ClientVpnEndpointAuthenticationOptionsActiveDirectoryDetails](#) object

Required: No

FederatedAuthentication

Information about the IAM SAML identity provider, if applicable.

Type: [AwsEc2ClientVpnEndpointAuthenticationOptionsFederatedAuthenticationDetails](#) object

Required: No

MutualAuthentication

Information about the authentication certificates, if applicable.

Type: [AwsEc2ClientVpnEndpointAuthenticationOptionsMutualAuthenticationDetails](#) object

Required: No

Type

The authentication type used.

Type: String

Pattern: .*S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2ClientVpnEndpointAuthenticationOptionsFederatedAuthenticationDetails

Describes the IAM SAML identity providers used for federated authentication.

Contents

SamlProviderArn

The Amazon Resource Name (ARN) of the IAM SAML identity provider.

Type: String

Pattern: `.*\S.*`

Required: No

SelfServiceSamlProviderArn

The Amazon Resource Name (ARN) of the IAM SAML identity provider for the self-service portal.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2ClientVpnEndpointAuthenticationOptionsMutualAuthenticationDetails

Information about the client certificate used for authentication.

Contents

ClientRootCertificateChain

The Amazon Resource Name (ARN) of the client certificate.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2ClientVpnEndpointClientConnectOptionsDetails

The options for managing connection authorization for new client connections.

Contents

Enabled

Indicates whether client connect options are enabled.

Type: Boolean

Required: No

LambdaFunctionArn

The Amazon Resource Name (ARN) of the Lambda function used for connection authorization.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The status of any updates to the client connect options.

Type: [AwsEc2ClientVpnEndpointClientConnectOptionsStatusDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2ClientVpnEndpointClientConnectOptionsStatusDetails

Describes the status of the Client VPN endpoint attribute.

Contents

Code

The status code.

Type: String

Pattern: `.*\S.*`

Required: No

Message

The status message.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2ClientVpnEndpointClientLoginBannerOptionsDetails

Options for enabling a customizable text banner that will be displayed on Amazon provided clients when a VPN session is established.

Contents

BannerText

Customizable text that will be displayed in a banner on Amazon provided clients when a VPN session is established.

Type: String

Pattern: `.*\S.*`

Required: No

Enabled

Current state of text banner feature.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2ClientVpnEndpointConnectionLogOptionsDetails

Information about the client connection logging options for the Client VPN endpoint.

Contents

CloudwatchLogGroup

The name of the Amazon CloudWatch Logs log group to which connection logging data is published.

Type: String

Pattern: `.*\S.*`

Required: No

CloudwatchLogStream

The name of the Amazon CloudWatch Logs log stream to which connection logging data is published.

Type: String

Pattern: `.*\S.*`

Required: No

Enabled

Indicates whether client connection logging is enabled for the Client VPN endpoint.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsEc2ClientVpnEndpointDetails

Describes an Amazon Client VPN endpoint. A Client VPN endpoint is the resource that you create and configure to enable and manage client VPN sessions. It's the termination point for all client VPN sessions.

Contents

AuthenticationOptions

Information about the authentication method used by the Client VPN endpoint.

Type: Array of [AwsEc2ClientVpnEndpointAuthenticationOptionsDetails](#) objects

Required: No

ClientCidrBlock

The IPv4 address range, in CIDR notation, from which client IP addresses are assigned.

Type: String

Pattern: `.*\S.*`

Required: No

ClientConnectOptions

The options for managing connection authorization for new client connections.

Type: [AwsEc2ClientVpnEndpointClientConnectOptionsDetails](#) object

Required: No

ClientLoginBannerOptions

Options for enabling a customizable text banner that will be displayed on Amazon provided clients when a VPN session is established.

Type: [AwsEc2ClientVpnEndpointClientLoginBannerOptionsDetails](#) object

Required: No

ClientVpnEndpointId

The ID of the Client VPN endpoint.

Type: String

Pattern: .*\\S.*

Required: No

ConnectionLogOptions

Information about the client connection logging options for the Client VPN endpoint.

Type: [AwsEc2ClientVpnEndpointConnectionLogOptionsDetails](#) object

Required: No

Description

A brief description of the endpoint.

Type: String

Pattern: .*\\S.*

Required: No

DnsServer

Information about the DNS servers to be used for DNS resolution.

Type: Array of strings

Pattern: .*\\S.*

Required: No

SecurityGroupIds

The IDs of the security groups for the target network.

Type: Array of strings

Pattern: .*\\S.*

Required: No

SelfServicePortalUrl

The URL of the self-service portal.

Type: String

Pattern: .*\\S.*

Required: No

ServerCertificateArn

The Amazon Resource Name (ARN) of the server certificate.

Type: String

Pattern: .*\\S.*

Required: No

SessionTimeoutHours

The maximum VPN session duration time in hours.

Type: Integer

Required: No

SplitTunnel

Indicates whether split-tunnel is enabled in the Amazon Client VPN endpoint.

Type: Boolean

Required: No

TransportProtocol

The transport protocol used by the Client VPN endpoint.

Type: String

Pattern: .*\\S.*

Required: No

VpcId

The ID of the VPC.

Type: String

Pattern: .*\\S.*

Required: No

VpnPort

The port number for the Client VPN endpoint.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2EipDetails

Information about an Elastic IP address.

Contents

AllocationId

The identifier that Amazon assigns to represent the allocation of the Elastic IP address for use with Amazon VPC.

Type: String

Pattern: `.*\S.*`

Required: No

AssociationId

The identifier that represents the association of the Elastic IP address with an EC2 instance.

Type: String

Pattern: `.*\S.*`

Required: No

Domain

The domain in which to allocate the address.

If the address is for use with EC2 instances in a VPC, then `Domain` is `vpc`. Otherwise, `Domain` is `standard`.

Type: String

Pattern: `.*\S.*`

Required: No

InstanceId

The identifier of the EC2 instance.

Type: String

Pattern: `.*\S.*`

Required: No

NetworkBorderGroup

The name of the location from which the Elastic IP address is advertised.

Type: String

Pattern: `.*\S.*`

Required: No

NetworkInterfaceId

The identifier of the network interface.

Type: String

Pattern: `.*\S.*`

Required: No

NetworkInterfaceOwnerId

The Amazon Web Services account ID of the owner of the network interface.

Type: String

Pattern: `.*\S.*`

Required: No

PrivateIpAddress

The private IP address that is associated with the Elastic IP address.

Type: String

Pattern: `.*\S.*`

Required: No

PublicIp

A public IP address that is associated with the EC2 instance.

Type: String

Pattern: `.*\S.*`

Required: No

PublicIpv4Pool

The identifier of an IP address pool. This parameter allows Amazon EC2 to select an IP address from the address pool.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2InstanceDetails

The details of an Amazon EC2 instance.

Contents

IamInstanceProfileArn

The IAM profile ARN of the instance.

Type: String

Pattern: `.*\S.*`

Required: No

ImageId

The Amazon Machine Image (AMI) ID of the instance.

Type: String

Pattern: `.*\S.*`

Required: No

IpV4Addresses

The IPv4 addresses associated with the instance.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

IpV6Addresses

The IPv6 addresses associated with the instance.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

KeyName

The key name associated with the instance.

Type: String

Pattern: `.*\S.*`

Required: No

LaunchedAt

Indicates when the instance was launched.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

MetadataOptions

Details about the metadata options for the Amazon EC2 instance.

Type: [AwsEc2InstanceMetadataOptions](#) object

Required: No

Monitoring

Describes the type of monitoring that's turned on for an instance.

Type: [AwsEc2InstanceMonitoringDetails](#) object

Required: No

NetworkInterfaces

The identifiers of the network interfaces for the EC2 instance. The details for each network interface are in a corresponding `AwsEc2NetworkInterfacesDetails` object.

Type: Array of [AwsEc2InstanceNetworkInterfacesDetails](#) objects

Required: No

SubnetId

The identifier of the subnet that the instance was launched in.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The instance type of the instance.

Type: String

Pattern: `.*\S.*`

Required: No

VirtualizationType

The virtualization type of the Amazon Machine Image (AMI) required to launch the instance.

Type: String

Pattern: `.*\S.*`

Required: No

VpcId

The identifier of the VPC that the instance was launched in.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2InstanceMetadataOptions

Metadata options that allow you to configure and secure the Amazon EC2 instance.

Contents

HttpEndpoint

Enables or disables the HTTP metadata endpoint on the instance.

Type: String

Pattern: `.*\S.*`

Required: No

HttpProtocolIpv6

Enables or disables the IPv6 endpoint for the instance metadata service.

Type: String

Pattern: `.*\S.*`

Required: No

HttpPutResponseHopLimit

The desired HTTP PUT response hop limit for instance metadata requests. The larger the number, the further instance metadata requests can travel.

Type: Integer

Required: No

HttpTokens

The state of token usage for your instance metadata requests.

Type: String

Pattern: `.*\S.*`

Required: No

InstanceMetadataTags

Specifies whether to allow access to instance tags from the instance metadata.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2InstanceMonitoringDetails

The type of monitoring that's turned on for an Amazon EC2 instance.

Contents

State

Indicates whether detailed monitoring is turned on. Otherwise, basic monitoring is turned on.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2InstanceNetworkInterfacesDetails

Identifies a network interface for the Amazon EC2 instance.

Contents

NetworkInterfaceId

The identifier of the network interface. The details are in a corresponding `AwsEc2NetworkInterfacesDetails` object.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataBlockDeviceMappingSetDetails

Information about a block device mapping for an Amazon Elastic Compute Cloud (Amazon EC2) launch template.

Contents

DeviceName

The device name.

Type: String

Pattern: `.*\S.*`

Required: No

Ebs

Parameters used to automatically set up Amazon EBS volumes when the instance is launched.

Type: [AwsEc2LaunchTemplateDataBlockDeviceMappingSetEbsDetails](#) object

Required: No

NoDevice

Omits the device from the block device mapping when an empty string is specified.

Type: String

Pattern: `.*\S.*`

Required: No

VirtualName

The virtual device name (ephemeralN). Instance store volumes are numbered starting from 0. An instance type with 2 available instance store volumes can specify mappings for `ephemeral0` and `ephemeral1`. The number of available instance store volumes depends on the instance type.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataBlockDeviceMappingSetEbsDetails

Parameters for a block device for an Amazon Elastic Block Store (Amazon EBS) volume in an Amazon EC2 launch template.

Contents

DeleteOnTermination

Indicates whether the EBS volume is deleted on instance termination.

Type: Boolean

Required: No

Encrypted

Indicates whether the EBS volume is encrypted. Encrypted volumes can only be attached to instances that support Amazon EBS encryption. If you're creating a volume from a snapshot, you can't specify an encryption value.

Type: Boolean

Required: No

Iops

The number of I/O operations per second (IOPS).

Type: Integer

Required: No

KmsKeyId

The Amazon Resource Name (ARN) of the symmetric Amazon Key Management Service (Amazon KMS) customer managed key used for encryption.

Type: String

Pattern: `.*\S.*`

Required: No

SnapshotId

The ID of the EBS snapshot.

Type: String

Pattern: .*\\S.*

Required: No

Throughput

The throughput to provision for a gp3 volume, with a maximum of 1,000 MiB/s.

Type: Integer

Required: No

VolumeSize

The size of the volume, in GiBs. You must specify either a snapshot ID or a volume size.

Type: Integer

Required: No

VolumeType

The volume type.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataCapacityReservationSpecificationCapacityReservationTarget

Information about the target Capacity Reservation or Capacity Reservation group in which to run an Amazon EC2 instance.

Contents

CapacityReservationId

The ID of the Capacity Reservation in which to run the instance.

Type: String

Pattern: `.*\S.*`

Required: No

CapacityReservationResourceGroupArn

The Amazon Resource Name (ARN) of the Capacity Reservation resource group in which to run the instance.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataCapacityReservationSpecificationDetails

Specifies the Capacity Reservation targeting option of an Amazon EC2 instance.

Contents

CapacityReservationPreference

Indicates the instance's Capacity Reservation preferences. If equal to open, the instance can run in any open Capacity Reservation that has matching attributes (instance type, platform, Availability Zone). If equal to none, the instance avoids running in a Capacity Reservation even if one is available. The instance runs in On-Demand capacity.

Type: String

Pattern: `.*\S.*`

Required: No

CapacityReservationTarget

Specifies a target Capacity Reservation.

Type:

[AwsEc2LaunchTemplateDataCapacityReservationSpecificationCapacityReservationTargetDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataCpuOptionsDetails

Specifies the CPU options for an Amazon EC2 instance. For more information, see [Optimize CPU options](#) in the *Amazon Elastic Compute Cloud User Guide*.

Contents

CoreCount

The number of CPU cores for the instance.

Type: Integer

Required: No

ThreadsPerCore

The number of threads per CPU core. A value of 1 disables multithreading for the instance, The default value is 2.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataCreditSpecificationDetails

Specifies the credit option for CPU usage of a T2, T3, or T3a Amazon EC2 instance.

Contents

CpuCredits

The credit option for CPU usage of a T instance.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataDetails

The information to include in an Amazon Elastic Compute Cloud (Amazon EC2) launch template.

Contents

BlockDeviceMappingSet

Information about a block device mapping for an Amazon EC2 launch template.

Type: Array of [AwsEc2LaunchTemplateDataBlockDeviceMappingSetDetails](#) objects

Required: No

CapacityReservationSpecification

Specifies an instance's Capacity Reservation targeting option. You can specify only one option at a time.

Type: [AwsEc2LaunchTemplateDataCapacityReservationSpecificationDetails](#) object

Required: No

CpuOptions

Specifies the CPU options for an instance. For more information, see [Optimize CPU options](#) in the *Amazon Elastic Compute Cloud User Guide*.

Type: [AwsEc2LaunchTemplateDataCpuOptionsDetails](#) object

Required: No

CreditSpecification

Specifies the credit option for CPU usage of a T2, T3, or T3a instance.

Type: [AwsEc2LaunchTemplateDataCreditSpecificationDetails](#) object

Required: No

DisableApiStop

Indicates whether to enable the instance for stop protection. For more information, see [Enable stop protection](#) in the *Amazon EC2 User Guide*.

Type: Boolean

Required: No

DisableApiTermination

If you set this parameter to `true`, you can't terminate the instance using the Amazon EC2 console, Amazon CLI, or API. If set to `true`, you can.

Type: Boolean

Required: No

EbsOptimized

Indicates whether the instance is optimized for Amazon EBS I/O.

Type: Boolean

Required: No

ElasticGpuSpecificationSet

Provides details about Elastic Graphics accelerators to associate with the instance.

Type: Array of [AwsEc2LaunchTemplateDataElasticGpuSpecificationSetDetails](#) objects

Required: No

ElasticInferenceAcceleratorSet

The Amazon Elastic Inference accelerator for the instance.

Type: Array of [AwsEc2LaunchTemplateDataElasticInferenceAcceleratorSetDetails](#) objects

Required: No

EnclaveOptions

Indicates whether the Amazon EC2 instance is enabled for Amazon Nitro Enclaves.

Type: [AwsEc2LaunchTemplateDataEnclaveOptionsDetails](#) object

Required: No

HibernationOptions

Specifies whether your Amazon EC2 instance is configured for hibernation.

Type: [AwsEc2LaunchTemplateDataHibernationOptionsDetails](#) object

Required: No

IamInstanceProfile

The name or Amazon Resource Name (ARN) of an IAM instance profile.

Type: [AwsEc2LaunchTemplateDataIamInstanceProfileDetails](#) object

Required: No

ImageId

The ID of the Amazon Machine Image (AMI).

Type: String

Pattern: `.*\S.*`

Required: No

InstanceInitiatedShutdownBehavior

Provides the options for specifying the instance initiated shutdown behavior.

Type: String

Pattern: `.*\S.*`

Required: No

InstanceMarketOptions

Specifies the market (purchasing) option for an instance.

Type: [AwsEc2LaunchTemplateDataInstanceMarketOptionsDetails](#) object

Required: No

InstanceRequirements

The attributes for the instance types. When you specify instance attributes, Amazon EC2 will identify instance types with these attributes. If you specify `InstanceRequirements`, you can't specify `InstanceType`.

Type: [AwsEc2LaunchTemplateDataInstanceRequirementsDetails](#) object

Required: No

InstanceType

The instance type. For more information, see [Instance types](#) in the *Amazon EC2 User Guide*. If you specify InstanceType, you can't specify InstanceRequirements.

Type: String

Pattern: `.*\S.*`

Required: No

KernelId

The ID of the kernel.

Type: String

Pattern: `.*\S.*`

Required: No

KeyName

The name of the key pair that allows users to connect to the instance.

Type: String

Pattern: `.*\S.*`

Required: No

LicenseSet

Specifies a license configuration for an instance.

Type: Array of [AwsEc2LaunchTemplateDataLicenseSetDetails](#) objects

Required: No

MaintenanceOptions

The maintenance options of your instance.

Type: [AwsEc2LaunchTemplateDataMaintenanceOptionsDetails](#) object

Required: No

MetadataOptions

The metadata options for the instance. For more information, see [Instance metadata and user data](#) in the *Amazon EC2 User Guide*.

Type: [AwsEc2LaunchTemplateDataMetadataOptionsDetails](#) object

Required: No

Monitoring

The monitoring for the instance.

Type: [AwsEc2LaunchTemplateDataMonitoringDetails](#) object

Required: No

NetworkInterfaceSet

Specifies the parameters for a network interface that is attached to the instance.

Type: Array of [AwsEc2LaunchTemplateDataNetworkInterfaceSetDetails](#) objects

Required: No

Placement

Specifies the placement of an instance.

Type: [AwsEc2LaunchTemplateDataPlacementDetails](#) object

Required: No

PrivateDnsNameOptions

The options for the instance hostname.

Type: [AwsEc2LaunchTemplateDataPrivateDnsNameOptionsDetails](#) object

Required: No

RamDiskId

The ID of the RAM disk.

Type: String

Pattern: `.*\S.*`

Required: No

SecurityGroupIdSet

One or more security group IDs.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

SecurityGroupSet

One or more security group names. For a nondefault VPC, you must use security group IDs instead. You cannot specify both a security group ID and security name in the same request.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

UserData

The user data to make available to the instance.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataElasticGpuSpecificationSetDetails

Provides details about an Elastic Graphics specification for an Amazon EC2 launch template.

Contents

Type

The type of Elastic Graphics accelerator.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataElasticInferenceAcceleratorSetDetails

Provides details for an Amazon Elastic Inference accelerator.

Contents

Count

The number of Elastic Inference accelerators to attach to the instance.

Type: Integer

Required: No

Type

The type of Elastic Inference accelerator.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataEnclaveOptionsDetails

Indicates whether the instance is enabled for Amazon Nitro Enclaves.

Contents

Enabled

If this parameter is set to `true`, the instance is enabled for Amazon Nitro Enclaves.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataHibernationOptionsDetails

Specifies whether your Amazon EC2 instance is configured for hibernation.

Contents

Configured

If you set this parameter to `true`, the instance is enabled for hibernation.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataIamInstanceProfileDetails

Provides details for an Amazon Identity and Access Management (IAM) instance profile, which is a container for an IAM role for your instance.

Contents

Arn

The Amazon Resource Name (ARN) of the instance profile.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the instance profile.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataInstanceMarketOptionsDetails

Provides details about the market (purchasing) option for an Amazon EC2 instance.

Contents

MarketType

The market type.

Type: String

Pattern: .*S.*

Required: No

SpotOptions

The options for Spot Instances.

Type: [AwsEc2LaunchTemplateDataInstanceMarketOptionsSpotOptionsDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataInstanceMarketOptionsSpotOptionsDetails

Provides details about the market (purchasing) options for Spot Instances.

Contents

BlockDurationMinutes

Deprecated.

Type: Integer

Required: No

InstanceInterruptionBehavior

The behavior when a Spot Instance is interrupted.

Type: String

Pattern: `.*\S.*`

Required: No

MaxPrice

The maximum hourly price you're willing to pay for the Spot Instances.

Type: String

Pattern: `.*\S.*`

Required: No

SpotInstanceType

The Spot Instance request type.

Type: String

Pattern: `.*\S.*`

Required: No

ValidUntil

The end date of the request, in UTC format (YYYY-MM-DDTHH:MM:SSZ), for persistent requests.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataInstanceRequirementsAcceleratorCountDetails

The minimum and maximum number of accelerators (GPUs, FPGAs, or Amazon Inferentia chips) on an Amazon EC2 instance.

Contents

Max

The maximum number of accelerators. If this parameter isn't specified, there's no maximum limit. To exclude accelerator-enabled instance types, set Max to 0.

Type: Integer

Required: No

Min

The minimum number of accelerators. If this parameter isn't specified, there's no minimum limit.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataInstanceRequirementsAcceleratorTotalMemoryMiBDetails

The minimum and maximum amount of memory, in MiB, for the accelerators on an Amazon EC2 instance.

Contents

Max

The maximum amount of memory, in MiB. If this parameter isn't specified, there's no maximum limit.

Type: Integer

Required: No

Min

The minimum amount of memory, in MiB. If 0 is specified, there's no maximum limit.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataInstanceRequirementsBaselineEbsBandwidthMbpsDetails

The minimum and maximum baseline bandwidth to Amazon Elastic Block Store (Amazon EBS), in Mbps. For more information, see [Amazon EBS–optimized instances](#) in the *Amazon EC2 User Guide*.

Contents

Max

The maximum baseline bandwidth, in Mbps. If this parameter is omitted, there's no maximum limit.

Type: Integer

Required: No

Min

The minimum baseline bandwidth, in Mbps. If this parameter is omitted, there's no minimum limit.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataInstanceRequirementsDetails

The attributes for the Amazon EC2 instance types.

Contents

AcceleratorCount

The minimum and maximum number of accelerators (GPUs, FPGAs, or Amazon Inferentia chips) on an instance.

Type: [AwsEc2LaunchTemplateDataInstanceRequirementsAcceleratorCountDetails](#) object

Required: No

AcceleratorManufacturers

Indicates whether instance types must have accelerators by specific manufacturers.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

AcceleratorNames

The accelerators that must be on the instance type.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

AcceleratorTotalMemoryMiB

The minimum and maximum amount of total accelerator memory, in MiB.

Type: [AwsEc2LaunchTemplateDataInstanceRequirementsAcceleratorTotalMemoryMiBDetails](#) object

Required: No

AcceleratorTypes

The accelerator types that must be on the instance type.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

BareMetal

Indicates whether bare metal instance types must be included, excluded, or required.

Type: String

Pattern: `.*\S.*`

Required: No

BaselineEbsBandwidthMbps

The minimum and maximum baseline bandwidth to Amazon EBS, in Mbps. For more information, see [Amazon EBS optimized instances](#) in the *Amazon EC2 User Guide*.

Type: [AwsEc2LaunchTemplateDataInstanceRequirementsBaselineEbsBandwidthMbpsDetails](#) object

Required: No

BurstablePerformance

Indicates whether burstable performance T instance types are included, excluded, or required. For more information, see [Burstable performance instances](#) in the *Amazon EC2 User Guide*.

Type: String

Pattern: `.*\S.*`

Required: No

CpuManufacturers

The CPU manufacturers to include.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

ExcludedInstanceTypes

The instance types to exclude.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

InstanceGenerations

Indicates whether current or previous generation instance types are included.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

LocalStorage

Indicates whether instance types with instance store volumes are included, excluded, or required. For more information, see [Amazon EC2 instance store](#) in the *Amazon EC2 User Guide*.

Type: String

Pattern: `.*\S.*`

Required: No

LocalStorageTypes

The type of local storage that is required.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

MemoryGiBPerVCpu

The minimum and maximum amount of memory per vCPU, in GiB.

Type: [AwsEc2LaunchTemplateDataInstanceRequirementsMemoryGiBPerVCpuDetails](#) object

Required: No

MemoryMiB

The minimum and maximum amount of memory, in MiB.

Type: [AwsEc2LaunchTemplateDataInstanceRequirementsMemoryMiBDetails](#) object

Required: No

NetworkInterfaceCount

The minimum and maximum number of network interfaces.

Type: [AwsEc2LaunchTemplateDataInstanceRequirementsNetworkInterfaceCountDetails](#) object

Required: No

OnDemandMaxPricePercentageOverLowestPrice

The price protection threshold for On-Demand Instances. This is the maximum you'll pay for an On-Demand Instance, expressed as a percentage above the least expensive current generation M, C, or R instance type with your specified attributes. When Amazon EC2 selects instance types with your attributes, it excludes instance types priced above your threshold.

The parameter accepts an integer, which Amazon EC2 interprets as a percentage.

A high value, such as 999999, turns off price protection.

Type: Integer

Required: No

RequireHibernateSupport

Indicates whether instance types must support hibernation for On-Demand Instances.

Type: Boolean

Required: No

SpotMaxPricePercentageOverLowestPrice

The price protection threshold for Spot Instances. This is the maximum you'll pay for a Spot Instance, expressed as a percentage above the least expensive current generation M, C, or R

instance type with your specified attributes. When Amazon EC2 selects instance types with your attributes, it excludes instance types priced above your threshold.

The parameter accepts an integer, which Amazon EC2 interprets as a percentage.

A high value, such as 999999, turns off price protection.

Type: Integer

Required: No

TotalLocalStorageGB

The minimum and maximum amount of total local storage, in GB.

Type: [AwsEc2LaunchTemplateDataInstanceRequirementsTotalLocalStorageGBDetails](#) object

Required: No

VCpuCount

The minimum and maximum number of vCPUs.

Type: [AwsEc2LaunchTemplateDataInstanceRequirementsVCpuCountDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataInstanceRequirementsMemoryGiBPerVCpuDetails

The minimum and maximum amount of memory per vCPU, in GiB.

Contents

Max

The maximum amount of memory per vCPU, in GiB. If this parameter is omitted, there's no maximum limit.

Type: Double

Required: No

Min

The minimum amount of memory per vCPU, in GiB. If this parameter is omitted, there's no maximum limit.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataInstanceRequirementsMemoryMiBDetails

The minimum and maximum amount of memory, in MiB, for an Amazon EC2 instance.

Contents

Max

The maximum amount of memory, in MiB.

Type: Integer

Required: No

Min

The minimum amount of memory, in MiB.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataInstanceRequirementsNetworkInterfaceCountDetails

The minimum and maximum number of network interfaces to be attached to an Amazon EC2 instance.

Contents

Max

The maximum number of network interfaces.

Type: Integer

Required: No

Min

The minimum number of network interfaces.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataInstanceRequirementsTotalLocalStorageGBDetails

The minimum and maximum amount of total local storage, in GB, that an Amazon EC2 instance uses.

Contents

Max

The maximum amount of total local storage, in GB.

Type: Double

Required: No

Min

The minimum amount of total local storage, in GB.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataInstanceRequirementsVCpuCountDetails

The minimum and maximum number of vCPUs for an Amazon EC2 instance.

Contents

Max

The maximum number of vCPUs.

Type: Integer

Required: No

Min

The minimum number of vCPUs.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataLicenseSetDetails

Provides details about the license configuration for an Amazon EC2 instance.

Contents

LicenseConfigurationArn

The Amazon Resource Name (ARN) of the license configuration.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataMaintenanceOptionsDetails

The maintenance options of an Amazon EC2 instance.

Contents

AutoRecovery

Disables the automatic recovery behavior of your instance or sets it to default.

Type: String

Pattern: .*S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataMetadataOptionsDetails

Specifies the metadata options for an Amazon EC2 instance.

Contents

HttpEndpoint

Enables or disables the HTTP metadata endpoint on your instances. If the parameter is not specified, the default state is enabled, and you won't be able to access your instance metadata.

Type: String

Pattern: `.*\S.*`

Required: No

HttpProtocolIpv6

Enables or disables the IPv6 endpoint for the instance metadata service.

Type: String

Pattern: `.*\S.*`

Required: No

HttpPutResponseHopLimit

The desired HTTP PUT response hop limit for instance metadata requests. The larger the number, the further instance metadata requests can travel.

Type: Integer

Required: No

HttpTokens

The state of token usage for your instance metadata requests.

Type: String

Pattern: `.*\S.*`

Required: No

InstanceMetadataTags

When set to `enabled`, this parameter allows access to instance tags from the instance metadata. When set to `disabled`, it turns off access to instance tags from the instance metadata. For more information, see [Work with instance tags in instance metadata](#) in the *Amazon EC2 User Guide*.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataMonitoringDetails

The monitoring for an Amazon EC2 instance.

Contents

Enabled

Enables detailed monitoring when `true` is specified. Otherwise, basic monitoring is enabled. For more information about detailed monitoring, see [Enable or turn off detailed monitoring for your instances](#) in the *Amazon EC2 User Guide*.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataNetworkInterfaceSetDetails

One or more network interfaces to attach to an Amazon EC2 instance. If you specify a network interface, you must specify security groups and subnets as part of the network interface.

Contents

AssociateCarrierIpAddress

Indicates whether to associate a Carrier IP address with eth0 for a new network interface. You use this option when you launch an instance in a Wavelength Zone and want to associate a Carrier IP address with the network interface. For more information, see [Carrier IP address](#) in the *Amazon Wavelength Developer Guide*.

Type: Boolean

Required: No

AssociatePublicIpAddress

Associates a public IPv4 address with eth0 for a new network interface.

Type: Boolean

Required: No

DeleteOnTermination

Indicates whether the network interface is deleted when the instance is terminated.

Type: Boolean

Required: No

Description

A description for the network interface.

Type: String

Pattern: `.*\S.*`

Required: No

DeviceIndex

The device index for the network interface attachment.

Type: Integer

Required: No

Groups

The IDs of one or more security groups.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

InterfaceType

The type of network interface.

Type: String

Pattern: `.*\S.*`

Required: No

Ipv4PrefixCount

The number of IPv4 prefixes to be automatically assigned to the network interface. You cannot use this option if you use the `Ipv4Prefixes` option.

Type: Integer

Required: No

Ipv4Prefixes

One or more IPv4 prefixes to be assigned to the network interface. You cannot use this option if you use the `Ipv4PrefixCount` option.

Type: Array of [AwsEc2LaunchTemplateDataNetworkInterfaceSetIpv4PrefixesDetails](#) objects

Required: No

Ipv6AddressCount

The number of IPv6 addresses to assign to a network interface. Amazon EC2 automatically selects the IPv6 addresses from the subnet range. You can't use this option if you use `Ipv6Addresses`.

Type: Integer

Required: No

Ipv6Addresses

One or more specific IPv6 addresses from the IPv6 CIDR block range of your subnet. You can't use this option if you use `Ipv6AddressCount`.

Type: Array of [AwsEc2LaunchTemplateDataNetworkInterfaceSetIpv6AddressesDetails](#) objects

Required: No

Ipv6PrefixCount

The number of IPv6 prefixes to be automatically assigned to the network interface. You cannot use this option if you use the `Ipv6Prefix` option.

Type: Integer

Required: No

Ipv6Prefixes

One or more IPv6 prefixes to be assigned to the network interface. You cannot use this option if you use the `Ipv6PrefixCount` option.

Type: Array of [AwsEc2LaunchTemplateDataNetworkInterfaceSetIpv6PrefixesDetails](#) objects

Required: No

NetworkCardIndex

The index of the network card. Some instance types support multiple network cards. The primary network interface must be assigned to network card index 0. The default is network card index 0.

Type: Integer

Required: No

NetworkInterfaceId

The ID of the network interface.

Type: String

Pattern: `.*\S.*`

Required: No

PrivateIpAddress

The primary private IPv4 address of the network interface.

Type: String

Pattern: `.*\S.*`

Required: No

PrivateIpAddresses

One or more private IPv4 addresses.

Type: Array of [AwsEc2LaunchTemplateDataNetworkInterfaceSetPrivateIpAddressesDetails](#) objects

Required: No

SecondaryPrivateIpAddressCount

The number of secondary private IPv4 addresses to assign to a network interface.

Type: Integer

Required: No

SubnetId

The ID of the subnet for the network interface.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataNetworkInterfaceSetIpv4PrefixesDetails

Provides details on one or more IPv4 prefixes for a network interface.

Contents

Ipv4Prefix

The IPv4 prefix. For more information, see [Assigning prefixes to Amazon EC2 network interfaces](#) in the *Amazon Elastic Compute Cloud User Guide*.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataNetworkInterfaceSetIpv6AddressesDetails

Specifies an IPv6 address in an Amazon EC2 launch template.

Contents

Ipv6Address

One or more specific IPv6 addresses from the IPv6 CIDR block range of your subnet.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataNetworkInterfaceSetIpv6PrefixesDetails

Provides details on one or more IPv6 prefixes to be assigned to the network interface.

Contents

Ipv6Prefix

The IPv6 prefix.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataNetworkInterfaceSetPrivateIpAddressesDetails

One or more private IPv4 addresses.

Contents

Primary

Indicates whether the private IPv4 address is the primary private IPv4 address. Only one IPv4 address can be designated as primary.

Type: Boolean

Required: No

PrivateIpAddress

The private IPv4 address.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataPlacementDetails

Provides details about the placement of an Amazon EC2 instance.

Contents

Affinity

The affinity setting for an instance on an EC2 Dedicated Host.

Type: String

Pattern: `.*\S.*`

Required: No

AvailabilityZone

The Availability Zone for the instance.

Type: String

Pattern: `.*\S.*`

Required: No

GroupName

The name of the placement group for the instance.

Type: String

Pattern: `.*\S.*`

Required: No

HostId

The ID of the Dedicated Host for the instance.

Type: String

Pattern: `.*\S.*`

Required: No

HostResourceGroupArn

The Amazon Resource Name (ARN) of the host resource group in which to launch the instances.

Type: String

Pattern: `.*\S.*`

Required: No

PartitionNumber

The number of the partition the instance should launch in.

Type: Integer

Required: No

SpreadDomain

Reserved for future use.

Type: String

Pattern: `.*\S.*`

Required: No

Tenancy

The tenancy of the instance (if the instance is running in a VPC). An instance with a tenancy of dedicated runs on single-tenant hardware.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDataPrivateDnsNameOptionsDetails

Describes the options for Amazon EC2 instance hostnames.

Contents

EnableResourceNameDnsAAAARecord

Indicates whether to respond to DNS queries for instance hostnames with DNS AAAA records.

Type: Boolean

Required: No

EnableResourceNameDnsARecord

Indicates whether to respond to DNS queries for instance hostnames with DNS A records.

Type: Boolean

Required: No

HostnameType

The type of hostname for EC2 instances.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2LaunchTemplateDetails

Specifies the properties for creating an Amazon Elastic Compute Cloud (Amazon EC2) launch template.

Contents

DefaultVersionNumber

The default version of the launch template.

Type: Long

Required: No

Id

An ID for the launch template.

Type: String

Pattern: `.*\S.*`

Required: No

LatestVersionNumber

The latest version of the launch template.

Type: Long

Required: No

LaunchTemplateData

The information to include in the launch template.

Type: [AwsEc2LaunchTemplateDataDetails](#) object

Required: No

LaunchTemplateName

A name for the launch template.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2NetworkAclAssociation

An association between the network ACL and a subnet.

Contents

NetworkAclAssociationId

The identifier of the association between the network ACL and the subnet.

Type: String

Pattern: `.*\S.*`

Required: No

NetworkAclId

The identifier of the network ACL.

Type: String

Pattern: `.*\S.*`

Required: No

SubnetId

The identifier of the subnet that is associated with the network ACL.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsEc2NetworkAclDetails

Contains details about an Amazon EC2 network access control list (ACL).

Contents

Associations

Associations between the network ACL and subnets.

Type: Array of [AwsEc2NetworkAclAssociation](#) objects

Required: No

Entries

The set of rules in the network ACL.

Type: Array of [AwsEc2NetworkAclEntry](#) objects

Required: No

IsDefault

Whether this is the default network ACL for the VPC.

Type: Boolean

Required: No

NetworkAclId

The identifier of the network ACL.

Type: String

Pattern: `.*\S.*`

Required: No

OwnerId

The identifier of the Amazon Web Services account that owns the network ACL.

Type: String

Pattern: `.*\S.*`

Required: No

VpcId

The identifier of the VPC for the network ACL.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2NetworkAclEntry

A rule for the network ACL. Each rule allows or denies access based on the IP address, traffic direction, port, and protocol.

Contents

CidrBlock

The IPV4 network range for which to deny or allow access.

Type: String

Pattern: `.*\S.*`

Required: No

Egress

Whether the rule is an egress rule. An egress rule is a rule that applies to traffic that leaves the subnet.

Type: Boolean

Required: No

IcmpTypeCode

The Internet Control Message Protocol (ICMP) type and code for which to deny or allow access.

Type: [IcmpTypeCode](#) object

Required: No

Ipv6CidrBlock

The IPV6 network range for which to deny or allow access.

Type: String

Pattern: `.*\S.*`

Required: No

PortRange

For TCP or UDP protocols, the range of ports that the rule applies to.

Type: [PortRangeFromTo](#) object

Required: No

Protocol

The protocol that the rule applies to. To deny or allow access to all protocols, use the value -1.

Type: String

Pattern: `.*\S.*`

Required: No

RuleAction

Whether the rule is used to allow access or deny access.

Type: String

Pattern: `.*\S.*`

Required: No

RuleNumber

The rule number. The rules are processed in order by their number.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PortRange

A range of ports.

Contents

Begin

The first port in the port range.

Type: Integer

Required: No

End

The last port in the port range.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PortRangeFromTo

A range of ports.

Contents

From

The first port in the port range.

Type: Integer

Required: No

To

The last port in the port range.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2NetworkInterfaceAttachment

Information about the network interface attachment.

Contents

AttachmentId

The identifier of the network interface attachment

Type: String

Pattern: `.*\S.*`

Required: No

AttachTime

Indicates when the attachment initiated.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

DeleteOnTermination

Indicates whether the network interface is deleted when the instance is terminated.

Type: Boolean

Required: No

DeviceIndex

The device index of the network interface attachment on the instance.

Type: Integer

Required: No

InstanceId

The ID of the instance.

Type: String

Pattern: `.*\S.*`

Required: No

InstanceOwnerId

The Amazon Web Services account ID of the owner of the instance.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The attachment state.

Valid values: `attaching` | `attached` | `detaching` | `detached`

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2NetworkInterfaceDetails

Details about the network interface

Contents

Attachment

The network interface attachment.

Type: [AwsEc2NetworkInterfaceAttachment](#) object

Required: No

IpV6Addresses

The IPv6 addresses associated with the network interface.

Type: Array of [AwsEc2NetworkInterfaceIpV6AddressDetail](#) objects

Required: No

NetworkInterfaceId

The ID of the network interface.

Type: String

Pattern: `.*\S.*`

Required: No

PrivateIpAddresses

The private IPv4 addresses associated with the network interface.

Type: Array of [AwsEc2NetworkInterfacePrivateIpAddressDetail](#) objects

Required: No

PublicDnsName

The public DNS name of the network interface.

Type: String

Pattern: `.*\S.*`

Required: No

PublicIp

The address of the Elastic IP address bound to the network interface.

Type: String

Pattern: `.*\S.*`

Required: No

SecurityGroups

Security groups for the network interface.

Type: Array of [AwsEc2NetworkInterfaceSecurityGroup](#) objects

Required: No

SourceDestCheck

Indicates whether traffic to or from the instance is validated.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2NetworkInterfaceIpV6AddressDetail

Provides information about an IPV6 address that is associated with the network interface.

Contents

IpV6Address

The IPV6 address.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2NetworkInterfacePrivateIpAddressDetail

Provides information about a private IPv4 address that is with the network interface.

Contents

PrivateDnsName

The private DNS name for the IP address.

Type: String

Pattern: `.*\S.*`

Required: No

PrivateIpAddress

The IP address.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2NetworkInterfaceSecurityGroup

A security group associated with the network interface.

Contents

GroupId

The ID of the security group.

Type: String

Pattern: `.*\S.*`

Required: No

GroupName

The name of the security group.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2RouteTableDetails

Provides details about a route table for the specified VPC.

Contents

AssociationSet

The associations between a route table and one or more subnets or a gateway.

Type: Array of [AssociationSetDetails](#) objects

Required: No

OwnerId

The ID of the Amazon Web Services account that owns the route table.

Type: String

Pattern: `.*\S.*`

Required: No

PropagatingVgwSet

Describes a virtual private gateway propagating route.

Type: Array of [PropagatingVgwSetDetails](#) objects

Required: No

RouteSet

The routes in the route table.

Type: Array of [RouteSetDetails](#) objects

Required: No

RouteTableId

The ID of the route table.

Type: String

Pattern: `.*\S.*`

Required: No

VpcId

The ID of the virtual private cloud (VPC).

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RouteSetDetails

Provides details about the routes in the route table.

Contents

CarrierGatewayId

The ID of the carrier gateway.

Type: String

Pattern: `.*\S.*`

Required: No

CoreNetworkArn

The Amazon Resource Name (ARN) of the core network.

Type: String

Pattern: `.*\S.*`

Required: No

DestinationCidrBlock

The IPv4 CIDR block used for the destination match.

Type: String

Pattern: `.*\S.*`

Required: No

DestinationIpv6CidrBlock

The IPv6 CIDR block used for the destination match.

Type: String

Pattern: `.*\S.*`

Required: No

DestinationPrefixListId

The prefix of the destination Amazon Web Services service.

Type: String

Pattern: `.*\S.*`

Required: No

EgressOnlyInternetGatewayId

The ID of the egress-only internet gateway.

Type: String

Pattern: `.*\S.*`

Required: No

GatewayId

The ID of a gateway attached to your VPC.

Type: String

Pattern: `.*\S.*`

Required: No

InstanceId

The ID of a NAT instance in your VPC.

Type: String

Pattern: `.*\S.*`

Required: No

InstanceOwnerId

The ID of the Amazon Web Services account that owns the instance.

Type: String

Pattern: `.*\S.*`

Required: No

LocalGatewayId

The ID of the local gateway.

Type: String

Pattern: `.*\S.*`

Required: No

NatGatewayId

The ID of a NAT gateway.

Type: String

Pattern: `.*\S.*`

Required: No

NetworkInterfaceId

The ID of the network interface.

Type: String

Pattern: `.*\S.*`

Required: No

Origin

Describes how the route was created.

Type: String

Pattern: `.*\S.*`

Required: No

State

The state of the route.

Type: String

Pattern: `.*\S.*`

Required: No

TransitGatewayId

The ID of a transit gateway.

Type: String

Pattern: `.*\S.*`

Required: No

VpcPeeringConnectionId

The ID of a VPC peering connection.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssociationSetDetails

The associations between a route table and one or more subnets or a gateway.

Contents

AssociationState

The state of the association between a route table and a subnet or gateway.

Type: [AssociationStateDetails](#) object

Required: No

GatewayId

The ID of the internet gateway or virtual private gateway.

Type: String

Pattern: `.*\S.*`

Required: No

Main

Indicates whether this is the main route table.

Type: Boolean

Required: No

RouteTableAssociationId

The ID of the association.

Type: String

Pattern: `.*\S.*`

Required: No

RouteTableId

The ID of the route table.

Type: String

Pattern: `.*\S.*`

Required: No

SubnetId

The ID of the subnet. A subnet ID is not returned for an implicit association.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssociationStateDetails

Describes the state of an association between a route table and a subnet or gateway.

Contents

State

The state of the association.

Type: String

Pattern: `.*\S.*`

Required: No

StatusMessage

The status message, if applicable.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PropagatingVgwSetDetails

Describes a virtual private gateway propagating route.

Contents

GatewayId

The ID of the virtual private gateway.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2SecurityGroupDetails

Details about an Amazon EC2 security group.

Contents

GroupId

The ID of the security group.

Type: String

Pattern: `.*\S.*`

Required: No

GroupName

The name of the security group.

Type: String

Pattern: `.*\S.*`

Required: No

IpPermissions

The inbound rules associated with the security group.

Type: Array of [AwsEc2SecurityGroupIpPermission](#) objects

Required: No

IpPermissionsEgress

[VPC only] The outbound rules associated with the security group.

Type: Array of [AwsEc2SecurityGroupIpPermission](#) objects

Required: No

OwnerId

The Amazon Web Services account ID of the owner of the security group.

Type: String

Pattern: `.*\S.*`

Required: No

VpcId

[VPC only] The ID of the VPC for the security group.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2SecurityGroupIpPermission

An IP permission for an EC2 security group.

Contents

FromPort

The start of the port range for the TCP and UDP protocols, or an ICMP/ICMPv6 type number.

A value of -1 indicates all ICMP/ICMPv6 types. If you specify all ICMP/ICMPv6 types, you must specify all codes.

Type: Integer

Required: No

IpProtocol

The IP protocol name (`tcp`, `udp`, `icmp`, `icmpv6`) or number.

[VPC only] Use -1 to specify all protocols.

When authorizing security group rules, specifying -1 or a protocol number other than `tcp`, `udp`, `icmp`, or `icmpv6` allows traffic on all ports, regardless of any port range you specify.

For `tcp`, `udp`, and `icmp`, you must specify a port range.

For `icmpv6`, the port range is optional. If you omit the port range, traffic for all types and codes is allowed.

Type: String

Pattern: `.*\S.*`

Required: No

IpRanges

The IPv4 ranges.

Type: Array of [AwsEc2SecurityGroupIpRange](#) objects

Required: No

Ipv6Ranges

The IPv6 ranges.

Type: Array of [AwsEc2SecurityGroupIpv6Range](#) objects

Required: No

PrefixListIds

[VPC only] The prefix list IDs for an Amazon service. With outbound rules, this is the Amazon service to access through a VPC endpoint from instances associated with the security group.

Type: Array of [AwsEc2SecurityGroupPrefixListId](#) objects

Required: No

ToPort

The end of the port range for the TCP and UDP protocols, or an ICMP/ICMPv6 code.

A value of -1 indicates all ICMP/ICMPv6 codes. If you specify all ICMP/ICMPv6 types, you must specify all codes.

Type: Integer

Required: No

UserIdGroupPairs

The security group and Amazon Web Services account ID pairs.

Type: Array of [AwsEc2SecurityGroupUserIdGroupPair](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2SecurityGroupIpRange

A range of IPv4 addresses.

Contents

CidrIp

The IPv4 CIDR range. You can specify either a CIDR range or a source security group, but not both. To specify a single IPv4 address, use the /32 prefix length.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2SecurityGroupIpv6Range

A range of IPv6 addresses.

Contents

CidrIpv6

The IPv6 CIDR range. You can specify either a CIDR range or a source security group, but not both. To specify a single IPv6 address, use the /128 prefix length.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2SecurityGroupPrefixListId

A prefix list ID.

Contents

PrefixListId

The ID of the prefix.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2SecurityGroupUserIdGroupPair

A relationship between a security group and a user.

Contents

GroupId

The ID of the security group.

Type: String

Pattern: `.*\S.*`

Required: No

GroupName

The name of the security group.

Type: String

Pattern: `.*\S.*`

Required: No

PeeringStatus

The status of a VPC peering connection, if applicable.

Type: String

Pattern: `.*\S.*`

Required: No

UserId

The ID of an Amazon Web Services account.

For a referenced security group in another VPC, the account ID of the referenced security group is returned in the response. If the referenced security group is deleted, this value is not returned.

[EC2-Classic] Required when adding or removing rules that reference a security group in another VPC.

Type: String

Pattern: `.*\S.*`

Required: No

VpcId

The ID of the VPC for the referenced security group, if applicable.

Type: String

Pattern: `.*\S.*`

Required: No

VpcPeeringConnectionId

The ID of the VPC peering connection, if applicable.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2SubnetDetails

Contains information about a subnet in Amazon EC2.

Contents

AssignIpv6AddressOnCreation

Whether to assign an IPV6 address to a network interface that is created in this subnet.

Type: Boolean

Required: No

AvailabilityZone

The Availability Zone for the subnet.

Type: String

Pattern: `.*\S.*`

Required: No

AvailabilityZoneId

The identifier of the Availability Zone for the subnet.

Type: String

Pattern: `.*\S.*`

Required: No

AvailableIpAddressCount

The number of available IPV4 addresses in the subnet. Does not include addresses for stopped instances.

Type: Integer

Required: No

CidrBlock

The IPV4 CIDR block that is assigned to the subnet.

Type: String

Pattern: `.*\S.*`

Required: No

DefaultForAz

Whether this subnet is the default subnet for the Availability Zone.

Type: Boolean

Required: No

Ipv6CidrBlockAssociationSet

The IPV6 CIDR blocks that are associated with the subnet.

Type: Array of [Ipv6CidrBlockAssociation](#) objects

Required: No

MapPublicIpOnLaunch

Whether instances in this subnet receive a public IP address.

Type: Boolean

Required: No

OwnerId

The identifier of the Amazon Web Services account that owns the subnet.

Type: String

Pattern: `.*\S.*`

Required: No

State

The current state of the subnet. Valid values are `available` or `pending`.

Type: String

Pattern: `.*\S.*`

Required: No

SubnetArn

The ARN of the subnet.

Type: String

Pattern: `.*\S.*`

Required: No

SubnetId

The identifier of the subnet.

Type: String

Pattern: `.*\S.*`

Required: No

VpcId

The identifier of the VPC that contains the subnet.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Ipv6CidrBlockAssociation

An IPV6 CIDR block association.

Contents

AssociationId

The association ID for the IPv6 CIDR block.

Type: String

Pattern: `.*\S.*`

Required: No

CidrBlockState

Information about the state of the CIDR block. Valid values are as follows:

- `associating`
- `associated`
- `disassociating`
- `disassociated`
- `failed`
- `failing`

Type: String

Pattern: `.*\S.*`

Required: No

Ipv6CidrBlock

The IPv6 CIDR block.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AvailabilityZone

Information about an Availability Zone.

Contents

SubnetId

The ID of the subnet. You can specify one subnet per Availability Zone.

Type: String

Pattern: `.*\S.*`

Required: No

ZoneName

The name of the Availability Zone.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2TransitGatewayDetails

Information about an Amazon Amazon EC2 Transit Gateway that interconnects virtual private clouds (VPCs) and on-premises networks.

Contents

AmazonSideAsn

A private Autonomous System Number (ASN) for the Amazon side of a BGP session.

Type: Integer

Required: No

AssociationDefaultRouteTableId

The ID of the default association route table.

Type: String

Pattern: `.*\S.*`

Required: No

AutoAcceptSharedAttachments

Turn on or turn off automatic acceptance of attachment requests.

Type: String

Pattern: `.*\S.*`

Required: No

DefaultRouteTableAssociation

Turn on or turn off automatic association with the default association route table.

Type: String

Pattern: `.*\S.*`

Required: No

DefaultRouteTablePropagation

Turn on or turn off automatic propagation of routes to the default propagation route table.

Type: String

Pattern: `.*\S.*`

Required: No

Description

The description of the transit gateway.

Type: String

Pattern: `.*\S.*`

Required: No

DnsSupport

Turn on or turn off DNS support.

Type: String

Pattern: `.*\S.*`

Required: No

Id

The ID of the transit gateway.

Type: String

Pattern: `.*\S.*`

Required: No

MulticastSupport

Indicates whether multicast is supported on the transit gateway.

Type: String

Pattern: `.*\S.*`

Required: No

PropagationDefaultRouteTableId

The ID of the default propagation route table.

Type: String

Pattern: `.*\S.*`

Required: No

TransitGatewayCidrBlocks

The transit gateway Classless Inter-Domain Routing (CIDR) blocks.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

VpnEcmpSupport

Turn on or turn off Equal Cost Multipath Protocol (ECMP) support.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2VolumeAttachment

An attachment to an Amazon EC2 volume.

Contents

AttachTime

The datetime when the attachment initiated.

Type: String

Pattern: .*\\S.*

Required: No

DeleteOnTermination

Whether the EBS volume is deleted when the EC2 instance is terminated.

Type: Boolean

Required: No

InstanceId

The identifier of the EC2 instance.

Type: String

Pattern: .*\\S.*

Required: No

Status

The attachment state of the volume. Valid values are as follows:

- attaching
- attached
- busy
- detaching
- detached

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2VolumeDetails

Details about an EC2 volume.

Contents

Attachments

The volume attachments.

Type: Array of [AwsEc2VolumeAttachment](#) objects

Required: No

CreateTime

Indicates when the volume was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

DeviceName

The device name for the volume that is attached to the instance.

Type: String

Pattern: `.*\S.*`

Required: No

Encrypted

Specifies whether the volume is encrypted.

Type: Boolean

Required: No

KmsKeyId

The ARN of the Amazon KMS key that was used to protect the volume encryption key for the volume.

Type: String

Pattern: `.*\S.*`

Required: No

Size

The size of the volume, in GiBs.

Type: Integer

Required: No

SnapshotId

The snapshot from which the volume was created.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The volume state. Valid values are as follows:

- `available`
- `creating`
- `deleted`
- `deleting`
- `error`
- `in-use`

Type: String

Pattern: `.*\S.*`

Required: No

VolumeId

The ID of the volume.

Type: String

Pattern: `.*\S.*`

Required: No

VolumeScanStatus

Indicates whether the volume was scanned or skipped.

Type: String

Pattern: `.*\S.*`

Required: No

VolumeType

The volume type.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2VpcDetails

Details about an EC2 VPC.

Contents

CidrBlockAssociationSet

Information about the IPv4 CIDR blocks associated with the VPC.

Type: Array of [CidrBlockAssociation](#) objects

Required: No

DhcpOptionsId

The identifier of the set of Dynamic Host Configuration Protocol (DHCP) options that are associated with the VPC. If the default options are associated with the VPC, then this is default.

Type: String

Pattern: `.*\S.*`

Required: No

Ipv6CidrBlockAssociationSet

Information about the IPv6 CIDR blocks associated with the VPC.

Type: Array of [Ipv6CidrBlockAssociation](#) objects

Required: No

State

The current state of the VPC. Valid values are available or pending.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

CidrBlockAssociation

An IPv4 CIDR block association.

Contents

AssociationId

The association ID for the IPv4 CIDR block.

Type: String

Pattern: `.*\S.*`

Required: No

CidrBlock

The IPv4 CIDR block.

Type: String

Pattern: `.*\S.*`

Required: No

CidrBlockState

Information about the state of the IPv4 CIDR block.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsEc2VpcEndpointServiceDetails

Contains details about the service configuration for a VPC endpoint service.

Contents

AcceptanceRequired

Whether requests from other Amazon Web Services accounts to create an endpoint to the service must first be accepted.

Type: Boolean

Required: No

AvailabilityZones

The Availability Zones where the service is available.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

BaseEndpointDnsNames

The DNS names for the service.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

GatewayLoadBalancerArns

The ARNs of the Gateway Load Balancers for the service.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

ManagesVpcEndpoints

Whether the service manages its VPC endpoints.

Type: Boolean

Required: No

NetworkLoadBalancerArns

The ARNs of the Network Load Balancers for the service.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

PrivateDnsName

The private DNS name for the service.

Type: String

Pattern: `.*\S.*`

Required: No

ServiceId

The identifier of the service.

Type: String

Pattern: `.*\S.*`

Required: No

ServiceName

The name of the service.

Type: String

Pattern: `.*\S.*`

Required: No

ServiceState

The current state of the service. Valid values are as follows:

- Available
- Deleted
- Deleting
- Failed
- Pending

Type: String

Pattern: `.*\S.*`

Required: No

ServiceType

The types for the service.

Type: Array of [AwsEc2VpcEndpointServiceServiceTypeDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2VpcEndpointServiceServiceTypeDetails

The service type information for a VPC endpoint service.

Contents

ServiceType

The type of service.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2VpcPeeringConnectionDetails

Provides information about a VPC peering connection between two VPCs: a requester VPC that you own and an acceptor VPC with which to create the connection.

Contents

AcceptorVpcInfo

Information about the acceptor VPC.

Type: [AwsEc2VpcPeeringConnectionVpcInfoDetails](#) object

Required: No

ExpirationTime

The time at which an unaccepted VPC peering connection will expire.

Type: String

Pattern: .*\\S.*

Required: No

RequesterVpcInfo

Information about the requester VPC.

Type: [AwsEc2VpcPeeringConnectionVpcInfoDetails](#) object

Required: No

Status

The status of the VPC peering connection.

Type: [AwsEc2VpcPeeringConnectionStatusDetails](#) object

Required: No

VpcPeeringConnectionId

The ID of the VPC peering connection.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

VpcInfoCidrBlockSetDetails

Provides details about the IPv4 CIDR blocks for the VPC.

Contents

CidrBlock

The IPv4 CIDR block for the VPC.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

VpcInfoIpv6CidrBlockSetDetails

Provides details about the IPv6 CIDR blocks for the VPC.

Contents

Ipv6CidrBlock

The IPv6 CIDR block for the VPC.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

VpcInfoPeeringOptionsDetails

Provides information about the VPC peering connection options for the acceptor or requester VPC.

Contents

AllowDnsResolutionFromRemoteVpc

Indicates whether a local VPC can resolve public DNS hostnames to private IP addresses when queried from instances in a peer VPC.

Type: Boolean

Required: No

AllowEgressFromLocalClassicLinkToRemoteVpc

Indicates whether a local ClassicLink connection can communicate with the peer VPC over the VPC peering connection.

Type: Boolean

Required: No

AllowEgressFromLocalVpcToRemoteClassicLink

Indicates whether a local VPC can communicate with a ClassicLink connection in the peer VPC over the VPC peering connection.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2VpcPeeringConnectionStatusDetails

Details about the status of the VPC peering connection.

Contents

Code

The status of the VPC peering connection.

Type: String

Pattern: `.*\S.*`

Required: No

Message

A message that provides more information about the status, if applicable.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2VpcPeeringConnectionVpcInfoDetails

Describes a VPC in a VPC peering connection.

Contents

CidrBlock

The IPv4 CIDR block for the VPC.

Type: String

Pattern: `.*\S.*`

Required: No

CidrBlockSet

Information about the IPv4 CIDR blocks for the VPC.

Type: Array of [VpcInfoCidrBlockSetDetails](#) objects

Required: No

Ipv6CidrBlockSet

The IPv6 CIDR block for the VPC.

Type: Array of [VpcInfoIpv6CidrBlockSetDetails](#) objects

Required: No

OwnerId

The ID of the Amazon Web Services account that owns the VPC.

Type: String

Pattern: `.*\S.*`

Required: No

PeeringOptions

Information about the VPC peering connection options for the acceptor or requester VPC.

Type: [VpcInfoPeeringOptionsDetails](#) object

Required: No

Region

The Amazon Web Services Region in which the VPC is located.

Type: String

Pattern: `.*\S.*`

Required: No

VpcId

The ID of the VPC.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2VpnConnectionDetails

Details about an Amazon EC2 VPN connection.

Contents

Category

The category of the VPN connection. `VPN` indicates an Amazon VPN connection. `VPN-Classic` indicates an Amazon Classic VPN connection.

Type: String

Pattern: `.*\S.*`

Required: No

CustomerGatewayConfiguration

The configuration information for the VPN connection's customer gateway, in the native XML format.

Type: String

Pattern: `.*\S.*`

Required: No

CustomerGatewayId

The identifier of the customer gateway that is at your end of the VPN connection.

Type: String

Pattern: `.*\S.*`

Required: No

Options

The VPN connection options.

Type: [AwsEc2VpnConnectionOptionsDetails](#) object

Required: No

Routes

The static routes that are associated with the VPN connection.

Type: Array of [AwsEc2VpnConnectionRoutesDetails](#) objects

Required: No

State

The current state of the VPN connection. Valid values are as follows:

- available
- deleted
- deleting
- pending

Type: String

Pattern: `.*\S.*`

Required: No

TransitGatewayId

The identifier of the transit gateway that is associated with the VPN connection.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The type of VPN connection.

Type: String

Pattern: `.*\S.*`

Required: No

VgwTelemetry

Information about the VPN tunnel.

Type: Array of [AwsEc2VpnConnectionVgwTelemetryDetails](#) objects

Required: No

VpnConnectionId

The identifier of the VPN connection.

Type: String

Pattern: `.*\S.*`

Required: No

VpnGatewayId

The identifier of the virtual private gateway that is at the Amazon side of the VPN connection.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2VpnConnectionOptionsDetails

VPN connection options.

Contents

StaticRoutesOnly

Whether the VPN connection uses static routes only.

Type: Boolean

Required: No

TunnelOptions

The VPN tunnel options.

Type: Array of [AwsEc2VpnConnectionOptionsTunnelOptionsDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2VpnConnectionOptionsTunnelOptionsDetails

The VPN tunnel options.

Contents

DpdTimeoutSeconds

The number of seconds after which a Dead Peer Detection (DPD) timeout occurs.

Type: Integer

Required: No

IkeVersions

The Internet Key Exchange (IKE) versions that are permitted for the VPN tunnel.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

OutsidelpAddress

The external IP address of the VPN tunnel.

Type: String

Pattern: `.*\S.*`

Required: No

Phase1DhGroupNumbers

The permitted Diffie-Hellman group numbers for the VPN tunnel for phase 1 IKE negotiations.

Type: Array of integers

Required: No

Phase1EncryptionAlgorithms

The permitted encryption algorithms for the VPN tunnel for phase 1 IKE negotiations.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Phase1IntegrityAlgorithms

The permitted integrity algorithms for the VPN tunnel for phase 1 IKE negotiations.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Phase1LifetimeSeconds

The lifetime for phase 1 of the IKE negotiation, in seconds.

Type: Integer

Required: No

Phase2DhGroupNumbers

The permitted Diffie-Hellman group numbers for the VPN tunnel for phase 2 IKE negotiations.

Type: Array of integers

Required: No

Phase2EncryptionAlgorithms

The permitted encryption algorithms for the VPN tunnel for phase 2 IKE negotiations.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Phase2IntegrityAlgorithms

The permitted integrity algorithms for the VPN tunnel for phase 2 IKE negotiations.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Phase2LifetimeSeconds

The lifetime for phase 2 of the IKE negotiation, in seconds.

Type: Integer

Required: No

PreSharedKey

The preshared key to establish initial authentication between the virtual private gateway and the customer gateway.

Type: String

Pattern: `.*\S.*`

Required: No

RekeyFuzzPercentage

The percentage of the rekey window, which is determined by `RekeyMarginTimeSeconds` during which the rekey time is randomly selected.

Type: Integer

Required: No

RekeyMarginTimeSeconds

The margin time, in seconds, before the phase 2 lifetime expires, during which the Amazon side of the VPN connection performs an IKE rekey.

Type: Integer

Required: No

ReplayWindowSize

The number of packets in an IKE replay window.

Type: Integer

Required: No

TunnelInsideCidr

The range of inside IPv4 addresses for the tunnel.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2VpnConnectionRoutesDetails

A static routes associated with the VPN connection.

Contents

DestinationCidrBlock

The CIDR block associated with the local subnet of the customer data center.

Type: String

Pattern: `.*\S.*`

Required: No

State

The current state of the static route.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEc2VpnConnectionVgwTelemetryDetails

Information about the VPN tunnel.

Contents

AcceptedRouteCount

The number of accepted routes.

Type: Integer

Required: No

CertificateArn

The ARN of the VPN tunnel endpoint certificate.

Type: String

Pattern: `.*\S.*`

Required: No

LastStatusChange

The date and time of the last change in status.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

OutsideIpAddress

The Internet-routable IP address of the virtual private gateway's outside interface.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The status of the VPN tunnel. Valid values are DOWN or UP.

Type: String

Pattern: `.*\S.*`

Required: No

StatusMessage

If an error occurs, a description of the error.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon EC2 Auto Scaling

Amazon EC2 Auto Scaling objects

- [AwsAutoScalingAutoScalingGroupAvailabilityZonesListDetails](#)
- [AwsAutoScalingAutoScalingGroupDetails](#)
- [AwsAutoScalingAutoScalingGroupLaunchTemplateLaunchTemplateSpecification](#)
- [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyDetails](#)
- [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyInstancesDistributionDetails](#)
- [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyLaunchTemplateDetails](#)

- [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyLaunchTemplateLaunchTemplateSpecification](#)
- [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyLaunchTemplateOverridesListDetails](#)
- [AwsAutoScalingLaunchConfigurationBlockDeviceMappingsDetails](#)
- [AwsAutoScalingLaunchConfigurationBlockDeviceMappingsEbsDetails](#)
- [AwsAutoScalingLaunchConfigurationDetails](#)
- [AwsAutoScalingLaunchConfigurationInstanceMonitoringDetails](#)
- [AwsAutoScalingLaunchConfigurationMetadataOptions](#)

AwsAutoScalingAutoScalingGroupAvailabilityZonesListDetails

An Availability Zone for the automatic scaling group.

Contents

Value

The name of the Availability Zone.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAutoScalingAutoScalingGroupDetails

Provides details about an auto scaling group.

Contents

AvailabilityZones

The list of Availability Zones for the automatic scaling group.

Type: Array of [AwsAutoScalingAutoScalingGroupAvailabilityZonesListDetails](#) objects

Required: No

CapacityRebalance

Indicates whether capacity rebalancing is enabled.

Type: Boolean

Required: No

CreatedTime

Indicates when the auto scaling group was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

HealthCheckGracePeriod

The amount of time, in seconds, that Amazon EC2 Auto Scaling waits before it checks the health status of an EC2 instance that has come into service.

Type: Integer

Required: No

HealthCheckType

The service to use for the health checks. Valid values are EC2 or ELB.

Type: String

Pattern: .*\\S.*

Required: No

LaunchConfigurationName

The name of the launch configuration.

Type: String

Pattern: .*\\S.*

Required: No

LaunchTemplate

The launch template to use.

Type: [AwsAutoScalingAutoScalingGroupLaunchTemplateLaunchTemplateSpecification](#) object

Required: No

LoadBalancerNames

The list of load balancers associated with the group.

Type: Array of strings

Pattern: .*\\S.*

Required: No

MixedInstancesPolicy

The mixed instances policy for the automatic scaling group.

Type: [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAutoScalingAutoScalingGroupLaunchTemplateLaunchTemplateSpecification

Details about the launch template to use.

Contents

LaunchTemplateId

The identifier of the launch template. You must specify either `LaunchTemplateId` or `LaunchTemplateName`.

Type: String

Pattern: `.*\S.*`

Required: No

LaunchTemplateName

The name of the launch template. You must specify either `LaunchTemplateId` or `LaunchTemplateName`.

Type: String

Pattern: `.*\S.*`

Required: No

Version

Identifies the version of the launch template. You can specify a version identifier, or use the values `$Latest` or `$Default`.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAutoScalingAutoScalingGroupMixedInstancesPolicyDetails

The mixed instances policy for the automatic scaling group.

Contents

InstancesDistribution

The instances distribution. The instances distribution specifies the distribution of On-Demand Instances and Spot Instances, the maximum price to pay for Spot Instances, and how the Auto Scaling group allocates instance types to fulfill On-Demand and Spot capacity.

Type: [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyInstancesDistributionDetails](#) object

Required: No

LaunchTemplate

The launch template to use and the instance types (overrides) to use to provision EC2 instances to fulfill On-Demand and Spot capacities.

Type: [AwsAutoScalingAutoScalingGroupMixedInstancesPolicyLaunchTemplateDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAutoScalingAutoScalingGroupMixedInstancesPolicyInstancesDistributionDetails

Information about the instances distribution.

Contents

OnDemandAllocationStrategy

How to allocate instance types to fulfill On-Demand capacity. The valid value is prioritized.

Type: String

Pattern: `.*\S.*`

Required: No

OnDemandBaseCapacity

The minimum amount of the Auto Scaling group's capacity that must be fulfilled by On-Demand Instances.

Type: Integer

Required: No

OnDemandPercentageAboveBaseCapacity

The percentage of On-Demand Instances and Spot Instances for additional capacity beyond `OnDemandBaseCapacity`.

Type: Integer

Required: No

SpotAllocationStrategy

How to allocate instances across Spot Instance pools. Valid values are as follows:

- `lowest-price`
- `capacity-optimized`
- `capacity-optimized-prioritized`

Type: String

Pattern: `.*\S.*`

Required: No

SpotInstancePools

The number of Spot Instance pools across which to allocate your Spot Instances.

Type: Integer

Required: No

SpotMaxPrice

The maximum price per unit hour that you are willing to pay for a Spot Instance.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAutoScalingAutoScalingGroupMixedInstancesPolicyLaunchTemplateDetails

Describes a launch template and overrides for a mixed instances policy.

Contents

LaunchTemplateSpecification

The launch template to use for a mixed instances policy.

Type:

[AwsAutoScalingAutoScalingGroupMixedInstancesPolicyLaunchTemplateLaunchTemplateSpecification](#)
object

Required: No

Overrides

Property values to use to override the values in the launch template.

Type: Array of

[AwsAutoScalingAutoScalingGroupMixedInstancesPolicyLaunchTemplateOverridesListDetails](#)
objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAutoScalingAutoScalingGroupMixedInstancesPolicyLaunchTemplateLaunchTemplate

Details about the launch template to use for a mixed instances policy.

Contents

LaunchTemplateId

The identifier of the launch template. You must specify either `LaunchTemplateId` or `LaunchTemplateName`.

Type: String

Pattern: `.*\S.*`

Required: No

LaunchTemplateName

The name of the launch template. You must specify either `LaunchTemplateId` or `LaunchTemplateName`.

Type: String

Pattern: `.*\S.*`

Required: No

Version

Identifies the version of the launch template. You can specify a version identifier, or use the values `$Latest` or `$Default`.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAutoScalingAutoScalingGroupMixedInstancesPolicyLaunchTemplateOverridesListD

Property values to use to override the values in the launch template.

Contents

InstanceType

The instance type. For example, `m3.xlarge`.

Type: String

Pattern: `.*\S.*`

Required: No

WeightedCapacity

The number of capacity units provided by the specified instance type in terms of virtual CPUs, memory, storage, throughput, or other relative performance characteristic.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAutoScalingLaunchConfigurationBlockDeviceMappingsDetails

A block device for the instance.

Contents

DeviceName

The device name that is exposed to the EC2 instance. For example, /dev/sdh or xvdh.

Type: String

Pattern: `.*\S.*`

Required: No

Ebs

Parameters that are used to automatically set up Amazon EBS volumes when an instance is launched.

Type: [AwsAutoScalingLaunchConfigurationBlockDeviceMappingsEbsDetails](#) object

Required: No

NoDevice

Whether to suppress the device that is included in the block device mapping of the Amazon Machine Image (AMI).

If NoDevice is true, then you cannot specify Ebs.>

Type: Boolean

Required: No

VirtualName

The name of the virtual device (for example, ephemeral0).

You can provide either VirtualName or Ebs, but not both.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAutoScalingLaunchConfigurationBlockDeviceMappingsEbsDetails

Parameters that are used to automatically set up EBS volumes when an instance is launched.

Contents

DeleteOnTermination

Whether to delete the volume when the instance is terminated.

Type: Boolean

Required: No

Encrypted

Whether to encrypt the volume.

Type: Boolean

Required: No

Iops

The number of input/output (I/O) operations per second (IOPS) to provision for the volume.

Only supported for gp3 or io1 volumes. Required for io1 volumes. Not used with standard, gp2, st1, or sc1 volumes.

Type: Integer

Required: No

SnapshotId

The snapshot ID of the volume to use.

You must specify either VolumeSize or SnapshotId.

Type: String

Pattern: .*\\S.*

Required: No

VolumeSize

The volume size, in GiBs. The following are the supported volumes sizes for each volume type:

- gp2 and gp3: 1-16,384
- io1: 4-16,384
- st1 and sc1: 125-16,384
- standard: 1-1,024

You must specify either `SnapshotId` or `VolumeSize`. If you specify both `SnapshotId` and `VolumeSize`, the volume size must be equal or greater than the size of the snapshot.

Type: Integer

Required: No

VolumeType

The volume type. Valid values are as follows:

- gp2
- gp3
- io1
- sc1
- st1
- standard

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsAutoScalingLaunchConfigurationDetails

Details about a launch configuration.

Contents

AssociatePublicIpAddress

For Auto Scaling groups that run in a VPC, specifies whether to assign a public IP address to the group's instances.

Type: Boolean

Required: No

BlockDeviceMappings

Specifies the block devices for the instance.

Type: Array of [AwsAutoScalingLaunchConfigurationBlockDeviceMappingsDetails](#) objects

Required: No

ClassicLinkVpcId

The identifier of a ClassicLink-enabled VPC that EC2-Classic instances are linked to.

Type: String

Pattern: `.*\S.*`

Required: No

ClassicLinkVpcSecurityGroups

The identifiers of one or more security groups for the VPC that is specified in `ClassicLinkVPCId`.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

CreatedTime

The creation date and time for the launch configuration.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

EbsOptimized

Whether the launch configuration is optimized for Amazon EBS I/O.

Type: Boolean

Required: No

IamInstanceProfile

The name or the ARN of the instance profile associated with the IAM role for the instance. The instance profile contains the IAM role.

Type: String

Pattern: `.*\S.*`

Required: No

ImageId

The identifier of the Amazon Machine Image (AMI) that is used to launch EC2 instances.

Type: String

Pattern: `.*\S.*`

Required: No

InstanceMonitoring

Indicates the type of monitoring for instances in the group.

Type: [AwsAutoScalingLaunchConfigurationInstanceMonitoringDetails](#) object

Required: No

InstanceType

The instance type for the instances.

Type: String

Pattern: `.*\S.*`

Required: No

KernelId

The identifier of the kernel associated with the AMI.

Type: String

Pattern: `.*\S.*`

Required: No

KeyName

The name of the key pair.

Type: String

Pattern: `.*\S.*`

Required: No

LaunchConfigurationName

The name of the launch configuration.

Type: String

Pattern: `.*\S.*`

Required: No

MetadataOptions

The metadata options for the instances.

Type: [AwsAutoScalingLaunchConfigurationMetadataOptions](#) object

Required: No

PlacementTenancy

The tenancy of the instance. An instance with dedicated tenancy runs on isolated, single-tenant hardware and can only be launched into a VPC.

Type: String

Pattern: `.*\S.*`

Required: No

RamdiskId

The identifier of the RAM disk associated with the AMI.

Type: String

Pattern: `.*\S.*`

Required: No

SecurityGroups

The security groups to assign to the instances in the Auto Scaling group.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

SpotPrice

The maximum hourly price to be paid for any Spot Instance that is launched to fulfill the request.

Type: String

Pattern: `.*\S.*`

Required: No

UserData

The user data to make available to the launched EC2 instances. Must be base64-encoded text.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAutoScalingLaunchConfigurationInstanceMonitoringDetails

Information about the type of monitoring for instances in the group.

Contents

Enabled

If set to `true`, then instances in the group launch with detailed monitoring.

If set to `false`, then instances in the group launch with basic monitoring.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsAutoScalingLaunchConfigurationMetadataOptions

The metadata options for the instances.

Contents

HttpEndpoint

Enables or disables the HTTP metadata endpoint on your instances. By default, the metadata endpoint is enabled.

Type: String

Pattern: `.*\S.*`

Required: No

HttpPutResponseHopLimit

The HTTP PUT response hop limit for instance metadata requests. The larger the number, the further instance metadata requests can travel.

Type: Integer

Required: No

HttpTokens

Indicates whether token usage is required or optional for metadata requests. By default, token usage is optional.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

>

Amazon Elastic Container Registry (ECR)

Amazon Elastic Container Registry (ECR) objects

- [AwsEcrContainerImageDetails](#)
- [AwsEcrRepositoryDetails](#)
- [AwsEcrRepositoryImageScanningConfigurationDetails](#)
- [AwsEcrRepositoryLifecyclePolicyDetails](#)

AwsEcrContainerImageDetails

Information about an Amazon ECR image.

Contents

Architecture

The architecture of the image. Valid values are as follows:

- arm64
- i386
- x86_64

Type: String

Pattern: `.*\S.*`

Required: No

ImageDigest

The sha256 digest of the image manifest.

Type: String

Pattern: `.*\S.*`

Required: No

ImagePublishedAt

The date and time when the image was pushed to the repository.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

ImageTags

The list of tags that are associated with the image.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

RegistryId

The Amazon Web Services account identifier that is associated with the registry that the image belongs to.

Type: String

Pattern: `.*\S.*`

Required: No

RepositoryName

The name of the repository that the image belongs to.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcrRepositoryDetails

Provides information about an Amazon Elastic Container Registry repository.

Contents

Arn

The ARN of the repository.

Type: String

Pattern: `.*\S.*`

Required: No

ImageScanningConfiguration

The image scanning configuration for a repository.

Type: [AwsEcrRepositoryImageScanningConfigurationDetails](#) object

Required: No

ImageTagMutability

The tag mutability setting for the repository. Valid values are IMMUTABLE or MUTABLE.

Type: String

Pattern: `.*\S.*`

Required: No

LifecyclePolicy

Information about the lifecycle policy for the repository.

Type: [AwsEcrRepositoryLifecyclePolicyDetails](#) object

Required: No

RepositoryName

The name of the repository.

Type: String

Pattern: `.*\S.*`

Required: No

RepositoryPolicyText

The text of the repository policy.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcrRepositoryImageScanningConfigurationDetails

The image scanning configuration for a repository.

Contents

ScanOnPush

Whether to scan images after they are pushed to a repository.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcrRepositoryLifecyclePolicyDetails

Information about the lifecycle policy for the repository.

Contents

LifecyclePolicyText

The text of the lifecycle policy.

Type: String

Pattern: .*S.*

Required: No

RegistryId

The Amazon Web Services account identifier that is associated with the registry that contains the repository.

Type: String

Pattern: .*S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Elastic Container Service (ECS) objects

Amazon Elastic Container Service (ECS) objects

- [AwsEcsClusterClusterSettingsDetails](#)

- [AwsEcsClusterConfigurationDetails](#)
- [AwsEcsClusterConfigurationExecuteCommandConfigurationDetails](#)
- [AwsEcsClusterConfigurationExecuteCommandConfigurationLogConfigurationDetails](#)
- [AwsEcsClusterDefaultCapacityProviderStrategyDetails](#)
- [AwsEcsClusterDetails](#)
- [AwsEcsContainerDetails](#)
- [AwsEcsServiceCapacityProviderStrategyDetails](#)
- [AwsEcsServiceDeploymentConfigurationDeploymentCircuitBreakerDetails](#)
- [AwsEcsServiceDeploymentConfigurationDetails](#)
- [AwsEcsServiceDeploymentControllerDetails](#)
- [AwsEcsServiceDetails](#)
- [AwsEcsServiceLoadBalancersDetails](#)
- [AwsEcsServiceNetworkConfigurationAwsVpcConfigurationDetails](#)
- [AwsEcsServiceNetworkConfigurationDetails](#)
- [AwsEcsServicePlacementConstraintsDetails](#)
- [AwsEcsServicePlacementStrategiesDetails](#)
- [AwsEcsServiceServiceRegistriesDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsDependsOnDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsEnvironmentDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsEnvironmentFilesDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsExtraHostsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsFirelensConfigurationDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsHealthCheckDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersCapabilitiesDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersDevicesDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersTmpfsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLogConfigurationDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsLogConfigurationSecretOptionsDetails](#)

- [AwsEcsTaskDefinitionContainerDefinitionsMountPointsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsPortMappingsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsRepositoryCredentialsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsResourceRequirementsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsSecretsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsSystemControlsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsUlimitsDetails](#)
- [AwsEcsTaskDefinitionContainerDefinitionsVolumesFromDetails](#)
- [AwsEcsTaskDefinitionDetails](#)
- [AwsEcsTaskDefinitionInferenceAcceleratorsDetails](#)
- [AwsEcsTaskDefinitionPlacementConstraintsDetails](#)
- [AwsEcsTaskDefinitionProxyConfigurationDetails](#)
- [AwsEcsTaskDefinitionProxyConfigurationProxyConfigurationPropertiesDetails](#)
- [AwsEcsTaskDefinitionVolumesDetails](#)
- [AwsEcsTaskDefinitionVolumesDockerVolumeConfigurationDetails](#)
- [AwsEcsTaskDefinitionVolumesEfsVolumeConfigurationAuthorizationConfigDetails](#)
- [AwsEcsTaskDefinitionVolumesEfsVolumeConfigurationDetails](#)
- [AwsEcsTaskDefinitionVolumesHostDetails](#)
- [AwsEcsTaskDetails](#)
- [AwsEcsTaskVolumeDetails](#)
- [AwsEcsTaskVolumeHostDetails](#)
- [AwsMountPoint](#)

AwsEcsClusterClusterSettingsDetails

Indicates whether to enable CloudWatch Container Insights for the ECS cluster.

Contents

Name

The name of the setting. The valid value is `containerInsights`.

Type: String

Pattern: `.*\S.*`

Required: No

Value

The value of the setting. Valid values are `disabled` or `enabled`.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsClusterConfigurationDetails

The run command configuration for the cluster.

Contents

ExecuteCommandConfiguration

Contains the run command configuration for the cluster.

Type: [AwsEcsClusterConfigurationExecuteCommandConfigurationDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsClusterConfigurationExecuteCommandConfigurationDetails

Contains the run command configuration for the cluster.

Contents

KmsKeyId

The identifier of the KMS key that is used to encrypt the data between the local client and the container.

Type: String

Pattern: `.*\S.*`

Required: No

LogConfiguration

The log configuration for the results of the run command actions. Required if Logging is NONE.

Type: [AwsEcsClusterConfigurationExecuteCommandConfigurationLogConfigurationDetails](#) object

Required: No

Logging

The log setting to use for redirecting logs for run command results.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsEcsClusterConfigurationExecuteCommandConfigurationLogConfigurationDetails

The log configuration for the results of the run command actions.

Contents

CloudWatchEncryptionEnabled

Whether to enable encryption on the CloudWatch logs.

Type: Boolean

Required: No

CloudWatchLogGroupName

The name of the CloudWatch log group to send the logs to.

Type: String

Pattern: `.*\S.*`

Required: No

S3BucketName

The name of the S3 bucket to send logs to.

Type: String

Pattern: `.*\S.*`

Required: No

S3EncryptionEnabled

Whether to encrypt the logs that are sent to the S3 bucket.

Type: Boolean

Required: No

S3KeyPrefix

Identifies the folder in the S3 bucket to send the logs to.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsClusterDefaultCapacityProviderStrategyDetails

The default capacity provider strategy for the cluster. The default capacity provider strategy is used when services or tasks are run without a specified launch type or capacity provider strategy.

Contents

Base

The minimum number of tasks to run on the specified capacity provider.

Type: Integer

Required: No

CapacityProvider

The name of the capacity provider.

Type: String

Pattern: `.*\S.*`

Required: No

Weight

The relative percentage of the total number of tasks launched that should use the capacity provider.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsClusterDetails

Provides details about an Amazon ECS cluster.

Contents

ActiveServicesCount

The number of services that are running on the cluster in an ACTIVE state. You can view these services with the Amazon ECS [ListServices](#) API operation.

Type: Integer

Required: No

CapacityProviders

The short name of one or more capacity providers to associate with the cluster.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

ClusterArn

The Amazon Resource Name (ARN) that identifies the cluster.

Type: String

Pattern: `.*\S.*`

Required: No

ClusterName

A name that you use to identify your cluster.

Type: String

Pattern: `.*\S.*`

Required: No

ClusterSettings

The setting to use to create the cluster. Specifically used to configure whether to enable CloudWatch Container Insights for the cluster.

Type: Array of [AwsEcsClusterClusterSettingsDetails](#) objects

Required: No

Configuration

The run command configuration for the cluster.

Type: [AwsEcsClusterConfigurationDetails](#) object

Required: No

DefaultCapacityProviderStrategy

The default capacity provider strategy for the cluster. The default capacity provider strategy is used when services or tasks are run without a specified launch type or capacity provider strategy.

Type: Array of [AwsEcsClusterDefaultCapacityProviderStrategyDetails](#) objects

Required: No

RegisteredContainerInstancesCount

The number of container instances registered into the cluster. This includes container instances in both ACTIVE and DRAINING status.

Type: Integer

Required: No

RunningTasksCount

The number of tasks in the cluster that are in the RUNNING state.

Type: Integer

Required: No

Status

The status of the cluster.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsContainerDetails

Provides information about an Amazon ECS container.

Contents

Image

The image used for the container.

Type: String

Pattern: `.*\S.*`

Required: No

MountPoints

The mount points for data volumes in your container.

Type: Array of [AwsMountPoint](#) objects

Required: No

Name

The name of the container.

Type: String

Pattern: `.*\S.*`

Required: No

Privileged

When this parameter is true, the container is given elevated privileges on the host container instance (similar to the root user).

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsServiceCapacityProviderStrategyDetails

Strategy item for the capacity provider strategy that the service uses.

Contents

Base

The minimum number of tasks to run on the capacity provider. Only one strategy item can specify a value for Base.

The value must be between 0 and 100000.

Type: Integer

Required: No

CapacityProvider

The short name of the capacity provider.

Type: String

Pattern: `.*\S.*`

Required: No

Weight

The relative percentage of the total number of tasks that should use the capacity provider.

If no weight is specified, the default value is 0. At least one capacity provider must have a weight greater than 0.

The value can be between 0 and 1000.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsServiceDeploymentConfigurationDeploymentCircuitBreakerDetails

Determines whether a service deployment fails if a service cannot reach a steady state.

Contents

Enable

Whether to enable the deployment circuit breaker logic for the service.

Type: Boolean

Required: No

Rollback

Whether to roll back the service if a service deployment fails. If rollback is enabled, when a service deployment fails, the service is rolled back to the last deployment that completed successfully.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsServiceDeploymentConfigurationDetails

Optional deployment parameters for the service.

Contents

DeploymentCircuitBreaker

Determines whether a service deployment fails if a service cannot reach a steady state.

Type: [AwsEcsServiceDeploymentConfigurationDeploymentCircuitBreakerDetails](#) object

Required: No

MaximumPercent

For a service that uses the rolling update (ECS) deployment type, the maximum number of tasks in a service that are allowed in the RUNNING or PENDING state during a deployment, and for tasks that use the EC2 launch type, when any container instances are in the DRAINING state. Provided as a percentage of the desired number of tasks. The default value is 200%.

For a service that uses the blue/green (CODE_DEPLOY) or EXTERNAL deployment types, and tasks that use the EC2 launch type, the maximum number of tasks in the service that remain in the RUNNING state while the container instances are in the DRAINING state.

For the Fargate launch type, the maximum percent value is not used.

Type: Integer

Required: No

MinimumHealthyPercent

For a service that uses the rolling update (ECS) deployment type, the minimum number of tasks in a service that must remain in the RUNNING state during a deployment, and while any container instances are in the DRAINING state if the service contains tasks using the EC2 launch type. Expressed as a percentage of the desired number of tasks. The default value is 100%.

For a service that uses the blue/green (CODE_DEPLOY) or EXTERNAL deployment types and tasks that use the EC2 launch type, the minimum number of the tasks in the service that remain in the RUNNING state while the container instances are in the DRAINING state.

For the Fargate launch type, the minimum healthy percent value is not used.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsServiceDeploymentControllerDetails

Information about the deployment controller type that the service uses.

Contents

Type

The rolling update (ECS) deployment type replaces the current running version of the container with the latest version.

The blue/green (CODE_DEPLOY) deployment type uses the blue/green deployment model that is powered by Amazon CodeDeploy. This deployment model a new deployment of a service can be verified before production traffic is sent to it.

The external (EXTERNAL) deployment type allows the use of any third-party deployment controller for full control over the deployment process for an Amazon ECS service.

Valid values: ECS | CODE_DEPLOY | EXTERNAL

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsServiceDetails

Provides details about a service within an ECS cluster.

Contents

CapacityProviderStrategy

The capacity provider strategy that the service uses.

Type: Array of [AwsEcsServiceCapacityProviderStrategyDetails](#) objects

Required: No

Cluster

The ARN of the cluster that hosts the service.

Type: String

Pattern: `.*\S.*`

Required: No

DeploymentConfiguration

Deployment parameters for the service. Includes the number of tasks that run and the order in which to start and stop tasks.

Type: [AwsEcsServiceDeploymentConfigurationDetails](#) object

Required: No

DeploymentController

Contains the deployment controller type that the service uses.

Type: [AwsEcsServiceDeploymentControllerDetails](#) object

Required: No

DesiredCount

The number of instantiations of the task definition to run on the service.

Type: Integer

Required: No

EnableEcsManagedTags

Whether to enable Amazon ECS managed tags for the tasks in the service.

Type: Boolean

Required: No

EnableExecuteCommand

Whether the execute command functionality is enabled for the service.

Type: Boolean

Required: No

HealthCheckGracePeriodSeconds

After a task starts, the amount of time in seconds that the Amazon ECS service scheduler ignores unhealthy Elastic Load Balancing target health checks.

Type: Integer

Required: No

LaunchType

The launch type that the service uses.

Valid values: EC2 | FARGATE | EXTERNAL

Type: String

Pattern: `.*\S.*`

Required: No

LoadBalancers

Information about the load balancers that the service uses.

Type: Array of [AwsEcsServiceLoadBalancersDetails](#) objects

Required: No

Name

The name of the service.

Type: String

Pattern: `.*\S.*`

Required: No

NetworkConfiguration

For tasks that use the `awsvpc` networking mode, the VPC subnet and security group configuration.

Type: [AwsEcsServiceNetworkConfigurationDetails](#) object

Required: No

PlacementConstraints

The placement constraints for the tasks in the service.

Type: Array of [AwsEcsServicePlacementConstraintsDetails](#) objects

Required: No

PlacementStrategies

Information about how tasks for the service are placed.

Type: Array of [AwsEcsServicePlacementStrategiesDetails](#) objects

Required: No

PlatformVersion

The platform version on which to run the service. Only specified for tasks that are hosted on Amazon Fargate. If a platform version is not specified, the LATEST platform version is used by default.

Type: String

Pattern: `.*\S.*`

Required: No

PropagateTags

Indicates whether to propagate the tags from the task definition to the task or from the service to the task. If no value is provided, then tags are not propagated.

Valid values: TASK_DEFINITION | SERVICE

Type: String

Pattern: .*\\S.*

Required: No

Role

The ARN of the IAM role that is associated with the service. The role allows the Amazon ECS container agent to register container instances with an Elastic Load Balancing load balancer.

Type: String

Pattern: .*\\S.*

Required: No

SchedulingStrategy

The scheduling strategy to use for the service.

The REPLICA scheduling strategy places and maintains the desired number of tasks across the cluster. By default, the service scheduler spreads tasks across Availability Zones. Task placement strategies and constraints are used to customize task placement decisions.

The DAEMON scheduling strategy deploys exactly one task on each active container instance that meets all of the task placement constraints that are specified in the cluster. The service scheduler also evaluates the task placement constraints for running tasks and stops tasks that don't meet the placement constraints.

Valid values: REPLICA | DAEMON

Type: String

Pattern: .*\\S.*

Required: No

ServiceArn

The ARN of the service.

Type: String

Pattern: `.*\S.*`

Required: No

ServiceName

The name of the service.

The name can contain up to 255 characters. It can use letters, numbers, underscores, and hyphens.

Type: String

Pattern: `.*\S.*`

Required: No

ServiceRegistries

Information about the service discovery registries to assign to the service.

Type: Array of [AwsEcsServiceServiceRegistriesDetails](#) objects

Required: No

TaskDefinition

The task definition to use for tasks in the service.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsServiceLoadBalancersDetails

Information about a load balancer that the service uses.

Contents

ContainerName

The name of the container to associate with the load balancer.

Type: String

Pattern: `.*\S.*`

Required: No

ContainerPort

The port on the container to associate with the load balancer. This port must correspond to a `containerPort` in the task definition the tasks in the service are using. For tasks that use the EC2 launch type, the container instance they are launched on must allow ingress traffic on the `hostPort` of the port mapping.

Type: Integer

Required: No

LoadBalancerName

The name of the load balancer to associate with the Amazon ECS service or task set.

Only specified when using a Classic Load Balancer. For an Application Load Balancer or a Network Load Balancer, the load balancer name is omitted.

Type: String

Pattern: `.*\S.*`

Required: No

TargetGroupArn

The ARN of the Elastic Load Balancing target group or groups associated with a service or task set.

Only specified when using an Application Load Balancer or a Network Load Balancer. For a Classic Load Balancer, the target group ARN is omitted.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsServiceNetworkConfigurationAwsVpcConfigurationDetails

For tasks that use the awsvpc networking mode, the VPC subnet and security group configuration.

Contents

AssignPublicIp

Whether the task's elastic network interface receives a public IP address. The default value is DISABLED.

Valid values: ENABLED | DISABLED

Type: String

Pattern: `.*\S.*`

Required: No

SecurityGroups

The IDs of the security groups associated with the task or service.

You can provide up to five security groups.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Subnets

The IDs of the subnets associated with the task or service.

You can provide up to 16 subnets.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsServiceNetworkConfigurationDetails

For tasks that use the awsvpc networking mode, the VPC subnet and security group configuration.

Contents

AwsVpcConfiguration

The VPC subnet and security group configuration.

Type: [AwsEcsServiceNetworkConfigurationAwsVpcConfigurationDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsServicePlacementConstraintsDetails

A placement constraint for the tasks in the service.

Contents

Expression

A cluster query language expression to apply to the constraint. You cannot specify an expression if the constraint type is `distinctInstance`.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The type of constraint. Use `distinctInstance` to run each task in a particular group on a different container instance. Use `memberOf` to restrict the selection to a group of valid candidates.

Valid values: `distinctInstance` | `memberOf`

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsServicePlacementStrategiesDetails

A placement strategy that determines how to place the tasks for the service.

Contents

Field

The field to apply the placement strategy against.

For the `spread` placement strategy, valid values are `instanceId` (or `host`, which has the same effect), or any platform or custom attribute that is applied to a container instance, such as `attribute:ecs.availability-zone`.

For the `binpack` placement strategy, valid values are `cpu` and `memory`.

For the `random` placement strategy, this attribute is not used.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The type of placement strategy.

The `random` placement strategy randomly places tasks on available candidates.

The `spread` placement strategy spreads placement across available candidates evenly based on the value of `Field`.

The `binpack` strategy places tasks on available candidates that have the least available amount of the resource that is specified in `Field`.

Valid values: `random | spread | binpack`

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsServiceServiceRegistriesDetails

Information about a service discovery registry to assign to the service.

Contents

ContainerName

The container name value to use for the service discovery service.

If the task definition uses the `bridge` or `host` network mode, you must specify `ContainerName` and `ContainerPort`.

If the task definition uses the `awsvpc` network mode and a type `SRV` DNS record, you must specify either `ContainerName` and `ContainerPort`, or `Port` , but not both.

Type: String

Pattern: `.*\S.*`

Required: No

ContainerPort

The port value to use for the service discovery service.

If the task definition uses the `bridge` or `host` network mode, you must specify `ContainerName` and `ContainerPort`.

If the task definition uses the `awsvpc` network mode and a type `SRV` DNS record, you must specify either `ContainerName` and `ContainerPort`, or `Port` , but not both.

Type: Integer

Required: No

Port

The port value to use for a service discovery service that specifies an `SRV` record. This field can be used if both the `awsvpc` network mode and `SRV` records are used.

Type: Integer

Required: No

RegistryArn

The ARN of the service registry.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsDependsOnDetails

A dependency that is defined for container startup and shutdown.

Contents

Condition

The dependency condition of the dependent container. Indicates the required status of the dependent container before the current container can start. Valid values are as follows:

- COMPLETE
- HEALTHY
- SUCCESS
- START

Type: String

Pattern: `.*\S.*`

Required: No

ContainerName

The name of the dependent container.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsDetails

A container definition that describes a container in the task.

Contents

Command

The command that is passed to the container.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Cpu

The number of CPU units reserved for the container.

Type: Integer

Required: No

DependsOn

The dependencies that are defined for container startup and shutdown.

Type: Array of [AwsEcsTaskDefinitionContainerDefinitionsDependsOnDetails](#) objects

Required: No

DisableNetworking

Whether to disable networking within the container.

Type: Boolean

Required: No

DnsSearchDomains

A list of DNS search domains that are presented to the container.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

DnsServers

A list of DNS servers that are presented to the container.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

DockerLabels

A key-value map of labels to add to the container.

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

DockerSecurityOptions

A list of strings to provide custom labels for SELinux and AppArmor multi-level security systems.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

EntryPoint

The entry point that is passed to the container.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Environment

The environment variables to pass to a container.

Type: Array of [AwsEcsTaskDefinitionContainerDefinitionsEnvironmentDetails](#) objects

Required: No

EnvironmentFiles

A list of files containing the environment variables to pass to a container.

Type: Array of [AwsEcsTaskDefinitionContainerDefinitionsEnvironmentFilesDetails](#) objects

Required: No

Essential

Whether the container is essential. All tasks must have at least one essential container.

Type: Boolean

Required: No

ExtraHosts

A list of hostnames and IP address mappings to append to the `/etc/hosts` file on the container.

Type: Array of [AwsEcsTaskDefinitionContainerDefinitionsExtraHostsDetails](#) objects

Required: No

FirelensConfiguration

The FireLens configuration for the container. Specifies and configures a log router for container logs.

Type: [AwsEcsTaskDefinitionContainerDefinitionsFirelensConfigurationDetails](#) object

Required: No

HealthCheck

The container health check command and associated configuration parameters for the container.

Type: [AwsEcsTaskDefinitionContainerDefinitionsHealthCheckDetails](#) object

Required: No

Hostname

The hostname to use for the container.

Type: String

Pattern: `.*\S.*`

Required: No

Image

The image used to start the container.

Type: String

Pattern: `.*\S.*`

Required: No

Interactive

If set to true, then containerized applications can be deployed that require `stdin` or a `tty` to be allocated.

Type: Boolean

Required: No

Links

A list of links for the container in the form `container_name:alias`. Allows containers to communicate with each other without the need for port mappings.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

LinuxParameters

Linux-specific modifications that are applied to the container, such as Linux kernel capabilities.

Type: [AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersDetails](#) object

Required: No

LogConfiguration

The log configuration specification for the container.

Type: [AwsEcsTaskDefinitionContainerDefinitionsLogConfigurationDetails](#) object

Required: No

Memory

The amount (in MiB) of memory to present to the container. If the container attempts to exceed the memory specified here, the container is shut down. The total amount of memory reserved for all containers within a task must be lower than the task memory value, if one is specified.

Type: Integer

Required: No

MemoryReservation

The soft limit (in MiB) of memory to reserve for the container.

Type: Integer

Required: No

MountPoints

The mount points for the data volumes in the container.

Type: Array of [AwsEcsTaskDefinitionContainerDefinitionsMountPointsDetails](#) objects

Required: No

Name

The name of the container.

Type: String

Pattern: `.*\S.*`

Required: No

PortMappings

The list of port mappings for the container.

Type: Array of [AwsEcsTaskDefinitionContainerDefinitionsPortMappingsDetails](#) objects

Required: No

Privileged

Whether the container is given elevated privileges on the host container instance. The elevated privileges are similar to the root user.

Type: Boolean

Required: No

PseudoTerminal

Whether to allocate a TTY to the container.

Type: Boolean

Required: No

ReadOnlyRootFilesystem

Whether the container is given read-only access to its root file system.

Type: Boolean

Required: No

RepositoryCredentials

The private repository authentication credentials to use.

Type: [AwsEcsTaskDefinitionContainerDefinitionsRepositoryCredentialsDetails](#) object

Required: No

ResourceRequirements

The type and amount of a resource to assign to a container. The only supported resource is a GPU.

Type: Array of [AwsEcsTaskDefinitionContainerDefinitionsResourceRequirementsDetails](#) objects

Required: No

Secrets

The secrets to pass to the container.

Type: Array of [AwsEcsTaskDefinitionContainerDefinitionsSecretsDetails](#) objects

Required: No

StartTimeout

The number of seconds to wait before giving up on resolving dependencies for a container.

Type: Integer

Required: No

StopTimeout

The number of seconds to wait before the container is stopped if it doesn't shut down normally on its own.

Type: Integer

Required: No

SystemControls

A list of namespaced kernel parameters to set in the container.

Type: Array of [AwsEcsTaskDefinitionContainerDefinitionsSystemControlsDetails](#) objects

Required: No

Ulimits

A list of ulimits to set in the container.

Type: Array of [AwsEcsTaskDefinitionContainerDefinitionsUlimitsDetails](#) objects

Required: No

User

The user to use inside the container.

The value can use one of the following formats.

- *user*
- *user : group*
- *uid*
- *uid : gid*
- *user : gid*
- *uid : group*

Type: String

Pattern: `.*\S.*`

Required: No

VolumesFrom

Data volumes to mount from another container.

Type: Array of [AwsEcsTaskDefinitionContainerDefinitionsVolumesFromDetails](#) objects

Required: No

WorkingDirectory

The working directory in which to run commands inside the container.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsEnvironmentDetails

An environment variable to pass to the container.

Contents

Name

The name of the environment variable.

Type: String

Pattern: `.*\S.*`

Required: No

Value

The value of the environment variable.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsEnvironmentFilesDetails

A file that contain environment variables to pass to a container.

Contents

Type

The type of environment file. The valid value is s3.

Type: String

Pattern: `.*\S.*`

Required: No

Value

The ARN of the S3 object that contains the environment variable file.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsExtraHostsDetails

A hostname and IP address mapping to append to the `/etc/hosts` file on the container.

Contents

Hostname

The hostname to use in the `/etc/hosts` entry.

Type: String

Pattern: `.*\S.*`

Required: No

IpAddress

The IP address to use in the `/etc/hosts` entry.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsFirelensConfigurationDetails

The FireLens configuration for the container. The configuration specifies and configures a log router for container logs.

Contents

Options

The options to use to configure the log router.

The valid option keys are as follows:

- `enable-ecs-log-metadata`. The value can be `true` or `false`.
- `config-file-type`. The value can be `s3` or `file`.
- `config-file-value`. The value is either an S3 ARN or a file path.

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

Type

The log router to use. Valid values are `fluentbit` or `fluentd`.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsHealthCheckDetails

The container health check command and associated configuration parameters for the container.

Contents

Command

The command that the container runs to determine whether it is healthy.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Interval

The time period in seconds between each health check execution. The default value is 30 seconds.

Type: Integer

Required: No

Retries

The number of times to retry a failed health check before the container is considered unhealthy. The default value is 3.

Type: Integer

Required: No

StartPeriod

The optional grace period in seconds that allows containers time to bootstrap before failed health checks count towards the maximum number of retries.

Type: Integer

Required: No

Timeout

The time period in seconds to wait for a health check to succeed before it is considered a failure. The default value is 5.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersCapabilitiesDetails

The Linux capabilities for the container that are added to or dropped from the default configuration provided by Docker.

Contents

Add

The Linux capabilities for the container that are added to the default configuration provided by Docker. Valid values are as follows:

Valid values: "ALL" | "AUDIT_CONTROL" | "AUDIT_WRITE" | "BLOCK_SUSPEND" | "CHOWN" | "DAC_OVERRIDE" | "DAC_READ_SEARCH" | "FOWNER" | "FSETID" | "IPC_LOCK" | "IPC_OWNER" | "KILL" | "LEASE" | "LINUX_IMMUTABLE" | "MAC_ADMIN" | "MAC_OVERRIDE" | "MKNOD" | "NET_ADMIN" | "NET_BIND_SERVICE" | "NET_BROADCAST" | "NET_RAW" | "SETFCAP" | "SETGID" | "SETPCAP" | "SETUID" | "SYS_ADMIN" | "SYS_BOOT" | "SYS_CHROOT" | "SYS_MODULE" | "SYS_NICE" | "SYS_PACCT" | "SYS_PTRACE" | "SYS_RAWIO" | "SYS_RESOURCE" | "SYS_TIME" | "SYS_TTY_CONFIG" | "SYSLOG" | "WAKE_ALARM"

Type: Array of strings

Pattern: .*\\S.*

Required: No

Drop

The Linux capabilities for the container that are dropped from the default configuration provided by Docker.

Valid values: "ALL" | "AUDIT_CONTROL" | "AUDIT_WRITE" | "BLOCK_SUSPEND" | "CHOWN" | "DAC_OVERRIDE" | "DAC_READ_SEARCH" | "FOWNER" | "FSETID" | "IPC_LOCK" | "IPC_OWNER" | "KILL" | "LEASE" | "LINUX_IMMUTABLE" | "MAC_ADMIN" | "MAC_OVERRIDE" | "MKNOD" | "NET_ADMIN" | "NET_BIND_SERVICE" | "NET_BROADCAST" | "NET_RAW" | "SETFCAP" | "SETGID" | "SETPCAP" | "SETUID" | "SYS_ADMIN" | "SYS_BOOT" | "SYS_CHROOT" | "SYS_MODULE" | "SYS_NICE" | "SYS_PACCT" | "SYS_PTRACE" | "SYS_RAWIO" | "SYS_RESOURCE" | "SYS_TIME" | "SYS_TTY_CONFIG" | "SYSLOG" | "WAKE_ALARM"

Type: Array of strings

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersDetails

>Linux-specific modifications that are applied to the container, such as Linux kernel capabilities.

Contents

Capabilities

The Linux capabilities for the container that are added to or dropped from the default configuration provided by Docker.

Type: [AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersCapabilitiesDetails](#) object

Required: No

Devices

The host devices to expose to the container.

Type: Array of [AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersDevicesDetails](#) objects

Required: No

InitProcessEnabled

Whether to run an `init` process inside the container that forwards signals and reaps processes.

Type: Boolean

Required: No

MaxSwap

The total amount of swap memory (in MiB) that a container can use.

Type: Integer

Required: No

SharedMemorySize

The value for the size (in MiB) of the `/dev/shm` volume.

Type: Integer

Required: No

Swappiness

Configures the container's memory swappiness behavior. Determines how aggressively pages are swapped. The higher the value, the more aggressive the swappiness. The default is 60.

Type: Integer

Required: No

Tmpfs

The container path, mount options, and size (in MiB) of the tmpfs mount.

Type: Array of [AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersTmpfsDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersDevicesDetails

A host device to expose to the container.

Contents

ContainerPath

The path inside the container at which to expose the host device.

Type: String

Pattern: `.*\S.*`

Required: No

HostPath

The path for the device on the host container instance.

Type: String

Pattern: `.*\S.*`

Required: No

Permissions

The explicit permissions to provide to the container for the device. By default, the container has permissions for read, write, and mknod for the device.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsLinuxParametersTmpfsDetails

The container path, mount options, and size (in MiB) of a tmpfs mount.

Contents

ContainerPath

The absolute file path where the tmpfs volume is to be mounted.

Type: String

Pattern: `.*\S.*`

Required: No

MountOptions

The list of tmpfs volume mount options.

Valid values: `"defaults" | "ro" | "rw" | "suid" | "nosuid" | "dev" | "nodev" | "exec" | "noexec" | "sync" | "async" | "dirsync" | "remount" | "mand" | "nomand" | "atime" | "noatime" | "diratime" | "nodiratime" | "bind" | "rbind" | "unbindable" | "runbindable" | "private" | "rprivate" | "shared" | "rshared" | "slave" | "rslave" | "relatime" | "norelatime" | "strictatime" | "nostrictatime" | "mode" | "uid" | "gid" | "nr_inodes" | "nr_blocks" | "mpol"`

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Size

The maximum size (in MiB) of the tmpfs volume.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsLogConfigurationDetails

The log configuration specification for the container.

Contents

LogDriver

The log driver to use for the container.

Valid values on Amazon Fargate are as follows:

- `awsfirelens`
- `awslogs`
- `splunk`

Valid values on Amazon EC2 are as follows:

- `awsfirelens`
- `awslogs`
- `fluentd`
- `gelf`
- `journald`
- `json-file`
- `logentries`
- `splunk`
- `syslog`

Type: String

Pattern: `.*\S.*`

Required: No

Options

The configuration options to send to the log driver. Requires version 1.19 of the Docker Remote API or greater on your container instance.

Type: String to string map

Key Pattern: .*\\S.*

Value Pattern: .*\\S.*

Required: No

SecretOptions

The secrets to pass to the log configuration.

Type: Array of [AwsEcsTaskDefinitionContainerDefinitionsLogConfigurationSecretOptionsDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsLogConfigurationSecretOptionsDetails

A secret to pass to the log configuration.

Contents

Name

The name of the secret.

Type: String

Pattern: `.*\S.*`

Required: No

ValueFrom

The secret to expose to the container.

The value is either the full ARN of the Secrets Manager secret or the full ARN of the parameter in the Systems Manager Parameter Store.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsMountPointsDetails

A mount point for the data volumes in the container.

Contents

ContainerPath

The path on the container to mount the host volume at.

Type: String

Pattern: `.*\S.*`

Required: No

ReadOnly

Whether the container has read-only access to the volume.

Type: Boolean

Required: No

SourceVolume

The name of the volume to mount. Must match the name of a volume listed in `VolumeDetails` for the task definition.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsPortMappingsDetails

A port mapping for the container.

Contents

ContainerPort

The port number on the container that is bound to the user-specified or automatically assigned host port.

Type: Integer

Required: No

HostPort

The port number on the container instance to reserve for the container.

Type: Integer

Required: No

Protocol

The protocol used for the port mapping. The default is `tcp`.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsRepositoryCredentialsDetails

The private repository authentication credentials to use.

Contents

CredentialsParameter

The ARN of the secret that contains the private repository credentials.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsResourceRequirementsDetails

A resource to assign to a container.

Contents

Type

The type of resource to assign to a container. Valid values are GPU or InferenceAccelerator.

Type: String

Pattern: `.*\S.*`

Required: No

Value

The value for the specified resource type.

For GPU, the value is the number of physical GPUs the Amazon ECS container agent reserves for the container.

For InferenceAccelerator, the value should match the DeviceName attribute of an entry in InferenceAccelerators.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsSecretsDetails

A secret to pass to the container.

Contents

Name

The name of the secret.

Type: String

Pattern: `.*\S.*`

Required: No

ValueFrom

The secret to expose to the container. The value is either the full ARN of the Secrets Manager secret or the full ARN of the parameter in the Systems Manager Parameter Store.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsSystemControlsDetails

A namespaced kernel parameter to set in the container.

Contents

Namespace

The namespaced kernel parameter for which to set a value.

Type: String

Pattern: `.*\S.*`

Required: No

Value

The value of the parameter.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsUlimitsDetails

A ulimit to set in the container.

Contents

HardLimit

The hard limit for the ulimit type.

Type: Integer

Required: No

Name

The type of the ulimit. Valid values are as follows:

- core
- cpu
- data
- fsize
- locks
- memlock
- msgqueue
- nice
- nofile
- nproc
- rss
- rtprio
- rtttime
- sigpending
- stack

Type: String

Pattern: `.*\S.*`

Required: No

SoftLimit

The soft limit for the ulimit type.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionContainerDefinitionsVolumesFromDetails

A data volume to mount from another container.

Contents

ReadOnly

Whether the container has read-only access to the volume.

Type: Boolean

Required: No

SourceContainer

The name of another container within the same task definition from which to mount volumes.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionDetails

Details about a task definition. A task definition describes the container and volume definitions of an Amazon Elastic Container Service task.

Contents

ContainerDefinitions

The container definitions that describe the containers that make up the task.

Type: Array of [AwsEcsTaskDefinitionContainerDefinitionsDetails](#) objects

Required: No

Cpu

The number of CPU units used by the task. Valid values are as follows:

- 256 (.25 vCPU)
- 512 (.5 vCPU)
- 1024 (1 vCPU)
- 2048 (2 vCPU)
- 4096 (4 vCPU)

Type: String

Pattern: `.*\S.*`

Required: No

ExecutionRoleArn

The ARN of the task execution role that grants the container agent permission to make API calls on behalf of the container user.

Type: String

Pattern: `.*\S.*`

Required: No

Family

The name of a family that this task definition is registered to.

Type: String

Pattern: `.*\S.*`

Required: No

InferenceAccelerators

The Elastic Inference accelerators to use for the containers in the task.

Type: Array of [AwsEcsTaskDefinitionInferenceAcceleratorsDetails](#) objects

Required: No

IpcMode

The inter-process communication (IPC) resource namespace to use for the containers in the task. Valid values are as follows:

- host
- none
- task

Type: String

Pattern: `.*\S.*`

Required: No

Memory

The amount (in MiB) of memory used by the task.

For tasks that are hosted on Amazon EC2, you can provide a task-level memory value or a container-level memory value. For tasks that are hosted on Amazon Fargate, you must use one of the [specified values](#) in the Amazon Elastic Container Service Developer Guide , which determines your range of supported values for the Cpu and Memory parameters.

Type: String

Pattern: `.*\S.*`

Required: No

NetworkMode

The Docker networking mode to use for the containers in the task. Valid values are as follows:

- `awsvpc`
- `bridge`
- `host`
- `none`

Type: String

Pattern: `.*\S.*`

Required: No

PidMode

The process namespace to use for the containers in the task. Valid values are `host` or `task`.

Type: String

Pattern: `.*\S.*`

Required: No

PlacementConstraints

The placement constraint objects to use for tasks.

Type: Array of [AwsEcsTaskDefinitionPlacementConstraintsDetails](#) objects

Required: No

ProxyConfiguration

The configuration details for the App Mesh proxy.

Type: [AwsEcsTaskDefinitionProxyConfigurationDetails](#) object

Required: No

RequiresCompatibilities

The task launch types that the task definition was validated against.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Status

The status of the task definition.

Type: String

Pattern: `.*\S.*`

Required: No

TaskRoleArn

The short name or ARN of the IAM role that grants containers in the task permission to call Amazon API operations on your behalf.

Type: String

Pattern: `.*\S.*`

Required: No

Volumes

The data volume definitions for the task.

Type: Array of [AwsEcsTaskDefinitionVolumesDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionInferenceAcceleratorsDetails

An Elastic Inference accelerator to use for the containers in the task.

Contents

DeviceName

The Elastic Inference accelerator device name.

Type: String

Pattern: `.*\S.*`

Required: No

DeviceType

The Elastic Inference accelerator type to use.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionPlacementConstraintsDetails

A placement constraint object to use for tasks.

Contents

Expression

A cluster query language expression to apply to the constraint.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The type of constraint.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionProxyConfigurationDetails

The configuration details for the App Mesh proxy.

Contents

ContainerName

The name of the container that will serve as the App Mesh proxy.

Type: String

Pattern: `.*\S.*`

Required: No

ProxyConfigurationProperties

The set of network configuration parameters to provide to the Container Network Interface (CNI) plugin, specified as key-value pairs.

Type: Array of [AwsEcsTaskDefinitionProxyConfigurationProxyConfigurationPropertiesDetails](#) objects

Required: No

Type

The proxy type.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionProxyConfigurationProxyConfigurationPropertiesDetails

A network configuration parameter to provide to the Container Network Interface (CNI) plugin.

Contents

Name

The name of the property.

Type: String

Pattern: `.*\S.*`

Required: No

Value

The value of the property.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionVolumesDetails

A data volume to mount from another container.

Contents

DockerVolumeConfiguration

Information about a Docker volume.

Type: [AwsEcsTaskDefinitionVolumesDockerVolumeConfigurationDetails](#) object

Required: No

EfsVolumeConfiguration

Information about the Amazon Elastic File System file system that is used for task storage.

Type: [AwsEcsTaskDefinitionVolumesEfsVolumeConfigurationDetails](#) object

Required: No

Host

Information about a bind mount host volume.

Type: [AwsEcsTaskDefinitionVolumesHostDetails](#) object

Required: No

Name

The name of the data volume.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionVolumesDockerVolumeConfigurationDetails

Information about a Docker volume.

Contents

Autoprovision

Whether to create the Docker volume automatically if it does not already exist.

Type: Boolean

Required: No

Driver

The Docker volume driver to use.

Type: String

Pattern: `.*\S.*`

Required: No

DriverOpts

A map of Docker driver-specific options that are passed through.

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

Labels

Custom metadata to add to the Docker volume.

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

Scope

The scope for the Docker volume that determines its lifecycle. Docker volumes that are scoped to a task are provisioned automatically when the task starts and destroyed when the task stops. Docker volumes that are shared persist after the task stops. Valid values are `shared` or `task`.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionVolumesEfsVolumeConfigurationAuthorizationConfigDetails

Contents

AccessPointId

The Amazon EFS access point identifier to use.

Type: String

Pattern: .*\\S.*

Required: No

Iam

Whether to use the Amazon ECS task IAM role defined in a task definition when mounting the Amazon EFS file system.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionVolumesEfsVolumeConfigurationDetails

Information about the Amazon Elastic File System file system that is used for task storage.

Contents

AuthorizationConfig

The authorization configuration details for the Amazon EFS file system.

Type: [AwsEcsTaskDefinitionVolumesEfsVolumeConfigurationAuthorizationConfigDetails](#) object

Required: No

FilesystemId

The Amazon EFS file system identifier to use.

Type: String

Pattern: .*\\S.*

Required: No

RootDirectory

The directory within the Amazon EFS file system to mount as the root directory inside the host.

Type: String

Pattern: .*\\S.*

Required: No

TransitEncryption

Whether to enable encryption for Amazon EFS data in transit between the Amazon ECS host and the Amazon EFS server.

Type: String

Pattern: .*\\S.*

Required: No

TransitEncryptionPort

The port to use when sending encrypted data between the Amazon ECS host and the Amazon EFS server.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDefinitionVolumesHostDetails

Information about a bind mount host volume.

Contents

SourcePath

The path on the host container instance that is presented to the container.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskDetails

Provides details about a task in a cluster.

Contents

ClusterArn

The Amazon Resource Name (ARN) of the cluster that hosts the task.

Type: String

Pattern: `.*\S.*`

Required: No

Containers

The containers that are associated with the task.

Type: Array of [AwsEcsContainerDetails](#) objects

Required: No

CreatedAt

The Unix timestamp for the time when the task was created. More specifically, it's for the time when the task entered the PENDING state.

Type: String

Pattern: `.*\S.*`

Required: No

Group

The name of the task group that's associated with the task.

Type: String

Pattern: `.*\S.*`

Required: No

StartedAt

The Unix timestamp for the time when the task started. More specifically, it's for the time when the task transitioned from the PENDING state to the RUNNING state.

Type: String

Pattern: `.*\S.*`

Required: No

StartedBy

The tag specified when a task is started. If an Amazon ECS service started the task, the `startedBy` parameter contains the deployment ID of that service.

Type: String

Pattern: `.*\S.*`

Required: No

TaskDefinitionArn

The ARN of the task definition that creates the task.

Type: String

Pattern: `.*\S.*`

Required: No

Version

The version counter for the task.

Type: String

Pattern: `.*\S.*`

Required: No

Volumes

Details about the data volume that is used in a task definition.

Type: Array of [AwsEcsTaskVolumeDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskVolumeDetails

Provides information about a data volume that's used in a task definition.

Contents

Host

This parameter is specified when you use bind mount host volumes. The contents of the `host` parameter determine whether your bind mount host volume persists on the host container instance and where it's stored.

Type: [AwsEcsTaskVolumeHostDetails](#) object

Required: No

Name

The name of the volume. Up to 255 letters (uppercase and lowercase), numbers, underscores, and hyphens are allowed. This name is referenced in the `sourceVolume` parameter of container definition `mountPoints`.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEcsTaskVolumeHostDetails

Provides details on a container instance bind mount host volume.

Contents

SourcePath

When the host parameter is used, specify a sourcePath to declare the path on the host container instance that's presented to the container.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsMountPoint

Details for a volume mount point that's used in a container definition.

Contents

ContainerPath

The path on the container to mount the host volume at.

Type: String

Pattern: `.*\S.*`

Required: No

SourceVolume

The name of the volume to mount. Must be a volume name referenced in the name parameter of task definition `volume`.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Elastic File System (EFS) objects

Amazon Elastic File System (EFS) objects

- [AwsEfsAccessPointDetails](#)

- [AwsEfsAccessPointPosixUserDetails](#)
- [AwsEfsAccessPointRootDirectoryCreationInfoDetails](#)
- [AwsEfsAccessPointRootDirectoryDetails](#)

AwsEfsAccessPointDetails

Provides information about an Amazon EFS access point.

Contents

AccessPointId

The ID of the Amazon EFS access point.

Type: String

Pattern: `.*\S.*`

Required: No

Arn

The Amazon Resource Name (ARN) of the Amazon EFS access point.

Type: String

Pattern: `.*\S.*`

Required: No

ClientToken

The opaque string specified in the request to ensure idempotent creation.

Type: String

Pattern: `.*\S.*`

Required: No

FileSystemId

The ID of the Amazon EFS file system that the access point applies to.

Type: String

Pattern: `.*\S.*`

Required: No

PosixUser

The full POSIX identity, including the user ID, group ID, and secondary group IDs on the access point, that is used for all file operations by NFS clients using the access point.

Type: [AwsEfsAccessPointPosixUserDetails](#) object

Required: No

RootDirectory

The directory on the Amazon EFS file system that the access point exposes as the root directory to NFS clients using the access point.

Type: [AwsEfsAccessPointRootDirectoryDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEfsAccessPointPosixUserDetails

Provides details for all file system operations using this Amazon EFS access point.

Contents

Gid

The POSIX group ID used for all file system operations using this access point.

Type: String

Pattern: `.*\S.*`

Required: No

SecondaryGids

Secondary POSIX group IDs used for all file system operations using this access point.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Uid

The POSIX user ID used for all file system operations using this access point.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsEfsAccessPointRootDirectoryCreationInfoDetails

Provides information about the settings that Amazon EFS uses to create the root directory when a client connects to an access point.

Contents

OwnerGid

Specifies the POSIX group ID to apply to the root directory.

Type: String

Pattern: `.*\S.*`

Required: No

OwnerUid

Specifies the POSIX user ID to apply to the root directory.

Type: String

Pattern: `.*\S.*`

Required: No

Permissions

Specifies the POSIX permissions to apply to the root directory, in the format of an octal number representing the file's mode bits.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEfsAccessPointRootDirectoryDetails

Provides information about the directory on the Amazon EFS file system that the access point exposes as the root directory to NFS clients using the access point.

Contents

CreationInfo

Specifies the POSIX IDs and permissions to apply to the access point's root directory.

Type: [AwsEfsAccessPointRootDirectoryCreationInfoDetails](#) object

Required: No

Path

Specifies the path on the Amazon EFS file system to expose as the root directory to NFS clients using the access point to access the EFS file system. A path can have up to four subdirectories. If the specified path does not exist, you are required to provide `CreationInfo`.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Elastic Kubernetes Service (EKS) objects

Amazon Elastic Kubernetes Service objects

- [AwsEksClusterDetails](#)

- [AwsEksClusterLoggingClusterLoggingDetails](#)
- [AwsEksClusterLoggingDetails](#)
- [AwsEksClusterResourcesVpcConfigDetails](#)

AwsEksClusterDetails

Provides details about an Amazon EKS cluster.

Contents

Arn

The ARN of the cluster.

Type: String

Pattern: `.*\S.*`

Required: No

CertificateAuthorityData

The certificate authority data for the cluster.

Type: String

Pattern: `.*\S.*`

Required: No

ClusterStatus

The status of the cluster. Valid values are as follows:

- ACTIVE
- CREATING
- DELETING
- FAILED
- PENDING
- UPDATING

Type: String

Pattern: `.*\S.*`

Required: No

Endpoint

The endpoint for the Amazon EKS API server.

Type: String

Pattern: `.*\S.*`

Required: No

Logging

The logging configuration for the cluster.

Type: [AwsEksClusterLoggingDetails](#) object

Required: No

Name

The name of the cluster.

Type: String

Pattern: `.*\S.*`

Required: No

ResourcesVpcConfig

The VPC configuration used by the cluster control plane.

Type: [AwsEksClusterResourcesVpcConfigDetails](#) object

Required: No

RoleArn

The ARN of the IAM role that provides permissions for the Amazon EKS control plane to make calls to Amazon API operations on your behalf.

Type: String

Pattern: `.*\S.*`

Required: No

Version

The Amazon EKS server version for the cluster.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEksClusterLoggingClusterLoggingDetails

Details for a cluster logging configuration.

Contents

Enabled

Whether the logging types that are listed in `Types` are enabled.

Type: Boolean

Required: No

Types

A list of logging types. Valid values are as follows:

- `api`
- `audit`
- `authenticator`
- `controllerManager`
- `scheduler`

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEksClusterLoggingDetails

The logging configuration for an Amazon EKS cluster.

Contents

ClusterLogging

Cluster logging configurations.

Type: Array of [AwsEksClusterLoggingClusterLoggingDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEksClusterResourcesVpcConfigDetails

Information about the VPC configuration used by the cluster control plane.

Contents

EndpointPublicAccess

Indicates whether the Amazon EKS public API server endpoint is turned on. If the Amazon EKS public API server endpoint is turned off, your cluster's Kubernetes API server can only receive requests that originate from within the cluster VPC.

Type: Boolean

Required: No

SecurityGroupIds

The security groups that are associated with the cross-account elastic network interfaces that are used to allow communication between your nodes and the Amazon EKS control plane.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

SubnetIds

The subnets that are associated with the cluster.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Elastic Beanstalk

Amazon Elastic Beanstalk objects

- [AwsElasticBeanstalkEnvironmentDetails](#)
- [AwsElasticBeanstalkEnvironmentEnvironmentLink](#)
- [AwsElasticBeanstalkEnvironmentOptionSetting](#)
- [AwsElasticBeanstalkEnvironmentTier](#)

AwsElasticBeanstalkEnvironmentDetails

Contains details about an Elastic Beanstalk environment.

Contents

ApplicationName

The name of the application that is associated with the environment.

Type: String

Pattern: `.*\S.*`

Required: No

Cname

The URL to the CNAME for this environment.

Type: String

Pattern: `.*\S.*`

Required: No

DateCreated

The creation date for this environment.

Type: String

Pattern: `.*\S.*`

Required: No

DateUpdated

The date when this environment was last modified.

Type: String

Pattern: `.*\S.*`

Required: No

Description

A description of the environment.

Type: String

Pattern: `.*\S.*`

Required: No

EndpointUrl

For load-balanced, autoscaling environments, the URL to the load balancer. For single-instance environments, the IP address of the instance.

Type: String

Pattern: `.*\S.*`

Required: No

EnvironmentArn

The ARN of the environment.

Type: String

Pattern: `.*\S.*`

Required: No

EnvironmentId

The identifier of the environment.

Type: String

Pattern: `.*\S.*`

Required: No

EnvironmentLinks

Links to other environments in the same group.

Type: Array of [AwsElasticBeanstalkEnvironmentEnvironmentLink](#) objects

Required: No

EnvironmentName

The name of the environment.

Type: String

Pattern: `.*\S.*`

Required: No

OptionSettings

The configuration setting for the environment.

Type: Array of [AwsElasticBeanstalkEnvironmentOptionSetting](#) objects

Required: No

PlatformArn

The ARN of the platform version for the environment.

Type: String

Pattern: `.*\S.*`

Required: No

SolutionStackName

The name of the solution stack that is deployed with the environment.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The current operational status of the environment. Valid values are as follows:

- `Aborting`
- `Launching`
- `LinkingFrom`

- LinkingTo
- Ready
- Terminated
- Terminating
- Updating

Type: String

Pattern: `.*\S.*`

Required: No

Tier

The tier of the environment.

Type: [AwsElasticBeanstalkEnvironmentTier](#) object

Required: No

VersionLabel

The application version of the environment.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElasticBeanstalkEnvironmentEnvironmentLink

Contains information about a link to another environment that is in the same group.

Contents

EnvironmentName

The name of the linked environment.

Type: String

Pattern: `.*\S.*`

Required: No

LinkName

The name of the environment link.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElasticBeanstalkEnvironmentOptionSetting

A configuration option setting for the environment.

Contents

Namespace

The type of resource that the configuration option is associated with.

Type: String

Pattern: `.*\S.*`

Required: No

OptionName

The name of the option.

Type: String

Pattern: `.*\S.*`

Required: No

ResourceName

The name of the resource.

Type: String

Pattern: `.*\S.*`

Required: No

Value

The value of the configuration setting.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElasticBeanstalkEnvironmentTier

Contains information about the tier of the environment.

Contents

Name

The name of the environment tier. Valid values are `WebServer` or `Worker`.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The type of environment tier. Valid values are `Standard` or `SQS/HTTP`.

Type: String

Pattern: `.*\S.*`

Required: No

Version

The version of the environment tier.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

Amazon ElasticSearch objects

ElasticSearch objects

- [AwsElasticsearchDomainDetails](#)
- [AwsElasticsearchDomainDomainEndpointOptions](#)
- [AwsElasticsearchDomainElasticsearchClusterConfigDetails](#)
- [AwsElasticsearchDomainElasticsearchClusterConfigZoneAwarenessConfigDetails](#)
- [AwsElasticsearchDomainEncryptionAtRestOptions](#)
- [AwsElasticsearchDomainLogPublishingOptions](#)
- [AwsElasticsearchDomainLogPublishingOptionsLogConfig](#)
- [AwsElasticsearchDomainNodeToNodeEncryptionOptions](#)
- [AwsElasticsearchDomainServiceSoftwareOptions](#)
- [AwsElasticsearchDomainVPCOptions](#)

AwsElasticsearchDomainDetails

Information about an Elasticsearch domain.

Contents

AccessPolicies

IAM policy document specifying the access policies for the new Elasticsearch domain.

Type: String

Pattern: `.*\S.*`

Required: No

DomainEndpointOptions

Additional options for the domain endpoint.

Type: [AwsElasticsearchDomainDomainEndpointOptions](#) object

Required: No

DomainId

Unique identifier for an Elasticsearch domain.

Type: String

Pattern: `.*\S.*`

Required: No

DomainName

Name of an Elasticsearch domain.

Domain names are unique across all domains owned by the same account within an Amazon Region.

Domain names must start with a lowercase letter and must be between 3 and 28 characters.

Valid characters are a-z (lowercase only), 0-9, and – (hyphen).

Type: String

Pattern: `.*\S.*`

Required: No

ElasticsearchClusterConfig

Information about an OpenSearch cluster configuration.

Type: [AwsElasticsearchDomainElasticsearchClusterConfigDetails](#) object

Required: No

ElasticsearchVersion

OpenSearch version.

Type: String

Pattern: `.*\S.*`

Required: No

EncryptionAtRestOptions

Details about the configuration for encryption at rest.

Type: [AwsElasticsearchDomainEncryptionAtRestOptions](#) object

Required: No

Endpoint

Domain-specific endpoint used to submit index, search, and data upload requests to an Elasticsearch domain.

The endpoint is a service URL.

Type: String

Pattern: `.*\S.*`

Required: No

Endpoints

The key-value pair that exists if the Elasticsearch domain uses VPC endpoints.

Type: String to string map

Key Pattern: .*\\S.*

Value Pattern: .*\\S.*

Required: No

LogPublishingOptions

Configures the CloudWatch Logs to publish for the Elasticsearch domain.

Type: [AwsElasticsearchDomainLogPublishingOptions](#) object

Required: No

NodeToNodeEncryptionOptions

Details about the configuration for node-to-node encryption.

Type: [AwsElasticsearchDomainNodeToNodeEncryptionOptions](#) object

Required: No

ServiceSoftwareOptions

Information about the status of a domain relative to the latest service software.

Type: [AwsElasticsearchDomainServiceSoftwareOptions](#) object

Required: No

VPCOptions

Information that OpenSearch derives based on VPCOptions for the domain.

Type: [AwsElasticsearchDomainVPCOptions](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElasticsearchDomainDomainEndpointOptions

Additional options for the domain endpoint, such as whether to require HTTPS for all traffic.

Contents

EnforceHTTPS

Whether to require that all traffic to the domain arrive over HTTPS.

Type: Boolean

Required: No

TLSSecurityPolicy

The TLS security policy to apply to the HTTPS endpoint of the OpenSearch domain.

Valid values:

- `Policy-Min-TLS-1-0-2019-07`, which supports TLSv1.0 and higher
- `Policy-Min-TLS-1-2-2019-07`, which only supports TLSv1.2

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElasticsearchDomainElasticsearchClusterConfigDetails

details about the configuration of an OpenSearch cluster.

Contents

DedicatedMasterCount

The number of instances to use for the master node. If this attribute is specified, then `DedicatedMasterEnabled` must be `true`.

Type: Integer

Required: No

DedicatedMasterEnabled

Whether to use a dedicated master node for the Elasticsearch domain. A dedicated master node performs cluster management tasks, but doesn't hold data or respond to data upload requests.

Type: Boolean

Required: No

DedicatedMasterType

The hardware configuration of the computer that hosts the dedicated master node. A sample value is `m3.medium.elasticsearch`. If this attribute is specified, then `DedicatedMasterEnabled` must be `true`.

For a list of valid values, see [Supported instance types in Amazon OpenSearch Service](#) in the *Amazon OpenSearch Service Developer Guide*.

Type: String

Pattern: `.*\S.*`

Required: No

InstanceCount

The number of data nodes to use in the Elasticsearch domain.

Type: Integer

Required: No

InstanceType

The instance type for your data nodes. For example, `m3.medium.elasticsearch`.

For a list of valid values, see [Supported instance types in Amazon OpenSearch Service](#) in the *Amazon OpenSearch Service Developer Guide*.

Type: String

Pattern: `.*\S.*`

Required: No

ZoneAwarenessConfig

Configuration options for zone awareness. Provided if `ZoneAwarenessEnabled` is true.

Type: [AwsElasticsearchDomainElasticsearchClusterConfigZoneAwarenessConfigDetails](#) object

Required: No

ZoneAwarenessEnabled

Whether to enable zone awareness for the Elasticsearch domain. When zone awareness is enabled, OpenSearch allocates the cluster's nodes and replica index shards across Availability Zones in the same Region. This prevents data loss and minimizes downtime if a node or data center fails.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElasticsearchDomainElasticsearchClusterConfigZoneAwarenessConfigDetails

Configuration options for zone awareness.

Contents

AvailabilityZoneCount

The number of Availability Zones that the domain uses. Valid values are 2 and 3. The default is 2.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElasticsearchDomainEncryptionAtRestOptions

Details about the configuration for encryption at rest.

Contents

Enabled

Whether encryption at rest is enabled.

Type: Boolean

Required: No

KmsKeyId

The Amazon KMS key ID. Takes the form 1a2a3a4-1a2a-3a4a-5a6a-1a2a3a4a5a6a.

Type: String

Pattern: .*\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElasticsearchDomainLogPublishingOptions

configures the CloudWatch Logs to publish for the Elasticsearch domain.

Contents

AuditLogs

The log configuration.

Type: [AwsElasticsearchDomainLogPublishingOptionsLogConfig](#) object

Required: No

IndexSlowLogs

Configures the OpenSearch index logs publishing.

Type: [AwsElasticsearchDomainLogPublishingOptionsLogConfig](#) object

Required: No

SearchSlowLogs

Configures the OpenSearch search slow log publishing.

Type: [AwsElasticsearchDomainLogPublishingOptionsLogConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElasticsearchDomainLogPublishingOptionsLogConfig

The log configuration.

Contents

CloudWatchLogsLogGroupArn

The ARN of the CloudWatch Logs group to publish the logs to.

Type: String

Pattern: `.*\S.*`

Required: No

Enabled

Whether the log publishing is enabled.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElasticsearchDomainNodeToNodeEncryptionOptions

Details about the configuration for node-to-node encryption.

Contents

Enabled

Whether node-to-node encryption is enabled.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElasticsearchDomainServiceSoftwareOptions

Information about the state of the domain relative to the latest service software.

Contents

AutomatedUpdateDate

The epoch time when the deployment window closes for required updates. After this time, Amazon OpenSearch Service schedules the software upgrade automatically.

Type: String

Pattern: `.*\S.*`

Required: No

Cancellable

Whether a request to update the domain can be canceled.

Type: Boolean

Required: No

CurrentVersion

The version of the service software that is currently installed on the domain.

Type: String

Pattern: `.*\S.*`

Required: No

Description

A more detailed description of the service software status.

Type: String

Pattern: `.*\S.*`

Required: No

NewVersion

The most recent version of the service software.

Type: String

Pattern: `.*\S.*`

Required: No

UpdateAvailable

Whether a service software update is available for the domain.

Type: Boolean

Required: No

UpdateStatus

The status of the service software update. Valid values are as follows:

- COMPLETED
- ELIGIBLE
- IN_PROGRESS
- NOT_ELIGIBLE
- PENDING_UPDATE

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElasticsearchDomainVPCOptions

Information that OpenSearch derives based on VPCOptions for the domain.

Contents

AvailabilityZones

The list of Availability Zones associated with the VPC subnets.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

SecurityGroupIds

The list of security group IDs associated with the VPC endpoints for the domain.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

SubnetIds

A list of subnet IDs associated with the VPC endpoints for the domain.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

VPCId

ID for the VPC.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Elastic Load Balancing objects

Elastic Load Balancing objects

- [AwsElbAppCookieStickinessPolicy](#)
- [AwsElbLbCookieStickinessPolicy](#)
- [AwsElbLoadBalancerAccessLog](#)
- [AwsElbLoadBalancerAdditionalAttribute](#)
- [AwsElbLoadBalancerAttributes](#)
- [AwsElbLoadBalancerBackendServerDescription](#)
- [AwsElbLoadBalancerConnectionDraining](#)
- [AwsElbLoadBalancerConnectionSettings](#)
- [AwsElbLoadBalancerCrossZoneLoadBalancing](#)
- [AwsElbLoadBalancerDetails](#)
- [AwsElbLoadBalancerHealthCheck](#)
- [AwsElbLoadBalancerInstance](#)
- [AwsElbLoadBalancerListener](#)
- [AwsElbLoadBalancerListenerDescription](#)
- [AwsElbLoadBalancerPolicies](#)
- [AwsElbLoadBalancerSourceSecurityGroup](#)
- [AwsElbv2LoadBalancerAttribute](#)
- [AwsElbv2LoadBalancerDetails](#)
- [LoadBalancerState](#)

AwsElbAppCookieStickinessPolicy

Contains information about a stickiness policy that was created using `CreateAppCookieStickinessPolicy`.

Contents

CookieName

The name of the application cookie used for stickiness.

Type: String

Pattern: `.*\S.*`

Required: No

PolicyName

The mnemonic name for the policy being created. The name must be unique within the set of policies for the load balancer.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElbLbCookieStickinessPolicy

Contains information about a stickiness policy that was created using `CreateLbCookieStickinessPolicy`.

Contents

CookieExpirationPeriod

The amount of time, in seconds, after which the cookie is considered stale. If an expiration period is not specified, the stickiness session lasts for the duration of the browser session.

Type: Long

Required: No

PolicyName

The name of the policy. The name must be unique within the set of policies for the load balancer.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElbLoadBalancerAccessLog

Contains information about the access log configuration for the load balancer.

Contents

EmitInterval

The interval in minutes for publishing the access logs.

You can publish access logs either every 5 minutes or every 60 minutes.

Type: Integer

Required: No

Enabled

Indicates whether access logs are enabled for the load balancer.

Type: Boolean

Required: No

S3BucketName

The name of the S3 bucket where the access logs are stored.

Type: String

Pattern: `.*\S.*`

Required: No

S3BucketPrefix

The logical hierarchy that was created for the S3 bucket.

If a prefix is not provided, the log is placed at the root level of the bucket.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElbLoadBalancerAdditionalAttribute

Provides information about additional attributes for the load balancer.

Contents

Key

The name of the attribute.

Type: String

Pattern: `.*\S.*`

Required: No

Value

The value of the attribute.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElbLoadBalancerAttributes

Contains attributes for the load balancer.

Contents

AccessLog

Information about the access log configuration for the load balancer.

If the access log is enabled, the load balancer captures detailed information about all requests. It delivers the information to a specified S3 bucket.

Type: [AwsElbLoadBalancerAccessLog](#) object

Required: No

AdditionalAttributes

Any additional attributes for a load balancer.

Type: Array of [AwsElbLoadBalancerAdditionalAttribute](#) objects

Required: No

ConnectionDraining

Information about the connection draining configuration for the load balancer.

If connection draining is enabled, the load balancer allows existing requests to complete before it shifts traffic away from a deregistered or unhealthy instance.

Type: [AwsElbLoadBalancerConnectionDraining](#) object

Required: No

ConnectionSettings

Connection settings for the load balancer.

If an idle timeout is configured, the load balancer allows connections to remain idle for the specified duration. When a connection is idle, no data is sent over the connection.

Type: [AwsElbLoadBalancerConnectionSettings](#) object

Required: No

CrossZoneLoadBalancing

Cross-zone load balancing settings for the load balancer.

If cross-zone load balancing is enabled, the load balancer routes the request traffic evenly across all instances regardless of the Availability Zones.

Type: [AwsElbLoadBalancerCrossZoneLoadBalancing](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElbLoadBalancerBackendServerDescription

Provides information about the configuration of an EC2 instance for the load balancer.

Contents

InstancePort

The port on which the EC2 instance is listening.

Type: Integer

Required: No

PolicyNames

The names of the policies that are enabled for the EC2 instance.

Type: Array of strings

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElbLoadBalancerConnectionDraining

Contains information about the connection draining configuration for the load balancer.

Contents

Enabled

Indicates whether connection draining is enabled for the load balancer.

Type: Boolean

Required: No

Timeout

The maximum time, in seconds, to keep the existing connections open before deregistering the instances.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElbLoadBalancerConnectionSettings

Contains connection settings for the load balancer.

Contents

IdleTimeout

The time, in seconds, that the connection can be idle (no data is sent over the connection) before it is closed by the load balancer.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElbLoadBalancerCrossZoneLoadBalancing

Contains cross-zone load balancing settings for the load balancer.

Contents

Enabled

Indicates whether cross-zone load balancing is enabled for the load balancer.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElbLoadBalancerDetails

Contains details about a Classic Load Balancer.

Contents

AvailabilityZones

The list of Availability Zones for the load balancer.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

BackendServerDescriptions

Information about the configuration of the EC2 instances.

Type: Array of [AwsElbLoadBalancerBackendServerDescription](#) objects

Required: No

CanonicalHostedZoneName

The name of the Amazon Route 53 hosted zone for the load balancer.

Type: String

Pattern: `.*\S.*`

Required: No

CanonicalHostedZoneNameID

The ID of the Amazon Route 53 hosted zone for the load balancer.

Type: String

Pattern: `.*\S.*`

Required: No

CreatedTime

Indicates when the load balancer was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

DnsName

The DNS name of the load balancer.

Type: String

Pattern: .*\\S.*

Required: No

HealthCheck

Information about the health checks that are conducted on the load balancer.

Type: [AwsElbLoadBalancerHealthCheck](#) object

Required: No

Instances

List of EC2 instances for the load balancer.

Type: Array of [AwsElbLoadBalancerInstance](#) objects

Required: No

ListenerDescriptions

The policies that are enabled for the load balancer listeners.

Type: Array of [AwsElbLoadBalancerListenerDescription](#) objects

Required: No

LoadBalancerAttributes

The attributes for a load balancer.

Type: [AwsElbLoadBalancerAttributes](#) object

Required: No

LoadBalancerName

The name of the load balancer.

Type: String

Pattern: `.*\S.*`

Required: No

Policies

The policies for a load balancer.

Type: [AwsElbLoadBalancerPolicies](#) object

Required: No

Scheme

The type of load balancer. Only provided if the load balancer is in a VPC.

If Scheme is `internet-facing`, the load balancer has a public DNS name that resolves to a public IP address.

If Scheme is `internal`, the load balancer has a public DNS name that resolves to a private IP address.

Type: String

Pattern: `.*\S.*`

Required: No

SecurityGroups

The security groups for the load balancer. Only provided if the load balancer is in a VPC.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

SourceSecurityGroup

Information about the security group for the load balancer. This is the security group that is used for inbound rules.

Type: [AwsElbLoadBalancerSourceSecurityGroup](#) object

Required: No

Subnets

The list of subnet identifiers for the load balancer.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

VpcId

The identifier of the VPC for the load balancer.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElbLoadBalancerHealthCheck

Contains information about the health checks that are conducted on the load balancer.

Contents

HealthyThreshold

The number of consecutive health check successes required before the instance is moved to the Healthy state.

Type: Integer

Required: No

Interval

The approximate interval, in seconds, between health checks of an individual instance.

Type: Integer

Required: No

Target

The instance that is being checked. The target specifies the protocol and port. The available protocols are TCP, SSL, HTTP, and HTTPS. The range of valid ports is 1 through 65535.

For the HTTP and HTTPS protocols, the target also specifies the ping path.

For the TCP protocol, the target is specified as TCP: *<port>* .

For the SSL protocol, the target is specified as SSL . *<port>* .

For the HTTP and HTTPS protocols, the target is specified as *<protocol>:<port>/<path to ping>* .

Type: String

Pattern: `.*\S.*`

Required: No

Timeout

The amount of time, in seconds, during which no response means a failed health check.

Type: Integer

Required: No

UnhealthyThreshold

The number of consecutive health check failures that must occur before the instance is moved to the Unhealthy state.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElbLoadBalancerInstance

Provides information about an EC2 instance for a load balancer.

Contents

InstanceId

The instance identifier.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElbLoadBalancerListener

Information about a load balancer listener.

Contents

InstancePort

The port on which the instance is listening.

Type: Integer

Required: No

InstanceProtocol

The protocol to use to route traffic to instances.

Valid values: HTTP | HTTPS | TCP | SSL

Type: String

Pattern: .*S.*

Required: No

LoadBalancerPort

The port on which the load balancer is listening.

On EC2-VPC, you can specify any port from the range 1-65535.

On EC2-Classic, you can specify any port from the following list: 25, 80, 443, 465, 587, 1024-65535.

Type: Integer

Required: No

Protocol

The load balancer transport protocol to use for routing.

Valid values: HTTP | HTTPS | TCP | SSL

Type: String

Pattern: `.*\S.*`

Required: No

SslCertificateId

The ARN of the server certificate.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElbLoadBalancerListenerDescription

Lists the policies that are enabled for a load balancer listener.

Contents

Listener

Information about the listener.

Type: [AwsElbLoadBalancerListener](#) object

Required: No

PolicyNames

The policies enabled for the listener.

Type: Array of strings

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElbLoadBalancerPolicies

Contains information about the policies for a load balancer.

Contents

AppCookieStickinessPolicies

The stickiness policies that are created using `CreateAppCookieStickinessPolicy`.

Type: Array of [AwsElbAppCookieStickinessPolicy](#) objects

Required: No

LbCookieStickinessPolicies

The stickiness policies that are created using `CreateLbCookieStickinessPolicy`.

Type: Array of [AwsElbLbCookieStickinessPolicy](#) objects

Required: No

OtherPolicies

The policies other than the stickiness policies.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElbLoadBalancerSourceSecurityGroup

Contains information about the security group for the load balancer.

Contents

GroupName

The name of the security group.

Type: String

Pattern: .*S.*

Required: No

OwnerAlias

The owner of the security group.

Type: String

Pattern: .*S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElbv2LoadBalancerAttribute

A load balancer attribute.

Contents

Key

The name of the load balancer attribute.

Type: String

Pattern: `.*\S.*`

Required: No

Value

The value of the load balancer attribute.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsElbv2LoadBalancerDetails

Information about a load balancer.

Contents

AvailabilityZones

The Availability Zones for the load balancer.

Type: Array of [AvailabilityZone](#) objects

Required: No

CanonicalHostedZoneId

The ID of the Amazon Route 53 hosted zone associated with the load balancer.

Type: String

Pattern: `.*\S.*`

Required: No

CreatedTime

Indicates when the load balancer was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

DNSName

The public DNS name of the load balancer.

Type: String

Pattern: `.*\S.*`

Required: No

IpAddressType

The type of IP addresses used by the subnets for your load balancer. The possible values are `ipv4` (for IPv4 addresses) and `dualstack` (for IPv4 and IPv6 addresses).

Type: String

Pattern: `.*\S.*`

Required: No

LoadBalancerAttributes

Attributes of the load balancer.

Type: Array of [AwsElbv2LoadBalancerAttribute](#) objects

Required: No

Scheme

The nodes of an Internet-facing load balancer have public IP addresses.

Type: String

Pattern: `.*\S.*`

Required: No

SecurityGroups

The IDs of the security groups for the load balancer.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

State

The state of the load balancer.

Type: [LoadBalancerState](#) object

Required: No

Type

The type of load balancer.

Type: String

Pattern: `.*\S.*`

Required: No

VpcId

The ID of the VPC for the load balancer.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

LoadBalancerState

Information about the state of the load balancer.

Contents

Code

The state code. The initial state of the load balancer is provisioning.

After the load balancer is fully set up and ready to route traffic, its state is active.

If the load balancer could not be set up, its state is failed.

Type: String

Pattern: `.*\S.*`

Required: No

Reason

A description of the state.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon EventBridge objects

Amazon EventBridge objects

- [AwsEventSchemasRegistryDetails](#)
- [AwsEventsEndpointDetails](#)
- [AwsEventsEndpointEventBusesDetails](#)
- [AwsEventsEndpointReplicationConfigDetails](#)
- [AwsEventsEndpointRoutingConfigDetails](#)
- [AwsEventsEndpointRoutingConfigFailoverConfigDetails](#)
- [AwsEventsEndpointRoutingConfigFailoverConfigPrimaryDetails](#)
- [AwsEventsEndpointRoutingConfigFailoverConfigSecondaryDetails](#)
- [AwsEventsEventbusDetails](#)

AwsEventSchemasRegistryDetails

A schema defines the structure of events that are sent to Amazon EventBridge. Schema registries are containers for schemas. They collect and organize schemas so that your schemas are in logical groups.

Contents

Description

A description of the registry to be created.

Type: String

Pattern: `.*\S.*`

Required: No

RegistryArn

The Amazon Resource Name (ARN) of the registry.

Type: String

Pattern: `.*\S.*`

Required: No

RegistryName

The name of the schema registry.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEventsEndpointDetails

Provides details about an Amazon EventBridge global endpoint. The endpoint can improve your application's availability by making it Regional-fault tolerant.

Contents

Arn

The Amazon Resource Name (ARN) of the endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

Description

A description of the endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

EndpointId

The URL subdomain of the endpoint. For example, if `EndpointUrl` is `https://abcde.veo.endpoints.event.amazonaws.com`, then the `EndpointId` is `abcde.veo`.

Type: String

Pattern: `.*\S.*`

Required: No

EndpointUrl

The URL of the endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

EventBuses

The event buses being used by the endpoint.

Type: Array of [AwsEventsEndpointEventBusesDetails](#) objects

Required: No

Name

The name of the endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

ReplicationConfig

Whether event replication was enabled or disabled for this endpoint. The default state is ENABLED, which means you must supply a RoleArn. If you don't have a RoleArn or you don't want event replication enabled, set the state to DISABLED.

Type: [AwsEventsEndpointReplicationConfigDetails](#) object

Required: No

RoleArn

The ARN of the role used by event replication for the endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

RoutingConfig

The routing configuration of the endpoint.

Type: [AwsEventsEndpointRoutingConfigDetails](#) object

Required: No

State

The current state of the endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

StateReason

The reason the endpoint is in its current state.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEventsEndpointEventBusesDetails

Provides details about the Amazon EventBridge event buses that the endpoint is associated with.

Contents

EventBusArn

The Amazon Resource Name (ARN) of the event bus that the endpoint is associated with.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEventsEndpointReplicationConfigDetails

Indicates whether replication is enabled or disabled for the endpoint. If enabled, the endpoint can replicate all events to a secondary Amazon Web Services Region.

Contents

State

The state of event replication.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEventsEndpointRoutingConfigDetails

Provides details about the routing configuration of the endpoint.

Contents

FailoverConfig

The failover configuration for an endpoint. This includes what triggers failover and what happens when it's triggered.

Type: [AwsEventsEndpointRoutingConfigFailoverConfigDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEventsEndpointRoutingConfigFailoverConfigDetails

The failover configuration for an endpoint. This includes what triggers failover and what happens when it's triggered.

Contents

Primary

The main Region of the endpoint.

Type: [AwsEventsEndpointRoutingConfigFailoverConfigPrimaryDetails](#) object

Required: No

Secondary

The Region that events are routed to when failover is triggered or event replication is enabled.

Type: [AwsEventsEndpointRoutingConfigFailoverConfigSecondaryDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEventsEndpointRoutingConfigFailoverConfigPrimaryDetails

Provides details about the primary Amazon Web Services Region of the endpoint.

Contents

HealthCheck

The Amazon Resource Name (ARN) of the health check used by the endpoint to determine whether failover is triggered.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEventsEndpointRoutingConfigFailoverConfigSecondaryDetails

The Amazon Web Services Region that events are routed to when failover is triggered or event replication is enabled.

Contents

Route

Defines the secondary Region.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsEventsEventbusDetails

Provides details about Amazon EventBridge event bus. An event bus is a router that receives events and delivers them to zero or more destinations, or targets. This can be a custom event bus which you can use to receive events from your custom applications and services, or it can be a partner event bus which can be matched to a partner event source.

Contents

Arn

The Amazon Resource Name (ARN) of the account permitted to write events to the current account.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the event bus.

Type: String

Pattern: `.*\S.*`

Required: No

Policy

The policy that enables the external account to send events to your account.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon GuardDuty objects

Amazon GuardDuty objects

- [AwsGuardDutyDetectorDetails](#)
- [AwsGuardDutyDetectorFeaturesDetails](#)
- [AwsGuardDutyDetectorDataSourcesCloudTrailDetails](#)
- [AwsGuardDutyDetectorDataSourcesDetails](#)
- [AwsGuardDutyDetectorDataSourcesDnsLogsDetails](#)
- [AwsGuardDutyDetectorDataSourcesFlowLogsDetails](#)
- [AwsGuardDutyDetectorDataSourcesKubernetesAuditLogsDetails](#)
- [AwsGuardDutyDetectorDataSourcesKubernetesDetails](#)
- [AwsGuardDutyDetectorDataSourcesMalwareProtectionDetails](#)
- [AwsGuardDutyDetectorDataSourcesMalwareProtectionScanEc2InstanceWithFindingsDetails](#)
- [AwsGuardDutyDetectorDataSourcesMalwareProtectionScanEc2InstanceWithFindingsEbsVolumesDetails](#)
- [AwsGuardDutyDetectorDataSourcesS3LogsDetails](#)

AwsGuardDutyDetectorDetails

Provides details about an Amazon GuardDuty detector. A detector is an object that represents the GuardDuty service. A detector is required for GuardDuty to become operational.

Contents

DataSources

Describes which data sources are activated for the detector.

Type: [AwsGuardDutyDetectorDataSourcesDetails](#) object

Required: No

Features

Describes which features are activated for the detector.

Type: Array of [AwsGuardDutyDetectorFeaturesDetails](#) objects

Required: No

FindingPublishingFrequency

The publishing frequency of the finding.

Type: String

Pattern: `.*\S.*`

Required: No

ServiceRole

The GuardDuty service role.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The activation status of the detector.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsGuardDutyDetectorFeaturesDetails

Describes which features are activated for the detector.

Contents

Name

Indicates the name of the feature that is activated for the detector.

Type: String

Pattern: `.*\S.*`

Required: No

Status

Indicates the status of the feature that is activated for the detector.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsGuardDutyDetectorDataSourcesCloudTrailDetails

An object that contains information on the status of Amazon CloudTrail as a data source for the detector.

Contents

Status

Specifies whether CloudTrail is activated as a data source for the detector.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsGuardDutyDetectorDataSourcesDetails

Describes which data sources are activated for the detector.

Contents

CloudTrail

An object that contains information on the status of CloudTrail as a data source for the detector.

Type: [AwsGuardDutyDetectorDataSourcesCloudTrailDetails](#) object

Required: No

DnsLogs

An object that contains information on the status of DNS logs as a data source for the detector.

Type: [AwsGuardDutyDetectorDataSourcesDnsLogsDetails](#) object

Required: No

FlowLogs

An object that contains information on the status of VPC Flow Logs as a data source for the detector.

Type: [AwsGuardDutyDetectorDataSourcesFlowLogsDetails](#) object

Required: No

Kubernetes

An object that contains information on the status of Kubernetes data sources for the detector.

Type: [AwsGuardDutyDetectorDataSourcesKubernetesDetails](#) object

Required: No

MalwareProtection

An object that contains information on the status of Malware Protection as a data source for the detector.

Type: [AwsGuardDutyDetectorDataSourcesMalwareProtectionDetails](#) object

Required: No

S3Logs

An object that contains information on the status of S3 Data event logs as a data source for the detector.

Type: [AwsGuardDutyDetectorDataSourcesS3LogsDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsGuardDutyDetectorDataSourcesDnsLogsDetails

An object that contains information on the status of DNS logs as a data source for the detector.

Contents

Status

Describes whether DNS logs is enabled as a data source for the detector.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsGuardDutyDetectorDataSourcesFlowLogsDetails

An object that contains information on the status of VPC Flow Logs as a data source for the detector.

Contents

Status

Describes whether VPC Flow Logs are activated as a data source for the detector.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsGuardDutyDetectorDataSourcesKubernetesAuditLogsDetails

An object that contains information on the status of Kubernetes audit logs as a data source for the detector.

Contents

Status

Describes whether Kubernetes audit logs are activated as a data source for the detector.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsGuardDutyDetectorDataSourcesKubernetesDetails

An object that contains information on the status of Kubernetes data sources for the detector.

Contents

AuditLogs

Describes whether Kubernetes audit logs are activated as a data source for the detector.

Type: [AwsGuardDutyDetectorDataSourcesKubernetesAuditLogsDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsGuardDutyDetectorDataSourcesMalwareProtectionDetails

An object that contains information on the status of Malware Protection as a data source for the detector.

Contents

ScanEc2InstanceWithFindings

Describes the configuration of Malware Protection for EC2 instances with findings.

Type:

[AwsGuardDutyDetectorDataSourcesMalwareProtectionScanEc2InstanceWithFindingsDetails](#)
object

Required: No

ServiceRole

The GuardDuty Malware Protection service role.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsGuardDutyDetectorDataSourcesMalwareProtectionScanEc2InstanceWithFindingsDe

Describes the configuration of Malware Protection for EC2 instances with findings.

Contents

EbsVolumes

Describes the configuration of scanning EBS volumes (Malware Protection) as a data source.

Type:

[AwsGuardDutyDetectorDataSourcesMalwareProtectionScanEc2InstanceWithFindingsEbsVolumesDetail](#)
object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsGuardDutyDetectorDataSourcesMalwareProtectionScanEc2InstanceWithFindingsEb

Describes the configuration of scanning EBS volumes (Malware Protection) as a data source.

Contents

Reason

Specifies the reason why scanning EBS volumes (Malware Protection) isn't activated as a data source.

Type: String

Pattern: `.*\S.*`

Required: No

Status

Describes whether scanning EBS volumes is activated as a data source for the detector.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsGuardDutyDetectorDataSourcesS3LogsDetails

An object that contains information on the status of S3 data event logs as a data source for the detector.

Contents

Status

A value that describes whether S3 data event logs are automatically enabled for new members of an organization.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Identity and Access Management (IAM) objects

Amazon Identity and Access Management (IAM) objects

- [AwslamAccessKeyDetails](#)
- [AwslamAccessKeySessionContext](#)
- [AwslamAccessKeySessionContextAttributes](#)
- [AwslamAccessKeySessionContextSessionIssuer](#)
- [AwslamAttachedManagedPolicy](#)
- [AwslamGroupDetails](#)
- [AwslamGroupPolicy](#)

- [AwsIamInstanceProfile](#)
- [AwsIamInstanceProfileRole](#)
- [AwsIamPermissionsBoundary](#)
- [AwsIamPolicyDetails](#)
- [AwsIamPolicyVersion](#)
- [AwsIamRoleDetails](#)
- [AwsIamRolePolicy](#)
- [AwsIamUserDetails](#)
- [AwsIamUserPolicy](#)

AwsIamAccessKeyDetails

IAM access key details related to a finding.

Contents

AccessKeyId

The identifier of the access key.

Type: String

Pattern: `.*\S.*`

Required: No

AccountId

The Amazon Web Services account ID of the account for the key.

Type: String

Pattern: `.*\S.*`

Required: No

CreatedAt

Indicates when the IAM access key was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

PrincipalId

The ID of the principal associated with an access key.

Type: String

Pattern: `.*\S.*`

Required: No

PrincipalName

The name of the principal.

Type: String

Pattern: `.*\S.*`

Required: No

PrincipalType

The type of principal associated with an access key.

Type: String

Pattern: `.*\S.*`

Required: No

SessionContext

Information about the session that the key was used for.

Type: [AwsIamAccessKeySessionContext](#) object

Required: No

Status

The status of the IAM access key related to a finding.

Type: String

Valid Values: Active | Inactive

Required: No

UserName

This member has been deprecated.

The user associated with the IAM access key related to a finding.

The `UserName` parameter has been replaced with the `PrincipalName` parameter because access keys can also be assigned to principals that are not IAM users.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsIamAccessKeySessionContext

Provides information about the session that the key was used for.

Contents

Attributes

Attributes of the session that the key was used for.

Type: [AwsIamAccessKeySessionContextAttributes](#) object

Required: No

SessionIssuer

Information about the entity that created the session.

Type: [AwsIamAccessKeySessionContextSessionIssuer](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsIamAccessKeySessionContextAttributes

Attributes of the session that the key was used for.

Contents

CreationDate

Indicates when the session was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

MfaAuthenticated

Indicates whether the session used multi-factor authentication (MFA).

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsIamAccessKeySessionContextSessionIssuer

Information about the entity that created the session.

Contents

AccountId

The identifier of the Amazon Web Services account that created the session.

Type: String

Pattern: `.*\S.*`

Required: No

Arn

The ARN of the session.

Type: String

Pattern: `.*\S.*`

Required: No

PrincipalId

The principal ID of the principal (user, role, or group) that created the session.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The type of principal (user, role, or group) that created the session.

Type: String

Pattern: `.*\S.*`

Required: No

UserName

The name of the principal that created the session.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsIamAttachedManagedPolicy

A managed policy that is attached to an IAM principal.

Contents

PolicyArn

The ARN of the policy.

Type: String

Pattern: `.*\S.*`

Required: No

PolicyName

The name of the policy.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsIamGroupDetails

Contains details about an IAM group.

Contents

AttachedManagedPolicies

A list of the managed policies that are attached to the IAM group.

Type: Array of [AwsIamAttachedManagedPolicy](#) objects

Required: No

CreateDate

Indicates when the IAM group was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

GroupId

The identifier of the IAM group.

Type: String

Pattern: `.*\S.*`

Required: No

GroupName

The name of the IAM group.

Type: String

Pattern: `.*\S.*`

Required: No

GroupPolicyList

The list of inline policies that are embedded in the group.

Type: Array of [AwsIamGroupPolicy](#) objects

Required: No

Path

The path to the group.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwslamGroupPolicy

A managed policy that is attached to the IAM group.

Contents

PolicyName

The name of the policy.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsIamInstanceProfile

Information about an instance profile.

Contents

Arn

The ARN of the instance profile.

Type: String

Pattern: `.*\S.*`

Required: No

CreateDate

Indicates when the instance profile was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

InstanceProfileId

The identifier of the instance profile.

Type: String

Pattern: `.*\S.*`

Required: No

InstanceProfileName

The name of the instance profile.

Type: String

Pattern: `.*\S.*`

Required: No

Path

The path to the instance profile.

Type: String

Pattern: `.*\S.*`

Required: No

Roles

The roles associated with the instance profile.

Type: Array of [AwsIamInstanceProfileRole](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsIamInstanceProfileRole

Information about a role associated with an instance profile.

Contents

Arn

The ARN of the role.

Type: String

Pattern: `.*\S.*`

Required: No

AssumeRolePolicyDocument

The policy that grants an entity permission to assume the role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: `[\u0009\u000A\u000D\u0020-\u007E\u00A1-\u00FF]+`

Required: No

CreateDate

Indicates when the role was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

Path

The path to the role.

Type: String

Pattern: `.*\S.*`

Required: No

RoleId

The identifier of the role.

Type: String

Pattern: `.*\S.*`

Required: No

RoleName

The name of the role.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsIamPermissionsBoundary

Information about the policy used to set the permissions boundary for an IAM principal.

Contents

PermissionsBoundaryArn

The ARN of the policy used to set the permissions boundary.

Type: String

Pattern: `.*\S.*`

Required: No

PermissionsBoundaryType

The usage type for the permissions boundary.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsIamPolicyDetails

Represents an IAM permissions policy.

Contents

AttachmentCount

The number of users, groups, and roles that the policy is attached to.

Type: Integer

Required: No

CreateDate

When the policy was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

DefaultVersionId

The identifier of the default version of the policy.

Type: String

Pattern: `.*\S.*`

Required: No

Description

A description of the policy.

Type: String

Pattern: `.*\S.*`

Required: No

IsAttachable

Whether the policy can be attached to a user, group, or role.

Type: Boolean

Required: No

Path

The path to the policy.

Type: String

Pattern: `.*\S.*`

Required: No

PermissionsBoundaryUsageCount

The number of users and roles that use the policy to set the permissions boundary.

Type: Integer

Required: No

PolicyId

The unique identifier of the policy.

Type: String

Pattern: `.*\S.*`

Required: No

PolicyName

The name of the policy.

Type: String

Pattern: `.*\S.*`

Required: No

PolicyVersionList

List of versions of the policy.

Type: Array of [AwsIamPolicyVersion](#) objects

Required: No

UpdateDate

When the policy was most recently updated.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsIamPolicyVersion

A version of an IAM policy.

Contents

CreateDate

Indicates when the version was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

IsDefaultVersion

Whether the version is the default version.

Type: Boolean

Required: No

VersionId

The identifier of the policy version.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsIamRoleDetails

Contains information about an IAM role, including all of the role's policies.

Contents

AssumeRolePolicyDocument

The trust policy that grants permission to assume the role.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: `[\u0009\u000A\u000D\u0020-\u007E\u00A1-\u00FF]+`

Required: No

AttachedManagedPolicies

The list of the managed policies that are attached to the role.

Type: Array of [AwsIamAttachedManagedPolicy](#) objects

Required: No

CreateDate

Indicates when the role was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

InstanceProfileList

The list of instance profiles that contain this role.

Type: Array of [AwsIamInstanceProfile](#) objects

Required: No

MaxSessionDuration

The maximum session duration (in seconds) that you want to set for the specified role.

Type: Integer

Required: No

Path

The path to the role.

Type: String

Pattern: `.*\S.*`

Required: No

PermissionsBoundary

Information about the policy used to set the permissions boundary for an IAM principal.

Type: [AwsIamPermissionsBoundary](#) object

Required: No

RoleId

The stable and unique string identifying the role.

Type: String

Pattern: `.*\S.*`

Required: No

RoleName

The friendly name that identifies the role.

Type: String

Pattern: `.*\S.*`

Required: No

RolePolicyList

The list of inline policies that are embedded in the role.

Type: Array of [AwsIamRolePolicy](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwslamRolePolicy

An inline policy that is embedded in the role.

Contents

PolicyName

The name of the policy.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsIamUserDetails

Information about an IAM user.

Contents

AttachedManagedPolicies

A list of the managed policies that are attached to the user.

Type: Array of [AwsIamAttachedManagedPolicy](#) objects

Required: No

CreateDate

Indicates when the user was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

GroupList

A list of IAM groups that the user belongs to.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Path

The path to the user.

Type: String

Pattern: `.*\S.*`

Required: No

PermissionsBoundary

The permissions boundary for the user.

Type: [AwsIamPermissionsBoundary](#) object

Required: No

UserId

The unique identifier for the user.

Type: String

Pattern: `.*\S.*`

Required: No

UserName

The name of the user.

Type: String

Pattern: `.*\S.*`

Required: No

UserPolicyList

The list of inline policies that are embedded in the user.

Type: Array of [AwsIamUserPolicy](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsIamUserPolicy

Information about an inline policy that is embedded in the user.

Contents

PolicyName

The name of the policy.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Kinesis objects

Amazon Kinesis objects

- [AwsKinesisStreamDetails](#)
- [AwsKinesisStreamStreamEncryptionDetails](#)

AwsKinesisStreamDetails

Provides information about an Amazon Kinesis data stream.

Contents

Arn

The Amazon Resource Name (ARN) of the Kinesis data stream.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the Kinesis stream. If you don't specify a name, CloudFront generates a unique physical ID and uses that ID for the stream name.

Type: String

Pattern: `.*\S.*`

Required: No

RetentionPeriodHours

The number of hours for the data records that are stored in shards to remain accessible.

Type: Integer

Required: No

ShardCount

The number of shards that the stream uses.

Type: Integer

Required: No

StreamEncryption

When specified, enables or updates server-side encryption using an Amazon KMS key for a specified stream. Removing this property from your stack template and updating your stack disables encryption.

Type: [AwsKinesisStreamStreamEncryptionDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsKinesisStreamStreamEncryptionDetails

Provides information about stream encryption.

Contents

EncryptionType

The encryption type to use.

Type: String

Pattern: .*S.*

Required: No

KeyId

The globally unique identifier for the customer-managed Amazon KMS key to use for encryption.

Type: String

Pattern: .*S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Key Management Service (Amazon KMS) objects

objects

- [AwsKmsKeyDetails](#)

AwsKmsKeyDetails

Contains metadata about an Amazon KMS key.

Contents

AWSAccountId

The twelve-digit account ID of the Amazon Web Services account that owns the KMS key.

Type: String

Pattern: `.*\S.*`

Required: No

CreationDate

Indicates when the KMS key was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: Double

Required: No

Description

A description of the KMS key.

Type: String

Pattern: `.*\S.*`

Required: No

KeyId

The globally unique identifier for the KMS key.

Type: String

Pattern: `.*\S.*`

Required: No

KeyManager

The manager of the KMS key. KMS keys in your Amazon Web Services account are either customer managed or Amazon managed.

Type: String

Pattern: `.*\S.*`

Required: No

KeyRotationStatus

Whether the key has key rotation enabled.

Type: Boolean

Required: No

KeyState

The state of the KMS key. Valid values are as follows:

- Disabled
- Enabled
- PendingDeletion
- PendingImport
- Unavailable

Type: String

Pattern: `.*\S.*`

Required: No

Origin

The source of the KMS key material.

When this value is `AWS_KMS`, Amazon KMS created the key material.

When this value is `EXTERNAL`, the key material was imported from your existing key management infrastructure or the KMS key lacks key material.

When this value is `AWS_CLOUDHSM`, the key material was created in the Amazon CloudHSM cluster associated with a custom key store.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Lambda objects

Amazon Lambda objects

- [AwsLambdaFunctionDetails](#)
- [AwsLambdaFunctionCode](#)
- [AwsLambdaFunctionDeadLetterConfig](#)
- [AwsLambdaFunctionEnvironment](#)
- [AwsLambdaFunctionEnvironmentError](#)
- [AwsLambdaFunctionLayer](#)
- [AwsLambdaFunctionTracingConfig](#)
- [AwsLambdaFunctionVpcConfig](#)
- [AwsLambdaLayerVersionDetails](#)

AwsLambdaFunctionDetails

Details about an Amazon Lambda function's configuration.

Contents

Architectures

The instruction set architecture that the function uses. Valid values are `x86_64` or `arm64`.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Code

An `AwsLambdaFunctionCode` object.

Type: [AwsLambdaFunctionCode](#) object

Required: No

CodeSha256

The SHA256 hash of the function's deployment package.

Type: String

Pattern: `.*\S.*`

Required: No

DeadLetterConfig

The function's dead letter queue.

Type: [AwsLambdaFunctionDeadLetterConfig](#) object

Required: No

Environment

The function's environment variables.

Type: [AwsLambdaFunctionEnvironment](#) object

Required: No

FunctionName

The name of the function.

Type: String

Pattern: `.*\S.*`

Required: No

Handler

The function that Lambda calls to begin executing your function.

Type: String

Pattern: `.*\S.*`

Required: No

KmsKeyArn

The Amazon KMS key that is used to encrypt the function's environment variables. This key is only returned if you've configured a customer managed customer managed key.

Type: String

Pattern: `.*\S.*`

Required: No

LastModified

Indicates when the function was last updated.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

Layers

The function's layers.

Type: Array of [AwsLambdaFunctionLayer](#) objects

Required: No

MasterArn

For Lambda@Edge functions, the ARN of the master function.

Type: String

Pattern: `.*\S.*`

Required: No

MemorySize

The memory that is allocated to the function.

Type: Integer

Required: No

PackageType

The type of deployment package that's used to deploy the function code to Lambda. Set to Image for a container image and Zip for a .zip file archive.

Type: String

Pattern: `.*\S.*`

Required: No

RevisionId

The latest updated revision of the function or alias.

Type: String

Pattern: `.*\S.*`

Required: No

Role

The function's execution role.

Type: String

Pattern: `.*\S.*`

Required: No

Runtime

The runtime environment for the Lambda function.

Type: String

Pattern: `.*\S.*`

Required: No

Timeout

The amount of time that Lambda allows a function to run before stopping it.

Type: Integer

Required: No

TracingConfig

The function's Amazon X-Ray tracing configuration.

Type: [AwsLambdaFunctionTracingConfig](#) object

Required: No

Version

The version of the Lambda function.

Type: String

Pattern: `.*\S.*`

Required: No

VpcConfig

The function's networking configuration.

Type: [AwsLambdaFunctionVpcConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsLambdaFunctionCode

The code for the Lambda function. You can specify either an object in Amazon S3, or upload a deployment package directly.

Contents

S3Bucket

An Amazon S3 bucket in the same Amazon Web Services Region as your function. The bucket can be in a different Amazon Web Services account.

Type: String

Pattern: `.*\S.*`

Required: No

S3Key

The Amazon S3 key of the deployment package.

Type: String

Pattern: `.*\S.*`

Required: No

S3ObjectVersion

For versioned objects, the version of the deployment package object to use.

Type: String

Pattern: `.*\S.*`

Required: No

ZipFile

The base64-encoded contents of the deployment package. Amazon SDK and Amazon CLI clients handle the encoding for you.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsLambdaFunctionDeadLetterConfig

The dead-letter queue for failed asynchronous invocations.

Contents

TargetArn

The ARN of an SQS queue or SNS topic.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsLambdaFunctionEnvironment

A function's environment variable settings.

Contents

Error

An `AwsLambdaFunctionEnvironmentError` object.

Type: [AwsLambdaFunctionEnvironmentError](#) object

Required: No

Variables

Environment variable key-value pairs.

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsLambdaFunctionEnvironmentError

Error messages for environment variables that could not be applied.

Contents

ErrorCode

The error code.

Type: String

Pattern: `.*\S.*`

Required: No

Message

The error message.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsLambdaFunctionLayer

An Amazon Lambda layer.

Contents

Arn

The ARN of the function layer.

Type: String

Pattern: `.*\S.*`

Required: No

CodeSize

The size of the layer archive in bytes.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsLambdaFunctionTracingConfig

The function's Amazon X-Ray tracing configuration.

Contents

Mode

The tracing mode.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsLambdaFunctionVpcConfig

The VPC security groups and subnets that are attached to a Lambda function.

Contents

SecurityGroupIds

A list of VPC security groups IDs.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

SubnetIds

A list of VPC subnet IDs.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

VpcId

The ID of the VPC.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsLambdaLayerVersionDetails

Details about a Lambda layer version.

Contents

CompatibleRuntimes

The layer's compatible [function runtimes](#).

The following list includes deprecated runtimes. For more information, see [Runtime deprecation policy](#) in the *Amazon Lambda Developer Guide*.

Array Members: Maximum number of 5 items.

Valid Values: nodejs | nodejs4.3 | nodejs6.10 | nodejs8.10 | nodejs10.x | nodejs12.x | nodejs14.x | nodejs16.x | java8 | java8.al2 | java11 | python2.7 | python3.6 | python3.7 | python3.8 | python3.9 | dotnetcore1.0 | dotnetcore2.0 | dotnetcore2.1 | dotnetcore3.1 | dotnet6 | nodejs4.3-edge | go1.x | ruby2.5 | ruby2.7 | provided | provided.al2 | nodejs18.x | python3.10 | java17 | ruby3.2 | python3.11 | nodejs20.x | provided.al2023 | python3.12 | java21

Type: Array of strings

Pattern: .*\\S.*

Required: No

CreatedDate

Indicates when the version was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

Version

The version number.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon MSK objects

Amazon MSK objects

- [AwsMskClusterDetails](#)
- [AwsMskClusterClusterInfoClientAuthenticationDetails](#)
- [AwsMskClusterClusterInfoClientAuthenticationSaslDetails](#)
- [AwsMskClusterClusterInfoClientAuthenticationSslIamDetails](#)
- [AwsMskClusterClusterInfoClientAuthenticationSaslScramDetails](#)
- [AwsMskClusterClusterInfoClientAuthenticationTlsDetails](#)
- [AwsMskClusterClusterInfoClientAuthenticationUnauthenticatedDetails](#)
- [AwsMskClusterClusterInfoDetails](#)
- [AwsMskClusterClusterInfoEncryptionInfoDetails](#)
- [AwsMskClusterClusterInfoEncryptionInfoEncryptionAtRestDetails](#)
- [AwsMskClusterClusterInfoEncryptionInfoEncryptionInTransitDetails](#)

AwsMskClusterDetails

Provides details about an Amazon Managed Streaming for Apache Kafka (Amazon MSK) cluster.

Contents

ClusterInfo

Provides information about a cluster.

Type: [AwsMskClusterClusterInfoDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsMskClusterClusterInfoClientAuthenticationDetails

Provides details about different modes of client authentication.

Contents

Sasl

Provides details for client authentication using SASL.

Type: [AwsMskClusterClusterInfoClientAuthenticationSaslDetails](#) object

Required: No

Tls

Provides details for client authentication using TLS.

Type: [AwsMskClusterClusterInfoClientAuthenticationTlsDetails](#) object

Required: No

Unauthenticated

Provides details for allowing no client authentication.

Type: [AwsMskClusterClusterInfoClientAuthenticationUnauthenticatedDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsMskClusterClusterInfoClientAuthenticationSaslDetails

Provides details for client authentication using SASL.

Contents

Iam

Provides details for SASL client authentication using IAM.

Type: [AwsMskClusterClusterInfoClientAuthenticationSaslIamDetails](#) object

Required: No

Scram

Details for SASL client authentication using SCRAM.

Type: [AwsMskClusterClusterInfoClientAuthenticationSaslScramDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsMskClusterClusterInfoClientAuthenticationSasllamDetails

Details for SASL/IAM client authentication.

Contents

Enabled

Indicates whether SASL/IAM authentication is enabled or not.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsMskClusterClusterInfoClientAuthenticationSaslScramDetails

Details for SASL/SCRAM client authentication.

Contents

Enabled

Indicates whether SASL/SCRAM authentication is enabled or not.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsMskClusterClusterInfoClientAuthenticationTlsDetails

Provides details for client authentication using TLS.

Contents

CertificateAuthorityArnList

List of Amazon Private CA Amazon Resource Names (ARNs). Amazon Private CA enables creation of private certificate authority (CA) hierarchies, including root and subordinate CAs, without the investment and maintenance costs of operating an on-premises CA.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Enabled

Indicates whether TLS authentication is enabled or not.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsMskClusterClusterInfoClientAuthenticationUnauthenticatedDetails

Provides details for allowing no client authentication.

Contents

Enabled

Indicates whether unauthenticated is allowed or not.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsMskClusterClusterInfoDetails

Provide details about an Amazon Managed Streaming for Apache Kafka (Amazon MSK) cluster.

Contents

ClientAuthentication

Provides information for different modes of client authentication.

Type: [AwsMskClusterClusterInfoClientAuthenticationDetails](#) object

Required: No

ClusterName

The name of the cluster.

Type: String

Pattern: `.*\S.*`

Required: No

CurrentVersion

The current version of the cluster.

Type: String

Pattern: `.*\S.*`

Required: No

EncryptionInfo

Includes encryption-related information, such as the Amazon KMS key used for encrypting data at rest and whether you want Amazon MSK to encrypt your data in transit.

Type: [AwsMskClusterClusterInfoEncryptionInfoDetails](#) object

Required: No

EnhancedMonitoring

Specifies the level of monitoring for the cluster.

Type: String

Pattern: .*\\S.*

Required: No

NumberOfBrokerNodes

The number of broker nodes in the cluster.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsMskClusterClusterInfoEncryptionInfoDetails

Includes encryption-related information, such as the Amazon KMS key used for encrypting data at rest and whether you want MSK to encrypt your data in transit.

Contents

EncryptionAtRest

The data-volume encryption details. You can't update encryption at rest settings for existing clusters.

Type: [AwsMskClusterClusterInfoEncryptionInfoEncryptionAtRestDetails](#) object

Required: No

EncryptionInTransit

The settings for encrypting data in transit.

Type: [AwsMskClusterClusterInfoEncryptionInfoEncryptionInTransitDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsMskClusterClusterInfoEncryptionInfoEncryptionAtRestDetails

The data-volume encryption details. You can't update encryption at rest settings for existing clusters.

Contents

DataVolumeKMSKeyId

The Amazon Resource Name (ARN) of the Amazon KMS key for encrypting data at rest. If you don't specify a KMS key, MSK creates one for you and uses it.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsMskClusterClusterInfoEncryptionInfoEncryptionInTransitDetails

The settings for encrypting data in transit.

Contents

ClientBroker

Indicates the encryption setting for data in transit between clients and brokers.

Type: String

Pattern: `.*\S.*`

Required: No

InCluster

When set to `true`, it indicates that data communication among the broker nodes of the cluster is encrypted. When set to `false`, the communication happens in plain text. The default value is `true`.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Network Firewall objects

Amazon Network Firewall objects

- [AwsNetworkFirewallFirewallDetails](#)
- [AwsNetworkFirewallFirewallPolicyDetails](#)

- [FirewallPolicyDetails](#)
- [FirewallPolicyStatelessCustomActionsDetails](#)
- [StatelessCustomActionDefinition](#)
- [StatelessCustomPublishMetricAction](#)
- [StatelessCustomPublishMetricActionDimension](#)
- [AwsNetworkFirewallFirewallSubnetMappingsDetails](#)
- [AwsNetworkFirewallRuleGroupDetails](#)
- [RuleGroupDetails](#)
- [RuleGroupSource](#)
- [RuleGroupSourceCustomActionsDetails](#)
- [RuleGroupSourceListDetails](#)
- [RuleGroupSourceStatefulRulesDetails](#)
- [RuleGroupSourceStatefulRulesHeaderDetails](#)
- [RuleGroupSourceStatefulRulesOptionsDetails](#)
- [RuleGroupSourceStatelessRuleDefinition](#)
- [RuleGroupSourceStatelessRuleMatchAttributes](#)
- [RuleGroupSourceStatelessRuleMatchAttributesDestinationPorts](#)
- [RuleGroupSourceStatelessRuleMatchAttributesDestinations](#)
- [RuleGroupSourceStatelessRuleMatchAttributesSourcePorts](#)
- [RuleGroupSourceStatelessRuleMatchAttributesSources](#)
- [RuleGroupSourceStatelessRuleMatchAttributesTcpFlags](#)
- [RuleGroupSourceStatelessRulesAndCustomActionsDetails](#)
- [RuleGroupSourceStatelessRulesDetails](#)
- [RuleGroupVariables](#)
- [RuleGroupVariablesIpSetsDetails](#)
- [RuleGroupVariablesPortSetsDetails](#)
- [NetworkHeader](#)
- [FirewallPolicyStatefulRuleGroupReferencesDetails](#)
- [FirewallPolicyStatelessRuleGroupReferencesDetails](#)

AwsNetworkFirewallFirewallDetails

Details about an Amazon Network Firewall firewall.

Contents

DeleteProtection

Whether the firewall is protected from deletion. If set to `true`, then the firewall cannot be deleted.

Type: Boolean

Required: No

Description

A description of the firewall.

Type: String

Pattern: `.*\S.*`

Required: No

FirewallArn

The ARN of the firewall.

Type: String

Pattern: `.*\S.*`

Required: No

FirewallId

The identifier of the firewall.

Type: String

Pattern: `.*\S.*`

Required: No

FirewallName

A descriptive name of the firewall.

Type: String

Pattern: `.*\S.*`

Required: No

FirewallPolicyArn

The ARN of the firewall policy.

Type: String

Pattern: `.*\S.*`

Required: No

FirewallPolicyChangeProtection

Whether the firewall is protected from a change to the firewall policy. If set to `true`, you cannot associate a different policy with the firewall.

Type: Boolean

Required: No

SubnetChangeProtection

Whether the firewall is protected from a change to the subnet associations. If set to `true`, you cannot map different subnets to the firewall.

Type: Boolean

Required: No

SubnetMappings

The public subnets that Network Firewall uses for the firewall. Each subnet must belong to a different Availability Zone.

Type: Array of [AwsNetworkFirewallFirewallSubnetMappingsDetails](#) objects

Required: No

VpcId

The identifier of the VPC where the firewall is used.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsNetworkFirewallFirewallPolicyDetails

Details about a firewall policy. A firewall policy defines the behavior of a network firewall.

Contents

Description

A description of the firewall policy.

Type: String

Pattern: `.*\S.*`

Required: No

FirewallPolicy

The firewall policy configuration.

Type: [FirewallPolicyDetails](#) object

Required: No

FirewallPolicyArn

The ARN of the firewall policy.

Type: String

Pattern: `.*\S.*`

Required: No

FirewallPolicyId

The identifier of the firewall policy.

Type: String

Pattern: `.*\S.*`

Required: No

FirewallPolicyName

The name of the firewall policy.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

FirewallPolicyDetails

Defines the behavior of the firewall.

Contents

StatefulRuleGroupReferences

The stateful rule groups that are used in the firewall policy.

Type: Array of [FirewallPolicyStatefulRuleGroupReferencesDetails](#) objects

Required: No

StatelessCustomActions

The custom action definitions that are available to use in the firewall policy's `StatelessDefaultActions` setting.

Type: Array of [FirewallPolicyStatelessCustomActionsDetails](#) objects

Required: No

StatelessDefaultActions

The actions to take on a packet if it doesn't match any of the stateless rules in the policy.

You must specify a standard action (`aws:pass`, `aws:drop`, `aws:forward_to_sfe`), and can optionally include a custom action from `StatelessCustomActions`.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

StatelessFragmentDefaultActions

The actions to take on a fragmented UDP packet if it doesn't match any of the stateless rules in the policy.

You must specify a standard action (`aws:pass`, `aws:drop`, `aws:forward_to_sfe`), and can optionally include a custom action from `StatelessCustomActions`.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

StatelessRuleGroupReferences

The stateless rule groups that are used in the firewall policy.

Type: Array of [FirewallPolicyStatelessRuleGroupReferencesDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

FirewallPolicyStatelessCustomActionsDetails

A custom action that can be used for stateless packet handling.

Contents

ActionDefinition

The definition of the custom action.

Type: [StatelessCustomActionDefinition](#) object

Required: No

ActionName

The name of the custom action.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StatelessCustomActionDefinition

The definition of a custom action that can be used for stateless packet handling.

Contents

PublishMetricAction

Information about metrics to publish to CloudWatch.

Type: [StatelessCustomPublishMetricAction](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StatelessCustomPublishMetricAction

Information about metrics to publish to CloudWatch.

Contents

Dimensions

Defines CloudWatch dimension values to publish.

Type: Array of [StatelessCustomPublishMetricActionDimension](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StatelessCustomPublishMetricActionDimension

Defines a CloudWatch dimension value to publish.

Contents

Value

The value to use for the custom metric dimension.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsNetworkFirewallFirewallSubnetMappingsDetails

A public subnet that Network Firewall uses for the firewall.

Contents

SubnetId

The identifier of the subnet

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsNetworkFirewallRuleGroupDetails

Details about an Amazon Network Firewall rule group. Rule groups are used to inspect and control network traffic. Stateless rule groups apply to individual packets. Stateful rule groups apply to packets in the context of their traffic flow.

Rule groups are referenced in firewall policies.

Contents

Capacity

The maximum number of operating resources that this rule group can use.

Type: Integer

Required: No

Description

A description of the rule group.

Type: String

Pattern: `.*\S.*`

Required: No

RuleGroup

Details about the rule group.

Type: [RuleGroupDetails](#) object

Required: No

RuleGroupArn

The ARN of the rule group.

Type: String

Pattern: `.*\S.*`

Required: No

RuleGroupId

The identifier of the rule group.

Type: String

Pattern: `.*\S.*`

Required: No

RuleGroupName

The descriptive name of the rule group.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The type of rule group. A rule group can be stateful or stateless.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupDetails

Details about the rule group.

Contents

RulesSource

The rules and actions for the rule group.

For stateful rule groups, can contain `RulesString`, `RulesSourceList`, or `StatefulRules`.

For stateless rule groups, contains `StatelessRulesAndCustomActions`.

Type: [RuleGroupSource](#) object

Required: No

RuleVariables

Additional settings to use in the specified rules.

Type: [RuleGroupVariables](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupSource

The rules and actions for the rule group.

Contents

RulesSourceList

Stateful inspection criteria for a domain list rule group. A domain list rule group determines access by specific protocols to specific domains.

Type: [RuleGroupSourceListDetails](#) object

Required: No

RulesString

Stateful inspection criteria, provided in Suricata compatible intrusion prevention system (IPS) rules.

Type: String

Pattern: `.*\S.*`

Required: No

StatefulRules

Suricata rule specifications.

Type: Array of [RuleGroupSourceStatefulRulesDetails](#) objects

Required: No

StatelessRulesAndCustomActions

The stateless rules and custom actions used by a stateless rule group.

Type: [RuleGroupSourceStatelessRulesAndCustomActionsDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupSourceCustomActionsDetails

A custom action definition. A custom action is an optional, non-standard action to use for stateless packet handling.

Contents

ActionDefinition

The definition of a custom action.

Type: [StatelessCustomActionDefinition](#) object

Required: No

ActionName

A descriptive name of the custom action.

Type: String

Pattern: .*S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupSourceListDetails

Stateful inspection criteria for a domain list rule group.

Contents

GeneratedRulesType

Indicates whether to allow or deny access to the domains listed in `Targets`.

Type: String

Pattern: `.*\S.*`

Required: No

Targets

The domains that you want to inspect for in your traffic flows. You can provide full domain names, or use the `!` prefix as a wildcard. For example, `.example.com` matches all domains that end with `example.com`.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

TargetTypes

The protocols that you want to inspect. Specify `LS_SNI` for HTTPS. Specify `HTTP_HOST` for HTTP. You can specify either or both.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupSourceStatefulRulesDetails

A Suricata rule specification.

Contents

Action

Defines what Network Firewall should do with the packets in a traffic flow when the flow matches the stateful rule criteria.

Type: String

Pattern: .*\\S.*

Required: No

Header

The stateful inspection criteria for the rule.

Type: [RuleGroupSourceStatefulRulesHeaderDetails](#) object

Required: No

RuleOptions

Additional options for the rule.

Type: Array of [RuleGroupSourceStatefulRulesOptionsDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupSourceStatefulRulesHeaderDetails

The inspection criteria for a stateful rule.

Contents

Destination

The destination IP address or address range to inspect for, in CIDR notation. To match with any address, specify ANY.

Type: String

Pattern: `.*\S.*`

Required: No

DestinationPort

The destination port to inspect for. You can specify an individual port, such as 1994. You also can specify a port range, such as 1990:1994. To match with any port, specify ANY.

Type: String

Pattern: `.*\S.*`

Required: No

Direction

The direction of traffic flow to inspect. If set to ANY, the inspection matches bidirectional traffic, both from the source to the destination and from the destination to the source. If set to FORWARD, the inspection only matches traffic going from the source to the destination.

Type: String

Pattern: `.*\S.*`

Required: No

Protocol

The protocol to inspect for. To inspect for all protocols, use IP.

Type: String

Pattern: `.*\S.*`

Required: No

Source

The source IP address or address range to inspect for, in CIDR notation. To match with any address, specify ANY.

Type: String

Pattern: `.*\S.*`

Required: No

SourcePort

The source port to inspect for. You can specify an individual port, such as 1994. You also can specify a port range, such as 1990:1994. To match with any port, specify ANY.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupSourceStatefulRulesOptionsDetails

A rule option for a stateful rule.

Contents

Keyword

A keyword to look for.

Type: String

Pattern: `.*\S.*`

Required: No

Settings

A list of settings.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupSourceStatelessRuleDefinition

The definition of the stateless rule.

Contents

Actions

The actions to take on a packet that matches one of the stateless rule definition's match attributes. You must specify a standard action (`aws:pass`, `aws:drop`, or `aws:forward_to_sfe`). You can then add custom actions.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

MatchAttributes

The criteria for Network Firewall to use to inspect an individual packet in a stateless rule inspection.

Type: [RuleGroupSourceStatelessRuleMatchAttributes](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupSourceStatelessRuleMatchAttributes

Criteria for the stateless rule.

Contents

DestinationPorts

A list of port ranges to specify the destination ports to inspect for.

Type: Array of [RuleGroupSourceStatelessRuleMatchAttributesDestinationPorts](#) objects

Required: No

Destinations

The destination IP addresses and address ranges to inspect for, in CIDR notation.

Type: Array of [RuleGroupSourceStatelessRuleMatchAttributesDestinations](#) objects

Required: No

Protocols

The protocols to inspect for.

Type: Array of integers

Required: No

SourcePorts

A list of port ranges to specify the source ports to inspect for.

Type: Array of [RuleGroupSourceStatelessRuleMatchAttributesSourcePorts](#) objects

Required: No

Sources

The source IP addresses and address ranges to inspect for, in CIDR notation.

Type: Array of [RuleGroupSourceStatelessRuleMatchAttributesSources](#) objects

Required: No

TcpFlags

The TCP flags and masks to inspect for.

Type: Array of [RuleGroupSourceStatelessRuleMatchAttributesTcpFlags](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupSourceStatelessRuleMatchAttributesDestinationPorts

A port range to specify the destination ports to inspect for.

Contents

FromPort

The starting port value for the port range.

Type: Integer

Required: No

ToPort

The ending port value for the port range.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupSourceStatelessRuleMatchAttributesDestinations

A destination IP address or range.

Contents

AddressDefinition

An IP address or a block of IP addresses.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupSourceStatelessRuleMatchAttributesSourcePorts

A port range to specify the source ports to inspect for.

Contents

FromPort

The starting port value for the port range.

Type: Integer

Required: No

ToPort

The ending port value for the port range.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupSourceStatelessRuleMatchAttributesSources

A source IP addresses and address range to inspect for.

Contents

AddressDefinition

An IP address or a block of IP addresses.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupSourceStatelessRuleMatchAttributesTcpFlags

A set of TCP flags and masks to inspect for.

Contents

Flags

Defines the flags from the Masks setting that must be set in order for the packet to match. Flags that are listed must be set. Flags that are not listed must not be set.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Masks

The set of flags to consider in the inspection. If not specified, then all flags are inspected.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupSourceStatelessRulesAndCustomActionsDetails

Stateless rules and custom actions for a stateless rule group.

Contents

CustomActions

Custom actions for the rule group.

Type: Array of [RuleGroupSourceCustomActionsDetails](#) objects

Required: No

StatelessRules

Stateless rules for the rule group.

Type: Array of [RuleGroupSourceStatelessRulesDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupSourceStatelessRulesDetails

A stateless rule in the rule group.

Contents

Priority

Indicates the order in which to run this rule relative to all of the rules in the stateless rule group.

Type: Integer

Required: No

RuleDefinition

Provides the definition of the stateless rule.

Type: [RuleGroupSourceStatelessRuleDefinition](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupVariables

Additional settings to use in the specified rules.

Contents

IpSets

A list of IP addresses and address ranges, in CIDR notation.

Type: [RuleGroupVariablesIpSetsDetails](#) object

Required: No

PortSets

A list of port ranges.

Type: [RuleGroupVariablesPortSetsDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupVariablesIpSetsDetails

A list of IP addresses and address ranges, in CIDR notation.

Contents

Definition

The list of IP addresses and ranges.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RuleGroupVariablesPortSetsDetails

A list of port ranges.

Contents

Definition

The list of port ranges.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

NetworkHeader

Details about a network path component that occurs before or after the current component.

Contents

Destination

Information about the destination of the component.

Type: [NetworkPathComponentDetails](#) object

Required: No

Protocol

The protocol used for the component.

Length Constraints: Minimum of 1. Maximum of 16.

Type: String

Pattern: .*\\S.*

Required: No

Source

Information about the origin of the component.

Type: [NetworkPathComponentDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

FirewallPolicyStatefulRuleGroupReferencesDetails

A stateful rule group that is used by the firewall policy.

Contents

ResourceArn

The ARN of the stateful rule group.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

FirewallPolicyStatelessRuleGroupReferencesDetails

A stateless rule group that is used by the firewall policy.

Contents

Priority

The order in which to run the stateless rule group.

Type: Integer

Required: No

ResourceArn

The ARN of the stateless rule group.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon OpenSearch Service

Amazon OpenSearch Service objects

- [AwsOpenSearchServiceDomainAdvancedSecurityOptionsDetails](#)
- [AwsOpenSearchServiceDomainClusterConfigDetails](#)
- [AwsOpenSearchServiceDomainClusterConfigZoneAwarenessConfigDetails](#)
- [AwsOpenSearchServiceDomainDetails](#)

- [AwsOpenSearchServiceDomainDomainEndpointOptionsDetails](#)
- [AwsOpenSearchServiceDomainEncryptionAtRestOptionsDetails](#)
- [AwsOpenSearchServiceDomainLogPublishingOption](#)
- [AwsOpenSearchServiceDomainLogPublishingOptionsDetails](#)
- [AwsOpenSearchServiceDomainMasterUserOptionsDetails](#)
- [AwsOpenSearchServiceDomainNodeToNodeEncryptionOptionsDetails](#)
- [AwsOpenSearchServiceDomainServiceSoftwareOptionsDetails](#)
- [AwsOpenSearchServiceDomainVpcOptionsDetails](#)

AwsOpenSearchServiceDomainAdvancedSecurityOptionsDetails

Provides information about domain access control options.

Contents

Enabled

Enables fine-grained access control.

Type: Boolean

Required: No

InternalUserDatabaseEnabled

Enables the internal user database.

Type: Boolean

Required: No

MasterUserOptions

Specifies information about the master user of the domain.

Type: [AwsOpenSearchServiceDomainMasterUserOptionsDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsOpenSearchServiceDomainClusterConfigDetails

Details about the configuration of an OpenSearch cluster.

Contents

DedicatedMasterCount

The number of instances to use for the master node. If this attribute is specified, then `DedicatedMasterEnabled` must be `true`.

Type: Integer

Required: No

DedicatedMasterEnabled

Whether to use a dedicated master node for the OpenSearch domain. A dedicated master node performs cluster management tasks, but does not hold data or respond to data upload requests.

Type: Boolean

Required: No

DedicatedMasterType

The hardware configuration of the computer that hosts the dedicated master node.

If this attribute is specified, then `DedicatedMasterEnabled` must be `true`.

Type: String

Pattern: `.*\S.*`

Required: No

InstanceCount

The number of data nodes to use in the OpenSearch domain.

Type: Integer

Required: No

InstanceType

The instance type for your data nodes.

For a list of valid values, see [Supported instance types in Amazon OpenSearch Service](#) in the *Amazon OpenSearch Service Developer Guide*.

Type: String

Pattern: `.*\S.*`

Required: No

WarmCount

The number of UltraWarm instances.

Type: Integer

Required: No

WarmEnabled

Whether UltraWarm is enabled.

Type: Boolean

Required: No

WarmType

The type of UltraWarm instance.

Type: String

Pattern: `.*\S.*`

Required: No

ZoneAwarenessConfig

Configuration options for zone awareness. Provided if `ZoneAwarenessEnabled` is true.

Type: [AwsOpenSearchServiceDomainClusterConfigZoneAwarenessConfigDetails](#) object

Required: No

ZoneAwarenessEnabled

Whether to enable zone awareness for the OpenSearch domain. When zone awareness is enabled, OpenSearch Service allocates the cluster's nodes and replica index shards across Availability Zones (AZs) in the same Region. This prevents data loss and minimizes downtime if a node or data center fails.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsOpenSearchServiceDomainClusterConfigZoneAwarenessConfigDetails

Configuration options for zone awareness.

Contents

AvailabilityZoneCount

The number of Availability Zones that the domain uses. Valid values are 2 or 3. The default is 2.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsOpenSearchServiceDomainDetails

Information about an Amazon OpenSearch Service domain.

Contents

AccessPolicies

IAM policy document that specifies the access policies for the OpenSearch Service domain.

Type: String

Pattern: `.*\S.*`

Required: No

AdvancedSecurityOptions

Specifies options for fine-grained access control.

Type: [AwsOpenSearchServiceDomainAdvancedSecurityOptionsDetails](#) object

Required: No

Arn

The ARN of the OpenSearch Service domain.

Type: String

Pattern: `.*\S.*`

Required: No

ClusterConfig

Details about the configuration of an OpenSearch cluster.

Type: [AwsOpenSearchServiceDomainClusterConfigDetails](#) object

Required: No

DomainEndpoint

The domain endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

DomainEndpointOptions

Additional options for the domain endpoint.

Type: [AwsOpenSearchServiceDomainDomainEndpointOptionsDetails](#) object

Required: No

DomainEndpoints

The domain endpoints. Used if the OpenSearch domain resides in a VPC.

This is a map of key-value pairs. The key is always `vpc`. The value is the endpoint.

Type: String to string map

Key Pattern: `.*\S.*`

Value Pattern: `.*\S.*`

Required: No

DomainName

The name of the endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

EncryptionAtRestOptions

Details about the configuration for encryption at rest.

Type: [AwsOpenSearchServiceDomainEncryptionAtRestOptionsDetails](#) object

Required: No

EngineVersion

The version of the domain engine.

Type: String

Pattern: `.*\S.*`

Required: No

Id

The identifier of the domain.

Type: String

Pattern: `.*\S.*`

Required: No

LogPublishingOptions

Configures the CloudWatch Logs to publish for the OpenSearch domain.

Type: [AwsOpenSearchServiceDomainLogPublishingOptionsDetails](#) object

Required: No

NodeToNodeEncryptionOptions

Details about the configuration for node-to-node encryption.

Type: [AwsOpenSearchServiceDomainNodeToNodeEncryptionOptionsDetails](#) object

Required: No

ServiceSoftwareOptions

Information about the status of a domain relative to the latest service software.

Type: [AwsOpenSearchServiceDomainServiceSoftwareOptionsDetails](#) object

Required: No

VpcOptions

Information that OpenSearch Service derives based on VPCOptions for the domain.

Type: [AwsOpenSearchServiceDomainVpcOptionsDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsOpenSearchServiceDomainDomainEndpointOptionsDetails

Information about additional options for the domain endpoint.

Contents

CustomEndpoint

The fully qualified URL for the custom endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

CustomEndpointCertificateArn

The ARN for the security certificate. The certificate is managed in ACM.

Type: String

Pattern: `.*\S.*`

Required: No

CustomEndpointEnabled

Whether to enable a custom endpoint for the domain.

Type: Boolean

Required: No

EnforceHTTPS

Whether to require that all traffic to the domain arrive over HTTPS.

Type: Boolean

Required: No

TLSSecurityPolicy

The TLS security policy to apply to the HTTPS endpoint of the OpenSearch domain.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsOpenSearchServiceDomainEncryptionAtRestOptionsDetails

Details about the configuration for encryption at rest for the OpenSearch domain.

Contents

Enabled

Whether encryption at rest is enabled.

Type: Boolean

Required: No

KmsKeyId

The KMS key ID.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsOpenSearchServiceDomainLogPublishingOption

Configuration details for a log publishing option.

Contents

CloudWatchLogsLogGroupArn

The ARN of the CloudWatch Logs group to publish the logs to.

Type: String

Pattern: `.*\S.*`

Required: No

Enabled

Whether the log publishing is enabled.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsOpenSearchServiceDomainLogPublishingOptionsDetails

Configures the CloudWatch Logs to publish for the OpenSearch domain.

Contents

AuditLogs

Configures the OpenSearch audit logs publishing.

Type: [AwsOpenSearchServiceDomainLogPublishingOption](#) object

Required: No

IndexSlowLogs

Configures the OpenSearch index logs publishing.

Type: [AwsOpenSearchServiceDomainLogPublishingOption](#) object

Required: No

SearchSlowLogs

Configures the OpenSearch search slow log publishing.

Type: [AwsOpenSearchServiceDomainLogPublishingOption](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsOpenSearchServiceDomainMasterUserOptionsDetails

Specifies information about the master user of the domain.

Contents

MasterUserArn

The Amazon Resource Name (ARN) for the master user.

Type: String

Pattern: `.*\S.*`

Required: No

MasterUserName

The username for the master user.

Type: String

Pattern: `.*\S.*`

Required: No

MasterUserPassword

The password for the master user.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsOpenSearchServiceDomainNodeToNodeEncryptionOptionsDetails

Provides details about the configuration for node-to-node encryption.

Contents

Enabled

Whether node-to-node encryption is enabled.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsOpenSearchServiceDomainServiceSoftwareOptionsDetails

Provides information about the state of the domain relative to the latest service software.

Contents

AutomatedUpdateDate

The epoch time when the deployment window closes for required updates. After this time, OpenSearch Service schedules the software upgrade automatically.

Type: String

Pattern: `.*\S.*`

Required: No

Cancellable

Whether a request to update the domain can be canceled.

Type: Boolean

Required: No

CurrentVersion

The version of the service software that is currently installed on the domain.

Type: String

Pattern: `.*\S.*`

Required: No

Description

A more detailed description of the service software status.

Type: String

Pattern: `.*\S.*`

Required: No

NewVersion

The most recent version of the service software.

Type: String

Pattern: .*\\S.*

Required: No

OptionalDeployment

Whether the service software update is optional.

Type: Boolean

Required: No

UpdateAvailable

Whether a service software update is available for the domain.

Type: Boolean

Required: No

UpdateStatus

The status of the service software update. Valid values are as follows:

- COMPLETED
- ELIGIBLE
- IN_PROGRESS
- NOT_ELIGIBLE
- PENDING_UPDATE

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsOpenSearchServiceDomainVpcOptionsDetails

Contains information that OpenSearch Service derives based on the VPCOptions for the domain.

Contents

SecurityGroupIds

The list of security group IDs that are associated with the VPC endpoints for the domain.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

SubnetIds

A list of subnet IDs that are associated with the VPC endpoints for the domain.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Relational Database Service (RDS) objects

Amazon Relational Database Service (RDS) objects

- [AwsRdsDbClusterAssociatedRole](#)
- [AwsRdsDbClusterDetails](#)

- [AwsRdsDbClusterMember](#)
- [AwsRdsDbClusterOptionGroupMembership](#)
- [AwsRdsDbClusterSnapshotDbClusterSnapshotAttribute](#)
- [AwsRdsDbClusterSnapshotDetails](#)
- [AwsRdsDbDomainMembership](#)
- [AwsRdsDbInstanceAssociatedRole](#)
- [AwsRdsDbInstanceDetails](#)
- [AwsRdsDbInstanceEndpoint](#)
- [AwsRdsDbInstanceVpcSecurityGroup](#)
- [AwsRdsDbOptionGroupMembership](#)
- [AwsRdsDbParameterGroup](#)
- [AwsRdsDbPendingModifiedValues](#)
- [AwsRdsDbProcessorFeature](#)
- [AwsRdsDbSecurityGroupDetails](#)
- [AwsRdsDbSecurityGroupEc2SecurityGroup](#)
- [AwsRdsDbSecurityGroupIpRange](#)
- [AwsRdsDbSnapshotDetails](#)
- [AwsRdsDbStatusInfo](#)
- [AwsRdsDbSubnetGroup](#)
- [AwsRdsDbSubnetGroupSubnet](#)
- [AwsRdsDbSubnetGroupSubnetAvailabilityZone](#)
- [AwsRdsEventSubscriptionDetails](#)
- [AwsRdsPendingCloudWatchLogsExports](#)

AwsRdsDbClusterAssociatedRole

An IAM role that is associated with the Amazon RDS DB cluster.

Contents

RoleArn

The ARN of the IAM role.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The status of the association between the IAM role and the DB cluster. Valid values are as follows:

- ACTIVE
- INVALID
- PENDING

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbClusterDetails

Information about an Amazon RDS DB cluster.

Contents

ActivityStreamStatus

The status of the database activity stream. Valid values are as follows:

- started
- starting
- stopped
- stopping

Type: String

Pattern: `.*\S.*`

Required: No

AllocatedStorage

For all database engines except Aurora, specifies the allocated storage size in gibibytes (GiB).

Type: Integer

Required: No

AssociatedRoles

A list of the IAM roles that are associated with the DB cluster.

Type: Array of [AwsRdsDbClusterAssociatedRole](#) objects

Required: No

AutoMinorVersionUpgrade

Indicates if minor version upgrades are automatically applied to the cluster.

Type: Boolean

Required: No

AvailabilityZones

A list of Availability Zones (AZs) where instances in the DB cluster can be created.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

BackupRetentionPeriod

The number of days for which automated backups are retained.

Type: Integer

Required: No

ClusterCreateTime

Indicates when the DB cluster was created, in Universal Coordinated Time (UTC).

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

CopyTagsToSnapshot

Whether tags are copied from the DB cluster to snapshots of the DB cluster.

Type: Boolean

Required: No

CrossAccountClone

Whether the DB cluster is a clone of a DB cluster owned by a different Amazon account.

Type: Boolean

Required: No

CustomEndpoints

A list of custom endpoints for the DB cluster.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

DatabaseName

The name of the database.

Type: String

Pattern: `.*\S.*`

Required: No

DbClusterIdentifier

The DB cluster identifier that the user assigned to the cluster. This identifier is the unique key that identifies a DB cluster.

Type: String

Pattern: `.*\S.*`

Required: No

DbClusterMembers

The list of instances that make up the DB cluster.

Type: Array of [AwsRdsDbClusterMember](#) objects

Required: No

DbClusterOptionGroupMemberships

The list of option group memberships for this DB cluster.

Type: Array of [AwsRdsDbClusterOptionGroupMembership](#) objects

Required: No

DbClusterParameterGroup

The name of the DB cluster parameter group for the DB cluster.

Type: String

Pattern: `.*\S.*`

Required: No

DbClusterResourceId

The identifier of the DB cluster. The identifier must be unique within each Amazon Web Services Region and is immutable.

Type: String

Pattern: `.*\S.*`

Required: No

DbSubnetGroup

The subnet group that is associated with the DB cluster, including the name, description, and subnets in the subnet group.

Type: String

Pattern: `.*\S.*`

Required: No

DeletionProtection

Whether the DB cluster has deletion protection enabled.

Type: Boolean

Required: No

DomainMemberships

The Active Directory domain membership records that are associated with the DB cluster.

Type: Array of [AwsRdsDbDomainMembership](#) objects

Required: No

EnabledCloudWatchLogsExports

A list of log types that this DB cluster is configured to export to CloudWatch Logs.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Endpoint

The connection endpoint for the primary instance of the DB cluster.

Type: String

Pattern: `.*\S.*`

Required: No

Engine

The name of the database engine to use for this DB cluster. Valid values are as follows:

- `aurora`
- `aurora-mysql`
- `aurora-postgresql`

Type: String

Pattern: `.*\S.*`

Required: No

EngineMode

The database engine mode of the DB cluster. Valid values are as follows:

- `global`
- `multimaster`
- `parallelquery`
- `provisioned`
- `serverless`

Type: String

Pattern: .*\\S.*

Required: No

EngineVersion

The version number of the database engine to use.

Type: String

Pattern: .*\\S.*

Required: No

HostedZoneId

Specifies the identifier that Amazon Route 53 assigns when you create a hosted zone.

Type: String

Pattern: .*\\S.*

Required: No

HttpEndpointEnabled

Whether the HTTP endpoint for an Aurora Serverless DB cluster is enabled.

Type: Boolean

Required: No

IamDatabaseAuthenticationEnabled

Whether the mapping of IAM accounts to database accounts is enabled.

Type: Boolean

Required: No

KmsKeyId

The ARN of the Amazon KMS master key that is used to encrypt the database instances in the DB cluster.

Type: String

Pattern: `.*\S.*`

Required: No

MasterUsername

The name of the master user for the DB cluster.

Type: String

Pattern: `.*\S.*`

Required: No

MultiAz

Whether the DB cluster has instances in multiple Availability Zones.

Type: Boolean

Required: No

Port

The port number on which the DB instances in the DB cluster accept connections.

Type: Integer

Required: No

PreferredBackupWindow

The range of time each day when automated backups are created, if automated backups are enabled.

Uses the format `HH:MM-HH:MM`. For example, `04:52-05:22`.

Type: String

Pattern: `.*\S.*`

Required: No

PreferredMaintenanceWindow

The weekly time range during which system maintenance can occur, in Universal Coordinated Time (UTC).

Uses the format <day>:HH:MM-<day>:HH:MM.

For the day values, use mon|tue|wed|thu|fri|sat|sun.

For example, sun:09:32-sun:10:02.

Type: String

Pattern: .*\\S.*

Required: No

ReaderEndpoint

The reader endpoint for the DB cluster.

Type: String

Pattern: .*\\S.*

Required: No

ReadReplicaIdentifiers

The identifiers of the read replicas that are associated with this DB cluster.

Type: Array of strings

Pattern: .*\\S.*

Required: No

Status

The current status of this DB cluster.

Type: String

Pattern: .*\\S.*

Required: No

StorageEncrypted

Whether the DB cluster is encrypted.

Type: Boolean

Required: No

VpcSecurityGroups

A list of VPC security groups that the DB cluster belongs to.

Type: Array of [AwsRdsDbInstanceVpcSecurityGroup](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbClusterMember

Information about an instance in the DB cluster.

Contents

DbClusterParameterGroupStatus

The status of the DB cluster parameter group for this member of the DB cluster.

Type: String

Pattern: `.*\S.*`

Required: No

DbInstanceIdentifier

The instance identifier for this member of the DB cluster.

Type: String

Pattern: `.*\S.*`

Required: No

IsClusterWriter

Whether the cluster member is the primary instance for the DB cluster.

Type: Boolean

Required: No

PromotionTier

Specifies the order in which an Aurora replica is promoted to the primary instance when the existing primary instance fails.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbClusterOptionGroupMembership

Information about an option group membership for a DB cluster.

Contents

DbClusterOptionGroupName

The name of the DB cluster option group.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The status of the DB cluster option group.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbClusterSnapshotDbClusterSnapshotAttribute

Contains the name and values of a manual Amazon Relational Database Service (RDS) DB cluster snapshot attribute.

Contents

AttributeName

The name of the manual DB cluster snapshot attribute. The attribute named `restore` refers to the list of Amazon Web Services accounts that have permission to copy or restore the manual DB cluster snapshot.

Type: String

Pattern: `.*\S.*`

Required: No

AttributeValues

The value(s) for the manual DB cluster snapshot attribute. If the `AttributeName` field is set to `restore`, then this element returns a list of IDs of the Amazon Web Services accounts that are authorized to copy or restore the manual DB cluster snapshot. If a value of `all` is in the list, then the manual DB cluster snapshot is public and available for any Amazon Web Services account to copy or restore.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbClusterSnapshotDetails

Information about an Amazon RDS DB cluster snapshot.

Contents

AllocatedStorage

Specifies the allocated storage size in gibibytes (GiB).

Type: Integer

Required: No

AvailabilityZones

A list of Availability Zones where instances in the DB cluster can be created.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

ClusterCreateTime

Indicates when the DB cluster was created, in Universal Coordinated Time (UTC).

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

DbClusterIdentifier

The DB cluster identifier.

Type: String

Pattern: `.*\S.*`

Required: No

DbClusterSnapshotAttributes

Contains the name and values of a manual DB cluster snapshot attribute.

Type: Array of [AwsRdsDbClusterSnapshotDbClusterSnapshotAttribute](#) objects

Required: No

DbClusterSnapshotIdentifier

The identifier of the DB cluster snapshot.

Type: String

Pattern: `.*\S.*`

Required: No

Engine

The name of the database engine that you want to use for this DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

EngineVersion

The version of the database engine to use.

Type: String

Pattern: `.*\S.*`

Required: No

IamDatabaseAuthenticationEnabled

Whether mapping of IAM accounts to database accounts is enabled.

Type: Boolean

Required: No

KmsKeyId

The ARN of the Amazon KMS master key that is used to encrypt the database instances in the DB cluster.

Type: String

Pattern: `.*\S.*`

Required: No

LicenseModel

The license model information for this DB cluster snapshot.

Type: String

Pattern: `.*\S.*`

Required: No

MasterUsername

The name of the master user for the DB cluster.

Type: String

Pattern: `.*\S.*`

Required: No

PercentProgress

Specifies the percentage of the estimated data that has been transferred.

Type: Integer

Required: No

Port

The port number on which the DB instances in the DB cluster accept connections.

Type: Integer

Required: No

SnapshotCreateTime

Indicates when the snapshot was taken.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

SnapshotType

The type of DB cluster snapshot.

Type: String

Pattern: .*\\S.*

Required: No

Status

The status of this DB cluster snapshot.

Type: String

Pattern: .*\\S.*

Required: No

StorageEncrypted

Whether the DB cluster is encrypted.

Type: Boolean

Required: No

VpcId

The VPC ID that is associated with the DB cluster snapshot.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbDomainMembership

Information about an Active Directory domain membership record associated with the DB instance.

Contents

Domain

The identifier of the Active Directory domain.

Type: String

Pattern: `.*\S.*`

Required: No

Fqdn

The fully qualified domain name of the Active Directory domain.

Type: String

Pattern: `.*\S.*`

Required: No

IamRoleName

The name of the IAM role to use when making API calls to the Directory Service.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The status of the Active Directory Domain membership for the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbInstanceAssociatedRole

An IAM role associated with the DB instance.

Contents

FeatureName

The name of the feature associated with the IAM role.

Type: String

Pattern: `.*\S.*`

Required: No

RoleArn

The ARN of the IAM role that is associated with the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

Status

Describes the state of the association between the IAM role and the DB instance. The Status property returns one of the following values:

- **ACTIVE** - The IAM role ARN is associated with the DB instance and can be used to access other Amazon services on your behalf.
- **PENDING** - The IAM role ARN is being associated with the DB instance.
- **INVALID** - The IAM role ARN is associated with the DB instance. But the DB instance is unable to assume the IAM role in order to access other Amazon services on your behalf.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbInstanceDetails

Contains the details of an Amazon RDS DB instance.

Contents

AllocatedStorage

The amount of storage (in gigabytes) to initially allocate for the DB instance.

Type: Integer

Required: No

AssociatedRoles

The IAM roles associated with the DB instance.

Type: Array of [AwsRdsDbInstanceAssociatedRole](#) objects

Required: No

AutoMinorVersionUpgrade

Indicates whether minor version patches are applied automatically.

Type: Boolean

Required: No

AvailabilityZone

The Availability Zone where the DB instance will be created.

Type: String

Pattern: `.*\S.*`

Required: No

BackupRetentionPeriod

The number of days for which to retain automated backups.

Type: Integer

Required: No

CACertificateIdentifier

The identifier of the CA certificate for this DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

CharacterSetName

The name of the character set that this DB instance is associated with.

Type: String

Pattern: `.*\S.*`

Required: No

CopyTagsToSnapshot

Whether to copy resource tags to snapshots of the DB instance.

Type: Boolean

Required: No

DBClusterIdentifier

If the DB instance is a member of a DB cluster, contains the name of the DB cluster that the DB instance is a member of.

Type: String

Pattern: `.*\S.*`

Required: No

DBInstanceClass

Contains the name of the compute and memory capacity class of the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

DBInstanceIdentifier

Contains a user-supplied database identifier. This identifier is the unique key that identifies a DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

DbInstancePort

Specifies the port that the DB instance listens on. If the DB instance is part of a DB cluster, this can be a different port than the DB cluster port.

Type: Integer

Required: No

DbInstanceStatus

The current status of the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

DbiResourceId

The Amazon Web Services Region-unique, immutable identifier for the DB instance. This identifier is found in CloudTrail log entries whenever the Amazon KMS key for the DB instance is accessed.

Type: String

Pattern: `.*\S.*`

Required: No

DBName

The meaning of this parameter differs according to the database engine you use.

MySQL, MariaDB, SQL Server, PostgreSQL

Contains the name of the initial database of this instance that was provided at create time, if one was specified when the DB instance was created. This same name is returned for the life of the DB instance.

Oracle

Contains the Oracle System ID (SID) of the created DB instance. Not shown when the returned parameters don't apply to an Oracle DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

DbParameterGroups

A list of the DB parameter groups to assign to the DB instance.

Type: Array of [AwsRdsDbParameterGroup](#) objects

Required: No

DbSecurityGroups

A list of the DB security groups to assign to the DB instance.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

DbSubnetGroup

Information about the subnet group that is associated with the DB instance.

Type: [AwsRdsDbSubnetGroup](#) object

Required: No

DeletionProtection

Indicates whether the DB instance has deletion protection enabled.

When deletion protection is enabled, the database cannot be deleted.

Type: Boolean

Required: No

DomainMemberships

The Active Directory domain membership records associated with the DB instance.

Type: Array of [AwsRdsDbDomainMembership](#) objects

Required: No

EnabledCloudWatchLogsExports

A list of log types that this DB instance is configured to export to CloudWatch Logs.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Endpoint

Specifies the connection endpoint.

Type: [AwsRdsDbInstanceEndpoint](#) object

Required: No

Engine

Provides the name of the database engine to use for this DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

EngineVersion

Indicates the database engine version.

Type: String

Pattern: `.*\S.*`

Required: No

EnhancedMonitoringResourceArn

The ARN of the CloudWatch Logs log stream that receives the enhanced monitoring metrics data for the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

IAMDatabaseAuthenticationEnabled

True if mapping of IAM accounts to database accounts is enabled, and otherwise false.

IAM database authentication can be enabled for the following database engines.

- For MySQL 5.6, minor version 5.6.34 or higher
- For MySQL 5.7, minor version 5.7.16 or higher
- Aurora 5.6 or higher

Type: Boolean

Required: No

InstanceCreateTime

Indicates when the DB instance was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

Iops

Specifies the provisioned IOPS (I/O operations per second) for this DB instance.

Type: Integer

Required: No

KmsKeyId

If `StorageEncrypted` is true, the Amazon KMS key identifier for the encrypted DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

LatestRestorableTime

Specifies the latest time to which a database can be restored with point-in-time restore.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

LicenseModel

License model information for this DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

ListenerEndpoint

Specifies the connection endpoint.

Type: [AwsRdsDbInstanceEndpoint](#) object

Required: No

MasterUsername

The master user name of the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

MaxAllocatedStorage

The upper limit to which Amazon RDS can automatically scale the storage of the DB instance.

Type: Integer

Required: No

MonitoringInterval

The interval, in seconds, between points when enhanced monitoring metrics are collected for the DB instance.

Type: Integer

Required: No

MonitoringRoleArn

The ARN for the IAM role that permits Amazon RDS to send enhanced monitoring metrics to CloudWatch Logs.

Type: String

Pattern: `.*\S.*`

Required: No

MultiAz

Whether the DB instance is a multiple Availability Zone deployment.

Type: Boolean

Required: No

OptionGroupMemberships

The list of option group memberships for this DB instance.

Type: Array of [AwsRdsDbOptionGroupMembership](#) objects

Required: No

PendingModifiedValues

Changes to the DB instance that are currently pending.

Type: [AwsRdsDbPendingModifiedValues](#) object

Required: No

PerformanceInsightsEnabled

Indicates whether Performance Insights is enabled for the DB instance.

Type: Boolean

Required: No

PerformanceInsightsKmsKeyId

The identifier of the Amazon KMS key used to encrypt the Performance Insights data.

Type: String

Pattern: `.*\S.*`

Required: No

PerformanceInsightsRetentionPeriod

The number of days to retain Performance Insights data.

Type: Integer

Required: No

PreferredBackupWindow

The range of time each day when automated backups are created, if automated backups are enabled.

Uses the format HH:MM-HH:MM. For example, 04:52-05:22.

Type: String

Pattern: .*\\S.*

Required: No

PreferredMaintenanceWindow

The weekly time range during which system maintenance can occur, in Universal Coordinated Time (UTC).

Uses the format <day>:HH:MM-<day>:HH:MM.

For the day values, use mon|tue|wed|thu|fri|sat|sun.

For example, sun:09:32-sun:10:02.

Type: String

Pattern: .*\\S.*

Required: No

ProcessorFeatures

The number of CPU cores and the number of threads per core for the DB instance class of the DB instance.

Type: Array of [AwsRdsDbProcessorFeature](#) objects

Required: No

PromotionTier

The order in which to promote an Aurora replica to the primary instance after a failure of the existing primary instance.

Type: Integer

Required: No

PubliclyAccessible

Specifies the accessibility options for the DB instance.

A value of true specifies an Internet-facing instance with a publicly resolvable DNS name, which resolves to a public IP address.

A value of false specifies an internal instance with a DNS name that resolves to a private IP address.

Type: Boolean

Required: No

ReadReplicaDBClusterIdentifiers

List of identifiers of Aurora DB clusters to which the RDS DB instance is replicated as a read replica.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

ReadReplicaDBInstanceIdentifiers

List of identifiers of the read replicas associated with this DB instance.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

ReadReplicaSourceDBInstanceIdentifier

If this DB instance is a read replica, contains the identifier of the source DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

SecondaryAvailabilityZone

For a DB instance with multi-Availability Zone support, the name of the secondary Availability Zone.

Type: String

Pattern: `.*\S.*`

Required: No

StatusInfos

The status of a read replica. If the instance isn't a read replica, this is empty.

Type: Array of [AwsRdsDbStatusInfo](#) objects

Required: No

StorageEncrypted

Specifies whether the DB instance is encrypted.

Type: Boolean

Required: No

StorageType

The storage type for the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

TdeCredentialArn

The ARN from the key store with which the instance is associated for TDE encryption.

Type: String

Pattern: `.*\S.*`

Required: No

Timezone

The time zone of the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

VpcSecurityGroups

A list of VPC security groups that the DB instance belongs to.

Type: Array of [AwsRdsDbInstanceVpcSecurityGroup](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbInstanceEndpoint

Specifies the connection endpoint.

Contents

Address

Specifies the DNS address of the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

HostedZoneId

Specifies the ID that Amazon Route 53 assigns when you create a hosted zone.

Type: String

Pattern: `.*\S.*`

Required: No

Port

Specifies the port that the database engine is listening on.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbInstanceVpcSecurityGroup

A VPC security groups that the DB instance belongs to.

Contents

Status

The status of the VPC security group.

Type: String

Pattern: `.*\S.*`

Required: No

VpcSecurityGroupId

The name of the VPC security group.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbOptionGroupMembership

An option group membership.

Contents

OptionGroupName

The name of the option group.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The status of the option group membership.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbParameterGroup

Provides information about a parameter group for a DB instance.

Contents

DbParameterGroupName

The name of the parameter group.

Type: String

Pattern: `.*\S.*`

Required: No

ParameterApplyStatus

The status of parameter updates.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbPendingModifiedValues

Changes to a DB instance that are currently pending.

Contents

AllocatedStorage

The new value of the allocated storage for the DB instance.

Type: Integer

Required: No

BackupRetentionPeriod

The new backup retention period for the DB instance.

Type: Integer

Required: No

CaCertificateIdentifier

The new CA certificate identifier for the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

DbInstanceClass

The new DB instance class for the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

DbInstanceIdentifier

The new DB instance identifier for the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

DbSubnetGroupName

The name of the new subnet group for the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

EngineVersion

The new engine version for the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

Iops

The new provisioned IOPS value for the DB instance.

Type: Integer

Required: No

LicenseModel

The new license model value for the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

MasterUserPassword

The new master user password for the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

MultiAZ

Indicates that a single Availability Zone DB instance is changing to a multiple Availability Zone deployment.

Type: Boolean

Required: No

PendingCloudWatchLogsExports

A list of log types that are being enabled or disabled.

Type: [AwsRdsPendingCloudWatchLogsExports](#) object

Required: No

Port

The new port for the DB instance.

Type: Integer

Required: No

ProcessorFeatures

Processor features that are being updated.

Type: Array of [AwsRdsDbProcessorFeature](#) objects

Required: No

StorageType

The new storage type for the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbProcessorFeature

A processor feature.

Contents

Name

The name of the processor feature. Valid values are `coreCount` or `threadsPerCore`.

Type: String

Pattern: `.*\S.*`

Required: No

Value

The value of the processor feature.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbSecurityGroupDetails

Provides information about an Amazon RDS DB security group.

Contents

DbSecurityGroupArn

The ARN for the DB security group.

Type: String

Pattern: `.*\S.*`

Required: No

DbSecurityGroupDescription

Provides the description of the DB security group.

Type: String

Pattern: `.*\S.*`

Required: No

DbSecurityGroupName

Specifies the name of the DB security group.

Type: String

Pattern: `.*\S.*`

Required: No

Ec2SecurityGroups

Contains a list of EC2 security groups.

Type: Array of [AwsRdsDbSecurityGroupEc2SecurityGroup](#) objects

Required: No

IpRanges

Contains a list of IP ranges.

Type: Array of [AwsRdsDbSecurityGroupIpRange](#) objects

Required: No

OwnerId

Provides the Amazon ID of the owner of a specific DB security group.

Type: String

Pattern: `.*\S.*`

Required: No

VpcId

Provides VPC ID associated with the DB security group.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbSecurityGroupEc2SecurityGroup

EC2 security group information for an RDS DB security group.

Contents

Ec2SecurityGroupId

Specifies the ID for the EC2 security group.

Type: String

Pattern: `.*\S.*`

Required: No

Ec2SecurityGroupName

Specifies the name of the EC2 security group.

Type: String

Pattern: `.*\S.*`

Required: No

Ec2SecurityGroupOwnerId

Provides the Amazon ID of the owner of the EC2 security group.

Type: String

Pattern: `.*\S.*`

Required: No

Status

Provides the status of the EC2 security group.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbSecurityGroupIpRange

IP range information for an RDS DB security group.

Contents

CidrIp

Specifies the IP range.

Type: String

Pattern: `.*\S.*`

Required: No

Status

Specifies the status of the IP range.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbSnapshotDetails

Provides details about an Amazon RDS DB cluster snapshot.

Contents

AllocatedStorage

The amount of storage (in gigabytes) to be initially allocated for the database instance.

Type: Integer

Required: No

AvailabilityZone

Specifies the name of the Availability Zone in which the DB instance was located at the time of the DB snapshot.

Type: String

Pattern: `.*\S.*`

Required: No

DbInstanceIdentifier

A name for the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

DbiResourceId

The identifier for the source DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

DbSnapshotIdentifier

The name or ARN of the DB snapshot that is used to restore the DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

Encrypted

Whether the DB snapshot is encrypted.

Type: Boolean

Required: No

Engine

The name of the database engine to use for this DB instance. Valid values are as follows:

- `aurora`
- `aurora-mysql`
- `aurora-postgresql`
- `c`
- `mariadb`
- `mysql`
- `oracle-ee`
- `oracle-se`
- `oracle-se1`
- `oracle-se2`
- `sqlserver-ee`
- `sqlserver-ex`
- `sqlserver-se`
- `sqlserver-web`

Type: String

Pattern: `.*\S.*`

Required: No

EngineVersion

The version of the database engine.

Type: String

Pattern: `.*\S.*`

Required: No

IamDatabaseAuthenticationEnabled

Whether mapping of IAM accounts to database accounts is enabled.

Type: Boolean

Required: No

InstanceCreateTime

Specifies the time in Coordinated Universal Time (UTC) when the DB instance, from which the snapshot was taken, was created.

Type: String

Pattern: `.*\S.*`

Required: No

Iops

The provisioned IOPS (I/O operations per second) value of the DB instance at the time of the snapshot.

Type: Integer

Required: No

KmsKeyId

If Encrypted is `true`, the Amazon KMS key identifier for the encrypted DB snapshot.

Type: String

Pattern: `.*\S.*`

Required: No

LicenseModel

License model information for the restored DB instance.

Type: String

Pattern: `.*\S.*`

Required: No

MasterUsername

The master user name for the DB snapshot.

Type: String

Pattern: `.*\S.*`

Required: No

OptionGroupName

The option group name for the DB snapshot.

Type: String

Pattern: `.*\S.*`

Required: No

PercentProgress

The percentage of the estimated data that has been transferred.

Type: Integer

Required: No

Port

The port that the database engine was listening on at the time of the snapshot.

Type: Integer

Required: No

ProcessorFeatures

The number of CPU cores and the number of threads per core for the DB instance class of the DB instance.

Type: Array of [AwsRdsDbProcessorFeature](#) objects

Required: No

SnapshotCreateTime

When the snapshot was taken in Coordinated Universal Time (UTC).

Type: String

Pattern: `.*\S.*`

Required: No

SnapshotType

The type of the DB snapshot.

Type: String

Pattern: `.*\S.*`

Required: No

SourceDbSnapshotIdentifier

The DB snapshot ARN that the DB snapshot was copied from.

Type: String

Pattern: `.*\S.*`

Required: No

SourceRegion

The Amazon Web Services Region that the DB snapshot was created in or copied from.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The status of this DB snapshot.

Type: String

Pattern: `.*\S.*`

Required: No

StorageType

The storage type associated with the DB snapshot. Valid values are as follows:

- gp2
- io1
- standard

Type: String

Pattern: `.*\S.*`

Required: No

TdeCredentialArn

The ARN from the key store with which to associate the instance for TDE encryption.

Type: String

Pattern: `.*\S.*`

Required: No

Timezone

The time zone of the DB snapshot.

Type: String

Pattern: `.*\S.*`

Required: No

VpcId

The VPC ID associated with the DB snapshot.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbStatusInfo

Information about the status of a read replica.

Contents

Message

If the read replica is currently in an error state, provides the error details.

Type: String

Pattern: `.*\S.*`

Required: No

Normal

Whether the read replica instance is operating normally.

Type: Boolean

Required: No

Status

The status of the read replica instance.

Type: String

Pattern: `.*\S.*`

Required: No

StatusType

The type of status. For a read replica, the status type is read replication.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbSubnetGroup

Information about the subnet group for the database instance.

Contents

DbSubnetGroupArn

The ARN of the subnet group.

Type: String

Pattern: `.*\S.*`

Required: No

DbSubnetGroupDescription

The description of the subnet group.

Type: String

Pattern: `.*\S.*`

Required: No

DbSubnetGroupName

The name of the subnet group.

Type: String

Pattern: `.*\S.*`

Required: No

SubnetGroupStatus

The status of the subnet group.

Type: String

Pattern: `.*\S.*`

Required: No

Subnets

A list of subnets in the subnet group.

Type: Array of [AwsRdsDbSubnetGroupSubnet](#) objects

Required: No

VpcId

The VPC ID of the subnet group.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbSubnetGroupSubnet

Information about a subnet in a subnet group.

Contents

SubnetAvailabilityZone

Information about the Availability Zone for a subnet in the subnet group.

Type: [AwsRdsDbSubnetGroupSubnetAvailabilityZone](#) object

Required: No

SubnetIdentifier

The identifier of a subnet in the subnet group.

Type: String

Pattern: `.*\S.*`

Required: No

SubnetStatus

The status of a subnet in the subnet group.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsDbSubnetGroupSubnetAvailabilityZone

An Availability Zone for a subnet in a subnet group.

Contents

Name

The name of the Availability Zone for a subnet in the subnet group.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsEventSubscriptionDetails

Details about an Amazon RDS event notification subscription. The subscription allows Amazon RDS to post events to an SNS topic.

Contents

CustomerAwsId

The identifier of the event notification subscription.

Type: String

Pattern: `.*\S.*`

Required: No

CustSubscriptionId

The identifier of the account that is associated with the event notification subscription.

Type: String

Pattern: `.*\S.*`

Required: No

Enabled

Whether the event notification subscription is enabled.

Type: Boolean

Required: No

EventCategoriesList

The list of event categories for the event notification subscription.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

EventSubscriptionArn

The ARN of the event notification subscription.

Type: String

Pattern: `.*\S.*`

Required: No

SnsTopicArn

The ARN of the SNS topic to post the event notifications to.

Type: String

Pattern: `.*\S.*`

Required: No

SourceIdsList

A list of source identifiers for the event notification subscription.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

SourceType

The source type for the event notification subscription.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The status of the event notification subscription.

Valid values: `creating` | `modifying` | `deleting` | `active` | `no-permission` | `topic-not-exist`

Type: String

Pattern: .*\\S.*

Required: No

SubscriptionCreationTime

The datetime when the event notification subscription was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRdsPendingCloudWatchLogsExports

Identifies the log types to enable and disable.

Contents

LogTypesToDisable

A list of log types that are being disabled.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

LogTypesToEnable

A list of log types that are being enabled.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Redshift objects

Amazon Redshift objects

- [AwsRedshiftClusterClusterNode](#)
- [AwsRedshiftClusterClusterParameterGroup](#)

- [AwsRedshiftClusterClusterParameterStatus](#)
- [AwsRedshiftClusterClusterSecurityGroup](#)
- [AwsRedshiftClusterClusterSnapshotCopyStatus](#)
- [AwsRedshiftClusterDeferredMaintenanceWindow](#)
- [AwsRedshiftClusterDetails](#)
- [AwsRedshiftClusterElasticIpStatus](#)
- [AwsRedshiftClusterEndpoint](#)
- [AwsRedshiftClusterHsmStatus](#)
- [AwsRedshiftClusterIamRole](#)
- [AwsRedshiftClusterLoggingStatus](#)
- [AwsRedshiftClusterPendingModifiedValues](#)
- [AwsRedshiftClusterResizeInfo](#)
- [AwsRedshiftClusterRestoreStatus](#)
- [AwsRedshiftClusterVpcSecurityGroup](#)

AwsRedshiftClusterClusterNode

A node in an Amazon Redshift cluster.

Contents

NodeRole

The role of the node. A node might be a leader node or a compute node.

Type: String

Pattern: `.*\S.*`

Required: No

PrivateIpAddress

The private IP address of the node.

Type: String

Pattern: `.*\S.*`

Required: No

PublicIpAddress

The public IP address of the node.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsRedshiftClusterClusterParameterGroup

A cluster parameter group that is associated with an Amazon Redshift cluster.

Contents

ClusterParameterStatusList

The list of parameter statuses.

Type: Array of [AwsRedshiftClusterClusterParameterStatus](#) objects

Required: No

ParameterApplyStatus

The status of updates to the parameters.

Type: String

Pattern: `.*\S.*`

Required: No

ParameterGroupName

The name of the parameter group.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRedshiftClusterClusterParameterStatus

The status of a parameter in a cluster parameter group for an Amazon Redshift cluster.

Contents

ParameterApplyErrorDescription

The error that prevented the parameter from being applied to the database.

Type: String

Pattern: `.*\S.*`

Required: No

ParameterApplyStatus

The status of the parameter. Indicates whether the parameter is in sync with the database, waiting for a cluster reboot, or encountered an error when it was applied.

Valid values: `in-sync` | `pending-reboot` | `applying` | `invalid-parameter` | `apply-deferred` | `apply-error` | `unknown-error`

Type: String

Pattern: `.*\S.*`

Required: No

ParameterName

The name of the parameter.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRedshiftClusterClusterSecurityGroup

A security group that is associated with the cluster.

Contents

ClusterSecurityGroupName

The name of the cluster security group.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The status of the cluster security group.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRedshiftClusterClusterSnapshotCopyStatus

You can configure Amazon Redshift to copy snapshots for a cluster to another Amazon Web Services Region. This parameter provides information about a cross-Region snapshot copy.

Contents

DestinationRegion

The destination Region that snapshots are automatically copied to when cross-Region snapshot copy is enabled.

Type: String

Pattern: `.*\S.*`

Required: No

ManualSnapshotRetentionPeriod

The number of days that manual snapshots are retained in the destination Region after they are copied from a source Region.

If the value is `-1`, then the manual snapshot is retained indefinitely.

Valid values: Either `-1` or an integer between `1` and `3,653`

Type: Integer

Required: No

RetentionPeriod

The number of days to retain automated snapshots in the destination Region after they are copied from a source Region.

Type: Integer

Required: No

SnapshotCopyGrantName

The name of the snapshot copy grant.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRedshiftClusterDeferredMaintenanceWindow

A time windows during which maintenance was deferred for an Amazon Redshift cluster.

Contents

DeferMaintenanceEndTime

The end of the time window for which maintenance was deferred.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

DeferMaintenanceIdentifier

The identifier of the maintenance window.

Type: String

Pattern: `.*\S.*`

Required: No

DeferMaintenanceStartTime

The start of the time window for which maintenance was deferred.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRedshiftClusterDetails

Details about an Amazon Redshift cluster.

Contents

AllowVersionUpgrade

Indicates whether major version upgrades are applied automatically to the cluster during the maintenance window.

Type: Boolean

Required: No

AutomatedSnapshotRetentionPeriod

The number of days that automatic cluster snapshots are retained.

Type: Integer

Required: No

AvailabilityZone

The name of the Availability Zone in which the cluster is located.

Type: String

Pattern: `.*\S.*`

Required: No

ClusterAvailabilityStatus

The availability status of the cluster for queries. Possible values are the following:

- `Available` - The cluster is available for queries.
- `Unavailable` - The cluster is not available for queries.
- `Maintenance` - The cluster is intermittently available for queries due to maintenance activities.
- `Modifying` - The cluster is intermittently available for queries due to changes that modify the cluster.
- `Failed` - The cluster failed and is not available for queries.

Type: String

Pattern: `.*\S.*`

Required: No

ClusterCreateTime

Indicates when the cluster was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

ClusterIdentifier

The unique identifier of the cluster.

Type: String

Pattern: `.*\S.*`

Required: No

ClusterNodes

The nodes in the cluster.

Type: Array of [AwsRedshiftClusterClusterNode](#) objects

Required: No

ClusterParameterGroups

The list of cluster parameter groups that are associated with this cluster.

Type: Array of [AwsRedshiftClusterClusterParameterGroup](#) objects

Required: No

ClusterPublicKey

The public key for the cluster.

Type: String

Pattern: `.*\S.*`

Required: No

ClusterRevisionNumber

The specific revision number of the database in the cluster.

Type: String

Pattern: `.*\S.*`

Required: No

ClusterSecurityGroups

A list of cluster security groups that are associated with the cluster.

Type: Array of [AwsRedshiftClusterClusterSecurityGroup](#) objects

Required: No

ClusterSnapshotCopyStatus

Information about the destination Region and retention period for the cross-Region snapshot copy.

Type: [AwsRedshiftClusterClusterSnapshotCopyStatus](#) object

Required: No

ClusterStatus

The current status of the cluster.

Valid values: `available | available, prep-for-resize | available, resize-cleanup | cancelling-resize | creating | deleting | final-snapshot | hardware-failure | incompatible-hsm | incompatible-network | incompatible-parameters | incompatible-restore | modifying | paused | rebooting | renaming | resizing | rotating-keys | storage-full | updating-hsm`

Type: String

Pattern: `.*\S.*`

Required: No

ClusterSubnetGroupName

The name of the subnet group that is associated with the cluster. This parameter is valid only when the cluster is in a VPC.

Type: String

Pattern: `.*\S.*`

Required: No

ClusterVersion

The version ID of the Amazon Redshift engine that runs on the cluster.

Type: String

Pattern: `.*\S.*`

Required: No

DBName

The name of the initial database that was created when the cluster was created.

The same name is returned for the life of the cluster.

If an initial database is not specified, a database named `devdev` is created by default.

Type: String

Pattern: `.*\S.*`

Required: No

DeferredMaintenanceWindows

List of time windows during which maintenance was deferred.

Type: Array of [AwsRedshiftClusterDeferredMaintenanceWindow](#) objects

Required: No

ElasticIpStatus

Information about the status of the Elastic IP (EIP) address.

Type: [AwsRedshiftClusterElasticIpStatus](#) object

Required: No

ElasticResizeNumberOfNodeOptions

The number of nodes that you can use the elastic resize method to resize the cluster to.

Type: String

Pattern: `.*\S.*`

Required: No

Encrypted

Indicates whether the data in the cluster is encrypted at rest.

Type: Boolean

Required: No

Endpoint

The connection endpoint.

Type: [AwsRedshiftClusterEndpoint](#) object

Required: No

EnhancedVpcRouting

Indicates whether to create the cluster with enhanced VPC routing enabled.

Type: Boolean

Required: No

ExpectedNextSnapshotScheduleTime

Indicates when the next snapshot is expected to be taken. The cluster must have a valid snapshot schedule and have backups enabled.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

ExpectedNextSnapshotScheduleTimeStatus

The status of the next expected snapshot.

Valid values: `OnTrack` | `Pending`

Type: String

Pattern: `.*\S.*`

Required: No

HsmStatus

Information about whether the Amazon Redshift cluster finished applying any changes to hardware security module (HSM) settings that were specified in a modify cluster command.

Type: [AwsRedshiftClusterHsmStatus](#) object

Required: No

IamRoles

A list of IAM roles that the cluster can use to access other Amazon services.

Type: Array of [AwsRedshiftClusterIamRole](#) objects

Required: No

KmsKeyId

The identifier of the Amazon KMS encryption key that is used to encrypt data in the cluster.

Type: String

Pattern: `.*\S.*`

Required: No

LoggingStatus

Information about the logging status of the cluster.

Type: [AwsRedshiftClusterLoggingStatus](#) object

Required: No

MaintenanceTrackName

The name of the maintenance track for the cluster.

Type: String

Pattern: `.*\S.*`

Required: No

ManualSnapshotRetentionPeriod

The default number of days to retain a manual snapshot.

If the value is -1, the snapshot is retained indefinitely.

This setting doesn't change the retention period of existing snapshots.

Valid values: Either -1 or an integer between 1 and 3,653

Type: Integer

Required: No

MasterUsername

The master user name for the cluster. This name is used to connect to the database that is specified in as the value of DBName.

Type: String

Pattern: `.*\S.*`

Required: No

NextMaintenanceWindowStartTime

Indicates the start of the next maintenance window.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

NodeType

The node type for the nodes in the cluster.

Type: String

Pattern: .*\\S.*

Required: No

NumberOfNodes

The number of compute nodes in the cluster.

Type: Integer

Required: No

PendingActions

A list of cluster operations that are waiting to start.

Type: Array of strings

Pattern: .*\\S.*

Required: No

PendingModifiedValues

A list of changes to the cluster that are currently pending.

Type: [AwsRedshiftClusterPendingModifiedValues](#) object

Required: No

PreferredMaintenanceWindow

The weekly time range, in Universal Coordinated Time (UTC), during which system maintenance can occur.

Format: `<day>:HH:MM-<day>:HH:MM`

For the day values, use `mon | tue | wed | thu | fri | sat | sun`

For example, `sun:09:32-sun:10:02`

Type: String

Pattern: `.*\S.*`

Required: No

PubliclyAccessible

Whether the cluster can be accessed from a public network.

Type: Boolean

Required: No

ResizeInfo

Information about the resize operation for the cluster.

Type: [AwsRedshiftClusterResizeInfo](#) object

Required: No

RestoreStatus

Information about the status of a cluster restore action. Only applies to a cluster that was created by restoring a snapshot.

Type: [AwsRedshiftClusterRestoreStatus](#) object

Required: No

SnapshotScheduleIdentifier

A unique identifier for the cluster snapshot schedule.

Type: String

Pattern: `.*\S.*`

Required: No

SnapshotScheduleState

The current state of the cluster snapshot schedule.

Valid values: MODIFYING | ACTIVE | FAILED

Type: String

Pattern: `.*\S.*`

Required: No

VpcId

The identifier of the VPC that the cluster is in, if the cluster is in a VPC.

Type: String

Pattern: `.*\S.*`

Required: No

VpcSecurityGroups

The list of VPC security groups that the cluster belongs to, if the cluster is in a VPC.

Type: Array of [AwsRedshiftClusterVpcSecurityGroup](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRedshiftClusterElasticIpStatus

The status of the elastic IP (EIP) address for an Amazon Redshift cluster.

Contents

ElasticIp

The elastic IP address for the cluster.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The status of the elastic IP address.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRedshiftClusterEndpoint

The connection endpoint for an Amazon Redshift cluster.

Contents

Address

The DNS address of the cluster.

Type: String

Pattern: `.*\S.*`

Required: No

Port

The port that the database engine listens on.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRedshiftClusterHsmStatus

Information about whether an Amazon Redshift cluster finished applying any hardware changes to security module (HSM) settings that were specified in a modify cluster command.

Contents

HsmClientCertificateIdentifier

The name of the HSM client certificate that the Amazon Redshift cluster uses to retrieve the data encryption keys that are stored in an HSM.

Type: String

Pattern: `.*\S.*`

Required: No

HsmConfigurationIdentifier

The name of the HSM configuration that contains the information that the Amazon Redshift cluster can use to retrieve and store keys in an HSM.

Type: String

Pattern: `.*\S.*`

Required: No

Status

Indicates whether the Amazon Redshift cluster has finished applying any HSM settings changes specified in a modify cluster command.

Type: String

Valid values: `active` | `applying`

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRedshiftClusterIamRole

An IAM role that the cluster can use to access other Amazon services.

Contents

ApplyStatus

The status of the IAM role's association with the cluster.

Valid values: `in-sync` | `adding` | `removing`

Type: String

Pattern: `.*\S.*`

Required: No

IamRoleArn

The ARN of the IAM role.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRedshiftClusterLoggingStatus

Provides information about the logging status of the cluster.

Contents

BucketName

The name of the S3 bucket where the log files are stored.

Type: String

Pattern: `.*\S.*`

Required: No

LastFailureMessage

The message indicating that the logs failed to be delivered.

Type: String

Pattern: `.*\S.*`

Required: No

LastFailureTime

The last time when logs failed to be delivered.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

LastSuccessfulDeliveryTime

The last time that logs were delivered successfully.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

LoggingEnabled

Indicates whether logging is enabled.

Type: Boolean

Required: No

S3KeyPrefix

Provides the prefix applied to the log file names.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRedshiftClusterPendingModifiedValues

Changes to the Amazon Redshift cluster that are currently pending.

Contents

AutomatedSnapshotRetentionPeriod

The pending or in-progress change to the automated snapshot retention period.

Type: Integer

Required: No

ClusterIdentifier

The pending or in-progress change to the identifier for the cluster.

Type: String

Pattern: `.*\S.*`

Required: No

ClusterType

The pending or in-progress change to the cluster type.

Type: String

Pattern: `.*\S.*`

Required: No

ClusterVersion

The pending or in-progress change to the service version.

Type: String

Pattern: `.*\S.*`

Required: No

EncryptionType

The encryption type for a cluster.

Type: String

Pattern: `.*\S.*`

Required: No

EnhancedVpcRouting

Indicates whether to create the cluster with enhanced VPC routing enabled.

Type: Boolean

Required: No

MaintenanceTrackName

The name of the maintenance track that the cluster changes to during the next maintenance window.

Type: String

Pattern: `.*\S.*`

Required: No

MasterUserPassword

The pending or in-progress change to the master user password for the cluster.

Type: String

Pattern: `.*\S.*`

Required: No

NodeType

The pending or in-progress change to the cluster's node type.

Type: String

Pattern: `.*\S.*`

Required: No

NumberOfNodes

The pending or in-progress change to the number of nodes in the cluster.

Type: Integer

Required: No

PubliclyAccessible

The pending or in-progress change to whether the cluster can be connected to from the public network.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRedshiftClusterResizeInfo

Information about the resize operation for the cluster.

Contents

AllowCancelResize

Indicates whether the resize operation can be canceled.

Type: Boolean

Required: No

ResizeType

The type of resize operation.

Valid values: ClassicResize

Type: String

Pattern: .*S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRedshiftClusterRestoreStatus

Information about the status of a cluster restore action. It only applies if the cluster was created by restoring a snapshot.

Contents

CurrentRestoreRateInMegaBytesPerSecond

The number of megabytes per second being transferred from the backup storage. Returns the average rate for a completed backup.

This field is only updated when you restore to DC2 and DS2 node types.

Type: Double

Required: No

ElapsedTimeInSeconds

The amount of time an in-progress restore has been running, or the amount of time it took a completed restore to finish.

This field is only updated when you restore to DC2 and DS2 node types.

Type: Long

Required: No

EstimatedTimeToCompletionInSeconds

The estimate of the time remaining before the restore is complete. Returns 0 for a completed restore.

This field is only updated when you restore to DC2 and DS2 node types.

Type: Long

Required: No

ProgressInMegaBytes

The number of megabytes that were transferred from snapshot storage.

This field is only updated when you restore to DC2 and DS2 node types.

Type: Long

Required: No

SnapshotSizeInMegaBytes

The size of the set of snapshot data that was used to restore the cluster.

This field is only updated when you restore to DC2 and DS2 node types.

Type: Long

Required: No

Status

The status of the restore action.

Valid values: starting | restoring | completed | failed

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRedshiftClusterVpcSecurityGroup

A VPC security group that the cluster belongs to, if the cluster is in a VPC.

Contents

Status

The status of the VPC security group.

Type: String

Pattern: `.*\S.*`

Required: No

VpcSecurityGroupId

The identifier of the VPC security group.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Route 53

Amazon Route 53 objects

- [AwsRoute53HostedZoneConfigDetails](#)
- [AwsRoute53HostedZoneDetails](#)

- [AwsRoute53HostedZoneObjectDetails](#)
- [AwsRoute53HostedZoneVpcDetails](#)
- [AwsRoute53QueryLoggingConfigDetails](#)
- [CloudWatchLogsLogGroupArnConfigDetails](#)

AwsRoute53HostedZoneConfigDetails

An object that contains an optional comment about your Amazon Route 53 hosted zone.

Contents

Comment

Any comments that you include about the hosted zone.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRoute53HostedZoneDetails

Provides details about a specified Amazon Route 53 hosted zone, including the four name servers assigned to the hosted zone. A hosted zone represents a collection of records that can be managed together, belonging to a single parent domain name.

Contents

HostedZone

An object that contains information about the specified hosted zone.

Type: [AwsRoute53HostedZoneObjectDetails](#) object

Required: No

NameServers

An object that contains a list of the authoritative name servers for a hosted zone or for a reusable delegation set.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

QueryLoggingConfig

An array that contains one QueryLoggingConfig element for each DNS query logging configuration that is associated with the current Amazon Web Services account.

Type: [AwsRoute53QueryLoggingConfigDetails](#) object

Required: No

Vpcs

An object that contains information about the Amazon Virtual Private Clouds (Amazon VPCs) that are associated with the specified hosted zone.

Type: Array of [AwsRoute53HostedZoneVpcDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRoute53HostedZoneObjectDetails

An object that contains information about an Amazon Route 53 hosted zone.

Contents

Config

An object that includes the Comment element.

Type: [AwsRoute53HostedZoneConfigDetails](#) object

Required: No

Id

The ID that Route 53 assigns to the hosted zone when you create it.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the domain. For public hosted zones, this is the name that you have registered with your DNS registrar.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRoute53HostedZoneVpcDetails

For private hosted zones, this is a complex type that contains information about an Amazon VPC.

Contents

Id

The identifier of an Amazon VPC.

Type: String

Pattern: `.*\S.*`

Required: No

Region

The Amazon Web Services Region that an Amazon VPC was created in.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsRoute53QueryLoggingConfigDetails

Provides details about a specified Amazon Route 53 configuration for DNS query logging.

Contents

CloudWatchLogsLogGroupArn

The Amazon Resource Name (ARN) of the Amazon CloudWatch Logs log group that Route 53 is publishing logs to.

Type: [CloudWatchLogsLogGroupArnConfigDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

CloudWatchLogsLogGroupArnConfigDetails

The Amazon Resource Name (ARN) and other details of the Amazon CloudWatch Logs log group that Amazon Route 53 is publishing logs to.

Contents

CloudWatchLogsLogGroupArn

The ARN of the CloudWatch Logs log group that Route 53 is publishing logs to.

Type: String

Pattern: `.*\S.*`

Required: No

HostedZoneId

The ID of the hosted zone that CloudWatch Logs is logging queries for.

Type: String

Pattern: `.*\S.*`

Required: No

Id

The ID for a DNS query logging configuration.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

Amazon Simple Storage Service (S3) objects

Amazon Simple Storage Service (S3) objects

- [AwsS3AccessPointDetails](#)
- [AwsS3AccessPointVpcConfigurationDetails](#)
- [AwsS3AccountPublicAccessBlockDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesAbortIncompleteMultipartUploadDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesFilterDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateOperandsDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateOperandsTagDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateTagDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesNoncurrentVersionTransitionsDetails](#)
- [AwsS3BucketBucketLifecycleConfigurationRulesTransitionsDetails](#)
- [AwsS3BucketBucketVersioningConfiguration](#)
- [AwsS3BucketDetails](#)
- [AwsS3BucketLoggingConfiguration](#)
- [AwsS3BucketNotificationConfiguration](#)
- [AwsS3BucketNotificationConfigurationDetail](#)
- [AwsS3BucketNotificationConfigurationFilter](#)
- [AwsS3BucketNotificationConfigurationS3KeyFilter](#)
- [AwsS3BucketNotificationConfigurationS3KeyFilterRule](#)
- [AwsS3BucketObjectLockConfiguration](#)
- [AwsS3BucketObjectLockConfigurationRuleDefaultRetentionDetails](#)
- [AwsS3BucketObjectLockConfigurationRuleDetails](#)
- [AwsS3BucketServerSideEncryptionByDefault](#)
- [AwsS3BucketServerSideEncryptionConfiguration](#)

- [AwsS3BucketServerSideEncryptionRule](#)
- [AwsS3BucketWebsiteConfiguration](#)
- [AwsS3BucketWebsiteConfigurationRedirectTo](#)
- [AwsS3BucketWebsiteConfigurationRoutingRule](#)
- [AwsS3BucketWebsiteConfigurationRoutingRuleCondition](#)
- [AwsS3BucketWebsiteConfigurationRoutingRuleRedirect](#)
- [AwsS3ObjectDetails](#)

AwsS3AccessPointDetails

Returns configuration information about the specified Amazon S3 access point. S3 access points are named network endpoints that are attached to buckets that you can use to perform S3 object operations.

Contents

AccessPointArn

The Amazon Resource Name (ARN) of the access point.

Type: String

Pattern: `.*\S.*`

Required: No

Alias

The name or alias of the access point.

Type: String

Pattern: `.*\S.*`

Required: No

Bucket

The name of the S3 bucket associated with the specified access point.

Type: String

Pattern: `.*\S.*`

Required: No

BucketAccountId

The Amazon Web Services account ID associated with the S3 bucket associated with this access point.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the specified access point.

Type: String

Pattern: `.*\S.*`

Required: No

NetworkOrigin

Indicates whether this access point allows access from the public internet.

Type: String

Pattern: `.*\S.*`

Required: No

PublicAccessBlockConfiguration

provides information about the Amazon S3 Public Access Block configuration for accounts.

Type: [AwsS3AccountPublicAccessBlockDetails](#) object

Required: No

VpcConfiguration

Contains the virtual private cloud (VPC) configuration for the specified access point.

Type: [AwsS3AccessPointVpcConfigurationDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3AccessPointVpcConfigurationDetails

The virtual private cloud (VPC) configuration for an Amazon S3 access point.

Contents

VpcId

If this field is specified, this access point will only allow connections from the specified VPC ID.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3AccountPublicAccessBlockDetails

provides information about the Amazon S3 Public Access Block configuration for accounts.

Contents

BlockPublicAcls

Indicates whether to reject calls to update an S3 bucket if the calls include a public access control list (ACL).

Type: Boolean

Required: No

BlockPublicPolicy

Indicates whether to reject calls to update the access policy for an S3 bucket or access point if the policy allows public access.

Type: Boolean

Required: No

IgnorePublicAcls

Indicates whether Amazon S3 ignores public ACLs that are associated with an S3 bucket.

Type: Boolean

Required: No

RestrictPublicBuckets

Indicates whether to restrict access to an access point or S3 bucket that has a public policy to only Amazon service principals and authorized users within the S3 bucket owner's account.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketBucketLifecycleConfigurationDetails

The lifecycle configuration for the objects in the S3 bucket.

Contents

Rules

The lifecycle rules.

Type: Array of [AwsS3BucketBucketLifecycleConfigurationRulesDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketBucketLifecycleConfigurationRulesAbortIncompleteMultipartUploadDetail

Information about what Amazon S3 does when a multipart upload is incomplete.

Contents

DaysAfterInitiation

The number of days after which Amazon S3 cancels an incomplete multipart upload.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketBucketLifecycleConfigurationRulesDetails

Configuration for a lifecycle rule.

Contents

AbortIncompleteMultipartUpload

How Amazon S3 responds when a multipart upload is incomplete. Specifically, provides a number of days before Amazon S3 cancels the entire upload.

Type: [AwsS3BucketBucketLifecycleConfigurationRulesAbortIncompleteMultipartUploadDetails](#) object

Required: No

ExpirationDate

The date when objects are moved or deleted.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

ExpirationInDays

The length in days of the lifetime for objects that are subject to the rule.

Type: Integer

Required: No

ExpiredObjectDeleteMarker

Whether Amazon S3 removes a delete marker that has no noncurrent versions. If set to `true`, the delete marker is expired. If set to `false`, the policy takes no action.

If you provide `ExpiredObjectDeleteMarker`, you cannot provide `ExpirationInDays` or `ExpirationDate`.

Type: Boolean

Required: No

Filter

Identifies the objects that a rule applies to.

Type: [AwsS3BucketBucketLifecycleConfigurationRulesFilterDetails](#) object

Required: No

ID

The unique identifier of the rule.

Type: String

Pattern: `.*\S.*`

Required: No

NoncurrentVersionExpirationInDays

The number of days that an object is noncurrent before Amazon S3 can perform the associated action.

Type: Integer

Required: No

NoncurrentVersionTransitions

Transition rules that describe when noncurrent objects transition to a specified storage class.

Type: Array of

[AwsS3BucketBucketLifecycleConfigurationRulesNoncurrentVersionTransitionsDetails](#) objects

Required: No

Prefix

A prefix that identifies one or more objects that the rule applies to.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The current status of the rule. Indicates whether the rule is currently being applied.

Type: String

Pattern: `.*\S.*`

Required: No

Transitions

Transition rules that indicate when objects transition to a specified storage class.

Type: Array of [AwsS3BucketBucketLifecycleConfigurationRulesTransitionsDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketBucketLifecycleConfigurationRulesFilterDetails

Identifies the objects that a rule applies to.

Contents

Predicate

The configuration for the filter.

Type: [AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateDetails

The configuration for the filter.

Contents

Operands

The values to use for the filter.

Type: Array of [AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateOperandsDetails](#) objects

Required: No

Prefix

A prefix filter.

Type: String

Pattern: `.*\S.*`

Required: No

Tag

A tag filter.

Type: [AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateTagDetails](#) object

Required: No

Type

Whether to use AND or OR to join the operands. Valid values are `LifecycleAndOperator` or `LifecycleOrOperator`.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateOperandsDetails

A value to use for the filter.

Contents

Prefix

Prefix text for matching objects.

Type: String

Pattern: .*\\S.*

Required: No

Tag

A tag that is assigned to matching objects.

Type: [AwsS3BucketBucketLifecycleConfigurationRulesFilterPredicateOperandsTagDetails](#) object

Required: No

Type

The type of filter value. Valid values are LifecyclePrefixPredicate or LifecycleTagPredicate.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketLifecycleConfigurationRulesFilterPredicateOperandsTagDetails

A tag that is assigned to matching objects.

Contents

Key

The tag key.

Type: String

Pattern: `.*\S.*`

Required: No

Value

The tag value.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketLifecycleConfigurationRulesFilterPredicateTagDetails

A tag filter.

Contents

Key

The tag key.

Type: String

Pattern: `.*\S.*`

Required: No

Value

The tag value

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketLifecycleConfigurationRulesNoncurrentVersionTransitionsDetails

A transition rule that describes when noncurrent objects transition to a specified storage class.

Contents

Days

The number of days that an object is noncurrent before Amazon S3 can perform the associated action.

Type: Integer

Required: No

StorageClass

The class of storage to change the object to after the object is noncurrent for the specified number of days.

Type: String

Pattern: .*S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketLifecycleConfigurationRulesTransitionsDetails

A rule for when objects transition to specific storage classes.

Contents

Date

A date on which to transition objects to the specified storage class. If you provide Date, you cannot provide Days.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

Days

The number of days after which to transition the object to the specified storage class. If you provide Days, you cannot provide Date.

Type: Integer

Required: No

StorageClass

The storage class to transition the object to. Valid values are as follows:

- DEEP_ARCHIVE
- GLACIER
- INTELLIGENT_TIERING
- ONEZONE_IA
- STANDARD_IA

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketBucketVersioningConfiguration

Describes the versioning state of an S3 bucket.

Contents

IsMfaDeleteEnabled

Specifies whether MFA delete is currently enabled in the S3 bucket versioning configuration. If the S3 bucket was never configured with MFA delete, then this attribute is not included.

Type: Boolean

Required: No

Status

The versioning status of the S3 bucket. Valid values are Enabled or Suspended.

Type: String

Pattern: .*S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketDetails

The details of an Amazon Simple Storage Service (Amazon S3) bucket.

Contents

AccessControlList

The access control list for the S3 bucket.

Type: String

Pattern: .*\\S.*

Required: No

BucketLifecycleConfiguration

The lifecycle configuration for objects in the specified bucket.

Type: [AwsS3BucketBucketLifecycleConfigurationDetails](#) object

Required: No

BucketLoggingConfiguration

The logging configuration for the S3 bucket.

Type: [AwsS3BucketLoggingConfiguration](#) object

Required: No

BucketNotificationConfiguration

The notification configuration for the S3 bucket.

Type: [AwsS3BucketNotificationConfiguration](#) object

Required: No

BucketVersioningConfiguration

The versioning state of an S3 bucket.

Type: [AwsS3BucketBucketVersioningConfiguration](#) object

Required: No

BucketWebsiteConfiguration

The website configuration parameters for the S3 bucket.

Type: [AwsS3BucketWebsiteConfiguration](#) object

Required: No

CreatedAt

Indicates when the S3 bucket was created.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the bucket.

Type: String

Pattern: `.*\S.*`

Required: No

ObjectLockConfiguration

Specifies which rule Amazon S3 applies by default to every new object placed in the bucket.

Type: [AwsS3BucketObjectLockConfiguration](#) object

Required: No

OwnerAccountId

The Amazon Web Services account identifier of the account that owns the S3 bucket.

Type: String

Pattern: `.*\S.*`

Required: No

OwnerId

The canonical user ID of the owner of the S3 bucket.

Type: String

Pattern: .*\\S.*

Required: No

OwnerName

The display name of the owner of the S3 bucket.

Type: String

Pattern: .*\\S.*

Required: No

PublicAccessBlockConfiguration

Provides information about the Amazon S3 Public Access Block configuration for the S3 bucket.

Type: [AwsS3AccountPublicAccessBlockDetails](#) object

Required: No

ServerSideEncryptionConfiguration

The encryption rules that are applied to the S3 bucket.

Type: [AwsS3BucketServerSideEncryptionConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsS3BucketLoggingConfiguration

Information about logging for the S3 bucket

Contents

DestinationBucketName

The name of the S3 bucket where log files for the S3 bucket are stored.

Type: String

Pattern: .*\.S.*

Required: No

LogFilePrefix

The prefix added to log files for the S3 bucket.

Type: String

Pattern: .*\.S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketNotificationConfiguration

The notification configuration for the S3 bucket.

Contents

Configurations

Configurations for S3 bucket notifications.

Type: Array of [AwsS3BucketNotificationConfigurationDetail](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketNotificationConfigurationDetail

Details for an S3 bucket notification configuration.

Contents

Destination

The ARN of the Lambda function, Amazon SQS queue, or Amazon SNS topic that generates the notification.

Type: String

Pattern: `.*\S.*`

Required: No

Events

The list of events that trigger a notification.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

Filter

The filters that determine which S3 buckets generate notifications.

Type: [AwsS3BucketNotificationConfigurationFilter](#) object

Required: No

Type

Indicates the type of notification. Notifications can be generated using Lambda functions, Amazon SQS queues, or Amazon SNS topics, with corresponding valid values as follows:

- `LambdaConfiguration`
- `QueueConfiguration`
- `TopicConfiguration`

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketNotificationConfigurationFilter

Filtering information for the notifications. The filtering is based on Amazon S3 key names.

Contents

S3KeyFilter

Details for an Amazon S3 filter.

Type: [AwsS3BucketNotificationConfigurationS3KeyFilter](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketNotificationConfigurationS3KeyFilter

Details for an Amazon S3 filter.

Contents

FilterRules

The filter rules for the filter.

Type: Array of [AwsS3BucketNotificationConfigurationS3KeyFilterRule](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketNotificationConfigurationS3KeyFilterRule

Details for a filter rule.

Contents

Name

Indicates whether the filter is based on the prefix or suffix of the Amazon S3 key.

Type: String

Valid Values: Prefix | Suffix

Required: No

Value

The filter value.

Type: String

Pattern: .*S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketObjectLockConfiguration

The container element for S3 Object Lock configuration parameters. In Amazon S3, Object Lock can help prevent objects from being deleted or overwritten for a fixed amount of time or indefinitely.

Contents

ObjectLockEnabled

Indicates whether the bucket has an Object Lock configuration enabled.

Type: String

Pattern: `.*\S.*`

Required: No

Rule

Specifies the Object Lock rule for the specified object.

Type: [AwsS3BucketObjectLockConfigurationRuleDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketObjectLockConfigurationRuleDefaultRetentionDetails

The default S3 Object Lock retention mode and period that you want to apply to new objects placed in the specified Amazon S3 bucket.

Contents

Days

The number of days that you want to specify for the default retention period.

Type: Integer

Required: No

Mode

The default Object Lock retention mode you want to apply to new objects placed in the specified bucket.

Type: String

Pattern: `.*\S.*`

Required: No

Years

The number of years that you want to specify for the default retention period.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketObjectLockConfigurationRuleDetails

Specifies the S3 Object Lock rule for the specified object. In Amazon S3, Object Lock can help prevent objects from being deleted or overwritten for a fixed amount of time or indefinitely.

Contents

DefaultRetention

The default Object Lock retention mode and period that you want to apply to new objects placed in the specified bucket.

Type: [AwsS3BucketObjectLockConfigurationRuleDefaultRetentionDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketServerSideEncryptionByDefault

Specifies the default server-side encryption to apply to new objects in the bucket.

Contents

KMSMasterKeyID

Amazon KMS key ID to use for the default encryption.

Type: String

Pattern: `.*\S.*`

Required: No

SSEAlgorithm

Server-side encryption algorithm to use for the default encryption. Valid values are `aws:kms` or `AES256`.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketServerSideEncryptionConfiguration

The encryption configuration for the S3 bucket.

Contents

Rules

The encryption rules that are applied to the S3 bucket.

Type: Array of [AwsS3BucketServerSideEncryptionRule](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketServerSideEncryptionRule

An encryption rule to apply to the S3 bucket.

Contents

ApplyServerSideEncryptionByDefault

Specifies the default server-side encryption to apply to new objects in the bucket. If a PUT object request doesn't specify any server-side encryption, this default encryption is applied.

Type: [AwsS3BucketServerSideEncryptionByDefault](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketWebsiteConfiguration

Website parameters for the S3 bucket.

Contents

ErrorDocument

The name of the error document for the website.

Type: String

Pattern: `.*\S.*`

Required: No

IndexDocumentSuffix

The name of the index document for the website.

Type: String

Pattern: `.*\S.*`

Required: No

RedirectAllRequestsTo

The redirect behavior for requests to the website.

Type: [AwsS3BucketWebsiteConfigurationRedirectTo](#) object

Required: No

RoutingRules

The rules for applying redirects for requests to the website.

Type: Array of [AwsS3BucketWebsiteConfigurationRoutingRule](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketWebsiteConfigurationRedirectTo

The redirect behavior for requests to the website.

Contents

Hostname

The name of the host to redirect requests to.

Type: String

Pattern: `.*\S.*`

Required: No

Protocol

The protocol to use when redirecting requests. By default, this field uses the same protocol as the original request. Valid values are `http` or `https`.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketWebsiteConfigurationRoutingRule

A rule for redirecting requests to the website.

Contents

Condition

Provides the condition that must be met in order to apply the routing rule.

Type: [AwsS3BucketWebsiteConfigurationRoutingRuleCondition](#) object

Required: No

Redirect

Provides the rules to redirect the request if the condition in `Condition` is met.

Type: [AwsS3BucketWebsiteConfigurationRoutingRuleRedirect](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketWebsiteConfigurationRoutingRuleCondition

The condition that must be met in order to apply the routing rule.

Contents

HttpErrorCodeReturnedEquals

Indicates to redirect the request if the HTTP error code matches this value.

Type: String

Pattern: `.*\S.*`

Required: No

KeyPrefixEquals

Indicates to redirect the request if the key prefix matches this value.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3BucketWebsiteConfigurationRoutingRuleRedirect

The rules to redirect the request if the condition in `Condition` is met.

Contents

Hostname

The host name to use in the redirect request.

Type: String

Pattern: `.*\S.*`

Required: No

HttpRedirectCode

The HTTP redirect code to use in the response.

Type: String

Pattern: `.*\S.*`

Required: No

Protocol

The protocol to use to redirect the request. By default, uses the protocol from the original request.

Type: String

Pattern: `.*\S.*`

Required: No

ReplaceKeyPrefixWith

The object key prefix to use in the redirect request.

Cannot be provided if `ReplaceKeyWith` is present.

Type: String

Pattern: `.*\S.*`

Required: No

ReplaceKeyWith

The specific object key to use in the redirect request.

Cannot be provided if `ReplaceKeyPrefixWith` is present.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsS3ObjectDetails

Details about an Amazon S3 object.

Contents

ContentType

A standard MIME type describing the format of the object data.

Type: String

Pattern: .*\.S.*

Required: No

ETag

The opaque identifier assigned by a web server to a specific version of a resource found at a URL.

Type: String

Pattern: .*\.S.*

Required: No

LastModified

Indicates when the object was last modified.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\.S.*

Required: No

ServerSideEncryption

If the object is stored using server-side encryption, the value of the server-side encryption algorithm used when storing this object in Amazon S3.

Type: String

Pattern: .*\\S.*

Required: No

SSEKMSKeyId

The identifier of the Amazon KMS symmetric customer managed key that was used for the object.

Type: String

Pattern: .*\\S.*

Required: No

VersionId

The version of the object.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon SageMaker AI

Amazon SageMaker AI objects

- [AwsSageMakerNotebookInstanceDetails](#)
- [AwsSageMakerNotebookInstanceMetadataServiceConfigurationDetails](#)

AwsSageMakerNotebookInstanceDetails

Provides details about an Amazon SageMaker AI notebook instance.

Contents

AcceleratorTypes

A list of Amazon Elastic Inference instance types to associate with the notebook instance. Currently, only one instance type can be associated with a notebook instance.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

AdditionalCodeRepositories

An array of up to three Git repositories associated with the notebook instance. These can be either the names of Git repositories stored as resources in your account, or the URL of Git repositories in [Amazon CodeCommit](#) or in any other Git repository. These repositories are cloned at the same level as the default repository of your notebook instance. For more information, see [Associating Git repositories with SageMaker AI notebook instances](#) in the *Amazon SageMaker AI Developer Guide*.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

DefaultCodeRepository

The Git repository associated with the notebook instance as its default code repository. This can be either the name of a Git repository stored as a resource in your account, or the URL of a Git repository in [Amazon CodeCommit](#) or in any other Git repository. When you open a notebook instance, it opens in the directory that contains this repository. For more information, see [Associating Git repositories with SageMaker AI notebook instances](#) in the *Amazon SageMaker AI Developer Guide*.

Type: String

Pattern: `.*\S.*`

Required: No

DirectInternetAccess

Sets whether SageMaker AI provides internet access to the notebook instance. If you set this to `Disabled`, this notebook instance is able to access resources only in your VPC, and is not be able to connect to SageMaker AI training and endpoint services unless you configure a Network Address Translation (NAT) Gateway in your VPC.

Type: String

Pattern: `.*\S.*`

Required: No

FailureReason

If status of the instance is `Failed`, the reason it failed.

Type: String

Pattern: `.*\S.*`

Required: No

InstanceMetadataServiceConfiguration

Information on the IMDS configuration of the notebook instance.

Type: [AwsSageMakerNotebookInstanceMetadataServiceConfigurationDetails](#) object

Required: No

InstanceType

The type of machine learning (ML) compute instance to launch for the notebook instance.

Type: String

Pattern: `.*\S.*`

Required: No

KmsKeyId

The Amazon Resource Name (ARN) of an Amazon Key Management Service (Amazon KMS) key that SageMaker AI uses to encrypt data on the storage volume attached to your notebook instance. The KMS key you provide must be enabled. For information, see [Enabling and disabling keys](#) in the *Amazon Key Management Service Developer Guide*.

Type: String

Pattern: `.*\S.*`

Required: No

NetworkInterfaceId

The network interface ID that SageMaker AI created when the instance was created.

Type: String

Pattern: `.*\S.*`

Required: No

NotebookInstanceArn

The Amazon Resource Name (ARN) of the notebook instance.

Type: String

Pattern: `.*\S.*`

Required: No

NotebookInstanceLifecycleConfigName

The name of a notebook instance lifecycle configuration.

Type: String

Pattern: `.*\S.*`

Required: No

NotebookInstanceName

The name of the new notebook instance.

Type: String

Pattern: `.*\S.*`

Required: No

NotebookInstanceStatus

The status of the notebook instance.

Type: String

Pattern: `.*\S.*`

Required: No

PlatformIdentifier

The platform identifier of the notebook instance runtime environment.

Type: String

Pattern: `.*\S.*`

Required: No

RoleArn

The Amazon Resource Name (ARN) of the IAM role associated with the instance.

Type: String

Pattern: `.*\S.*`

Required: No

RootAccess

Whether root access is enabled or disabled for users of the notebook instance.

Type: String

Pattern: `.*\S.*`

Required: No

SecurityGroups

The VPC security group IDs.

Type: Array of strings

Pattern: `.*\S.*`

Required: No

SubnetId

The ID of the VPC subnet to which you have a connectivity from your ML compute instance.

Type: String

Pattern: `.*\S.*`

Required: No

Url

The URL that you use to connect to the Jupyter notebook that is running in your notebook instance.

Type: String

Pattern: `.*\S.*`

Required: No

VolumeSizeInGB

The size, in GB, of the ML storage volume to attach to the notebook instance.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsSageMakerNotebookInstanceMetadataServiceConfigurationDetails

Information on the instance metadata service (IMDS) configuration of the notebook instance.

Contents

MinimumInstanceMetadataServiceVersion

Indicates the minimum IMDS version that the notebook instance supports.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Secrets Manager objects

Amazon Secrets Manager objects

- [AwsSecretsManagerSecretDetails](#)
- [AwsSecretsManagerSecretRotationRules](#)

AwsSecretsManagerSecretDetails

Details about an Amazon Secrets Manager secret.

Contents

Deleted

Whether the secret is deleted.

Type: Boolean

Required: No

Description

The user-provided description of the secret.

Type: String

Pattern: `.*\S.*`

Required: No

KmsKeyId

The ARN, Key ID, or alias of the Amazon KMS key used to encrypt the `SecretString` or `SecretBinary` values for versions of this secret.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the secret.

Type: String

Pattern: `.*\S.*`

Required: No

RotationEnabled

Whether rotation is enabled.

Type: Boolean

Required: No

RotationLambdaArn

The ARN of the Lambda function that rotates the secret.

Type: String

Pattern: `.*\S.*`

Required: No

RotationOccurredWithinFrequency

Whether the rotation occurred within the specified rotation frequency.

Type: Boolean

Required: No

RotationRules

Defines the rotation schedule for the secret.

Type: [AwsSecretsManagerSecretRotationRules](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsSecretsManagerSecretRotationRules

Defines the rotation schedule for the secret.

Contents

AutomaticallyAfterDays

The number of days after the previous rotation to rotate the secret.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Simple Notification Service (SNS) objects

Amazon Simple Notification Service (SNS) objects

- [AwsSnsTopicDetails](#)
- [AwsSnsTopicSubscription](#)

AwsSnsTopicDetails

Provides information about an Amazon SNS topic to which notifications can be published.

Contents

ApplicationSuccessFeedbackRoleArn

Indicates failed message delivery status for an Amazon SNS topic that is subscribed to a platform application endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

FirehoseFailureFeedbackRoleArn

Indicates failed message delivery status for an Amazon SNS topic that is subscribed to an Amazon Kinesis Data Firehose endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

FirehoseSuccessFeedbackRoleArn

Indicates successful message delivery status for an Amazon SNS topic that is subscribed to an Amazon Kinesis Data Firehose endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

HttpFailureFeedbackRoleArn

Indicates failed message delivery status for an Amazon SNS topic that is subscribed to an HTTP endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

HttpSuccessFeedbackRoleArn

Indicates successful message delivery status for an Amazon SNS topic that is subscribed to an HTTP endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

KmsMasterKeyId

The ID of an Amazon managed key for Amazon SNS or a customer managed key.

Type: String

Pattern: `.*\S.*`

Required: No

Owner

The subscription's owner.

Type: String

Pattern: `.*\S.*`

Required: No

SqsFailureFeedbackRoleArn

Indicates failed message delivery status for an Amazon SNS topic that is subscribed to an Amazon SQS endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

SqsSuccessFeedbackRoleArn

Indicates successful message delivery status for an Amazon SNS topic that is subscribed to an Amazon SQS endpoint.

Type: String

Pattern: `.*\S.*`

Required: No

Subscription

Subscription is an embedded property that describes the subscription endpoints of an Amazon SNS topic.

Type: Array of [AwsSnsTopicSubscription](#) objects

Required: No

TopicName

The name of the Amazon SNS topic.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsSnsTopicSubscription

A wrapper type for the attributes of an Amazon SNS subscription.

Contents

Endpoint

The subscription's endpoint (format depends on the protocol).

Type: String

Pattern: `.*\S.*`

Required: No

Protocol

The subscription's protocol.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Simple Queue Service (SQS) objects

Amazon SQS objects

- [AwsSqsQueueDetails](#)

AwsSqsQueueDetails

Data about a queue.

Contents

DeadLetterTargetArn

The ARN of the dead-letter queue to which Amazon SQS moves messages after the value of `maxReceiveCount` is exceeded.

Type: String

Pattern: `.*\S.*`

Required: No

KmsDataKeyReusePeriodSeconds

The length of time, in seconds, for which Amazon SQS can reuse a data key to encrypt or decrypt messages before calling Amazon KMS again.

Type: Integer

Required: No

KmsMasterKeyId

The ID of an Amazon managed key for Amazon SQS or a custom KMS key.

Type: String

Pattern: `.*\S.*`

Required: No

QueueName

The name of the new queue.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Systems Manager objects

Amazon Systems Manager objects

- [AwsSsmComplianceSummary](#)
- [AwsSsmPatch](#)
- [AwsSsmPatchComplianceDetails](#)

AwsSsmComplianceSummary

Provides the details about the compliance status for a patch.

Contents

ComplianceType

The type of resource for which the compliance was determined. For `AwsSsmPatchCompliance`, `ComplianceType` is `Patch`.

Type: String

Pattern: `.*\S.*`

Required: No

CompliantCriticalCount

For the patches that are compliant, the number that have a severity of `CRITICAL`.

Type: Integer

Required: No

CompliantHighCount

For the patches that are compliant, the number that have a severity of `HIGH`.

Type: Integer

Required: No

CompliantInformationalCount

For the patches that are compliant, the number that have a severity of `INFORMATIONAL`.

Type: Integer

Required: No

CompliantLowCount

For the patches that are compliant, the number that have a severity of `LOW`.

Type: Integer

Required: No

CompliantMediumCount

For the patches that are compliant, the number that have a severity of MEDIUM.

Type: Integer

Required: No

CompliantUnspecifiedCount

For the patches that are compliant, the number that have a severity of UNSPECIFIED.

Type: Integer

Required: No

ExecutionType

The type of execution that was used determine compliance.

Type: String

Pattern: `.*\S.*`

Required: No

NonCompliantCriticalCount

For the patch items that are noncompliant, the number of items that have a severity of CRITICAL.

Type: Integer

Required: No

NonCompliantHighCount

For the patches that are noncompliant, the number that have a severity of HIGH.

Type: Integer

Required: No

NonCompliantInformationalCount

For the patches that are noncompliant, the number that have a severity of INFORMATIONAL.

Type: Integer

Required: No

NonCompliantLowCount

For the patches that are noncompliant, the number that have a severity of LOW.

Type: Integer

Required: No

NonCompliantMediumCount

For the patches that are noncompliant, the number that have a severity of MEDIUM.

Type: Integer

Required: No

NonCompliantUnspecifiedCount

For the patches that are noncompliant, the number that have a severity of UNSPECIFIED.

Type: Integer

Required: No

OverallSeverity

The highest severity for the patches. Valid values are as follows:

- CRITICAL
- HIGH
- MEDIUM
- LOW
- INFORMATIONAL
- UNSPECIFIED

Type: String

Pattern: `.*\S.*`

Required: No

PatchBaselineId

The identifier of the patch baseline. The patch baseline lists the patches that are approved for installation.

Type: String

Pattern: `.*\S.*`

Required: No

PatchGroup

The identifier of the patch group for which compliance was determined. A patch group uses tags to group EC2 instances that should have the same patch compliance.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The current patch compliance status. Valid values are as follows:

- COMPLIANT
- NON_COMPLIANT
- UNSPECIFIED_DATA

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsSsmPatch

Provides details about the compliance for a patch.

Contents

ComplianceSummary

The compliance status details for the patch.

Type: [AwsSsmComplianceSummary](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsSsmPatchComplianceDetails

Provides information about the state of a patch on an instance based on the patch baseline that was used to patch the instance.

Contents

Patch

Information about the status of a patch.

Type: [AwsSsmPatch](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon Step Functions objects

Amazon Step Functions objects

- [AwsStepFunctionStateMachineDetails](#)
- [AwsStepFunctionStateMachineLoggingConfigurationDestinationsCloudWatchLogsLogGroupDetails](#)
- [AwsStepFunctionStateMachineLoggingConfigurationDestinationsDetails](#)
- [AwsStepFunctionStateMachineLoggingConfigurationDetails](#)
- [AwsStepFunctionStateMachineTracingConfigurationDetails](#)

AwsStepFunctionStateMachineDetails

Provides details about an Amazon Step Functions state machine, which is a workflow consisting of a series of event- driven steps.

Contents

Label

A user-defined or an auto-generated string that identifies a Map state. This parameter is present only if the `stateMachineArn` specified in input is a qualified state machine ARN.

Type: String

Pattern: `.*\S.*`

Required: No

LoggingConfiguration

Used to set CloudWatch Logs options.

Type: [AwsStepFunctionStateMachineLoggingConfigurationDetails](#) object

Required: No

Name

The name of the state machine.

Type: String

Pattern: `.*\S.*`

Required: No

RoleArn

The Amazon Resource Name (ARN) of the IAM role used when creating this state machine.

Type: String

Pattern: `.*\S.*`

Required: No

StateMachineArn

The ARN that identifies the state machine.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The current status of the state machine.

Type: String

Pattern: `.*\S.*`

Required: No

TracingConfiguration

Specifies whether Amazon X-Ray tracing is enabled.

Type: [AwsStepFunctionStateMachineTracingConfigurationDetails](#) object

Required: No

Type

The type of the state machine (STANDARD or EXPRESS).

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsStepFunctionStateMachineLoggingConfigurationDestinationsCloudWatchLogsLogGroupArn

An object describing a CloudWatch log group. For more information, see [Amazon::Logs::LogGroup](#) in the *Amazon CloudFormation User Guide*.

Contents

LogGroupArn

The ARN (ends with `:*`) of the CloudWatch Logs log group to which you want your logs emitted.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsStepFunctionStateMachineLoggingConfigurationDestinationsDetails

An array of objects that describes where your execution history events will be logged.

Contents

CloudWatchLogsLogGroup

An object describing a CloudWatch Logs log group. For more information, see [Amazon::Logs::LogGroup](#) in the *Amazon CloudFormation User Guide*.

Type:

[AwsStepFunctionStateMachineLoggingConfigurationDestinationsCloudWatchLogsLogGroupDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsStepFunctionStateMachineLoggingConfigurationDetails

The LoggingConfiguration data type is used to set CloudWatch Logs options.

Contents

Destinations

An array of objects that describes where your execution history events will be logged.

Type: Array of [AwsStepFunctionStateMachineLoggingConfigurationDestinationsDetails](#) objects

Required: No

IncludeExecutionData

Determines whether execution data is included in your log. When set to false, data is excluded.

Type: Boolean

Required: No

Level

Defines which category of execution history events are logged.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsStepFunctionStateMachineTracingConfigurationDetails

Specifies whether Amazon X-Ray tracing is enabled.

Contents

Enabled

When set to true, Amazon X-Ray tracing is enabled.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon WAF objects

Amazon WAF objects

- [AwsWafRateBasedRuleDetails](#)
- [AwsWafRateBasedRuleMatchPredicate](#)
- [AwsWafRegionalRateBasedRuleDetails](#)
- [AwsWafRegionalRateBasedRuleMatchPredicate](#)
- [AwsWafRegionalRuleDetails](#)
- [AwsWafRegionalRuleGroupDetails](#)
- [AwsWafRegionalRuleGroupRulesActionDetails](#)
- [AwsWafRegionalRuleGroupRulesDetails](#)
- [AwsWafRegionalRulePredicateListDetails](#)
- [AwsWafRegionalWebAclDetails](#)

- [AwsWafRegionalWebAclRulesListActionDetails](#)
- [AwsWafRegionalWebAclRulesListDetails](#)
- [AwsWafRegionalWebAclRulesListOverrideActionDetails](#)
- [AwsWafRuleDetails](#)
- [AwsWafRuleGroupDetails](#)
- [AwsWafRuleGroupRulesActionDetails](#)
- [AwsWafRuleGroupRulesDetails](#)
- [AwsWafRulePredicateListDetails](#)
- [AwsWafv2ActionAllowDetails](#)
- [AwsWafv2ActionBlockDetails](#)
- [AwsWafv2CustomHTTPHeader](#)
- [AwsWafv2CustomRequestHandlingDetails](#)
- [AwsWafv2CustomResponseDetails](#)
- [AwsWafv2RuleGroupDetails](#)
- [AwsWafv2RulesActionCaptchaDetails](#)
- [AwsWafv2RulesActionCountDetails](#)
- [AwsWafv2RulesActionDetails](#)
- [AwsWafv2RulesDetails](#)
- [AwsWafv2VisibilityConfigDetails](#)
- [AwsWafv2WebAclActionDetails](#)
- [AwsWafv2WebAclCaptchaConfigDetails](#)
- [AwsWafv2WebAclCaptchaConfigImmunityTimePropertyDetails](#)
- [AwsWafv2WebAclDetails](#)
- [AwsWafWebAclDetails](#)
- [AwsWafWebAclRule](#)
- [WafAction](#)
- [WafExcludedRule](#)
- [WafOverrideAction](#)

AwsWafRateBasedRuleDetails

Details about a rate-based rule for global resources. A rate-based rule provides settings to indicate when to allow, block, or count a request. Rate-based rules include the number of requests that arrive over a specified period of time.

Contents

MatchPredicates

The predicates to include in the rate-based rule.

Type: Array of [AwsWafRateBasedRuleMatchPredicate](#) objects

Required: No

MetricName

The name of the metrics for the rate-based rule.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the rate-based rule.

Type: String

Pattern: `.*\S.*`

Required: No

RateKey

The field that Amazon WAF uses to determine whether requests are likely arriving from single source and are subject to rate monitoring.

Type: String

Pattern: `.*\S.*`

Required: No

RateLimit

The maximum number of requests that have an identical value for the field specified in `RateKey` that are allowed within a five-minute period. If the number of requests exceeds `RateLimit` and the other predicates specified in the rule are met, Amazon WAF triggers the action for the rule.

Type: Long

Required: No

RuleId

The unique identifier for the rate-based rule.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafRateBasedRuleMatchPredicate

A match predicate. A predicate might look for characteristics such as specific IP addresses, geographic locations, or sizes.

Contents

DataId

The unique identifier for the predicate.

Type: String

Pattern: `.*\S.*`

Required: No

Negated

If set to `true`, then the rule actions are performed on requests that match the predicate settings.

If set to `false`, then the rule actions are performed on all requests except those that match the predicate settings.

Type: Boolean

Required: No

Type

The type of predicate. Valid values are as follows:

- ByteMatch
- GeoMatch
- IPMatch
- RegexMatch
- SizeConstraint
- SqlInjectionMatch
- XssMatch

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafRegionalRateBasedRuleDetails

contains details about a rate-based rule for Regional resources. A rate-based rule provides settings to indicate when to allow, block, or count a request. Rate-based rules include the number of requests that arrive over a specified period of time.

Contents

MatchPredicates

The predicates to include in the rate-based rule.

Type: Array of [AwsWafRegionalRateBasedRuleMatchPredicate](#) objects

Required: No

MetricName

The name of the metrics for the rate-based rule.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the rate-based rule.

Type: String

Pattern: `.*\S.*`

Required: No

RateKey

The field that Amazon WAF uses to determine whether requests are likely arriving from single source and are subject to rate monitoring.

Type: String

Pattern: `.*\S.*`

Required: No

RateLimit

The maximum number of requests that have an identical value for the field specified in `RateKey` that are allowed within a five-minute period. If the number of requests exceeds `RateLimit` and the other predicates specified in the rule are met, Amazon WAF triggers the action for the rule.

Type: Long

Required: No

RuleId

The unique identifier for the rate-based rule.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafRegionalRateBasedRuleMatchPredicate

Details for a match predicate. A predicate might look for characteristics such as specific IP addresses, geographic locations, or sizes.

Contents

DataId

The unique identifier for the predicate.

Type: String

Pattern: `.*\S.*`

Required: No

Negated

If set to `true`, then the rule actions are performed on requests that match the predicate settings.

If set to `false`, then the rule actions are performed on all requests except those that match the predicate settings.

Type: Boolean

Required: No

Type

The type of predicate. Valid values are as follows:

- ByteMatch
- GeoMatch
- IPMatch
- RegexMatch
- SizeConstraint
- SqlInjectionMatch
- XssMatch

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafRegionalRuleDetails

Provides information about an Amazon WAF Regional rule. This rule identifies the web requests that you want to allow, block, or count.

Contents

MetricName

A name for the metrics for the rule.

Type: String

Pattern: `.*\S.*`

Required: No

Name

A descriptive name for the rule.

Type: String

Pattern: `.*\S.*`

Required: No

PredicateList

Specifies the `ByteMatchSet`, `IPSet`, `SqlInjectionMatchSet`, `XssMatchSet`, `RegexMatchSet`, `GeoMatchSet`, and `SizeConstraintSet` objects that you want to add to a rule and, for each object, indicates whether you want to negate the settings.

Type: Array of [AwsWafRegionalRulePredicateListDetails](#) objects

Required: No

RuleId

The ID of the rule.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafRegionalRuleGroupDetails

Provides information about an Amazon WAF Regional rule group. The rule group is a collection of rules for inspecting and controlling web requests.

Contents

MetricName

A name for the metrics for this rule group.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The descriptive name of the rule group.

Type: String

Pattern: `.*\S.*`

Required: No

RuleGroupId

The ID of the rule group.

Type: String

Pattern: `.*\S.*`

Required: No

Rules

Provides information about the rule statements used to identify the web requests that you want to allow, block, or count.

Type: Array of [AwsWafRegionalRuleGroupRulesDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafRegionalRuleGroupRulesActionDetails

Describes the action that Amazon WAF should take on a web request when it matches the criteria defined in the rule.

Contents

Type

Specifies the `ByteMatchSet`, `IPSet`, `SqlInjectionMatchSet`, `XssMatchSet`, `RegexMatchSet`, `GeoMatchSet`, and `SizeConstraintSet` objects that you want to add to a rule and, for each object, indicates whether you want to negate the settings.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafRegionalRuleGroupRulesDetails

Provides information about the rules attached to a rule group

Contents

Action

The action that Amazon WAF should take on a web request when it matches the criteria defined in the rule.

Type: [AwsWafRegionalRuleGroupRulesActionDetails](#) object

Required: No

Priority

If you define more than one rule in a web ACL, Amazon WAF evaluates each request against the rules in order based on the value of `Priority`.

Type: Integer

Required: No

RuleId

The ID for a rule.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The type of rule in the rule group.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafRegionalRulePredicateListDetails

Provides details about the ByteMatchSet, IPSet, SqlInjectionMatchSet, XssMatchSet, RegexMatchSet, GeoMatchSet, and SizeConstraintSet objects that you want to add to a rule and, for each object, indicates whether you want to negate the settings.

Contents

DataId

A unique identifier for a predicate in a rule, such as ByteMatchSetId or IPSetId.

Type: String

Pattern: `.*\S.*`

Required: No

Negated

Specifies if you want Amazon WAF to allow, block, or count requests based on the settings in the ByteMatchSet, IPSet, SqlInjectionMatchSet, XssMatchSet, RegexMatchSet, GeoMatchSet, or SizeConstraintSet.

Type: Boolean

Required: No

Type

The type of predicate in a rule, such as ByteMatch or IPSet.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafRegionalWebAclDetails

Provides information about the web access control list (web ACL). The web ACL contains the rules that identify the requests that you want to allow, block, or count.

Contents

DefaultAction

The action to perform if none of the rules contained in the web ACL match.

Type: String

Pattern: `.*\S.*`

Required: No

MetricName

A name for the metrics for this web ACL.

Type: String

Pattern: `.*\S.*`

Required: No

Name

A descriptive name for the web ACL.

Type: String

Pattern: `.*\S.*`

Required: No

RulesList

An array that contains the action for each rule in a web ACL, the priority of the rule, and the ID of the rule.

Type: Array of [AwsWafRegionalWebAclRulesListDetails](#) objects

Required: No

WebAclId

The ID of the web ACL.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafRegionalWebAclRulesListActionDetails

The action that Amazon WAF takes when a web request matches all conditions in the rule, such as allow, block, or count the request.

Contents

Type

For actions that are associated with a rule, the action that Amazon WAF takes when a web request matches all conditions in a rule.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafRegionalWebAclRulesListDetails

A combination of `ByteMatchSet`, `IPSet`, and/or `SqlInjectionMatchSet` objects that identify the web requests that you want to allow, block, or count.

Contents

Action

The action that Amazon WAF takes when a web request matches all conditions in the rule, such as allow, block, or count the request.

Type: [AwsWafRegionalWebAclRulesListActionDetails](#) object

Required: No

OverrideAction

Overrides the rule evaluation result in the rule group.

Type: [AwsWafRegionalWebAclRulesListOverrideActionDetails](#) object

Required: No

Priority

The order in which Amazon WAF evaluates the rules in a web ACL.

Type: Integer

Required: No

RuleId

The ID of an Amazon WAF Regional rule to associate with a web ACL.

Type: String

Pattern: `.*\S.*`

Required: No

Type

For actions that are associated with a rule, the action that Amazon WAF takes when a web request matches all conditions in a rule.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafRegionalWebAclRulesListOverrideActionDetails

Provides details about the action to use in the place of the action that results from the rule group evaluation.

Contents

Type

Overrides the rule evaluation result in the rule group.

Type: String

Pattern: .*\\S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafRuleDetails

Provides information about a Amazon WAF rule. This rule specifies the web requests that you want to allow, block, or count.

Contents

MetricName

The name of the metrics for this rule.

Type: String

Pattern: `.*\S.*`

Required: No

Name

A descriptive name for the rule.

Type: String

Pattern: `.*\S.*`

Required: No

PredicateList

Specifies the `ByteMatchSet`, `IPSet`, `SqlInjectionMatchSet`, `XssMatchSet`, `RegexMatchSet`, `GeoMatchSet`, and `SizeConstraintSet` objects that you want to add to a rule and, for each object, indicates whether you want to negate the settings.

Type: Array of [AwsWafRulePredicateListDetails](#) objects

Required: No

RuleId

The ID of the Amazon WAF rule.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafRuleGroupDetails

Provides information about an Amazon WAF rule group. A rule group is a collection of rules for inspecting and controlling web requests.

Contents

MetricName

The name of the metrics for this rule group.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the rule group.

Type: String

Pattern: `.*\S.*`

Required: No

RuleGroupId

The ID of the rule group.

Type: String

Pattern: `.*\S.*`

Required: No

Rules

Provides information about the rules attached to the rule group. These rules identify the web requests that you want to allow, block, or count.

Type: Array of [AwsWafRuleGroupRulesDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafRuleGroupRulesActionDetails

Provides information about what action Amazon WAF should take on a web request when it matches the criteria defined in the rule.

Contents

Type

The action that Amazon WAF should take on a web request when it matches the rule's statement.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafRuleGroupRulesDetails

Provides information about the rules attached to the rule group. These rules identify the web requests that you want to allow, block, or count.

Contents

Action

Provides information about what action Amazon WAF should take on a web request when it matches the criteria defined in the rule.

Type: [AwsWafRuleGroupRulesActionDetails](#) object

Required: No

Priority

If you define more than one rule in a web ACL, Amazon WAF evaluates each request against the rules in order based on the value of `Priority`.

Type: Integer

Required: No

RuleId

The rule ID for a rule.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The type of rule.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafRulePredicateListDetails

Provides details about the ByteMatchSet, IPSet, SqlInjectionMatchSet, XssMatchSet, RegexMatchSet, GeoMatchSet, and SizeConstraintSet objects that you want to add to a rule and, for each object, indicates whether you want to negate the settings.

Contents

DataId

A unique identifier for a predicate in a rule, such as ByteMatchSetId or IPSetId.

Type: String

Pattern: `.*\S.*`

Required: No

Negated

Specifies if you want Amazon WAF to allow, block, or count requests based on the settings in the ByteMatchSet, IPSet, SqlInjectionMatchSet, XssMatchSet, RegexMatchSet, GeoMatchSet, or SizeConstraintSet.

Type: Boolean

Required: No

Type

The type of predicate in a rule, such as ByteMatch or IPSet.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafv2ActionAllowDetails

Specifies that Amazon WAF should allow the request and optionally defines additional custom handling for the request.

Contents

CustomRequestHandling

Defines custom handling for the web request. For information about customizing web requests and responses, see [Customizing web requests and responses in Amazon WAF](#) in the *Amazon WAF Developer Guide*.

Type: [AwsWafv2CustomRequestHandlingDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafv2ActionBlockDetails

Specifies that Amazon WAF should block the request and optionally defines additional custom handling for the response to the web request.

Contents

CustomResponse

Defines a custom response for the web request. For information, see [Customizing web requests and responses in Amazon WAF](#) in the *Amazon WAF Developer Guide*.

Type: [AwsWafv2CustomResponseDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafv2CustomHTTPHeader

A custom header for custom request and response handling.

Contents

Name

The name of the custom header.

Type: String

Pattern: `.*\S.*`

Required: No

Value

The value of the custom header.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafv2CustomRequestHandlingDetails

Custom request handling behavior that inserts custom headers into a web request. Amazon WAF uses custom request handling when the rule action doesn't block the request.

Contents

InsertHeaders

The HTTP headers to insert into the request.

Type: Array of [AwsWafv2CustomHttpHeader](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafv2CustomResponseDetails

A custom response to send to the client. You can define a custom response for rule actions and default web ACL actions that are set to block.

Contents

CustomResponseBodyKey

References the response body that you want Amazon WAF to return to the web request client. You can define a custom response for a rule action or a default web ACL action that is set to block.

Type: String

Pattern: `.*\S.*`

Required: No

ResponseCode

The HTTP status code to return to the client. For a list of status codes that you can use in your custom responses, see [Supported status codes for custom response](#) in the *Amazon WAF Developer Guide*.

Type: Integer

Required: No

ResponseHeaders

The HTTP headers to use in the response.

Type: Array of [AwsWafv2CustomHTTPHeader](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafv2RuleGroupDetails

Details about an Amazon WAFv2 rule group.

Contents

Arn

The Amazon Resource Name (ARN) of the entity.

Type: String

Pattern: `.*\S.*`

Required: No

Capacity

The web ACL capacity units (WCUs) required for this rule group.

Type: Long

Required: No

Description

A description of the rule group that helps with identification.

Type: String

Pattern: `.*\S.*`

Required: No

Id

A unique identifier for the rule group.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the rule group. You cannot change the name of a rule group after you create it.

Type: String

Pattern: `.*\S.*`

Required: No

Rules

The Rule statements used to identify the web requests that you want to allow, block, or count. Each rule includes one top-level statement that Amazon WAF uses to identify matching web requests, and parameters that govern how Amazon WAF handles them.

Type: Array of [AwsWafv2RulesDetails](#) objects

Required: No

Scope

Specifies whether the rule group is for an Amazon CloudFront distribution or for a regional application. A regional application can be an Application Load Balancer (ALB), an Amazon API Gateway REST API, an Amazon AppSync GraphQL API, or an Amazon Cognito user pool.

Type: String

Pattern: `.*\S.*`

Required: No

VisibilityConfig

Defines and enables Amazon CloudWatch metrics and web request sample collection.

Type: [AwsWafv2VisibilityConfigDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

AwsWafv2RulesActionCaptchaDetails

Specifies that Amazon WAF should run a CAPTCHA check against the request.

Contents

CustomRequestHandling

Defines custom handling for the web request, used when the CAPTCHA inspection determines that the request's token is valid and unexpired. For more information, see [Customizing web requests and responses in Amazon WAF](#) in the *Amazon WAF Developer Guide*..

Type: [AwsWafv2CustomRequestHandlingDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafv2RulesActionCountDetails

Specifies that Amazon WAF should count the request.

Contents

CustomRequestHandling

Defines custom handling for the web request. For more information, see [Customizing web requests and responses in Amazon WAF](#) in the *Amazon WAF Developer Guide*.

Type: [AwsWafv2CustomRequestHandlingDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafv2RulesActionDetails

The action that Amazon WAF should take on a web request when it matches a rule's statement. Settings at the web ACL level can override the rule action setting.

Contents

Allow

Instructs Amazon WAF to allow the web request.

Type: [AwsWafv2ActionAllowDetails](#) object

Required: No

Block

Instructs Amazon WAF to block the web request.

Type: [AwsWafv2ActionBlockDetails](#) object

Required: No

Captcha

Instructs Amazon WAF to run a CAPTCHA check against the web request.

Type: [AwsWafv2RulesActionCaptchaDetails](#) object

Required: No

Count

Instructs Amazon WAF to count the web request and then continue evaluating the request using the remaining rules in the web ACL.

Type: [AwsWafv2RulesActionCountDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafv2RulesDetails

Provides details about rules in a rule group. A rule identifies web requests that you want to allow, block, or count. Each rule includes one top-level `Statement` that Amazon WAF uses to identify matching web requests, and parameters that govern how Amazon WAF handles them.

Contents

Action

The action that Amazon WAF should take on a web request when it matches the rule statement. Settings at the web ACL level can override the rule action setting.

Type: [AwsWafv2RulesActionDetails](#) object

Required: No

Name

The name of the rule.

Type: String

Pattern: `.*\S.*`

Required: No

OverrideAction

The action to use in the place of the action that results from the rule group evaluation.

Type: String

Pattern: `.*\S.*`

Required: No

Priority

If you define more than one Rule in a WebACL, Amazon WAF evaluates each request against the Rules in order based on the value of `Priority`. Amazon WAF processes rules with lower priority first. The priorities don't need to be consecutive, but they must all be different.

Type: Integer

Required: No

VisibilityConfig

Defines and enables Amazon CloudWatch metrics and web request sample collection.

Type: [AwsWafv2VisibilityConfigDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafv2VisibilityConfigDetails

Defines and enables Amazon CloudWatch metrics and web request sample collection.

Contents

CloudWatchMetricsEnabled

A boolean indicating whether the associated resource sends metrics to Amazon CloudWatch. For the list of available metrics, see [Amazon WAF metrics and dimensions](#) in the *Amazon WAF Developer Guide*.

Type: Boolean

Required: No

MetricName

A name of the Amazon CloudWatch metric.

Type: String

Pattern: `.*\S.*`

Required: No

SampledRequestsEnabled

A boolean indicating whether Amazon WAF should store a sampling of the web requests that match the rules. You can view the sampled requests through the Amazon WAF console.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafv2WebAclActionDetails

Specifies the action that Amazon CloudFront or Amazon WAF takes when a web request matches the conditions in the rule.

Contents

Allow

Specifies that Amazon WAF should allow requests by default.

Type: [AwsWafv2ActionAllowDetails](#) object

Required: No

Block

Specifies that Amazon WAF should block requests by default.

Type: [AwsWafv2ActionBlockDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafv2WebAclCaptchaConfigDetails

Specifies how Amazon WAF should handle CAPTCHA evaluations for rules that don't have their own CaptchaConfig settings.

Contents

ImmunityTimeProperty

Determines how long a CAPTCHA timestamp in the token remains valid after the client successfully solves a CAPTCHA puzzle.

Type: [AwsWafv2WebAclCaptchaConfigImmunityTimePropertyDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafv2WebAclCaptchaConfigImmunityTimePropertyDetails

Used for CAPTCHA and challenge token settings. Determines how long a CAPTCHA or challenge timestamp remains valid after Amazon WAF updates it for a successful CAPTCHA or challenge response.

Contents

ImmunityTime

The amount of time, in seconds, that a CAPTCHA or challenge timestamp is considered valid by Amazon WAF.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafv2WebAclDetails

Details about an Amazon WAFv2 web Access Control List (ACL).

Contents

Arn

The Amazon Resource Name (ARN) of the web ACL that you want to associate with the resource.

Type: String

Pattern: `.*\S.*`

Required: No

Capacity

The web ACL capacity units (WCUs) currently being used by this web ACL.

Type: Long

Required: No

CaptchaConfig

Specifies how Amazon WAF should handle CAPTCHA evaluations for rules that don't have their own CaptchaConfig settings.

Type: [AwsWafv2WebAclCaptchaConfigDetails](#) object

Required: No

DefaultAction

The action to perform if none of the Rules contained in the web ACL match.

Type: [AwsWafv2WebAclActionDetails](#) object

Required: No

Description

A description of the web ACL that helps with identification.

Type: String

Pattern: `.*\S.*`

Required: No

Id

A unique identifier for the web ACL.

Type: String

Pattern: `.*\S.*`

Required: No

ManagedbyFirewallManager

Indicates whether this web ACL is managed by Amazon Firewall Manager.

Type: Boolean

Required: No

Name

The name of the web ACL.

Type: String

Pattern: `.*\S.*`

Required: No

Rules

The Rule statements used to identify the web requests that you want to allow, block, or count. Each rule includes one top-level statement that Amazon WAF uses to identify matching web requests, and parameters that govern how Amazon WAF handles them.

Type: Array of [AwsWafv2RulesDetails](#) objects

Required: No

VisibilityConfig

Defines and enables Amazon CloudWatch metrics and web request sample collection.

Type: [AwsWafv2VisibilityConfigDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafWebAclDetails

Provides information about an Amazon WAF web access control list (web ACL).

Contents

DefaultAction

The action to perform if none of the rules contained in the web ACL match.

Type: String

Pattern: `.*\S.*`

Required: No

Name

A friendly name or description of the web ACL. You can't change the name of a web ACL after you create it.

Type: String

Pattern: `.*\S.*`

Required: No

Rules

An array that contains the action for each rule in a web ACL, the priority of the rule, and the ID of the rule.

Type: Array of [AwsWafWebAclRule](#) objects

Required: No

WebAclId

A unique identifier for a web ACL.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AwsWafWebAclRule

Details for a rule in an Amazon WAF web ACL.

Contents

Action

Specifies the action that CloudFront or Amazon WAF takes when a web request matches the conditions in the rule.

Type: [WafAction](#) object

Required: No

ExcludedRules

Rules to exclude from a rule group.

Type: Array of [WafExcludedRule](#) objects

Required: No

OverrideAction

Use the `OverrideAction` to test your `RuleGroup`.

Any rule in a `RuleGroup` can potentially block a request. If you set the `OverrideAction` to `None`, the `RuleGroup` blocks a request if any individual rule in the `RuleGroup` matches the request and is configured to block that request.

However, if you first want to test the `RuleGroup`, set the `OverrideAction` to `Count`. The `RuleGroup` then overrides any block action specified by individual rules contained within the group. Instead of blocking matching requests, those requests are counted.

`ActivatedRule|OverrideAction` applies only when updating or adding a `RuleGroup` to a web ACL. In this case you don't use `ActivatedRule Action`. For all other update requests, `ActivatedRule Action` is used instead of `ActivatedRule OverrideAction`.

Type: [WafOverrideAction](#) object

Required: No

Priority

Specifies the order in which the rules in a web ACL are evaluated. Rules with a lower value for `Priority` are evaluated before rules with a higher value. The value must be a unique integer. If you add multiple rules to a web ACL, the values don't need to be consecutive.

Type: Integer

Required: No

RuleId

The identifier for a rule.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The rule type.

Valid values: `REGULAR` | `RATE_BASED` | `GROUP`

The default is `REGULAR`.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

WafAction

Details about the action that CloudFront or Amazon WAF takes when a web request matches the conditions in the rule.

Contents

Type

Specifies how you want Amazon WAF to respond to requests that match the settings in a rule.

Valid settings include the following:

- **ALLOW** - Amazon WAF allows requests
- **BLOCK** - Amazon WAF blocks requests
- **COUNT** - Amazon WAF increments a counter of the requests that match all of the conditions in the rule. Amazon WAF then continues to inspect the web request based on the remaining rules in the web ACL. You can't specify **COUNT** for the default action for a web ACL.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

WafExcludedRule

Details about a rule to exclude from a rule group.

Contents

RuleId

The unique identifier for the rule to exclude from the rule group.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

WafOverrideAction

Details about an override action for a rule.

Contents

Type

COUNT overrides the action specified by the individual rule within a RuleGroup .

If set to NONE, the rule's action takes place.

Type: String

Pattern: .*S.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Amazon X-Ray objects

Amazon X-Ray objects

- [AwsXrayEncryptionConfigDetails](#)

AwsXrayEncryptionConfigDetails

Information about the encryption configuration for Amazon X-Ray.

Contents

KeyId

The identifier of the KMS key that is used for encryption. Provided if Type is KMS.

Type: String

Pattern: `.*\S.*`

Required: No

Status

The current status of the encryption configuration. Valid values are ACTIVE or UPDATING.

When Status is equal to UPDATING, Amazon X-Ray might use both the old and new encryption.

Type: String

Pattern: `.*\S.*`

Required: No

Type

The type of encryption. KMS indicates that the encryption uses KMS keys. NONE indicates the default encryption.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Container objects

Container objects

- [ContainerDetails](#)
- [VolumeMount](#)

ContainerDetails

Container details related to a finding.

Contents

ContainerRuntime

The runtime of the container.

Type: String

Pattern: .*\\S.*

Required: No

ImageId

The identifier of the container image related to a finding.

Type: String

Pattern: .*\\S.*

Required: No

ImageName

The name of the container image related to a finding.

Type: String

Pattern: .*\\S.*

Required: No

LaunchedAt

Indicates when the container started.

For more information about the validation and formatting of timestamp fields in Amazon Security Hub, see [Timestamps](#).

Type: String

Pattern: .*\\S.*

Required: No

Name

The name of the container related to a finding.

Type: String

Pattern: `.*\S.*`

Required: No

Privileged

When this parameter is `true`, the container is given elevated privileges on the host container instance (similar to the root user).

Type: Boolean

Required: No

VolumeMounts

Provides information about the mounting of a volume in a container.

Type: Array of [VolumeMount](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

VolumeMount

Describes the mounting of a volume in a container.

Contents

MountPath

The path in the container at which the volume should be mounted.

Type: String

Pattern: `.*\S.*`

Required: No

Name

The name of the volume.

Type: String

Pattern: `.*\S.*`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing Amazon API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed Amazon API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an Amazon API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to Amazon Security Token Service (Amazon STS). For a list of services that support temporary security credentials from Amazon STS, see [Amazon Web Services services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from Amazon STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed Amazon API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all Amazon services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to Amazon standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or Amazon access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The Amazon access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an Amazon service.

HTTP Status Code: 400