

IAM Identity Center



IAM Identity Center: API Reference

Table of Contents

Welcome	1
Actions	2
AttachCustomerManagedPolicyReferenceToPermissionSet	5
Request Syntax	5
Request Parameters	5
Response Elements	6
Errors	6
See Also	7
AttachManagedPolicyToPermissionSet	8
Request Syntax	8
Request Parameters	8
Response Elements	9
Errors	9
See Also	10
CreateAccountAssignment	12
Request Syntax	12
Request Parameters	13
Response Syntax	14
Response Elements	15
Errors	15
See Also	16
CreateApplication	18
Request Syntax	18
Request Parameters	19
Response Syntax	21
Response Elements	21
Errors	21
See Also	22
CreateApplicationAssignment	24
Request Syntax	24
Request Parameters	24
Response Elements	25
Errors	25
See Also	26

CreateInstance	27
Request Syntax	27
Request Parameters	27
Response Syntax	28
Response Elements	28
Errors	29
See Also	30
CreateInstanceAccessControlAttributeConfiguration	31
Request Syntax	31
Request Parameters	31
Response Elements	32
Errors	32
See Also	33
CreatePermissionSet	35
Request Syntax	35
Request Parameters	35
Response Syntax	37
Response Elements	37
Errors	38
See Also	39
CreateTrustedTokenIssuer	40
Request Syntax	40
Request Parameters	40
Response Syntax	42
Response Elements	42
Errors	43
See Also	44
DeleteAccountAssignment	45
Request Syntax	45
Request Parameters	45
Response Syntax	47
Response Elements	47
Errors	48
See Also	49
DeleteApplication	50
Request Syntax	50

Request Parameters	50
Response Elements	50
Errors	50
See Also	51
DeleteApplicationAccessScope	53
Request Syntax	53
Request Parameters	53
Response Elements	54
Errors	54
See Also	55
DeleteApplicationAssignment	56
Request Syntax	56
Request Parameters	56
Response Elements	57
Errors	57
See Also	58
DeleteApplicationAuthenticationMethod	59
Request Syntax	59
Request Parameters	59
Response Elements	59
Errors	60
See Also	61
DeleteApplicationGrant	62
Request Syntax	62
Request Parameters	62
Response Elements	63
Errors	63
See Also	64
DeleteInlinePolicyFromPermissionSet	65
Request Syntax	65
Request Parameters	65
Response Elements	66
Errors	66
See Also	67
DeleteInstance	68
Request Syntax	68

Request Parameters	68
Response Elements	68
Errors	68
See Also	69
DeleteInstanceAccessControlAttributeConfiguration	71
Request Syntax	71
Request Parameters	71
Response Elements	71
Errors	71
See Also	72
DeletePermissionsBoundaryFromPermissionSet	74
Request Syntax	74
Request Parameters	74
Response Elements	75
Errors	75
See Also	76
DeletePermissionSet	77
Request Syntax	77
Request Parameters	77
Response Elements	78
Errors	78
See Also	79
DeleteTrustedTokenIssuer	80
Request Syntax	80
Request Parameters	80
Response Elements	80
Errors	81
See Also	82
DescribeAccountAssignmentCreationStatus	83
Request Syntax	83
Request Parameters	83
Response Syntax	84
Response Elements	84
Errors	84
See Also	85
DescribeAccountAssignmentDeletionStatus	86

Request Syntax	86
Request Parameters	86
Response Syntax	87
Response Elements	87
Errors	87
See Also	88
DescribeApplication	89
Request Syntax	89
Request Parameters	89
Response Syntax	89
Response Elements	90
Errors	92
See Also	93
DescribeApplicationAssignment	94
Request Syntax	94
Request Parameters	94
Response Syntax	95
Response Elements	95
Errors	96
See Also	97
DescribeApplicationProvider	98
Request Syntax	98
Request Parameters	98
Response Syntax	98
Response Elements	99
Errors	100
See Also	100
DescribeInstance	102
Request Syntax	102
Request Parameters	102
Response Syntax	102
Response Elements	103
Errors	104
See Also	105
DescribeInstanceAccessControlAttributeConfiguration	106
Request Syntax	106

Request Parameters	106
Response Syntax	106
Response Elements	107
Errors	107
See Also	108
DescribePermissionSet	110
Request Syntax	110
Request Parameters	110
Response Syntax	111
Response Elements	111
Errors	111
See Also	112
DescribePermissionSetProvisioningStatus	113
Request Syntax	113
Request Parameters	113
Response Syntax	114
Response Elements	114
Errors	114
See Also	115
DescribeTrustedTokenIssuer	116
Request Syntax	116
Request Parameters	116
Response Syntax	116
Response Elements	117
Errors	118
See Also	118
DetachCustomerManagedPolicyReferenceFromPermissionSet	120
Request Syntax	120
Request Parameters	120
Response Elements	121
Errors	121
See Also	122
DetachManagedPolicyFromPermissionSet	123
Request Syntax	123
Request Parameters	123
Response Elements	124

Errors	124
See Also	125
GetApplicationAccessScope	126
Request Syntax	126
Request Parameters	126
Response Syntax	127
Response Elements	127
Errors	127
See Also	128
GetApplicationAssignmentConfiguration	130
Request Syntax	130
Request Parameters	130
Response Syntax	130
Response Elements	130
Errors	131
See Also	132
GetApplicationAuthenticationMethod	133
Request Syntax	133
Request Parameters	133
Response Syntax	133
Response Elements	134
Errors	134
See Also	135
GetApplicationGrant	136
Request Syntax	136
Request Parameters	136
Response Syntax	137
Response Elements	137
Errors	137
See Also	138
GetInlinePolicyForPermissionSet	139
Request Syntax	139
Request Parameters	139
Response Syntax	140
Response Elements	140
Errors	140

See Also	141
GetPermissionsBoundaryForPermissionSet	143
Request Syntax	143
Request Parameters	143
Response Syntax	144
Response Elements	144
Errors	144
See Also	145
ListAccountAssignmentCreationStatus	146
Request Syntax	146
Request Parameters	146
Response Syntax	147
Response Elements	147
Errors	148
See Also	149
ListAccountAssignmentDeletionStatus	150
Request Syntax	150
Request Parameters	150
Response Syntax	151
Response Elements	151
Errors	152
See Also	153
ListAccountAssignments	154
Request Syntax	154
Request Parameters	154
Response Syntax	155
Response Elements	156
Errors	156
See Also	157
ListAccountAssignmentsForPrincipal	159
Request Syntax	159
Request Parameters	159
Response Syntax	161
Response Elements	161
Errors	162
See Also	163

ListAccountsForProvisionedPermissionSet	164
Request Syntax	164
Request Parameters	164
Response Syntax	165
Response Elements	166
Errors	166
See Also	167
ListApplicationAccessScopes	168
Request Syntax	168
Request Parameters	168
Response Syntax	169
Response Elements	169
Errors	170
See Also	171
ListApplicationAssignments	172
Request Syntax	172
Request Parameters	172
Response Syntax	173
Response Elements	173
Errors	174
See Also	175
ListApplicationAssignmentsForPrincipal	176
Request Syntax	176
Request Parameters	176
Response Syntax	178
Response Elements	178
Errors	179
See Also	180
ListApplicationAuthenticationMethods	181
Request Syntax	181
Request Parameters	181
Response Syntax	182
Response Elements	182
Errors	182
See Also	183
ListApplicationGrants	185

Request Syntax	185
Request Parameters	185
Response Syntax	186
Response Elements	186
Errors	186
See Also	187
ListApplicationProviders	189
Request Syntax	189
Request Parameters	189
Response Syntax	190
Response Elements	190
Errors	191
See Also	192
ListApplications	193
Request Syntax	193
Request Parameters	193
Response Syntax	194
Response Elements	195
Errors	196
See Also	196
ListCustomerManagedPolicyReferencesInPermissionSet	198
Request Syntax	198
Request Parameters	198
Response Syntax	199
Response Elements	199
Errors	200
See Also	201
ListInstances	202
Request Syntax	202
Request Parameters	202
Response Syntax	203
Response Elements	203
Errors	204
See Also	204
ListManagedPoliciesInPermissionSet	206
Request Syntax	206

Request Parameters	206
Response Syntax	207
Response Elements	207
Errors	208
See Also	209
ListPermissionSetProvisioningStatus	210
Request Syntax	210
Request Parameters	210
Response Syntax	211
Response Elements	211
Errors	212
See Also	213
ListPermissionSets	214
Request Syntax	214
Request Parameters	214
Response Syntax	215
Response Elements	215
Errors	216
See Also	216
ListPermissionSetsProvisionedToAccount	218
Request Syntax	218
Request Parameters	218
Response Syntax	219
Response Elements	220
Errors	220
See Also	221
ListTagsForResource	222
Request Syntax	222
Request Parameters	222
Response Syntax	223
Response Elements	223
Errors	224
See Also	225
ListTrustedTokenIssuers	226
Request Syntax	226
Request Parameters	226

Response Syntax	227
Response Elements	227
Errors	228
See Also	229
ProvisionPermissionSet	230
Request Syntax	230
Request Parameters	230
Response Syntax	231
Response Elements	231
Errors	232
See Also	233
PutApplicationAccessScope	234
Request Syntax	234
Request Parameters	234
Response Elements	235
Errors	235
See Also	236
PutApplicationAssignmentConfiguration	237
Request Syntax	237
Request Parameters	237
Response Elements	238
Errors	238
See Also	239
PutApplicationAuthenticationMethod	240
Request Syntax	240
Request Parameters	240
Response Elements	241
Errors	241
See Also	242
PutApplicationGrant	243
Request Syntax	244
Request Parameters	244
Response Elements	245
Errors	245
See Also	246
PutInlinePolicyToPermissionSet	247

Request Syntax	247
Request Parameters	247
Response Elements	248
Errors	248
See Also	249
PutPermissionsBoundaryToPermissionSet	251
Request Syntax	251
Request Parameters	251
Response Elements	252
Errors	252
See Also	253
TagResource	254
Request Syntax	254
Request Parameters	254
Response Elements	255
Errors	255
See Also	256
UntagResource	258
Request Syntax	258
Request Parameters	258
Response Elements	259
Errors	259
See Also	260
UpdateApplication	262
Request Syntax	262
Request Parameters	262
Response Elements	263
Errors	263
See Also	264
UpdateInstance	266
Request Syntax	266
Request Parameters	266
Response Elements	267
Errors	267
See Also	268
UpdateInstanceAccessControlAttributeConfiguration	269

Request Syntax	269
Request Parameters	269
Response Elements	270
Errors	270
See Also	271
UpdatePermissionSet	272
Request Syntax	272
Request Parameters	272
Response Elements	273
Errors	274
See Also	275
UpdateTrustedTokenIssuer	276
Request Syntax	276
Request Parameters	276
Response Elements	277
Errors	277
See Also	278
Data Types	279
AccessControlAttribute	281
Contents	281
See Also	281
AccessControlAttributeValue	282
Contents	282
See Also	282
AccountAssignment	283
Contents	283
See Also	284
AccountAssignmentForPrincipal	285
Contents	285
See Also	286
AccountAssignmentOperationStatus	287
Contents	287
See Also	289
AccountAssignmentOperationStatusMetadata	290
Contents	290
See Also	290

Application	292
Contents	292
See Also	294
ApplicationAssignment	295
Contents	295
See Also	296
ApplicationAssignmentForPrincipal	297
Contents	297
See Also	298
ApplicationProvider	299
Contents	299
See Also	300
AttachedManagedPolicy	301
Contents	301
See Also	301
AuthenticationMethod	302
Contents	302
See Also	302
AuthenticationMethodItem	303
Contents	303
See Also	303
AuthorizationCodeGrant	304
Contents	304
See Also	304
AuthorizedTokenIssuer	305
Contents	305
See Also	305
CustomerManagedPolicyReference	307
Contents	307
See Also	307
DisplayData	309
Contents	309
See Also	309
Grant	311
Contents	311
See Also	312

GrantItem	313
Contents	313
See Also	313
IamAuthenticationMethod	314
Contents	314
See Also	314
InstanceAccessControlAttributeConfiguration	315
Contents	315
See Also	315
InstanceMetadata	316
Contents	316
See Also	317
JwtBearerGrant	318
Contents	318
See Also	318
ListAccountAssignmentsFilter	319
Contents	319
See Also	319
ListApplicationAssignmentsFilter	320
Contents	320
See Also	320
ListApplicationsFilter	321
Contents	321
See Also	321
OidcJwtConfiguration	322
Contents	322
See Also	323
OidcJwtUpdateConfiguration	324
Contents	324
See Also	325
OperationStatusFilter	326
Contents	326
See Also	326
PermissionsBoundary	327
Contents	327
See Also	328

PermissionSet	329
Contents	329
See Also	330
PermissionSetProvisioningStatus	331
Contents	331
See Also	332
PermissionSetProvisioningStatusMetadata	333
Contents	333
See Also	333
PortalOptions	335
Contents	335
See Also	335
RefreshTokenGrant	336
Contents	336
See Also	336
ResourceServerConfig	337
Contents	337
See Also	337
ResourceServerScopeDetails	338
Contents	338
See Also	338
ScopeDetails	339
Contents	339
See Also	339
SignInOptions	341
Contents	341
See Also	341
Tag	343
Contents	343
See Also	343
TokenExchangeGrant	344
Contents	344
See Also	344
TrustedTokenIssuerConfiguration	345
Contents	345
See Also	345

TrustedTokenIssuerMetadata	346
Contents	346
See Also	347
TrustedTokenIssuerUpdateConfiguration	348
Contents	348
See Also	348
UpdateApplicationPortalOptions	349
Contents	349
See Also	349
Common Parameters	350
Common Errors	353
Document History	355

Welcome to the IAM Identity Center API Reference

Amazon IAM Identity Center is the Amazon solution for connecting your workforce users to Amazon managed applications and other Amazon resources. You can connect your existing identity provider and synchronize users and groups from your directory, or create and manage your users directly in IAM Identity Center. You can then use IAM Identity Center for either or both of the following:

- User access to applications
- User access to Amazon accounts

This guide provides information about single sign-on operations that you can use for access to applications and Amazon Web Services accounts. For information about IAM Identity Center features, see the [IAM Identity Center User Guide](#).

 **Note**

IAM Identity Center uses the `sso` and `identitystore` API namespaces.

Many API operations for IAM Identity Center rely on identifiers for users and groups, known as principals. For more information about how to work with principals and principal IDs in IAM Identity Center, see the [Identity Store API Reference](#).

 **Note**

Amazon provides SDKs that consist of libraries and sample code for various programming languages and platforms (Java, Ruby, .Net, iOS, Android, and more). The SDKs provide a convenient way to programmatically access IAM Identity Center and other Amazon services. For more information about the Amazon SDKs, including how to download and install them, see [Tools for Amazon Web Services](#).

Actions

The following actions are supported:

- [AttachCustomerManagedPolicyReferenceToPermissionSet](#)
- [AttachManagedPolicyToPermissionSet](#)
- [CreateAccountAssignment](#)
- [CreateApplication](#)
- [CreateApplicationAssignment](#)
- [CreateInstance](#)
- [CreateInstanceAccessControlAttributeConfiguration](#)
- [CreatePermissionSet](#)
- [CreateTrustedTokenIssuer](#)
- [DeleteAccountAssignment](#)
- [DeleteApplication](#)
- [DeleteApplicationAccessScope](#)
- [DeleteApplicationAssignment](#)
- [DeleteApplicationAuthenticationMethod](#)
- [DeleteApplicationGrant](#)
- [DeleteInlinePolicyFromPermissionSet](#)
- [DeleteInstance](#)
- [DeleteInstanceAccessControlAttributeConfiguration](#)
- [DeletePermissionsBoundaryFromPermissionSet](#)
- [DeletePermissionSet](#)
- [DeleteTrustedTokenIssuer](#)
- [DescribeAccountAssignmentCreationStatus](#)
- [DescribeAccountAssignmentDeletionStatus](#)
- [DescribeApplication](#)
- [DescribeApplicationAssignment](#)
- [DescribeApplicationProvider](#)
- [DescribeInstance](#)

- [DescribeInstanceAccessControlAttributeConfiguration](#)
- [DescribePermissionSet](#)
- [DescribePermissionSetProvisioningStatus](#)
- [DescribeTrustedTokenIssuer](#)
- [DetachCustomerManagedPolicyReferenceFromPermissionSet](#)
- [DetachManagedPolicyFromPermissionSet](#)
- [GetApplicationAccessScope](#)
- [GetApplicationAssignmentConfiguration](#)
- [GetApplicationAuthenticationMethod](#)
- [GetApplicationGrant](#)
- [GetInlinePolicyForPermissionSet](#)
- [GetPermissionsBoundaryForPermissionSet](#)
- [ListAccountAssignmentCreationStatus](#)
- [ListAccountAssignmentDeletionStatus](#)
- [ListAccountAssignments](#)
- [ListAccountAssignmentsForPrincipal](#)
- [ListAccountsForProvisionedPermissionSet](#)
- [ListApplicationAccessScopes](#)
- [ListApplicationAssignments](#)
- [ListApplicationAssignmentsForPrincipal](#)
- [ListApplicationAuthenticationMethods](#)
- [ListApplicationGrants](#)
- [ListApplicationProviders](#)
- [ListApplications](#)
- [ListCustomerManagedPolicyReferencesInPermissionSet](#)
- [ListInstances](#)
- [ListManagedPoliciesInPermissionSet](#)
- [ListPermissionSetProvisioningStatus](#)
- [ListPermissionSets](#)
- [ListPermissionSetsProvisionedToAccount](#)

- [ListTagsForResource](#)
- [ListTrustedTokenIssuers](#)
- [ProvisionPermissionSet](#)
- [PutApplicationAccessScope](#)
- [PutApplicationAssignmentConfiguration](#)
- [PutApplicationAuthenticationMethod](#)
- [PutApplicationGrant](#)
- [PutInlinePolicyToPermissionSet](#)
- [PutPermissionsBoundaryToPermissionSet](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateApplication](#)
- [UpdateInstance](#)
- [UpdateInstanceAccessControlAttributeConfiguration](#)
- [UpdatePermissionSet](#)
- [UpdateTrustedTokenIssuer](#)

AttachCustomerManagedPolicyReferenceToPermissionSet

Attaches the specified customer managed policy to the specified [PermissionSet](#).

Request Syntax

```
{  
    "CustomerManagedPolicyReference": {  
        "Name": "string",  
        "Path": "string"  
    },  
    "InstanceArn": "string",  
    "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[CustomerManagedPolicyReference](#)

Specifies the name and path of a customer managed policy. You must have an IAM policy that matches the name and path in each Amazon Web Services account where you want to deploy your permission set.

Type: [CustomerManagedPolicyReference](#) object

Required: Yes

[InstanceArn](#)

The ARN of the IAM Identity Center instance under which the operation will be executed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

PermissionSetArn

The ARN of the PermissionSet.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Indicates that the principal has crossed the permitted number of resources that can be created.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

AttachManagedPolicyToPermissionSet

Attaches an Amazon managed policy ARN to a permission set.

Note

If the permission set is already referenced by one or more account assignments, you will need to call [ProvisionPermissionSet](#) after this operation. Calling ProvisionPermissionSet applies the corresponding IAM policy updates to all assigned accounts.

Request Syntax

```
{  
    "InstanceArn": "string",  
    "ManagedPolicyArn": "string",  
    "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

ManagedPolicyArn

The Amazon managed policy ARN to be attached to a permission set.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):iam::aws:policy((/[A-Za-z0-9\.,\+=@_-]+*)|([A-Za-z0-9\.,\+=@_-]+))

Required: Yes

PermissionSetArn

The ARN of the [PermissionSet](#) that the managed policy should be attached to.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Indicates that the principal has crossed the permitted number of resources that can be created.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateAccountAssignment

Assigns access to a principal for a specified Amazon Web Services account using a specified permission set.

Note

The term *principal* here refers to a user or group that is defined in IAM Identity Center.

Note

As part of a successful CreateAccountAssignment call, the specified permission set will automatically be provisioned to the account in the form of an IAM policy. That policy is attached to the IAM role created in IAM Identity Center. If the permission set is subsequently updated, the corresponding IAM policies attached to roles in your accounts will not be updated automatically. In this case, you must call [ProvisionPermissionSet](#) to make these updates.

Note

After a successful response, call [DescribeAccountAssignmentCreationStatus](#) to describe the status of an assignment creation request.

Request Syntax

```
{  
    "InstanceArn": "string",  
    "PermissionSetArn": "string",  
    "PrincipalId": "string",  
    "PrincipalType": "string",  
    "TargetId": "string",  
    "TargetType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

PermissionSetArn

The ARN of the permission set that the admin wants to grant the principal access to.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Required: Yes

PrincipalId

An identifier for an object in IAM Identity Center, such as a user or group. PrincipalIds are GUIDs (For example, f81d4fae-7dec-11d0-a765-00a0c91e6bf6). For more information about PrincipalIds in IAM Identity Center, see the [IAM Identity Center Identity Store API Reference](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 47.

Pattern: ([0-9a-f]{10}-|)[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}

Required: Yes

PrincipalType

The entity type for which the assignment will be created.

Type: String

Valid Values: USER | GROUP

Required: Yes

TargetId

TargetID is an Amazon Web Services account identifier, (For example, 123456789012).

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Required: Yes

TargetType

The entity type for which the assignment will be created.

Type: String

Valid Values: AWS_ACCOUNT

Required: Yes

Response Syntax

```
{  
  "AccountAssignmentCreationStatus": {  
    "CreatedDate": number,  
    "FailureReason": "string",  
    "PermissionSetArn": "string",  
  }  
}
```

```
"PrincipalId": "string",
"PrincipalType": "string",
"RequestId": "string",
"Status": "string",
"TargetId": "string",
"TargetType": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AccountAssignmentCreationStatus](#)

The status object for the account assignment creation operation.

Type: [AccountAssignmentOperationStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Indicates that the principal has crossed the permitted number of resources that can be created.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateApplication

Creates an OAuth 2.0 customer managed application in IAM Identity Center for the given application provider.

Note

This API does not support creating SAML 2.0 customer managed applications or Amazon managed applications. To learn how to create an Amazon managed application, see the application user guide. You can create a SAML 2.0 customer managed application in the Amazon Web Services Management Console only. See [Setting up customer managed SAML 2.0 applications](#). For more information on these application types, see [Amazon managed applications](#).

Request Syntax

```
{
  "ApplicationProviderArn": "string",
  "ClientToken": "string",
  "Description": "string",
  "InstanceArn": "string",
  "Name": "string",
  "PortalOptions": {
    "SignInOptions": {
      "ApplicationUrl": "string",
      "Origin": "string"
    },
    "Visibility": "string"
  },
  "Status": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationProviderArn](#)

The ARN of the application provider under which the operation will run.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::aws:applicationProvider/[a-zA-Z0-9-/]+`

Required: Yes

[ClientToken](#)

Specifies a unique, case-sensitive ID that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then Amazon generates a random one for you.

If you retry the operation with the same ClientToken, but with different parameters, the retry fails with an `IdempotentParameterMismatch` error.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[!-~]+`

Required: No

[Description](#)

The description of the [Application](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

InstanceArn

The ARN of the instance of IAM Identity Center under which the operation will run. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

Name

The name of the [Application](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[\S\s]*`

Required: Yes

PortalOptions

A structure that describes the options for the portal associated with an application.

Type: [PortalOptions](#) object

Required: No

Status

Specifies whether the application is enabled or disabled.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

Tags

Specifies tags to be attached to the application.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 75 items.

Required: No

Response Syntax

```
{  
  "ApplicationArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ApplicationArn](#)

Specifies the ARN of the application.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Indicates that the principal has crossed the permitted number of resources that can be created.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateApplicationAssignment

Grant application access to a user or group.

Request Syntax

```
{  
  "ApplicationArn": "string",  
  "PrincipalId": "string",  
  "PrincipalType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationArn](#)

The ARN of the application for which the assignment is created.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}`

Required: Yes

[PrincipalId](#)

An identifier for an object in IAM Identity Center, such as a user or group. PrincipalIds are GUIDs (For example, f81d4fae-7dec-11d0-a765-00a0c91e6bf6). For more information about PrincipalIds in IAM Identity Center, see the [IAM Identity Center Identity Store API Reference](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 47.

Pattern: `([0-9a-f]{10}-|)[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}`

Required: Yes

PrincipalType

The entity type for which the assignment will be created.

Type: String

Valid Values: USER | GROUP

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Indicates that the principal has crossed the permitted number of resources that can be created.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateInstance

Creates an instance of IAM Identity Center for a standalone Amazon Web Services account that is not managed by Amazon Organizations or a member Amazon Web Services account in an organization. You can create only one instance per account and across all Amazon Web Services Regions.

The CreateInstance request is rejected if the following apply:

- The instance is created within the organization management account.
- An instance already exists in the same account.

Request Syntax

```
{  
    "ClientToken": "string",  
    "Name": "string",  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ClientToken](#)

Specifies a unique, case-sensitive ID that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then Amazon generates a random one for you.

If you retry the operation with the same ClientToken, but with different parameters, the retry fails with an IdempotentParameterMismatch error.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [! -~]+

Required: No

Name

The name of the instance of IAM Identity Center.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: [\w+=, .@-]+

Required: No

Tags

Specifies tags to be attached to the instance of IAM Identity Center.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 75 items.

Required: No

Response Syntax

```
{  
  "InstanceArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InstanceArn

The ARN of the instance of IAM Identity Center under which the operation will run.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ServiceQuotaExceededException

Indicates that the principal has crossed the permitted number of resources that can be created.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateInstanceAccessControlAttributeConfiguration

Enables the attributes-based access control (ABAC) feature for the specified IAM Identity Center instance. You can also specify new attributes to add to your ABAC configuration during the enabling process. For more information about ABAC, see [Attribute-Based Access Control](#) in the *IAM Identity Center User Guide*.

Note

After a successful response, call `DescribeInstanceAccessControlAttributeConfiguration` to validate that `InstanceAccessControlAttributeConfiguration` was created.

Request Syntax

```
{  
    "InstanceAccessControlAttributeConfiguration": {  
        "AccessControlAttributes": [  
            {  
                "Key": "string",  
                "Value": {  
                    "Source": [ "string" ]  
                }  
            }  
        ]  
    },  
    "InstanceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[InstanceAccessControlAttributeConfiguration](#)

Specifies the IAM Identity Center identity store attributes to add to your ABAC configuration. When using an external identity provider as an identity source, you can pass attributes through

the SAML assertion. Doing so provides an alternative to configuring attributes from the IAM Identity Center identity store. If a SAML assertion passes any of these attributes, IAM Identity Center will replace the attribute value with the value from the IAM Identity Center identity store.

Type: [InstanceAccessControlAttributeConfiguration](#) object

Required: Yes

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreatePermissionSet

Creates a permission set within a specified IAM Identity Center instance.

Note

To grant users and groups access to Amazon Web Services account resources, use [CreateAccountAssignment](#).

Request Syntax

```
{  
    "Description": "string",  
    "InstanceArn": "string",  
    "Name": "string",  
    "RelayState": "string",  
    "SessionDuration": "string",  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Description

The description of the [PermissionSet](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 700.

Pattern: [\u0009\u000A\u000D\u0020-\u007E\u00A1-\u00FF]*

Required: No

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

Name

The name of the [PermissionSet](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `[\w+=, .@-]+`

Required: Yes

RelayState

Used to redirect users within the application during the federation authentication process.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 240.

Pattern: `[a-zA-Z0-9&$@#\\"%?=~\-_'"|!:,.;*+\[\]\ \(\)\{\}\]+`

Required: No

SessionDuration

The length of time that the application user sessions are valid in the ISO-8601 standard.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: (-?)P(?=\d|T\d)(?:(\d+)Y)?(?:(\d+)M)?(?:(\d+)([DW]))?(?:T(?:(\d+)H)?(?:(\d+)M)?(?:(\d+(?:\.\d+)?)S)?))?

Required: No

Tags

The tags to attach to the new [PermissionSet](#).

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 75 items.

Required: No

Response Syntax

```
{  
  "PermissionSet": {  
    "CreatedDate": number,  
    "Description": "string",  
    "Name": "string",  
    "PermissionSetArn": "string",  
    "RelayState": "string",  
    "SessionDuration": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[PermissionSet](#)

Defines the level of access on an Amazon Web Services account.

Type: [PermissionSet](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Indicates that the principal has crossed the permitted number of resources that can be created.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateTrustedTokenIssuer

Creates a connection to a trusted token issuer in an instance of IAM Identity Center. A trusted token issuer enables trusted identity propagation to be used with applications that authenticate outside of Amazon.

This trusted token issuer describes an external identity provider (IdP) that can generate claims or assertions in the form of access tokens for a user. Applications enabled for IAM Identity Center can use these tokens for authentication.

Request Syntax

```
{  
    "ClientToken": "string",  
    "InstanceArn": "string",  
    "Name": "string",  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ],  
    "TrustedTokenIssuerConfiguration": { ... },  
    "TrustedTokenIssuerType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ClientToken](#)

Specifies a unique, case-sensitive ID that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you also pass the same value for all other parameters. We recommend that you use a [UUID type of value..](#)

If you don't provide this value, then Amazon generates a random one for you.

If you retry the operation with the same ClientToken, but with different parameters, the retry fails with an IdempotentParameterMismatch error.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [! -~]+

Required: No

InstanceArn

Specifies the ARN of the instance of IAM Identity Center to contain the new trusted token issuer configuration.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

Name

Specifies the name of the new trusted token issuer configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [\w+=,.@-]+

Required: Yes

Tags

Specifies tags to be attached to the new trusted token issuer configuration.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 75 items.

Required: No

[TrustedTokenIssuerConfiguration](#)

Specifies settings that apply to the new trusted token issuer configuration. The settings that are available depend on what TrustedTokenIssuerType you specify.

Type: [TrustedTokenIssuerConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

[TrustedTokenIssuerType](#)

Specifies the type of the new trusted token issuer.

Type: String

Valid Values: OIDC_JWT

Required: Yes

Response Syntax

```
{  
    "TrustedTokenIssuerArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[TrustedTokenIssuerArn](#)

The ARN of the new trusted token issuer configuration.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::
\d{12}:trustedTokenIssuer/(sso)?ins-[a-zA-Z0-9-.]{16}/tti-[a-f0-9]{8}-
[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ServiceQuotaExceededException

Indicates that the principal has crossed the permitted number of resources that can be created.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteAccountAssignment

Deletes a principal's access from a specified Amazon Web Services account using a specified permission set.

Note

After a successful response, call `DescribeAccountAssignmentDeletionStatus` to describe the status of an assignment deletion request.

Request Syntax

```
{  
    "InstanceArn": "string",  
    "PermissionSetArn": "string",  
    "PrincipalId": "string",  
    "PrincipalType": "string",  
    "TargetId": "string",  
    "TargetType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

PermissionSetArn

The ARN of the permission set that will be used to remove access.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: Yes

PrincipalId

An identifier for an object in IAM Identity Center, such as a user or group. PrincipalIds are GUIDs (For example, f81d4fae-7dec-11d0-a765-00a0c91e6bf6). For more information about PrincipalIds in IAM Identity Center, see the [IAM Identity Center Identity Store API Reference](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 47.

Pattern: ([0-9a-f]{10}-|)[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}

Required: Yes

PrincipalType

The entity type for which the assignment will be deleted.

Type: String

Valid Values: USER | GROUP

Required: Yes

TargetId

TargetID is an Amazon Web Services account identifier, (For example, 123456789012).

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Required: Yes

TargetType

The entity type for which the assignment will be deleted.

Type: String

Valid Values: AWS_ACCOUNT

Required: Yes

Response Syntax

```
{  
    "AccountAssignmentDeletionStatus": {  
        "CreatedDate": "number",  
        "FailureReason": "string",  
        "PermissionSetArn": "string",  
        "PrincipalId": "string",  
        "PrincipalType": "string",  
        "RequestId": "string",  
        "Status": "string",  
        "TargetId": "string",  
        "TargetType": "string"  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccountAssignmentDeletionStatus

The status object for the account assignment deletion operation.

Type: [AccountAssignmentOperationStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteApplication

Deletes the association with the application. The connected service resource still exists.

Request Syntax

```
{  
    "ApplicationArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ApplicationArn

Specifies the ARN of the application. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteApplicationAccessScope

Deletes an IAM Identity Center access scope from an application.

Request Syntax

```
{  
  "ApplicationArn": "string",  
  "Scope": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ApplicationArn

Specifies the ARN of the application with the access scope to delete.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

Required: Yes

Scope

Specifies the name of the access scope to remove from the application.

Type: String

Pattern: ([A-Za-z0-9_]{1,50})(:[A-Za-z0-9_]{1,50}){0,1}(:[A-Za-z0-9_]{1,50}){0,1}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteApplicationAssignment

Revoke application access to an application by deleting application assignments for a user or group.

Request Syntax

```
{  
    "ApplicationArn": "string",  
    "PrincipalId": "string",  
    "PrincipalType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationArn](#)

Specifies the ARN of the application.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

Required: Yes

[PrincipalId](#)

An identifier for an object in IAM Identity Center, such as a user or group. PrincipalIds are GUIDs (For example, f81d4fae-7dec-11d0-a765-00a0c91e6bf6). For more information about PrincipalIds in IAM Identity Center, see the [IAM Identity Center Identity Store API Reference](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 47.

Pattern: ([0-9a-f]{10}-|)[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}

Required: Yes

PrincipalType

The entity type for which the assignment will be deleted.

Type: String

Valid Values: USER | GROUP

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteApplicationAuthenticationMethod

Deletes an authentication method from an application.

Request Syntax

```
{  
    "ApplicationArn": "string",  
    "AuthenticationMethodType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ApplicationArn

Specifies the ARN of the application with the authentication method to delete.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

Required: Yes

AuthenticationMethodType

Specifies the authentication method type to delete from the application.

Type: String

Valid Values: IAM

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteApplicationGrant

Deletes a grant from an application.

Request Syntax

```
{  
    "ApplicationArn": "string",  
    "GrantType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationArn](#)

Specifies the ARN of the application with the grant to delete.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

Required: Yes

[GrantType](#)

Specifies the type of grant to delete from the application.

Type: String

Valid Values: authorization_code | refresh_token | urn:ietf:params:oauth:grant-type:jwt-bearer | urn:ietf:params:oauth:grant-type:token-exchange

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteInlinePolicyFromPermissionSet

Deletes the inline policy from a specified permission set.

Request Syntax

```
{  
    "InstanceArn": "string",  
    "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

PermissionSetArn

The ARN of the permission set that will be used to remove access.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteInstance

Deletes the instance of IAM Identity Center. Only the account that owns the instance can call this API. Neither the delegated administrator nor member account can delete the organization instance, but those roles can delete their own instance.

Request Syntax

```
{  
    "InstanceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the instance of IAM Identity Center under which the operation will run.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteInstanceAccessControlAttributeConfiguration

Disables the attributes-based access control (ABAC) feature for the specified IAM Identity Center instance and deletes all of the attribute mappings that have been configured. Once deleted, any attributes that are received from an identity source and any custom attributes you have previously configured will not be passed. For more information about ABAC, see [Attribute-Based Access Control](#) in the *IAM Identity Center User Guide*.

Request Syntax

```
{  
    "InstanceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeletePermissionsBoundaryFromPermissionSet

Deletes the permissions boundary from a specified [PermissionSet](#).

Request Syntax

```
{  
    "InstanceArn": "string",  
    "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

PermissionSetArn

The ARN of the PermissionSet.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeletePermissionSet

Deletes the specified permission set.

Request Syntax

```
{  
    "InstanceArn": "string",  
    "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

PermissionSetArn

The ARN of the permission set that should be deleted.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteTrustedTokenIssuer

Deletes a trusted token issuer configuration from an instance of IAM Identity Center.

Note

Deleting this trusted token issuer configuration will cause users to lose access to any applications that are configured to use the trusted token issuer.

Request Syntax

```
{  
    "TrustedTokenIssuerArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

TrustedTokenIssuerArn

Specifies the ARN of the trusted token issuer configuration to delete.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::
\d{12}:trustedTokenIssuer/(sso)?ins-[a-zA-Z0-9-.]{16}/tti-[a-f0-9]{8}-
[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeAccountAssignmentCreationStatus

Describes the status of the assignment creation request.

Request Syntax

```
{  
    "AccountAssignmentCreationRequestId": "string",  
    "InstanceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AccountAssignmentCreationRequestId](#)

The identifier that is used to track the request operation progress.

Type: String

Length Constraints: Fixed length of 36.

Pattern: \b[0-9a-f]{8}\b-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-\b[0-9a-f]{12}\b

Required: Yes

[InstanceArn](#)

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

Response Syntax

```
{  
    "AccountAssignmentCreationStatus": {  
        "CreatedDate": number,  
        "FailureReason": "string",  
        "PermissionSetArn": "string",  
        "PrincipalId": "string",  
        "PrincipalType": "string",  
        "RequestId": "string",  
        "Status": "string",  
        "TargetId": "string",  
        "TargetType": "string"  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AccountAssignmentCreationStatus](#)

The status object for the account assignment creation operation.

Type: [AccountAssignmentOperationStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeAccountAssignmentDeletionStatus

Describes the status of the assignment deletion request.

Request Syntax

```
{  
    "AccountAssignmentDeletionRequestId": "string",  
    "InstanceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AccountAssignmentDeletionRequestId](#)

The identifier that is used to track the request operation progress.

Type: String

Length Constraints: Fixed length of 36.

Pattern: \b[0-9a-f]{8}\b-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-\b[0-9a-f]{12}\b

Required: Yes

[InstanceArn](#)

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

Response Syntax

```
{  
    "AccountAssignmentDeletionStatus": {  
        "CreatedDate": number,  
        "FailureReason": "string",  
        "PermissionSetArn": "string",  
        "PrincipalId": "string",  
        "PrincipalType": "string",  
        "RequestId": "string",  
        "Status": "string",  
        "TargetId": "string",  
        "TargetType": "string"  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AccountAssignmentDeletionStatus](#)

The status object for the account assignment deletion operation.

Type: [AccountAssignmentOperationStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeApplication

Retrieves the details of an application associated with an instance of IAM Identity Center.

Request Syntax

```
{  
    "ApplicationArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationArn](#)

Specifies the ARN of the application. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

Required: Yes

Response Syntax

```
{  
    "ApplicationAccount": "string",  
    "ApplicationArn": "string",  
    "ApplicationProviderArn": "string",  
    "CreatedDate": number,  
    "Description": "string",  
    "InstanceArn": "string",  
}
```

```
"Name": "string",
"PortalOptions": {
    "SignInOptionsApplicationUrl": "string",
        "Origin": "string"
    },
    "Visibility": "string"
},
"Status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ApplicationAccount](#)

The account ID.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

[ApplicationArn](#)

Specifies the ARN of the application.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

[ApplicationProviderArn](#)

The ARN of the application provider under which the operation will run.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::aws:applicationProvider/[a-zA-Z0-9-/]+`

[CreatedDate](#)

The date the application was created.

Type: `Timestamp`

[Description](#)

The description of the [Application](#).

Type: `String`

Length Constraints: Minimum length of 1. Maximum length of 128.

[InstanceArn](#)

The ARN of the IAM Identity Center application under which the operation will run. For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) and [Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: `String`

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

[Name](#)

The application name.

Type: `String`

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[\S\s]*`

[PortalOptions](#)

A structure that describes the options for the portal associated with an application.

Type: [PortalOptions](#) object

Status

Specifies whether the application is enabled or disabled.

Type: String

Valid Values: ENABLED | DISABLED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeApplicationAssignment

Retrieves a direct assignment of a user or group to an application. If the user doesn't have a direct assignment to the application, the user may still have access to the application through a group. Therefore, don't use this API to test access to an application for a user. Instead use [ListApplicationAssignmentsForPrincipal](#).

Request Syntax

```
{  
    "ApplicationArn": "string",  
    "PrincipalId": "string",  
    "PrincipalType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationArn](#)

Specifies the ARN of the application. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

Required: Yes

[PrincipalId](#)

An identifier for an object in IAM Identity Center, such as a user or group. PrincipalIds are GUIDs (For example, f81d4fae-7dec-11d0-a765-00a0c91e6bf6). For more information about PrincipalIds in IAM Identity Center, see the [IAM Identity Center Identity Store API Reference](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 47.

Pattern: ([0-9a-f]{10}-|)[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}

Required: Yes

PrincipalType

The entity type for which the assignment will be created.

Type: String

Valid Values: USER | GROUP

Required: Yes

Response Syntax

```
{  
    "ApplicationArn": "string",  
    "PrincipalId": "string",  
    "PrincipalType": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationArn

Specifies the ARN of the application. For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) and [Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::
\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

PrincipalId

An identifier for an object in IAM Identity Center, such as a user or group. PrincipalIds are GUIDs (For example, f81d4fae-7dec-11d0-a765-00a0c91e6bf6). For more information about PrincipalIds in IAM Identity Center, see the [IAM Identity Center Identity Store API Reference](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 47.

Pattern: ([0-9a-f]{10}-|)[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}

PrincipalType

The entity type for which the assignment will be created.

Type: String

Valid Values: USER | GROUP

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeApplicationProvider

Retrieves details about a provider that can be used to connect an Amazon managed application or customer managed application to IAM Identity Center.

Request Syntax

```
{  
    "ApplicationProviderArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationProviderArn](#)

Specifies the ARN of the application provider for which you want details.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::aws:applicationProvider/[a-zA-Z0-9-/]+

Required: Yes

Response Syntax

```
{  
    "ApplicationProviderArn": "string",  
    "DisplayData": {  
        "Description": "string",  
        "DisplayName": "string",  
        "IconUrl": "string"  
    },  
    "FederationProtocol": "string",
```

```
"ResourceServerConfig": {  
    "Scopes": {  
        "string": {  
            "DetailedTitle": "string",  
            "LongDescription": "string"  
        }  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ApplicationProviderArn](#)

The ARN of the application provider.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::aws:applicationProvider/[a-zA-Z0-9-/]+

[DisplayData](#)

A structure with details about the display data for the application provider.

Type: [DisplayData](#) object

[FederationProtocol](#)

The protocol used to federate to the application provider.

Type: String

Valid Values: SAML | OAUTH

[ResourceServerConfig](#)

A structure with details about the receiving application.

Type: [ResourceServerConfig](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeInstance

Returns the details of an instance of IAM Identity Center. The status can be one of the following:

- CREATE_IN_PROGRESS - The instance is in the process of being created. When the instance is ready for use, `DescribeInstance` returns the status of ACTIVE. While the instance is in the CREATE_IN_PROGRESS state, you can call only `DescribeInstance` and `DeleteInstance` operations.
- DELETE_IN_PROGRESS - The instance is being deleted. Returns `AccessDeniedException` after the delete operation completes.
- ACTIVE - The instance is active.

Request Syntax

```
{  
    "InstanceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the instance of IAM Identity Center under which the operation will run.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

Response Syntax

```
{
```

```
"CreatedDate": number,  
"IdentityStoreId": "string",  
"InstanceArn": "string",  
"Namestring",  
"OwnerAccountId": "string",  
"Status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CreatedDate

The date the instance was created.

Type: Timestamp

IdentityStoreId

The identifier of the identity store that is connected to the instance of IAM Identity Center.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9-]*

InstanceArn

The ARN of the instance of IAM Identity Center under which the operation will run. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Name

Specifies the instance name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: [\w+=, .@-]+

OwnerAccountId

The identifier of the Amazon Web Services account for which the instance was created.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Status

The status of the instance.

Type: String

Valid Values: CREATE_IN_PROGRESS | DELETE_IN_PROGRESS | ACTIVE

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeInstanceAccessControlAttributeConfiguration

Returns the list of IAM Identity Center identity store attributes that have been configured to work with attributes-based access control (ABAC) for the specified IAM Identity Center instance. This will not return attributes configured and sent by an external identity provider. For more information about ABAC, see [Attribute-Based Access Control](#) in the *IAM Identity Center User Guide*.

Request Syntax

```
{  
    "InstanceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

Response Syntax

```
{  
    "InstanceAccessControlAttributeConfiguration": {  
        "AccessControlAttributes": [  
            {  
                "Key": "string",  
                "Value": {  
                    "Type": "string",  
                    "Value": "string"  
                }  
            }  
        ]  
    }  
}
```

```
        "Source": [ "string" ]
    }
}
],
{
"Status": "string",
"StatusReason": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[InstanceAccessControlAttributeConfiguration](#)

Gets the list of IAM Identity Center identity store attributes that have been added to your ABAC configuration.

Type: [InstanceAccessControlAttributeConfiguration](#) object

[Status](#)

The status of the attribute configuration process.

Type: String

Valid Values: ENABLED | CREATION_IN_PROGRESS | CREATION_FAILED

[StatusReason](#)

Provides more details about the current status of the specified attribute.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

DescribePermissionSet

Gets the details of the permission set.

Request Syntax

```
{  
    "InstanceArn": "string",  
    "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

PermissionSetArn

The ARN of the permission set.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: Yes

Response Syntax

```
{  
    "PermissionSet": {  
        "CreatedDate": number,  
        "Description": "string",  
        "Name": "string",  
        "PermissionSetArn": "string",  
        "RelayState": "string",  
        "SessionDuration": "string"  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[PermissionSet](#)

Describes the level of access on an Amazon Web Services account.

Type: [PermissionSet](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribePermissionSetProvisioningStatus

Describes the status for the given permission set provisioning request.

Request Syntax

```
{  
    "InstanceArn": "string",  
    "ProvisionPermissionSetRequestId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

ProvisionPermissionSetRequestId

The identifier that is provided by the [ProvisionPermissionSet](#) call to retrieve the current status of the provisioning workflow.

Type: String

Length Constraints: Fixed length of 36.

Pattern: \b[0-9a-f]{8}\b-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-\b[0-9a-f]{12}\b

Required: Yes

Response Syntax

```
{  
    "PermissionSetProvisioningStatus": {  
        "AccountId": "string",  
        "CreatedDate": number,  
        "FailureReason": "string",  
        "PermissionSetArn": "string",  
        "RequestId": "string",  
        "Status": "string"  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[PermissionSetProvisioningStatus](#)

The status object for the permission set provisioning operation.

Type: [PermissionSetProvisioningStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeTrustedTokenIssuer

Retrieves details about a trusted token issuer configuration stored in an instance of IAM Identity Center. Details include the name of the trusted token issuer, the issuer URL, and the path of the source attribute and the destination attribute for a trusted token issuer configuration.

Request Syntax

```
{  
    "TrustedTokenIssuerArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

TrustedTokenIssuerArn

Specifies the ARN of the trusted token issuer configuration that you want details about.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:trustedTokenIssuer/(sso)?ins-[a-zA-Z0-9-.]{16}/tti-[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Required: Yes

Response Syntax

```
{  
    "Name": "string",  
    "TrustedTokenIssuerArn": "string",  
    "TrustedTokenIssuerConfiguration": { ... },  
    "TrustedTokenIssuerType": "string"
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Name

The name of the trusted token issuer configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [\w+=, .@-]+

TrustedTokenIssuerArn

The ARN of the trusted token issuer configuration.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::
\d{12}:trustedTokenIssuer/(sso)?ins-[a-zA-Z0-9-.]{16}/tti-[a-f0-9]{8}-
[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

TrustedTokenIssuerConfiguration

A structure that describes the settings that apply to this trusted token issuer.

Type: [TrustedTokenIssuerConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

TrustedTokenIssuerType

The type of the trusted token issuer.

Type: String

Valid Values: OIDC_JWT

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)

- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DetachCustomerManagedPolicyReferenceFromPermissionSet

Detaches the specified customer managed policy from the specified [PermissionSet](#).

Request Syntax

```
{  
    "CustomerManagedPolicyReference": {  
        "Name": "string",  
        "Path": "string"  
    },  
    "InstanceArn": "string",  
    "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[CustomerManagedPolicyReference](#)

Specifies the name and path of a customer managed policy. You must have an IAM policy that matches the name and path in each Amazon Web Services account where you want to deploy your permission set.

Type: [CustomerManagedPolicyReference](#) object

Required: Yes

[InstanceArn](#)

The ARN of the IAM Identity Center instance under which the operation will be executed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

PermissionSetArn

The ARN of the PermissionSet.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DetachManagedPolicyFromPermissionSet

Detaches the attached Amazon managed policy ARN from the specified permission set.

Request Syntax

```
{  
    "InstanceArn": "string",  
    "ManagedPolicyArn": "string",  
    "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

ManagedPolicyArn

The Amazon managed policy ARN to be detached from a permission set.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):iam::aws:policy((/[A-Za-z0-9\.,\+\@=_-]+)+)/([A-Za-z0-9\.,\+\@=_-]+)

Required: Yes

PermissionSetArn

The ARN of the [PermissionSet](#) from which the policy should be detached.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetApplicationAccessScope

Retrieves the authorized targets for an IAM Identity Center access scope for an application.

Request Syntax

```
{  
  "ApplicationArn": "string",  
  "Scope": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ApplicationArn

Specifies the ARN of the application with the access scope that you want to retrieve.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

Required: Yes

Scope

Specifies the name of the access scope for which you want the authorized targets.

Type: String

Pattern: ([A-Za-z0-9_]{1,50})(:[A-Za-z0-9_]{1,50}){0,1}(:[A-Za-z0-9_]{1,50}){0,1}

Required: Yes

Response Syntax

```
{  
  "AuthorizedTargets": [ "string" ],  
  "Scope": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AuthorizedTargets

An array of authorized targets associated with this access scope.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::
(\d{12}):application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9-]{16}|:instance/(sso)?ins-[a-zA-Z0-9-.]{16})

Scope

The name of the access scope that can be used with the authorized targets.

Type: String

Pattern: ([A-Za-z0-9_]{1,50})(:[A-Za-z0-9_]{1,50}){0,1}(:[A-Za-z0-9_]{1,50}){0,1}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

GetApplicationAssignmentConfiguration

Retrieves the configuration of [PutApplicationAssignmentConfiguration](#).

Request Syntax

```
{  
    "ApplicationArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationArn](#)

Specifies the ARN of the application. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}`

Required: Yes

Response Syntax

```
{  
    "AssignmentRequired": boolean  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AssignmentRequired

If `AssignmentsRequired` is `true` (default value), users don't have access to the application unless an assignment is created using the [CreateApplicationAssignment API](#). If `false`, all users have access to the application.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetApplicationAuthenticationMethod

Retrieves details about an authentication method used by an application.

Request Syntax

```
{  
  "ApplicationArn": "string",  
  "AuthenticationMethodType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationArn](#)

Specifies the ARN of the application.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::
\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

Required: Yes

[AuthenticationMethodType](#)

Specifies the type of authentication method for which you want details.

Type: String

Valid Values: IAM

Required: Yes

Response Syntax

```
{
```

```
"AuthenticationMethod": { ... }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AuthenticationMethod](#)

A structure that contains details about the requested authentication method.

Type: [AuthenticationMethod](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetApplicationGrant

Retrieves details about an application grant.

Request Syntax

```
{  
    "ApplicationArn": "string",  
    "GrantType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationArn](#)

Specifies the ARN of the application that contains the grant.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

Required: Yes

[GrantType](#)

Specifies the type of grant.

Type: String

Valid Values: authorization_code | refresh_token | urn:ietf:params:oauth:grant-type:jwt-bearer | urn:ietf:params:oauth:grant-type:token-exchange

Required: Yes

Response Syntax

```
{  
  "Grant": { ... }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Grant

A structure that describes the requested grant.

Type: [Grant](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetInlinePolicyForPermissionSet

Obtains the inline policy assigned to the permission set.

Request Syntax

```
{  
    "InstanceArn": "string",  
    "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

PermissionSetArn

The ARN of the permission set.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: Yes

Response Syntax

```
{  
    "InlinePolicy": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InlinePolicy

The inline policy that is attached to the permission set.

 **Note**

For Length Constraints, if a valid ARN is provided for a permission set, it is possible for an empty inline policy to be returned.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32768.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

GetPermissionsBoundaryForPermissionSet

Obtains the permissions boundary for a specified [PermissionSet](#).

Request Syntax

```
{  
    "InstanceArn": "string",  
    "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

PermissionSetArn

The ARN of the PermissionSet.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: Yes

Response Syntax

```
{  
    "PermissionsBoundary": {  
        "CustomerManagedPolicyReference": {  
            "Name": "string",  
            "Path": "string"  
        },  
        "ManagedPolicyArn": "string"  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

PermissionsBoundary

The permissions boundary attached to the specified permission set.

Type: [PermissionsBoundary](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListAccountAssignmentCreationStatus

Lists the status of the Amazon Web Services account assignment creation requests for a specified IAM Identity Center instance.

Request Syntax

```
{  
    "Filter": {  
        "Status": "string"  
    },  
    "InstanceArn": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filter

Filters results based on the passed attribute value.

Type: [OperationStatusFilter](#) object

Required: No

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

MaxResults

The maximum number of results to display for the assignment.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Required: No

Response Syntax

```
{  
    "AccountAssignmentsCreationStatus": [  
        {  
            "CreatedDate": number,  
            "RequestId": "string",  
            "Status": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AccountAssignmentsCreationStatus](#)

The status object for the account assignment creation operation.

Type: Array of [AccountAssignmentOperationStatusMetadata](#) objects

[NextToken](#)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListAccountAssignmentDeletionStatus

Lists the status of the Amazon Web Services account assignment deletion requests for a specified IAM Identity Center instance.

Request Syntax

```
{  
    "Filter": {  
        "Status": "string"  
    },  
    "InstanceArn": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filter

Filters results based on the passed attribute value.

Type: [OperationStatusFilter](#) object

Required: No

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

MaxResults

The maximum number of results to display for the assignment.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Required: No

Response Syntax

```
{  
    "AccountAssignmentsDeletionStatus": [  
        {  
            "CreatedDate": number,  
            "RequestId": "string",  
            "Status": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AccountAssignmentsDeletionStatus](#)

The status object for the account assignment deletion operation.

Type: Array of [AccountAssignmentOperationStatusMetadata](#) objects

[NextToken](#)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListAccountAssignments

Lists the assignee of the specified Amazon Web Services account with the specified permission set.

Request Syntax

```
{  
    "AccountId": "string",  
    "InstanceArn": "string",  
    "MaxResults": number,  
    "NextToken": "string",  
    "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AccountId

The identifier of the Amazon Web Services account from which to list the assignments.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Required: Yes

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the [Amazon General Reference](#).

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

MaxResults

The maximum number of results to display for the assignment.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[-a-zA-Z0-9+=/_]*`

Required: No

PermissionSetArn

The ARN of the permission set from which to list assignments.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Required: Yes

Response Syntax

```
{
```

```
"AccountAssignments": [  
    {  
        "AccountId        "PermissionSetArn        "PrincipalId        "PrincipalType    }  
,  
    "NextToken}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccountAssignments

The list of assignments that match the input Amazon Web Services account and permission set.

Type: Array of [AccountAssignment](#) objects

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListAccountAssignmentsForPrincipal

Retrieves a list of the IAM Identity Center associated Amazon Web Services accounts that the principal has access to. This action must be called from the management account containing your organization instance of IAM Identity Center. This action is not valid for account instances of IAM Identity Center.

Request Syntax

```
{  
    "Filter": {  
        "AccountId": "string"  
    },  
    "InstanceArn": "string",  
    "MaxResults": number,  
    "NextToken": "string",  
    "PrincipalId": "string",  
    "PrincipalType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filter

Specifies an Amazon Web Services account ID number. Results are filtered to only those that match this ID number.

Type: [ListAccountAssignmentsFilter](#) object

Required: No

InstanceArn

Specifies the ARN of the instance of IAM Identity Center that contains the principal.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

MaxResults

Specifies the total number of results that you want included in each response. If additional items exist beyond the number you specify, the `NextToken` response element is returned with a value (not null). Include the specified value as the `NextToken` request parameter in the next call to the operation to get the next set of results. Note that the service might return fewer results than the maximum even when there are more results available. You should check `NextToken` after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

Specifies that you want to receive the next page of results. Valid only if you received a `NextToken` response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's `NextToken` response to request the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[-a-zA-Z0-9+=/_]*`

Required: No

PrincipalId

Specifies the principal for which you want to retrieve the list of account assignments.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 47.

Pattern: `([0-9a-f]{10}-|)[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}`

Required: Yes

[PrincipalType](#)

Specifies the type of the principal.

Type: String

Valid Values: USER | GROUP

Required: Yes

Response Syntax

```
{  
    "AccountAssignments": [  
        {  
            "AccountId": "string",  
            "PermissionSetArn": "string",  
            "PrincipalId": "string",  
            "PrincipalType": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AccountAssignments](#)

An array list of the account assignments for the principal.

Type: Array of [AccountAssignmentForPrincipal](#) objects

[NextToken](#)

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the

operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null. This indicates that this is the last page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListAccountsForProvisionedPermissionSet

Lists all the Amazon accounts where the specified permission set is provisioned.

Request Syntax

```
{  
    "InstanceArn": "string",  
    "MaxResults": number,  
    "NextToken": "string",  
    "PermissionSetArn": "string",  
    "ProvisioningStatus": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

MaxResults

The maximum number of results to display for the [PermissionSet](#).

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Required: No

PermissionSetArn

The ARN of the [PermissionSet](#) from which the associated Amazon accounts will be listed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: Yes

ProvisioningStatus

The permission set provisioning status for an Amazon account.

Type: String

Valid Values: LATEST_PERMISSION_SET_PROVISIONED |
LATEST_PERMISSION_SET_NOT_PROVISIONED

Required: No

Response Syntax

```
{  
  "AccountIds": [ "string" ],  
  "NextToken": "string"
```

{}

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccountIds

The list of Amazon Account IDs.

Type: Array of strings

Length Constraints: Fixed length of 12.

Pattern: \d{12}

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListApplicationAccessScopes

Lists the access scopes and authorized targets associated with an application.

Request Syntax

```
{  
    "ApplicationArn": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationArn](#)

Specifies the ARN of the application.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::
\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

Required: Yes

[MaxResults](#)

Specifies the total number of results that you want included in each response. If additional items exist beyond the number you specify, the NextToken response element is returned with a value (not null). Include the specified value as the NextToken request parameter in the next call to the operation to get the next set of results. Note that the service might return fewer results than the maximum even when there are more results available. You should check NextToken after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10.

Required: No

NextToken

Specifies that you want to receive the next page of results. Valid only if you received a NextToken response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's NextToken response to request the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "Scopes": [  
        {  
            "AuthorizedTargets": [ "string" ],  
            "Scope": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the

operation to get the next part of the output. You should repeat this until the `NextToken` response element comes back as null. This indicates that this is the last page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Scopes

An array list of access scopes and their authorized targets that are associated with the application.

Type: Array of [ScopeDetails](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListApplicationAssignments

Lists Amazon Web Services account users that are assigned to an application.

Request Syntax

```
{  
    "ApplicationArn": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationArn](#)

Specifies the ARN of the application.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

Required: Yes

[MaxResults](#)

Specifies the total number of results that you want included in each response. If additional items exist beyond the number you specify, the NextToken response element is returned with a value (not null). Include the specified value as the NextToken request parameter in the next call to the operation to get the next set of results. Note that the service might return fewer results than the maximum even when there are more results available. You should check NextToken after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

Specifies that you want to receive the next page of results. Valid only if you received a NextToken response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's NextToken response to request the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Required: No

Response Syntax

```
{
  "ApplicationAssignments": [
    {
      "ApplicationArnPrincipalIdPrincipalTypeNextToken
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationAssignments

The list of users assigned to an application.

Type: Array of [ApplicationAssignment](#) objects

NextToken

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null. This indicates that this is the last page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListApplicationAssignmentsForPrincipal

Lists the applications to which a specified principal is assigned. You must provide a filter when calling this action from a member account against your organization instance of IAM Identity Center. A filter is not required when called from the management account against an organization instance of IAM Identity Center, or from a member account against an account instance of IAM Identity Center in the same account.

Request Syntax

```
{  
  "Filter": {  
    "ApplicationArn": "string"  
  },  
  "InstanceArn": "string",  
  "MaxResults": number,  
  "NextToken": "string",  
  "PrincipalId": "string",  
  "PrincipalType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filter

Filters the output to include only assignments associated with the application that has the specified ARN.

Type: [ListApplicationAssignmentsFilter](#) object

Required: No

InstanceArn

Specifies the instance of IAM Identity Center that contains principal and applications.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

MaxResults

Specifies the total number of results that you want included in each response. If additional items exist beyond the number you specify, the `NextToken` response element is returned with a value (not null). Include the specified value as the `NextToken` request parameter in the next call to the operation to get the next set of results. Note that the service might return fewer results than the maximum even when there are more results available. You should check `NextToken` after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

Specifies that you want to receive the next page of results. Valid only if you received a `NextToken` response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's `NextToken` response to request the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[-a-zA-Z0-9+=/_]*`

Required: No

PrincipalId

Specifies the unique identifier of the principal for which you want to retrieve its assignments.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 47.

Pattern: ([0-9a-f]{10}-|)[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}

Required: Yes

[PrincipalType](#)

Specifies the type of the principal for which you want to retrieve its assignments.

Type: String

Valid Values: USER | GROUP

Required: Yes

Response Syntax

```
{  
    "ApplicationAssignments": [  
        {  
            "ApplicationArn": "string",  
            "PrincipalId": "string",  
            "PrincipalType": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ApplicationAssignments](#)

An array list of the application assignments for the specified principal.

Type: Array of [ApplicationAssignmentForPrincipal](#) objects

NextToken

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null. This indicates that this is the last page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListApplicationAuthenticationMethods

Lists all of the authentication methods supported by the specified application.

Request Syntax

```
{  
    "ApplicationArn": "string",  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationArn](#)

Specifies the ARN of the application with the authentication methods you want to list.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}`

Required: Yes

[NextToken](#)

Specifies that you want to receive the next page of results. Valid only if you received a NextToken response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's NextToken response to request the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[-a-zA-Z0-9+=/_]*`

Required: No

Response Syntax

```
{  
  "AuthenticationMethods": [  
    {  
      "AuthenticationMethod": { ... },  
      "AuthenticationMethodType": "string"  
    }  
  ],  
  "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AuthenticationMethods](#)

An array list of authentication methods for the specified application.

Type: Array of [AuthenticationMethodItem](#) objects

[NextToken](#)

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null. This indicates that this is the last page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListApplicationGrants

List the grants associated with an application.

Request Syntax

```
{  
    "ApplicationArn": "string",  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ApplicationArn

Specifies the ARN of the application whose grants you want to list.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}`

Required: Yes

NextToken

Specifies that you want to receive the next page of results. Valid only if you received a NextToken response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's NextToken response to request the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[-a-zA-Z0-9+=/_]*`

Required: No

Response Syntax

```
{  
  "Grants": [  
    {  
      "Grant": { ... },  
      "GrantType": "string"  
    }  
  ],  
  "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Grants

An array list of structures that describe the requested grants.

Type: Array of [GrantItem](#) objects

NextToken

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null. This indicates that this is the last page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListApplicationProviders

Lists the application providers configured in the IAM Identity Center identity store.

Request Syntax

```
{  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

Specifies the total number of results that you want included in each response. If additional items exist beyond the number you specify, the NextToken response element is returned with a value (not null). Include the specified value as the NextToken request parameter in the next call to the operation to get the next set of results. Note that the service might return fewer results than the maximum even when there are more results available. You should check NextToken after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

Specifies that you want to receive the next page of results. Valid only if you received a NextToken response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's NextToken response to request the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Required: No

Response Syntax

```
{  
    "ApplicationProviders": [  
        {  
            "ApplicationProviderArn": "string",  
            "DisplayData": {  
                "Description": "string",  
                "DisplayName": "string",  
                "IconUrl": "string"  
            },  
            "FederationProtocol": "string",  
            "ResourceServerConfig": {  
                "Scopes": {  
                    "string" : {  
                        "DetailedTitle": "string",  
                        "LongDescription": "string"  
                    }  
                }  
            }  
        },  
        {"NextToken": "string"  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ApplicationProviders](#)

An array list of structures that describe application providers.

Type: Array of [ApplicationProvider](#) objects

NextToken

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null. This indicates that this is the last page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListApplications

Lists all applications associated with the instance of IAM Identity Center. When listing applications for an organization instance in the management account, member accounts must use the applicationAccount parameter to filter the list to only applications created from that account. When listing applications for an account instance in the same member account, a filter is not required.

Request Syntax

```
{  
  "Filter": {  
    "ApplicationAccount": "string",  
    "ApplicationProvider": "string"  
  },  
  "InstanceArn": "string",  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filter

Filters response results.

Type: [ListApplicationsFilter](#) object

Required: No

InstanceArn

The ARN of the IAM Identity Center application under which the operation will run. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

MaxResults

Specifies the total number of results that you want included in each response. If additional items exist beyond the number you specify, the NextToken response element is returned with a value (not null). Include the specified value as the NextToken request parameter in the next call to the operation to get the next set of results. Note that the service might return fewer results than the maximum even when there are more results available. You should check NextToken after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

Specifies that you want to receive the next page of results. Valid only if you received a NextToken response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's NextToken response to request the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Required: No

Response Syntax

```
{  
  "Applications": [  
    ...  
  ]  
}
```

```
{  
    "ApplicationAccount": "string",  
    "ApplicationArn": "string",  
    "ApplicationProviderArn": "string",  
    "CreatedDate": number,  
    "Description": "string",  
    "InstanceArn": "string",  
    "Name": "string",  
    "PortalOptions": {  
        "SignInOptions": {  
            "ApplicationUrl": "string",  
            "Origin": "string"  
        },  
        "Visibility": "string"  
    },  
    "Status": "string"  
},  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Applications](#)

Retrieves all applications associated with the instance.

Type: Array of [Application](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

[NextToken](#)

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null. This indicates that this is the last page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListCustomerManagedPolicyReferencesInPermissionSet

Lists all customer managed policies attached to a specified [PermissionSet](#).

Request Syntax

```
{  
    "InstanceArn": "string",  
    "MaxResults": number,  
    "NextToken": "string",  
    "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

MaxResults

The maximum number of results to display for the list call.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Required: No

PermissionSetArn

The ARN of the PermissionSet.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-./]{16}

Required: Yes

Response Syntax

```
{  
    "CustomerManagedPolicyReferences": [  
        {  
            "Name": "string",  
            "Path": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[CustomerManagedPolicyReferences](#)

Specifies the names and paths of the customer managed policies that you have attached to your permission set.

Type: Array of [CustomerManagedPolicyReference](#) objects

[NextToken](#)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListInstances

Lists the details of the organization and account instances of IAM Identity Center that were created in or visible to the account calling this API.

Request Syntax

```
{  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum number of results to display for the instance.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Required: No

Response Syntax

```
{  
    "Instances": [  
        {  
            "CreatedDate": number,  
            "IdentityStoreId": "string",  
            "InstanceArn": "string",  
            "Name": "string",  
            "OwnerAccountId": "string",  
            "Status": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Instances

Lists the IAM Identity Center instances that the caller has access to.

Type: Array of [InstanceMetadata](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)

- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListManagedPoliciesInPermissionSet

Lists the Amazon managed policy that is attached to a specified permission set.

Request Syntax

```
{  
    "InstanceArn": "string",  
    "MaxResults": number,  
    "NextToken": "string",  
    "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

MaxResults

The maximum number of results to display for the [PermissionSet](#).

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Required: No

PermissionSetArn

The ARN of the [PermissionSet](#) whose managed policies will be listed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-./]{16}

Required: Yes

Response Syntax

```
{  
    "AttachedManagedPolicies": [  
        {  
            "Arn": "string",  
            "Name": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AttachedManagedPolicies

An array of the [AttachedManagedPolicy](#) data type object.

Type: Array of [AttachedManagedPolicy](#) objects

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListPermissionSetProvisioningStatus

Lists the status of the permission set provisioning requests for a specified IAM Identity Center instance.

Request Syntax

```
{  
    "Filter": {  
        "Status": "string"  
    },  
    "InstanceArn": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Filter

Filters results based on the passed attribute value.

Type: [OperationStatusFilter](#) object

Required: No

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

MaxResults

The maximum number of results to display for the assignment.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "PermissionSetsProvisioningStatus": [  
        {  
            "CreatedDate": number,  
            "RequestId": "string",  
            "Status": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

PermissionSetsProvisioningStatus

The status object for the permission set provisioning operation.

Type: Array of [PermissionSetProvisioningStatusMetadata](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListPermissionSets

Lists the [PermissionSets](#) in an IAM Identity Center instance.

Request Syntax

```
{  
    "InstanceArn": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[InstanceArn](#)

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

[MaxResults](#)

The maximum number of results to display for the assignment.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "PermissionSets": [ "string" ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

PermissionSets

Defines the level of access on an Amazon account.

Type: Array of strings

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListPermissionSetsProvisionedToAccount

Lists all the permission sets that are provisioned to a specified Amazon account.

Request Syntax

```
{  
    "AccountId": "string",  
    "InstanceArn": "string",  
    "MaxResults": number,  
    "NextToken": "string",  
    "ProvisioningStatus": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AccountId

The identifier of the Amazon account from which to list the assignments.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Required: Yes

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the [Amazon General Reference](#).

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

MaxResults

The maximum number of results to display for the assignment.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `[-a-zA-Z0-9+=/_]*`

Required: No

ProvisioningStatus

The status object for the permission set provisioning operation.

Type: String

Valid Values: LATEST_PERMISSION_SET_PROVISIONED |
LATEST_PERMISSION_SET_NOT_PROVISIONED

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "PermissionSets": [ "string" ]
```

}

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

PermissionSets

Defines the level of access that an Amazon account has.

Type: Array of strings

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListTagsForResource

Lists the tags that are attached to a specified resource.

Request Syntax

```
{  
  "InstanceArn": "string",  
  "NextToken": "string",  
  "ResourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: No

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Required: No

ResourceArn

The ARN of the resource with the tags to be listed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 2048.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::(:instance/(sso)?ins-[a-zA-Z0-9-.]{16})|(:permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16})|(\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16})|(\d{12}:trustedTokenIssuer/(sso)?ins-[a-zA-Z0-9-.]{16}/tti-[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}))

Required: Yes

Response Syntax

```
{
  "NextTokenTagsKeyValue
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Tags

A set of key-value pairs that are used to manage the resource.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 75 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListTrustedTokenIssuers

Lists all the trusted token issuers configured in an instance of IAM Identity Center.

Request Syntax

```
{  
  "InstanceArn": "string",  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

Specifies the ARN of the instance of IAM Identity Center with the trusted token issuer configurations that you want to list.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

MaxResults

Specifies the total number of results that you want included in each response. If additional items exist beyond the number you specify, the NextToken response element is returned with a value (not null). Include the specified value as the NextToken request parameter in the next call to the operation to get the next set of results. Note that the service might return fewer results than the maximum even when there are more results available. You should check NextToken after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken

Specifies that you want to receive the next page of results. Valid only if you received a NextToken response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's NextToken response to request the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "TrustedTokenIssuers": [  
        {  
            "Name": "string",  
            "TrustedTokenIssuerArn": "string",  
            "TrustedTokenIssuerType": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the

operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null. This indicates that this is the last page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: [-a-zA-Z0-9+=/_]*

[TrustedTokenIssuers](#)

An array list of the trusted token issuer configurations.

Type: Array of [TrustedTokenIssuerMetadata](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ProvisionPermissionSet

The process by which a specified permission set is provisioned to the specified target.

Request Syntax

```
{  
    "InstanceArn": "string",  
    "PermissionSetArn": "string",  
    "TargetId": "string",  
    "TargetType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

PermissionSetArn

The ARN of the permission set.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: Yes

TargetId

TargetID is an Amazon Web Services account identifier, (For example, 123456789012).

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Required: No

TargetType

The entity type for which the assignment will be created.

Type: String

Valid Values: AWS_ACCOUNT | ALL_PROVISIONED_ACCOUNTS

Required: Yes

Response Syntax

```
{
  "PermissionSetProvisioningStatus": {
    "AccountId": "string",
    "CreatedDate": number,
    "FailureReason": "string",
    "PermissionSetArn": "string",
    "RequestId": "string",
    "Status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[PermissionSetProvisioningStatus](#)

The status object for the permission set provisioning operation.

Type: [PermissionSetProvisioningStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

PutApplicationAccessScope

Adds or updates the list of authorized targets for an IAM Identity Center access scope for an application.

Request Syntax

```
{  
    "ApplicationArn": "string",  
    "AuthorizedTargets": [ "string" ],  
    "Scope": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationArn](#)

Specifies the ARN of the application with the access scope with the targets to add or update.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::
\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

Required: Yes

[AuthorizedTargets](#)

Specifies an array list of ARNs that represent the authorized targets for this access scope.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::(\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}|:instance/(sso)?ins-[a-zA-Z0-9-.]{16})`

Required: No

Scope

Specifies the name of the access scope to be associated with the specified targets.

Type: String

Pattern: `([A-Za-z0-9_]{1,50})(:[A-Za-z0-9_]{1,50}){0,1}(:[A-Za-z0-9_]{1,50}){0,1}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

PutApplicationAssignmentConfiguration

Configure how users gain access to an application. If `AssignmentsRequired` is `true` (default value), users don't have access to the application unless an assignment is created using the [CreateApplicationAssignment API](#). If `false`, all users have access to the application. If an assignment is created using [CreateApplicationAssignment](#), the user retains access if `AssignmentsRequired` is set to `true`.

Request Syntax

```
{  
    "ApplicationArn": "string",  
    "AssignmentRequired": boolean  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationArn](#)

Specifies the ARN of the application. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}`

Required: Yes

[AssignmentRequired](#)

If `AssignmentsRequired` is `true` (default value), users don't have access to the application unless an assignment is created using the [CreateApplicationAssignment API](#). If `false`, all users have access to the application.

Type: Boolean

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

PutApplicationAuthenticationMethod

Adds or updates an authentication method for an application.

Request Syntax

```
{  
  "ApplicationArn": "string",  
  "AuthenticationMethod": { ... },  
  "AuthenticationMethodType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ApplicationArn

Specifies the ARN of the application with the authentication method to add or update.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}`

Required: Yes

AuthenticationMethod

Specifies a structure that describes the authentication method to add or update. The structure type you provide is determined by the AuthenticationMethodType parameter.

Type: [AuthenticationMethod](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

AuthenticationMethodType

Specifies the type of the authentication method that you want to add or update.

Type: String

Valid Values: IAM

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

PutApplicationGrant

Creates a configuration for an application to use grants. Conceptually grants are authorization to request actions related to tokens. This configuration will be used when parties are requesting and receiving tokens during the trusted identity propagation process. For more information on the IAM Identity Center supported grant workflows, see [SAML 2.0 and OAuth 2.0](#).

A grant is created between your applications and Identity Center instance which enables an application to use specified mechanisms to obtain tokens. These tokens are used by your applications to gain access to Amazon resources on behalf of users. The following elements are within these exchanges:

- **Requester** - The application requesting access to Amazon resources.
- **Subject** - Typically the user that is requesting access to Amazon resources.
- **Grant** - Conceptually, a grant is authorization to access Amazon resources. These grants authorize token generation for authenticating access to the requester and for the request to make requests on behalf of the subjects. There are four types of grants:
 - **AuthorizationCode** - Allows an application to request authorization through a series of user-agent redirects.
 - **JWT bearer** - Authorizes an application to exchange a JSON Web Token that came from an external identity provider. To learn more, see [RFC 6479](#).
 - **Refresh token** - Enables application to request new access tokens to replace expiring or expired access tokens.
 - **Exchange token** - A grant that requests tokens from the authorization server by providing a 'subject' token with access scope authorizing trusted identity propagation to this application. To learn more, see [RFC 8693](#).
- **Authorization server** - IAM Identity Center requests tokens.

User credentials are never shared directly within these exchanges. Instead, applications use grants to request access tokens from IAM Identity Center. For more information, see [RFC 6479](#).

Use cases

- Connecting to custom applications.
- Configuring an Amazon service to make calls to another Amazon services using JWT tokens.

Request Syntax

```
{  
  "ApplicationArn": "string",  
  "Grant": { ... },  
  "GrantType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationArn](#)

Specifies the ARN of the application to update.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

Required: Yes

[Grant](#)

Specifies a structure that describes the grant to update.

Type: [Grant](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

[GrantType](#)

Specifies the type of grant to update.

Type: String

Valid Values: authorization_code | refresh_token |
urn:ietf:params:oauth:grant-type:jwt-bearer |
urn:ietf:params:oauth:grant-type:token-exchange

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

PutInlinePolicyToPermissionSet

Attaches an inline policy to a permission set.

Note

If the permission set is already referenced by one or more account assignments, you will need to call [ProvisionPermissionSet](#) after this action to apply the corresponding IAM policy updates to all assigned accounts.

Request Syntax

```
{  
  "InlinePolicy": "string",  
  "InstanceArn": "string",  
  "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InlinePolicy

The inline policy to attach to a [PermissionSet](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32768.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Required: Yes

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: Yes

PermissionSetArn

The ARN of the permission set.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Indicates that the principal has crossed the permitted number of resources that can be created.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

PutPermissionsBoundaryToPermissionSet

Attaches an Amazon managed or customer managed policy to the specified [PermissionSet](#) as a permissions boundary.

Request Syntax

```
{  
    "InstanceArn": "string",  
    "PermissionsBoundary": {  
        "CustomerManagedPolicyReference": {  
            "Name": "string",  
            "Path": "string"  
        },  
        "ManagedPolicyArn": "string"  
    },  
    "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

PermissionsBoundary

The permissions boundary that you want to attach to a PermissionSet.

Type: [PermissionsBoundary](#) object

Required: Yes

PermissionSetArn

The ARN of the PermissionSet.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

TagResource

Associates a set of tags with a specified resource.

Request Syntax

```
{  
    "InstanceArn": "string",  
    "ResourceArn": "string",  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: No

ResourceArn

The ARN of the resource with the tags to be listed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 2048.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::(:instance/(sso)?ins-[a-zA-Z0-9-.]{16})|(:permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16})|(\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16})|(\d{12}:trustedTokenIssuer/(sso)?ins-[a-zA-Z0-9-.]{16}/tti-[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}))

Required: Yes

Tags

A set of key-value pairs that are used to manage the resource.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 75 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Indicates that the principal has crossed the permitted number of resources that can be created.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UntagResource

Disassociates a set of tags from a specified resource.

Request Syntax

```
{  
    "InstanceArn": "string",  
    "ResourceArn": "string",  
    "TagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: No

ResourceArn

The ARN of the resource with the tags to be listed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 2048.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::(:instance/(sso)?ins-[a-zA-Z0-9-.]{16})|(:permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16})

```
{16}/ps-[a-zA-Z0-9-./]{16})|(\d{12}:application/(sso)?ins-[a-zA-Z0-9-.] {16}/apl-[a-zA-Z0-9]{16})|(\d{12}:trustedTokenIssuer/(sso)?ins-[a-zA-Z0-9-.] {16}/tti-[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}))
```

Required: Yes

TagKeys

The keys of tags that are attached to the resource.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 75 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ([\p{L}\p{Z}\p{N}_.:/=+\-\@]*)

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateApplication

Updates application properties.

Request Syntax

```
{  
    "ApplicationArn": "string",  
    "Description": "string",  
    "Name": "string",  
    "PortalOptions": {  
        "SignInOptions": {  
            "ApplicationUrl": "string",  
            "Origin": "string"  
        }  
    },  
    "Status": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ApplicationArn

Specifies the ARN of the application. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

Required: Yes

Description

The description of the [Application](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Name

Specifies the updated name for the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [\S\s]*

Required: No

PortalOptions

A structure that describes the options for the portal associated with an application.

Type: [UpdateApplicationPortalOptions](#) object

Required: No

Status

Specifies whether the application is enabled or disabled.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateInstance

Update the details for the instance of IAM Identity Center that is owned by the Amazon Web Services account.

Request Syntax

```
{  
    "InstanceArn": "string",  
    "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

InstanceArn

The ARN of the instance of IAM Identity Center under which the operation will run. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

Name

Updates the instance name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\w+=,.@-]+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateInstanceAccessControlAttributeConfiguration

Updates the IAM Identity Center identity store attributes that you can use with the IAM Identity Center instance for attributes-based access control (ABAC). When using an external identity provider as an identity source, you can pass attributes through the SAML assertion as an alternative to configuring attributes from the IAM Identity Center identity store. If a SAML assertion passes any of these attributes, IAM Identity Center replaces the attribute value with the value from the IAM Identity Center identity store. For more information about ABAC, see [Attribute-Based Access Control](#) in the *IAM Identity Center User Guide*.

Request Syntax

```
{  
    "InstanceAccessControlAttributeConfiguration": {  
        "AccessControlAttributes": [  
            {  
                "Key": "string",  
                "Value": {  
                    "Source": [ "string" ]  
                }  
            }  
        ]  
    },  
    "InstanceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[InstanceAccessControlAttributeConfiguration](#)

Updates the attributes for your ABAC configuration.

Type: [InstanceAccessControlAttributeConfiguration](#) object

Required: Yes

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdatePermissionSet

Updates an existing permission set.

Request Syntax

```
{  
    "Description": "string",  
    "InstanceArn": "string",  
    "PermissionSetArn": "string",  
    "RelayState": "string",  
    "SessionDuration": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Description

The description of the [PermissionSet](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 700.

Pattern: [\u0009\u000A\u000D\u0020-\u007E\u00A1-\u00FF]*

Required: No

InstanceArn

The ARN of the IAM Identity Center instance under which the operation will be executed.

For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the [Amazon General Reference](#).

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

PermissionSetArn

The ARN of the permission set.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Required: Yes

RelayState

Used to redirect users within the application during the federation authentication process.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 240.

Pattern: `[a-zA-Z0-9$#@\\%?=-_'"|!:,.;*+\[\]\\ \(\)\{\}\]+`

Required: No

SessionDuration

The length of time that the application user sessions are valid for in the ISO-8601 standard.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(-?)P(?=\d|T\d)(?:(\d+)Y)?(?:(\d+)M)?(?:(\d+)([DW]))?(?:T(?:(\d+)H)?(?:(\d+)M)?(?:(\d+(?:\.\d+)?)S)?))?`

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateTrustedTokenIssuer

Updates the name of the trusted token issuer, or the path of a source attribute or destination attribute for a trusted token issuer configuration.

Note

Updating this trusted token issuer configuration might cause users to lose access to any applications that are configured to use the trusted token issuer.

Request Syntax

```
{  
  "Name": "string",  
  "TrustedTokenIssuerArnstring",  
  "TrustedTokenIssuerConfiguration}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

Specifies the updated name to be applied to the trusted token issuer configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [\w+=,.@-]+

Required: No

TrustedTokenIssuerArn

Specifies the ARN of the trusted token issuer configuration that you want to update.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::
\d{12}:trustedTokenIssuer/(sso)?ins-[a-zA-Z0-9-.]{16}/tti-[a-f0-9]{8}-
[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: Yes

TrustedTokenIssuerConfiguration

Specifies a structure with settings to apply to the specified trusted token issuer. The settings that you can provide are determined by the type of the trusted token issuer that you are updating.

Type: [TrustedTokenIssuerUpdateConfiguration](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 500

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go v2](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for Kotlin](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

Data Types

The IAM Identity Center API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccessControlAttribute](#)
- [AccessControlAttributeValue](#)
- [AccountAssignment](#)
- [AccountAssignmentForPrincipal](#)
- [AccountAssignmentOperationStatus](#)
- [AccountAssignmentOperationStatusMetadata](#)
- [Application](#)
- [ApplicationAssignment](#)
- [ApplicationAssignmentForPrincipal](#)
- [ApplicationProvider](#)
- [AttachedManagedPolicy](#)
- [AuthenticationMethod](#)
- [AuthenticationMethodItem](#)
- [AuthorizationCodeGrant](#)
- [AuthorizedTokenIssuer](#)
- [CustomerManagedPolicyReference](#)
- [DisplayData](#)
- [Grant](#)
- [GrantItem](#)
- [IamAuthenticationMethod](#)

- [InstanceAccessControlAttributeConfiguration](#)
- [InstanceMetadata](#)
- [JwtBearerGrant](#)
- [ListAccountAssignmentsFilter](#)
- [ListApplicationAssignmentsFilter](#)
- [ListApplicationsFilter](#)
- [OidcJwtConfiguration](#)
- [OidcJwtUpdateConfiguration](#)
- [OperationStatusFilter](#)
- [PermissionsBoundary](#)
- [PermissionSet](#)
- [PermissionSetProvisioningStatus](#)
- [PermissionSetProvisioningStatusMetadata](#)
- [PortalOptions](#)
- [RefreshTokenGrant](#)
- [ResourceServerConfig](#)
- [ResourceServerScopeDetails](#)
- [ScopeDetails](#)
- [SignInOptions](#)
- [Tag](#)
- [TokenExchangeGrant](#)
- [TrustedTokenIssuerConfiguration](#)
- [TrustedTokenIssuerMetadata](#)
- [TrustedTokenIssuerUpdateConfiguration](#)
- [UpdateApplicationPortalOptions](#)

AccessControlAttribute

These are IAM Identity Center identity store attributes that you can configure for use in attributes-based access control (ABAC). You can create permissions policies that determine who can access your Amazon resources based upon the configured attribute values. When you enable ABAC and specify AccessControlAttributes, IAM Identity Center passes the attribute values of the authenticated user into IAM for use in policy evaluation.

Contents

Key

The name of the attribute associated with your identities in your identity source. This is used to map a specified attribute in your identity source with an attribute in IAM Identity Center.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\p{L}\p{Z}\p{N}_.:/\+=\-\@]+

Required: Yes

Value

The value used for mapping a specified attribute to an identity source.

Type: [AccessControlAttributeValue](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AccessControlAttributeValue

The value used for mapping a specified attribute to an identity source. For more information, see [Attribute mappings](#) in the *IAM Identity Center User Guide*.

Contents

Source

The identity source to use when mapping a specified attribute to IAM Identity Center.

Type: Array of strings

Array Members: Fixed number of 1 item.

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: [\p{L}\p{Z}\p{N}_.:\\=+-@[\]\\{}\\}\\\$\\"]*

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AccountAssignment

The assignment that indicates a principal's limited access to a specified Amazon account with a specified permission set.

Note

The term *principal* here refers to a user or group that is defined in IAM Identity Center.

Contents

AccountId

The identifier of the Amazon account.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Required: No

PermissionSetArn

The ARN of the permission set. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: No

PrincipalId

An identifier for an object in IAM Identity Center, such as a user or group. PrincipalIds are GUIDs (For example, f81d4fae-7dec-11d0-a765-00a0c91e6bf6). For more information about PrincipalIds in IAM Identity Center, see the [IAM Identity Center Identity Store API Reference](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 47.

Pattern: ([0-9a-f]{10}-|)[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}

Required: No

PrincipalType

The entity type for which the assignment will be created.

Type: String

Valid Values: USER | GROUP

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AccountAssignmentForPrincipal

A structure that describes an assignment of an Amazon Web Services account to a principal and the permissions that principal has in the account.

Contents

AccountId

The account ID number of the Amazon Web Services account.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Required: No

PermissionSetArn

The ARN of the IAM Identity Center permission set assigned to this principal for this Amazon Web Services account.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: No

PrincipalId

The ID of the principal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 47.

Pattern: ([0-9a-f]{10}-|)[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}

Required: No

PrincipalType

The type of the principal.

Type: String

Valid Values: USER | GROUP

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AccountAssignmentOperationStatus

The status of the creation or deletion operation of an assignment that a principal needs to access an account.

Contents

CreatedDate

The date that the permission set was created.

Type: Timestamp

Required: No

FailureReason

The message that contains an error or exception in case of an operation failure.

Type: String

Pattern: [\p{L}\p{M}\p{Z}\p{S}\p{N}\p{P}]*

Required: No

PermissionSetArn

The ARN of the permission set. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: No

PrincipalId

An identifier for an object in IAM Identity Center, such as a user or group. PrincipalIds are GUIDs (For example, f81d4fae-7dec-11d0-a765-00a0c91e6bf6). For more information about PrincipalIds in IAM Identity Center, see the [IAM Identity Center Identity Store API Reference](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 47.

Pattern: ([0-9a-f]{10}-|)[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}

Required: No

PrincipalType

The entity type for which the assignment will be created.

Type: String

Valid Values: USER | GROUP

Required: No

RequestId

The identifier for tracking the request operation that is generated by the universally unique identifier (UUID) workflow.

Type: String

Length Constraints: Fixed length of 36.

Pattern: \b[0-9a-f]{8}\b-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-\b[0-9a-f]{12}\b

Required: No

Status

The status of the permission set provisioning process.

Type: String

Valid Values: IN_PROGRESS | FAILED | SUCCEEDED

Required: No

TargetId

TargetID is an Amazon Web Services account identifier, (For example, 123456789012).

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Required: No

TargetType

The entity type for which the assignment will be created.

Type: String

Valid Values: AWS_ACCOUNT

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AccountAssignmentOperationStatusMetadata

Provides information about the [AccountAssignment](#) creation request.

Contents

CreatedDate

The date that the permission set was created.

Type: Timestamp

Required: No

RequestId

The identifier for tracking the request operation that is generated by the universally unique identifier (UUID) workflow.

Type: String

Length Constraints: Fixed length of 36.

Pattern: \b[0-9a-f]{8}\b-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-\b[0-9a-f]{12}\b

Required: No

Status

The status of the permission set provisioning process.

Type: String

Valid Values: IN_PROGRESS | FAILED | SUCCEEDED

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Application

A structure that describes an application that uses IAM Identity Center for access management.

Contents

ApplicationAccount

The Amazon Web Services account ID number of the application.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Required: No

ApplicationArn

The ARN of the application.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}

Required: No

ApplicationProviderArn

The ARN of the application provider for this application.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::aws:applicationProvider/[a-zA-Z0-9-/]+

Required: No

CreatedDate

The date and time when the application was originally created.

Type: Timestamp

Required: No

Description

The description of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

InstanceArn

The ARN of the instance of IAM Identity Center that is configured with this application.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: No

Name

The name of the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[\S\s]*`

Required: No

PortalOptions

A structure that describes the options for the access portal associated with this application.

Type: [PortalOptions object](#)

Required: No

Status

The current status of the application in this instance of IAM Identity Center.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ApplicationAssignment

A structure that describes an assignment of a principal to an application.

Contents

ApplicationArn

The ARN of the application that has principals assigned.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}`

Required: Yes

PrincipalId

The unique identifier of the principal assigned to the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 47.

Pattern: `([0-9a-f]{10}-|)[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}`

Required: Yes

PrincipalType

The type of the principal assigned to the application.

Type: String

Valid Values: USER | GROUP

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ApplicationAssignmentForPrincipal

A structure that describes an application to which a principal is assigned.

Contents

ApplicationArn

The ARN of the application to which the specified principal is assigned.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}`

Required: No

PrincipalId

The unique identifier of the principal assigned to the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 47.

Pattern: `([0-9a-f]{10}-|)[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}`

Required: No

PrincipalType

The type of the principal assigned to the application.

Type: String

Valid Values: USER | GROUP

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ApplicationProvider

A structure that describes a provider that can be used to connect an Amazon managed application or customer managed application to IAM Identity Center.

Contents

ApplicationProviderArn

The ARN of the application provider.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::aws:applicationProvider/[a-zA-Z0-9-/]+`

Required: Yes

DisplayData

A structure that describes how IAM Identity Center represents the application provider in the portal.

Type: [DisplayData](#) object

Required: No

FederationProtocol

The protocol that the application provider uses to perform federation.

Type: String

Valid Values: SAML | OAUTH

Required: No

ResourceServerConfig

A structure that describes the application provider's resource server.

Type: [ResourceServerConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AttachedManagedPolicy

A structure that stores a list of managed policy ARNs that describe the associated Amazon managed policy.

Contents

Arn

The ARN of the Amazon managed policy. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):iam::aws:policy((/[A-Za-z0-9\.,\+=@_-]+)*)(/[A-Za-z0-9\.,\+=@_-]+)`

Required: No

Name

The name of the Amazon managed policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AuthenticationMethod

A structure that describes an authentication method that can be used by an application.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

Iam

A structure that describes details for IAM authentication.

Type: [IamAuthenticationMethod](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AuthenticationMethodItem

A structure that describes an authentication method and its type.

Contents

AuthenticationMethod

A structure that describes an authentication method. The contents of this structure is determined by the AuthenticationMethodType.

Type: [AuthenticationMethod](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

AuthenticationMethodType

The type of authentication that is used by this method.

Type: String

Valid Values: IAM

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AuthorizationCodeGrant

A structure that defines configuration settings for an application that supports the OAuth 2.0 Authorization Code Grant.

Contents

RedirectUris

A list of URIs that are valid locations to redirect a user's browser after the user is authorized.

 **Note**

RedirectUris is required when the grant type is authorization_code.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AuthorizedTokenIssuer

A structure that describes a trusted token issuer and associates it with a set of authorized audiences.

Contents

AuthorizedAudiences

An array list of authorized audiences, or applications, that can consume the tokens generated by the associated trusted token issuer.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

TrustedTokenIssuerArn

The ARN of the trusted token issuer.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:trustedTokenIssuer/(sso)?ins-[a-zA-Z0-9-.]{16}/tti-[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

CustomerManagedPolicyReference

Specifies the name and path of a customer managed policy. You must have an IAM policy that matches the name and path in each Amazon Web Services account where you want to deploy your permission set.

Contents

Name

The name of the IAM policy that you have configured in each account where you want to deploy your permission set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+=, .@-]+

Required: Yes

Path

The path to the IAM policy that you have configured in each account where you want to deploy your permission set. The default is /. For more information, see [Friendly names and paths](#) in the *IAM User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: ((/[A-Za-z0-9\.,\+@\-=_-]+)+)/

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DisplayData

A structure that describes how the portal represents an application provider.

Contents

Description

The description of the application provider that appears in the portal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

DisplayName

The name of the application provider that appears in the portal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

IconUrl

A URL that points to an icon that represents the application provider.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 768.

Pattern: (http|https):\/\/.*

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Grant

The Grant union represents the set of possible configuration options for the selected grant type. Exactly one member of the union must be specified, and must match the grant type selected.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

AuthorizationCode

Configuration options for the authorization_code grant type.

Type: [AuthorizationCodeGrant](#) object

Required: No

JwtBearer

Configuration options for the urn:ietf:params:oauth:grant-type:jwt-bearer grant type.

Type: [JwtBearerGrant](#) object

Required: No

RefreshToken

Configuration options for the refresh_token grant type.

Type: [RefreshTokenGrant](#) object

Required: No

TokenExchange

Configuration options for the urn:ietf:params:oauth:grant-type:token-exchange grant type.

Type: [TokenExchangeGrant](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

GrantItem

A structure that defines a single grant and its configuration.

Contents

Grant

The configuration structure for the selected grant.

Type: [Grant](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

GrantType

The type of the selected grant.

Type: String

Valid Values: authorization_code | refresh_token |
urn:ietf:params:oauth:grant-type:jwt-bearer |
urn:ietf:params:oauth:grant-type:token-exchange

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

IamAuthenticationMethod

A structure that describes details for authentication that uses IAM.

Contents

ActorPolicy

An IAM policy document in JSON.

Type: JSON value

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

InstanceAccessControlAttributeConfiguration

Specifies the attributes to add to your attribute-based access control (ABAC) configuration.

Contents

AccessControlAttributes

Lists the attributes that are configured for ABAC in the specified IAM Identity Center instance.

Type: Array of [AccessControlAttribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

InstanceMetadata

Provides information about the IAM Identity Center instance.

Contents

CreatedDate

The date and time that the Identity Center instance was created.

Type: Timestamp

Required: No

IdentityStoreId

The identifier of the identity store that is connected to the Identity Center instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9-]*

Required: No

InstanceArn

The ARN of the Identity Center instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::::instance/(sso)?ins-[a-zA-Z0-9-.]{16}

Required: No

Name

The name of the Identity Center instance.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: [\w+=,.@-]+

Required: No

OwnerAccountId

The Amazon Web Services account ID number of the owner of the Identity Center instance.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Required: No

Status

The current status of this Identity Center instance.

Type: String

Valid Values: CREATE_IN_PROGRESS | DELETE_IN_PROGRESS | ACTIVE

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

JwtBearerGrant

A structure that defines configuration settings for an application that supports the JWT Bearer Token Authorization Grant. The AuthorizedAudience field is the aud claim. For more information, see [RFC 7523](#).

Contents

AuthorizedTokenIssuers

A list of allowed token issuers trusted by the Identity Center instances for this application.

 **Note**

AuthorizedTokenIssuers is required when the grant type is JwtBearerGrant.

Type: Array of [AuthorizedTokenIssuer](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ListAccountAssignmentsFilter

A structure that describes a filter for account assignments.

Contents

AccountId

The ID number of an Amazon Web Services account that filters the results in the response.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ListApplicationAssignmentsFilter

A structure that describes a filter for application assignments.

Contents

ApplicationArn

The ARN of an application.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ListApplicationsFilter

A structure that describes a filter for applications.

Contents

ApplicationAccount

An Amazon Web Services account ID number that filters the results in the response.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Required: No

ApplicationProvider

The ARN of an application provider that can filter the results in the response.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::aws:applicationProvider/[a-zA-Z0-9-/]+

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

OidcJwtConfiguration

A structure that describes configuration settings for a trusted token issuer that supports OpenID Connect (OIDC) and JSON Web Tokens (JWTs).

Contents

ClaimAttributePath

The path of the source attribute in the JWT from the trusted token issuer. The attribute mapped by this JMESPath expression is compared against the attribute mapped by IdentityStoreAttributePath when a trusted token issuer token is exchanged for an IAM Identity Center token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: \p{L}+(?:(\.|_) \p{L}+){0,2}

Required: Yes

IdentityStoreAttributePath

The path of the destination attribute in a JWT from IAM Identity Center. The attribute mapped by this JMESPath expression is compared against the attribute mapped by ClaimAttributePath when a trusted token issuer token is exchanged for an IAM Identity Center token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: \p{L}+(?:\.\p{L}+){0,2}

Required: Yes

IssuerUrl

The URL that IAM Identity Center uses for OpenID Discovery. OpenID Discovery is used to obtain the information required to verify the tokens that the trusted token issuer generates.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `https?:\/\/[-a-zA-Z0-9+&@\/%=~_|!:,.;]*[-a-zA-Z0-9+&@\/%=~_|]`

Required: Yes

JwksRetrievalOption

The method that the trusted token issuer can use to retrieve the JSON Web Key Set used to verify a JWT.

Type: String

Valid Values: OPEN_ID_DISCOVERY

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

OidcJwtUpdateConfiguration

A structure that describes updated configuration settings for a trusted token issuer that supports OpenID Connect (OIDC) and JSON Web Tokens (JWTs).

Contents

ClaimAttributePath

The path of the source attribute in the JWT from the trusted token issuer. The attribute mapped by this JMESPath expression is compared against the attribute mapped by IdentityStoreAttributePath when a trusted token issuer token is exchanged for an IAM Identity Center token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: \p{L}+(?:(\.|_) \p{L}+){0,2}

Required: No

IdentityStoreAttributePath

The path of the destination attribute in a JWT from IAM Identity Center. The attribute mapped by this JMESPath expression is compared against the attribute mapped by ClaimAttributePath when a trusted token issuer token is exchanged for an IAM Identity Center token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: \p{L}+(?:\.\p{L}+){0,2}

Required: No

JwksRetrievalOption

The method that the trusted token issuer can use to retrieve the JSON Web Key Set used to verify a JWT.

Type: String

Valid Values: OPEN_ID_DISCOVERY

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

OperationStatusFilter

Filters the operation status list based on the passed attribute value.

Contents

Status

Filters the list operations result based on the status attribute.

Type: String

Valid Values: IN_PROGRESS | FAILED | SUCCEEDED

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PermissionsBoundary

Specifies the configuration of the Amazon managed or customer managed policy that you want to set as a permissions boundary. Specify either `CustomerManagedPolicyReference` to use the name and path of a customer managed policy, or `ManagedPolicyArn` to use the ARN of an Amazon managed policy. A permissions boundary represents the maximum permissions that any policy can grant your role. For more information, see [Permissions boundaries for IAM entities](#) in the *IAM User Guide*.

Important

Policies used as permissions boundaries don't provide permissions. You must also attach an IAM policy to the role. To learn how the effective permissions for a role are evaluated, see [IAM JSON policy evaluation logic](#) in the *IAM User Guide*.

Contents

CustomerManagedPolicyReference

Specifies the name and path of a customer managed policy. You must have an IAM policy that matches the name and path in each Amazon Web Services account where you want to deploy your permission set.

Type: [CustomerManagedPolicyReference](#) object

Required: No

ManagedPolicyArn

The Amazon managed policy ARN that you want to attach to a permission set as a permissions boundary.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):iam::aws:policy((/[A-Za-z0-9\.,\+=@_-]+)+)(/[A-Za-z0-9\.,\+=@_-]+)`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PermissionSet

An entity that contains IAM policies.

Contents

CreatedDate

The date that the permission set was created.

Type: Timestamp

Required: No

Description

The description of the [PermissionSet](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 700.

Pattern: [\u0009\u000A\u000D\u0020-\u007E\u00A1-\u00FF]*

Required: No

Name

The name of the permission set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: [\w+=,.@-]+

Required: No

PermissionSetArn

The ARN of the permission set. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Required: No

RelayState

Used to redirect users within the application during the federation authentication process.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 240.

Pattern: `[a-zA-Z0-9&#$@#\\"%?=~\-_'"|!:,.;*+\[\]\ \(\)\{\}\]+`

Required: No

SessionDuration

The length of time that the application user sessions are valid for in the ISO-8601 standard.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(-?)P(?=\d|T\d)(?:(\d+)Y)?(?:(\d+)M)?(?:(\d+)([DW]))?(?:T(?:(\d+)H)?(?:(\d+)M)?(?:(\d+(?:\.\d+)?)S)?)?`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PermissionSetProvisioningStatus

A structure that is used to provide the status of the provisioning operation for a specified permission set.

Contents

AccountId

The identifier of the Amazon account from which to list the assignments.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Required: No

CreatedDate

The date that the permission set was created.

Type: Timestamp

Required: No

FailureReason

The message that contains an error or exception in case of an operation failure.

Type: String

Pattern: [\p{L}\p{M}\p{Z}\p{S}\p{N}\p{P}]*

Required: No

PermissionSetArn

The ARN of the permission set that is being provisioned. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and Amazon Service Namespaces](#) in the *Amazon General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Required: No

RequestId

The identifier for tracking the request operation that is generated by the universally unique identifier (UUID) workflow.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `\b[0-9a-f]{8}\b-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-\b[0-9a-f]{12}\b`

Required: No

Status

The status of the permission set provisioning process.

Type: String

Valid Values: IN_PROGRESS | FAILED | SUCCEEDED

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PermissionSetProvisioningStatusMetadata

Provides information about the permission set provisioning status.

Contents

CreatedDate

The date that the permission set was created.

Type: Timestamp

Required: No

RequestId

The identifier for tracking the request operation that is generated by the universally unique identifier (UUID) workflow.

Type: String

Length Constraints: Fixed length of 36.

Pattern: \b[0-9a-f]{8}\b-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-\b[0-9a-f]{12}\b

Required: No

Status

The status of the permission set provisioning process.

Type: String

Valid Values: IN_PROGRESS | FAILED | SUCCEEDED

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PortalOptions

A structure that describes the options for the access portal associated with an application.

Contents

SignInOptions

A structure that describes the sign-in options for the access portal.

Type: [SignInOptions](#) object

Required: No

Visibility

Indicates whether this application is visible in the access portal.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RefreshTokenGrant

A structure that defines configuration settings for an application that supports the OAuth 2.0 Refresh Token Grant. For more, see [RFC 6749](#).

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ResourceServerConfig

A structure that describes the configuration of a resource server.

Contents

Scopes

A list of the IAM Identity Center access scopes that are associated with this resource server.

Type: String to [ResourceServerScopeDetails](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 80.

Key Pattern: [^:=\-\.\s][0-9a-zA-Z_-:\-\.\.]+

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ResourceServerScopeDetails

A structure that describes details for an IAM Identity Center access scope that is associated with a resource server.

Contents

DetailedTitle

The title of an access scope for a resource server.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

LongDescription

The description of an access scope for a resource server.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ScopeDetails

A structure that describes an IAM Identity Center access scope and its authorized targets.

Contents

Scope

The name of the access scope.

Type: String

Pattern: ([A-Za-z0-9_]{1,50})(:[A-Za-z0-9_]{1,50}){0,1}(:[A-Za-z0-9_]{1,50}){0,1}

Required: Yes

AuthorizedTargets

An array list of ARNs of applications.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::(\d{12}:application/(sso)?ins-[a-zA-Z0-9-.]{16}/apl-[a-zA-Z0-9]{16}|:instance/(sso)?ins-[a-zA-Z0-9-.]{16})

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SignInOptions

A structure that describes the sign-in options for an application portal.

Contents

Origin

This determines how IAM Identity Center navigates the user to the target application. It can be one of the following values:

- APPLICATION: IAM Identity Center redirects the customer to the configured ApplicationUrl.
- IDENTITY_CENTER: IAM Identity Center uses SAML identity-provider initiated authentication to sign the customer directly into a SAML-based application.

Type: String

Valid Values: IDENTITY_CENTER | APPLICATION

Required: Yes

ApplicationUrl

The URL that accepts authentication requests for an application. This is a required parameter if the Origin parameter is APPLICATION.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: http(s)?://[-a-zA-Z0-9+&@#\%?=~_|!:.;]*[-a-zA-Z0-9+&bb@#\%?=~_|]

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Tag

A set of key-value pairs that are used to manage the resource. Tags can only be applied to permission sets and cannot be applied to corresponding roles that IAM Identity Center creates in Amazon accounts.

Contents

Key

The key for the tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ([\p{L}]\p{Z}\p{N}_.:=/+\\-@]*)

Required: Yes

Value

The value of the tag.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: ([\p{L}]\p{Z}\p{N}_.:=/+\\-@]*)

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

TokenExchangeGrant

A structure that defines configuration settings for an application that supports the OAuth 2.0 Token Exchange Grant. For more information, see [RFC 8693](#).

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

TrustedTokenIssuerConfiguration

A structure that describes the configuration of a trusted token issuer. The structure and available settings are determined by the type of the trusted token issuer.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

OidcJwtConfiguration

A structure that describes the settings for a trusted token issuer that works with OpenID Connect (OIDC) by using JSON Web Tokens (JWT).

Type: [OidcJwtConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

TrustedTokenIssuerMetadata

A structure that describes a trusted token issuer.

Contents

Name

The name of the trusted token issuer configuration in the instance of IAM Identity Center.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: [\w+=, .@-]+

Required: No

TrustedTokenIssuerArn

The ARN of the trusted token issuer configuration in the instance of IAM Identity Center.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::
\d{12}:trustedTokenIssuer/(sso)?ins-[a-zA-Z0-9-.]{16}/tti-[a-f0-9]{8}-
[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: No

TrustedTokenIssuerType

The type of trusted token issuer.

Type: String

Valid Values: OIDC_JWT

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

TrustedTokenIssuerUpdateConfiguration

A structure that contains details to be updated for a trusted token issuer configuration. The structure and settings that you can include depend on the type of the trusted token issuer being updated.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

OidcJwtConfiguration

A structure that describes an updated configuration for a trusted token issuer that uses OpenID Connect (OIDC) with JSON web tokens (JWT).

Type: [OidcJwtUpdateConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

UpdateApplicationPortalOptions

A structure that describes the options for the access portal associated with an application that can be updated.

Contents

SignInOptions

A structure that describes the sign-in options for an application portal.

Type: [SignInOptions](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing Amazon API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed Amazon API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an Amazon API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to Amazon Security Token Service (Amazon STS). For a list of services that support temporary security credentials from Amazon STS, see [Amazon Web Services services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from Amazon STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed Amazon API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all Amazon services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to Amazon standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or Amazon access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The Amazon access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an Amazon service.

HTTP Status Code: 400

Document History

The following table describes the important changes to the documentation in this release of the *IAM Identity Center API Reference Guide*.

- **Latest documentation update:** July 26, 2022

Change	Description	Date Changed
Amazon Single Sign-On (Amazon SSO) renamed to Amazon IAM Identity Center	Amazon introduces Amazon IAM Identity Center. IAM Identity Center expands the capabilities of Amazon Identity and Access Management (IAM) to help you centrally manage account and access to cloud applications for your workforce users. For more information, see IAM Identity Center rename .	July 26th, 2022
Permission boundaries	Added new APIs to support permission boundaries and customer managed policies in permission sets. For more information, see Permission sets .	July 14, 2022
ABAC	Added new APIs to support attribute-based access control (ABAC). For more information, see Attribute-based access control .	November 4, 2020
New guide	This is the first release of the IAM Identity Center API Reference Guide.	September 10, 2020