

Amazon WorkSpaces Service



Amazon WorkSpaces Service: API Reference

Table of Contents

Welcome	1
Actions	2
AssociateConnectionAlias	5
Request Syntax	5
Request Parameters	5
Response Syntax	6
Response Elements	6
Errors	6
See Also	7
AssociateIpGroups	8
Request Syntax	8
Request Parameters	8
Response Elements	8
Errors	9
See Also	9
AssociateWorkspaceApplication	11
Request Syntax	11
Request Parameters	11
Response Syntax	11
Response Elements	12
Errors	12
See Also	13
AuthorizeIpRules	15
Request Syntax	15
Request Parameters	15
Response Elements	16
Errors	16
See Also	16
CopyWorkspaceImage	18
Request Syntax	18
Request Parameters	18
Response Syntax	20
Response Elements	20
Errors	20

See Also	21
CreateConnectClientAddIn	22
Request Syntax	22
Request Parameters	22
Response Syntax	23
Response Elements	23
Errors	23
See Also	24
CreateConnectionAlias	25
Request Syntax	25
Request Parameters	25
Response Syntax	26
Response Elements	26
Errors	26
See Also	27
CreateHelpGroup	29
Request Syntax	29
Request Parameters	29
Response Syntax	30
Response Elements	30
Errors	31
See Also	31
CreateStandbyWorkspaces	33
Request Syntax	33
Request Parameters	33
Response Syntax	34
Response Elements	34
Errors	35
See Also	36
CreateTags	37
Request Syntax	37
Request Parameters	37
Response Elements	37
Errors	38
See Also	38
CreateUpdatedWorkspaceImage	39

Request Syntax	39
Request Parameters	39
Response Syntax	41
Response Elements	41
Errors	41
See Also	42
CreateWorkspaceBundle	43
Request Syntax	43
Request Parameters	43
Response Syntax	45
Response Elements	45
Errors	46
See Also	47
CreateWorkspaceImage	48
Request Syntax	48
Request Parameters	48
Response Syntax	49
Response Elements	49
Errors	51
See Also	52
CreateWorkspaces	53
Request Syntax	53
Request Parameters	54
Response Syntax	54
Response Elements	56
Errors	57
See Also	57
DeleteClientBranding	58
Request Syntax	58
Request Parameters	58
Response Elements	59
Errors	59
See Also	59
DeleteConnectClientAddIn	61
Request Syntax	61
Request Parameters	61

Response Elements	61
Errors	62
See Also	62
DeleteConnectionAlias	63
Request Syntax	63
Request Parameters	63
Response Elements	64
Errors	64
See Also	65
DeleteHelpGroup	66
Request Syntax	66
Request Parameters	66
Response Elements	66
Errors	66
See Also	67
DeleteTags	68
Request Syntax	68
Request Parameters	68
Response Elements	68
Errors	68
See Also	69
DeleteWorkspaceBundle	70
Request Syntax	70
Request Parameters	70
Response Elements	70
Errors	70
See Also	71
DeleteWorkspaceImage	72
Request Syntax	72
Request Parameters	72
Response Elements	72
Errors	72
See Also	73
DeployWorkspaceApplications	74
Request Syntax	74
Request Parameters	74

Response Syntax	74
Response Elements	75
Errors	75
See Also	76
DeregisterWorkspaceDirectory	77
Request Syntax	77
Request Parameters	77
Response Elements	78
Errors	78
See Also	78
DescribeAccount	80
Response Syntax	80
Response Elements	80
Errors	81
See Also	81
DescribeAccountModifications	82
Request Syntax	82
Request Parameters	82
Response Syntax	82
Response Elements	83
Errors	83
See Also	83
DescribeApplicationAssociations	85
Request Syntax	85
Request Parameters	85
Response Syntax	86
Response Elements	86
Errors	87
See Also	87
DescribeApplications	89
Request Syntax	89
Request Parameters	89
Response Syntax	91
Response Elements	91
Errors	92
See Also	92

DescribeBundleAssociations	94
Request Syntax	94
Request Parameters	94
Response Syntax	94
Response Elements	95
Errors	95
See Also	96
DescribeClientBranding	97
Request Syntax	97
Request Parameters	97
Response Syntax	97
Response Elements	99
Errors	100
See Also	100
DescribeClientProperties	102
Request Syntax	102
Request Parameters	102
Response Syntax	102
Response Elements	103
Errors	103
See Also	103
DescribeConnectClientAddIns	105
Request Syntax	105
Request Parameters	105
Response Syntax	106
Response Elements	106
Errors	106
See Also	107
DescribeConnectionAliases	108
Request Syntax	108
Request Parameters	108
Response Syntax	109
Response Elements	110
Errors	110
See Also	111
DescribeConnectionAliasPermissions	112

Request Syntax	112
Request Parameters	112
Response Syntax	113
Response Elements	113
Errors	114
See Also	114
DescribeImageAssociations	116
Request Syntax	116
Request Parameters	116
Response Syntax	116
Response Elements	117
Errors	117
See Also	118
DescribeIpGroups	119
Request Syntax	119
Request Parameters	119
Response Syntax	120
Response Elements	120
Errors	121
See Also	121
DescribeTags	122
Request Syntax	122
Request Parameters	122
Response Syntax	122
Response Elements	122
Errors	123
See Also	123
DescribeWorkspaceAssociations	124
Request Syntax	124
Request Parameters	124
Response Syntax	124
Response Elements	125
Errors	125
See Also	126
DescribeWorkspaceBundles	127
Request Syntax	127

Request Parameters	127
Response Syntax	128
Response Elements	128
Errors	129
See Also	129
DescribeWorkspaceDirectories	131
Request Syntax	131
Request Parameters	131
Response Syntax	132
Response Elements	133
Errors	133
See Also	134
DescribeWorkspacesImagePermissions	135
Request Syntax	135
Request Parameters	135
Response Syntax	136
Response Elements	136
Errors	137
See Also	137
DescribeWorkspacesImages	138
Request Syntax	138
Request Parameters	138
Response Syntax	139
Response Elements	140
Errors	140
See Also	140
DescribeWorkspaces	142
Request Syntax	142
Request Parameters	142
Response Syntax	144
Response Elements	145
Errors	146
See Also	146
DescribeWorkspacesConnectionStatus	148
Request Syntax	148
Request Parameters	148

Response Syntax	148
Response Elements	149
Errors	149
See Also	150
DescribeWorkspaceSnapshots	151
Request Syntax	151
Request Parameters	151
Response Syntax	151
Response Elements	152
Errors	152
See Also	153
DisassociateConnectionAlias	154
Request Syntax	154
Request Parameters	154
Response Elements	154
Errors	155
See Also	155
DisassociateIpGroups	157
Request Syntax	157
Request Parameters	157
Response Elements	157
Errors	158
See Also	158
DisassociateWorkspaceApplication	160
Request Syntax	160
Request Parameters	160
Response Syntax	160
Response Elements	161
Errors	161
See Also	162
ImportClientBranding	163
Request Syntax	163
Request Parameters	165
Response Syntax	166
Response Elements	167
Errors	168

See Also	169
ImportWorkspaceImage	170
Request Syntax	170
Request Parameters	170
Response Syntax	172
Response Elements	172
Errors	173
See Also	174
ListAvailableManagementCidrRanges	175
Request Syntax	175
Request Parameters	175
Response Syntax	176
Response Elements	176
Errors	177
See Also	177
MigrateWorkspace	178
Request Syntax	178
Request Parameters	178
Response Syntax	179
Response Elements	179
Errors	179
See Also	180
ModifyAccount	182
Request Syntax	182
Request Parameters	182
Response Elements	183
Errors	183
See Also	183
ModifyCertificateBasedAuthProperties	185
Request Syntax	185
Request Parameters	185
Response Elements	186
Errors	186
See Also	186
ModifyClientProperties	188
Request Syntax	188

Request Parameters	188
Response Elements	188
Errors	188
See Also	189
ModifySamlProperties	190
Request Syntax	190
Request Parameters	190
Response Elements	191
Errors	191
See Also	192
ModifySelfservicePermissions	193
Request Syntax	193
Request Parameters	193
Response Elements	194
Errors	194
See Also	194
ModifyWorkspaceAccessProperties	196
Request Syntax	196
Request Parameters	196
Response Elements	197
Errors	197
See Also	197
ModifyWorkspaceCreationProperties	198
Request Syntax	198
Request Parameters	198
Response Elements	199
Errors	199
See Also	199
ModifyWorkspaceProperties	201
Request Syntax	201
Request Parameters	201
Response Elements	202
Errors	202
See Also	203
ModifyWorkspaceState	204
Request Syntax	204

Request Parameters	204
Response Elements	204
Errors	205
See Also	205
RebootWorkspaces	207
Request Syntax	207
Request Parameters	207
Response Syntax	207
Response Elements	208
Errors	208
See Also	208
RebuildWorkspaces	210
Request Syntax	210
Request Parameters	210
Response Syntax	210
Response Elements	211
Errors	211
See Also	211
RegisterWorkspaceDirectory	213
Request Syntax	213
Request Parameters	213
Response Elements	215
Errors	215
See Also	216
RestoreWorkspace	217
Request Syntax	217
Request Parameters	217
Response Elements	217
Errors	217
See Also	218
RevokeRules	219
Request Syntax	219
Request Parameters	219
Response Elements	219
Errors	219
See Also	220

StartWorkspaces	221
Request Syntax	221
Request Parameters	221
Response Syntax	221
Response Elements	222
Errors	222
See Also	222
StopWorkspaces	223
Request Syntax	223
Request Parameters	223
Response Syntax	223
Response Elements	224
Errors	224
See Also	224
TerminateWorkspaces	225
Request Syntax	225
Request Parameters	226
Response Syntax	226
Response Elements	226
Errors	227
See Also	227
UpdateConnectClientAddIn	228
Request Syntax	228
Request Parameters	228
Response Elements	229
Errors	229
See Also	230
UpdateConnectionAliasPermission	231
Request Syntax	231
Request Parameters	231
Response Elements	232
Errors	232
See Also	233
UpdateRulesOfIpGroup	234
Request Syntax	234
Request Parameters	234

Response Elements	234
Errors	235
See Also	235
UpdateWorkspaceBundle	237
Request Syntax	237
Request Parameters	237
Response Elements	238
Errors	238
See Also	238
UpdateWorkspacesImagePermission	240
Request Syntax	240
Request Parameters	240
Response Elements	241
Errors	241
See Also	242
Data Types	244
AccountModification	247
Contents	247
See Also	248
ApplicationResourceAssociation	249
Contents	249
See Also	250
AssociationStateReason	251
Contents	251
See Also	251
BundleResourceAssociation	253
Contents	253
See Also	254
CertificateBasedAuthProperties	255
Contents	255
See Also	255
ClientProperties	256
Contents	256
See Also	256
ClientPropertiesResult	258
Contents	258

See Also	258
ComputeType	259
Contents	259
See Also	259
ConnectClientAddIn	260
Contents	260
See Also	261
ConnectionAlias	262
Contents	262
See Also	263
ConnectionAliasAssociation	264
Contents	264
See Also	265
ConnectionAliasPermission	266
Contents	266
See Also	266
DataReplicationSettings	267
Contents	267
See Also	267
DefaultClientBrandingAttributes	268
Contents	268
See Also	270
DefaultImportClientBrandingAttributes	271
Contents	271
See Also	273
DefaultWorkspaceCreationProperties	274
Contents	274
See Also	275
ErrorDetails	276
Contents	276
See Also	276
FailedCreateStandbyWorkspacesRequest	278
Contents	278
See Also	278
FailedCreateWorkspaceRequest	279
Contents	279

See Also	279
FailedWorkspaceChangeRequest	280
Contents	280
See Also	280
ImagePermission	282
Contents	282
See Also	282
ImageResourceAssociation	283
Contents	283
See Also	284
IosClientBrandingAttributes	285
Contents	285
See Also	288
IosImportClientBrandingAttributes	289
Contents	289
See Also	292
IpRuleItem	293
Contents	293
See Also	293
ModificationState	294
Contents	294
See Also	294
OperatingSystem	295
Contents	295
See Also	295
PendingCreateStandbyWorkspacesRequest	296
Contents	296
See Also	297
RebootRequest	298
Contents	298
See Also	298
RebuildRequest	299
Contents	299
See Also	299
RelatedWorkspaceProperties	300
Contents	300

See Also	301
RootStorage	302
Contents	302
See Also	302
SamlProperties	303
Contents	303
See Also	304
SelfservicePermissions	305
Contents	305
See Also	306
Snapshot	307
Contents	307
See Also	307
StandbyWorkspace	308
Contents	308
See Also	309
StandbyWorkspacesProperties	310
Contents	310
See Also	310
StartRequest	312
Contents	312
See Also	312
StopRequest	313
Contents	313
See Also	313
Tag	314
Contents	314
See Also	314
TerminateRequest	315
Contents	315
See Also	315
UpdateResult	316
Contents	316
See Also	316
UserStorage	318
Contents	318

See Also	318
Workspace	319
Contents	319
See Also	323
WorkspaceAccessProperties	325
Contents	325
See Also	326
WorkSpaceApplication	328
Contents	328
See Also	330
WorkSpaceApplicationDeployment	331
Contents	331
See Also	331
WorkspaceBundle	332
Contents	332
See Also	334
WorkspaceConnectionStatus	335
Contents	335
See Also	336
WorkspaceCreationProperties	337
Contents	337
See Also	339
WorkspaceDirectory	340
Contents	340
See Also	344
WorkspacelImage	345
Contents	345
See Also	347
WorkspaceProperties	348
Contents	348
See Also	350
WorkspaceRequest	351
Contents	351
See Also	353
WorkspaceResourceAssociation	354
Contents	354

See Also	355
WorkspacesIpGroup	356
Contents	356
See Also	356
Common Errors	358
WorkSpaces Core API actions	360
CloudTrail Logging	363
WorkSpaces Information in CloudTrail	363
Example: WorkSpaces Log File Entry	364

Welcome to the Amazon WorkSpaces API Reference

Amazon WorkSpaces enables you to provision virtual, cloud-based Microsoft Windows or Amazon Linux desktops for your users, known as *WorkSpaces*. WorkSpaces eliminates the need to procure and deploy hardware or install complex software. You can quickly add or remove users as your needs change. Users can access their virtual desktops from multiple devices or web browsers.

This API Reference provides detailed information about the actions, data types, parameters, and errors of the WorkSpaces service. For more information about the supported Amazon Regions, endpoints, and service quotas of the WorkSpaces service, see [WorkSpaces endpoints and quotas](#) in the *Amazon General Reference*.

You can also manage your WorkSpaces resources using the WorkSpaces console, Amazon Command Line Interface (Amazon CLI), and SDKs. For more information about administering WorkSpaces, see the [Amazon WorkSpaces Administration Guide](#). For more information about using the Amazon WorkSpaces client application or web browser to access provisioned WorkSpaces, see the [Amazon WorkSpaces User Guide](#). For more information about using the Amazon CLI to manage your WorkSpaces resources, see the [WorkSpaces section of the Amazon CLI Reference](#).

Actions

The following actions are supported:

- [AssociateConnectionAlias](#)
- [AssociateIpGroups](#)
- [AssociateWorkspaceApplication](#)
- [AuthorizelpRules](#)
- [CopyWorkspacelImage](#)
- [CreateConnectClientAddIn](#)
- [CreateConnectionAlias](#)
- [CreateIpGroup](#)
- [CreateStandbyWorkspaces](#)
- [CreateTags](#)
- [CreateUpdatedWorkspacelImage](#)
- [CreateWorkspaceBundle](#)
- [CreateWorkspacelImage](#)
- [CreateWorkspaces](#)
- [DeleteClientBranding](#)
- [DeleteConnectClientAddIn](#)
- [DeleteConnectionAlias](#)
- [DeleteIpGroup](#)
- [DeleteTags](#)
- [DeleteWorkspaceBundle](#)
- [DeleteWorkspacelImage](#)
- [DeployWorkspaceApplications](#)
- [DeregisterWorkspaceDirectory](#)
- [DescribeAccount](#)
- [DescribeAccountModifications](#)
- [DescribeApplicationAssociations](#)
- [DescribeApplications](#)

- [DescribeBundleAssociations](#)
- [DescribeClientBranding](#)
- [DescribeClientProperties](#)
- [DescribeConnectClientAddIns](#)
- [DescribeConnectionAliases](#)
- [DescribeConnectionAliasPermissions](#)
- [DescribeImageAssociations](#)
- [DescribelpGroups](#)
- [DescribeTags](#)
- [DescribeWorkspaceAssociations](#)
- [DescribeWorkspaceBundles](#)
- [DescribeWorkspaceDirectories](#)
- [DescribeWorkspacelImagePermissions](#)
- [DescribeWorkspacelImages](#)
- [DescribeWorkspaces](#)
- [DescribeWorkspacesConnectionStatus](#)
- [DescribeWorkspaceSnapshots](#)
- [DisassociateConnectionAlias](#)
- [DisassociatelpGroups](#)
- [DisassociateWorkspaceApplication](#)
- [ImportClientBranding](#)
- [ImportWorkspacelImage](#)
- [ListAvailableManagementCidrRanges](#)
- [MigrateWorkspace](#)
- [ModifyAccount](#)
- [ModifyCertificateBasedAuthProperties](#)
- [ModifyClientProperties](#)
- [ModifySamlProperties](#)
- [ModifySelfservicePermissions](#)
- [ModifyWorkspaceAccessProperties](#)

- [ModifyWorkspaceCreationProperties](#)
- [ModifyWorkspaceProperties](#)
- [ModifyWorkspaceState](#)
- [RebootWorkspaces](#)
- [RebuildWorkspaces](#)
- [RegisterWorkspaceDirectory](#)
- [RestoreWorkspace](#)
- [RevokeIpRules](#)
- [StartWorkspaces](#)
- [StopWorkspaces](#)
- [TerminateWorkspaces](#)
- [UpdateConnectClientAddIn](#)
- [UpdateConnectionAliasPermission](#)
- [UpdateRulesOfIpGroup](#)
- [UpdateWorkspaceBundle](#)
- [UpdateWorkspaceImagePermission](#)

AssociateConnectionAlias

Associates the specified connection alias with the specified directory to enable cross-Region redirection. For more information, see [Cross-Region Redirection for Amazon WorkSpaces](#).

Note

Before performing this operation, call [DescribeConnectionAliases](#) to make sure that the current state of the connection alias is CREATED.

Request Syntax

```
{  
    "AliasId": "string",  
    "ResourceId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

AliasId

The identifier of the connection alias.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 68.

Pattern: ^wsca-[0-9a-z]{8,63}\$

Required: Yes

ResourceId

The identifier of the directory to associate the connection alias with.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Response Syntax

```
{  
  "ConnectionIdentifier": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ConnectionIdentifier](#)

The identifier of the connection alias association. You use the connection identifier in the DNS TXT record when you're configuring your DNS routing policies.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: ^[a-zA-Z0-9]+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceAssociatedException

The resource is associated with a directory.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

AssociateIpGroups

Associates the specified IP access control group with the specified directory.

Request Syntax

```
{  
    "DirectoryId": "string",  
    "GroupIds": [ "string" ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

DirectoryId

The identifier of the directory.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: Yes

GroupIds

The identifiers of one or more IP access control groups.

Type: Array of strings

Pattern: wsipg-[0-9a-z]{8,63}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

AssociateWorkspaceApplication

Associates the specified application to the specified WorkSpace.

Request Syntax

```
{  
    "ApplicationId": "string",  
    "WorkspaceId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationId

The identifier of the application.

Type: String

Pattern: ^wsa-[0-9a-z]{8,63}\$

Required: Yes

WorkspaceId

The identifier of the WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: Yes

Response Syntax

```
{  
    "Association": {  
        "AssociatedResourceId": "string",  
        "AssociatedResourceType": "string",  
        "Created": number,  
    }  
}
```

```
"LastUpdatedTime": number,  
"Statestring",  
"StateReason": {  
    "ErrorCode": "string",  
    "ErrorMessage": "string"  
},  
"WorkspaceId": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Association

Information about the association between the specified WorkSpace and the specified application.

Type: [WorkspaceResourceAssociation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

ApplicationNotSupportedException

The specified application is not supported.

HTTP Status Code: 400

ComputeNotCompatibleException

The compute type of the WorkSpace is not compatible with the application.

HTTP Status Code: 400

IncompatibleApplicationsException

The specified application is not compatible with the resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperatingSystemNotCompatibleException

The operating system of the WorkSpace is not compatible with the application.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceInUseException

The specified resource is currently in use.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

AuthorizelpRules

Adds one or more rules to the specified IP access control group.

This action gives users permission to access their WorkSpaces from the CIDR address ranges specified in the rules.

Request Syntax

```
{  
    "GroupId": "string",  
    "UserRules": [  
        {  
            "ipRule": "string",  
            "ruleDesc": "string"  
        }  
    ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

GroupId

The identifier of the group.

Type: String

Pattern: wsipg-[0-9a-z]{8,63}\$

Required: Yes

UserRules

The rules to add to the group.

Type: Array of [IpRuleItem](#) objects

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CopyWorkspacesImage

Copies the specified image from the specified Region to the current Region. For more information about copying images, see [Copy a Custom WorkSpaces Image](#).

In the China (Ningxia) Region, you can copy images only within the same Region.

In Amazon GovCloud (US), to copy images to and from other Regions, contact Amazon Web Services Support.

Important

Before copying a shared image, be sure to verify that it has been shared from the correct Amazon Web Services account. To determine if an image has been shared and to see the ID of the Amazon Web Services account that owns an image, use the [DescribeWorkSpaceImages](#) and [DescribeWorkspaceImagePermissions](#) API operations.

Request Syntax

```
{  
    "Description": "string",  
    "Name": "string",  
    "SourceImageId": "string",  
    "SourceRegion": "string",  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

[Description](#)

A description of the image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^[a-zA-Z0-9_./() -]+\$

Required: No

Name

The name of the image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[a-zA-Z0-9_./()\\-]+\$

Required: Yes

SourceImageId

The identifier of the source image.

Type: String

Pattern: wsi-[0-9a-z]{9,63}\$

Required: Yes

SourceRegion

The identifier of the source Region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 31.

Pattern: ^[-0-9a-z]{1,31}\$

Required: Yes

Tags

The tags for the image.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
{  
    "ImageId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ImageId

The identifier of the image.

Type: String

Pattern: wsi-[0-9a-z]{9,63}\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

ResourceUnavailableException

The specified resource is not available.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateConnectClientAddIn

Creates a client-add-in for Amazon Connect within a directory. You can create only one Amazon Connect client add-in within a directory.

This client add-in allows WorkSpaces users to seamlessly connect to Amazon Connect.

Request Syntax

```
{  
    "Name": "string",  
    "ResourceId": "string",  
    "URL": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

Name

The name of the client add-in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^ . *\$

Required: Yes

ResourcedId

The directory identifier for which to configure the client add-in.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: Yes

URL

The endpoint URL of the Amazon Connect client add-in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: ^(http|https)\:\/\/\S+

Required: Yes

Response Syntax

```
{  
    "AddInId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AddInId

The client add-in identifier.

Type: String

Length Constraints: Fixed length of 36.

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceCreationFailedException

The resource could not be created.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateConnectionAlias

Creates the specified connection alias for use with cross-Region redirection. For more information, see [Cross-Region Redirection for Amazon WorkSpaces](#).

Request Syntax

```
{  
    "ConnectionString": "string",  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

ConnectionString

A connection string in the form of a fully qualified domain name (FQDN), such as `www.example.com`.

⚠ Important

After you create a connection string, it is always associated to your Amazon Web Services account. You cannot recreate the same connection string with a different account, even if you delete all instances of it from the original account. The connection string is globally reserved for your account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[\.\-_a-zA-Z\-_]{1,255}\$`

Required: Yes

Tags

The tags to associate with the connection alias.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
{  
    "AliasId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AliasId](#)

The identifier of the connection alias.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 68.

Pattern: ^wsca-[0-9a-z]{8,63}\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)

- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateIpGroup

Creates an IP access control group.

An IP access control group provides you with the ability to control the IP addresses from which users are allowed to access their WorkSpaces. To specify the CIDR address ranges, add rules to your IP access control group and then associate the group with your directory. You can add rules when you create the group or at any time using [AuthorizelpRules](#).

There is a default IP access control group associated with your directory. If you don't associate an IP access control group with your directory, the default group is used. The default group includes a default rule that allows users to access their WorkSpaces from anywhere. You cannot modify the default IP access control group for your directory.

Request Syntax

```
{  
    "GroupDesc": "string",  
    "GroupName": "string",  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ],  
    "UserRules": [  
        {  
            "ipRule": "string",  
            "ruleDesc": "string"  
        }  
    ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

GroupDesc

The description of the group.

Type: String

Required: No

[GroupName](#)

The name of the group.

Type: String

Required: Yes

[Tags](#)

The tags. Each WorkSpaces resource can have a maximum of 50 tags.

Type: Array of [Tag](#) objects

Required: No

[UserRules](#)

The rules to add to the group.

Type: Array of [IpRuleItem](#) objects

Required: No

Response Syntax

```
{  
    "GroupId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[GroupId](#)

The identifier of the group.

Type: String

Pattern: wsipg-[0-9a-z]{8,63}\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceCreationFailedException

The resource could not be created.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateStandbyWorkspaces

Creates a standby WorkSpace in a secondary Region.

Request Syntax

```
{  
    "PrimaryRegion": "string",  
    "StandbyWorkspaces": [  
        {  
            "DataReplication": "string",  
            "DirectoryId": "string",  
            "PrimaryWorkspaceId": "string",  
            "Tags": [  
                {  
                    "Key": "string",  
                    "Value": "string"  
                }  
            ],  
            "VolumeEncryptionKey": "string"  
        }  
    ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

PrimaryRegion

The Region of the primary WorkSpace.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 31.

Pattern: ^[-0-9a-z]{1,31}\$

Required: Yes

StandbyWorkspaces

Information about the standby WorkSpace to be created.

Type: Array of [StandbyWorkspace](#) objects

Required: Yes

Response Syntax

```
{  
    "FailedStandbyRequests": [  
        {  
            "ErrorCode": "string",  
            "ErrorMessage": "string",  
            "StandbyWorkspaceRequest": {  
                "DataReplication": "string",  
                "DirectoryId": "string",  
                "PrimaryWorkspaceId": "string",  
                "Tags": [  
                    {  
                        "Key": "string",  
                        "Value": "string"  
                    }  
                ],  
                "VolumeEncryptionKey": "string"  
            }  
        }  
    ],  
    "PendingStandbyRequests": [  
        {  
            "DirectoryId": "string",  
            "State": "string",  
            "UserName": "string",  
            "WorkspaceId": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

FailedStandbyRequests

Information about the standby WorkSpace that could not be created.

Type: Array of [FailedCreateStandbyWorkspacesRequest](#) objects

PendingStandbyRequests

Information about the standby WorkSpace that was created.

Type: Array of [PendingCreateStandbyWorkspacesRequest](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateTags

Creates the specified tags for the specified WorkSpaces resource.

Request Syntax

```
{  
    "ResourceId": "string",  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

ResourceId

The identifier of the WorkSpaces resource. The supported resource types are WorkSpaces, registered directories, images, custom bundles, IP access control groups, and connection aliases.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Tags

The tags. Each WorkSpaces resource can have a maximum of 50 tags.

Type: Array of [Tag](#) objects

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateUpdatedWorkSpaceImage

Creates a new updated WorkSpace image based on the specified source image. The new updated WorkSpace image has the latest drivers and other updates required by the Amazon WorkSpaces components.

To determine which WorkSpace images need to be updated with the latest Amazon WorkSpaces requirements, use [DescribeWorkSpaceImages](#).

Note

- Only Windows 10, Windows Server 2016, and Windows Server 2019 WorkSpace images can be programmatically updated at this time.
- Microsoft Windows updates and other application updates are not included in the update process.
- The source WorkSpace image is not deleted. You can delete the source image after you've verified your new updated image and created a new bundle.

Request Syntax

```
{  
    "Description": "string",  
    "Name": "string",  
    "SourceImageId": "string",  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

Description

A description of whether updates for the WorkSpace image are available.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^[a-zA-Z0-9_./() -]+\$

Required: Yes

Name

The name of the new updated WorkSpace image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[a-zA-Z0-9_./()\\"-]+\$

Required: Yes

SourceImageId

The identifier of the source WorkSpace image.

Type: String

Pattern: wsi-[0-9a-z]{9,63}\$

Required: Yes

Tags

The tags that you want to add to the new updated WorkSpace image.

Note

To add tags at the same time when you're creating the updated image, you must create an IAM policy that grants your IAM user permissions to use `workspaces:CreateTags`.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
{  
    "ImageId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ImageId

The identifier of the new updated WorkSpace image.

Type: String

Pattern: wsi-[0-9a-z]{9,63}\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateWorkspaceBundle

Creates the specified WorkSpace bundle. For more information about creating WorkSpace bundles, see [Create a Custom WorkSpaces Image and Bundle](#).

Request Syntax

```
{  
    "BundleDescription": "string",  
    "BundleName": "string",  
    "ComputeType": {  
        "Name": "string"  
    },  
    "ImageId": "string",  
    "RootStorage": {  
        "Capacity": "string"  
    },  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ],  
    "UserStorage": {  
        "Capacity": "string"  
    }  
}
```

Request Parameters

The request accepts the following data in JSON format.

BundleDescription

The description of the bundle.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: ^[a-zA-Z0-9_./() -]+\$

Required: Yes

BundleName

The name of the bundle.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[a-zA-Z0-9_./()\\-]+\$

Required: Yes

ComputeType

Describes the compute type of the bundle.

Type: [ComputeType](#) object

Required: Yes

ImageId

The identifier of the image that is used to create the bundle.

Type: String

Pattern: wsi-[0-9a-z]{9,63}\$

Required: Yes

RootStorage

Describes the root volume for a WorkSpace bundle.

Type: [RootStorage](#) object

Required: No

Tags

The tags associated with the bundle.

Note

To add tags at the same time when you're creating the bundle, you must create an IAM policy that grants your IAM user permissions to use `workspaces:CreateTags`.

Type: Array of [Tag](#) objects

Required: No

[UserStorage](#)

Describes the user volume for a WorkSpace bundle.

Type: [UserStorage](#) object

Required: Yes

Response Syntax

```
{  
    "WorkspaceBundle": {  
        "BundleId": "string",  
        "BundleType": "string",  
        "ComputeType": {  
            "Name": "string"  
        },  
        "CreationTime": number,  
        "Description": "string",  
        "ImageId": "string",  
        "LastUpdatedTime": number,  
        "Name": "string",  
        "Owner": "string",  
        "RootStorage": {  
            "Capacity": "string"  
        },  
        "State": "string",  
        "UserStorage": {  
            "Capacity": "string"  
        }  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[WorkspaceBundle](#)

Describes a WorkSpace bundle.

Type: [WorkspaceBundle](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

ResourceUnavailableException

The specified resource is not available.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateWorkSpaceImage

Creates a new WorkSpace image from an existing WorkSpace.

Request Syntax

```
{  
    "Description": "string",  
    "Name": "string",  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ],  
    "WorkspaceId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

Description

The description of the new WorkSpace image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^[a-zA-Z0-9_./() -]+\$

Required: Yes

Name

The name of the new WorkSpace image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[a-zA-Z0-9_./()\\-]+\$

Required: Yes

Tags

The tags that you want to add to the new WorkSpace image. To add tags when you're creating the image, you must create an IAM policy that grants your IAM user permission to use `workspaces:CreateTags`.

Type: Array of [Tag](#) objects

Required: No

WorkspaceId

The identifier of the source WorkSpace

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: Yes

Response Syntax

```
{  
    "Created": number,  
    "Description": "string",  
    "ImageId": "string",  
    "Name": "string",  
    "OperatingSystem": {  
        "Type": "string"  
    },  
    "OwnerAccountId": "string",  
    "RequiredTenancy": "string",  
    "State": "string  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Created

The date when the image was created.

Type: Timestamp

Description

The description of the image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^[a-zA-Z0-9_./() -]+\$

ImageId

The identifier of the new WorkSpace image.

Type: String

Pattern: wsi-[0-9a-z]{9,63}\$

Name

The name of the image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[a-zA-Z0-9_./()\\-]+\$

OperatingSystem

The operating system that the image is running.

Type: [OperatingSystem](#) object

OwnerAccountId

The identifier of the Amazon account that owns the image.

Type: String

Pattern: ^\d{12}\$

RequiredTenancy

Specifies whether the image is running on dedicated hardware. When Bring Your Own License (BYOL) is enabled, this value is set to DEDICATED. For more information, see [Bring Your Own Windows Desktop Images..](#)

Type: String

Valid Values: DEFAULT | DEDICATED

State

The availability status of the image.

Type: String

Valid Values: AVAILABLE | PENDING | ERROR

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

CreateWorkspaces

Creates one or more WorkSpaces.

This operation is asynchronous and returns before the WorkSpaces are created.

Note

- The MANUAL running mode value is only supported by Amazon WorkSpaces Core. Contact your account team to be allow-listed to use this value. For more information, see [Amazon WorkSpaces Core](#).
- You don't need to specify the PCOIP protocol for Linux bundles because WSP is the default protocol for those bundles.
- User-decoupled WorkSpaces are only supported by Amazon WorkSpaces Core.

Request Syntax

```
{  
    "Workspaces": [  
        {  
            "BundleId": "string",  
            "DirectoryId": "string",  
            "RootVolumeEncryptionEnabled": boolean,  
            "Tags": [  
                {  
                    "Key": "string",  
                    "Value": "string"  
                }  
            ],  
            "UserName": "string",  
            "UserVolumeEncryptionEnabled": boolean,  
            "VolumeEncryptionKey": "string",  
            "WorkspaceName": "string",  
            "WorkspaceProperties": {  
                "ComputeTypeName": "string",  
                "OperatingSystemName": "string",  
                "Protocols": [ "string" ],  
                "RootVolumeSizeGib": number,  
                "RunningMode": "string",  
                "StorageType": "string",  
                "VolumeEncryptionKey": "string"  
            }  
        }  
    ]  
}
```

```
        "RunningModeAutoStopTimeoutInMinutes": number,
        "UserVolumeSizeGiB": number
    }
}
]
}
```

Request Parameters

The request accepts the following data in JSON format.

Workspaces

The WorkSpaces to create. You can specify up to 25 WorkSpaces.

Type: Array of [WorkspaceRequest](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Required: Yes

Response Syntax

```
{
    "FailedRequestsErrorCodestring",
            "ErrorMessagestring",
            "WorkspaceRequestBundleIdstring",
                "DirectoryIdstring",
                "RootVolumeEncryptionEnabledboolean,
                "TagsKeystring",
                        "Valuestring"
                    }
                ],
                "UserNamestring",
                "UserVolumeEncryptionEnabledboolean,
                "VolumeEncryptionKeystring",
                "WorkspaceNamestring",
                "WorkspaceProperties
```

```
        "ComputeTypeName": "string",
        "OperatingSystemName": "string",
        "Protocols": [ "string" ],
        "RootVolumeSizeGib": number,
        "RunningMode": "string",
        "RunningModeAutoStopTimeoutInMinutes": number,
        "UserVolumeSizeGib": number
    }
}
],
"PendingRequests": [
{
    "BundleId": "string",
    "ComputerName": "string",
    "DataReplicationSettings": {
        "DataReplication": "string",
        "RecoverySnapshotTime": number
    },
    "DirectoryId": "string",
    "ErrorCode": "string",
    "ErrorMessage": "string",
    "IpAddress": "string",
    "ModificationStates": [
        {
            "Resource": "string",
            "State": "string"
        }
    ],
    "RelatedWorkspaces": [
    {
        "Region": "string",
        "State": "string",
        "Type": "string",
        "WorkspaceId": "string"
    }
    ],
    "RootVolumeEncryptionEnabled": boolean,
    "StandbyWorkspacesProperties": [
    {
        "DataReplication": "string",
        "RecoverySnapshotTime": number,
        "StandbyWorkspaceId": "string"
    }
]
```

```
],
  "State": "string",
  "SubnetId": "string",
  "UserName": "string",
  "UserVolumeEncryptionEnabled": boolean,
  "VolumeEncryptionKey": "string",
  "WorkspaceId": "string",
  "WorkspaceName": "string",
  "WorkspaceProperties": {
    "ComputeTypeName": "string",
    "OperatingSystemName": "string",
    "Protocols": [ "string" ],
    "RootVolumeSizeGiB": number,
    "RunningMode": "string",
    "RunningModeAutoStopTimeoutInMinutes": number,
    "UserVolumeSizeGiB": number
  }
}
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[FailedRequests](#)

Information about the WorkSpaces that could not be created.

Type: Array of [FailedCreateWorkspaceRequest](#) objects

[PendingRequests](#)

Information about the WorkSpaces that were created.

Because this operation is asynchronous, the identifier returned is not immediately available for use with other operations. For example, if you call [DescribeWorkspaces](#) before the WorkSpace is created, the information returned can be incomplete.

Type: Array of [Workspace](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteClientBranding

Deletes customized client branding. Client branding allows you to customize your WorkSpace's client login portal. You can tailor your login portal company logo, the support email address, support link, link to reset password, and a custom message for users trying to sign in.

After you delete your customized client branding, your login portal reverts to the default client branding.

Request Syntax

```
{  
    "Platforms": [ "string" ],  
    "ResourceId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

Platforms

The device type for which you want to delete client branding.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 6 items.

Valid Values: DeviceTypeWindows | DeviceTypeOsx | DeviceTypeAndroid | DeviceTypeIos | DeviceTypeLinux | DeviceTypeWeb

Required: Yes

ResourceId

The directory identifier of the WorkSpace for which you want to delete client branding.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)

- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteConnectClientAddIn

Deletes a client-add-in for Amazon Connect that is configured within a directory.

Request Syntax

```
{  
    "AddInId": "string",  
    "ResourceId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

AddInId

The identifier of the client add-in to delete.

Type: String

Length Constraints: Fixed length of 36.

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: Yes

ResourceId

The directory identifier for which the client add-in is configured.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteConnectionAlias

Deletes the specified connection alias. For more information, see [Cross-Region Redirection for Amazon WorkSpaces](#).

Important

If you will no longer be using a fully qualified domain name (FQDN) as the registration code for your WorkSpaces users, you must take certain precautions to prevent potential security issues. For more information, see [Security Considerations if You Stop Using Cross-Region Redirection](#).

Note

To delete a connection alias that has been shared, the shared account must first disassociate the connection alias from any directories it has been associated with. Then you must unshare the connection alias from the account it has been shared with. You can delete a connection alias only after it is no longer shared with any accounts or associated with any directories.

Request Syntax

```
{  
    "AliasId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

AliasId

The identifier of the connection alias to delete.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 68.

Pattern: ^wsca-[0-9a-z]{8,63}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceAssociatedException

The resource is associated with a directory.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteIpGroup

Deletes the specified IP access control group.

You cannot delete an IP access control group that is associated with a directory.

Request Syntax

```
{  
    "GroupId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

GroupId

The identifier of the IP access control group.

Type: String

Pattern: wsipg-[0-9a-z]{8,63}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceAssociatedException

The resource is associated with a directory.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteTags

Deletes the specified tags from the specified WorkSpaces resource.

Request Syntax

```
{  
    "ResourceId": "string",  
    "TagKeys": [ "string" ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

ResourceId

The identifier of the WorkSpaces resource. The supported resource types are WorkSpaces, registered directories, images, custom bundles, IP access control groups, and connection aliases.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

TagKeys

The tag keys.

Type: Array of strings

Length Constraints: Minimum length of 1.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteWorkspaceBundle

Deletes the specified WorkSpace bundle. For more information about deleting WorkSpace bundles, see [Delete a Custom WorkSpaces Bundle or Image](#).

Request Syntax

```
{  
    "BundleId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

BundleId

The identifier of the bundle.

Type: String

Pattern: ^wsb-[0-9a-z]{8,63}\$

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceAssociatedException

The resource is associated with a directory.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeleteWorkspaceImage

Deletes the specified image from your account. To delete an image, you must first delete any bundles that are associated with the image and unshare the image if it is shared with other accounts.

Request Syntax

```
{  
    "ImageId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

ImageId

The identifier of the image.

Type: String

Pattern: wsi-[0-9a-z]{9,63}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

ResourceAssociatedException

The resource is associated with a directory.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeployWorkspaceApplications

Deploys associated applications to the specified WorkSpace

Request Syntax

```
{  
    "Force": boolean,  
    "WorkspaceId": string  
}
```

Request Parameters

The request accepts the following data in JSON format.

Force

Indicates whether the force flag is applied for the specified WorkSpace. When the force flag is enabled, it allows previously failed deployments to be retried.

Type: Boolean

Required: No

WorkspaceId

The identifier of the WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: Yes

Response Syntax

```
{  
    "Deployment": {  
        "Associations": [  
            {
```

```
"AssociatedResourceId": "string",
"AssociatedResourceType": "string",
"Created": number,
"LastUpdatedTime": number,
"State": "string",
"StateReason": {
    "ErrorCode": "string",
    "ErrorMessage": "string"
},
"WorkspaceId": "string"
}
]
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Deployment

The list of deployed associations and information about them.

Type: [WorkSpaceApplicationDeployment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

IncompatibleApplicationsException

The specified application is not compatible with the resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceInUseException

The specified resource is currently in use.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DeregisterWorkspaceDirectory

Deregisters the specified directory. This operation is asynchronous and returns before the WorkSpace directory is deregistered. If any WorkSpaces are registered to this directory, you must remove them before you can deregister the directory.

Note

Simple AD and AD Connector are made available to you free of charge to use with WorkSpaces. If there are no WorkSpaces being used with your Simple AD or AD Connector directory for 30 consecutive days, this directory will be automatically deregistered for use with Amazon WorkSpaces, and you will be charged for this directory as per the [Amazon Directory Service pricing terms](#).

To delete empty directories, see [Delete the Directory for Your WorkSpaces](#). If you delete your Simple AD or AD Connector directory, you can always create a new one when you want to start using WorkSpaces again.

Request Syntax

```
{  
    "DirectoryId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

DirectoryId

The identifier of the directory. If any WorkSpaces are registered to this directory, you must remove them before you deregister the directory, or you will receive an OperationNotSupportedException error.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeAccount

Retrieves a list that describes the configuration of Bring Your Own License (BYOL) for the specified account.

Response Syntax

```
{  
    "DedicatedTenancyManagementCidrRange": "string",  
    "DedicatedTenancySupport": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[**DedicatedTenancyManagementCidrRange**](#)

The IP address range, specified as an IPv4 CIDR block, used for the management network interface.

The management network interface is connected to a secure Amazon WorkSpaces management network. It is used for interactive streaming of the WorkSpace desktop to Amazon WorkSpaces clients, and to allow Amazon WorkSpaces to manage the WorkSpace.

Type: String

Pattern: (^([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])\.([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])\.\.0\.(\\/(16\$))\$

[**DedicatedTenancySupport**](#)

The status of BYOL (whether BYOL is enabled or disabled).

Type: String

Valid Values: ENABLED | DISABLED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeAccountModifications

Retrieves a list that describes modifications to the configuration of Bring Your Own License (BYOL) for the specified account.

Request Syntax

```
{  
    "NextToken": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

NextToken

If you received a NextToken from a previous call that was paginated, provide this token to receive the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Response Syntax

```
{  
    "AccountModifications": [  
        {  
            "DedicatedTenancyManagementCidrRange": "string",  
            "DedicatedTenancySupport": "string",  
            "ErrorCode": "string",  
            "ErrorMessage": "string",  
            "ModificationState": "string",  
            "StartTime": number  
        }  
    ],  
    "NextToken": "string"
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AccountModifications](#)

The list of modifications to the configuration of BYOL.

Type: Array of [AccountModification](#) objects

[NextToken](#)

The token to use to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeApplicationAssociations

Describes the associations between the application and the specified associated resources.

Request Syntax

```
{  
    "ApplicationId": "string",  
    "AssociatedResourceTypes": [ "string" ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

[ApplicationId](#)

The identifier of the specified application.

Type: String

Pattern: ^wsa-[0-9a-z]{8,63}\$

Required: Yes

[AssociatedResourceTypes](#)

The resource type of the associated resources.

Type: Array of strings

Valid Values: WORKSPACE | BUNDLE | IMAGE

Required: Yes

[MaxResults](#)

The maximum number of associations to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

NextToken

If you received a NextToken from a previous call that was paginated, provide this token to receive the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Response Syntax

```
{  
    "Associations": [  
        {  
            "ApplicationId": "string",  
            "AssociatedResourceId": "string",  
            "AssociatedResourceType": "string",  
            "Created": number,  
            "LastUpdatedTime": number,  
            "State": "string",  
            "StateReason": {  
                "ErrorCode": "string",  
                "ErrorMessage": "string"  
            }  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Associations

List of associations and information about them.

Type: Array of [ApplicationResourceAssociation](#) objects

NextToken

If you received a NextToken from a previous call that was paginated, provide this token to receive the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeApplications

Describes the specified applications by filtering based on their compute types, license availability, operating systems, and owners.

Request Syntax

```
{  
    "ApplicationIds": [ "string" ],  
    "ComputeTypeNames": [ "string" ],  
    "LicenseType": "string",  
    "MaxResults": number,  
    "NextToken": "string",  
    "OperatingSystemNames": [ "string" ],  
    "Owner": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationIds

The identifiers of one or more applications.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Pattern: ^wsa-[0-9a-z]{8,63}\$

Required: No

ComputeTypeNames

The compute types supported by the applications.

Type: Array of strings

Valid Values: VALUE | STANDARD | PERFORMANCE | POWER | GRAPHICS | POWERPRO | GRAPHICSPRO | GRAPHICS_G4DN | GRAPHICSPRO_G4DN

Required: No

[LicenseType](#)

The license availability for the applications.

Type: String

Valid Values: LICENSED | UNLICENSED

Required: No

[MaxResults](#)

The maximum number of applications to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

[NextToken](#)

If you received a NextToken from a previous call that was paginated, provide this token to receive the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

[OperatingSystemNames](#)

The operating systems supported by the applications.

Type: Array of strings

Valid Values: AMAZON_LINUX_2 | UBUNTU_18_04 | UBUNTU_20_04 | UBUNTU_22_04 | UNKNOWN | WINDOWS_10 | WINDOWS_11 | WINDOWS_7 | WINDOWS_SERVER_2016 | WINDOWS_SERVER_2019 | WINDOWS_SERVER_2022

Required: No

[Owner](#)

The owner of the applications.

Type: String

Pattern: ^\d{12}|AMAZON\$

Required: No

Response Syntax

```
{  
    "Applications": [  
        {  
            "ApplicationId": "string",  
            "Created": number,  
            "Description": "string",  
            "LicenseType": "string",  
            "Name": "string",  
            "Owner": "string",  
            "State": "string",  
            "SupportedComputeTypeNames": [ "string" ],  
            "SupportedOperatingSystemNames": [ "string" ]  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Applications](#)

List of information about the specified applications.

Type: Array of [WorkSpaceApplication](#) objects

[NextToken](#)

If you received a NextToken from a previous call that was paginated, provide this token to receive the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeBundleAssociations

Describes the associations between the applications and the specified bundle.

Request Syntax

```
{  
    "AssociatedResourceTypes": [ "string" ],  
    "BundleId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

AssociatedResourceTypes

The resource types of the associated resource.

Type: Array of strings

Valid Values: APPLICATION

Required: Yes

BundleId

The identifier of the bundle.

Type: String

Pattern: ^wsb-[0-9a-z]{8,63}\$

Required: Yes

Response Syntax

```
{  
    "Associations": [  
        {  
            "AssociatedResourceId": "string",  
            "AssociatedResourceType": "string",  
            "BundleId": "string",  
            "LastModified": "string",  
            "Status": "string"  
        }  
    ]  
}
```

```
"AssociatedResourceType": "string",
"BundleId": "string",
"Created": number,
"LastUpdatedTime": number,
"State": "string",
"StateReason": {
    "ErrorCode": "string",
    "ErrorMessage": "string"
}
}
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Associations

List of information about the specified associations.

Type: Array of [BundleResourceAssociation](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeClientBranding

Describes the specified client branding. Client branding allows you to customize the log in page of various device types for your users. You can add your company logo, the support email address, support link, link to reset password, and a custom message for users trying to sign in.

Note

Only device types that have branding information configured will be shown in the response.

Request Syntax

```
{  
    "ResourceId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

ResourceId

The directory identifier of the WorkSpace for which you want to view client branding information.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: Yes

Response Syntax

```
{  
    "DeviceTypeAndroid": {  
        "ForgotPasswordLink": "string",  
    },  
}
```

```
"LoginMessage": {  
    "string" : "string"  
},  
"LogoUrl": "string",  
"SupportEmail": "string",  
"SupportLink": "string"  
},  
"DeviceTypeIos": {  
    "ForgotPasswordLink": "string",  
    "LoginMessage": {  
        "string" : "string"  
    },  
    "Logo2xUrl": "string",  
    "Logo3xUrl": "string",  
    "LogoUrl": "string",  
    "SupportEmail": "string",  
    "SupportLink": "string"  
},  
"DeviceTypeLinux": {  
    "ForgotPasswordLink": "string",  
    "LoginMessage": {  
        "string" : "string"  
    },  
    "LogoUrl": "string",  
    "SupportEmail": "string",  
    "SupportLink": "string"  
},  
"DeviceTypeOsx": {  
    "ForgotPasswordLink": "string",  
    "LoginMessage": {  
        "string" : "string"  
    },  
    "LogoUrl": "string",  
    "SupportEmail": "string",  
    "SupportLink": "string"  
},  
"DeviceTypeWeb": {  
    "ForgotPasswordLink": "string",  
    "LoginMessage": {  
        "string" : "string"  
    },  
    "LogoUrl": "string",  
    "SupportEmail": "string",  
    "SupportLink": "string"  
}
```

```
 },
"DeviceTypeWindows": {
    "ForgotPasswordLink": "string",
    "LoginMessage": {
        "string" : "string"
    },
    "LogoUrl": "string",
    "SupportEmail": "string",
    "SupportLink": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[DeviceTypeAndroid](#)

The branding information for Android devices.

Type: [DefaultClientBrandingAttributes](#) object

[DeviceTypeIos](#)

The branding information for iOS devices.

Type: [IosClientBrandingAttributes](#) object

[DeviceTypeLinux](#)

The branding information for Linux devices.

Type: [DefaultClientBrandingAttributes](#) object

[DeviceTypeOsx](#)

The branding information for macOS devices.

Type: [DefaultClientBrandingAttributes](#) object

[DeviceTypeWeb](#)

The branding information for Web access.

Type: [DefaultClientBrandingAttributes](#) object

[DeviceTypeWindows](#)

The branding information for Windows devices.

Type: [DefaultClientBrandingAttributes](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeClientProperties

Retrieves a list that describes one or more specified Amazon WorkSpaces clients.

Request Syntax

```
{  
    "ResourceIds": [ "string" ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

ResourceIds

The resource identifier, in the form of directory IDs.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Length Constraints: Minimum length of 1.

Required: Yes

Response Syntax

```
{  
    "ClientPropertiesList": [  
        {  
            "ClientProperties": {  
                "LogUploadEnabled": "string",  
                "ReconnectEnabled": "string"  
            },  
            "ResourceId": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ClientPropertiesList](#)

Information about the specified Amazon WorkSpaces clients.

Type: Array of [ClientPropertiesResult](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)

- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeConnectClientAddIns

Retrieves a list of Amazon Connect client add-ins that have been created.

Request Syntax

```
{  
    "MaxResults": number,  
    "NextToken": "string",  
    "ResourceId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

MaxResults

The maximum number of items to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

NextToken

If you received a NextToken from a previous call that was paginated, provide this token to receive the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

ResourceId

The directory identifier for which the client add-in is configured.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: Yes

Response Syntax

```
{  
    "AddIns": [  
        {  
            "AddInId": "string",  
            "Name": "string",  
            "ResourceId": "string",  
            "URL": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AddIns

Information about client add-ins.

Type: Array of [ConnectClientAddIn](#) objects

NextToken

The token to use to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeConnectionAliases

Retrieves a list that describes the connection aliases used for cross-Region redirection. For more information, see [Cross-Region Redirection for Amazon WorkSpaces](#).

Request Syntax

```
{  
    "AliasIds": [ "string" ],  
    "Limit": number,  
    "NextToken": "string",  
    "ResourceId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

[AliasIds](#)

The identifiers of the connection aliases to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Length Constraints: Minimum length of 13. Maximum length of 68.

Pattern: ^wsca-[0-9a-z]{8,63}\$

Required: No

[Limit](#)

The maximum number of connection aliases to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

NextToken

If you received a NextToken from a previous call that was paginated, provide this token to receive the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

ResourceId

The identifier of the directory associated with the connection alias.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{  
    "ConnectionAliases": [  
        {  
            "AliasId": "string",  
            "Associations": [  
                {  
                    "AssociatedAccountId": "string",  
                    "AssociationStatus": "string",  
                    "ConnectionIdentifier": "string",  
                    "ResourceId": "string"  
                }  
            ],  
            "ConnectionString": "string",  
            "OwnerAccountId": "string",  
            "State": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ConnectionAliases](#)

Information about the specified connection aliases.

Type: Array of [ConnectionAlias](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

[NextToken](#)

The token to use to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeConnectionAliasPermissions

Describes the permissions that the owner of a connection alias has granted to another Amazon Web Services account for the specified connection alias. For more information, see [Cross-Region Redirection for Amazon WorkSpaces](#).

Request Syntax

```
{  
    "AliasId": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

[AliasId](#)

The identifier of the connection alias.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 68.

Pattern: ^wsca-[0-9a-z]{8,63}\$

Required: Yes

[MaxResults](#)

The maximum number of results to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

[NextToken](#)

If you received a NextToken from a previous call that was paginated, provide this token to receive the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Response Syntax

```
{  
    "AliasId": "string",  
    "ConnectionAliasPermissions": [  
        {  
            "AllowAssociation": boolean,  
            "SharedAccountId": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AliasId](#)

The identifier of the connection alias.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 68.

Pattern: ^wsca-[0-9a-z]{8,63}\$

[ConnectionAliasPermissions](#)

The permissions associated with a connection alias.

Type: Array of [ConnectionAliasPermission](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

NextToken

The token to use to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeImageAssociations

Describes the associations between the applications and the specified image.

Request Syntax

```
{  
    "AssociatedResourceTypes": [ "string" ],  
    "ImageId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

AssociatedResourceTypes

The resource types of the associated resource.

Type: Array of strings

Valid Values: APPLICATION

Required: Yes

ImageId

The identifier of the image.

Type: String

Pattern: wsi-[0-9a-z]{9,63}\$

Required: Yes

Response Syntax

```
{  
  "Associations": [  
    {  
      "AssociatedResourceId": "string",
```

```
"AssociatedResourceType": "string",
"CreatedImageId": "string",
"LastUpdatedTime": "number",
"State": "string",
"StateReason": {
    "ErrorCode": "string",
    "ErrorMessage": "string"
}
}
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Associations

List of information about the specified associations.

Type: Array of [ImageResourceAssociation](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeIpGroups

Describes one or more of your IP access control groups.

Request Syntax

```
{  
    "GroupIds": [ "string" ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

GroupIds

The identifiers of one or more IP access control groups.

Type: Array of strings

Pattern: wsipg-[0-9a-z]{8,63}\$

Required: No

MaxResults

The maximum number of items to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

NextToken

If you received a NextToken from a previous call that was paginated, provide this token to receive the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "Result": [  
        {  
            "groupDesc": "string",  
            "groupId": "string",  
            "groupName": "string",  
            "userRules": [  
                {  
                    "ipRule": "string",  
                    "ruleDesc": "string"  
                }  
            ]  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Result

Information about the IP access control groups.

Type: Array of [WorkspacesIpGroup](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeTags

Describes the specified tags for the specified WorkSpaces resource.

Request Syntax

```
{  
    "ResourceId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

ResourceId

The identifier of the WorkSpaces resource. The supported resource types are WorkSpaces, registered directories, images, custom bundles, IP access control groups, and connection aliases.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Response Syntax

```
{  
    "TagList": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

TagList

The tags.

Type: Array of [Tag](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeWorkspaceAssociations

Describes the associations between applications and the specified WorkSpace.

Request Syntax

```
{  
    "AssociatedResourceTypes": [ "string" ],  
    "WorkspaceId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

AssociatedResourceTypes

The resource types of the associated resources.

Type: Array of strings

Valid Values: APPLICATION

Required: Yes

WorkspaceId

The identifier of the WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: Yes

Response Syntax

```
{  
    "Associations": [  
        {  
            "AssociatedResourceId": "string",  
            "ApplicationId": "string",  
            "LastSyncTime": "string",  
            "SyncStatus": "string"  
        }  
    ]  
}
```

```
"AssociatedResourceType": "string",
"CreatedLastUpdatedTime": "number",
"State": "string",
"StateReason": {
    "ErrorCode": "string",
    "ErrorMessage": "string"
},
"WorkspaceId": "string"
}
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Associations

List of information about the specified associations.

Type: Array of [WorkspaceResourceAssociation](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeWorkspaceBundles

Retrieves a list that describes the available WorkSpace bundles.

You can filter the results using either bundle ID or owner, but not both.

Request Syntax

```
{  
    "BundleIds": [ "string" ],  
    "NextToken": "string",  
    "Owner": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

BundleIds

The identifiers of the bundles. You cannot combine this parameter with any other filter.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Pattern: ^wsb-[0-9a-z]{8,63}\$

Required: No

NextToken

The token for the next set of results. (You received this token from a previous call.)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Owner

The owner of the bundles. You cannot combine this parameter with any other filter.

To describe the bundles provided by Amazon, specify AMAZON. To describe the bundles that belong to your account, don't specify a value.

Type: String

Required: No

Response Syntax

```
{  
    "Bundles": [  
        {  
            "BundleId": "string",  
            "BundleType": "string",  
            "ComputeType": {  
                "Name": "string"  
            },  
            "CreationTime": number,  
            "Description": "string",  
            "ImageId": "string",  
            "LastUpdatedTime": number,  
            "Name": "string",  
            "Owner": "string",  
            "RootStorage": {  
                "Capacity": "string"  
            },  
            "State": "string",  
            "UserStorage": {  
                "Capacity": "string"  
            }  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Bundles

Information about the bundles.

Type: Array of [WorkspaceBundle](#) objects

NextToken

The token to use to retrieve the next page of results. This value is null when there are no more results to return. This token is valid for one day and must be used within that time frame.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

DescribeWorkspaceDirectories

Describes the available directories that are registered with Amazon WorkSpaces.

Request Syntax

```
{  
    "DirectoryIds": [ "string" ],  
    "Limit": number,  
    "NextToken": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

DirectoryIds

The identifiers of the directories. If the value is null, all directories are retrieved.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: No

Limit

The maximum number of directories to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

NextToken

If you received a NextToken from a previous call that was paginated, provide this token to receive the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Response Syntax

```
{  
    "Directories": [  
        {  
            "Alias": "string",  
            "CertificateBasedAuthProperties": {  
                "CertificateAuthorityArn": "string",  
                "Status": "string"  
            },  
            "CustomerUserName": "string",  
            "DirectoryId": "string",  
            "DirectoryName": "string",  
            "DirectoryType": "string",  
            "DnsIpAddresses": [ "string" ],  
            "IamRoleId": "string",  
            "ipGroupIds": [ "string" ],  
            "RegistrationCode": "string",  
            "SamlProperties": {  
                "RelayStateParameterName": "string",  
                "Status": "string",  
                "UserAccessUrl": "string"  
            },  
            "SelfservicePermissions": {  
                "ChangeComputeType": "string",  
                "IncreaseVolumeSize": "string",  
                "RebuildWorkspace": "string",  
                "RestartWorkspace": "string",  
                "SwitchRunningMode": "string"  
            },  
            "State": "string",  
            "SubnetIds": [ "string" ],  
            "Tenancy": "string",  
            "WorkspaceAccessProperties": {  
                "DeviceTypeAndroid": "string",  
                "DeviceTypeChromeOs": "string",  
                "DeviceTypeIos": "string",  
            }  
        }  
    ]  
}
```

```
        "DeviceTypeLinux": "string",
        "DeviceTypeOsx": "string",
        "DeviceTypeWeb": "string",
        "DeviceTypeWindows": "string",
        "DeviceTypeZeroClient": "string"
    },
    "WorkspaceCreationProperties": {
        "CustomSecurityGroupId": "string",
        "DefaultOu": "string",
        "EnableInternetAccess": boolean,
        "EnableMaintenanceMode": boolean,
        "EnableWorkDocs": boolean,
        "UserEnabledAsLocalAdministrator": boolean
    },
    "WorkspaceSecurityGroupId": "string"
}
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Directories

Information about the directories.

Type: Array of [WorkspaceDirectory](#) objects

NextToken

The token to use to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeWorkspaceImagePermissions

Describes the permissions that the owner of an image has granted to other Amazon Web Services accounts for an image.

Request Syntax

```
{  
    "ImageId": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

ImageId

The identifier of the image.

Type: String

Pattern: wsi-[0-9a-z]{9,63}\$

Required: Yes

MaxResults

The maximum number of items to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

NextToken

If you received a NextToken from a previous call that was paginated, provide this token to receive the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Response Syntax

```
{  
    "ImageId": "string",  
    "ImagePermissions": [  
        {  
            "SharedAccountId": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ImageId

The identifier of the image.

Type: String

Pattern: wsi-[0-9a-z]{9,63}\$

ImagePermissions

The identifiers of the Amazon Web Services accounts that the image has been shared with.

Type: Array of [ImagePermission](#) objects

NextToken

The token to use to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeWorkspaceImages

Retrieves a list that describes one or more specified images, if the image identifiers are provided. Otherwise, all images in the account are described.

Request Syntax

```
{  
    "ImageIds": [ "string" ],  
    "ImageType": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

ImageIds

The identifier of the image.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Pattern: wsi-[0-9a-z]{9,63}\$

Required: No

ImageType

The type (owned or shared) of the image.

Type: String

Valid Values: OWNED | SHARED

Required: No

MaxResults

The maximum number of items to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

NextToken

If you received a NextToken from a previous call that was paginated, provide this token to receive the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Response Syntax

```
{  
    "Images": [  
        {  
            "Created": number,  
            "Description": "string",  
            "ErrorCode": "string",  
            "ErrorDetails": [  
                {  
                    "ErrorCode": "string",  
                    "ErrorMessage": "string"  
                }  
            ],  
            "ErrorMessage": "string",  
            "ImageId": "string",  
            "Name": "string",  
            "OperatingSystem": {  
                "Type": "string"  
            },  
            "OwnerAccountId": "string",  
            "RequiredTenancy": "string",  
            "State": "string",  
            "Updates": {  
                "Description": "string",  
                "UpdateAvailable": boolean  
            }  
        }  
    ]  
}
```

```
        }
    ],
    "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Images

Information about the images.

Type: Array of [WorkSpaceImage](#) objects

NextToken

The token to use to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeWorkspaces

Describes the specified WorkSpaces.

You can filter the results by using the bundle identifier, directory identifier, or owner, but you can specify only one filter at a time.

Request Syntax

```
{  
    "BundleId": "string",  
    "DirectoryId": "string",  
    "Limit": number,  
    "NextToken": "string",  
    "UserName": "string",  
    "WorkspaceIds": [ "string" ],  
    "WorkspaceName": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

BundleId

The identifier of the bundle. All WorkSpaces that are created from this bundle are retrieved. You cannot combine this parameter with any other filter.

Type: String

Pattern: ^wsb-[0-9a-z]{8,63}\$

Required: No

DirectoryId

The identifier of the directory. In addition, you can optionally specify a specific directory user (see `UserName`). You cannot combine this parameter with any other filter.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: No

Limit

The maximum number of items to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

NextToken

If you received a NextToken from a previous call that was paginated, provide this token to receive the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

UserName

The name of the directory user. You must specify this parameter with DirectoryId.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Required: No

WorkspacesIds

The identifiers of the WorkSpaces. You cannot combine this parameter with any other filter.

Because the [CreateWorkspaces](#) operation is asynchronous, the identifier it returns is not immediately available. If you immediately call [DescribeWorkspaces](#) with this identifier, no information is returned.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: No

WorkspaceName

The name of the user-decoupled WorkSpace.

Type: String

Pattern: ^[a-zA-Z0-9_()][a-zA-Z0-9_.()]{1,63}\$

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "Workspaces": [  
        {  
            "BundleId": "string",  
            "ComputerName": "string",  
            "DataReplicationSettings": {  
                "DataReplication": "string",  
                "RecoverySnapshotTime": number  
            },  
            "DirectoryId": "string",  
            "ErrorCode": "string",  
            "ErrorMessage": "string",  
            "IpAddress": "string",  
            "ModificationStates": [  
                {  
                    "Resource": "string",  
                    "State": "string"  
                }  
            ],  
            "RelatedWorkspaces": [  
                {  
                    "Region": "string",  
                    "State": "string",  
                    "Type": "string",  
                    "WorkspaceId": "string"  
                }  
            ]  
        }  
    ]  
}
```

```
],
  "RootVolumeEncryptionEnabled": boolean,
  "StandbyWorkspacesProperties": [
    {
      "DataReplication": "string",
      "RecoverySnapshotTime": number,
      "StandbyWorkspaceId": "string"
    }
  ],
  "State": "string",
  "SubnetId": "string",
  "UserName": "string",
  "UserVolumeEncryptionEnabled": boolean,
  "VolumeEncryptionKey": "string",
  "WorkspaceId": "string",
  "WorkspaceName": "string",
  "WorkspaceProperties": {
    "ComputeTypeName": "string",
    "OperatingSystemName": "string",
    "Protocols": [ "string" ],
    "RootVolumeSizeGiB": number,
    "RunningMode": "string",
    "RunningModeAutoStopTimeoutInMinutes": number,
    "UserVolumeSizeGiB": number
  }
}
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken](#)

The token to use to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

[Workspaces](#)

Information about the WorkSpaces.

Because [CreateWorkspaces](#) is an asynchronous operation, some of the returned information could be incomplete.

Type: Array of [Workspace](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceUnavailableException

The specified resource is not available.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

DescribeWorkspacesConnectionStatus

Describes the connection status of the specified WorkSpaces.

Request Syntax

```
{  
    "NextToken": "string",  
    "WorkspaceIds": [ "string" ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

NextToken

If you received a NextToken from a previous call that was paginated, provide this token to receive the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

WorkspaceIds

The identifiers of the WorkSpaces. You can specify up to 25 WorkSpaces.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: No

Response Syntax

```
{
```

```
"NextToken": "string",  
"WorkspacesConnectionStatus": [  
    {  
        "ConnectionStatestring",  
        "ConnectionStateCheckTimestamp": number,  
        "LastKnownUserConnectionTimestamp": number,  
        "WorkspaceId": "string"  
    }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

WorkspacesConnectionStatus

Information about the connection status of the WorkSpace.

Type: Array of WorkspaceConnectionStatus objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DescribeWorkspaceSnapshots

Describes the snapshots for the specified WorkSpace.

Request Syntax

```
{  
    "WorkspaceId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

WorkspaceId

The identifier of the WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: Yes

Response Syntax

```
{  
    "RebuildSnapshots": [  
        {  
            "SnapshotTime": number  
        }  
    ],  
    "RestoreSnapshots": [  
        {  
            "SnapshotTime": number  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[RebuildSnapshots](#)

Information about the snapshots that can be used to rebuild a WorkSpace. These snapshots include the user volume.

Type: Array of [Snapshot](#) objects

[RestoreSnapshots](#)

Information about the snapshots that can be used to restore a WorkSpace. These snapshots include both the root volume and the user volume.

Type: Array of [Snapshot](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DisassociateConnectionAlias

Disassociates a connection alias from a directory. Disassociating a connection alias disables cross-Region redirection between two directories in different Regions. For more information, see [Cross-Region Redirection for Amazon WorkSpaces](#).

Note

Before performing this operation, call [DescribeConnectionAliases](#) to make sure that the current state of the connection alias is CREATED.

Request Syntax

```
{  
    "AliasId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

AliasId

The identifier of the connection alias to disassociate.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 68.

Pattern: ^wsca-[0-9a-z]{8,63}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

DisassociateIpGroups

Disassociates the specified IP access control group from the specified directory.

Request Syntax

```
{  
    "DirectoryId": "string",  
    "GroupIds": [ "string" ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

DirectoryId

The identifier of the directory.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: Yes

GroupIds

The identifiers of one or more IP access control groups.

Type: Array of strings

Pattern: wsipg-[0-9a-z]{8,63}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

DisassociateWorkspaceApplication

Disassociates the specified application from a WorkSpace.

Request Syntax

```
{  
    "ApplicationId": "string",  
    "WorkspaceId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

ApplicationId

The identifier of the application.

Type: String

Pattern: ^wsa-[0-9a-z]{8,63}\$

Required: Yes

Workspaceld

The identifier of the WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: Yes

Response Syntax

```
{  
    "Association": {  
        "AssociatedResourceId": "string",  
        "AssociatedResourceType": "string",  
    }  
}
```

```
"Created": number,  
"LastUpdatedTime": number,  
"State": "string",  
"StateReason": {  
    "ErrorCode": "string",  
    "ErrorMessage": "string"  
},  
"WorkspaceId": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Association

Information about the targeted association.

Type: [WorkspaceResourceAssociation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceInUseException

The specified resource is currently in use.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ImportClientBranding

Imports client branding. Client branding allows you to customize your WorkSpace's client login portal. You can tailor your login portal company logo, the support email address, support link, link to reset password, and a custom message for users trying to sign in.

After you import client branding, the default branding experience for the specified platform type is replaced with the imported experience

Note

- You must specify at least one platform type when importing client branding.
- You can import up to 6 MB of data with each request. If your request exceeds this limit, you can import client branding for different platform types using separate requests.
- In each platform type, the `SupportEmail` and `SupportLink` parameters are mutually exclusive. You can specify only one parameter for each platform type, but not both.
- Imported data can take up to a minute to appear in the WorkSpaces client.

Request Syntax

```
{  
    "DeviceTypeAndroid": {  
        "ForgotPasswordLink": "string",  
        "LoginMessage": {  
            "string" : "string"  
        },  
        "Logo": blob,  
        "SupportEmail": "string",  
        "SupportLink": "string"  
    },  
    "DeviceTypeIos": {  
        "ForgotPasswordLink": "string",  
        "LoginMessage": {  
            "string" : "string"  
        },  
        "Logo": blob,  
        "Logo2x": blob,  
        "Logo3x": blob,  
    }  
}
```

```
"SupportEmail": "string",
"SupportLink": "string"
},
"DeviceTypeLinux": {
  "ForgotPasswordLink": "string",
  "LoginMessage": {
    "string" : "string"
  },
  "Logo": blob,
  "SupportEmail": "string",
  "SupportLink": "string"
},
"DeviceTypeOsx": {
  "ForgotPasswordLink": "string",
  "LoginMessage": {
    "string" : "string"
  },
  "Logo": blob,
  "SupportEmail": "string",
  "SupportLink": "string"
},
"DeviceTypeWeb": {
  "ForgotPasswordLink": "string",
  "LoginMessage": {
    "string" : "string"
  },
  "Logo": blob,
  "SupportEmail": "string",
  "SupportLink": "string"
},
"DeviceTypeWindows": {
  "ForgotPasswordLink": "string",
  "LoginMessage": {
    "string" : "string"
  },
  "Logo": blob,
  "SupportEmail": "string",
  "SupportLink": "string"
},
"ResourceId": "string"
}
```

Request Parameters

The request accepts the following data in JSON format.

[DeviceTypeAndroid](#)

The branding information to import for Android devices.

Type: [DefaultImportClientBrandingAttributes](#) object

Required: No

[DeviceTypeIos](#)

The branding information to import for iOS devices.

Type: [IosImportClientBrandingAttributes](#) object

Required: No

[DeviceTypeLinux](#)

The branding information to import for Linux devices.

Type: [DefaultImportClientBrandingAttributes](#) object

Required: No

[DeviceTypeOsx](#)

The branding information to import for macOS devices.

Type: [DefaultImportClientBrandingAttributes](#) object

Required: No

[DeviceTypeWeb](#)

The branding information to import for web access.

Type: [DefaultImportClientBrandingAttributes](#) object

Required: No

[DeviceTypeWindows](#)

The branding information to import for Windows devices.

Type: [DefaultImportClientBrandingAttributes](#) object

Required: No

ResourceId

The directory identifier of the WorkSpace for which you want to import client branding.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: Yes

Response Syntax

```
{  
    "DeviceTypeAndroid": {  
        "ForgotPasswordLink": "string",  
        "LoginMessage": {  
            "string" : "string"  
        },  
        "LogoUrl": "string",  
        "SupportEmail": "string",  
        "SupportLink": "string"  
    },  
    "DeviceTypeIos": {  
        "ForgotPasswordLink": "string",  
        "LoginMessage": {  
            "string" : "string"  
        },  
        "Logo2xUrl": "string",  
        "Logo3xUrl": "string",  
        "LogoUrl": "string",  
        "SupportEmail": "string",  
        "SupportLink": "string"  
    },  
    "DeviceTypeLinux": {  
        "ForgotPasswordLink": "string",  
        "LoginMessage": {  
            "string" : "string"  
        }  
    }  
}
```

```
        },
        "LogoUrl": "string",
        "SupportEmail": "string",
        "SupportLink": "string"
    },
    "DeviceTypeOsx": {
        "ForgotPasswordLink": "string",
        "LoginMessage": {
            "string" : "string"
        },
        "LogoUrl": "string",
        "SupportEmail": "string",
        "SupportLink": "string"
    },
    "DeviceTypeWeb": {
        "ForgotPasswordLink": "string",
        "LoginMessage": {
            "string" : "string"
        },
        "LogoUrl": "string",
        "SupportEmail": "string",
        "SupportLink": "string"
    },
    "DeviceTypeWindows": {
        "ForgotPasswordLink": "string",
        "LoginMessage": {
            "string" : "string"
        },
        "LogoUrl": "string",
        "SupportEmail": "string",
        "SupportLink": "string"
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[DeviceTypeAndroid](#)

The branding information configured for Android devices.

Type: [DefaultClientBrandingAttributes](#) object

[DeviceTypeIos](#)

The branding information configured for iOS devices.

Type: [IosClientBrandingAttributes](#) object

[DeviceTypeLinux](#)

The branding information configured for Linux devices.

Type: [DefaultClientBrandingAttributes](#) object

[DeviceTypeOsx](#)

The branding information configured for macOS devices.

Type: [DefaultClientBrandingAttributes](#) object

[DeviceTypeWeb](#)

The branding information configured for web access.

Type: [DefaultClientBrandingAttributes](#) object

[DeviceTypeWindows](#)

The branding information configured for Windows devices.

Type: [DefaultClientBrandingAttributes](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceLimitExceeded**Exception**

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ImportWorkspacesImage

Imports the specified Windows 10 or 11 Bring Your Own License (BYOL) image into Amazon WorkSpaces. The image must be an already licensed Amazon EC2 image that is in your Amazon Web Services account, and you must own the image. For more information about creating BYOL images, see [Bring Your Own Windows Desktop Licenses](#).

Request Syntax

```
{  
    "Applications": [ "string" ],  
    "Ec2ImageId": "string",  
    "ImageDescription": "string",  
    "ImageName": "string",  
    "IngestionProcess": "string",  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

Applications

If specified, the version of Microsoft Office to subscribe to. Valid only for Windows 10 and 11 BYOL images. For more information about subscribing to Office for BYOL images, see [Bring Your Own Windows Desktop Licenses](#).

 **Note**

- Although this parameter is an array, only one item is allowed at this time.
- Windows 11 only supports Microsoft_Office_2019.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Valid Values: Microsoft_Office_2016 | Microsoft_Office_2019

Required: No

[Ec2ImageId](#)

The identifier of the EC2 image.

Type: String

Pattern: ^ami\-[a-f0-9]{8}|[a-f0-9]{17}\\$

Required: Yes

[ImageDescription](#)

The description of the WorkSpace image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^[a-zA-Z0-9_./() -]+\\$

Required: Yes

[ImageName](#)

The name of the WorkSpace image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[a-zA-Z0-9_./()\\"-]+\\$

Required: Yes

[IngestionProcess](#)

The ingestion process to be used when importing the image, depending on which protocol you want to use for your BYOL Workspace image, either PCoIP, WorkSpaces Streaming Protocol (WSP), or bring your own protocol (BYOP). To use WSP, specify a value that ends in _WSP. To

use PCoIP, specify a value that does not end in `_WSP`. To use BYOP, specify a value that ends in `_BYOP`.

For non-GPU-enabled bundles (bundles other than Graphics or GraphicsPro), specify `BYOL_REGULAR`, `BYOL_REGULAR_WSP`, or `BYOL_REGULAR_BYOP`, depending on the protocol.

 **Note**

The `BYOL_REGULAR_BYOP` and `BYOL_GRAPHICS_G4DN_BYOP` values are only supported by Amazon WorkSpaces Core. Contact your account team to be allow-listed to use these values. For more information, see [Amazon WorkSpaces Core](#).

Type: String

Valid Values: `BYOL_REGULAR` | `BYOL_GRAPHICS` | `BYOL_GRAPHICSPRO` |
`BYOL_GRAPHICS_G4DN` | `BYOL_REGULAR_WSP` | `BYOL_REGULAR_BYOP` |
`BYOL_GRAPHICS_G4DN_BYOP`

Required: Yes

Tags

The tags. Each WorkSpaces resource can have a maximum of 50 tags.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
{  
  "ImageId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ImageId

The identifier of the WorkSpace image.

Type: String

Pattern: wsi-[0-9a-z]{9,63}\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ListAvailableManagementCidrRanges

Retrieves a list of IP address ranges, specified as IPv4 CIDR blocks, that you can use for the network management interface when you enable Bring Your Own License (BYOL).

This operation can be run only by Amazon Web Services accounts that are enabled for BYOL. If your account isn't enabled for BYOL, you'll receive an `AccessDeniedException` error.

The management network interface is connected to a secure Amazon WorkSpaces management network. It is used for interactive streaming of the WorkSpace desktop to Amazon WorkSpaces clients, and to allow Amazon WorkSpaces to manage the WorkSpace.

Request Syntax

```
{  
    "ManagementCidrRangeConstraint": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

ManagementCidrRangeConstraint

The IP address range to search. Specify an IP address range that is compatible with your network and in CIDR notation (that is, specify the range as an IPv4 CIDR block).

Type: String

Pattern: ^(([0-9]|[1-9][0-9]|1[0-9]{2}|2[0-4][0-9]|25[0-5])\.){3}([0-9]| [1-9][0-9]|1[0-9]{2}|2[0-4][0-9]|25[0-5])(\/(3[0-2]|1[2-9]|0-9))\$

Required: Yes

MaxResults

The maximum number of items to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 5.

Required: No

NextToken

If you received a NextToken from a previous call that was paginated, provide this token to receive the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Response Syntax

```
{  
    "ManagementCidrRanges": [ "string" ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ManagementCidrRanges

The list of available IP address ranges, specified as IPv4 CIDR blocks.

Type: Array of strings

Pattern: (^([0-9]|1[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])\.([0-9]|1[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])\.\.0\.0)(\/(16\$))\$

NextToken

The token to use to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

MigrateWorkspace

Migrates a WorkSpace from one operating system or bundle type to another, while retaining the data on the user volume.

The migration process recreates the WorkSpace by using a new root volume from the target bundle image and the user volume from the last available snapshot of the original WorkSpace. During migration, the original D:\Users\%USERNAME% user profile folder is renamed to D:\Users\%USERNAME%MMddyyTHmmss%.NotMigrated. A new D:\Users\%USERNAME%\ folder is generated by the new OS. Certain files in the old user profile are moved to the new user profile.

For available migration scenarios, details about what happens during migration, and best practices, see [Migrate a WorkSpace](#).

Request Syntax

```
{  
    "BundleId": "string",  
    "SourceWorkspaceId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

BundleId

The identifier of the target bundle type to migrate the WorkSpace to.

Type: String

Pattern: ^wsb-[0-9a-z]{8,63}\$

Required: Yes

SourceWorkspaceId

The identifier of the WorkSpace to migrate from.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: Yes

Response Syntax

```
{  
  "SourceWorkspaceId": "string",  
  "TargetWorkspaceId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[SourceWorkspaceId](#)

The original identifier of the WorkSpace that is being migrated.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

[TargetWorkspaceId](#)

The new identifier of the WorkSpace that is being migrated. If the migration does not succeed, the target WorkSpace ID will not be used, and the WorkSpace will still have the original WorkSpace ID.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationInProgressException

The properties of this WorkSpace are currently being modified. Try again in a moment.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

ResourceUnavailableException

The specified resource is not available.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ModifyAccount

Modifies the configuration of Bring Your Own License (BYOL) for the specified account.

Request Syntax

```
{  
    "DedicatedTenancyManagementCidrRange": "string",  
    "DedicatedTenancySupport": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

DedicatedTenancyManagementCidrRange

The IP address range, specified as an IPv4 CIDR block, for the management network interface. Specify an IP address range that is compatible with your network and in CIDR notation (that is, specify the range as an IPv4 CIDR block). The CIDR block size must be /16 (for example, 203.0.113.25/16). It must also be specified as available by the `ListAvailableManagementCidrRanges` operation.

Type: String

Pattern: (^([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])\.([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])\.\.0\.(\\/(16\$))\$

Required: No

DedicatedTenancySupport

The status of BYOL.

Type: String

Valid Values: ENABLED

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

ResourceUnavailableException

The specified resource is not available.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)

- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ModifyCertificateBasedAuthProperties

Modifies the properties of the certificate-based authentication you want to use with your WorkSpaces.

Request Syntax

```
{  
    "CertificateBasedAuthProperties": {  
        "CertificateAuthorityArn": "string",  
        "Status": "string"  
    },  
    "PropertiesToDelete": [ "string" ],  
    "ResourceId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

CertificateBasedAuthProperties

The properties of the certificate-based authentication.

Type: [CertificateBasedAuthProperties](#) object

Required: No

PropertiesToDelete

The properties of the certificate-based authentication you want to delete.

Type: Array of strings

Valid Values: CERTIFICATE_BASED_AUTH_PROPERTIES_CERTIFICATE_AUTHORITY_ARN

Required: No

ResourceId

The resource identifiers, in the form of directory IDs.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ModifyClientProperties

Modifies the properties of the specified Amazon WorkSpaces clients.

Request Syntax

```
{  
    "ClientProperties": {  
        "LogUploadEnabled": "string",  
        "ReconnectEnabled": "string"  
    },  
    "ResourceId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

[ClientProperties](#)

Information about the Amazon WorkSpaces client.

Type: [ClientProperties](#) object

Required: Yes

[ResourceId](#)

The resource identifiers, in the form of directory IDs.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ModifySamlProperties

Modifies multiple properties related to SAML 2.0 authentication, including the enablement status, user access URL, and relay state parameter name that are used for configuring federation with an SAML 2.0 identity provider.

Request Syntax

```
{  
    "PropertiesToDelete": [ "string" ],  
    "ResourceId": "string",  
    "SamlProperties": {  
        "RelayStateParameterName": "string",  
        "Status": "string",  
        "UserAccessUrl": "string"  
    }  
}
```

Request Parameters

The request accepts the following data in JSON format.

PropertiesToDelete

The SAML properties to delete as part of your request.

Specify one of the following options:

- SAML_PROPERTIES_USER_ACCESS_URL to delete the user access URL.
- SAML_PROPERTIES_RELAY_STATE_PARAMETER_NAME to delete the relay state parameter name.

Type: Array of strings

Valid Values: SAML_PROPERTIES_USER_ACCESS_URL |
SAML_PROPERTIES_RELAY_STATE_PARAMETER_NAME

Required: No

ResourceId

The directory identifier for which you want to configure SAML properties.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: Yes

SamlProperties

The properties for configuring SAML 2.0 authentication.

Type: [SamlProperties](#) object

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ModifySelfservicePermissions

Modifies the self-service WorkSpace management capabilities for your users. For more information, see [Enable Self-Service WorkSpace Management Capabilities for Your Users](#).

Request Syntax

```
{  
    "ResourceId": "string",  
    "SelfservicePermissions": {  
        "ChangeComputeType": "string",  
        "IncreaseVolumeSize": "string",  
        "RebuildWorkspace": "string",  
        "RestartWorkspace": "string",  
        "SwitchRunningMode": "string"  
    }  
}
```

Request Parameters

The request accepts the following data in JSON format.

ResourceId

The identifier of the directory.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: Yes

SelfservicePermissions

The permissions to enable or disable self-service capabilities.

Type: [SelfservicePermissions object](#)

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ModifyWorkspaceAccessProperties

Specifies which devices and operating systems users can use to access their WorkSpaces. For more information, see [Control Device Access](#).

Request Syntax

```
{  
    "ResourceId": "string",  
    "WorkspaceAccessProperties": {  
        "DeviceTypeAndroid": "string",  
        "DeviceTypeChromeOs": "string",  
        "DeviceTypeIos": "string",  
        "DeviceTypeLinux": "string",  
        "DeviceTypeOsx": "string",  
        "DeviceTypeWeb": "string",  
        "DeviceTypeWindows": "string",  
        "DeviceTypeZeroClient": "string"  
    }  
}
```

Request Parameters

The request accepts the following data in JSON format.

ResourceId

The identifier of the directory.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: Yes

WorkspaceAccessProperties

The device types and operating systems to enable or disable for access.

Type: [WorkspaceAccessProperties](#) object

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ModifyWorkspaceCreationProperties

Modify the default properties used to create WorkSpaces.

Request Syntax

```
{  
    "ResourceId": "string",  
    "WorkspaceCreationProperties": {  
        "CustomSecurityGroupId": "string",  
        "DefaultOu": "string",  
        "EnableInternetAccess": boolean,  
        "EnableMaintenanceMode": boolean,  
        "EnableWorkDocs": boolean,  
        "UserEnabledAsLocalAdministrator": boolean  
    }  
}
```

Request Parameters

The request accepts the following data in JSON format.

ResourceId

The identifier of the directory.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: Yes

WorkspaceCreationProperties

The default properties for creating WorkSpaces.

Type: [WorkspaceCreationProperties](#) object

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ModifyWorkspaceProperties

Modifies the specified WorkSpace properties. For important information about how to modify the size of the root and user volumes, see [Modify a WorkSpace](#).

Note

The MANUAL running mode value is only supported by Amazon WorkSpaces Core. Contact your account team to be allow-listed to use this value. For more information, see [Amazon WorkSpaces Core](#).

Request Syntax

```
{  
    "DataReplication": "string",  
    "WorkspaceId": "string",  
    "WorkspaceProperties": {  
        "ComputeTypeName": "string",  
        "OperatingSystemName": "string",  
        "Protocols": [ "string" ],  
        "RootVolumeSizeGib": number,  
        "RunningMode": "string",  
        "RunningModeAutoStopTimeoutInMinutes": number,  
        "UserVolumeSizeGib": number  
    }  
}
```

Request Parameters

The request accepts the following data in JSON format.

DataReplication

Indicates the data replication status.

Type: String

Valid Values: NO_REPLICATION | PRIMARY_AS_SOURCE

Required: No

WorkSpaceId

The identifier of the WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: Yes

WorkspaceProperties

The properties of the WorkSpace.

Type: [WorkspaceProperties](#) object

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

OperationInProgressException

The properties of this WorkSpace are currently being modified. Try again in a moment.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

ResourceUnavailableException

The specified resource is not available.

HTTP Status Code: 400

UnsupportedWorkspaceConfigurationException

The configuration of this WorkSpace is not supported for this operation. For more information, see [Required Configuration and Service Components for WorkSpaces](#).

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

ModifyWorkspaceState

Sets the state of the specified WorkSpace.

To maintain a WorkSpace without being interrupted, set the WorkSpace state to ADMIN_MAINTENANCE. WorkSpaces in this state do not respond to requests to reboot, stop, start, rebuild, or restore. An AutoStop WorkSpace in this state is not stopped. Users cannot log into a WorkSpace in the ADMIN_MAINTENANCE state.

Request Syntax

```
{  
    "WorkspaceId": "string",  
    "WorkspaceState": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

Workspaceld

The identifier of the WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: Yes

WorkspaceState

The WorkSpace state.

Type: String

Valid Values: AVAILABLE | ADMIN_MAINTENANCE

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)

- [Amazon SDK for Ruby V3](#)

RebootWorkspaces

Reboots the specified WorkSpaces.

You cannot reboot a WorkSpace unless its state is AVAILABLE, UNHEALTHY, or REBOOTING. Reboot a WorkSpace in the REBOOTING state only if your WorkSpace has been stuck in the REBOOTING state for over 20 minutes.

This operation is asynchronous and returns before the WorkSpaces have rebooted.

Request Syntax

```
{  
    "RebootWorkspaceRequests": [  
        {  
            "WorkspaceId": "string"  
        }  
    ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

RebootWorkspaceRequests

The WorkSpaces to reboot. You can specify up to 25 WorkSpaces.

Type: Array of [RebootRequest](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Required: Yes

Response Syntax

```
{  
    "FailedRequests": [  
        {  
            "ErrorCode": "string",  
            "ErrorMessage": "string"  
        }  
    ]  
}
```

```
        "ErrorMessage": "string",
        "WorkspaceId": "string"
    }
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[FailedRequests](#)

Information about the WorkSpaces that could not be rebooted.

Type: Array of [FailedWorkspaceChangeRequest](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)

- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

RebuildWorkspaces

Rebuilds the specified WorkSpace.

You cannot rebuild a WorkSpace unless its state is AVAILABLE, ERROR, UNHEALTHY, STOPPED, or REBOOTING.

Rebuilding a WorkSpace is a potentially destructive action that can result in the loss of data. For more information, see [Rebuild a WorkSpace](#).

This operation is asynchronous and returns before the WorkSpaces have been completely rebuilt.

Request Syntax

```
{  
    "RebuildWorkspaceRequests": [  
        {  
            "WorkspaceId": "string"  
        }  
    ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

[RebuildWorkspaceRequests](#)

The WorkSpace to rebuild. You can specify a single WorkSpace.

Type: Array of [RebuildRequest](#) objects

Array Members: Fixed number of 1 item.

Required: Yes

Response Syntax

```
{  
    "FailedRequests": [  
        ...  
    ]  
}
```

```
{  
    "ErrorCode": "string",  
    "ErrorMessage": "string",  
    "WorkspaceId": "string"  
}  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[FailedRequests](#)

Information about the WorkSpace that could not be rebuilt.

Type: Array of [FailedWorkspaceChangeRequest](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

RegisterWorkspaceDirectory

Registers the specified directory. This operation is asynchronous and returns before the WorkSpace directory is registered. If this is the first time you are registering a directory, you will need to create the `workspaces_DefaultRole` role before you can register a directory. For more information, see [Creating the workspaces_DefaultRole Role](#).

Request Syntax

```
{  
    "DirectoryId": "string",  
    "EnableSelfService": boolean,  
    "EnableWorkDocs": boolean,  
    "SubnetIds": [ "string" ],  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ],  
    "Tenancy": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

DirectoryId

The identifier of the directory. You cannot register a directory if it does not have a status of Active. If the directory does not have a status of Active, you will receive an `InvalidResourceStateException` error. If you have already registered the maximum number of directories that you can register with Amazon WorkSpaces, you will receive a `ResourceLimitExceeded` error. Deregister directories that you are not using for WorkSpaces, and try again.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: Yes

[EnableSelfService](#)

Indicates whether self-service capabilities are enabled or disabled.

Type: Boolean

Required: No

[EnableWorkDocs](#)

Indicates whether Amazon WorkDocs is enabled or disabled. If you have enabled this parameter and WorkDocs is not available in the Region, you will receive an OperationNotSupportedException error. Set EnableWorkDocs to disabled, and try again.

Type: Boolean

Required: Yes

[SubnetIds](#)

The identifiers of the subnets for your virtual private cloud (VPC). Make sure that the subnets are in supported Availability Zones. The subnets must also be in separate Availability Zones. If these conditions are not met, you will receive an OperationNotSupportedException error.

Type: Array of strings

Array Members: Maximum number of 2 items.

Length Constraints: Minimum length of 15. Maximum length of 24.

Pattern: ^(subnet-([0-9a-f]{8}|[0-9a-f]{17}))\$

Required: No

[Tags](#)

The tags associated with the directory.

Type: Array of [Tag](#) objects

Required: No

[Tenancy](#)

Indicates whether your WorkSpace directory is dedicated or shared. To use Bring Your Own License (BYOL) images, this value must be set to DEDICATED and your Amazon Web Services

account must be enabled for BYOL. If your account has not been enabled for BYOL, you will receive an InvalidParameterValuesException error. For more information about BYOL images, see [Bring Your Own Windows Desktop Images](#).

Type: String

Valid Values: DEDICATED | SHARED

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

UnsupportedNetworkConfigurationException

The configuration of this network is not supported for this operation, or your network configuration conflicts with the Amazon WorkSpaces management network IP range. For more information, see [Configure a VPC for Amazon WorkSpaces](#).

HTTP Status Code: 400

WorkspacesDefaultRoleNotFoundException

The workspaces_DefaultRole role could not be found. If this is the first time you are registering a directory, you will need to create the workspaces_DefaultRole role before you can register a directory. For more information, see [Creating the workspaces_DefaultRole Role](#).

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

RestoreWorkspace

Restores the specified WorkSpace to its last known healthy state.

You cannot restore a WorkSpace unless its state is AVAILABLE, ERROR, UNHEALTHY, or STOPPED.

Restoring a WorkSpace is a potentially destructive action that can result in the loss of data. For more information, see [Restore a WorkSpace](#).

This operation is asynchronous and returns before the WorkSpace is completely restored.

Request Syntax

```
{  
    "WorkspaceId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

WorkspaceId

The identifier of the WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

RevokeIpRules

Removes one or more rules from the specified IP access control group.

Request Syntax

```
{  
    "GroupId": "string",  
    "UserRules": [ "string" ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

GroupId

The identifier of the group.

Type: String

Pattern: wsipg-[0-9a-z]{8,63}\$

Required: Yes

UserRules

The rules to remove from the group.

Type: Array of strings

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

StartWorkspaces

Starts the specified WorkSpaces.

You cannot start a WorkSpace unless it has a running mode of AutoStop and a state of STOPPED.

Request Syntax

```
{  
    "StartWorkspaceRequests": [  
        {  
            "WorkspaceId": "string"  
        }  
    ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

StartWorkspaceRequests

The WorkSpaces to start. You can specify up to 25 WorkSpaces.

Type: Array of [StartRequest](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Required: Yes

Response Syntax

```
{  
    "FailedRequests": [  
        {  
            "ErrorCode": "string",  
            "ErrorMessage": "string",  
            "WorkspaceId": "string"  
        }  
    ]  
}
```

}

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

FailedRequests

Information about the WorkSpaces that could not be started.

Type: Array of [FailedWorkspaceChangeRequest](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

StopWorkspaces

Stops the specified WorkSpaces.

You cannot stop a WorkSpace unless it has a running mode of AutoStop and a state of AVAILABLE, IMPAIRED, UNHEALTHY, or ERROR.

Request Syntax

```
{  
    "StopWorkspaceRequests": [  
        {  
            "WorkspaceId": "string"  
        }  
    ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

[StopWorkspaceRequests](#)

The WorkSpaces to stop. You can specify up to 25 WorkSpaces.

Type: Array of [StopRequest](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Required: Yes

Response Syntax

```
{  
    "FailedRequests": [  
        {  
            "ErrorCode": "string",  
            "ErrorMessage": "string",  
            "WorkspaceId": "string"  
        }  
    ]  
}
```

```
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[FailedRequests](#)

Information about the WorkSpaces that could not be stopped.

Type: Array of [FailedWorkspaceChangeRequest](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

TerminateWorkspaces

Terminates the specified WorkSpaces.

Important

Terminating a WorkSpace is a permanent action and cannot be undone. The user's data is destroyed. If you need to archive any user data, contact Amazon Web Services Support before terminating the WorkSpace.

You can terminate a WorkSpace that is in any state except SUSPENDED.

This operation is asynchronous and returns before the WorkSpaces have been completely terminated. After a WorkSpace is terminated, the TERMINATED state is returned only briefly before the WorkSpace directory metadata is cleaned up, so this state is rarely returned. To confirm that a WorkSpace is terminated, check for the WorkSpace ID by using [DescribeWorkSpaces](#). If the WorkSpace ID isn't returned, then the WorkSpace has been successfully terminated.

Note

Simple AD and AD Connector are made available to you free of charge to use with WorkSpaces. If there are no WorkSpaces being used with your Simple AD or AD Connector directory for 30 consecutive days, this directory will be automatically deregistered for use with Amazon WorkSpaces, and you will be charged for this directory as per the [Amazon Directory Service pricing terms](#).

To delete empty directories, see [Delete the Directory for Your WorkSpaces](#). If you delete your Simple AD or AD Connector directory, you can always create a new one when you want to start using WorkSpaces again.

Request Syntax

```
{  
    "TerminateWorkspaceRequests": [  
        {  
            "WorkspaceId": "string"  
        }  
    ]  
}
```

```
]  
}
```

Request Parameters

The request accepts the following data in JSON format.

TerminateWorkspaceRequests

The WorkSpaces to terminate. You can specify up to 25 WorkSpaces.

Type: Array of [TerminateRequest](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Required: Yes

Response Syntax

```
{  
    "FailedRequests": [  
        {  
            "ErrorCode": "string",  
            "ErrorMessage": "string",  
            "WorkspaceId": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

FailedRequests

Information about the WorkSpaces that could not be terminated.

Type: Array of [FailedWorkspaceChangeRequest](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateConnectClientAddIn

Updates a Amazon Connect client add-in. Use this action to update the name and endpoint URL of a Amazon Connect client add-in.

Request Syntax

```
{  
    "AddInId": "string",  
    "Name": "string",  
    "ResourceId": "string",  
    "URL": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

AddInId

The identifier of the client add-in to update.

Type: String

Length Constraints: Fixed length of 36.

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: Yes

Name

The name of the client add-in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^.*\$

Required: No

ResourceId

The directory identifier for which the client add-in is configured.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: Yes

URL

The endpoint URL of the Amazon Connect client add-in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: ^(http|https)\:\/\/\S+

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateConnectionAliasPermission

Shares or unshares a connection alias with one account by specifying whether that account has permission to associate the connection alias with a directory. If the association permission is granted, the connection alias is shared with that account. If the association permission is revoked, the connection alias is unshared with the account. For more information, see [Cross-Region Redirection for Amazon WorkSpaces](#).

Note

- Before performing this operation, call [DescribeConnectionAliases](#) to make sure that the current state of the connection alias is CREATED.
- To delete a connection alias that has been shared, the shared account must first disassociate the connection alias from any directories it has been associated with. Then you must unshare the connection alias from the account it has been shared with. You can delete a connection alias only after it is no longer shared with any accounts or associated with any directories.

Request Syntax

```
{  
    "AliasId": "string",  
    "ConnectionAliasPermission": {  
        "AllowAssociation": boolean,  
        "SharedAccountId": "string"  
    }  
}
```

Request Parameters

The request accepts the following data in JSON format.

[AliasId](#)

The identifier of the connection alias that you want to update permissions for.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 68.

Pattern: ^wsca-[0-9a-z]{8,63}\$

Required: Yes

[ConnectionAliasPermission](#)

Indicates whether to share or unshare the connection alias with the specified Amazon Web Services account.

Type: [ConnectionAliasPermission](#) object

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceAssociatedException

The resource is associated with a directory.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateRulesOfIpGroup

Replaces the current rules of the specified IP access control group with the specified rules.

Request Syntax

```
{  
    "GroupId": "string",  
    "UserRules": [  
        {  
            "ipRule": "string",  
            "ruleDesc": "string"  
        }  
    ]  
}
```

Request Parameters

The request accepts the following data in JSON format.

GroupId

The identifier of the group.

Type: String

Pattern: wsipg-[0-9a-z]{8,63}\$

Required: Yes

UserRules

One or more rules.

Type: Array of [IpRuleItem](#) objects

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

InvalidResourceStateException

The state of the resource is not valid for this operation.

HTTP Status Code: 400

ResourceLimitExceededException

Your resource limits have been exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateWorkspaceBundle

Updates a WorkSpace bundle with a new image. For more information about updating WorkSpace bundles, see [Update a Custom WorkSpaces Bundle](#).

⚠ Important

Existing WorkSpaces aren't automatically updated when you update the bundle that they're based on. To update existing WorkSpaces that are based on a bundle that you've updated, you must either rebuild the WorkSpaces or delete and recreate them.

Request Syntax

```
{  
  "BundleId": "string",  
  "ImageId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

BundleId

The identifier of the bundle.

Type: String

Pattern: ^wsb-[0-9a-z]{8,63}\$

Required: No

ImageId

The identifier of the image.

Type: String

Pattern: wsi-[0-9a-z]{9,63}\$

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

ResourceUnavailableException

The specified resource is not available.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)
- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

UpdateWorkspaceImagePermission

Shares or unshares an image with one account in the same Amazon Web Services Region by specifying whether that account has permission to copy the image. If the copy image permission is granted, the image is shared with that account. If the copy image permission is revoked, the image is unshared with the account.

After an image has been shared, the recipient account can copy the image to other Regions as needed.

In the China (Ningxia) Region, you can copy images only within the same Region.

In Amazon GovCloud (US), to copy images to and from other Regions, contact Amazon Web Services Support.

For more information about sharing images, see [Share or Unshare a Custom WorkSpaces Image](#).

Note

- To delete an image that has been shared, you must unshare the image before you delete it.
- Sharing Bring Your Own License (BYOL) images across Amazon Web Services accounts isn't supported at this time in Amazon GovCloud (US). To share BYOL images across accounts in Amazon GovCloud (US), contact Amazon Web Services Support.

Request Syntax

```
{  
    "AllowCopyImage": boolean,  
    "ImageId": "string",  
    "SharedAccountId": "string"  
}
```

Request Parameters

The request accepts the following data in JSON format.

AllowCopyImage

The permission to copy the image. This permission can be revoked only after an image has been shared.

Type: Boolean

Required: Yes

ImageId

The identifier of the image.

Type: String

Pattern: wsi-[0-9a-z]{9,63}\$

Required: Yes

SharedAccountId

The identifier of the Amazon Web Services account to share or unshare the image with.

⚠ Important

Before sharing the image, confirm that you are sharing to the correct Amazon Web Services account ID.

Type: String

Pattern: ^\d{12}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user is not authorized to access a resource.

HTTP Status Code: 400

InvalidParameterValuesException

One or more parameter values are not valid.

HTTP Status Code: 400

OperationNotSupportedException

This operation is not supported.

HTTP Status Code: 400

ResourceNotFoundException

The resource could not be found.

HTTP Status Code: 400

ResourceUnavailableException

The specified resource is not available.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon Command Line Interface](#)
- [Amazon SDK for .NET](#)
- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for JavaScript V3](#)
- [Amazon SDK for PHP V3](#)

- [Amazon SDK for Python](#)
- [Amazon SDK for Ruby V3](#)

Data Types

The Amazon WorkSpaces API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccountModification](#)
- [ApplicationResourceAssociation](#)
- [AssociationStateReason](#)
- [BundleResourceAssociation](#)
- [CertificateBasedAuthProperties](#)
- [ClientProperties](#)
- [ClientPropertiesResult](#)
- [ComputeType](#)
- [ConnectClientAddIn](#)
- [ConnectionAlias](#)
- [ConnectionAliasAssociation](#)
- [ConnectionAliasPermission](#)
- [DataReplicationSettings](#)
- [DefaultClientBrandingAttributes](#)
- [DefaultImportClientBrandingAttributes](#)
- [DefaultWorkspaceCreationProperties](#)
- [ErrorDetails](#)
- [FailedCreateStandbyWorkspacesRequest](#)
- [FailedCreateWorkspaceRequest](#)
- [FailedWorkspaceChangeRequest](#)

- [ImagePermission](#)
- [ImageResourceAssociation](#)
- [IosClientBrandingAttributes](#)
- [IosImportClientBrandingAttributes](#)
- [IpRuleItem](#)
- [ModificationState](#)
- [OperatingSystem](#)
- [PendingCreateStandbyWorkspacesRequest](#)
- [RebootRequest](#)
- [RebuildRequest](#)
- [RelatedWorkspaceProperties](#)
- [RootStorage](#)
- [SamlProperties](#)
- [SelfservicePermissions](#)
- [Snapshot](#)
- [StandbyWorkspace](#)
- [StandbyWorkspacesProperties](#)
- [StartRequest](#)
- [StopRequest](#)
- [Tag](#)
- [TerminateRequest](#)
- [UpdateResult](#)
- [UserStorage](#)
- [Workspace](#)
- [WorkspaceAccessProperties](#)
- [WorkSpaceApplication](#)
- [WorkSpaceApplicationDeployment](#)
- [WorkspaceBundle](#)
- [WorkspaceConnectionStatus](#)
- [WorkspaceCreationProperties](#)

- [WorkspaceDirectory](#)
- [WorkspacelImage](#)
- [WorkspaceProperties](#)
- [WorkspaceRequest](#)
- [WorkspaceResourceAssociation](#)
- [WorkspacesIpGroup](#)

AccountModification

Describes a modification to the configuration of Bring Your Own License (BYOL) for the specified account.

Contents

DedicatedTenancyManagementCidrRange

The IP address range, specified as an IPv4 CIDR block, for the management network interface used for the account.

Type: String

Pattern: (^([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])\.([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])\.\.0\.\.0)(\/(16\$))\$

Required: No

DedicatedTenancySupport

The status of BYOL (whether BYOL is being enabled or disabled).

Type: String

Valid Values: ENABLED | DISABLED

Required: No

ErrorCode

The error code that is returned if the configuration of BYOL cannot be modified.

Type: String

Required: No

ErrorMessage

The text of the error message that is returned if the configuration of BYOL cannot be modified.

Type: String

Required: No

ModificationState

The state of the modification to the configuration of BYOL.

Type: String

Valid Values: PENDING | COMPLETED | FAILED

Required: No

StartTime

The timestamp when the modification of the BYOL configuration was started.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ApplicationResourceAssociation

Describes the association between an application and an application resource.

Contents

ApplicationId

The identifier of the application.

Type: String

Pattern: ^wsa-[0-9a-z]{8,63}\$

Required: No

AssociatedResourceId

The identifier of the associated resource.

Type: String

Length Constraints: Minimum length of 1.

Required: No

AssociatedResourceType

The resource type of the associated resource.

Type: String

Valid Values: WORKSPACE | BUNDLE | IMAGE

Required: No

Created

The time the association was created.

Type: Timestamp

Required: No

LastUpdatedTime

The time the association status was last updated.

Type: Timestamp

Required: No

State

The status of the application resource association.

Type: String

Valid Values: PENDING_INSTALL | PENDING_INSTALL_DEPLOYMENT | PENDING_UNINSTALL | PENDING_UNINSTALL_DEPLOYMENT | INSTALLING | UNINSTALLING | ERROR | COMPLETED | REMOVED

Required: No

StateReason

The reason the association deployment failed.

Type: [AssociationStateReason](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

AssociationStateReason

Indicates the reason that the association deployment failed, including the error code and error message.

Contents

ErrorCode

The error code of the association deployment failure.

Type: String

Valid Values: ValidationError.InsufficientDiskSpace |
ValidationError.InsufficientMemory |
ValidationError.UnsupportedOperatingSystem |
DeploymentError.InternalServerError |
DeploymentError.WorkspaceUnreachable

Required: No

ErrorMessage

The error message of the association deployment failure.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

BundleResourceAssociation

Describes the association between an application and a bundle resource.

Contents

AssociatedResourceId

The identifier of the associated resource.

Type: String

Length Constraints: Minimum length of 1.

Required: No

AssociatedResourceType

The resource type of the associated resources.

Type: String

Valid Values: APPLICATION

Required: No

BundleId

The identifier of the bundle.

Type: String

Pattern: ^wsb-[0-9a-z]{8,63}\$

Required: No

Created

The time the association is created.

Type: Timestamp

Required: No

LastUpdatedTime

The time the association status was last updated.

Type: Timestamp

Required: No

State

The status of the bundle resource association.

Type: String

Valid Values: PENDING_INSTALL | PENDING_INSTALL_DEPLOYMENT | PENDING_UNINSTALL | PENDING_UNINSTALL_DEPLOYMENT | INSTALLING | UNINSTALLING | ERROR | COMPLETED | REMOVED

Required: No

StateReason

The reason the association deployment failed.

Type: [AssociationStateReason](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

CertificateBasedAuthProperties

Describes the properties of the certificate-based authentication you want to use with your WorkSpaces.

Contents

CertificateAuthorityArn

The Amazon Resource Name (ARN) of the Amazon Certificate Manager Private CA resource.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: arn:[\w+=/, .@-]+:[\w+=/, .@-]+:[\w+=/, .@-]*:[0-9]*:[\w+=, .@-]+(/[\w+=, .@-]+)*

Required: No

Status

The status of the certificate-based authentication properties.

Type: String

Valid Values: DISABLED | ENABLED

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ClientProperties

Describes an Amazon WorkSpaces client.

Contents

LogUploadEnabled

Specifies whether users can upload diagnostic log files of Amazon WorkSpaces client directly to WorkSpaces to troubleshoot issues when using the WorkSpaces client. When enabled, the log files will be sent to WorkSpaces automatically and will be applied to all users in the specified directory.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

ReconnectEnabled

Specifies whether users can cache their credentials on the Amazon WorkSpaces client. When enabled, users can choose to reconnect to their WorkSpaces without re-entering their credentials.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ClientPropertiesResult

Information about the Amazon WorkSpaces client.

Contents

ClientProperties

Information about the Amazon WorkSpaces client.

Type: [ClientProperties](#) object

Required: No

ResourceId

The resource identifier, in the form of a directory ID.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ComputeType

Describes the compute type of the bundle.

Contents

Name

The compute type.

Type: String

Valid Values: VALUE | STANDARD | PERFORMANCE | POWER | GRAPHICS | POWERPRO | GRAPHICSPRO | GRAPHICS_G4DN | GRAPHICSPRO_G4DN

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ConnectClientAddIn

Describes an Amazon Connect client add-in.

Contents

AddInId

The client add-in identifier.

Type: String

Length Constraints: Fixed length of 36.

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: No

Name

The name of the client add in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^ . *\$

Required: No

ResourceId

The directory identifier for which the client add-in is configured.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: No

URL

The endpoint URL of the client add-in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: ^(http|https)\:\/\/\S+

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ConnectionAlias

Describes a connection alias. Connection aliases are used for cross-Region redirection. For more information, see [Cross-Region Redirection for Amazon WorkSpaces](#).

Contents

AliasId

The identifier of the connection alias.

Type: String

Length Constraints: Minimum length of 13. Maximum length of 68.

Pattern: ^wsca-[0-9a-z]{8,63}\$

Required: No

Associations

The association status of the connection alias.

Type: Array of [ConnectionAliasAssociation](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Required: No

ConnectionString

The connection string specified for the connection alias. The connection string must be in the form of a fully qualified domain name (FQDN), such as www.example.com.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: ^[.0-9a-zA-Z\-\-]{1,255}\$

Required: No

OwnerAccountId

The identifier of the Amazon Web Services account that owns the connection alias.

Type: String

Pattern: ^\d{12}\$

Required: No

State

The current state of the connection alias.

Type: String

Valid Values: CREATING | CREATED | DELETING

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ConnectionAliasAssociation

Describes a connection alias association that is used for cross-Region redirection. For more information, see [Cross-Region Redirection for Amazon WorkSpaces](#).

Contents

AssociatedAccountId

The identifier of the Amazon Web Services account that associated the connection alias with a directory.

Type: String

Pattern: ^\d{12}\\$

Required: No

AssociationStatus

The association status of the connection alias.

Type: String

Valid Values: NOT_ASSOCIATED | ASSOCIATED_WITH_OWNER_ACCOUNT
| ASSOCIATED_WITH_SHARED_ACCOUNT | PENDING_ASSOCIATION |
PENDING_DISASSOCIATION

Required: No

ConnectionIdentifier

The identifier of the connection alias association. You use the connection identifier in the DNS TXT record when you're configuring your DNS routing policies.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: ^[a-zA-Z0-9]+\\$

Required: No

ResourceId

The identifier of the directory associated with a connection alias.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ConnectionAliasPermission

Describes the permissions for a connection alias. Connection aliases are used for cross-Region redirection. For more information, see [Cross-Region Redirection for Amazon WorkSpaces](#).

Contents

AllowAssociation

Indicates whether the specified Amazon Web Services account is allowed to associate the connection alias with a directory.

Type: Boolean

Required: Yes

SharedAccountId

The identifier of the Amazon Web Services account that the connection alias is shared with.

Type: String

Pattern: ^\d{12}\\$

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DataReplicationSettings

Describes the data replication settings.

Contents

DataReplication

Indicates whether data replication is enabled, and if enabled, the type of data replication.

Type: String

Valid Values: NO_REPLICATION | PRIMARY_AS_SOURCE

Required: No

RecoverySnapshotTime

The date and time at which the last successful snapshot was taken of the primary WorkSpace used for replicating data.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DefaultClientBrandingAttributes

Returns default client branding attributes that were imported. These attributes display on the client login screen.

⚠ Important

Client branding attributes are public facing. Ensure that you don't include sensitive information.

Contents

ForgotPasswordLink

The forgotten password link. This is the web address that users can go to if they forget the password for their WorkSpace.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `^(http|https)\:\/\/[S+]`

Required: No

LoginMessage

The login message. Specified as a key value pair, in which the key is a locale and the value is the localized message for that locale. The only key supported is en_US. The HTML tags supported include the following: a, b, blockquote, br, cite, code, dd, dl, dt, div, em, i, li, ol, p, pre, q, small, span, strike, strong, sub, sup, u, ul.

Type: String to string map

Key Length Constraints: Fixed length of 5.

Key Pattern: `^[a-z]{2}_[A-Z]{2}$`

Value Length Constraints: Minimum length of 0. Maximum length of 2000.

Value Pattern: `^.*$`

Required: No

LogoUrl

The logo. The only image format accepted is a binary data object that is converted from a .png file.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: ^(http|https)\:\/\/\S+

Required: No

SupportEmail

The support email. The company's customer support email address.

Note

- In each platform type, the SupportEmail and SupportLink parameters are mutually exclusive. You can specify one parameter for each platform type, but not both.
- The default email is workspaces-feedback@amazon.com.

Type: String

Length Constraints: Minimum length of 6. Maximum length of 64.

Pattern: ^[a-zA-Z0-9._%+-]+@[a-zA-Z0-9.-]+\.[a-zA-Z]{2,4}\$

Required: No

SupportLink

The support link. The link for the company's customer support page for their WorkSpace.

Note

- In each platform type, the SupportEmail and SupportLink parameters are mutually exclusive. You can specify one parameter for each platform type, but not both.

- The default support link is `workspaces-feedback@amazon.com`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `^(http|https)\:\/\/\S+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DefaultImportClientBrandingAttributes

The default client branding attributes to be imported. These attributes display on the client login screen.

Important

Client branding attributes are public facing. Ensure that you do not include sensitive information.

Contents

ForgotPasswordLink

The forgotten password link. This is the web address that users can go to if they forget the password for their WorkSpace.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `^(http|https)\:\/\/[S+]`

Required: No

LoginMessage

The login message. Specified as a key value pair, in which the key is a locale and the value is the localized message for that locale. The only key supported is en_US. The HTML tags supported include the following: a, b, blockquote, br, cite, code, dd, dl, dt, div, em, i, li, ol, p, pre, q, small, span, strike, strong, sub, sup, u, ul.

Type: String to string map

Key Length Constraints: Fixed length of 5.

Key Pattern: `^[a-z]{2}_[A-Z]{2}$`

Value Length Constraints: Minimum length of 0. Maximum length of 2000.

Value Pattern: `^.*$`

Required: No

Logo

The logo. The only image format accepted is a binary data object that is converted from a .png file.

Type: Base64-encoded binary data object

Length Constraints: Minimum length of 1. Maximum length of 1500000.

Required: No

SupportEmail

The support email. The company's customer support email address.

Note

- In each platform type, the `SupportEmail` and `SupportLink` parameters are mutually exclusive. You can specify one parameter for each platform type, but not both.
- The default email is `workspaces-feedback@amazon.com`.

Type: String

Length Constraints: Minimum length of 6. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._%+-]+@[a-zA-Z0-9.-]+\.\w{2,4}$`

Required: No

SupportLink

The support link. The link for the company's customer support page for their WorkSpace.

Note

- In each platform type, the `SupportEmail` and `SupportLink` parameters are mutually exclusive. You can specify one parameter for each platform type, but not both.

- The default support link is `workspaces-feedback@amazon.com`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `^(http|https)\:\/\/\S+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

DefaultWorkspaceCreationProperties

Describes the default values that are used to create WorkSpaces. For more information, see [Update Directory Details for Your WorkSpaces](#).

Contents

CustomSecurityGroupId

The identifier of the default security group to apply to WorkSpaces when they are created. For more information, see [Security Groups for Your WorkSpaces](#).

Type: String

Length Constraints: Minimum length of 11. Maximum length of 20.

Pattern: ^(sg-([0-9a-f]{8}|[0-9a-f]{17}))\$

Required: No

DefaultOu

The organizational unit (OU) in the directory for the WorkSpace machine accounts.

Type: String

Required: No

EnableInternetAccess

Specifies whether to automatically assign an Elastic public IP address to WorkSpaces in this directory by default. If enabled, the Elastic public IP address allows outbound internet access from your WorkSpaces when you're using an internet gateway in the Amazon VPC in which your WorkSpaces are located. If you're using a Network Address Translation (NAT) gateway for outbound internet access from your VPC, or if your WorkSpaces are in public subnets and you manually assign them Elastic IP addresses, you should disable this setting. This setting applies to new WorkSpaces that you launch or to existing WorkSpaces that you rebuild. For more information, see [Configure a VPC for Amazon WorkSpaces](#).

Type: Boolean

Required: No

EnableMaintenanceMode

Specifies whether maintenance mode is enabled for WorkSpaces. For more information, see [WorkSpace Maintenance](#).

Type: Boolean

Required: No

EnableWorkDocs

Specifies whether the directory is enabled for Amazon WorkDocs.

Type: Boolean

Required: No

UserEnabledAsLocalAdministrator

Specifies whether WorkSpace users are local administrators on their WorkSpaces.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ErrorDetails

Describes in-depth details about the error. These details include the possible causes of the error and troubleshooting information.

Contents

ErrorCode

Indicates the error code returned.

Type: String

Valid Values: OutdatedPowershellVersion | OfficeInstalled | PCoIPAgentInstalled | WindowsUpdatesEnabled | AutoMountDisabled | WorkspacesBYOLAccountNotFound | WorkspacesBYOLAccountDisabled | DHCPDisabled | DiskFreeSpace | AdditionalDrivesAttached | OSNotSupported | DomainJoined | AzureDomainJoined | FirewallEnabled | VMWareToolsInstalled | DiskSizeExceeded | IncompatiblePartitioning | PendingReboot | AutoLogonEnabled | RealTimeUniversalDisabled | MultipleBootPartition | Requires64BitOS | ZeroRearmCount | InPlaceUpgrade | AntiVirusInstalled | UEFINotSupported

Required: No

ErrorMessage

The text of the error message related the error code.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

FailedCreateStandbyWorkspacesRequest

Describes the standby WorkSpace that could not be created.

Contents

ErrorCode

The error code that is returned if the standby WorkSpace could not be created.

Type: String

Required: No

ErrorMessage

The text of the error message that is returned if the standby WorkSpace could not be created.

Type: String

Required: No

StandbyWorkspaceRequest

Information about the standby WorkSpace that could not be created.

Type: [StandbyWorkspace](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

FailedCreateWorkspaceRequest

Describes a WorkSpace that cannot be created.

Contents

ErrorCode

The error code that is returned if the WorkSpace cannot be created.

Type: String

Required: No

ErrorMessage

The text of the error message that is returned if the WorkSpace cannot be created.

Type: String

Required: No

WorkspaceRequest

Information about the WorkSpace.

Type: [WorkspaceRequest](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

FailedWorkspaceChangeRequest

Describes a WorkSpace that could not be rebooted. ([RebootWorkspaces](#)), rebuilt ([RebuildWorkspaces](#)), restored ([RestoreWorkspace](#)), terminated ([TerminateWorkspaces](#)), started ([StartWorkspaces](#)), or stopped ([StopWorkspaces](#)).

Contents

ErrorCode

The error code that is returned if the WorkSpace cannot be rebooted.

Type: String

Required: No

ErrorMessage

The text of the error message that is returned if the WorkSpace cannot be rebooted.

Type: String

Required: No

WorkspaceId

The identifier of the WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)

- [Amazon SDK for Ruby V3](#)

ImagePermission

Describes the Amazon Web Services accounts that have been granted permission to use a shared image. For more information about sharing images, see [Share or Unshare a Custom WorkSpaces Image](#).

Contents

SharedAccountId

The identifier of the Amazon Web Services account that an image has been shared with.

Type: String

Pattern: ^\d{12}\\$

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ImageResourceAssociation

Describes the association between an application and an image resource.

Contents

AssociatedResourceId

The identifier of the associated resource.

Type: String

Length Constraints: Minimum length of 1.

Required: No

AssociatedResourceType

The resource type of the associated resources.

Type: String

Valid Values: APPLICATION

Required: No

Created

The time the association is created.

Type: Timestamp

Required: No

ImageId

The identifier of the image.

Type: String

Pattern: wsi-[0-9a-z]{9,63}\$

Required: No

LastUpdatedTime

The time the association status was last updated.

Type: Timestamp

Required: No

State

The status of the image resource association.

Type: String

Valid Values: PENDING_INSTALL | PENDING_INSTALL_DEPLOYMENT | PENDING_UNINSTALL | PENDING_UNINSTALL_DEPLOYMENT | INSTALLING | UNINSTALLING | ERROR | COMPLETED | REMOVED

Required: No

StateReason

The reason the association deployment failed.

Type: [AssociationStateReason](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

IosClientBrandingAttributes

The client branding attributes for iOS device types. These attributes are displayed on the iOS client login screen only.

⚠ Important

Client branding attributes are public facing. Ensure you do not include sensitive information.

Contents

ForgotPasswordLink

The forgotten password link. This is the web address that users can go to if they forget the password for their WorkSpace.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `^(http|https)\:\/\/[S+]`

Required: No

LoginMessage

The login message. Specified as a key value pair, in which the key is a locale and the value is the localized message for that locale. The only key supported is en_US. The HTML tags supported include the following: a, b, blockquote, br, cite, code, dd, dl, dt, div, em, i, li, ol, p, pre, q, small, span, strike, strong, sub, sup, u, ul.

Type: String to string map

Key Length Constraints: Fixed length of 5.

Key Pattern: `^[a-z]{2}_[A-Z]{2}$`

Value Length Constraints: Minimum length of 0. Maximum length of 2000.

Value Pattern: `^.*$`

Required: No

Logo2xUrl

The @2x version of the logo. This is the higher resolution display that offers a scale factor of 2.0 (or @2x). The only image format accepted is a binary data object that is converted from a .png file.

 **Note**

For more information about iOS image size and resolution, see [Image Size and Resolution](#) in the *Apple Human Interface Guidelines*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: ^([http](http://)|[https](https://))\:/\S+

Required: No

Logo3xUrl

The @3x version of the logo. This is the higher resolution display that offers a scale factor of 3.0 (or @3x).The only image format accepted is a binary data object that is converted from a .png file.

 **Note**

For more information about iOS image size and resolution, see [Image Size and Resolution](#) in the *Apple Human Interface Guidelines*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: ^([http](http://)|[https](https://))\:/\S+

Required: No

LogoUrl

The logo. This is the standard-resolution display that has a 1:1 pixel density (or @1x), where one pixel is equal to one point. The only image format accepted is a binary data object that is converted from a .png file.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: ^(http|https)\:\/\/\S+

Required: No

SupportEmail

The support email. The company's customer support email address.

Note

- In each platform type, the SupportEmail and SupportLink parameters are mutually exclusive. You can specify one parameter for each platform type, but not both.
- The default email is workspaces-feedback@amazon.com.

Type: String

Length Constraints: Minimum length of 6. Maximum length of 64.

Pattern: ^[a-zA-Z0-9._%+-]+@[a-zA-Z0-9.-]+\.[a-zA-Z]{2,4}\$

Required: No

SupportLink

The support link. The link for the company's customer support page for their WorkSpace.

Note

- In each platform type, the SupportEmail and SupportLink parameters are mutually exclusive. You can specify one parameter for each platform type, but not both.

- The default support link is `workspaces-feedback@amazon.com`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `^(http|https)\:\/\/\S+`

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

IosImportClientBrandingAttributes

The client branding attributes to import for iOS device types. These attributes are displayed on the iOS client login screen.

⚠ Important

Client branding attributes are public facing. Ensure you do not include sensitive information.

Contents

ForgotPasswordLink

The forgotten password link. This is the web address that users can go to if they forget the password for their WorkSpace.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `^(http|https)\:\/\/[S+]`

Required: No

LoginMessage

The login message. Specified as a key value pair, in which the key is a locale and the value is the localized message for that locale. The only key supported is en_US. The HTML tags supported include the following: a, b, blockquote, br, cite, code, dd, dl, dt, div, em, i, li, ol, p, pre, q, small, span, strike, strong, sub, sup, u, ul.

Type: String to string map

Key Length Constraints: Fixed length of 5.

Key Pattern: `^[a-z]{2}_[A-Z]{2}$`

Value Length Constraints: Minimum length of 0. Maximum length of 2000.

Value Pattern: `^.*$`

Required: No

Logo

The logo. This is the standard-resolution display that has a 1:1 pixel density (or @1x), where one pixel is equal to one point. The only image format accepted is a binary data object that is converted from a .png file.

Type: Base64-encoded binary data object

Length Constraints: Minimum length of 1. Maximum length of 447000.

Required: No

Logo2x

The @2x version of the logo. This is the higher resolution display that offers a scale factor of 2.0 (or @2x). The only image format accepted is a binary data object that is converted from a .png file.

 **Note**

For more information about iOS image size and resolution, see [Image Size and Resolution](#) in the *Apple Human Interface Guidelines*.

Type: Base64-encoded binary data object

Length Constraints: Minimum length of 1. Maximum length of 1770000.

Required: No

Logo3x

The @3x version of the logo. This is the higher resolution display that offers a scale factor of 3.0 (or @3x). The only image format accepted is a binary data object that is converted from a .png file.

 **Note**

For more information about iOS image size and resolution, see [Image Size and Resolution](#) in the *Apple Human Interface Guidelines*.

Type: Base64-encoded binary data object

Length Constraints: Minimum length of 1. Maximum length of 1770000.

Required: No

SupportEmail

The support email. The company's customer support email address.

Note

- In each platform type, the `SupportEmail` and `SupportLink` parameters are mutually exclusive. You can specify one parameter for each platform type, but not both.
- The default email is `workspaces-feedback@amazon.com`.

Type: String

Length Constraints: Minimum length of 6. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._%+-]+@[a-zA-Z0-9.-]+\.[a-zA-Z]{2,4}$`

Required: No

SupportLink

The support link. The link for the company's customer support page for their WorkSpace.

Note

- In each platform type, the `SupportEmail` and `SupportLink` parameters are mutually exclusive. You can specify one parameter for each platform type, but not both.
- The default support link is `workspaces-feedback@amazon.com`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: ^(http|https)\:\/\/\S+

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

IpRuleItem

Describes a rule for an IP access control group.

Contents

ipRule

The IP address range, in CIDR notation.

Type: String

Required: No

ruleDesc

The description.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

ModificationState

Describes a WorkSpace modification.

Contents

Resource

The resource.

Type: String

Valid Values: ROOT_VOLUME | USER_VOLUME | COMPUTE_TYPE

Required: No

State

The modification state.

Type: String

Valid Values: UPDATE_INITIATED | UPDATE_IN_PROGRESS

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

OperatingSystem

The operating system that the image is running.

Contents

Type

The operating system.

Type: String

Valid Values: WINDOWS | LINUX

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

PendingCreateStandbyWorkspacesRequest

Information about the standby WorkSpace.

Contents

DirectoryId

The identifier of the directory for the standby WorkSpace.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: No

State

The operational state of the standby WorkSpace.

Type: String

Valid Values: PENDING | AVAILABLE | IMPAIRED | UNHEALTHY | REBOOTING | STARTING | REBUILDING | RESTORING | MAINTENANCE | ADMIN_MAINTENANCE | TERMINATING | TERMINATED | SUSPENDED | UPDATING | STOPPING | STOPPED | ERROR

Required: No

UserName

Describes the standby WorkSpace that was created.

Because this operation is asynchronous, the identifier returned is not immediately available for use with other operations. For example, if you call [DescribeWorkspaces](#) before the WorkSpace is created, the information returned can be incomplete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Required: No

WorkspaceId

The identifier of the standby WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RebootRequest

Describes the information used to reboot a WorkSpace.

Contents

WorkSpaceId

The identifier of the WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RebuildRequest

Describes the information used to rebuild a WorkSpace.

Contents

WorkSpaceId

The identifier of the WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RelatedWorkspaceProperties

Describes the related WorkSpace. The related WorkSpace could be a standby WorkSpace or primary WorkSpace related to the specified WorkSpace.

Contents

Region

The Region of the related WorkSpace.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 31.

Pattern: ^[-0-9a-z]{1,31}\$

Required: No

State

Indicates the state of the WorkSpace.

Type: String

Valid Values: PENDING | AVAILABLE | IMPAIRED | UNHEALTHY | REBOOTING | STARTING | REBUILDING | RESTORING | MAINTENANCE | ADMIN_MAINTENANCE | TERMINATING | TERMINATED | SUSPENDED | UPDATING | STOPPING | STOPPED | ERROR

Required: No

Type

Indicates the type of WorkSpace.

Type: String

Valid Values: PRIMARY | STANDBY

Required: No

WorkspaceId

The identifier of the related WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

RootStorage

Describes the root volume for a WorkSpace bundle.

Contents

Capacity

The size of the root volume.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SamlProperties

Describes the enablement status, user access URL, and relay state parameter name that are used for configuring federation with an SAML 2.0 identity provider.

Contents

RelyStateParameterName

The relay state parameter name supported by the SAML 2.0 identity provider (IdP). When the end user is redirected to the user access URL from the WorkSpaces client application, this relay state parameter name is appended as a query parameter to the URL along with the relay state endpoint to return the user to the client application session.

To use SAML 2.0 authentication with WorkSpaces, the IdP must support IdP-initiated deep linking for the relay state URL. Consult your IdP documentation for more information.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Status

Indicates the status of SAML 2.0 authentication. These statuses include the following.

- If the setting is DISABLED, end users will be directed to login with their directory credentials.
- If the setting is ENABLED, end users will be directed to login via the user access URL. Users attempting to connect to WorkSpaces from a client application that does not support SAML 2.0 authentication will not be able to connect.
- If the setting is ENABLED_WITH_DIRECTORY_LOGIN_FALLBACK, end users will be directed to login via the user access URL on supported client applications, but will not prevent clients that do not support SAML 2.0 authentication from connecting as if SAML 2.0 authentication was disabled.

Type: String

Valid Values: DISABLED | ENABLED | ENABLED_WITH_DIRECTORY_LOGIN_FALLBACK

Required: No

UserAccessUrl

The SAML 2.0 identity provider (IdP) user access URL is the URL a user would navigate to in their web browser in order to federate from the IdP and directly access the application, without any SAML 2.0 service provider (SP) bindings.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 200.

Pattern: ^(http|https)\:\/\/[^\$]+\$

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

SelfservicePermissions

Describes the self-service permissions for a directory. For more information, see [Enable Self-Service WorkSpace Management Capabilities for Your Users](#).

Contents

ChangeComputeType

Specifies whether users can change the compute type (bundle) for their WorkSpace.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

IncreaseVolumeSize

Specifies whether users can increase the volume size of the drives on their WorkSpace.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

RebuildWorkspace

Specifies whether users can rebuild the operating system of a WorkSpace to its original state.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

RestartWorkspace

Specifies whether users can restart their WorkSpace.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

SwitchRunningMode

Specifies whether users can switch the running mode of their WorkSpace.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Snapshot

Describes a snapshot.

Contents

SnapshotTime

The time when the snapshot was created.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StandbyWorkspace

Describes a standby WorkSpace.

Contents

DirectoryId

The identifier of the directory for the standby WorkSpace.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: Yes

PrimaryWorkSpaceId

The identifier of the standby WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: Yes

DataReplication

Indicates whether data replication is enabled, and if enabled, the type of data replication.

Type: String

Valid Values: NO_REPLICATION | PRIMARY_AS_SOURCE

Required: No

Tags

The tags associated with the standby WorkSpace.

Type: Array of [Tag](#) objects

Required: No

VolumeEncryptionKey

The volume encryption key of the standby WorkSpace.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StandbyWorkspacesProperties

Describes the properties of the related standby WorkSpaces.

Contents

DataReplication

Indicates whether data replication is enabled, and if enabled, the type of data replication.

Type: String

Valid Values: NO_REPLICATION | PRIMARY_AS_SOURCE

Required: No

RecoverySnapshotTime

The date and time at which the last successful snapshot was taken of the primary WorkSpace used for replicating data.

Type: Timestamp

Required: No

StandbyWorkspaceId

The identifier of the standby WorkSpace

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StartRequest

Information used to start a WorkSpace.

Contents

WorkSpaceId

The identifier of the WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

StopRequest

Describes the information used to stop a WorkSpace.

Contents

WorkSpaceId

The identifier of the WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Tag

Describes a tag.

Contents

Key

The key of the tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 127.

Required: Yes

Value

The value of the tag.

Type: String

Length Constraints: Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

TerminateRequest

Describes the information used to terminate a WorkSpace.

Contents

WorkSpaceId

The identifier of the WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: Yes

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

UpdateResult

Describes whether a WorkSpace image needs to be updated with the latest drivers and other components required by Amazon WorkSpaces.

 **Note**

Only Windows 10 WorkSpace images can be programmatically updated at this time.

Contents

Description

A description of whether updates for the WorkSpace image are pending or available.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: ^[a-zA-Z0-9_./() -]+\$

Required: No

UpdateAvailable

Indicates whether updated drivers or other components are available for the specified WorkSpace image.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

UserStorage

Describes the user volume for a WorkSpace bundle.

Contents

Capacity

The size of the user volume.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Workspace

Describes a WorkSpace.

Contents

BundleId

The identifier of the bundle used to create the WorkSpace.

Type: String

Pattern: ^wsb-[0-9a-z]{8,63}\$

Required: No

ComputerName

The name of the WorkSpace, as seen by the operating system. The format of this name varies.

For more information, see [Launch a WorkSpace](#).

Type: String

Required: No

DataReplicationSettings

Indicates the settings of the data replication.

Type: [DataReplicationSettings](#) object

Required: No

DirectoryId

The identifier of the Amazon Directory Service directory for the WorkSpace.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: No

ErrorCode

The error code that is returned if the WorkSpace cannot be created.

Type: String

Required: No

ErrorMessage

The text of the error message that is returned if the WorkSpace cannot be created.

Type: String

Required: No

IpAddress

The IP address of the WorkSpace.

Type: String

Required: No

ModificationStates

The modification states of the WorkSpace.

Type: Array of [ModificationState](#) objects

Required: No

RelatedWorkspaces

The standby WorkSpace or primary WorkSpace related to the specified WorkSpace.

Type: Array of [RelatedWorkspaceProperties](#) objects

Required: No

RootVolumeEncryptionEnabled

Indicates whether the data stored on the root volume is encrypted.

Type: Boolean

Required: No

StandbyWorkspacesProperties

The properties of the standby WorkSpace

Type: Array of [StandbyWorkspacesProperties](#) objects

Required: No

State

The operational state of the WorkSpace.

- PENDING – The WorkSpace is in a waiting state (for example, the WorkSpace is being created).
- AVAILABLE – The WorkSpace is running and has passed the health checks.
- IMPAIRED – Refer to UNHEALTHY state.
- UNHEALTHY – The WorkSpace is not responding to health checks.
- REBOOTING – The WorkSpace is being rebooted (restarted).
- STARTING – The WorkSpace is starting up and health checks are being run.
- REBUILDING – The WorkSpace is being rebuilt.
- RESTORING – The WorkSpace is being restored.
- MAINTENANCE – The WorkSpace is undergoing scheduled maintenance by Amazon.
- ADMIN_MAINTENANCE – The WorkSpace is undergoing maintenance by the WorkSpaces administrator.
- TERMINATING – The WorkSpace is being deleted.
- TERMINATED – The WorkSpace has been deleted.
- SUSPENDED – The WorkSpace has been suspended for image creation.
- UPDATING – The WorkSpace is undergoing an update.
- STOPPING – The WorkSpace is being stopped.
- STOPPED – The WorkSpace has been stopped.
- ERROR – The WorkSpace is an error state (for example, an error occurred during startup).

Note

After a WorkSpace is terminated, the TERMINATED state is returned only briefly before the WorkSpace directory metadata is cleaned up, so this state is rarely returned.

To confirm that a WorkSpace is terminated, check for the WorkSpace ID by using [DescribeWorkSpaces](#). If the WorkSpace ID isn't returned, then the WorkSpace has been successfully terminated.

Type: String

Valid Values: PENDING | AVAILABLE | IMPAIRED | UNHEALTHY | REBOOTING | STARTING | REBUILDING | RESTORING | MAINTENANCE | ADMIN_MAINTENANCE | TERMINATING | TERMINATED | SUSPENDED | UPDATING | STOPPING | STOPPED | ERROR

Required: No

SubnetId

The identifier of the subnet for the WorkSpace.

Type: String

Length Constraints: Minimum length of 15. Maximum length of 24.

Pattern: ^(subnet-([0-9a-f]{8}|[0-9a-f]{17}))\$

Required: No

UserName

The user for the WorkSpace.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Required: No

UserVolumeEncryptionEnabled

Indicates whether the data stored on the user volume is encrypted.

Type: Boolean

Required: No

VolumeEncryptionKey

The ARN of the symmetric Amazon KMS key used to encrypt data stored on your WorkSpace. Amazon WorkSpaces does not support asymmetric KMS keys.

Type: String

Required: No

WorkspaceId

The identifier of the WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: No

WorkspaceName

The name of the user-decoupled WorkSpace.

Type: String

Pattern: ^[a-zA-Z0-9_()][a-zA-Z0-9_.()_-]{1,63}\$

Required: No

WorkspaceProperties

The properties of the WorkSpace.

Type: [WorkspaceProperties](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)

- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

WorkspaceAccessProperties

The device types and operating systems that can be used to access a WorkSpace. For more information, see [Amazon WorkSpaces Client Network Requirements](#).

Contents

DeviceTypeAndroid

Indicates whether users can use Android and Android-compatible Chrome OS devices to access their WorkSpaces.

Type: String

Valid Values: ALLOW | DENY

Required: No

DeviceTypeChromeOs

Indicates whether users can use Chromebooks to access their WorkSpaces.

Type: String

Valid Values: ALLOW | DENY

Required: No

DeviceTypeIos

Indicates whether users can use iOS devices to access their WorkSpaces.

Type: String

Valid Values: ALLOW | DENY

Required: No

DeviceTypeLinux

Indicates whether users can use Linux clients to access their WorkSpaces.

Type: String

Valid Values: ALLOW | DENY

Required: No

DeviceTypeOsx

Indicates whether users can use macOS clients to access their WorkSpaces.

Type: String

Valid Values: ALLOW | DENY

Required: No

DeviceTypeWeb

Indicates whether users can access their WorkSpaces through a web browser.

Type: String

Valid Values: ALLOW | DENY

Required: No

DeviceTypeWindows

Indicates whether users can use Windows clients to access their WorkSpaces.

Type: String

Valid Values: ALLOW | DENY

Required: No

DeviceTypeZeroClient

Indicates whether users can use zero client devices to access their WorkSpaces.

Type: String

Valid Values: ALLOW | DENY

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

WorkSpaceApplication

Describes the WorkSpace application.

Contents

ApplicationId

The identifier of the application.

Type: String

Pattern: ^wsa-[0-9a-z]{8,63}\$

Required: No

Created

The time the application is created.

Type: Timestamp

Required: No

Description

The description of the WorkSpace application.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

LicenseType

The license availability for the applications.

Type: String

Valid Values: LICENSED | UNLICENSED

Required: No

Name

The name of the WorkSpace application.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Owner

The owner of the WorkSpace application.

Type: String

Pattern: ^\d{12} | AMAZON\$

Required: No

State

The status of WorkSpace application.

Type: String

Valid Values: PENDING | ERROR | AVAILABLE | UNINSTALL_ONLY

Required: No

SupportedComputeTypeNames

The supported compute types of the WorkSpace application.

Type: Array of strings

Valid Values: VALUE | STANDARD | PERFORMANCE | POWER | GRAPHICS | POWERPRO | GRAPHICSPRO | GRAPHICS_G4DN | GRAPHICSPRO_G4DN

Required: No

SupportedOperatingSystemNames

The supported operating systems of the WorkSpace application.

Type: Array of strings

Valid Values: AMAZON_LINUX_2 | UBUNTU_18_04 | UBUNTU_20_04 | UBUNTU_22_04 | UNKNOWN | WINDOWS_10 | WINDOWS_11 | WINDOWS_7 | WINDOWS_SERVER_2016 | WINDOWS_SERVER_2019 | WINDOWS_SERVER_2022

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

WorkSpaceApplicationDeployment

Describes the WorkSpace application deployment.

Contents

Associations

The associations between the applications and the associated resources.

Type: Array of [WorkspaceResourceAssociation](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

WorkspaceBundle

Describes a WorkSpace bundle.

Contents

BundleId

The identifier of the bundle.

Type: String

Pattern: ^wsb-[0-9a-z]{8,63}\$

Required: No

BundleType

The type of WorkSpace bundle.

Type: String

Valid Values: REGULAR | STANDBY

Required: No

ComputeType

The compute type of the bundle. For more information, see [Amazon WorkSpaces Bundles](#).

Type: [ComputeType](#) object

Required: No

CreationTime

The time when the bundle was created.

Type: Timestamp

Required: No

Description

The description of the bundle.

Type: String

Required: No

ImageId

The identifier of the image that was used to create the bundle.

Type: String

Pattern: `wsi-[0-9a-z]{9,63}$`

Required: No

LastUpdatedTime

The last time that the bundle was updated.

Type: Timestamp

Required: No

Name

The name of the bundle.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Owner

The owner of the bundle. This is the account identifier of the owner, or AMAZON if the bundle is provided by Amazon.

Type: String

Required: No

RootStorage

The size of the root volume.

Type: [RootStorage](#) object

Required: No

State

The state of the WorkSpace bundle.

Type: String

Valid Values: AVAILABLE | PENDING | ERROR

Required: No

UserStorage

The size of the user volume.

Type: [UserStorage](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

WorkspaceConnectionStatus

Describes the connection status of a WorkSpace.

Contents

ConnectionState

The connection state of the WorkSpace. The connection state is unknown if the WorkSpace is stopped.

Type: String

Valid Values: CONNECTED | DISCONNECTED | UNKNOWN

Required: No

ConnectionStateCheckTimestamp

The timestamp of the connection status check.

Type: Timestamp

Required: No

LastKnownUserConnectionTimestamp

The timestamp of the last known user connection.

Type: Timestamp

Required: No

WorkspaceId

The identifier of the WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

WorkspaceCreationProperties

Describes the default properties that are used for creating WorkSpaces. For more information, see [Update Directory Details for Your WorkSpaces](#).

Contents

CustomSecurityGroupId

The identifier of your custom security group.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 20.

Pattern: ^(sg-([0-9a-f]{8}|[0-9a-f]{17}))\$

Required: No

DefaultOu

The default organizational unit (OU) for your WorkSpaces directories. This string must be the full Lightweight Directory Access Protocol (LDAP) distinguished name for the target domain and OU. It must be in the form "OU=*value*,DC=*value*,DC=*value*", where *value* is any string of characters, and the number of domain components (DCs) is two or more. For example, OU=WorkSpaces_machines,DC=machines,DC=example,DC=com.

Important

- To avoid errors, certain characters in the distinguished name must be escaped. For more information, see [Distinguished Names](#) in the Microsoft documentation.
- The API doesn't validate whether the OU exists.

Type: String

Required: No

EnableInternetAccess

Indicates whether internet access is enabled for your WorkSpaces.

Type: Boolean

Required: No

EnableMaintenanceMode

Indicates whether maintenance mode is enabled for your WorkSpaces. For more information, see [WorkSpace Maintenance](#).

Type: Boolean

Required: No

EnableWorkDocs

Indicates whether Amazon WorkDocs is enabled for your WorkSpaces.

Note

If WorkDocs is already enabled for a WorkSpaces directory and you disable it, new WorkSpaces launched in the directory will not have WorkDocs enabled. However, WorkDocs remains enabled for any existing WorkSpaces, unless you either disable users' access to WorkDocs or you delete the WorkDocs site. To disable users' access to WorkDocs, see [Disabling Users](#) in the *Amazon WorkDocs Administration Guide*. To delete a WorkDocs site, see [Deleting a Site](#) in the *Amazon WorkDocs Administration Guide*.

If you enable WorkDocs on a directory that already has existing WorkSpaces, the existing WorkSpaces and any new WorkSpaces that are launched in the directory will have WorkDocs enabled.

Type: Boolean

Required: No

UserEnabledAsLocalAdministrator

Indicates whether users are local administrators of their WorkSpaces.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

WorkspaceDirectory

Describes a directory that is used with Amazon WorkSpaces.

Contents

Alias

The directory alias.

Type: String

Required: No

CertificateBasedAuthProperties

The certificate-based authentication properties used to authenticate SAML 2.0 Identity Provider (IdP) user identities to Active Directory for WorkSpaces login.

Type: [CertificateBasedAuthProperties](#) object

Required: No

CustomerUserName

The user name for the service account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Required: No

DirectoryId

The directory identifier.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: No

DirectoryName

The name of the directory.

Type: String

Required: No

DirectoryType

The directory type.

Type: String

Valid Values: SIMPLE_AD | AD_CONNECTOR

Required: No

DnsIpAddresses

The IP addresses of the DNS servers for the directory.

Type: Array of strings

Required: No

IamRoleId

The identifier of the IAM role. This is the role that allows Amazon WorkSpaces to make calls to other services, such as Amazon EC2, on your behalf.

Type: String

Pattern: ^arn:aws:[A-Za-z0-9][A-za-z0-9_/-]{0,62}:[A-za-z0-9_/-]{0,63}:[A-za-z0-9_/-]{0,63}:[A-Za-z0-9][A-za-z0-9_/-]{0,127}\$

Required: No

ipGroupIds

The identifiers of the IP access control groups associated with the directory.

Type: Array of strings

Pattern: wsipg-[0-9a-z]{8,63}\$

Required: No

RegistrationCode

The registration code for the directory. This is the code that users enter in their Amazon WorkSpaces client application to connect to the directory.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Required: No

SamlProperties

Describes the enablement status, user access URL, and relay state parameter name that are used for configuring federation with an SAML 2.0 identity provider.

Type: [SamlProperties](#) object

Required: No

SelfservicePermissions

The default self-service permissions for WorkSpaces in the directory.

Type: [SelfservicePermissions](#) object

Required: No

State

The state of the directory's registration with Amazon WorkSpaces. After a directory is deregistered, the Deregistered state is returned very briefly before the directory metadata is cleaned up, so this state is rarely returned. To confirm that a directory is deregistered, check for the directory ID by using [DescribeWorkspaceDirectories](#). If the directory ID isn't returned, then the directory has been successfully deregistered.

Type: String

Valid Values: REGISTERING | REGISTERED | Deregistering | Deregistered | ERROR

Required: No

SubnetIds

The identifiers of the subnets used with the directory.

Type: Array of strings

Array Members: Maximum number of 2 items.

Length Constraints: Minimum length of 15. Maximum length of 24.

Pattern: ^(subnet-([0-9a-f]{8}|[0-9a-f]{17}))\$

Required: No

Tenancy

Specifies whether the directory is dedicated or shared. To use Bring Your Own License (BYOL), this value must be set to DEDICATED. For more information, see [Bring Your Own Windows Desktop Images](#).

Type: String

Valid Values: DEDICATED | SHARED

Required: No

WorkspaceAccessProperties

The devices and operating systems that users can use to access WorkSpaces.

Type: [WorkspaceAccessProperties](#) object

Required: No

WorkspaceCreationProperties

The default creation properties for all WorkSpaces in the directory.

Type: [DefaultWorkspaceCreationProperties](#) object

Required: No

WorkspaceSecurityGroupId

The identifier of the security group that is assigned to new WorkSpaces.

Type: String

Length Constraints: Minimum length of 11. Maximum length of 20.

Pattern: ^(sg-([0-9a-f]{8}|[0-9a-f]{17}))\$

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

WorkSpaceImage

Describes a WorkSpace image.

Contents

Created

The date when the image was created. If the image has been shared, the Amazon Web Services account that the image has been shared with sees the original creation date of the image.

Type: Timestamp

Required: No

Description

The description of the image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^[a-zA-Z0-9_./() -]+\$

Required: No

ErrorCode

The error code that is returned for the image.

Type: String

Required: No

ErrorDetails

Additional details of the error returned for the image, including the possible causes of the errors and troubleshooting information.

Type: Array of [ErrorDetails](#) objects

Required: No

ErrorMessage

The text of the error message that is returned for the image.

Type: String

Required: No

ImageId

The identifier of the image.

Type: String

Pattern: wsi-[0-9a-z]{9,63}\$

Required: No

Name

The name of the image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[a-zA-Z0-9_./()\\-]+\$

Required: No

OperatingSystem

The operating system that the image is running.

Type: [OperatingSystem](#) object

Required: No

OwnerAccountId

The identifier of the Amazon Web Services account that owns the image.

Type: String

Pattern: ^\d{12}\$

Required: No

RequiredTenancy

Specifies whether the image is running on dedicated hardware. When Bring Your Own License (BYOL) is enabled, this value is set to DEDICATED. For more information, see [Bring Your Own Windows Desktop Images](#).

Type: String

Valid Values: DEFAULT | DEDICATED

Required: No

State

The status of the image.

Type: String

Valid Values: AVAILABLE | PENDING | ERROR

Required: No

Updates

The updates (if any) that are available for the specified image.

Type: [UpdateResult](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

WorkspaceProperties

Describes a WorkSpace.

Contents

ComputeTypeName

The compute type. For more information, see [Amazon WorkSpaces Bundles](#).

Type: String

Valid Values: VALUE | STANDARD | PERFORMANCE | POWER | GRAPHICS | POWERPRO | GRAPHICSPRO | GRAPHICS_G4DN | GRAPHICSPRO_G4DN

Required: No

OperatingSystemName

The name of the operating system.

Type: String

Valid Values: AMAZON_LINUX_2 | UBUNTU_18_04 | UBUNTU_20_04 | UBUNTU_22_04 | UNKNOWN | WINDOWS_10 | WINDOWS_11 | WINDOWS_7 | WINDOWS_SERVER_2016 | WINDOWS_SERVER_2019 | WINDOWS_SERVER_2022

Required: No

Protocols

The protocol. For more information, see [Protocols for Amazon WorkSpaces](#).

Note

- Only available for WorkSpaces created with PCoIP bundles.
- The Protocols property is case sensitive. Ensure you use PCOIP or WSP.
- Unavailable for Windows 7 WorkSpaces and WorkSpaces using GPU-based bundles (Graphics, GraphicsPro, Graphics.g4dn, and GraphicsPro.g4dn).

Type: Array of strings

Valid Values: PCOIP | WSP

Required: No

RootVolumeSizeGiB

The size of the root volume. For important information about how to modify the size of the root and user volumes, see [Modify a WorkSpace](#).

Type: Integer

Required: No

RunningMode

The running mode. For more information, see [Manage the WorkSpace Running Mode](#).

Note

The MANUAL value is only supported by Amazon WorkSpaces Core. Contact your account team to be allow-listed to use this value. For more information, see [Amazon WorkSpaces Core](#).

Type: String

Valid Values: AUTO_STOP | ALWAYS_ON | MANUAL

Required: No

RunningModeAutoStopTimeoutInMinutes

The time after a user logs off when WorkSpaces are automatically stopped. Configured in 60-minute intervals.

Type: Integer

Required: No

UserVolumeSizeGiB

The size of the user storage. For important information about how to modify the size of the root and user volumes, see [Modify a WorkSpace](#).

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

WorkspaceRequest

Describes the information used to create a WorkSpace.

Contents

BundleId

The identifier of the bundle for the WorkSpace. You can use [DescribeWorkspaceBundles](#) to list the available bundles.

Type: String

Pattern: ^wsb-[0-9a-z]{8,63}\$

Required: Yes

DirectoryId

The identifier of the Amazon Directory Service directory for the WorkSpace. You can use [DescribeWorkspaceDirectories](#) to list the available directories.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 65.

Pattern: ^d-[0-9a-f]{8,63}\$

Required: Yes

UserName

The user name of the user for the WorkSpace. This user name must exist in the Amazon Directory Service directory for the WorkSpace.

The reserved keyword, [UNDEFINED], is used when creating user-decoupled WorkSpaces.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 63.

Required: Yes

RootVolumeEncryptionEnabled

Indicates whether the data stored on the root volume is encrypted.

Type: Boolean

Required: No

Tags

The tags for the WorkSpace.

Type: Array of [Tag](#) objects

Required: No

UserVolumeEncryptionEnabled

Indicates whether the data stored on the user volume is encrypted.

Type: Boolean

Required: No

VolumeEncryptionKey

The ARN of the symmetric Amazon KMS key used to encrypt data stored on your WorkSpace. Amazon WorkSpaces does not support asymmetric KMS keys.

Type: String

Required: No

WorkspaceName

The name of the user-decoupled WorkSpace.

Type: String

Pattern: ^[a-zA-Z0-9_()][a-zA-Z0-9_.()]{1,63}\$

Required: No

WorkspaceProperties

The WorkSpace properties.

Type: [WorkspaceProperties](#) object

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

WorkspaceResourceAssociation

Describes the association between an application and a WorkSpace resource.

Contents

AssociatedResourceId

The identifier of the associated resource.

Type: String

Length Constraints: Minimum length of 1.

Required: No

AssociatedResourceType

The resource types of the associated resource.

Type: String

Valid Values: APPLICATION

Required: No

Created

The time the association is created.

Type: Timestamp

Required: No

LastUpdatedTime

The time the association status was last updated.

Type: Timestamp

Required: No

State

The status of the WorkSpace resource association.

Type: String

Valid Values: PENDING_INSTALL | PENDING_INSTALL_DEPLOYMENT | PENDING_UNINSTALL | PENDING_UNINSTALL_DEPLOYMENT | INSTALLING | UNINSTALLING | ERROR | COMPLETED | REMOVED

Required: No

StateReason

The reason the association deployment failed.

Type: [AssociationStateReason](#) object

Required: No

WorkspaceId

The identifier of the WorkSpace.

Type: String

Pattern: ^ws-[0-9a-z]{8,63}\$

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

WorkspacesIpGroup

Describes an IP access control group.

Contents

groupDesc

The description of the group.

Type: String

Required: No

groupId

The identifier of the group.

Type: String

Pattern: wsipg-[0-9a-z]{8,63}\$

Required: No

groupName

The name of the group.

Type: String

Required: No

userRules

The rules.

Type: Array of [IpRuleItem](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific Amazon SDKs, see the following:

- [Amazon SDK for C++](#)
- [Amazon SDK for Go](#)
- [Amazon SDK for Java V2](#)
- [Amazon SDK for Ruby V3](#)

Common Errors

This section lists the errors common to the API actions of all Amazon services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to Amazon standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or Amazon access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The Amazon access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an Amazon service.

HTTP Status Code: 400

WorkSpaces Core API actions

You can use the following APIs to perform various actions for WorkSpaces Core. We have provided some recommendations next to these actions to help you create your workflow.

- Deployment and setup
 - [CreateTags](#) - Possible
 - [CreateWorkspaceBundle](#) - Required
 - [CreateWorkspaces](#) - Required
 - [DescribeAccount](#) - Required
 - [DescribeAccountModifications](#) - Possible
 - [ImportWorkspacelImage](#) - Possible, but we highly recommend partners have an interface to import images into Amazon WorkSpaces using this API.
 - [ModifyAccount](#) - Possible
 - [ListAvailableManagementCidrRanges](#) - Possible, but we highly recommend partners have an interface to onboard customers into Amazon WorkSpaces BYOL using this API.
 - [RegisterWorkspaceDirectory](#) - Required
 - EnableInternetAccess - Optional
 - EnableWorkDocs - Optional
 - Tags - Optional
- Operations
 - [CopyWorkspacelImage](#) - Possible, but we highly recommend this action. It supports an UpdateWorkspaceBundle image process and copying from one region to another.
 - [CreateWorkspacelImage](#) - Required
 - [DescribeTags](#) - Possible, but we highly recommend partners have an interface to use and modify tags on Amazon WorkSpaces desktops using this API.
 - [DescribeWorkspaceBundles](#) - Required
 - [DescribeWorkspaceDirectories](#) - Required
 - [DescribeWorkspacelImagePermissions](#) - Required
 - [DescribeWorkspacelImages](#) - Required for creation of new desktops and within a workflow to use the UpdateWorkspaceBundle API that updates an image within a bundle.
 - [DescribeWorkspaces](#) - Required

- [DescribeWorkspaceSnapshots](#) - Possible, but we highly recommend partners have an interface to view snapshots into Amazon WorkSpaces desktops using this API.
- [MigrateWorkspace](#) - Possible, but we highly recommend partners have an interface to migrate an Amazon WorkSpaces desktop from one bundle to another using this API.
- [ModifyWorkspaceCreationProperties](#) - Possible, but we highly recommend partners have an interface to modify the following properties:
 - Custom Security Group
 - Default OU
 - EnableInternetAccess
 - EnableMaintenanceMode
 - EnableWorkDocs
 - UserEnabledAsLocalAdministrator
- [ModifyWorkspaceProperties](#) - Possible, but we highly recommend partners have an interface to modify the following properties:
 - [ComputeTypeName](#)
 - [RootVolumeSizeGib](#)
 - [RunningMode](#) (can change to Manual)
 - [RunningModeAutoStopTimeoutInMinutes](#)
 - [UserVolumeSizeGib](#)
- [ModifyWorkspaceState](#) - Required
- [RebootWorkspaces](#) - Required
- [RebuildWorkspaces](#) - Required
- [RestoreWorkspace](#) - Required
- [StartWorkspaces](#) - Required
- [StopWorkspaces](#) - Required
- [UpdateWorkspaceBundle](#) - Required
- [UpdateWorkspaceImagePermission](#) - Possible, but we highly recommend partners have an interface to modify these properties.
- Termination
 - [DeleteTags](#) - Possible
 - [DeleteWorkspaceBundle](#) - Required

- [DeleteWorkspaceImage](#) - Required
- [DeregisterWorkspaceDirectory](#) - Required
- [TerminateWorkspaces](#) - Required

Logging WorkSpaces API Calls by Using CloudTrail

The WorkSpaces API is integrated with Amazon CloudTrail, a service that provides a record of actions taken by a user, role, or an Amazon service in WorkSpaces. CloudTrail captures API calls for WorkSpaces as events. The calls captured include calls from the WorkSpaces console and code calls to the WorkSpaces API operations. If you create a trail, you can enable continuous delivery of CloudTrail events to an Amazon S3 bucket, including events for WorkSpaces. If you don't configure a trail, you can still view the most recent events in the CloudTrail console in **Event history**. Using the information collected by CloudTrail, you can determine the request that was made to WorkSpaces, the IP address from which the request was made, who made the request, when it was made, and additional details.

To learn more about CloudTrail, including how to configure and enable it, see the [Amazon CloudTrail User Guide](#).

WorkSpaces Information in CloudTrail

CloudTrail is enabled on your Amazon account when you create the account. When supported event activity occurs in WorkSpaces, that activity is recorded in a CloudTrail event along with other Amazon service events in **Event history**. For example, calls to create, rebuild, or terminate WorkSpaces generate entries in CloudTrail log files. For more information, see [Actions](#).

You can view, search, and download recent events in your Amazon account. For more information, see [Viewing Events with CloudTrail Event History](#).

For an ongoing record of events in your Amazon account, including events for WorkSpaces, create a trail. A *trail* enables CloudTrail to deliver log files to an Amazon S3 bucket. By default, when you create a trail in the console, the trail applies to all Amazon Regions. The trail logs events from all Regions in the Amazon partition and delivers the log files to the Amazon S3 bucket that you specify. Additionally, you can configure other Amazon services to further analyze and act upon the event data collected in CloudTrail logs. For more information, see the following:

- [Overview for Creating a Trail](#)
- [CloudTrail Supported Services and Integrations](#)
- [Configuring Amazon SNS Notifications for CloudTrail](#)
- [Receiving CloudTrail Log Files from Multiple Regions](#) and [Receiving CloudTrail Log Files from Multiple Accounts](#)

Example: WorkSpaces Log File Entry

A trail is a configuration that enables delivery of events as log files to an Amazon S3 bucket that you specify. CloudTrail log files contain one or more log entries. An event represents a single request from any source and includes information about the requested action, the date and time of the action, request parameters, and so on. CloudTrail log files aren't an ordered stack trace of the public API calls, so they don't appear in any specific order.

Any sensitive information, such as passwords, authentication tokens, file comments, and file contents are redacted in the log entries.

The following shows an example of a CloudTrail log entry for WorkSpaces.

```
{  
  "Records" : [  
    {  
      "eventVersion" : "1.02",  
      "userIdentity" :  
      {  
        "type" : "IAMUser",  
        "principalId" : "user_id",  
        "arn" : "user_arn",  
        "accountId" : "account_id",  
        "accessKeyId" : "access_key_id",  
        "userName" : "username"  
      },  
      "eventTime" : "event_time",  
      "eventSource" : "workspaces.amazonaws.com",  
      "eventName" : "DescribeWorkspaces",  
      "awsRegion" : "region",  
      "sourceIPAddress" : "IP_address",  
      "userAgent" : "user_agent",  
      "requestParameters" :  
      {  
        "requestContext" :  
        {  
          "awsAccountId" : "account_id"  
        }  
      },  
      "responseElements" :  
      {  
        "workspaces" : [  
          {  
            "id" : "ws_id",  
            "arn" : "ws_arn",  
            "name" : "ws_name",  
            "status" : "ws_status",  
            "type" : "ws_type",  
            "region" : "ws_region",  
            "tags" : [{"key": "tag1", "value": "tag1_value"}, {"key": "tag2", "value": "tag2_value"}]  
          }  
        ]  
      }  
    }  
  ]  
}
```

```
{  
    "bundleId" : "bundle_id",  
    "userName" : "workspace_user_name",  
    "ipAddress" : ";ip_address",  
    "directoryId" : ";directory_id",  
    "state" : "state",  
    "workspaceId" : "workspace_id",  
    "subnetId" : "subnet_id"  
}  
]  
],  
"requestID" : "request_id",  
"eventID" : "event_id",  
"eventType" : "AwsApiCall",  
"recipientAccountId" : "account_id"  
}  
]  
}
```